Temporal Feasibility Constraints on Wingbeat-Call Synchrony in Actively Echolocating Bats

Ravi Umadi [1]

[1] Lehrstuhl für Zoologie, TUM School of Life Sciences, Technische Universität München, Liesel-Beckmann-Str. 4, 85354 Freising-Weihenstephan, Germany

ABSTRACT.

1. Echolocating bats coordinate sound production, echo reception, and flight within a closed sensorimotor loop that operates under finite propagation delays and bounded response times. Although call timing and wingbeat synchrony have been described across many behavioural contexts, it remains unclear when such coordination is temporally feasible and when it must necessarily break down. Here, I develop a constraint-based analysis that formalises how temporal feasibility limits shape behavioural coordination during active echolocation.

2. Building on the responsivity framework, the model explicitly represents the ordering and timing dependencies between call emission, echo delay, sensory processing, and subsequent action, and derives conditions under which call timing can remain phase-locked to a cyclic motor rhythm such as the wingbeat. Analysis of these constraints reveals distinct coordination regimes: permissive regimes in which phase locking can emerge without dedicated coupling, and constrained regimes in which progressive phase slip or decoupling becomes unavoidable as sensory demand increases.

3. Monte Carlo simulations show that transitions between synchrony and asynchrony arise as necessary consequences of first-principles timing constraints and bounded motor dynamics, rather than from changes in behavioural strategy. Increased motor flexibility shifts, but does not eliminate, the boundaries of synchrony-permissive regimes. Empirical observations from field studies are discussed as illustrative examples of these regimes, highlighting how apparent coupling and decoupling can both emerge from the same underlying control architecture.

4. Together, this work identifies temporal feasibility as a governing constraint on echolocation behaviour, clarifies when buffered pseudo–closed-loop operation can masquerade as feedback control, and generates testable predictions for when and why wingbeat–call synchrony should fail in ecological contexts such as prey pursuit. More broadly, the framework situates bat echolocation within a general class of active sensing systems shaped by delayed feedback and bounded response dynamics.

KEYWORDS: Active Sensing, Behavioural Control, Echolocation, Sensorimotor Coordination, Temporal Constraint, Wingbeat–Call Synchrony

Corresponding author: Ravi Umadi– Email: ravi.umadi@tum.de

1 INTRODUCTION

Echolocation in bats is a paradigmatic example of active sensing, in which an animal actively structures its sensory input through self-generated signals and adapts behaviour based on the resulting sensory feedback [1–9]. During flight, echolocating bats must coordinate signal emission, echo reception, neural processing, and motor actions within a tightly coupled sensorimotor loop, often while navigating complex and dynamically changing environments. This coordination enables rapid localisation of prey, obstacle avoidance, and agile manoeuvring, frequently on millisecond time scales [4, 10–13].

Because call production, respiration, and wing motion share biomechanical and physiological pathways, early work proposed that echolocation calls are intrinsically coupled to the wingbeat and respiratory cycles during flight [14, 15]. This view was reinforced by observations of phase-locked call emission during steady flight and by arguments that synchronising vocal output with expiratory phases could reduce energetic cost [15, 16]. Under this interpretation, wingbeat–call synchrony emerges as an energetically efficient solution for biosonar production.

However, subsequent studies across species and behavioural contexts have demonstrated that such synchrony is neither obligatory nor universal. In *Eptesicus fuscus*, calls are often phase-locked to the upstroke during cruising flight but become increasingly decoupled during feeding buzzes [17]. Field recordings further show that wild bats transiently abandon wingbeat–call coupling in cluttered environments or during manoeuvring, where flexible call timing improves echo reception [18]. More recently, Xia et al. [19] demonstrated that while coupling is common at low duty cycles, it systematically degrades as call rates increase, revealing substantial phase flexibility and call insertion outside stereotyped respiratory phases.

Together, these findings indicate that wingbeat–call synchrony is context dependent and tends to break down when sensory demands increase. Notably, this breakdown occurs precisely in behavioural regimes characterised by high call rates, rapid changes in target distance, or dense clutter—conditions under which the temporal demands of the echolocation loop intensify.

Recent analyses have further suggested that bats may regulate call timing according to spatial heuristics. Jakobsen et al. [20] reported that in aerial-hawking vespertilionid bats, call rate scales with approach velocity in a manner consistent with maintaining an approximately constant distance travelled per call. They proposed a "dual convergence" in sonar sampling, preserving both a constant spatial sampling interval and a stable temporal window to traverse the sonar range. Such findings have been interpreted as evidence that call timing may be governed primarily by spatial rather than temporal considerations.

At the same time, it remains unresolved whether such apparent invariants reflect fundamental control objectives or emerge only under specific operating conditions. In particular, most existing analyses treat call timing descriptively—relating interpulse intervals to distance, velocity, or behavioural phase—without explicitly considering whether the required coordination of emission, echo arrival, neural processing, and response is temporally feasible within bounded response windows.

Here I argue that a central, underexplored constraint governing echolocation behaviour is *temporal feasibility*: the requirement that sensory feedback and subsequent motor responses must be ordered and completed within finite temporal margins to sustain closed-loop interaction. Importantly, the presence of a call–echo–call sequence alone does not establish strict

Figure 1: Schematic illustration of the transition from wingbeat–call synchrony to asynchrony in echolocating bats. The sine wave depicts wing motion over time, with red dots marking call emissions. In the *synchrony regime* (t_0–t_2), calls are phase-synched to a point in the wingbeat cycle (IPI $\approx T_w$). As echo-processing demands rise, the interpulse interval (IPI) becomes shorter than the wingbeat period (T_w), initiating the *asynchrony regime* (t_2–t_5) where calls slip in phase and are no longer strictly tied to the wingbeat. The schematic demonstrates that synchrony is only possible when timing constraints are met; as demand increases, asynchrony emerges as a necessary, adaptive solution for maintaining temporal precision.

closed-loop control, as apparent feedback coupling can arise trivially when acoustic propagation delays are short relative to biological reaction times. In such buffered regimes, calls may be generated according to internal schedules or kinematic heuristics while still receiving informative echoes before the next emission becomes mechanically or neurally possible. This pseudo–closed-loop operation can mimic echo-anchored control without requiring that call timing be causally governed by echo arrival.

As call rates increase and echo streams lengthen, however, this buffer collapses. Call scheduling then becomes explicitly constrained by the timing of sensory feedback itself: calls cannot be meaningfully emitted before sufficient echo information is available, yet need not await the full termination of the echo stream. Instead, timing is expected to be organised relative to the informative portion of the echo response, creating a finite temporal window within which action updates must occur. Under such conditions, internal pacing policies are no longer sufficient, and call timing becomes rate-limited by echo arrival and processing delays.

The present study formalises this transition using the *responsivity framework* [21], which abstracts echolocation as a sequence of causally ordered events—signal emission, echo return, neural processing, and behavioural response—each associated with characteristic delays. This formulation yields explicit feasibility conditions under which call scheduling can remain phase-locked to cyclic motor rhythms such as the wingbeat, and conditions under which progressive phase slip and eventual decoupling become unavoidable. Crucially, these transitions arise from first-principles timing constraints and do not require changes in behavioural strategy, motivation, or energetic optimisation. In this view, the breakdown of wingbeat–call synchrony is not a failure of coordination, but a predictable and adaptive consequence of finite temporal feasibility.

More broadly, this work situates bat echolocation within a general class of closed-loop active sensing systems subject to delay and feasibility constraints. Similar interactions between delayed feedback and rhythmic actuation arise in engineered control systems and other biological sensorimotor loops [22–27]. By treating temporal feasibility as a governing constraint, the present framework provides a unifying account of when synchrony can be maintained, when it must break down, and why such breakdowns can enhance rather than impair sensory performance.

2 METHODS

2.1 Analytical framework and modelling assumptions

The analytical framework developed here treats echolocation call timing and wingbeat dynamics as two distinct cyclic processes with time-varying frequencies. Call emission is governed by a sensory-driven timing loop whose rhythm is constrained by acoustic propagation delays, neural processing times, and response latencies, as formalised in the responsivity framework [21]. In contrast, wingbeat dynamics arise from biomechanical and aerodynamic constraints associated with flight, including muscle physiology, body inertia, lift generation, and energetic demands, and are not assumed to be directly controlled by sensory feedback on a call-by-call basis. As a result, the two oscillatory processes are treated as *functionally independent* in their generative mechanisms, even though their interaction gives rise to observable coordination patterns.

This perspective differs from classical coupled-oscillator models, in which synchrony emerges from explicit bidirectional coupling terms or mutual phase adjustment, often with fixed or delayed interactions. Here, no such coupling is assumed. Instead, coordination—or its breakdown— emerges from temporal feasibility constraints imposed by delayed sensory feedback acting on one oscillator (call timing) in the presence of bounded dynamics in the other (wingbeat rhythm). The analysis therefore focuses on when phase-locked coordination is temporally admissible given the ordering and latency structure of the closed-loop system, instead of how oscillators entrain one another. The following sections formalise these constraints and derive the conditions under which synchrony, phase slip, or decoupling must occur.

3 THEORETICAL FRAMEWORK

3.1 Echo delay and salient reflectors

Let $d(t)$ denote the instantaneous range to a salient reflector that dominates the relevant echo stream for behavioural guidance, and c the speed of sound. In the simplest stationary-reflector case,

$$T_a(t) = \frac{2d(t)}{c}. \tag{1}$$

For moving targets or non-negligible bat motion during call emission, higher-order corrections can be included, but the present analysis depends only on the monotonic relation between T_a and the effective range to the echo that the bat uses for feedback. This framing is also consistent with laboratory settings where the farthest prominent reflector within the enclosure can set an upper bound on the longest feasible IPI under closed-loop operation.

3.2 Responsivity relations and interpulse timing

Within the responsivity framework [21], behavioural coordination is governed by the temporal ordering of four events: call emission, echo return, sensory processing, and initiation of the next action. The present analysis abstracts the latter two stages into a single behavioural response window, denoted T_b, which represents the minimal time required for extracting behaviourally relevant information from the echo and implementing the subsequent motor update. Importantly, T_b is not assumed to be fixed, nor is it identified with a specific neural or biomechanical process; rather, it serves as a phenomenological descriptor of the closed-loop response latency.

A core assumption of the responsivity framework is that, over a broad operating range, the effective response window scales with the acoustic round-trip delay T_a according to

$$T_b(t) = k_r \, T_a(t), \tag{2}$$

where $k_r > 0$ is a *dimensionless responsivity coefficient*. In the present study, k_r is treated as constant for a given behavioural condition or simulation run: it is not a time-varying control signal, and all temporal variation in T_b arises through changes in $T_a(t)$. Differences in k_r across simulations or species are interpreted as differences in overall sensorimotor demand or effective response latency, not as rapid within-flight modulation.

At the same time, biological systems are subject to finite processing and actuation limits. Accordingly, the behavioural response window cannot be reduced arbitrarily. I therefore consider the lower bound T_{b^*}, representing the minimum effective response window below which the closed-loop system cannot reliably implement sensory-driven updates. This bound corresponds to the saturation regime of responsivity and reflects irreducible latencies in sensory encoding, decision formation, and motor execution. The response window thus satisfies

$$T_b(t) \geq T_{b^*}. \tag{3}$$

The interpulse interval (IPI), defined as the time between consecutive call emissions, must accommodate both the acoustic propagation delay and the subsequent behavioural response. Combining Eqs. (2) and (3), the admissible interpulse interval is

$$\text{IPI}(t) = T_a(t) + \max\!\big(k_r \, T_a(t), \, T_{b^*}\big). \tag{4}$$

Equation (4) is a *feasibility specification* for closed-loop timing: it defines the shortest interpulse interval compatible with an echo-guided update, given the prevailing acoustic delay and the irreducible response bound.

Two regimes follow immediately. When $k_r T_a(t) \geq T_{b^*}$, the system operates in a scaling-dominated regime and

$$\text{IPI}(t) = (1 + k_r) \, T_a(t). \tag{5}$$

When $k_r T_a(t) < T_{b^*}$, the response window saturates at its lower bound and

$$\text{IPI}(t) = T_a(t) + T_{b^*}. \tag{6}$$

The transition occurs at $k_r T_a = T_{b^*}$ and marks the point at which closed-loop timing becomes explicitly constrained by irreducible response delays rather than by proportional responsivity scaling.

3.2.1 Wingbeat rhythm and phase representation

Let $f_w(t)$ be wingbeat frequency and $T_w(t) = 1/f_w(t)$ the wingbeat period. To discuss coordination in a way that does not assume strict synchrony, it is convenient to represent call times relative to the wingbeat phase. If t_n denotes the time of the n-th call emission, the corresponding

wingbeat phase can be written as

$$\phi_n = 2\pi \, \text{mod}\left(\frac{t_n}{T_w}, 1\right). \tag{7}$$

A preference for particular call phases would appear as non-uniformity (clustering) in the distribution of $\{\phi_n\}$. In this study, phase is used as a theoretical bookkeeping device to describe feasible coordination regimes, not as a directly inferred quantity.

3.2.2   Feasibility of 1:1 synchrony and higher-order coordination

A common reference point in discussions of motor–vocal coordination is *1:1 locking*, where one call is emitted per wingbeat cycle, implying

$$\text{IPI}(t) = T_w(t) = \frac{1}{f_w(t)}. \tag{8}$$

Combining Eq. (8) with the responsivity identity in Eq. (5) yields the wingbeat frequency required for 1:1 locking at a given echo delay,

$$f_w^{(1:1)}(t) = \frac{1}{(1 + k_r)\, T_a(t)}. \tag{9}$$

Equation (9) provides a *feasibility condition* for 1:1 locking: if the bat's achievable wingbeat frequencies do not include $f_w^{(1:1)}(t)$ for the relevant $T_a(t)$ and k_r, then strict 1:1 synchrony cannot be sustained, unless voluntary corrective behavioural responses follow.

More generally, coordination may occur in higher-order patterns, in which m calls occur over n wingbeat cycles (an *m:n* relation). In such cases,

$$\text{IPI}(t) \approx \frac{n}{m}\, T_w(t), \tag{10}$$

and the corresponding wingbeat frequency compatible with the responsivity-implied IPI is

$$f_w^{(m:n)}(t) \approx \frac{m}{n}\, \frac{1}{(1 + k_r)\, T_a(t)}. \tag{11}$$

As sensory demand increases (typically as T_a decreases), Eqs. (9)–(11) predict a natural progression from regimes where 1:1 locking is feasible (IPI $\gtrsim T_w$) to regimes where multiple calls must occur within a wingbeat (IPI $< T_w$), necessitating higher-order locking or phase slip. Importantly, this transition follows from timing feasibility and does not require assuming that bats seek to maintain strict wingbeat synchrony as a behavioural goal.

3.2.3   Coordination regimes implied by temporal feasibility

The relations above imply three broad regimes of behavioural coordination:

1. **Permissive synchrony** (IPI $\gtrsim T_w$). Temporal feasibility permits 1:1 locking, and calls *may* cluster at a preferred wingbeat phase, consistent with stable coordination under low sensory demand.

2. **Multi-call coordination** (IPI $< T_w$). Multiple emissions occur within a wingbeat cycle,

making strict 1:1 locking impossible. Coordination may persist as higher-order locking

(m:n relations) or as phase clustering at multiple phase families.

3. **Phase slip / decoupling** (high demand). As IPI decreases further, stable phase relations

become difficult to maintain even in higher-order patterns, leading to systematic drift of

ϕ_n across the wingbeat cycle.

In the remainder of the study, simulations are used to illustrate how transitions between

these regimes arise from the responsivity timing relations under changing T_a and bounded wing-

beat frequencies. Empirical observations are discussed only insofar as they provide qualitative

examples consistent with the predicted regimes.

3.2.4   Phase representation and feasibility of phase-locked call insertion

The following section formalises wingbeat–call coordination in terms of phase compatibility

rather than explicit oscillator coupling. To characterise wingbeat–call coordination without

conflating oscillatory phase with kinematic amplitude, I represent the wingbeat as a continuous

phase oscillator with time-varying frequency. The wingbeat phase is defined as

$$\Phi(t) = \Phi(0) + \int_0^t 2\pi f_w(\tau)\,\mathrm{d}\tau, \tag{12}$$

187 where $f_w(t)$ is the instantaneous wingbeat frequency. The within-cycle phase is

$$\varphi(t) = \mathrm{mod}(\Phi(t),\, 2\pi), \qquad \varphi(t) \in [0, 2\pi). \tag{13}$$

188 This definition ensures that the phase advances uniformly by 2π per wingbeat cycle, independent

189 of wing excursion amplitude.

190   Wingbeat kinematics constrain *when* within a cycle a call can be emitted in a phase-locked

191 manner. Rather than encoding this constraint through the phase rate, I represent it as an

192 admissible phase subset

$$\mathcal{A}(t) \subseteq [0, 2\pi), \tag{14}$$

which specifies the range of wingbeat phases at which synchronous call emission is biomechani-

cally permissible. The width and location of $\mathcal{A}(t)$ may depend on wing excursion, flight mode,

or other kinematic factors, but its role is purely restrictive: it does not influence the evolution

of the wingbeat phase itself.

The responsivity framework yields a feasibility-determined time at which the next call can

be emitted based on echo delay and bounded response latency. Denoting this time by t_{n+1}^*, the

corresponding predicted wingbeat phase is

$$\varphi_{n+1}^* = \varphi(t_{n+1}^*). \tag{15}$$

200 Phase-locked call insertion is feasible if and only if this predicted phase lies within the admissible

201 set:

$$\varphi_{n+1}^* \in \mathcal{A}(t_{n+1}^*) \quad \Rightarrow \quad \text{synchronous insertion feasible.} \tag{16}$$

202 If this condition is violated, no phase-locked solution exists for the given timing constraints, and

(a) Constant wingbeat frequency and constant excursion.

(b) Dynamic wingbeat frequency, constant excursion.

(c) Dynamic wingbeat frequency and dynamic excursion.

Figure 2: Waveform representations of wingbeat–call synchrony and asynchrony under different motoric strategies. Each panel shows the simulated wingbeat waveform as a function of time, with vertical markers indicating the timing of call emissions. **(A)** With a fixed wingbeat frequency, synchrony between call emission and specific wingbeat phases is maintained only at low call rates; as call rate increases, calls occur at increasingly variable phases. **(B)** When wingbeat frequency is allowed to increase dynamically (up to a maximum), synchrony persists for longer as the bat accelerates its wingbeats to match call timing, but ultimately breaks down as the maximum is reached. **(C)** When both wingbeat frequency and excursion are allowed to adjust, synchrony can be extended, but only within physiological bounds; as call rate surpasses the system's capacity, asynchrony becomes unavoidable and call emission is dissociated from wing movement. These example trajectories illustrate how precise temporal coordination between call emission and wingbeat is limited by bounded motor dynamics. As sensory demand increases, phase-locked coordination becomes infeasible once physiological limits are reached, giving rise to asynchronous call timing.

the call must be emitted asynchronously with respect to the wingbeat:

$$\varphi_{n+1}^* \notin \mathcal{A}(t_{n+1}^*) \quad \Rightarrow \quad \text{asynchronous insertion required.} \qquad (17)$$

This formulation makes explicit that synchrony and asynchrony are determined by the compatibility between feasibility-imposed call timing and kinematic phase constraints, rather than by an assumed coupling mechanism. Phase slip arises naturally when the admissible phase interval collapses below the timing precision required by closed-loop updating.

3.2.5   Model implications and conditional predictions

The constraint-based framework developed here yields several *conditional implications* for how echolocation call timing may interact with cyclic motor rhythms such as the wingbeat. These implications follow directly from temporal feasibility considerations and do not assume that bats actively seek or maintain synchrony.

1. **Loss of feasible synchrony with decreasing echo delay:** As a bat approaches a target, the acoustic round-trip delay $T_a(t)$ decreases. Within the present framework, maintaining phase-locked coordination between call emission and a cyclic motor rhythm requires that the period of that rhythm remain compatible with the minimum feasible interpulse interval. When $T_a(t)$ becomes sufficiently small, this compatibility condition can no longer be satisfied for a given wingbeat frequency. Under such conditions, phase-locked call–wingbeat coordination becomes temporally infeasible, and call timing must transition to a regime that is asynchronous with respect to the wingbeat cycle. This implication is consistent with observations of progressive call–wingbeat decoupling during high call-rate phases, such as the terminal approach to prey, without requiring that such decoupling be an explicit behavioural goal.

2. **Context-dependent contraction of the synchrony-permissive regime:** The range of echo delays over which synchrony remains feasible depends on the achievable characteristics of the underlying motor rhythm. If flight conditions or behavioural demands constrain wingbeat frequency or amplitude—such as during rapid manoeuvres, load-bearing flight, or other kinematically demanding tasks—the region of parameter space in which synchrony is possible correspondingly contracts. The model therefore implies that call–wingbeat asynchrony should arise more readily in situations where locomotor degrees of freedom are limited, even if call timing alone would permit synchronous coordination under less constrained conditions.

3. **Morphological and biomechanical modulation of feasibility bounds:** Differences in flight morphology and biomechanics can shift the boundaries of temporal feasibility without eliminating them. Species or individuals capable of sustaining higher wingbeat frequencies or broader kinematic ranges may retain synchrony across a wider range of echo delays and call rates. However, within the present framework, no morphological configuration abolishes the existence of a feasibility threshold: as sensory–motor timing demands increase, a point is eventually reached at which phase-locked coordination is no longer compatible with closed-loop operation.

Taken together, these implications link temporal precision in echolocation to general constraints imposed by delayed sensory feedback and bounded motor rhythms. They suggest concrete avenues for empirical testing, including combined acoustic and kinematic recordings that quantify the evolution of call–wingbeat phase relationships across behavioural contexts, as well as comparative analyses examining how differences in flight mechanics shift the boundaries of synchrony-permissive regimes. Importantly, the framework does not predict specific coordination strategies, but instead delineates the conditions under which particular patterns of coordination are temporally feasible or infeasible.

3.3　Wingbeat–Call Synchrony Simulation

To systematically explore the capacity and constraints for maintaining synchrony between wingbeats and call emission, I implemented three distinct simulation regimes:

1. *Constant wingbeat frequency (f_w)*: The bat's wingbeat frequency was held constant throughout the simulated approach, set to a nomical cruising frequency. Call emission timing was determined solely by the echo-processing constraint, independent of the wingbeat cycle. Synchrony was deemed possible only when the calculated call insertion phase ($\phi^*(t)$) fell within the biomechanical limits of the fixed wingbeat excursion (θ), and when no more than one call was required per wingbeat cycle.

2. *Dynamic wingbeat frequency*: Here, the bat's wingbeat frequency was allowed to increase in step with the required call rate, up to a physiologically defined maximum ($f_{w,\max}$). Synchrony was maintained by locking call emission to the wingbeat cycle as long as $f_w \leq f_{w,\max}$ and the phase constraint ($\phi^*(t) \leq \theta$) was met. Once the required call rate exceeded this maximum, synchrony necessarily broke down and calls were emitted asynchronously relative to the wingbeat.

3. *Dynamic frequency with adaptive wing excursion (θ)*: Recognising that bats can also modulate the angular excursion of each wingbeat to further increase wingbeat frequency, I implemented a third regime where, upon reaching $f_{w,\max}$, the model allowed the wing excursion angle (θ) to decrease dynamically in proportion to the required increase in frequency, down to a set physiological minimum ($\theta_{\min}$), implying an aerodynamic threshold. This adjustment enabled the simulated bat to maintain synchrony further into the high call rate regime. Synchrony, in this context, was defined as the condition in which (i) a single call could be accommodated per wingbeat, and (ii) the predicted call insertion phase fell within the instantaneous wing excursion limit.

Recent field measurements support the assumption that wingbeat kinematics are not fixed during prey pursuit. Using on-board inertial sensors, Stidsholt et al. (2021 & 2025) [18, 28] report systematic variation in both wingbeat frequency and wingbeat acceleration amplitude during natural hunting sequences. Although the IMU-derived amplitude reflects wingbeat intensity rather than excursion angle per se, changes in acceleration and frequency necessarily imply modulation of underlying wing kinematics under finite physiological limits. The motor-control conditions explored here therefore bracket empirically observed regimes: from fixed-frequency motion (Condition 1), through frequency-adaptive wingbeats (Condition 2), to combined fre-

quency and excursion-bound adaptation (Condition 3), without assuming a direct mapping between measured acceleration and geometric excursion.

Across all regimes, *synchrony* is thus operationally defined as the temporal and biomechanical alignment of call emission with the wingbeat cycle: a call is synchronous if it occurs within a new wingbeat, at a phase within the instantaneous excursion angle (θ), and at no more than one call per wingbeat. This framework allows explicit identification of when synchrony is lost—either due to echo-processing constraints, biomechanical limitations, or both—and thus enables predictive testing of the hypothesis that asynchrony becomes inevitable as sensory demands intensify.

3.3.1 Simulation framework and model lineage.

The simulations presented in here build directly on the *Vespertillio numeralis* implementation introduced in the responsivity framework [21, 29]. In that work, call timing dynamics were governed by echo-delay–dependent responsivity constraints without explicit representation of cyclic flight mechanics. Here, this baseline implementation is extended by incorporating an explicit wingbeat oscillator with bounded frequency and excursion, as described in the preceeding sections. For a detailed description of the original *V. numeralis* model, including acoustic timing, target interaction, and responsivity parameterisation, see Umadi & Firzlaff (2025) [21].

3.3.2 Simulation Parameters

Each simulation was fully specified by a MATLAB parameter structure, `params`, whose key fields are as follows:

- `bandwidth` [Hz]: Two-element vector $[f_{\min}, f_{\max}]$, the frequency range of simulated FM calls.

- `kr` [dimensionless]: The biological reaction constant (or responsivity coefficient), relating echo delay to the required call emission interval. (See [21])

- `target_distance` [m]: Initial range to the target at the start of the simulation.

- `initial_velocity` [m/s]: The initial approach velocity of the bat relative to the target.

- `initial_call_duration` [s]: Duration of calls at the beginning of the approach.

- `max_call_rate` [Hz]: Maximum call rate, empirical buzz call rate.

- `motile` [logical]: Boolean indicating whether the target is stationary or includes randomised motion (simulating unpredictable prey).

- `makeAudio` [logical]: Option to generate synthetic audio signals (calls and echoes) in the output.

- `f_wing` [Hz]: Baseline wingbeat frequency (used when frequency is fixed).

- `theta` [rad]: Maximum wing excursion angle.

- `min_theta` [rad]: Minimum physiological wing excursion (used in dynamic theta regime).

- `max_wingbeat_freq` [Hz]: Maximum physiological wingbeat frequency.

(a) Constant wingbeat frequency and constant excursion.

(b) Dynamic wingbeat frequency, constant excursion.

(c) Dynamic wingbeat frequency and dynamic excursion.

Figure 3: Simulation of wingbeat–call synchrony under increasing sensory-motor demand. Each panel shows the evolution of predicted and actual wingbeat–call phase relationships as a simulated bat approaches a stationary target, with call rate and wing kinematics computed from the theoretical framework (see text). **Teal line**: Predicted call insertion phase (ϕ^*) in degrees, representing the optimal phase within the wingbeat cycle for emitting each call, given the current echo delay and response window. **Blue dots on black dashed line**: Actual phase of the wingbeat at the time of each call emission. **Red dots**: Calls that are asynchronous by the phase-only criterion (predicted phase exceeds the current excursion). **Yellow dots**: Calls that are truly synchronous, i.e., occur within a new wingbeat, at a phase within the current excursion, and at no more than one call per wingbeat. **Red line (right axis)**: Call rate profile (Hz), increasing as the bat nears the target. **Horizontal dashed line**: Maximum (or current) wing excursion (θ), serving as the phase limit for synchronous call insertion. (**a**) With fixed wingbeat frequency and fixed excursion, synchrony (green) is possible only at low call rates. As call rate rises, synchrony rapidly breaks down, as wingbeat cannot keep pace with the sensory-motor demand. (**b**) With dynamic wingbeat frequency (but fixed excursion), synchrony persists further into the approach, but is ultimately lost when the physiological limit of wingbeat frequency is reached. (**c**) When both wingbeat frequency and excursion are allowed to adapt (i.e., θ decreases as f_w is capped), synchrony can be maintained the longest. Only when both the frequency and amplitude limits are reached does synchrony become impossible, resulting in a rapid onset of asynchrony. These results illustrate the progressive trade-offs bats may employ to maintain temporal coordination of call emission and wingbeat, and reveal how phase-locked coordination breaks down once temporal feasibility bounds are exceeded in high call-rate regimes..

- wing_sync_mode [string]: Simulation regime; either 'fixed' (constant frequency), or 'dynamic' (frequency adapts).

- theta_mode [string]: Mode for wing excursion; either 'fixed' (constant excursion) or 'dynamic' (amplitude adapts to allow higher frequency).

A typical call to the simulation function is as follows:

```matlab
params = struct();
params.bandwidth = [45000, 90000];
params.kr = 5;
params.target_distance = 9; % m
params.max_call_rate = 200;
params.initial_velocity = 2;
params.initial_call_duration = 0.005;
params.f_wing = 5;
params.theta = pi/4;
params.min_theta = 0.3 * params.theta; % lowest wing excursion angle
params.max_wingbeat_freq = 3*params.f_wing;
params.wing_sync_mode = 'dynamic'; % or 'fixed'
params.theta_mode = 'dynamic'; % or 'fixed'
params.motile = true;
params.makeAudio = false;
result = simulateEcholocationWings(params);
```

All simulation outputs described above (including synchrony flags, wingbeat frequency, call phase, and so on) are returned as fields of the output structure result.

3.4   Parameter Sampling for Comparative Simulations

To further examine how synchrony and asynchrony emerge under different motor control scenarios, I performed a Monte Carlo simulation across a range of biologically plausible parameter combinations. For each of the three simulation conditions, (Section 3.3), I generated 200 independent simulation runs with randomly sampled input parameters and a simulated motile prey that randomly shifted in position with a random jitter ($k_{noise} = 0.1$). The initial target distance was drawn uniformly between 10 and 15 metres, initial flight velocity between 2 and 5 m/s, and responsivity coefficient k_r between 3 and 7. The initial wingbeat frequency was randomly selected between 3 and 7 Hz, and the maximum excursion angle θ was sampled between $\pi/6$ and $\pi/4$ radians. To account for biologically realistic modulation of wingbeat properties, the maximum wingbeat frequency was set as a multiple between 2 and 4 times the baseline frequency, and the minimal excursion amplitude was drawn between 10% and 50% of θ. In each run, all other physiological and acoustic parameters (e.g., sampling frequency, call bandwidth, and call duration) were held constant. This stochastic sampling approach allowed quantification of system behaviour across a wide but biologically relevant parameter space.

3.5 Analysis of simulation outputs

Simulation outputs were analysed to characterise how temporal feasibility constraints shape coordination regimes across different motor-control configurations. All analyses were performed on the full ensemble of Monte Carlo simulation runs and are descriptive in nature, quantifying distributional structure and effect size.

Outcome measures. For each simulation run, the following outcome measures were extracted from the output structure returned by `simulateEcholocationWings`:

1. *Number of synchronous calls* (n_{sync}): the total number of calls classified as synchronous according to the operational definition of synchrony (Section 1.3), requiring accommodation of a single call per wingbeat within the instantaneous excursion limit.

2. *Number of asynchronous calls* (n_{async}): the complement of n_{sync}, reflecting calls that could not be accommodated within a wingbeat-aligned emission window.

3. *Fraction of asynchronous calls* (n_{async}/n_{total}): a normalised measure that controls for variation in the total number of calls across simulation runs and provides a direct index of coordination breakdown.

4. *Calls per wingbeat*: computed as the ratio between the total number of calls and the total number of wingbeat cycles completed during the simulated approach. This dimensionless quantity provides a continuous measure of departure from one-to-one coordination and captures transitions toward multi-call-per-cycle regimes.

5. *Wingbeat phase of asynchronous calls*: for calls classified as asynchronous, emission times were converted to wingbeat phase fractions using Eq. (7), yielding a circular variable on $[0, 1]$ that characterises the structure of phase slip.

Descriptive statistics. For each simulation condition, outcome distributions were summarised using robust descriptive statistics, including medians, interquartile ranges (IQR), 5–95% percentile ranges, and median absolute deviation (MAD). These summaries characterise the typical behaviour of the system and its variability across parameter space without assuming underlying sampling noise or independent biological replicates.

Effect size estimation. To quantify the magnitude of distributional shifts between simulation conditions, pairwise comparisons were performed using two complementary effect-size measures:

1. The difference in medians between conditions, with 95% bootstrap confidence intervals obtained by resampling simulation runs with replacement.

2. Cliff's delta (δ), a non-parametric effect size that quantifies the probability that an outcome drawn from one condition exceeds an outcome drawn from another.

These effect sizes provide a scale-free assessment of how strongly coordination regimes differ under alternative motor-control constraints, without invoking null-hypothesis significance testing.

Complete numerical summaries and effect-size estimates for all outcome measures are provided in Supplementary Tables S1–S3.

3.5.1 Quantifying phase locking in simulations

To quantify the presence and strength of wingbeat–call phase locking in simulated data, call emission times were converted to wingbeat phases using Eq. (7). The resulting phase angles $\{\phi_n\}$ define a circular variable on $[0, 2\pi)$, allowing standard circular statistics to be applied.

Phase concentration was assessed using the Rayleigh statistic, which tests the null hypothesis that phases are uniformly distributed around the cycle. The mean resultant vector length,

$$R = \frac{1}{N} \left| \sum_{n=1}^{N} e^{i\phi_n} \right|, \tag{18}$$

provides a measure of phase locking strength, with $R \approx 0$ indicating uniform phase dispersion and $R \to 1$ indicating strong clustering. Statistical significance was evaluated using the Rayleigh test for non-uniformity.

4 RESULTS

4.1 Illustrative coordination regimes under bounded motor dynamics

To provide intuition for how temporal feasibility constraints shape coordination between echolocation call timing and wingbeat dynamics, I first consider representative simulation trajectories under different motor-control configurations. These examples are intended to illustrate the qualitative coordination regimes implied by the theoretical framework. The prevalence and robustness of these regimes are quantified in the following section.

Figure 2 shows time-domain representations of simulated wingbeat motion together with the timing of call emissions for three motor-control configurations: (i) fixed wingbeat frequency and fixed excursion, (ii) dynamic wingbeat frequency with fixed excursion, and (iii) dynamic wingbeat frequency with dynamic excursion. In all cases, call rate increases over time as the simulated bat approaches the target, leading to a progressive reduction in acoustic delay and, consequently, in the minimum feasible interpulse interval.

Under fixed wingbeat frequency and excursion (Fig. 2a), call emission initially remains phase-locked to a narrow region of the wingbeat cycle at low call rates. As sensory–motor demand increases, however, the wingbeat period can no longer accommodate successive calls within a single cycle. Calls are then emitted at increasingly variable phases, resulting in asynchronous timing relative to the wingbeat. This transition occurs without any change in control strategy and reflects a loss of temporal feasibility as the call rate exceeds what the fixed motor rhythm can support.

Allowing wingbeat frequency to vary dynamically while maintaining a fixed excursion (Fig. 2b) extends the range of call rates over which phase-locked coordination can be maintained. As call rate increases, the wingbeat accelerates to preserve compatibility with the shrinking interpulse interval. Nonetheless, once the maximum permitted wingbeat frequency is reached, further increases in call rate again lead to asynchronous call timing. In this configuration, asynchrony thus emerges later in the approach sequence, but remains unavoidable once motor limits are encountered.

When both wingbeat frequency and excursion are allowed to vary (Fig. 2c), synchrony can be maintained over the widest range of call rates. Dynamic adjustment of excursion effectively

enlarges the phase window available for call insertion within each wingbeat cycle. Even in this maximally flexible configuration, however, synchrony persists only while motor parameters remain within imposed bounds. Once both frequency and excursion limits are reached, calls again decouple from the wingbeat, illustrating that increased flexibility shifts but does not eliminate the boundary of temporal feasibility.

The same regimes are shown in a complementary phase-based representation in Figure 3. Here, call timing is expressed in terms of the predicted wingbeat phase at which each call would be inserted based on the current acoustic delay and response window, together with the actual wingbeat phase at call emission. For each motor-control configuration, synchronous calls occupy a bounded region of phase space defined by the available wingbeat excursion. As call rate increases, the predicted insertion phase moves progressively toward this boundary. Once the predicted phase exceeds the admissible range, synchronous insertion is no longer possible and calls occur outside the synchrony-permissive window, producing phase slip and asynchronous timing.

Across all configurations, these illustrative trajectories show that transitions between synchronous and asynchronous coordination arise from the interaction between shrinking sensory delays and bounded motor dynamics. In the next section, I quantify how often these regimes occur across parameter space and how motor flexibility alters the relative prevalence of synchronous and asynchronous coordination.

4.2 Distribution of coordination regimes across parameter space

I next quantified how the coordination regimes illustrated in Section 4.1 are expressed across parameter space using Monte Carlo ensembles of simulation runs under each motor-control configuration (Section 3.5). Because each simulation run represents a deterministic outcome of specified temporal and motor constraints under parameter variation, the resulting distributions reflect heterogeneity across parameter space rather than stochastic measurement error. Accordingly, I summarise these distributions using robust statistics and distribution-level effect sizes (median differences with bootstrap confidence intervals; Cliff's delta) to characterise how motor constraints shape the prevalence of synchronous and asynchronous coordination.

Motor flexibility reduces asynchronous timing and expands the synchrony-permissive regime. Across simulation runs, the fraction of asynchronous calls per run decreased systematically as motor flexibility increased (Fig. 4a). Under fixed wingbeat frequency and fixed excursion (Condition 1), the model produced predominantly asynchronous timing, with a median asynchronous fraction of 0.8269 (IQR 0.0266) (see Table 1). Allowing wingbeat frequency to vary dynamically while keeping excursion fixed (Condition 2) substantially reduced this proportion (median 0.5714, IQR 0.0969), and allowing both dynamic wingbeat frequency and dynamic excursion (Condition 3) reduced it further (median 0.4600, IQR 0.0833) (also see Supplementary Table S1). These shifts indicate that increasing motor flexibility enlarges the region of parameter space in which phase-locked call insertion remains temporally feasible, consistent with the qualitative regime progression illustrated in Figs. 2–3.

Pairwise distribution comparisons confirm that these changes are large and robust (median differences with bootstrap CIs and Cliff's δ; see Supplementary Table S2). Relative to Condition 1, Condition 2 reduced the median asynchronous fraction by 0.2555 (95% bootstrap CI

(a) Fraction of asynchronous calls per run.

(b) Empirical CDF of calls per wingbeat.

(c) Synchronous and asynchronous call counts per run.

(d) Wingbeat phase of asynchronous calls.

Figure 4: Distributional structure of wingbeat–call coordination regimes across motor-control configurations. (a) Fraction of asynchronous calls per simulation run (median, IQR, whiskers; points denote individual Monte Carlo runs). (b) Empirical cumulative distribution functions (ECDFs) of calls per wingbeat, a dimensionless indicator of departure from one-to-one coordination. (c) Raw counts of synchronous (n_{sync}) and asynchronous (n_{async}) calls per run, shown for completeness but sensitive to variation in total call output. (d) Wingbeat phase distributions of asynchronous calls (mapped to $[0, 1]$), pooled across runs within each condition.
Across panels, increasing motor flexibility (from fixed wingbeat frequency and excursion to dynamic frequency and excursion) systematically reduces the prevalence of asynchronous timing and shifts the system toward coordination regimes compatible with phase-locked call insertion. Asynchronous calls are not uniformly distributed in phase but cluster near the boundary of the synchrony-permissive window, consistent with structured phase slip arising from temporal feasibility constraints rather than phase-random decoupling. Normalised measures (fraction asynchronous; calls per wingbeat) provide the most robust indicators of regime structure across parameter space.

$[-0.2684, -0.2428]$), and Condition 3 reduced it by 0.3669 (95% bootstrap CI $[-0.3821, -0.3549]$). The corresponding Cliff's deltas for Condition 1 versus Conditions 2 and 3 were -1, indicating near-complete separation of the outcome distributions under the sampled parameter ensemble. Condition 3 additionally reduced the asynchronous fraction relative to Condition 2 by 0.1114 (95% bootstrap CI $[-0.1305, -0.0946]$; $\delta = -0.7857$), indicating that excursion flexibility provides further, though smaller, expansion of feasible coordination once frequency flexibility is already available.

Calls-per-wingbeat decreases with motor flexibility, indicating reduced reliance on multi-call regimes. A complementary indicator of coordination breakdown is the number of calls emitted per wingbeat cycle. Across simulations, calls-per-wingbeat decreased monotonically as motor flexibility increased (Fig. 4b), reflecting reduced reliance on multi-call-per-cycle regimes when wingbeat dynamics can adapt to shrinking temporal feasibility windows (see Supplementary Table S1). Under Condition 1, calls-per-wingbeat were highly variable and frequently exceeded two (median 2.7101, IQR 1.4181; 5–95% range $[1.6028, 5.1723]$). Under Condition 2, the distribution shifted toward lower values (median 1.9666, IQR 0.4445), and under Condition 3 it shifted lower still (median 1.5624, IQR 0.2129).

Median differences were -0.7435 for Condition 2 relative to Condition 1 (95% CI $[-0.9493, -0.6213]$; $\delta = -0.6249$), -1.1477 for Condition 3 relative to Condition 1 (95% CI $[-1.3490, -1.0375]$; $\delta = -0.8856$), and -0.4042 for Condition 3 relative to Condition 2 (95% CI $[-0.4764, -0.3393]$; $\delta = -0.8294$). Together, these results show that allowing frequency and excursion adaptation shifts the system toward coordination patterns closer to one-to-one emission within the wingbeat cycle, without implying that such synchrony constitutes a behavioural objective.

Synchronous and asynchronous call counts shift in opposite directions, but normalised measures are more interpretable. Raw counts of synchronous and asynchronous calls per run varied systematically across motor-control configurations (Fig. 4c). The median number of synchronous calls increased from 9 in Condition 1 (IQR 7) to 22 in Condition 2 (IQR 14.5) and 28 in Condition 3 (IQR 18). Conversely, the median number of asynchronous calls decreased from 42 (IQR 25) to 30 (IQR 20) and 25 (IQR 15), respectively. Because the total number of calls per run can vary across simulations, normalised measures such as the fraction of asynchronous calls and calls-per-wingbeat provide the most directly interpretable indicators of coordination regime structure, while raw counts serve as intuitive complements.

Asynchronous call phases exhibit structured phase-slip near feasibility boundaries. To assess whether asynchronous calls in the model occur at arbitrary wingbeat phases or exhibit structured timing, I analysed the wingbeat phase fractions of asynchronous call emissions (Fig. 4d). Across all conditions, asynchronous phases were strongly clustered within a narrow phase interval (mean phase fractions ≈ 0.017–0.030), with high mean resultant lengths ($R = 0.9367$–0.9678). This concentration indicates that asynchrony in the model is dominated by phase-slip events occurring near the boundary of the synchrony-permissive window, rather than by uniformly distributed decoupled timing. This phase structure arises from the boundary-defined synchrony criterion used in the model and should not be interpreted as evidence for preferred biomechanical or respiratory phases in bats. Circular summary statistics for asyn-

Table 1: Headline coordination metrics across simulation conditions. Values are reported as median (IQR) across $N = 200$ Monte Carlo runs per condition. The fraction of asynchronous calls and calls-per-wingbeat provide normalised indicators of regime structure that are robust to differences in total call output across runs. Full descriptive statistics underlying these headline metrics are provided in Supplementary Table S1.

Condition	f_w	θ	Fraction async	Calls per wingbeat
C1	fixed	fixed	0.827 (0.027)	2.710 (1.418)
C2	dynamic	fixed	0.571 (0.097)	1.967 (0.444)
C3	dynamic	dynamic	0.460 (0.083)	1.562 (0.213)

chronous call phases are reported in Supplementary Table S3.

5 DISCUSSION

5.1 Temporal feasibility as a governing constraint on closed-loop echolocation

Bat echolocation is a canonical closed-loop sensing system: vocal emissions shape the sensory scene, echoes return after a propagation delay, and the animal updates behaviour under finite neural and motor latencies [3, 5, 8, 30]. The present study formalises a narrower question: *when is closed-loop timing compatible with bounded response dynamics and an ongoing cyclic motor rhythm?* In the framework developed here, that question is answered by feasibility relations that specify the shortest admissible interpulse interval (IPI) consistent with echo-guided updating (Eq. 4 and related expressions), and by the consequent compatibility conditions for phase-locked coordination with a wingbeat rhythm (e.g. Eq. 9 and the phase-violation criterion in Eq. 14).

A key conceptual point is that feasibility is not a behavioural objective. The model does not assume that bats *seek* wingbeat–call synchrony, minimise asynchrony, or enforce a particular phase. Rather, the framework delineates a region of state space in which phase-locked insertion is possible and a region in which it is not, independent of motivation or strategy. In this sense, the work provides a constraint-based baseline: it separates patterns that could plausibly be produced by any controller from patterns that would require additional mechanisms (or would be impossible) once temporal margins become binding.

5.2 Buffered pseudo–closed-loop behaviour can masquerade as feedback control

A call–echo–call sequence is not, by itself, sufficient evidence for tight closed-loop control. When acoustic delays are short relative to the animal's effective update time, echoes often arrive with substantial temporal slack. In this buffered regime, a bat could emit calls according to an internally generated schedule or a kinematic heuristic, while still receiving informative echoes "in time" before the next emission becomes mechanically or neurally available. Such *pseudo–closed-loop* operation can therefore mimic echo-anchored regulation without requiring that call timing be causally governed by echo arrival. This interpretation is consistent with recent analyses emphasising that, in some contexts, call timing can be accurately generated by internal pacing mechanisms when echoes are not rate-limiting [31].

The distinction becomes behaviourally consequential once the buffer collapses. As ranges shorten and call rates rise, the informative portion of the echo response competes directly with the scheduling of subsequent emissions. In the responsivity formulation, this corresponds to the regime in which IPI is explicitly constrained by the combination of echo delay and the bounded

response window (Eq. 4–6). Importantly, this does not imply that bats must wait for the full termination of the echo stream: the relevant anchor is the earliest time at which sufficient *information* is available to drive an update. Nevertheless, once the feasibility bound is active, internally paced schedules can no longer remain decoupled from the acoustic scene.

Within the buffered regime, apparent invariants such as an approximately constant *distance travelled per call* can arise as emergent regularities rather than controlled objectives. If call timing follows an internal policy IPI $\approx g(v)$ that covaries with velocity over a restricted behavioural range, the derived quantity $d_{\mathrm{pc}} = v \cdot \mathrm{IPI}$ can appear stable even when echo timing is not rate-limiting. This provides a concrete route by which "invariants" can be observed under conditions where propagation delays are not yet the dominant constraint.

In contrast, once the system enters the temporally constrained regime (Eq. 5 and the saturation bound in Eq. 6), maintaining a fixed spatial sampling interval becomes progressively incompatible with the necessary contraction of IPI with decreasing range. The prediction is therefore not that invariants are "excluded", but that they should be *regime contingent*: they are most expected under buffered operation and should degrade systematically as temporal feasibility becomes the binding limitation, particularly in high-demand phases such as pursuit and the terminal buzz, as the results from Jakobsen et. al. (2025) indicate [20]. Moreover, when temporal overlap threatens interpretability (e.g. increasing broadcast–echo ambiguity in clutter), bats are known to recruit signal-domain degrees of freedom rather than attempting to preserve a fixed spatial sampling interval; one concrete example is dynamic frequency shifting to reduce ambiguity under cluttered echo streams [32]. In the present framing, such adjustments are naturally interpreted as auxiliary control dimensions recruited when feasibility constraints begin to bind, rather than as evidence that a single spatial invariant is the maintained objective across regimes.

5.3 Synchrony and asynchrony as regime outcomes rather than control objectives

The framework provides a parsimonious interpretation of wingbeat–call synchrony. In low-demand conditions (longer delays, longer feasible IPIs), there is ample slack: many call insertion times are compatible with closed-loop updating, and one-to-one locking can occur without requiring a dedicated coupling mechanism. Synchrony is therefore expected to be common during steady flight or other low-demand tasks, consistent with long-standing observations of phase-locked calling in some contexts [15–17]. At broader comparative scales, scaling relationships between wingbeat frequency and pulse emission rate (including common 1:1 and 1:2 coordination patterns) further support the view that phase-locked regimes are feasible and often realised under permissive conditions, without implying that phase locking itself is the control variable [33].

As sensory demand increases, feasibility margins contract. The wingbeat period cannot be reduced indefinitely, and the admissible phase window for inserting calls within a wing excursion narrows (Eq. 12–15). Under these conditions, strict phase locking becomes fragile and eventually infeasible. Crucially, this transition does not require a discrete "switch" in behavioural mode: asynchrony emerges as the expected outcome when timing requirements exceed what the motor rhythm can accommodate. This framing aligns with empirical reports that coupling is common at low duty cycles but degrades as call rate increases, and that wild bats can transiently decouple

sound production from wingbeats during demanding capture manoeuvres [18, 19].

The term "brief decoupling" as used by Stidsholt et al. (2021) [18] can be given a precise interpretation within the present framework. In their data, decoupling does not correspond to a sustained loss of coordination, but to short intervals—predominantly during late approach and the buzz—where call timing no longer exhibits a stable phase relationship to the wingbeat cycle. The feasibility analysis developed here predicts exactly such transient breakdowns: as call rates increase and interpulse intervals approach the minimum required for echo-guided updating, the admissible phase window for call insertion collapses relative to the wingbeat period. Under these conditions, phase-locked coordination becomes intermittently infeasible, producing brief phase-slip without requiring a discrete change in control strategy. Importantly, the model reproduces this effect even when call timing remains fully echo-constrained, indicating that the empirically observed decoupling reflects a regime-limited consequence of closed-loop timing rather than an active disengagement of wingbeat–call coordination.

Recent laboratory evidence further supports this interpretation. Xia et al. (2025) demonstrate that wingbeat–call coupling is flexible across species, call types, and task demands, with structured synchrony during permissive regimes and systematic decoupling during high call-rate sequences such as long sonar sound groups and terminal buzzes [19]. Rather than indicating multiple control modes, these observations are naturally explained by the present framework as shifts in feasibility boundaries driven by differences in wingbeat frequency, excursion limits, or respiratory timing. Together, the field observations of Stidsholt et al. and the controlled laboratory results of Xia et al. converge on a unified conclusion: wingbeat–call decoupling is not an optional behavioural strategy, but an expected and transient outcome when temporal constraints imposed by closed-loop sensing exceed what a cyclic motor rhythm can accommodate.

The simulations further predict that asynchrony need not be phase-random. When the feasibility boundary is defined relative to a limited excursion window, violations occur preferentially near that boundary, producing structured phase-slip. In this study, the clustering of asynchronous phases is therefore interpreted as a *geometric consequence of the feasibility criterion* (Eq. 14–15), not as evidence for preferred biomechanical or respiratory phases in bats. This distinction matters: structured asynchrony can arise even in a single underlying control architecture, simply because the admissible timing region has collapsed.

5.4 Moving targets, lagged estimates, and why synchrony can fail during pursuit

Temporal feasibility constraints become especially salient for motile targets. For a stationary reflector, T_a provides a reliable estimate of range, and successive emissions can be planned from information that remains valid across the IPI. For an erratically moving prey item, however, the echo-derived state available at emission time is necessarily lagged by the time the next call is scheduled. Under such conditions, maintaining strict wingbeat–call synchrony would require continuous compensatory adjustments of flight kinematics to counteract target motion, effectively demanding motor flexibility precisely when the feasibility window is shrinking.

The framework therefore predicts that synchrony breakdown during pursuit is not merely an "adaptive choice" but a likely consequence of operating with delayed sensory feedback at high update rates. This interpretation also sharpens what synchrony can (and cannot) imply in data: synchrony may be common when the task is temporally permissive, but its disappearance during

pursuit does not by itself indicate a loss of control. It may simply indicate that phase locking has become infeasible given the prevailing delays, response bounds, and motor limits.

5.5   Comparative and morphological implications

Although the model is intentionally agnostic about detailed aerodynamics and muscle physiology, it yields clear comparative implications. Morphological and biomechanical differences should primarily shift *where* feasibility boundaries occur, rather than introducing fundamentally different coordination principles. Species with broader kinematic ranges (e.g. higher sustainable wingbeat frequencies, greater flexibility in excursion) should retain phase-locked coordination over a wider range of echo delays and call rates, whereas species with constrained flight dynamics should cross feasibility limits earlier. This perspective is consistent with the wide diversity of flight morphology and foraging guilds in bats, and with the continuous variation in echolocation behaviour across ecological contexts [5, 19, 34, 35]. Comparative scaling of wingbeat frequency and pulse emission rate provides an additional constraint-based bridge between morphology and coordination regimes, supporting the interpretation that morphological differences modulate the location of feasibility boundaries rather than altering the governing principles [33].

Notably, the framework does *not* ascribe adaptive value to synchrony or asynchrony themselves. Instead, it predicts quantitative shifts in the prevalence of coordination regimes under comparable sensory demands. This makes the comparative question tractable: measure how the synchrony-permissive region moves with morphology and kinematic capacity, rather than asking whether a species "uses synchrony" as a strategy.

5.6   Methodological implications for interpreting coordination data

The feasibility framework clarifies which aspects of wingbeat–call coordination are diagnostically informative and which are not. Because phase-locked calling can occur whenever temporal margins are permissive, the mere presence of synchrony is insufficient evidence for causal motor coupling. Conversely, asynchrony is an expected outcome once feasibility bounds are exceeded and therefore does not, by itself, imply flexible or decoupled control. Interpreting coordination data therefore requires explicit reference to the temporal regime in which calls are produced.

A practical implication is that analyses based solely on correlation or coincidence metrics (e.g. synchrony counts, phase histograms pooled across an entire sequence) conflate fundamentally different operating regimes. The present results show that regime structure is more directly captured by normalised measures that reference the motor cycle, such as calls-per-wingbeat, the fraction of asynchronous calls, and stage-resolved phase distributions (Section 4.2). These quantities remain interpretable across variations in total call output and flight duration, and they map directly onto the feasibility constraints that delimit admissible timing.

The framework also specifies where additional measurements are essential. Acoustic timing alone cannot distinguish buffered pseudo–closed-loop operation from genuinely echo-limited control. Disambiguating these regimes requires concurrent kinematic data, particularly wingbeat phase and excursion, obtained via high-speed videography, inertial sensors, or on-board telemetry. Recent developments in on-board telemetry provide a powerful means to elucidate the temporal coordination of behavioural parameters in freely flying bats [36].

More generally, the feasibility analysis motivates a shift in emphasis from asking whether calls are synchronised to asking *when synchrony is possible at all*. By anchoring coordination

metrics to explicit temporal constraints, empirical studies can avoid over-interpreting correlation structure and instead test whether observed patterns track the boundaries imposed by delayed feedback and bounded response dynamics.

5.7 Generality, limitations, and testable predictions

The logic of temporal feasibility is not specific to bats. Any active sensing system that relies on self-generated signals, delayed feedback, and bounded response dynamics will exhibit analogous constraints, including electrosensing fish and whisking rodents [23, 37], as well as engineered active-perception systems [22]. In such systems, coordination with rhythmic actuation is expected to hold in permissive regimes and to fail in structured ways once temporal margins collapse.

The present work deliberately omits energetic costs, detailed aerodynamics, sensory noise, and learning. Accordingly, it should be read as identifying *necessary constraints*, not as a complete behavioural model. Within that scope, it yields testable predictions: (i) synchrony breakdown should correlate more strongly with temporal demand (echo delay, required response window) than with categorical behavioural labels; (ii) feasibility boundaries should shift with kinematic capacity across individuals and species; and (iii) asynchronous timing near transitions should show structured phase-slip consistent with the geometry implied by Eq. 14–15. These predictions can be evaluated with combined acoustic and kinematic datasets collected across controlled range manipulations and natural pursuit sequences.

6 CONCLUSIONS

This study identifies *temporal feasibility* as a fundamental constraint shaping wingbeat–call coordination in bat echolocation. By formalising the timing dependencies between call emission, acoustic delay, sensory processing, and motor response, the framework specifies when phase-locked coordination with a rhythmic motor cycle is possible and when it must fail. Synchrony and asynchrony thus emerge as regime-dependent outcomes of bounded response dynamics, rather than as behavioural objectives or discrete control strategies.

Under temporally permissive conditions, substantial slack allows phase-locked calling to occur without requiring dedicated coupling mechanisms. As sensory demand increases during pursuit and the terminal buzz, feasibility margins contract and the admissible phase window for call insertion collapses relative to the wingbeat period. The resulting phase slip and brief decoupling arise necessarily, even when call timing remains echo-constrained. This provides a mechanistic explanation for empirical observations of transient decoupling during capture manoeuvres without invoking changes in control architecture.

By separating feasibility constraints from behavioural goals, the framework reconciles diverse empirical patterns, including phase locking, discrete coordination modes, and regime-specific breakdown of synchrony. More broadly, the results illustrate how rhythmic motor coordination in active sensing systems is governed by delayed feedback and bounded response dynamics, offering a general constraint-based perspective for interpreting sensorimotor timing in ecological behaviour.

SUMMARY OF REVISIONS

This revised version with an updated title extends earlier analyses of wingbeat–call coordination by embedding the problem explicitly within a temporal feasibility framework grounded in closed-loop sensory–motor constraints. Building on the responsivity model, the present work formalises when synchrony with cyclic motor rhythms is physically possible, and when it must necessarily fail.

Relative to the earlier version, the manuscript now (i) derives explicit feasibility bounds linking echo delay, biological response time, and wingbeat dynamics; (ii) distinguishes buffered pseudo–closed-loop operation from genuinely rate-limited closed-loop behaviour; (iii) demonstrates, via Monte Carlo simulations, how motor flexibility (frequency and excursion modulation) shifts but does not eliminate synchrony limits; and (iv) shows that structured asynchrony and phase slip emerge as geometric consequences of collapsing admissible timing windows, rather than as distinct behavioural strategies.

These additions unify empirical observations of synchrony, decoupling and morphological underpinnings within a single constraint-based framework. The revised manuscript clarifies that wingbeat–call synchrony is not a controlled objective, but a regime outcome that holds only while temporal margins remain permissive. When sensory demand increases, asynchrony becomes an inevitable and predictable consequence of first-principles timing constraints in active echolocation.

ACKNOWLEDGEMENTS

I thank my colleagues at the Technical University of Munich for helpful discussions and continued support throughout the development of this work. I am particularly grateful to Uwe Firzlaff for his supervision, guidance, and many insightful discussions. I also thank two anonymous reviewers for their critical and constructive comments, which prompted substantial clarification of the theoretical framework and helped reshape the manuscript toward a more precise control-theoretic perspective on active echolocation.

CODE AND DATA AVAILABILITY

The simulation code, experimental data, and analysis scripts have been made available in support of the research presented in this work.

Available at Zenodo DOI: https://doi.org/10.5281/zenodo.15854977

The corresponding GitHub Repository is located at: https://github.com/raviumadi/wingbeats

FUNDING

This study did not use external funding.

COMPTETING INTERESTS

The author declares no competing interests.

Manuscript Information

Version: V2

Peer-Review: September 24, 2025

Revised: December 25, 2025

Words in text: 7823

Number of floats/tables/figures: 11

Number of math displayed: 18

REFERENCES

1. Griffin, D. R. & Galambos, R. The Sensory Basis of Obstacle Avoidance by Flying Bats. *Journal of Experimental Zoology* **86,** 481–506. ISSN: 1097-010X. doi:10.1002/jez.1400860310 (1941).

2. Griffin, D. R. How Bats Guide Their Flight by Supersonic Echoes. *American Journal of Physics* **12,** 342–345. ISSN: 0002-9505. doi:10.1119/1.1990634 (Dec. 1944).

3. Griffin, D. R. *Listening in the Dark: The Acoustic Orientation of Bats and Men* xviii, 413 (Yale Univer. Press, Oxford, England, 1958).

4. Moss, C. F. & Surlykke, A. Auditory Scene Analysis by Echolocation in Bats. *The Journal of the Acoustical Society of America* **110,** 2207–2226. ISSN: 0001-4966. doi:10.1121/1.1398051 (2001).

5. Schnitzler, H.-U. & Kalko, E. K. V. Echolocation by Insect-Eating Bats. *BioScience* **51,** 557. ISSN: 0006-3568. doi:10.1641/0006-3568(2001)051[0557:ebieb]2.0.co;2 (2001).

6. Surlykke, A. & Kalko, E. K. V. Echolocating Bats Cry Out Loud to Detect Their Prey. *PLoS ONE* **3,** e2036. doi:10.1371/journal.pone.0002036 (2008).

7. Jakobsen, L. & Surlykke, A. Vespertilionid Bats Control the Width of Their Biosonar Sound Beam Dynamically during Prey Pursuit. *Proceedings of the National Academy of Sciences* **107,** 13930–13935. ISSN: 0027-8424. doi:10.1073/pnas.1006630107 (2010).

8. Moss, C. F. & Surlykke, A. Probing the Natural Scene by Echolocation in Bats. *Frontiers in Behavioral Neuroscience* **4.** ISSN: 1662-5153. doi:10.3389/fnbeh.2010.00033 (Aug. 2010).

9. *Biosonar* (eds Surlykke, A., Nachtigall, P. E., Fay, R. R. & Popper, A. N.) ISBN: 978-1-4614-9145-3 978-1-4614-9146-0. doi:10.1007/978-1-4614-9146-0 (Springer New York, New York, NY, 2014).

10. Moss, C. F., Bohn, K., Gilkenson, H. & Surlykke, A. Active Listening for Spatial Orientation in a Complex Auditory Scene. *PLOS Biology* **4,** e79. ISSN: 1545-7885. doi:10.1371/journal.pbio.0040079 (Mar. 2006).

11. Moss, C. F., Chiu, C. & Surlykke, A. Adaptive Vocal Behavior Drives Perception by Echolocation in Bats. *Current Opinion in Neurobiology* **21,** 645–652. ISSN: 09594388. doi:10.1016/j.conb.2011.05.028 (Aug. 2011).

12. Geberl, C., Brinkløv, S., Wiegrebe, L. & Surlykke, A. Fast Sensory–Motor Reactions in Echolocating Bats to Sudden Changes during the Final Buzz and Prey Intercept. *Proceedings of the National Academy of Sciences* **112,** 4122–4127. doi:10.1073/pnas.1424457112 (Mar. 2015).

13. Genzel, D., Hoffmann, S., Prosch, S., Firzlaff, U. & Wiegrebe, L. Biosonar Navigation above Water II: Exploiting Mirror Images. *Journal of Neurophysiology* **113,** 1146–1155. ISSN: 0022-3077, 1522-1598. doi:10.1152/jn.00264.2014 (Feb. 2015).

14. Schnitzler, H.-U. Die Ultraschall-Ortungslaute der Hufeisen-Fledermäuse (Chiroptera-Rhinolophidae) in verschiedenen Orientierungssituationen. *Zeitschrift für vergleichende Physiologie* **57,** 376–408. ISSN: 1432-1351. doi:10.1007/BF00303062 (Dec. 1968).

15. Suthers, R. A., Thomas, S. P. & Suthers, B. J. Respiration, Wing-Beat and Ultrasonic Pulse Emission in an Echo-Locating Bat. *Journal of Experimental Biology* **56,** 37–48. ISSN: 1477-9145 (1972).

16. Koblitz, J. C., Stilz, P. & Schnitzler, H. .-. Source Levels of Echolocation Signals Vary in Correlation with Wingbeat Cycle in Landing Big Brown Bats (Eptesicus Fuscus). *Journal of Experimental Biology* **213,** 3263–3268. ISSN: 0022-0949. doi:10.1242/jeb.045450 (2010).

17. Wong, J. G. & Waters, D. A. The Synchronisation of Signal Emission with Wingbeat During the Approach Phase in Soprano Pipistrelles (*Pipistrellus Pygmaeus*). *Journal of Experimental Biology* **204,** 575–583. ISSN: 0022-0949, 1477-9145. doi:10.1242/jeb.204.3.575 (Feb. 2001).

18. Stidsholt, L., Johnson, M., Goerlitz, H. R. & Madsen, P. T. Wild Bats Briefly Decouple Sound Production from Wingbeats to Increase Sensory Flow during Prey Captures. *iScience* **24,** 102896. ISSN: 25890042. doi:10.1016/j.isci.2021.102896 (Aug. 2021).

19. Xia, H., Ma, N., Li, A. & Luo, J. Call Production and Wingbeat Coupling Is Flexible and Species-Specific in Echolocating Bats. *Annals of the New York Academy of Sciences* **1547,** 105–115. ISSN: 1749-6632. doi:10.1111/nyas.15325 (Mar. 2025).

20. Jakobsen, L. *et al.* Velocity as an Overlooked Driver in the Echolocation Behavior of Aerial Hawking Vespertilionid Bats. *Current Biology,* S096098222401710X. ISSN: 09609822. doi:10.1016/j.cub.2024.12.042 (Jan. 2025).

21. Umadi, R. & Firzlaff, U. *Biosonar Responsivity Sets the Stage for the Terminal Buzz* June 2025. doi:10.1101/2025.06.16.659925.

22. Bajcsy, R. Active Perception. *Proceedings of the IEEE* **76,** 966–1005. ISSN: 1558-2256. doi:10.1109/5.5968 (Aug. 1988).

23. Kleinfeld, D., Ahissar, E. & Diamond, M. E. Active Sensation: Insights from the Rodent Vibrissa Sensorimotor System. *Current Opinion in Neurobiology. Sensory Systems* **16,** 435–444. ISSN: 0959-4388. doi:10.1016/j.conb.2006.06.009 (Aug. 2006).

24. Pio-Lopez, L., Nizard, A., Friston, K. & Pezzulo, G. Active Inference and Robot Control: A Case Study. *Journal of The Royal Society Interface* **13,** 20160616. ISSN: 1742-5689. doi:10.1098/rsif.2016.0616 (Sept. 2016).

25. Rojas-Líbano, D. & Parada, F. J. Body-World Coupling, Sensorimotor Mechanisms, and the Ontogeny of Social Cognition. *Frontiers in Psychology* **10.** ISSN: 1664-1078. doi:10.3389/fpsyg.2019.03005 (Jan. 2020).

26. Nguyen, P. D. H. *et al.* Sensorimotor Representation Learning for an "Active Self" in Robots: A Model Survey. *KI - Künstliche Intelligenz* **35,** 9–35. ISSN: 1610-1987. doi:10.1007/s13218-021-00703-z (Mar. 2021).

27. Strohmeier, P. *et al. Sensorimotor Devices: Coupling Sensing and Actuation to Augment Bodily Experience* in *Proceedings of the Extended Abstracts of the CHI Conference on Human Factors in Computing Systems* (Association for Computing Machinery, New York, NY, USA, Apr. 2025), 1–7. ISBN: 979-8-4007-1395-8. doi:10.1145/3706599.3706735.

28. Stidsholt, L., Zebele, M., Scholz, C. & Voigt, C. C. Wild Bats Hunt Insects Faster under Lit Conditions by Integrating Acoustic and Visual Information. *Proceedings of the National Academy of Sciences* **122,** e2515087122. doi:10.1073/pnas.2515087122 (Sept. 2025).

29. Umadi, R. *Biosonar Responsivity - Simulation Code, Data, And Supporting Files* Zenodo. July 2025. doi:10.5281/zenodo.15854831.

30. Griffin, D. R., Webster, F. A. & Michael, C. R. The Echolocation of Flying Insects by Bats. *Animal Behaviour* **8,** 141–154. ISSN: 0003-3472. doi:10.1016/0003-3472(60)90022-1 (July 1960).

31. Taub, M. *et al.* What Determines the Information Update Rate in Echolocating Bats. *Communications Biology* **6,** 1–8. ISSN: 2399-3642. doi:10.1038/s42003-023-05563-x (Nov. 2023).

32. Hiryu, S., Bates, M. E., Simmons, J. A. & Riquimaroux, H. FM Echolocating Bats Shift Frequencies to Avoid Broadcast–Echo Ambiguity in Clutter. *Proceedings of the National Academy of Sciences* **107,** 7048–7053. doi:10.1073/pnas.1000429107 (Apr. 2010).

33. Jones, G. Scaling of Wingbeat and Echolocation Pulse Emission Rates in Bats: Why Are Aerial Insectivorous Bats so Small? *Functional Ecology* **8,** 450–457. ISSN: 0269-8463. doi:10.2307/2390068. JSTOR: 2390068 (1994).

34. Norberg, U. M. & Rayner, J. M. V. Ecological Morphology and Flight in Bats (Mammalia; Chiroptera): Wing Adaptations, Flight Performance, Foraging Strategy and Echolocation. *Philosophical Transactions of the Royal Society of London. B, Biological Sciences* **316,** 335–427. ISSN: 0080-4622, 2054-0280. doi:10.1098/rstb.1987.0030 (Sept. 1987).

35. Denzinger, A. & Schnitzler, H.-U. Bat Guilds, a Concept to Classify the Highly Diverse Foraging and
Echolocation Behaviors of Microchiropteran Bats. *Frontiers in Physiology* **4.** ISSN: 1664-042X. doi:`10.3389/`
`fphys.2013.00164` (July 2013).

36. Stidsholt, L. Unlocking the Mysteries of Biosonar Use and Foraging Behaviour in Wild Bats with On-Board
Acoustic Recording Tags. *Journal of Experimental Biology* **228,** jeb250777. ISSN: 0022-0949, 1477-9145.
doi:`10.1242/jeb.250777` (Aug. 2025).

37. Nelson, M. E. & Maciver, M. A. Prey Capture in the Weakly Electric Fish Apteronotus Albifrons: Sensory
Acquisition Strategies and Electrosensory Consequences. *Journal of Experimental Biology* **202,** 1195–1203.
ISSN: 0022-0949. doi:`10.1242/jeb.202.10.1195` (May 1999).

A SUPPLEMENTARY INFORMATION

A.1 Quantitative Output

Table 2: Supplementary Table S1. Descriptive statistics for synchronous call counts per run. Summary statistics are computed across $N = 200$ Monte Carlo runs for each condition.

Condition	Mean	SD	Median	IQR	P05	P25	P75	P95	MAD
C1 (f_w fixed, θ fixed)	10.2	5.6	9	7.0	4.0	6.0	13.0	21.5	3
C2 (f_w dyn, θ fixed)	24.9	12.3	22	14.5	10.0	16.0	30.5	50.5	7
C3 (f_w dyn, θ dyn)	32.0	15.3	28	18.0	14.0	21.0	39.0	64.0	9

Table 3: Supplementary Table S1 (continued). Descriptive statistics for asynchronous call counts per run. Summary statistics are computed across $N = 200$ Monte Carlo runs for each condition.

Condition	Mean	SD	Median	IQR	P05	P25	P75	P95	MAD
C1 (f_w fixed, θ fixed)	46.9	21.2	42	25.0	24.0	31.5	56.5	100.5	12
C2 (f_w dyn, θ fixed)	32.6	15.2	30	20.0	14.5	21.0	41.0	67.5	10
C3 (f_w dyn, θ dyn)	26.5	11.6	25	15.0	12.5	18.0	33.0	50.0	7

Table 4: Supplementary Table S1 (continued). Descriptive statistics for asynchronous call fraction per run. Summary statistics are computed across $N = 200$ Monte Carlo runs for each condition.

Condition	Mean	SD	Median	IQR	P05	P25	P75	P95	MAD
C1 (f_w fixed, θ fixed)	0.827	0.023	0.827	0.027	0.790	0.812	0.838	0.866	0.013
C2 (f_w dyn, θ fixed)	0.569	0.065	0.571	0.097	0.467	0.520	0.617	0.672	0.047
C3 (f_w dyn, θ dyn)	0.457	0.059	0.460	0.083	0.356	0.417	0.500	0.547	0.041

Table 5: Supplementary Table S1 (continued). Descriptive statistics for calls per wingbeat. Summary statistics are computed across $N = 200$ Monte Carlo runs for each condition.

Condition	Mean	SD	Median	IQR	P05	P25	P75	P95	MAD
C1 (f_w fixed, θ fixed)	3.028	1.178	2.710	1.418	1.603	2.214	3.633	5.172	0.662
C2 (f_w dyn, θ fixed)	2.024	0.305	1.967	0.444	1.622	1.783	2.227	2.556	0.214
C3 (f_w dyn, θ dyn)	1.587	0.166	1.562	0.213	1.344	1.475	1.688	1.898	0.102

Table 6: Supplementary Table S2. Pairwise effect sizes between conditions. For each metric, the table reports the difference in medians (CondA−CondB) with bootstrap 95% confidence intervals, and Cliff's δ with 95% confidence intervals.

Metric	Comparison	ΔMedian	CI_{low}	CI_{high}	δ	CI_{low}	CI_{high}
Synchronous calls (n_{sync})	C1–C2	13.0	11.0	15.0	0.800	0.740	0.854
Synchronous calls (n_{sync})	C1–C3	19.0	16.0	22.0	0.908	0.872	0.941
Synchronous calls (n_{sync})	C2–C3	6.0	3.0	9.5	0.302	0.198	0.410
Asynchronous calls (n_{async})	C1–C2	-12.0	-16.0	-8.0	-0.450	-0.547	-0.348
Asynchronous calls (n_{async})	C1–C3	-17.0	-20.0	-14.0	-0.661	-0.733	-0.581
Asynchronous calls (n_{async})	C2–C3	-5.0	-9.0	-1.0	-0.240	-0.345	-0.126
Async fraction (f_{async})	C1–C2	-0.255	-0.268	-0.243	-1.000	-1.000	-1.000
Async fraction (f_{async})	C1–C3	-0.367	-0.382	-0.355	-1.000	-1.000	-1.000
Async fraction (f_{async})	C2–C3	-0.111	-0.131	-0.094	-0.786	-0.842	-0.722
Calls per wingbeat (c_{pw})	C1–C2	-0.743	-0.944	-0.620	-0.625	-0.713	-0.534
Calls per wingbeat (c_{pw})	C1–C3	-1.148	-1.347	-1.042	-0.886	-0.935	-0.829
Calls per wingbeat (c_{pw})	C2–C3	-0.404	-0.477	-0.340	-0.829	-0.876	-0.774

Table 7: Supplementary Table S3. Circular summaries of asynchronous call phases. Asynchronous call phases are pooled within each condition (total $N_{async\ phases}$ shown). Reported are the mean angle (radians), mean phase as a fraction of the wingbeat cycle, mean resultant length R, and circular standard deviation.

Condition	N_{async}	Mean angle (rad)	Mean phase (frac.)	R	Circ. SD (rad)
C1 (f_w fixed, θ fixed)	9377	0.188	0.0299	0.937	0.362
C2 (f_w dyn, θ fixed)	6516	0.130	0.0207	0.968	0.256
C3 (f_w dyn, θ dyn)	5292	0.108	0.0172	0.966	0.265