AI-Based Detection of Coliform Colonies Using CNN Transfer Learning for Application to Cultured Plate Analysis in Water Quality Research

Shivaji Mallela[1], Abria Gates[1], Sutanu Bhattacharya[1], Benedict Okeke[2], Olcay Kursun[1,*]

[1]Department of Computer Science and Computer Information Systems, [2]Department of Biology and Environmental Sciences, Auburn University at Montgomery, Montgomery, AL 36117, USA.

*Corresponding author: Olcay Kursun
310F Goodwyn Hall, 7400 East Dr,
Auburn University at Montgomery, Montgomery, AL 36117, USA
Phone: 1-334-244-3314
E-mail: okursun@aum.edu

Abstract

Pathogenic bacterial contamination of water poses a severe public health risk where laboratory resources are scarce. We propose a two-stage Artificial Intelligence (AI) pipeline for automated detection and classification of coliform colonies on agar plates. In Stage 1, a YOLOv8 detector localizes every colony (replacing manual ImageJ annotation) and achieves a mean average precision at 0.5 intersection-over-union (mAP@50) of 87.6% on 105 held-out public images. In Stage 2, each detected patch is classified by a convolutional neural network (CNN) that is first "warmed up" via pretraining on ten classes drawn from a 24-class public bacterial-colony dataset (~5,000 patches) and then fine-tuned on two separate four-class tasks: our in-house-collected coliform dataset (80/20 train/test split), where accuracy rose from 73% (no pretraining) to 86%, and an independent four-class subset from the same public dataset, where accuracy reached 91%. The full pipeline processes each plate in under five seconds. Comparative baselines using Histogram of Oriented Gradients (HOG), Local Binary Patterns (LBP), and Haralick features with Support Vector Machine (SVM) classifiers underscore the deep-learning approach's superiority. Future work will integrate full-color media cues and contextual metadata, and optimize on-device inference for truly portable field deployment.

Keywords

Coliform Detection, Deep Learning in Microbiology, Transfer Learning, YOLOv8 Object Detection, Water Quality Monitoring

1. Introduction

Waterborne diseases remain a major public health challenge worldwide, with an estimated 1.6 million deaths annually linked to unsafe water and sanitation [1]. Fecal contamination, often stemming from agricultural runoff, sewage leaks, or inadequate sanitation, introduces pathogenic microorganisms into drinking and recreational water supplies. Among these, coliform bacteria such as *Escherichia coli* serve as reliable sentinel organisms: their presence correlates strongly with fecal pollution and the potential co-occurrence of more dangerous pathogens like *Salmonella* species or *Vibrio* cholerae [2,3].

Conventional microbiological assays for coliform detection involve sample filtration or plating on selective agar media, followed by 24-48 hours of incubation and manual colony enumeration. Though well established, these workflows are time-consuming, labor-intensive, and require specialized laboratory facilities and trained personnel [46]. In remote or resource-limited settings, such constraints often delay critical interventions, sometimes by days, undermining efforts to prevent outbreaks and protect vulnerable communities [6]. Recent efforts to automate bacterial colony counting have explored deep learning approaches [79]. Despite their promise, existing approaches require large training datasets, rely on color-specific cues, or lack adaptability across diverse field conditions.

To address these limitations, our interdisciplinary team supported by the NSF ExpandAI program has developed an end-to-end, AI-powered framework for automated colony detection and classification on agar plates. Leveraging advances in computer vision and deep learning, our

system replaces manual preprocessing (previously performed in ImageJ [4] or EBImage [10]) with a YOLOv8 object detector [11] that rapidly localizes colonies. A second stage employs transfer-learned convolutional neural networks (CNNs) trained on a diverse 10-class dataset [12] to differentiate coliform species with high precision. By combining these two components into a cohesive pipeline, we achieve accurate and scalable analysis in seconds per plate for low-cost, field-deployable water quality monitoring and opening new avenues for interdisciplinary research in environmental health science.

2. Materials and Methods

2.1 Dataset Collection and Description

In this study, we leverage two complementary image collections to develop and evaluate our two-stage AI pipeline. The Source (Pretraining) Dataset comprises a publicly available repository of high-resolution agar-plate photographs spanning 24 bacterial species [12], from which we drew ten classes ($\approx$5,000 patches) to pretrain both our YOLOv8 detector and the initial convolutional backbone. In contrast, the Target (Fine-Tuning) Dataset consists of images we collected in-house at Auburn University at Montgomery (AUM) of four coliform species [13], which are *Citrobacter freundii*, *Enterobacter aerogenes*, *Escherichia coli*, and *Klebsiella pneumoniae*. Detection of these species is the target task that we picked for downstream fine-tuning, validation, and benchmarking of classification performance.

2.1.1 In-house Dataset (Target Dataset)

Our local dataset [13] was generated by cultivating four coliform species on tryptic soy agar (TSA) plates in the laboratory. Cell suspension of *Citrobacter freundii* (OD_{600} = 0.062), *Enterobacter aerogenes* (OD_{600} = 0.034), *Escherichia coli* (OD_{600} = 0.064) and *Klebsiella pneumoniae* (OD_{600} = 0.058) were serially diluted (10^{-1} to 10^{-9}) and plated on TSA plates. Cultures were incubated at 37°C for 48 hours. Once incubation was complete, photographs of discrete colonies on each agar plate were acquired using a modern smartphone camera. The use of a cellphone streamlined image acquisition and demonstrated the feasibility of low-cost, field-friendly data collection as an important consideration for potential deployment in resource-limited settings.

For our initial classification experiments, colony detection was performed manually in ImageJ. We annotated each of the four plate images to draw bounding boxes around individual colonies, then exported these regions as 185 discrete patches (approximately 40-50 patches per species). These manually cropped patches became the foundation of our early deep-learning trials, allowing us to benchmark simple CNN architectures against hand-crafted feature methods. By starting with a small but carefully labeled dataset, we could rapidly iterate on model design and preprocessing techniques without the overhead of large-scale annotation.

To further illustrate the robustness of our pipeline, we also prepared a mixed-coliform culture plate containing all four species on a single agar dish. This mixed plate served as a realistic test case: after applying our trained YOLO-based detector, the system successfully localized and then classified each colony patch via the transfer-learned CNN. The mixed-culture demonstration

highlighted the end-to-end capability of our approach to potentially handle heterogeneous samples, exactly the scenario water-quality monitors might face in the field.

Figure 1. Representative images from the target (fine-tuning) dataset, showing the four coliform species in panel order from upper left to lower right: *Citrobacter freundii* (upper left), *Enterobacter aerogenes* (upper right), *Escherichia coli* (lower left), and *Klebsiella pneumoniae* (lower right).

Figure 2. Three mixed-coliform agar plate samples from our in-house dataset, each containing colonies of *Citrobacter freundii* (Red), *Enterobacter aerogenes* (Green), *Escherichia coli* (Blue), and *Klebsiella pneumoniae* (Black). Bounding boxes overlaid on each plate indicate colony detections generated by the proposed YOLOv8 + CNN pipeline.

2.1.2 Public Dataset for Transfer Learning (Pretraining dataset)

The public dataset [12] we leveraged comprises 369 high-resolution images of bacterial cultures on solid media, with 56,865 colonies manually annotated via bounding boxes. Images were acquired under realistic lab conditions using three different smartphone models (LG Nexus 5X, iPhone 6, Huawei P30 Lite) and both black and white backgrounds to introduce variability in lighting and device optics. Expert bacteriologists curated and validated all annotations using COCO Annotator v0.11.1, and the dataset is distributed in multiple formats (COCO JSON, Pascal VOC XML, YOLO, CSV/TSV) to facilitate diverse training workflows [12].

From this broad collection of 24 species, we selected 10 taxonomically distinct classes: *Actinobacillus pleuropneumoniae, Bibersteinia trehalosi, Bordetella bronchiseptica, Brucella ovis, Erysipelothrix rhusiopathiae, Glaesserella parasuis, Listeria monocytogenes, Pasteurella multocida, Rhodococcus equi, and Staphylococcus aureus*. These classes used as the base task encourages our CNN's early layers to learn generalizable colony features rather than overfit to our four-species target set. Approximately 450 patches per class were extracted from the annotations, yielding ~4,500 training samples for base-model pretraining.

In our pipeline, we leveraged the public dataset in three complementary ways to maximize its impact on both detection and classification performance. First, we trained the YOLOv8 detector on 119 full-plate images drawn from the public collection, collapsing all annotated colonies into a single "colony" class. Regardless of species, by targeting any colony identically during this stage, the detector learned to generalize across a wide spectrum of colony shapes, sizes, and textures, and to produce tight bounding boxes under varying lighting and background conditions. This automated annotation step replaced the manual ImageJ workflow and formed the basis for patch extraction in downstream stages.

Second, we repurposed the detector's outputs to assemble a large, diverse training corpus for our base CNN. Every colony that YOLO localized was cropped, zero-padded, and resized to 100×100

px, yielding approximately 4,500 image patches spanning ten taxonomically distinct bacterial species. These patches served as the pretraining set for a CNN classifier, which was fine-tuned from ImageNet initialization. By learning generic colony features, rather than memorizing patterns specific to our four laboratory-cultured species, the CNN developed robust and transferrable representations that accelerated convergence. These robust features also raised validation accuracy during subsequent fine-tuning on our smaller, laboratory-collected dataset.

Finally, to demonstrate the broader applicability of our transfer-learning strategy, we conducted an additional validation using four further public classes (*Listeria monocytogenes*, *Pasteurella multocida*, *Salmonella enterica*, and *Staphylococcus hyicus*). Following the same pretrain-and-fine-tune workflow, the CNN pretrained on the original ten classes was readily adapted to these novel species, achieving comparable classification performance without architectural changes. This result underscores the versatility of our approach and its potential for rapid extension to new bacterial targets as more annotated data becomes available.

Figure 3. Sample images from the **Source (Pretraining) Dataset**, illustrating four of the pretraining classes: *Listeria monocytogenes*, *Pasteurella multocida*, *Salmonella enterica*, and *Staphylococcus hyicus*.

2.2 Proposed Method: Two-Stage Deep-Learning Pipeline

To automate and scale bacterial-colony analysis on agar plates, we designed a two-stage framework that first localizes colonies via object detection and then classifies each instance with a deep convolutional network. By chaining a YOLOv8 detector with a transfer-learned CNN, our pipeline replaces manual ImageJ annotation and handcrafted feature engineering with an end-to-end learning approach optimized for both speed and accuracy.

Figure 4. Two-column workflow illustrating the use of the Source (Pretraining) Dataset (left) and the Target (Fine-Tuning) Dataset (right). In the source domain, YOLOv8 is trained to detect colonies and a CNN is pretrained on ten public bacterial classes. These pretrained components are then transferred to the target domain, where YOLOv8 performs colony detection on in-house laboratory images and the CNN is fine-tuned on four local coliform species. The final model performs colony classification for downstream analysis.

2.2.1 Image Preparation and Preprocessing

Every agar-plate photograph, whether acquired in our in-house lab or drawn from public repositories, was converted to 8-bit grayscale [14]. This normalization step strips away variations in media coloration and lighting, channeling the detector's attention toward colony morphology, texture, and shape. Although our current implementation leverages grayscale imagery to demonstrate baseline performance, future iterations will integrate full-color inputs to exploit chromogenic media cues, and will incorporate sample metadata (e.g., source, incubation temperature, pH) via a parallel network branch to enrich context for downstream classification [15].

2.2.2 Stage 1 - Colony Detection with YOLO

In the first stage of our pipeline, we leverage YOLO-Nano [11], a lightweight variant of the You Only Look Once (YOLO) architecture optimized for resource-constrained environments, to automate colony localization. YOLO is a state-of-the-art, real-time object detection algorithm that simultaneously identifies and localizes objects within an image using a single convolutional neural

network. It divides the input image into a grid and, for each grid cell, predicts bounding boxes, confidence scores, and class probabilities. This architecture achieves high inference speed with competitive accuracy, making YOLO well suited for applications requiring real-time processing or limited computing resources.

In our study, we employed YOLOv8 [11] as the colony detector. It was trained on 119 plate images from the aforementioned pretraining dataset (see Figure 4) and evaluated on a held-out test set of 105 images. All annotated colonies regardless of species were collapsed into a single "colony" label, directing YOLO to focus exclusively on precise bounding-box placement rather than species discrimination. We opted not to retrain YOLO for colony classification, as doing so would require a large number of annotated examples for each species. Thus, we used YOLO strictly as a colony detector. YOLOv8's ability to accurately detect colonies allowed us to replace manual annotation tools such as ImageJ, significantly accelerating the preprocessing workflow for a scalable downstream classification.

Given the small size and high density of many colonies, each full-plate image was subdivided into overlapping tiles (both 640×640 px and $1{,}280 \times 1{,}280$ px grids with 100 px and 200 px overlaps). This tiling strategy ensures that colonies near tile borders retain sufficient context for reliable detection. When using overlapping tiles, it's common for the same colony to be detected multiple times near tile edges. A standard approach to address this redundancy is the use of Non-Maximum Suppression (NMS), a post-processing technique that filters overlapping predictions by retaining only the one with the highest confidence score based on the Intersection over Union (IoU) metric. Integrating NMS is especially useful in tiled object detection pipelines, as it can improve output clarity by consolidating redundant detections. While our current pipeline proceeds directly to classification using all predicted regions without applying NMS, this design choice does not substantially impact performance, as each detected patch is independently cropped, resized, and classified. Nonetheless, incorporating NMS in future iterations may help streamline detection outputs and reduce post-processing effort, particularly in densely populated regions or at tile boundaries.

Training was conducted on an AWS EC2 g5.xlarge instance equipped with an NVIDIA GPU. We optimized tile size and overlap parameters via grid search, using the Adam optimizer with standard YOLOv8 hyperparameters. After 50 epochs, the model generalized well to unseen data, achieving an mAP@50 of 87.6 % on a held-out set of 105 public images. The resulting detector automatically produces tight bounding boxes around each colony, which are subsequently cropped, zero-padded to preserve aspect ratio, and resized to 100×100 px for the classification stage.

2.2.3 Stage 2 - Colony Classification with CNN

To address the specific challenges of bacterial colony classification with a limited sample size, we designed a lightweight CNN architecture tailored to the morphological characteristics of microbial growth patterns. The model was pretrained on a domain-relevant public dataset of bacterial colonies, compensating for the lack of widely available pretrained models suited to this specific task. This pretraining improved feature generalization and accelerated convergence. Compared to standard architectures commonly used for large-scale natural image classification [16], our custom model offers a simpler structure that reduces overfitting risk and provides greater interpretability.

It also allows finer control over learned representations, aligning more closely with the visual distinctions relevant to colony classification. Once colonies had been localized, each cropped region entered a two-phase transfer learning [17] workflow. In the first phase, we trained a base CNN model on a curated 10-class subset of the public dataset. This model was designed to learn generalized visual features, such as shape, edge orientation, and texture, across a diverse set of bacterial colonies. To avoid task leakage and promote feature transferability, we intentionally excluded classes closely related to those in our target dataset.

As also shown in Figure 8 in detail, the base CNN architecture consists of three convolutional blocks. The first block applies a 2D convolution with 32 filters (3×3 kernel), followed by a 2×2 max pooling layer to reduce spatial dimensions. The second block uses 64 filters (3×3) and another 2×2 pooling layer to capture more complex patterns. The third block includes 128 filters (3×3) without additional pooling, enabling deeper feature extraction. These convolutional layers are followed by a global average pooling layer, a fully connected dense layer with 64 ReLU-activated units, and a softmax output layer with 10 units for classification during the pretraining phase.

In the second phase, we transferred the learned weights from the base model to a new classification head tailored for our target task. Specifically, we removed the original softmax layer, appended a new dense layer (64 units, ReLU), and added a final softmax output layer with 4 units corresponding to the bacterial species in the in-house dataset. This fine-tuning was performed using colony patches extracted from the in-house high-resolution plate images.

Figure 5. Representative samples from the ten base classes used for pretraining, arranged in a 10 × 5 grid (five patches per class). Each row corresponds to one species: sp02 *Actinobacillus pleuropneumoniae*, sp05 *Bibersteinia trehalosi*, sp06 *Bordetella bronchiseptica*, sp07 *Brucella ovis*, sp10 *Erysipelothrix rhusiopathiae*, sp12 *Glaesserella parasuis*, sp14 *Listeria monocytogenes*, sp16 *Pasteurella multocida*, sp19 *Rhodococcus equi*, and sp21 *Staphylococcus aureus*. The left panel shows original color crops and the right panel shows the corresponding 8-bit grayscale versions used by our models to focus on colony morphology and texture. Using the gray-level transformation helps reduce sensitivity to background color and lighting artifacts that do not carry biologically meaningful information.

Figure 6. Grid of sample patches for the four public-dataset classes used in fine-tuning, arranged in 4 rows (one per class: sp14 *Listeria monocytogenes*, sp16 *Pasteurella multocida*, sp20 *Salmonella enterica*, sp22 *Staphylococcus hyicus*) and 5 columns (five representative colonies). Each cell shows the original color crop on the left and the corresponding 8-bit grayscale version on the right.

Figure 7. Representative detections for the four coliform species in the in-house (Target) dataset. From left to right: *Escherichia coli, Citrobacter freundii, Enterobacter aerogenes*, and *Klebsiella pneumoniae*. As in Figures 5 and 6, each pair shows the original color image (left) and the 8-bit grayscale version (right).

Base Model

Modified Model

Figure 8. Transfer learning workflow for coliform classification. The base CNN architecture (left) consists of three convolutional blocks: Conv-1 applies 32 filters with a 3×3 kernel followed by 2×2 max pooling; Conv-2 applies 64 filters (3×3) with 2×2 pooling; and Conv-3 uses 128 filters (3×3) without pooling. These are followed by a global average pooling layer, a 64-unit dense layer with ReLU activation, and a 10-class softmax output. This model is pretrained on a subset of a public bacterial colony dataset to learn generalizable morphological features such as shape and

texture. For the target task, the learned convolutional layers are reused (frozen), and a new classification head with two 64-unit dense layers and a 4-class softmax output is fine-tuned using a dataset of in-house-collected coliform images. This two-stage transfer learning approach enables robust classification performance despite limited labeled data from the target domain.

2.2.4. Training Procedure and Transfer Learning Performance Evaluation

To initialize the network (i.e., to obtain the base CNN model shown in Figure 8), we adopted ImageNet-pretrained weights and "warmed up" the architecture by pretraining on ten taxonomically distinct classes drawn from the same 24-class public dataset (approximately 4,500 colony patches, 450 per class). We trained the model for 90 epochs using the Adam optimizer (learning rate = 1×10^{-4}), with early stopping based on validation loss. This base-training phase yielded a mean validation accuracy of 77% on a 10-class colony classification task, evaluated on 500 test patches corresponding to those classes, which demonstrates that the network learned generalizable morphological features such as colony shape and texture (see Figures 4 and 8 for a schematic overview of the detection process and the usage of the base-task for the transfer learning process).

In the second phase, the pretrained CNN was fine-tuned separately on two four-class classification tasks: (i) For our in-house dataset comprising *Citrobacter freundii*, *Enterobacter aerogenes*, *Escherichia coli*, and *Klebsiella pneumoniae*, and (ii) a different four-class subset of the public dataset comprising *Listeria monocytogenes*, *Pasteurella multocida*, *Salmonella enterica*, *Staphylococcus hyicus*. As shown in Figure 8, the fine-tuning was performed by appending a fully connected Dense layer (Dense-2) on top of a frozen base CNN, without modifying the underlying architecture. We used an 80/20 train/test split and applied standard data augmentations (random horizontal/vertical flips and small-angle rotations) for the training phase. Inference time per patch remained under five seconds on an EC2 instance, demonstrating that the proposed transfer learning framework offers both high accuracy and practical efficiency for potential use in scalable, field-deployable water-quality monitoring systems.

2.3 Traditional Feature Extraction (Baseline Comparison)

To establish a performance baseline, we implemented three well-known, handcrafted feature descriptors including Histogram of Oriented Gradients (HOG) [18], Local Binary Patterns (LBP) [19], and Haralick texture features [20] and paired each with two classical classifiers (Support Vector Machine [21] and Random Forest [22]). By comparing these pipelines against our deep-learning approach, we quantify the gains afforded by end-to-end feature learning.

First, each 100×100-pixel colony patch was converted to an 8-bit grayscale image, matching the inputs used by our CNN. We then computed:

- **HOG:** Initially applied using default settings, 9 orientation bins, cell size of 8×8 pixels, and block size of 2×2 cells. We also performed hyperparameter tuning, which yielded

optimal settings of: pixels_per_cell = (16, 16), cells_per_block = (2, 2), and orientations = 8.

- **LBP:** Used the default uniform Local Binary Pattern configuration with a radius of 1 pixel and 8 sampling points, producing 59-bin histograms. Varying the radius did not lead to improved performance.
- **Haralick:** Extracted 13 standard texture descriptors (e.g., contrast, correlation, energy, homogeneity) from gray-level co-occurrence matrices (GLCMs) computed at a distance of 1 pixel and angles of {0°, 45°, 90°, 135°}. Hyperparameter tuning did not yield performance gains.

All feature vectors were z-score standardized before classification. For each descriptor set, we trained:

- **Support Vector Machine (SVM):** with RBF kernel, cost parameter C and kernel width γ optimized via grid search over $\{10^{-2}, 10^{-1}, 1, 10\}$ with five-fold cross-validation.
- **Random Forest (RF):** For all handcrafted feature sets, classification was performed using a Random Forest with 100 trees. We tuned the maximum depth over the set {None, 10, 20}, and at each split, $\sqrt{p}$ features were randomly selected (where p is the number of input features).

3. Results

3.1 Colony Detection Accuracy with YOLOv8

We evaluated our YOLOv8-based colony detector on 105 held-out images drawn from the public dataset. The model achieved a precision of 0.906 and a recall of 0.827, corresponding to an mAP@50 of 0.877. When measured across the full IoU spectrum (mAP@50-95), the detector yielded 0.451, indicating robust localization under varying overlap thresholds. Compared to our initial ImageJ workflow that identified 185 colonies across the four in-house culture plates, the YOLO detector located 248 colonies on the same plates, demonstrating its ability to discover subtler instances that manual annotation missed. As before, we used an 80/20 train/test split, rounding the test set down to 49 examples rather than up to 50, in order to avoid overly round accuracy values and better reflect reporting granularity.

3.2 Improving Classification Accuracy with Transfer Learning

We evaluated classification performance under several regimes, starting with a manual workflow based on ImageJ. Using ImageJ-cropped "tight" bounding boxes from our four-class in-house dataset, a CNN trained from scratch achieved 73% accuracy. When trained instead on slightly larger, loosely cropped patches around each colony, accuracy improved to 83%, suggesting that overly tight crops may omit visual context important for robust classification.

Next, we incorporated transfer learning by pretraining the CNN on ten public colony classes and fine-tuning it on the in-house dataset, which further boosted accuracy to 94% (±3.6% over ten runs). However, this result may appear deceptively strong, as it was based on a manually curated subset; ImageJ failed to detect as many colonies as YOLOv8, missing a number of subtler or overlapping instances. Thus, the effective classification task involved fewer and more distinct examples. To address this limitation and improve scalability, we replaced the manual annotation step with automated colony detection using YOLOv8. This YOLO+CNN pipeline processes raw plate images end-to-end—without the need for ImageJ and enables consistent classification of all visible colonies, including small and densely clustered ones.

To assess the end-to-end pipeline (YOLO + CNN) on the in-house plates, we first used automatic cropping via our trained YOLO (Figure 4) and classification by the transfer-learned CNN (Figure 8). This proposed pipeline yielded an average accuracy of ≈ 86%, with the best-performing model achieving ≈ 92% on held-out in-house patches.

Finally, to assess generality (applicability of our method to other small datasets), we applied our pipeline to an independent four-class subset of the original 24-class public dataset. This subset comprised two classes from our initial ten (with different, randomly selected plate images) plus two novel classes drawn from the remaining 14, for a total of 17 agar-plate images. YOLO detected 1,791 colonies across those plates, and the CNN achieved 92% classification accuracy on the corresponding test split. Together, these results underscore the usefulness of transfer learning in accelerating convergence and substantially improving accuracy across both in-house and larger public-dataset tasks.

Tables 1 and 2 present a direct comparison of our traditional ML baselines and the proposed CNN pipeline, using a uniform header in each: Model, Mean Accuracy (%), Std Dev (%), Min Accuracy (%), and Max Accuracy (%), which are computed from 10 independent runs (using different train-test splits). Table 1 reports these classification statistics on the Target Dataset (in-house four coliform classes: *Citrobacter freundii, Enterobacter aerogenes, Escherichia coli, Klebsiella pneumoniae*). Table 2 shows analogous experiments on the 4 classes from the big public dataset: *Listeria monocytogenes, Pasteurella multocida, Salmonella enterica, Staphylococcus hyicus*). In both tables, entries labeled "Optimized" denote feature-classifier pipelines whose hyperparameters were exhaustively tuned with scikit-learn's GridSearchCV (cross-validating over SVM kernels and regularization strengths, Random Forest tree counts, etc.). All other rows correspond to default-parameter settings. Systematic tuning via GridSearchCV consistently produced higher test accuracies and tighter standard deviations of those accuracies across all the runs, which demonstrate improved validation performance and generalization over the out-of-the-box configurations.

Table 1. Experimental results on the target dataset (in-house dataset with 4-classes [13]), used for fine-tuning. The dataset includes four bacterial classes: *Citrobacter freundii, Enterobacter aerogenes, Escherichia coli, and Klebsiella pneumoniae.*

Model	Mean Accuracy (%)	Std Dev (%)	Min Accuracy (%)	Max Accuracy (%)
HOG + SVM	76.73	5.78	69.38	89.79
HOG + RF	73.26	6.48	63.26	87.75
HOG + SVM (optimized)	83.87	3.81	77.55	91.83
HOG + RF (optimized)	80.20	3.65	75.51	87.75
LBP + SVM	60.61	5.40	53.06	71.42
LBP + RF	66.53	5.71	57.14	75.51
Haralick + SVM	65.31	4.47	59.18	75.51
Haralick + RF	79.59	5.77	69.38	87.75
Proposed Method	85.91	4.12	79.59	91.83

As shown in Table 1, on our 4-class in-house data test split, the best baseline was HOG + SVM ($\approx 84\%$ accuracy), followed by HOG + RF ($\approx 80\%$) and Haralick + RF ($\approx 80\%$), all of which fell short of the $\approx 86\%$ achieved by our CNN fine-tuned with transfer learning. These results underscore the superiority of learned deep features over handcrafted descriptors for robust, high-throughput bacterial-colony classification. Similarly, as shown in Table 2, the proposed method remained among the top-performing approaches, with only a slight edge in accuracy observed for Haralick + RF, a non-transfer-learning baseline. The comparatively lower performance of Haralick + RF on the in-house dataset (Table 1) underscores the consistency and generalizability of our transfer learning approach.

Table 2. Classification results on a four-class subset of the public bacterial colony dataset [12], which also served as the pretraining base for transfer learning. The four bacterial classes are: *Listeria monocytogenes, Pasteurella multocida, Salmonella enterica, and Staphylococcus hyicus*.

Model	Mean Accuracy (%)	Std Dev (%)	Min Accuracy (%)	Max Accuracy (%)
HOG + SVM	87.10	2.15	84.12	91.92
HOG + RF	79.94	2.34	76.04	83.56
HOG + SVM (optimized)	89.80	1.85	87.46	93.87
HOG + RF (optimized)	74.26	2.46	71.30	78.27
LBP + SVM	79.13	2.93	74.65	85.51
LBP + RF	82.06	2.76	77.99	87.46
Haralick + SVM	54.12	1.88	51.81	57.93
Haralick + RF	92.81	1.33	90.52	94.70
Proposed Method	91.27	1.07	89.47	93.35

3.3 Evaluation of Classification Performance Across Datasets

To assess the discriminative power and generalization capability of our CNN-based classification pipeline, we examined confusion matrices derived from three distinct classification tasks: (i) the in-house 4-class dataset (sp01-sp04), (ii) a 4-class subset of the public dataset (sp14, sp16, sp20, sp22), and (iii) a challenging 10-class task using a diverse selection of public bacterial colony images (sp02-sp21). These visualizations offer fine-grained insights into class-wise accuracy and common patterns of misclassification.

Figure 9. Subplot A shows the confusion matrix for the in-house 4-class classification task (sp01-sp04). Subplot B shows the confusion matrix for the public 4-class dataset (sp14, sp16, sp20, sp22). Darker blue cells indicate more correct predictions, while lighter cells reflect fewer or misclassified instances. Axis labels represent true and predicted class codes.

Figure 9(A) illustrates the confusion matrix for the in-house dataset. The model demonstrates highly reliable classification, with perfect prediction for sp01 and sp04. Minor confusion occurs between sp02 and sp03, including two sp03 samples misclassified as sp02, likely due to overlapping colony morphology. Despite these modest misclassifications, the matrix is sharply diagonally dominant, indicating the model's strong ability to distinguish local coliform species even in a relatively small dataset. Moreover, Figure 9(B) presents the results on the public 4-class dataset. Performance remains high across all classes, with sp22 and sp14 achieving particularly strong accuracy. Limited confusion is observed between sp14 and sp16, possibly stemming from shared visual features such as shape or texture. The overall structure of the matrix supports the model's effectiveness in transferring learned features from the pretraining phase to unseen public data.

In addition, Figure 10 displays the confusion matrix for the 10-class public dataset, offering a more rigorous evaluation. Several classes, including sp07, sp10, and sp12, exhibit excellent separation with minimal off-diagonal entries. Conversely, more pronounced misclassification is observed among sp05, sp14, and sp16, where instances are frequently confused with one another, suggesting intra-class variability or inter-class similarity. Additionally, sp06 and sp19 show diffuse misclassification patterns, likely reflecting broader morphological diversity or a lack of uniquely distinguishing features. Even under this increased complexity, the model preserves coherent structure and maintains classification fidelity across most classes.

Overall, these results validate the robustness and adaptability of our deep learning framework. The model performs reliably across multiple datasets and classification granularities, consistently achieving high accuracy and demonstrating clear class boundaries in most cases. The confusion matrices further highlight the model's strengths and limitations, offering a foundation for future improvements through expanded training data, additional features, or ensemble-based strategies.

Figure 10. Confusion matrix for the public 10-class dataset (sp02, sp05, sp06, sp07, sp10, sp12, sp14, sp16, sp19, sp21). Darker blue cells indicate more correct predictions, while lighter cells reflect fewer or misclassified instances.

4. Discussion

Our AI-powered pipeline achieved dramatic reductions in analysis time, shortening colony detection and classification from hours of manual work to under five seconds per plate. Transfer learning was especially impactful: by "warming up" the CNN on a diverse, 10-class public dataset, we minimized the amount of in-house -specific data required to reach high accuracy. With the transfer learning approach, the proposed model accelerated model convergence and also mitigated overfitting on our limited in-house dataset. The decision to standardize on 8-bit grayscale imagery proved advantageous for generalization across different culture media and lighting conditions, focusing the detector and classifier on morphological cues rather than color variations.

Comparing our YOLOv8-based detection to the original ImageJ workflow underscores the strength of deep learning for localization: YOLO detected 248 colonies on the four in-house culture plates, which is 35% more than the 185 colonies annotated using the manual ImageJ process. This automation helps deliver end-to-end and real-time inference. Additionally, these gains reflect both YOLO's capacity to spot subtle, low-contrast colonies and its robustness to plate

artifacts. In the classification stage, deep features learned by our transfer-learned CNN consistently ranked among the top-performing methods. As an end-to-end neural network, it offers greater flexibility and generalizability that enables the integration of additional features such as color and contextual metadata. These advantages allow the CNN-based approach to outperform traditional pipelines built on handcrafted descriptors such as HOG, LBP, and Haralick.

In addition to advancing technical capabilities for microbial monitoring, this study presents a substantially reproducible, low-cost pipeline that combines wet-lab culturing, smartphone imaging, and deep learning for colony detection and classification. The data-collection and annotation workflows were intentionally designed for accessibility in educational and interdisciplinary research environments, enabling students and non-CS collaborators to contribute meaningfully without specialized equipment. This framework therefore supports both scalable field deployment and straightforward adoption in resource-limited settings.

5. Conclusions

Our pipeline demonstrated that combining YOLOv8 for object detection with a transfer-learned CNN can deliver accurate and rapid bacterial colony identification and classification, with potential application to water quality monitoring. By reducing processing time to under five seconds per plate and achieving up to 91% accuracy, the system is well suited for scalable and field-deployable applications. However, further fine tuning of the pipeline is needed to improve detection accuracy. To extend both the scientific reach and practical utility of our pipeline, we have identified the following complementary directions. First, we will move beyond monochrome imagery by using full-color plate photos and logging additional metadata such as pH, temperature, and media composition. Color channels will greatly reveal diagnostic pigmentation on chromogenic media, while metadata will let the network adjust its expectations to environmental factors. The dataset will be broadened to include additional bacterial species, rarer pathogens, and mixed-culture plates collected under diverse lighting conditions and with multiple camera types. We are prototyping a lightweight web and mobile app that lets users upload agar-plate photos, optionally enter metadata, and receive real-time colony detection and classification. This interface will bridge the gap between our research prototype and real-world use in remote or resource-limited settings. Finally, we will embed the entire workflow inside the NSF ExpandAI conversational tutor now in development. The chatbot will guide non-CS users through image acquisition, quality control, model training, and results interpretation. All tutorials, images, and annotations are available at [13].

CRediT authorship contribution statement

Shivaji Mallela: Writing -review & editing, Writing -- original draft, Software, Visualization, Validation; **Abria Gates**: Writing -review & editing, Writing -- original draft, Software; **Sutanu Bhattacharya**: Writing -review & editing, Writing -- original draft, Visualization, Validation, Funding acquisition; **Benedict Okeke**: Writing -review & editing, Writing -- original draft,

Visualization, Validation, Funding acquisition, Data curation; **Olcay Kursun**: Writing -review & editing, Writing -- original draft, Visualization, Validation, Supervision, Software, Resources, Project administration, Methodology, Investigation, Funding acquisition, Formal analysis, Data curation, Conceptualization.

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Acknowledgements

This work was supported by the NSF grant 2435093 and the NSF LSAMP Award # 1712692 - The Greater Alabama Black Belt Region (GABBR) LSAMP.

Data Availability

The public dataset used in this study is available at: https://doi.org/10.1038/s41597-023-02404-8. The complete in-house dataset and annotation guidelines are available on GitHub at https://github.com/ShivajiMallela/AUM_WaterQualityDataset_v1 and also from the authors upon request.

References

[1] Guidelines for drinking-water quality, 4th edition, incorporating the 1st addendum n.d. https://www.who.int/publications/i/item/9789241549950 (accessed June 27, 2025).

[2] Edberg S c., Rice E w., Karlin R j., Allen M j. Escherichia coli: the best biological drinking water indicator for public health protection. Journal of Applied Microbiology 2000;88:106S-116S. https://doi.org/10.1111/j.1365-2672.2000.tb05338.x.

[3] Oon Y-L, Oon Y-S, Ayaz M, Deng M, Li L, Song K. Waterborne pathogens detection technologies: advances, challenges, and future perspectives. Front Microbiol 2023;14. https://doi.org/10.3389/fmicb.2023.1286923.

[4] Schneider CA, Rasband WS, Eliceiri KW. NIH Image to ImageJ: 25 years of image analysis. Nat Methods 2012;9:6715. https://doi.org/10.1038/nmeth.2089.

[5] Method 1103.2: Escherichia coli (E. coli) in Water by Membrane Filtration Using membrane-Thermotolerant Escherichia coli Agar (mTEC) 2023.

[6] Feleni U, Morare R, Masunga GS, Magwaza N, Saasa V, Madito MJ, et al. Recent developments in waterborne pathogen detection technologies. Environ Monit Assess 2025;197:233. https://doi.org/10.1007/s10661-025-13644-z.

[7] Ferrari A, Lombardi S, Signoroni A. Bacterial colony counting with Convolutional Neural Networks in Digital Microbiology Imaging. Pattern Recognition 2017;61:62940. https://doi.org/10.1016/j.patcog.2016.07.016.

[8]   Chin SY, Dong J, Hasikin K, Ngui R, Lai KW, Yeoh PSQ, et al. Bacterial image analysis using multi-task deep learning approaches for clinical microscopy. PeerJ Comput Sci 2024;10:e2180. https://doi.org/10.7717/peerj-cs.2180.

[9]   Zieliński B, Plichta A, Misztal K, Spurek P, Brzychczy-Włoch M, Ochońska D. Deep learning approach to bacterial colony classification. PLOS ONE 2017;12:e0184554. https://doi.org/10.1371/journal.pone.0184554.

[10]   Pau G, Fuchs F, Sklyar O, Boutros M, Huber W. EBImage—an R package for image processing with applications to cellular phenotypes. Bioinformatics 2010;26:97981. https://doi.org/10.1093/bioinformatics/btq046.

[11]   GitHub - ultralytics/ultralytics: Ultralytics YOLO11 https://github.com/ultralytics/ultralytics (accessed June 27, 2025).

[12]   Makrai L, Fodróczy B, Nagy SÁ, Czeiszing P, Csabai I, Szita G, et al. Annotated dataset for deep-learning-based bacterial colony detection. Sci Data 2023;10:497. https://doi.org/10.1038/s41597-023-02404-8.

[13]   Mallela S. ShivajiMallela/AUM_WaterQualityDataset_v1 2025. GitHub repository: https://github.com/ShivajiMallela/AUM_WaterQualityDataset_v1 (accessed June 27, 2025).

[14]   Digital Image Processing n.d. https://www.pearson.com/en-us/subject-catalog/p/digital-image-processing/P200000003224/9780137848560?srsltid=AfmBOor0g_WpPcJtIwvCJRlHoP6oStxPd89bR63EUNeZuabXTizNL_b8 (accessed June 27, 2025).

[15]   Tøn A, Ahmed A, Imran AS, Ullah M, Azad RMA. Metadata augmented deep neural networks for wild animal classification. Ecological Informatics 2024;83:102805. https://doi.org/10.1016/j.ecoinf.2024.102805.

[16]   He K, Zhang X, Ren S, Sun J. Deep Residual Learning for Image Recognition. 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2016, p. 7708. https://doi.org/10.1109/CVPR.2016.90.

[17]   Pan SJ, Yang Q. A Survey on Transfer Learning. IEEE Transactions on Knowledge and Data Engineering 2010;22:134559. https://doi.org/10.1109/TKDE.2009.191.

[18]   Dalal N, Triggs B. Histograms of oriented gradients for human detection. 2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05), vol. 1, 2005, p. 88693 vol. 1. https://doi.org/10.1109/CVPR.2005.177.

[19]   Ojala T, Pietikainen M, Maenpaa T. Multiresolution gray-scale and rotation invariant texture classification with local binary patterns. IEEE Transactions on Pattern Analysis and Machine Intelligence 2002;24:97187. https://doi.org/10.1109/TPAMI.2002.1017623.

[20]   Haralick RM, Shanmugam K, Dinstein I. Textural Features for Image Classification. IEEE Transactions on Systems, Man, and Cybernetics 1973;SMC-3:61021. https://doi.org/10.1109/TSMC.1973.4309314.

[21]   Cortes C, Vapnik V. Support-Vector Networks. Mach Learn 1995;20:27397. https://doi.org/10.1023/A:1022627411411.

[22]   Breiman L. Random Forests. Machine Learning 2001;45:532. https://doi.org/10.1023/A:1010933404324.