GIVEN THE BIRDS, WHERE IS THE FLOCK?

Visual estimation of the location of collections of points

Keiji Ota[1,2,3,4]* Qihan Wu[5] Pascal Mamassian[6] Laurence T Maloney[3,4]

[1] Centre for Brain and Behaviour, Department of Psychology, Queen Mary University of London

[2] Institute of Cognitive Neuroscience, University College London

[3] Department of Psychology, New York University, New York, United States

[4] Center for Neural Science, New York University, New York, United States

[5] Department of Psychological and Brain Sciences, Johns Hopkins University

[6] Laboratoire des systèmes perceptifs, Département d'études cognitives, École normale supérieure, PSL University, CNRS, Paris, France

* Corresponding author

Keywords

Location estimation, Gestalt, perceptual organization, clustering, non-Gaussian distributions

Abstract

Many visual tasks resemble statistical judgments, estimating the center of a 'cloud' of identical items for example. In statistical form, the observer sees a sample drawn from an invisible probability density function (PDF) : the observer attempts to estimate the location of the PDF. He receives larger rewards for lower variance. Optimal minimum variance estimators are different for different distributions. We evaluated performance for three location families (Gaussian, Laplacian, and Uniform). How does human perceptual organization 'stack up' against optimal perceptual estimation? We found that observers adopted distinct estimators for distinct distribution families, each approximately minimizing variance for its family. To explain observers' ability to adapt to different distributional families, we propose that observers adopt a single estimator based on clusters in the sample. This Visual Cluster Model accounted for performance across distributions, suggesting that perceptual grouping first aggregates 'parts' into clusters and only then into a 'whole'.

[148 words]

Significance statement

Imagine a flock of birds. We can predict where additional birds might appear by estimating the probability density function (PDF) of the birds. We compared performance in estimating the location of PDFs drawn from Gaussian, Laplacian or Uniform location families, rewarding lower variance. The optimal estimators for the three families are different. Observers approximately minimized variance for each condition and used different estimators for different families. How could they do so? We propose that observers use a single estimator based on sample clusters: perceptual grouping first aggregates 'parts' into clusters and only then into a 'whole'.

[96 Words]

51
Introduction

The human visual system segments scenes into visual objects (Koffka, 1935/2013;

Wagemans, Elder, et al., 2012; Wagemans, Feldman, et al., 2012) adding visual structure

to what are initially only patterns of light across the retinas. Such 'wholes made of parts'

have their own spatial locations in 1D, 2D or 3D which the observer can be asked to

estimate. If the observer is asked, for example, to saccade to a 2D cloud of points, the

saccade can be interpreted as an estimate of the center of the cloud (McGowan et al.,

1998; Melcher & Kowler, 1999). *The first question is, how is this location estimate*

computed from the individual points? Birds in flight form a flock in 3D (Figure 1A) but

typically no one bird marks the center of the flock. There is no obvious answer to the

problem as posed.

We focus on a statistical version of the task where the 'parts' form a 1D sample

drawn from a 1D statistical distribution and – importantly – we can compare human

performance to normative. Different families of pdfs will serve as generators

Not every perceptual task can be modeled as a statistical task where 'parts' are a

sample drawn from a partially-known PDF, but considering such tasks allows us to use

powerful statistical tools in a special case.

Other Gestalt phenomena such as border ownership (D'Angelo et al., 2025), object

segmentation (Chen et al., 2025; Jeurissen et al., 2024; Papale et al., 2024) and shape

perception (Nielsen & Connor, 2024) and more are also part of 'middle vision' (Ullman,

1984), the stage in visual processing that follows encoding of initial visual information into

retinotopic areas and links local features to the items in the environment that generated

them (Groen et al., 2017; Peirce, 2015).

Terminology: The collection of points ('*parts*') form a *sample* drawn from a one-

dimensional *probability density function* (PDF), the *generator*. In Figure 1B, the red curves,

dashed and solid, are copies of the same PDF with the red, solid PDF being the PDF used

to generate the sample. They represent a *location family*, a collection of PDFs differing

only in location (e.g. Figure 1B). The colored dots are a 1D sample from the solid PDF.

The location estimation problem is a problem in parametric point estimation (Lehmann,

1998; Mood et al., 1974) as summarized in Figure 1C.

We address three questions: (1) *How does the observer estimate the location of*

the PDF given only the sample and knowledge of the location family which the PDF

belongs to? (2) How does changing the PDF ('generator') underlying the location family

affect the location estimation – if it has any effect at all? And (3) *How does human location*

estimation compare to uniform minimum variance unbiased estimation (UMVUE) for each

of the distributions we consider?

The three location families we consider are the Gaussian, the Laplacian and the

Uniform, illustrated below (Figure 2). A possible outcome is that the observer uses the

same estimator, possibly the Gaussian, for all three distributions. A second possibility is

that the observer uses different estimators for the different location distributions but at

least one of them is not the UMVUE of the corresponding distribution. A final possibility is

that the observer chooses estimators close to the UMVUE for each of three location

distributions, somehow adapting its estimation algorithm to the distribution (generator).

Figure 1: Estimating the Location of a Collection of Points. A. A Flock of Birds. A flock of birds in flight. **B. The one-dimensional Gaussian Location Task.** The dashed and solid red curves are examples of Gaussian probability density functions (PDFs) with unit variance for different values of the location parameter μ. All of the red curves together comprise a *Gaussian location family*. The solid red curve is the actual PDF from which the sample was drawn. The sample is composed of N positions and is plotted as red points along the horizontal axis. The observer sees only the sample $X_1, ... , X_N$ and is asked to estimate the value of the location parameter μ corresponding to the PDF that was used to generate the sample. **C. 1D Parametric Estimation.** The observer sees the individual points and knows that the points are a sample from a PDF in the Gaussian location family with unit variance. He estimates the unknown location of the generating PDF and knowledge of the PDF may influence his choice of estimator.

In the present study, we consider three different location-scale families of

probability density functions (PDFs). One of these families is the Gaussian PDF,

commonly used in visual modeling, notably cue combination models (Landy et al., 2007;

Oruç et al., 2003). A second motivation for using Gaussian distributions in modeling visual

judgments is that actual visual and motor error is close to Gaussian in a wide class of

everyday tasks (Ota et al., 2019; Tanae et al., 2021; Trommershauser et al., 2008).

Humans frequently encounter tasks involving Gaussian random variables and they may

tend to apply estimation rules and other statistical procedures that are appropriate when

distributions are Gaussian (Tassinari et al., 2006; Vilares et al., 2012). However, it is less

well known how humans behave when distributions are non-Gaussian (see (Maloney &

Thomas, 1991) for an exception).

Figure 1C summarizes what the observer in our experiment knows – the locations

of points and knowledge of the distributional family from which they are drawn but not the

precise PDF. *Parametric point estimation* methods (Lehmann, 1998; Mood et al., 1974)

allow us to compute optimal estimators for each PDF family based on criteria such as

minimum variance for a wide range of distributions.

If the PDF is Gaussian with fixed variance 1 and with unknown *location* parameter

μ, the PDF is

$$\phi_\mu(x) \;=\; \frac{1}{\sqrt{2\pi}} \; e^{-\frac{(x-\mu)^2}{2}} \;\;. \tag{1}$$

Several examples of PDFs from a *Gaussian location family* (Eq. 1) are plotted as dashed

red curves in Figure 1B. As μ is varied, the PDF moves left and right (hence the term

"location parameter"). The "true" PDF, the one from which the sample was actually drawn,

is plotted as a solid red curve.

Again, the observer's task is – given only the sample and the Gaussian constraint –

to estimate the unknown *location* μ of the true PDF. The estimator that the observer uses

is a function of the sample and may depend as well on the distributional assumption

(Figure 1C). The observer's estimate can be denoted $T_G^O(\ X_1,\ ...,\ X_n\ )$ or, if there is no

ambiguity, just T_G^O . "O" stands for the Observer, "G" for the Gaussian assumption.

While the observer has two sources of information (*distributional constraints* and

the *sample*) that inform their estimate $T_G^O(\ X_1,\ ...,\ X_n\ )$, it is usually the sample values that

take center stage, with the Gaussian assumption in the background. But what use – if any

– does the observer make of the distributional constraints? How are the parts combined to

estimate the location of the whole when the distribution generating the parts is not

Gaussian?

In Figure 2 we illustrate the Location Task for three choices of distributional family.

Figure 2A corresponds to the Gaussian case that we just discussed (Eq. 1). Figure 2B

illustrates a location task based on the Laplacian distribution[1], where the PDF is now

$$\varphi_\mu(x)\ =\ \frac{1}{2}e^{-|x-\mu|} \qquad . \qquad\qquad (2)$$

The PDF is symmetric around the unknown location parameter μ. The observer's task is

still to estimate μ. Finally, the Uniform Location Task is based on a uniform distribution

(Figure 2C),

---

[1] The actual PDFs used were always scaled to have the same variance. We present them in simplified form in Eqs. 2 and 3. See Methods.

154
$$\varphi_\mu(x) = 1 \qquad |x-\mu| < \frac{1}{2}$$
$$\varphi_\mu(x) = 0 \qquad |x-\mu| \geq \frac{1}{2}$$
. (3)

156
157
158 **Figure 2. Location Tasks. A. Gaussian Location Task. B. Laplacian Location Task. C.**
159 **Uniform Location Task.** Each plot shows a probability function and a sample, color coded.
160 The PDFs used in the experiment all had the same variance. See Methods and Materials.
161

We assessed human performance in the three location tasks for the distributions

shown in Figure 2. In our experiment, the observer familiarized himself with the

distributional families and the typical samples they generate. On every training trial, they

saw a sample drawn from a PDF. The color of the points identified the PDF location family

from which the PDF is drawn (as in Figure 2).

Uniformly Minimum Variance Unbiased Estimators (UMVUE). An estimator is any

function of the sample, $T(X_1, \dots, X_n)$ and, since an estimator is a function of random

variables, it is itself a random variable with its own expected value $E[T]$ and variance

$Var(T)$.

A common criterion for a "good" estimator is that it is *unbiased*, i.e. $E[T] = \mu$. A

second common criterion is that the estimator should have the lowest possible variance. If

an estimator satisfies both of these two criteria for all values of μ then it is a *Uniformly*

Minimum Variance Unbiased Estimator (UMVUE) or, less formally, the *minimum variance*

estimator. Cue combination models use UMVUEs and compare these with estimators

human observers adopt (Landy et al., 1995; Oruç et al., 2003; Trommershauser et al.,

2011).

We can compute a measure of the *efficiency* of any unbiased estimator **T** for a

task as the ratio of the variance of the UMVUE to that of the estimator. Since

$Var(T^{UMVUE}) \leq Var(T)$, the *efficiency* of *T*

$$H = Var(T^{UMVUE}) / Var(T) \tag{4}$$

is a value between 0 and 1.

L-Estimators. For convenience, we will focus on a set of estimators referred to as L-

estimators (Lehmann, 1998). They are defined as weighted combinations of order

statistics

$$T^w(X_1, ..., X_n) = w_1 X_{(1)} + ... + w_n X_{(n)} \tag{5}$$

where the sum of the weights is constrained to be 1. The order statistics (Mood et al.,

1974) are just the sample values renumbered from left to right. We can represent any L-

estimator by a plot of its weights (Figure 3).

The UMVUEs for the Three Location Tasks. Parametric estimation comprises a

collection of mathematical techniques that allow us to identify optimal estimators including

UMVUEs for different estimation problems with different distributional families (Lehmann,

1998; Mood et al., 1974). The unbiased estimator T^+ minimizing variance for the

Gaussian task illustrated in Figure 1A is just the arithmetic mean of the sample (Lehmann,

1998; Mood et al., 1974). It is repeated in Eq. 6, written in the form of an L-estimator

197
$$T^+ = T^+(X_1, \ldots X_n) = \sum_{i=1}^{n} X_i \Big/ n = \sum_{i=1}^{n} \frac{1}{n} X_{(i)} . \qquad (6)$$

This estimator is unbiased $E[T^+] = \mu$ and it minimizes the variance $E[(T^+ - \mu)^2]$.

Not every location task has an *UMVUE*. While the *UMVUE* for the Gaussian is the

sample *mean* (Eq. 6), the Laplacian has no closed-form solution for its *UMVUE*. We

computed the unbiased L-estimator that minimized variance by numerical methods

(exhaustive search) and plot it in Figure 3B, the *UMVUE* among L-estimators denoted

$UMVUE_L$. We use the term *UMVUE* to refer to either *UMVUE* or $UMVUE_L$ when it is clear

from context which is intended.

The *UMVUE* for the uniform family is

206
$$T^u(X_1, \ldots, X_n) = \frac{X_{(1)} + X_{(n)}}{2} , \qquad (7)$$

the average of the minimum and maximum values in the sample (the *average of extremes*).

We have three different *UMVUEs* each matched to the distribution family of a location

estimation task (Fig 3). Each is unbiased.

Previous studies on human vision have typically used the Gaussian location family

in modeling human performance. These studies have shown that human observers

accurately estimate the center of a 2D cloud of points and thus adopt the correct UMVUE

for a location estimation of a Gaussian distribution (Gan et al., 2023; Juni et al., 2010;

McGowan et al., 1998; Melcher & Kowler, 1999; Rashid & Chubb, 2022; Sun et al., 2016,

2018). However, the centroid is not the minimum variance estimator for the locations of

Laplacian and Uniform distributions. It has not been tested how a different location family

of a statistical distribution systematically influences human location estimation based on

the individual points.

We will investigate how the human visual system adapts its estimation rule

$T^O(X_1,...,X_n)$ to location tasks based on each of the distributional families in Figure 2 – if

it adapts it at all? Second, we will compare human performance to optimal unbiased

estimators minimizing variance (UMVUEs) for each of the three location families in Figure

2.

One possible outcome is that observers may simply adopt the same estimator for

all three location tasks, ignoring the distributional information. At the other extreme, the

observer might adopt the correct UMVUE estimator for each of the three tasks in Figure 3.

228
Figure 3: Uniformly Minimum Variance Unbiased Estimators (UMVUEs). A. Gaussian
Location Task. B. Laplacian Location Task. The *UMVUE$_L$* L-estimator estimated
numerically (the Laplacian has no *UMVUE*). **C. Uniform Location Task.** Three UMVUE
estimators are represented as L-estimators of weighted average of order statistics. The Y-
axis denotes weights (i.e., regression coefficients) on each sample point ordered from left
to right. UMVUE estimator for the Gaussian location task is the arithmetic mean of the
sample. The UMVUE for the Laplacian location task has the largest weight on the median.
The UMVUE for the Uniform location task is the average of extremes.
237
238
Influence. We can interpret the weights in an L-estimator as measures of the *influence* of

each point (each order statistic), a useful characterization of a statistical task (Juni et al.,

2010; Maloney & Landy, 1989; Ota & Maloney, 2024) that is important for research in

robust statistical estimation (Hampel et al., 1986; Huber, 1981).

In our experiment, we are presenting an observer with a sample whose order

statistics — left to right − are $X_{(1)}, \ldots X_{(i)}, \ldots, X_{(n)}$ and recording the observer's

response $T^O(X_{(1)}, \ldots X_{(i)}, \ldots, X_{(n)})$, the location estimate. The influence of the point at

position *i* on the location estimate is the partial derivative

$$I_i = \frac{dT^O}{dX_i} \qquad . \qquad\qquad (8)$$

which allows us to measure the contribution of each point to the overall estimate. If the

location estimator is an L-estimator, then the influence estimates are just the weights in Eq.

(5). We compare the normative influence measures for each task (Figure 3) with the

observed influence measures computed by linear regression.

To summarize, in this article we first examine how observers combine locations of

individual points to estimate the location of the generating PDF, an exemplary parametric

estimation problem in visual form. We then propose a model of human performance, the

Visual Cluster Model (VCM) of location estimation. We test the VCM model against

alternatives.

Results

The observers were first familiarized with the three distributional families (Gaussian,

Laplacian, and Uniform) by viewing the typical samples generated for different sample

sizes (Supplementary Figure1A; see Methods and Materials). In the main experiment

observers were presented with samples of 9 points drawn from one of the three

distributional families and asked to estimate the position of the center of the generating

PDF given only 9 sample points and the knowledge of which distribution family had

generated the sample. They were given feedback concerning their visual estimate

(Supplementary Figure1B). We confirmed that behavioral performance did not

systematically change across trials (Supplementary Figure 2AB).

We know the UMVUE weights (influences) for each task (Figure 3) and we can

estimate the observers' weights by linear regression (see Methods and Materials). Figure

4 (and Supplementary Figure 3A) illustrates the estimated weights for each participant and

the average across participants. Observers were sensitive to the distributional constraints.

Observers' influence measure markedly changed with changes in distributional family

(interaction between the order of points and the distributional families by ANOVA on the

estimated weights: $F[16, 304] = 44.53$, $p < 0.0001$, partial $\eta^2 = 0.701$).

278
Figure 4: Observers' Estimated Influence Measures Compared to UMVUE Influence
Measures. A. Gaussian Location Task. B. Laplacian Location Task. C. Uniform
Location Task. Influence (i.e. regression coefficients) of each point in samples (ordered
from left to right) on observer's visual estimates. Results for each observer are plotted as
faint grey lines. Mean results across observers are plotted as color-coded squares. Error
bar denotes 99.7% confidence interval (± 3 SEM). Weights employed by UMVUE are
taken from Figure 3 and replotted as dashed lines. For the Laplacian distribution,
observers' estimated influence measures are not significantly different from the $UMVUE_L$.
The observers' influence measures for the other two distributions deviate from those of
their respective UMVUEs.
289

Do observers' choice of estimators approximate the UMVUEs for each location

task? We compared measured influence with normative (UMVUE or $UMVUE_L$) influence

for each location task separately. For the Gaussian task, the normative estimator is just

the arithmetic mean of the sample. In contrast, the observer's estimated influences look w-

shaped and are significantly different from the normative influences (F [8, 152] = 19.56, $p <$

0.0001, partial η^2 = 0.507) by particularly placing larger weights on the median sample

point than UMVUE (Supplementary Figure 3B), meaning that observers do something

other than averaging points.

For the Uniform task, the measured influences are also different from normative

influences (F [8, 152] = 35.27, $p < 0.0001$, partial η^2 = 0.650). Even though observers gave

most weight to the extreme sample points, they placed significantly less weight on them

than the UMVUE (Supplementary Figure 3B). For the Laplacian task, observers

approximated the UMVUE (F [8, 152] = 1.83, p = 0.076, partial η^2 = 0.088). We note that

there were no significant changes in the measured influences from the beginning to the

end of the experiment (Supplementary Figure 2C). The efficiency of the observers'

estimators (Eq. 4) was overall 69.6% (Supplementary Figure 4). In other words, the

observers were 1.44 times more variable than the UMVUE. There was no significant

difference across the three location tasks (the main effect of the distributional families by

ANOVA on the efficiency: F [2, 38] = 2.53, p = 0.093, partial η^2 = 0.118).

In summary, the observers are sensitive to the distributional constraints in the three

location tasks – choosing significantly different estimators for the three location tasks. The

observers' estimators did not differ significantly from the UMVUE$_L$ for the Laplacian

location task and roughly approximated the UMVUE for the Uniform location task.

The Visual Cluster Model (VCM)

The observers used different estimators for the three location families. *Here, we considered the possibility that the visual system's choice of estimator is based entirely on the cluster structure of the samples (Sun et al., 2019).* Intuitively, clusters convey information about the PDFs from which they are drawn. A cluster confined to an interval [a,b] will tend to have more points when the probability density across the interval is larger. We first illustrate the computation with an example.

In Figure 5A we plot a 9-point sample and in Figure 5B we partition the sample into $K = 5$ non-overlapping clusters denoted left to right as $C_1, C_2, \ldots, C_5$ using a standard clustering algorithm described below. Clusters in our experiment have a minimum size of 1 element, and a maximum size of 9 (in which case, there is only one cluster). We assign a location c_j to the j^{th} cluster C_j, the midpoint of the endpoints of the cluster.

In our example, the largest cluster, C_4 contains three points. If we had to base our estimate of location on just one of the clusters in the cluster structure of the sample, it would plausibly be the 4th cluster. But there are competing clusters with either 1 or 2 points, and we can attempt to improve our estimator by weighting together the locations of the clusters with weights that depend on the clusters.

333
334
Figure 5: Visual Cluster Model. A. Gaussian Location task. A sample of 9 points is
drawn from a Gaussian distribution. Observers were asked to estimate the location of the
invisible center of the underlying distribution given only sample points. **B. Partition.** Visual
cluster model partition points (partitions shown as dashed vertical lines) into K clusters of
the sample, $C_1,...,C_K$. Each cluster is assigned a location $c_1,...,c_K$ defined as the average
of its largest and smallest points if the cluster contains more than one point. Otherwise, the
location of the single point is the location of the cluster. **C. Global Agreement.** Visual
cluster model assigns the log likelihood λ_j of the center μ of the PDF to the location c_j of
the j^{th} cluster. A dashed curve represents the log likelihood values across the entire space
of the task. The log likelihood values $\lambda_1,...,\lambda_K$ are converted to the relative weights
$w_1,...,w_K$ via a softmax transformation. The visual cluster model estimates the position of
the center of the PDF as a weighted average of cluster locations $c_1,...,c_K$ with weights
$w_1,...,w_K$.
348
349

We considered variations on the model at each step but – to simplify the

presentation of the model – we first describe one version of the model and discuss

possible variations only after presentation of this base version of the model. One goal of

the model is to reduce the complexity of the computation (Lieder & Griffiths, 2019) by

relying on the cluster structure of the model (five clusters in our example) (Sun et al.,

2019) rather than the nine points.

Step 1: Partition. The visual system partitions points in the sample into a small set of non-

overlapping clusters. In Figures 5A and 5B, we apply a standard clustering algorithm, K-

means clustering (Hartigan & Wong, 1979), to a sample $X_1, \dots , X_N$ from the Gaussian

distribution (Eq. 1). The K-means clustering algorithm has a free parameter K (the number

of clusters). In Figure 5B, we obtained $K = 5$. The result is a partition into non-overlapping

clusters $C_1, \dots, C_K$ numbered from left to right, possibly varying in number of points. We

assign a location to each cluster $c_1, \dots, c_K$ as the average of its largest and smallest points

(average of extremes) if the cluster contains more than one point, otherwise the location of

the single point if the cluster contains only one. The first step is analogous to the cluster-

of-samples representation developed by Sun et al. (2019). We extend their model by

introducing *global agreement*.

Step 2: Global agreement. How well does each cluster C_j at location c_j capture not just

the points in its own cluster but rather the entire sample of points $X_1, \dots , X_N$? We

hypothesize that observers make use of the distributional constraint to assess the

likelihood of the location of the distribution generating the points. In Figure 5C, for each

cluster, we compute the log likelihood λ_j of the location parameter μ of the population

PDF with respect to the location c_j of the j^{th} cluster:

374
$$\lambda_j = \sum_{i=1}^{9} \log f_\mu(X_i \mid \mu = c_j) \qquad .$$
(8)

where f_μ is the likelihood function of the distribution chosen to generate the sample points,

with unit variance. This step results in a measure of the likelihood that the location c_j of

cluster j reflects the center of the distribution, taking into account all the points of the entire

sample. Therefore, we refer to it as *global agreement*. A dashed curve in Figure 5C shows

the log likelihood computed across the entire space of the task. In the Gaussian location

task, finding the location of the maximum log likelihood value will correspond to averaging

sample points. Instead of the performing the log likelihood computation over the entire

space, we reduced the complexity of computation (Lieder & Griffiths, 2019) by computing

the log likelihood value with respect to the locations c_j of the j^{th} clusters.

We use a softmax transformation with one parameter $\boldsymbol{\beta}$, i.e., known as inverse

temperature (Reverdy & Leonard, 2016) to convert the log likelihood λ_j to weights

386
$$w_j = \frac{\exp(\beta\lambda_j)}{\sum_{j=1}^{K} \exp(\beta\lambda_j)}$$
(9)

The parameter $\boldsymbol{\beta}$ is a free parameter used to scale measures of global agreement. When

$\boldsymbol{\beta}$ is fixed at 0, the relative weights w_j are all 1/K: all clusters get equal weight. When $\boldsymbol{\beta}$

increases, clusters having a large log-likelihood value gets relatively larger weights relative

to those with smaller log-likelihood values. In the limit as $\boldsymbol{\beta}$ grows, the weight of the cluster

with the largest log-likelihood converges to 1 while the other weights drop to 0.

On any given trial, the visual system's estimate of the position of the center of the

distribution is modelled as the weighted mean of the locations of the clusters with softmax

weights that depend on the log-likelihoods assigned to clusters (Figure 5C)

395
$$T^{VCM} = \sum_{j=1}^{K} w_j c_j + b \qquad . \tag{10}$$

A bias term b is added to account for the small but constant bias that we found in the

participants' visual estimates (on average, 2.07 mm, SD = 1.41 mm), possibly a visuo-

motor error.

The weight on each cluster is determined by the value of the measure of global

agreement (i.e., how accurately the center of the distribution is approximated) relative to

the measures of global agreement in other clusters.

Factorial model comparison. We test two levels of the grouping parameter K. At the first

level, we will fix K at 9. At the second level, the grouping parameter K will be treated as a

free parameter and estimated separately from the data in each location task (maximum

likelihood). Given that samples from the three possible distributions are color-coded, the

observer can select different values K_G, K_L, K_U of the grouping parameter K for the

three different distributional families.

For global agreement (β) we test three levels in the factorial design. At the first

level, we will fix β at 0 so all clusters get equal weights. At the second level, the parameter

β will be treated as a free parameter constrained to be the same value across the three

distributional families. Last, at the third level, we will fix it at 1. By this constraint, global

agreement is applied to the model fit but the β value is not informed from each observer's

data.

We built six models by combining two levels of partition and three levels of global

agreement and compare the models by a factorial model comparison (van den Berg et al.,

2014; Zhang et al., 2020). Figure 6A shows the summed AICc score across participants

for the six models. The two-stage visual cluster model (partition and global agreement)

outperformed the other five variants of the model. A group-level Bayesian model selection

(Rigoux et al., 2014; Stephan et al., 2009) showed that the protected exceedance

probability of the two-stage VCM, i.e. the probability for the model to outperform all the

other models was 99.9%. This model was also better than the normative model where

UMVUE was fitted to the observer's data. Furthermore, the three models based on

partitioning points (K_G, K_L, K_U estimated from the data) outperformed the other three

models without partitioning (*K* fixed at 9; the protected exceedance probability = 99.8%). A

model where partitioning was applied while global agreement was partially applied ($\boldsymbol{\beta}$ fixed

at 1) outperformed a model where partitioning was applied but global agreement was not

($\boldsymbol{\beta}$ fixed at 0), though the $\boldsymbol{\beta}$ value was not fitted to the data in these two models (the

protected exceedance probability = 87.1%). *These results support the claim that both*

partitioning and global agreement are essential computations that underpin the observers'

visual judgments.

432
Figure 6: Visual Cluster Model Compared to Human Performance. A. Factorial model comparison. We built six models by combining two levels of partitioning (Step 1) and three levels of global agreement (Step 2). The y-axis denotes the AICc score summed across participants. The lower the AICc, the better the model. A dashed red line plots the AICc score for the normative UMVUE. A grouping parameter *K* is the cluster size in K-means clustering we used to fit to the data. A parameter β is inverse temperature in the softmax transformation which converts the log likelihood values to the relative weights (Figure 5). **B. Prediction of the Estimated Weights (Influence).** Regression weights estimated from the data are taken from Figure 4 and replotted as colored squares. The model prediction of the estimated weights for each location task was estimated using a linear regression on the visual estimates recovered from the best Visual Cluster Model (Partition applied × Global agreement applied). The prediction of the estimated weights was averaged across observers for each task and was plotted as a black solid line. Shaded gray area denotes 99.7% confidence interval (± 3 SEM).

We estimated the influence of each point in the sample on the visual estimates

generated by the two-stage VCM. The prediction of the influence measure by the model

captured human data well in all three distributional families (Figure 6B). Specifically, the

model produced a w-shaped influence pattern in the Gaussian task, a median-biased

influence in the Laplacian task, and the average of extremes in the Uniform task. It is

remarkable that a single model can generate such different estimators each tailored to a

distribution family.

Patterns of predicted influence by other variants of the model are summarized in

Supplementary Figure 5. When we applied the global agreement partially (β fixed at 1)

and had grouping parameters free, the model still produced distinct patterns of measured

influence in the three location tasks (Supplementary Figure 5F), suggesting that we are not

overfitting the data by including the global agreement parameter. However, without

applying global agreement (β fixed at 0), we failed to properly fit the data (Supplementary

Figure 5A&D). The models without partition (K fixed at 9) also failed to fit the data

(Supplementary Figure 5A-C). These results again demonstrate that both partitioning and

global agreement are essential computations.

Finally, we tested whether our results depend on the choice of the clustering

algorithm. We repeated the model fit using a hierarchical clustering with single linkage

algorithm (Nielsen, 2016; Shetty & Singh, 2021) and found that the results were almost

identical (Supplementary Figure 6).

468
469

Discussion

A central task of visual perceptual organization is to model how the visual system

combines 'parts' into 'wholes' (Groen et al., 2017; Peirce, 2015; Ullman, 1984; Ullman et

al., 2002). When parts have spatial attributes such as location, how does the visual system

combine the locations of the parts into an estimate of the location of the whole? We

considered a statistical version of this problem modeled on parametric point estimation

(Lehmann, 1998). We asked observers to estimate the center of the PDFs of three

different location families of one-dimensional PDFs. Observers knew everything about the

PDF except for its location parameter which they were asked to estimate. In instructing the

observers, we used the neutral term 'center' to refer to what was in fact the mean, median,

and axis of symmetry of the PDF. The task is a paradigmatic statistical task: given a

sample, estimate the parameters of the PDF that generated it. It is also a part of

perceptual organization.

We compare human performance to that of a Uniformly Minimum Variance

Unbiased Estimator (UMVUE) for that distribution. The UMVUE for each distribution is

unbiased and has the lowest possible variance among location estimators. The normative

minimum variance estimator is markedly different for the different distributional families we

considered, namely the Gaussian, the Laplacian, and the Uniform.

How does the observer carry out the task? For the Gaussian location family, for

example, the statistician needs only compute the mean of the sample. The resulting

estimate is the UMVUE but, as we have seen this is not what human observers do. We

sought an alternative computation that would reproduce what human observers do, and

that could be applied to estimation problems for the non-Gaussian distributions as well.

We propose that the visual system bases its estimates on the clusters in the sample and

integrates the locations of the clusters, weighting them by how well each cluster alone

accounts for the observed sample.

Using influence measures, we tested whether observers adopt the same estimator for the three different distributions. We found that observers used different location estimators for the three distributions. We also tested whether the estimator for each distribution was the UMVUE for that distribution. The observers' rules were different from UMVUE for Gaussian and Uniform location tasks but we could not reject the hypothesis that observers used the UMVUE in the Laplacian location task.

In the Gaussian location task, observers exhibit a systematic bias that deviate from equal weighting of each sample point, demonstrating a w-shaped influence pattern – placing large weights on the median and the two extreme points. This result is counterintuitive because it suggests that observers are not simply averaging visual elements, despite averaging being an elementary statistical operation that they are presumably familiar with. Deviations from equal weighting in the Gaussian location task have also been confirmed in previous studies, which show that observer's estimates are biased by outliers in a sample (Juni et al., 2010; Moreland & Boynton, 2017; Rashid & Chubb, 2021). However, the influence patterns were flexibly adapted to the distributional constraints. In the Uniform location task, the two extreme sample points exerted strong influence on the observer's estimates, while their influences were minimal in the Laplacian. Intuitively, the extreme points, if these are drawn from the Laplacian distribution, are poor indicators of the location of Laplacian distribution. If observers were estimating the likelihood of the location of the distribution, the influence of these extreme points would be expected to be small in the Laplacian location task.

It is implausible that the human visual system has different rules of location

estimation for any choice of location family. We wondered whether a common estimation

algorithm, ideally based on Gestalt structure, could account for how the visual system

assigns locations to samples from arbitrary location families.

We developed a two-stage Visual Cluster Model (VCM). Our model comparison

analysis validated the two stages on the VCM. The first partition stage edits individual

visual points so that points can be grouped into a cluster which itself defines a location. At

the second stage (global agreement), the VCM evaluates how likely each cluster

approximates the location of the distribution generating the points. A cluster with a high

likelihood value is weighted more in the visual judgment than a cluster with a low likelihood

value.

The VCM then combines the cluster locations using weights that are proportional to

the likelihood values assigned to clusters. The distributional constraints provided

information that was necessary to estimate the likelihood of the location parameter of the

distribution (Eq. 8). We demonstrated that a two-stage VCM simultaneously accounts for

distinct patterns of the observer's visual judgments across all the three location tasks. We

note that the VCM is not an L-estimator as the location estimator by the VCM is not the

weighted sum of the order statistics of a sample. However, the VCM produces good

approximations of observers' estimators and therefore provides a descriptive account for

how their location estimations were produced.

Sun et al (2019) also used a clustering algorithm to model the representation of

human visual experience. In their task, observers were asked to estimate the location of

the empirical mean or mode of the sample of 70 visual points, and points were drawn from

a mixture of distributions that had three different peaks. The nature of their stimuli likely

enhanced the visual segmentation of points beneath each peak, making clusters more

salient. In contrast, the cluster structure in our task may be visually less salient, as we

generated just 9 points from a unimodal (Gaussian, Laplacian, or Uniform) distribution.

Nevertheless, models without the partition stage did not explain the data well.

Gestalt psychologists (Koffka, 1935/2013; Wagemans, Elder, et al., 2012;

Wagemans, Feldman, et al., 2012) identified Gestalt rules underlying perceptual

organization (for review see (Kubovy & Gepshtein, 2003)). Visual objects are grouped

together based on a similarity of spatial attributes and these new *Gestalten* are assigned

attributes including locations in space. The theory is descriptive and provides no clear

justification for why Gestalten such as clusters are part of our visual experience (Jakel et

al., 2016). The VCM offers two possible reasons for this.

First, the visual system can reduce the amount of information that must be

processed by aggregating parts (Stigler, 2016).   This becomes progressively

advantageous as the number of visual elements increases. It is not simply the clusters that

are useful but the fact that there can be many fewer clusters than sample points. Second,

a cluster of points triggers useful information for visual judgments beyond just spatial

attributes. In the VCM, each cluster is assigned its own location, which serves as an

anchor where the likelihood of the center of the generating PDF is evaluated. By

combining these two advantages, the VCM reduces the number of computations required

to carry out the task, analogous to the resource rational principle in perception, cognition

and decision-making (Lieder & Griffiths, 2019). For instance, in Figure 5C, the likelihood of

the location of the PDF underlying the sample points is evaluated only at five cluster

locations. Nevertheless, it approximates the maximum likelihood estimation as if we

applied a low-pass filter at the limited sampling points. The resulting estimated likelihood

function is not perfectly accurate. To compensate for this, the VCM computes a weighted

average of these sampling points based on their estimated likelihoods. In this sense,

Gestalten are not just fascinating visual illusions but may also correspond to intermediate

steps in optimal computations.

In Marr's framework of three levels of analysis (computational, algorithmic, or

implementational) (Marr, 1982), the VCM exists on the computational level, concerning

how the visual system assigns a location to a 'whole' composed of 'parts' and what

objective is optimized in perceptual organization. The goal of the VCM can be interpreted

as balancing task accuracy with minimizing computational costs such as time (Griffiths et

al., 2015). The resource rational principle is considered a variant of Bayesian inference,

which posits that the visual system aims to identify the most plausible interpretation of the

structure of the image given its constituent visual elements (Froyen et al., 2015; Gershman

et al., 2016; Shivkumar et al., 2025).

How the VCM is implemented algorithmically or biologically is a separate question.

In particular, we implemented the first partition stage using two standard clustering

algorithms, a centroid-based K-means clustering (Hartigan & Wong, 1979) and a

connectivity-based hierarchical clustering (Nielsen, 2016; Shetty & Singh, 2021). We found

that both algorithms reproduced behavioral patterns equally well. It should be noted that

recent work has successfully modeled human perceptual experience from a clustering

perspective in tasks such as auditory streaming (Larigaldie et al., 2025), motion perception

(Gershman et al., 2016; Shivkumar et al., 2025), and the representation of uncertainty

(Sun et al., 2019). These studies employed a stochastic clustering approach called the

Chinese restaurant process, assuming that perceptual noise leads to variability in cluster

size. Such an approach may produce similar behavioral consequences as the clustering

algorithms we used.

In conclusion, we addressed a central question in perceptual organization

concerning how the 'whole' and its attributes are estimated from the attributes of individual

'parts'. We formalized a statistical version of this problem by presenting observers with

samples of points ('parts') drawn from three probability density functions (Gaussian,

Laplacian, and Uniform) and asking them to estimate the location of the center of the PDF

('whole'). We demonstrated that the observer's visual judgments can be explained by a

two-stage computational process: partition and global agreement. These results suggest

that the observer's estimate of the location of the 'whole' is based not directly on the local

locations of the 'parts' but rather on the locations of 'clusters' they form. As such our

findings imply that to further understand how the human visual system estimates the

location of the 'whole', it is necessary to consider both the perceptual process which

structures the groups based on 'parts' and the probabilistic structure (i.e., probability

density function) that generates local locations of the 'parts'.

Methods and Materials

Participants

Twenty participants (mean age 22.9, range 18–29, 13 females, 7 males, 0 other)

participated in the experiment. This study was approved by the University Committee on

Activities Involving Human Subjects of New York University (IRB-FY2019-3450) and

carried out in accordance with its approved guidelines. Informed consent was given by

each participant before the experiment. None of the participants was aware of the

hypotheses under test in the experiment. Participants knew that they would receive $12

per hour plus a performance-related bonus (average bonus: $16.90, range: $11–$24). The

experiment took approximately 2 hours.

Apparatus

Stimuli were displayed on a horizontal monitor (VPIXX, VIEWPIXX, 514 mm × 288 mm).

The monitor resolution was 1920 × 1080 pixels with a 60-Hz refresh rate and we refer to

location on the monitor by horizontal coordinates ranging from -257 mm to 257 mm and

vertical coordinates -144 mm to 144 mm. The participants were seated at a viewing

distance of approximately 43 cm and manipulated a computer mouse to carry out tasks. All

stimuli were presented and controlled using the Matlab Psychophysics Toolbox (Brainard,

1997; Pelli, 1997).

Training Task

Participants were first familiarized with the three distributional families: Gaussian,

Laplacian, and Uniform (see Supplementary Figure 1A). In this training stage, participants

were not yet asked to make any estimates but were asked to observe the population PDFs,

the population means, and the samples drawn from these population distributions. On

each trial, we plotted a PDF drawn from one of the three distributional families and a

sample from the same PDF. The origin (0,0) was set at the vertical and horizontal center of

the screen. The location μ of the PDF was drawn uniformly from the interval -100 mm and

100 mm. Following this, a sample of N points was randomly drawn. The sample points

were displayed underneath the shape of the PDF. The points were discs with a radius of

1.5 mm and colored by the same color that was used to draw the underlying PDF (for

instance, red Gaussian; green Laplacian; blue Uniform). The color codes were counter-

balanced across participants.

The population variances σ^2 of all PDFs was fixed at 2500 mm^2 (σ = 50 mm). We

added vertical jitter to the vertical positions of the sample points to reduce the chance that

sample points would occlude one another. The variance of vertical jitter was fixed at 6.25

mm^2. To aid the observer in interpreting the PDF and sample during training, we marked

the location μ of the PDF by a white solid line segment and dashed lines (width: 2 mm,

height: 35 mm).

During training, the sample size N was initially 300 and was gradually reduced to

50, 20 and finally 9. With 300 points the displayed sample could be readily matched to the

PDF from which it was drawn.

Presentation of the sample when N > 9 was extended across time: 18 additional

points were drawn every 100 ms from the underlying PDF until the required number of

points (300, 50, 20, or 9) points appeared on the screen. The sample points were

displayed for 2s. After an inter-trial interval of 1s, a new PDF with randomly chosen

location μ was displayed together with a sample drawn from the PDF.

A distribution was chosen from one of the three distributional families (Gaussian,

Laplacian, and Uniform) and was repeated for five trials. In each trial, a new sample was

generated from the distribution chosen. After the presentation of 300 sample points in

groups of 15 = 5 x 3, the second block of 50 sample points started. The third block and the

fourth block used 20 and 9 points, respectively, giving 60 trials in total. The final sample

size ($N = 9$) was the one used in the main experimental task, the location task. The training

task provided substantial opportunity to observe typical Gaussian, Laplacian, and Uniform

samples while learning the color codes.

In the instructions, we used the following analogy:
660
661   On every trial, you will first see a white apple tree located somewhere on
the screen. You will then see a curve which tells you where the apples are most
likely to fall. The higher the curve is, the more likely an apple will fall below that
point on the curve. Where the curve is high, there probably will be more apples.
Where the curve is low, fewer. The density curve is always symmetric around the
apple tree. The horizontal location of the apple tree is not fixed but it will vary from
trial to trial along with the curve and the apples. The tree, the apples and the curve
will all move together from left to right on each trial. There are three types of
density curves from where apples will fall, each coded by color. One is bell-shaped
(red), the second is "pointy" (green), and the last is like a box (blue).
671
672
Visual Location Task [Main Experiment]

The stimuli in the visual location task were the same as in the visual training task with the

following differences: On each trial in the Visual Location Task, participants saw only a

colored-coded sample of N = 9 points randomly drawn from the Gaussian, Laplacian or

Uniform distribution. The PDF and the location of the PDF were not shown on the screen.

To help participants remember the three density curves, small icons representing the

shape of the three distributions were drawn near the top of the screen (see Supplementary

Figure 1B and Supplementary Videos 2&3).

Participants were asked to estimate the unknown position of the center (i.e.,

location μ) of the underlying PDF using only the positions of sample points. They could

move a white upward pointing arrow (10 mm) to any location on the screen using a mouse.

Participants set the arrow at a position where they believed the horizontal center of the

underlying PDF was located and clicked the mouse button to record their estimates. We

ignored the vertical displacement of the arrow in analyzing the observer's settings.

Following a response, we presented a white vertical line (35 mm) marking the

location of the underlying PDF as feedback on the error between the participant's

estimates and the true position of the center of the PDF. Participants received $500 - D^2$

points where D^2 is the squared magnitude of their error in mm. If the position of the

estimates perfectly matched the true center ($D^2 = 0$), the participant received 500 points.

Points received could be negative if the error in distance was above 22.4 mm or below -

22.4 mm. At the end of each trial, the estimation error (mm), the score (points) and the

cumulative score were presented as a graphical display for 1.5 s. Participants received a

bonus payment proportional to the total score they earned across all trials ($1 per 10,000

points). The estimator that maximized the participants' expected bonus for each

distribution family was the UMVUE for that distribution family.

We provided warm-up trials before the main experiment. During warm-up, the

sample size was initially 300 and gradually reduced to 50, 20, and 9. The warm-up task

became more difficult as the sample size was reduced. As in the training task, a

distribution was chosen from one of the three distributional families (Gaussian, Laplacian,

and Uniform) and was repeated for five trials. In each trial, a new sample was generated

from the distribution chosen, giving 15 = 5 x 3 trials for the first block of 300 sample points.

Then the second block of 50 sample points started. The third block and the fourth block

used 20 and 9 points, respectively, giving 60 warm-up trials in total. Following a short

break, the main experiment started. One block consisted of 10 trials. Samples from the

three distributions were interleaved across blocks. Each participant ran 90 blocks (30

blocks for each distribution) with a short break after every 6 blocks.

Uniformly Minimum Variance Unbiased Estimator among L-estimators

The Laplacian location family has no closed-form solution for its UMVUE. Therefore we

computed the unbiased L-estimator that minimized variance numerically as follows. We

denote the UMVUE among L-estimators as $UMVUE_L$.

Given the n × n covariance matrix Σ of the order statistics $X_1, \dots, X_N$ we can

compute the choice of weights that leads to a minimum variance estimator as

$$w \propto \Sigma^{-1} e \qquad (11)$$

where $e = [1,1,...,1]'$, assuming that the correlations between the random variables are non-

zero (for proof, see Appendix A in Oruc et al., 2003), which is our case because the

random variables are ordered. We ran the numerical simulation by resampling the order

statistics 1,000,000 times and then computing the inverse of the covariance matrix and the

weights in Eq. 11. We normalized the weights so they sum to 1.

Measuring influence

Order statistics. We performed a regression analysis to estimate the influence of each

point in the sample on the participant's estimate of the position of the horizontal location of

the distribution (Gaussian, Laplacian, or Uniform) that had generated the sample. We

ordered 9 sample points in each sample in ascending order from the leftmost point to the

rightmost point. For each of the three distributions, we regressed the vector of the

participant's estimators $\mathbf{T^o}$ which contained 300 data points by the 300 by 9 matrix $\mathbf{X}$.

Columns were vectors of order statistics for each trial $\mathbf{X_{(1)}, \dots, X_{(9)}}$. Our linear regression

model is thus $\mathbf{T^o} = \mathbf{X}\widehat{\mathbf{W}}$ where $\widehat{\mathbf{W}}$ is the estimated weight vector. We used an ordinary

least squares regression with the constraint that weights add to 1: $\sum_{i=1}^{9} \widehat{w}_i = 1$. We

estimated influence for each participant and each distribution family of the population

distribution. In addition, we estimated the weight vector of the visual cluster model by

regressing the vector of the visual estimates predicted by the VCM by the matrix **X**. For

each variant of the VCM, we retrieved their visual estimates from the best fit parameters in

each model (see *Model fitting and evaluation*). See Supplementary Figure 5 for the

estimated weights in each model. The influence measures are a sensitive way to uncover

how participants behave in carrying out the task and discover discrepancies between

human performance and optimal performance (Dal Martello et al., 2023; Ota et al., 2024;

Ota et al., 2025b; Ota et al., 2025a; Ota & Maloney, 2024).

Model fitting and evaluation

For each participant, we fitted the model's visual estimates [Eq. 10] to the participant's

estimates by minimizing the negative log-likelihood of the observed estimates using

Bayesian adaptive direct search (BADS) (Acerbi & Ma, 2017). We assumed that the

observer's location estimate $T^O \sim N(T^{VCM}, \sigma^2)$ was Gaussian distributed.

In the first stage of the VCM, we tested two levels of partitioning sample points. At

the first level, we did not apply partition and fixed the grouping parameter K (i.e., the

number of clusters) in K-means clustering at 9 across all three location tasks. At the

second level of applying partition, we estimated K separately from data in each of the

three location tasks as a free parameter. Because K must be an integer, we estimated K

by a grid search in steps of 1. In each iteration of the grid search, the same integer value

of K was used across trials in each task. The estimated value of K could differ across the

three location tasks as the tasks for the three conditions were interleaved. We optimized

other parameters (described below) for each combination of the values of the three

grouping parameters K_G, K_L, K_U and chose the best combination that minimized negative

log-likelihood on each individual's data.

In the second stage of the VCM, we tested three levels of global agreement. At the

first level, we did not apply global agreement and fixed the parameter β (the inverse

temperature in the softmax decision rule) at 0. At the second level of applying global

agreement, we treated β as a free parameter with the boundary $\beta \in [0,4]$. Here we fitted

the value of β jointly across the three location tasks. Because the probability density did

not convey any information about how the relative weights should be assigned to each

cluster, we reasoned that participants did not adjust the global agreement parameter

according to the distribution family. Finally, at the third level, we partially applied global

agreement by fixing β at 1. Therefore, this factorial design allowed us to compare six

variants of the model. In all six models, we included a Gaussian response variance σ^2 and

a constant bias parameter b for individual's location estimates with the boundary

$b \in [-50,50]$. Again, we fitted the values of σ^2 and b jointly across the three location

tasks.

We also used hierarchical clustering with single linkage to test whether the results

of the VCM depend on a clustering algorithm we chose. Instead of K, we used $\theta \in [0,150]$

as a grouping parameter. We fitted $\theta_G, \theta_L, \theta_U$ to the data while other parameters remained

the same (Supplementary Figure 6). This parameter is a cutoff threshold in millimeter. If

the distance between two sample points or clusters is below a threshold, these two are

grouped into one cluster.

In the normative model, we fitted UMVUEs matched to the distribution family to the

data in the corresponding location task with two free parameters σ^2 and b. In all models,

we repeated the search process with different starting points to verify that we had found

the global minimum. For model comparison, we applied AICc—Akaike information criterion

with a correction for finite sample size—to each participant and each model as the

information criterion for goodness-of-fit (Burnham & Anderson, 2002; Hurvich & Tsai,

1989). The Bayesian information criterion (BIC) is motivated as a dimension-consistent

model selection criterion designed to select the "true model" when it is contained in the

candidate models being considered. Burnham & Anderson (2002) argues that expecting

any candidate model to represent the "full truth" is often unrealistic in biological sciences.

They therefore recommend AIC-type criteria for the analysis of empirical data, because

AIC is not designed to identify the true model but rather to select the model expected to be

closest to the data-generating process by minimizing the relative information loss among

the candidate models. The AIC's justification is asymptotic and it can be biased toward

more complex models when sample size is small relative to the number of model

parameters. AICc introduces an additional penalty term that reduces this small-sample

bias, helping to avoid potential overfitting and favour more parsimonious models. Based on

AICc values across participants and across models, we computed the protected

exceedance probabilities (Rigoux et al., 2014; Stephan et al., 2009) using a Matlab

function 'spm_BMS' in SPM 12 (https://www.fil.ion.ucl.ac.uk/spm/). The sign of AICc

values was reversed by multiplying with $-\frac{1}{2}$ so that an entry to the function 'spm_BMS' can

be converted to log model evidence (https://mbb-team.github.io/VBA-toolbox/wiki/BMS-for-

group-studies/).

Competing Interests

The authors declare no competing interests.

Author's Contributions

KO, QW, PM and LTM designed the experiment and analysis, QW and KO collected data. KO carried out the analyses. All authors contributed to developing and evaluating models and writing the article.

Data and code availability

The data frames and the codes used to generate the figures are shared at GitHub repository: https://github.com/keijiota/Given-the-birds-where-is-the-flock-

Acknowledgments

This research was supported by Grant-Aid for JSPS Fellows No. 17J07822 awarded to KO, by a Fellowship from the Institute for Advanced Studies of Paris and a Guggenheim Fellowship awarded to LTM, and an ANR/NIH grant "Probabilistic models of perceptual grouping and segmentation in natural vision" (ANR-19-NEUC-0003-01) awarded to PM.

References

Acerbi, L., & Ma, W. J. (2017). Practical Bayesian optimization for model fitting with Bayesian adaptive direct search. *Advances in neural information processing systems*, *30*, 1834-1844.

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*, 433–436. https://doi.org/https://doi.org/10.1163/156856897X00357

Burnham, K. P., & Anderson, D. R. (2002). *Model Selection and Multimodel Inference* (2nd ed.). Springer.

Chen, Y. J., Sun, Z., & Nishida, S. (2025). Human visual grouping based on within- and cross-area temporal correlations. *PLoS Comput Biol*, *21*(9), e1013001. https://doi.org/10.1371/journal.pcbi.1013001

D'Angelo, G., Voto, S., Iacono, M., Glover, A., Niebur, E., & Bartolozzi, C. (2025). Event-driven figure-ground organisation model for the humanoid robot iCub. *Nat Commun*, *16*(1), 1874. https://doi.org/10.1038/s41467-025-56904-9

Dal Martello, M. F., Ota, K., Pietralla, D. E., & Maloney, L. T. (2023). Detecting visual texture patterns in binary sequences through pattern features. *J Vis*, *23*(13), 1. https://doi.org/10.1167/jov.23.13.1

Froyen, V., Feldman, J., & Singh, M. (2015). Bayesian hierarchical grouping: Perceptual grouping as mixture estimation. *Psychol Rev*, *122*(4), 575-597. https://doi.org/10.1037/a0039540

Gan, L., Sun, P., & Sperling, G. (2023). Deriving the number of salience maps an observer has from the number and quality of concurrent centroid judgments. *Proc Natl Acad Sci U S A*, *120*(21), e2301707120. https://doi.org/10.1073/pnas.2301707120

Gershman, S. J., Tenenbaum, J. B., & Jakel, F. (2016). Discovering hierarchical motion structure. *Vision Res*, *126*, 232-241. https://doi.org/10.1016/j.visres.2015.03.004

Griffiths, T. L., Lieder, F., & Goodman, N. D. (2015). Rational use of cognitive resources: levels of analysis between the computational and the algorithmic. *Top Cogn Sci*, *7*(2), 217-229. https://doi.org/10.1111/tops.12142

Groen, II, Silson, E. H., & Baker, C. I. (2017). Contributions of low- and high-level properties to neural processing of visual scenes in the human brain. *Philos Trans R Soc Lond B Biol Sci*, *372*(1714). https://doi.org/10.1098/rstb.2016.0102

Hampel, F. R., Ronchetti, E. M., & Rousseeuw, P. J. (1986). *Robust Statistics: The Approach Based on Influence Functions*. Wiley.

Hartigan, J. A., & Wong, M. A. (1979). Algorithm AS 136: A K-Means Clustering Algorithm. *Applied Statistics*, *28*(1). https://doi.org/10.2307/2346830

Huber, P. J. (1981). *Robust_statistics*. Wiley.

Hurvich, C. M., & Tsai, C.-L. (1989). Regression and time series model selection in small samples. *Biometrika*, *76*(2), 297-307. https://doi.org/10.1093/biomet/76.2.297

Jakel, F., Singh, M., Wichmann, F. A., & Herzog, M. H. (2016). An overview of quantitative approaches in Gestalt perception. *Vision Res*, *126*, 3-8. https://doi.org/10.1016/j.visres.2016.06.004

Jeurissen, D., van Ham, A. F., Gilhuis, A., Papale, P., Roelfsema, P. R., & Self, M. W. (2024). Border-ownership tuning determines the connectivity between V4 and V1 in the macaque visual system. *Nat Commun*, *15*(1), 9115. https://doi.org/10.1038/s41467-024-53256-8

Juni, M. Z., Singh, M., & Maloney, L. T. (2010). Robust visual estimation as source separation. *J Vis*, *10*(14), 2. https://doi.org/10.1167/10.14.2

Koffka, K. (1935/2013). *Principles of Gestalt psychology*. Routledge.

Kubovy, M., & Gepshtein, S. (2003). Perceptual grouping in space and in space-time: An exercise in phenomenological psychophysics. In R. Kimchi, M. Behrmann, & C. R. Olson (Eds.),

Perceptual organization in vision: Behavioral and neural perspectives (pp. 57-98).
Psychology Press.
Landy, M. S., Goutcher, R., Trommershauser, J., & Mamassian, P. (2007). Visual estimation under
risk. *J Vis*, *7*(6), 4. https://doi.org/10.1167/7.6.4
Landy, M. S., Maloney, L. T., Johnston, E. B., & Young, M. (1995). Measurement and modeling of
depth cue combination: in defense of weak fusion. *Vision Res*, *35*(3), 389-412.
https://doi.org/10.1016/0042-6989(94)00176-m
Larigaldie, N., Yates, T., & Beierholm, U. R. (2025). Perceptual clustering in auditory streaming.
PLoS Comput Biol, *21*(7), e1013189. https://doi.org/10.1371/journal.pcbi.1013189
Lehmann, E. L. (1998). *Theory of point estimation*. Springer.
Lieder, F., & Griffiths, T. L. (2019). Resource-rational analysis: Understanding human cognition as
the optimal use of limited computational resources. *Behav Brain Sci*, *43*, e1.
https://doi.org/10.1017/S0140525X1900061X
Maloney, L. T., & Landy, M. S. (1989). A statistical framework for robust fusion of depth
information. *Proceedings of the SPIE: Visual Communications and Image Processing
IV*(1199), 1154-1163.
Maloney, L. T., & Thomas, E. A. C. (1991). Distributional assumptions and observed conservatism
in the theory of signal detectability. *Journal of Mathematical Psychology*, *35*(4), 443-470.
https://doi.org/10.1016/0022-2496(91)90043-s
Marr, D. (1982). *Vision: A computational investigation into the human representation and
processing of visual information*. MIT Press.
McGowan, J. W., Kowler, E., Sharma, A., & Chubb, C. (1998). Saccadic localization of random dot
targets. *Vision Res*, *38*(6), 895-909. https://doi.org/10.1016/s0042-6989(97)00232-0
Melcher, D., & Kowler, E. (1999). Shapes, surfaces and saccades. *Vision Res*, *39*(17), 2929-2946.
https://doi.org/10.1016/s0042-6989(99)00029-2
Mood, A. M., Graybill, F. A., & C., B. D. (1974). *Introduction to the theory of statistics* (3rd ed.).
McGraw-Hill.
Moreland, J. C., & Boynton, G. M. (2017). A neurophysiological explanation for biases in visual
localization. *Atten Percept Psychophys*, *79*(2), 553-562. https://doi.org/10.3758/s13414-
016-1251-z
Nielsen, F. (2016). Hierarchical Clustering. In *Introduction to HPC with MPI for Data Science* (pp.
195-211). https://doi.org/10.1007/978-3-319-21903-5_8
Nielsen, K. J., & Connor, C. E. (2024). How Shape Perception Works, in Two Dimensions and
Three Dimensions. *Annu Rev Vis Sci*, *10*(1), 47-68. https://doi.org/10.1146/annurev-vision-
112823-031607
Oruç, İ., Maloney, L. T., & Landy, M. S. (2003). Weighted linear cue combination with possibly
correlated error. *Vision Research*, *43*(23), 2451-2468. https://doi.org/10.1016/s0042-
6989(03)00435-8
Ota, K., Charles, L., & Haggard, P. (2024). Autonomous behaviour and the limits of human volition.
Cognition, *244*, 105684. https://doi.org/10.1016/j.cognition.2023.105684
Ota, K., Christofilea, E., Charles, L., Daunizeau, J., & Haggard, P. (2025b). Freedom through
understanding: instructed knowledge shapes voluntary action choices. *Preprint at PsyArXiv*.
https://doi.org/https://doi.org/10.31234/osf.io/mgksv_v2
Ota, K., Ciston, A., Haggard, P., Gajdos, T., & Charles, L. (2025a). Integrating explicit reliability
for optimal choices: effect of trustworthiness on decisions and metadecisions. *Preprint at
bioRxiv*. https://doi.org/https://doi.org/10.1101/2025.01.12.632598

Ota, K., & Maloney, L. T. (2024). Dissecting Bayes: Using influence measures to test normative use of probability density information derived from a sample. *PLoS Comput Biol*, *20*(5), e1011999. https://doi.org/10.1371/journal.pcbi.1011999

Ota, K., Shinya, M., Maloney, L. T., & Kudo, K. (2019). Sub-optimality in motor planning is not improved by explicit observation of motor uncertainty. *Sci Rep*, *9*(1), 14850. https://doi.org/10.1038/s41598-019-50901-x

Papale, P., Zuiderbaan, W., Teeuwen, R. R. M., Gilhuis, A., Self, M. W., Roelfsema, P. R., & Dumoulin, S. O. (2024). V1 neurons are tuned to perceptual borders in natural scenes. *Proc Natl Acad Sci U S A*, *121*(46), e2221623121. https://doi.org/10.1073/pnas.2221623121

Peirce, J. W. (2015). Understanding mid-level representations in visual processing. *J Vis*, *15*(7), 5. https://doi.org/10.1167/15.7.5

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: transforming numbers into movies. *Spatial Vision*, *10*(4), 437-442. https://doi.org/10.1163/156856897x00366

Rashid, J. A., & Chubb, C. (2021). The density effect in centroid estimation is blind to contrast polarity. *Vision Res*, *186*, 41-51. https://doi.org/10.1016/j.visres.2021.04.005

Rashid, J. A., & Chubb, C. (2022). On the flexibility of strategies for center estimation. *Vision Res*, *201*, 108125. https://doi.org/10.1016/j.visres.2022.108125

Reverdy, P., & Leonard, N. E. (2016). Parameter Estimation in Softmax Decision-Making Models With Linear Objective Functions. *IEEE Transactions on Automation Science and Engineering*, *13*(1), 54-67. https://doi.org/10.1109/tase.2015.2499244

Rigoux, L., Stephan, K. E., Friston, K. J., & Daunizeau, J. (2014). Bayesian model selection for group studies - revisited. *Neuroimage*, *84*, 971-985. https://doi.org/10.1016/j.neuroimage.2013.08.065

Shetty, P., & Singh, S. (2021). Hierarchical Clustering: A Survey. *International Journal of Applied Research*, *7*(4), 178-181. https://doi.org/10.22271/allresearch.2021.v7.i4c.8484

Shivkumar, S., DeAngelis, G. C., & Haefner, R. M. (2025). Hierarchical motion perception as causal inference. *Nat Commun*, *16*(1), 3868. https://doi.org/10.1038/s41467-025-58797-0

Stephan, K. E., Penny, W. D., Daunizeau, J., Moran, R. J., & Friston, K. J. (2009). Bayesian model selection for group studies. *Neuroimage*, *46*(4), 1004-1017. https://doi.org/10.1016/j.neuroimage.2009.03.025

Sun, J., Li, J., & Zhang, H. (2019). Human representation of multimodal distributions as clusters of samples. *PLoS Comput Biol*, *15*(5), e1007047. https://doi.org/10.1371/journal.pcbi.1007047

Sun, P., Chubb, C., Wright, C. E., & Sperling, G. (2016). The centroid paradigm: Quantifying feature-based attention in terms of attention filters. *Atten Percept Psychophys*, *78*(2), 474-515. https://doi.org/10.3758/s13414-015-0978-2

Sun, P., Chubb, C., Wright, C. E., & Sperling, G. (2018). High-capacity preconscious processing in concurrent groupings of colored dots. *Proc Natl Acad Sci U S A*, *115*(52), E12153-E12162. https://doi.org/10.1073/pnas.1814657115

Tanae, M., Ota, K., & Takiyama, K. (2021). Competition Rather Than Observation and Cooperation Facilitates Optimal Motor Planning. *Frontiers in Sports and Active Living*, *3*. https://doi.org/10.3389/fspor.2021.637225

Tassinari, H., Hudson, T. E., & Landy, M. S. (2006). Combining priors and noisy visual cues in a rapid pointing task. *J Neurosci*, *26*(40), 10154-10163. https://doi.org/10.1523/JNEUROSCI.2779-06.2006

Trommershauser, J., Kording, K., & Landy, M. S. (2011). *Sensory cue integration*. Oxford University Press.

960   Trommershauser, J., Maloney, L. T., & Landy, M. S. (2008). Decision making, movement planning
961   and statistical decision theory. *Trends Cogn Sci*, *12*(8), 291-297.
962   https://doi.org/10.1016/j.tics.2008.04.010
963   Ullman, S. (1984). Visual routines. *Cognition*, *18*(1-3), 97-159. https://doi.org/10.1016/0010-
964   0277(84)90023-4
965   Ullman, S., Vidal-Naquet, M., & Sali, E. (2002). Visual features of intermediate complexity and
966   their use in classification. *Nat Neurosci*, *5*(7), 682-687. https://doi.org/10.1038/nn870
967   van den Berg, R., Awh, E., & Ma, W. J. (2014). Factorial comparison of working memory models.
968   *Psychol Rev*, *121*(1), 124-149. https://doi.org/10.1037/a0035234
969   Vilares, I., Howard, J. D., Fernandes, H. L., Gottfried, J. A., & Kording, K. P. (2012). Differential
970   representations of prior and likelihood uncertainty in the human brain. *Curr Biol*, *22*(18),
971   1641-1648. https://doi.org/10.1016/j.cub.2012.07.010
972   Wagemans, J., Elder, J. H., Kubovy, M., Palmer, S. E., Peterson, M. A., Singh, M., & von der
973   Heydt, R. (2012). A century of Gestalt psychology in visual perception: I. Perceptual
974   grouping and figure-ground organization. *Psychol Bull*, *138*(6), 1172-1217.
975   https://doi.org/10.1037/a0029333
976   Wagemans, J., Feldman, J., Gepshtein, S., Kimchi, R., Pomerantz, J. R., van der Helm, P. A., & van
977   Leeuwen, C. (2012). A century of Gestalt psychology in visual perception: II. Conceptual
978   and theoretical foundations. *Psychol Bull*, *138*(6), 1218-1252.
979   https://doi.org/10.1037/a0029334
980   Zhang, H., Ren, X., & Maloney, L. T. (2020). The bounded rationality of probability distortion.
981   *Proc Natl Acad Sci U S A*, *117*(36), 22024-22034. https://doi.org/10.1073/pnas.1922401117
982

983   **Supplementary Information**

Supplementary Figure 1. Training Task and Visual Location Task.

A. Training Task. Three distributional families were color-coded. On each trial, we presented one of the three PDFs with varying its location μ along the horizontal axis and a sample drawn from the same PDF. The sample size reduced from $N = 300$ to $N = 9$ between blocks. Participants were asked to observe a color-coded sample drawn from the PDF with the same color code. **B. Visual Location Task**. On each trial, a sample of 9

992   points is drawn from one of the three distributional families with its location μ varied along
993   the horizontal axis. Participants were asked to estimate the location of the invisible center
994   of the PDF that had generated the sample by moving an arrow horizontally. Following a
995   response, the true location of the center of the PDF was presented as a vertical line. A
996   squared error and a score for a trial were also provided as feedback.
997
998

Supplementary Figure 2. Behavioral Performance did not Change Systematically Across Trials.

A. Total Score. The participant's total score in each location task is plotted across blocks. Data are averaged across all participants. The shaded areas indicate 99.7% confidence interval (± 3 SEM). Black horizontal lines are the theoretically maximum total score obtained by UMVUE that corresponds to each distribution family. Two-way within participant ANOVA, using the number of blocks (30) and the distribution family (3) as independent variables, shows neither main effect of the block (F [299, 5681] = 1.11, p = 0.095, partial η^2 = 0.055) nor a significant interaction between the block and the distribution (F [598, 11362] = 1.08, p = 0.091, partial η^2 = 0.054). **B. Squared Error.** The squared error between the participant's visual estimate and the true location of the center of the distribution is plotted versus trial. Two-way within-participant ANOVA, using the number of trials (300) and the distribution family (3) as independent variables, shows neither main effect of the block (F [29, 551] = 1.43, p = 0.069, partial η^2 = 0.070) nor a significant interaction between the block and the distribution (F [58, 1102] = 1.19, p =

0.155, partial η^2 = 0.059). **C. Estimated Weights (Influence).** To additionally confirm a
lack of learning effect over trials, we computed influence measures separately for the first,
the second, and the last 100 trials using a linear regression. The estimated weights are
averaged across all participants. The error bars indicate 99.7% confidence interval (± 3
SEM). A two-way within participant ANOVA, using the order of points (9) and the bin of
trials (3) as independent variables, shows no significant interaction between the order
index of the sample point and the trial bin in the Gaussian location task (F[16, 304] = 0.70,
p = 0.796, partial η^2 = 0.035), in the Laplacian location task (F[16, 304] = 0.74, p = 0.751,
partial η^2 = 0.038), nor in the Uniform location task (F[16, 304] = 1.22, p = 0.250, partial η^2
= 0.060).
1025

1026

1027
Supplementary Figure 3. Pairwise Comparisons of the Estimated Weights.

A. The values of the estimated weights (influence measure) from the data are taken from
Figure 4 and replotted as a bar graph as a function of the order statistics. **B.** Difference
between the estimated weights and the weights employed by the UMVUE (for the
Laplacian the UMVUE$_L$). In all panels, bars represent the average across participants. The
error bars indicate 99.7% confidence interval (± 3 SEM).

1034
1035

1036

Supplementary Figure 4. Efficiency of the obersers' estimators.

For each of the three location tasks and for each observer, we computed the variance of observer's estimator across trials and the variance of the UMVUE (which matched each location family) across trials. We then calculated the efficiency based on Equation 4. Bars represent the average across participants, whereas gray lines represent individual participants. The error bars indicate 99.7% confidence interval (± 3 SEM).

1044

1045

1046   **Supplementary Figure 5. All Variants of the Visual Cluster Model.**

1047   The predictions of the estimated weights for each model in the factorial model comparison.
1048   Regression weights estimated from the data are taken from Figure 4 and replotted as
1049   colored squares. Mean model fits across observers are plotted as black solid lines while
1050   shaded gray areas denote 99.7% confidence interval (± 3 SEM).

1051

1052
Supplementary Figure 6. Comparison of the Model Fit across Two Clustering

Algorithms.

A. A Comparison of AICc Scores. We adopted K-means clustering in the main text to fit
the visual cluster model to the data. We repeated the clustering algorithm analysis using
hierarchical clustering with single linkage. **B.** Prediction of the Estimated Weights
(Influence). Regression weights estimated from the predictions of the VCM using
hierarchical clustering. AICc scores and the estimated weights are almost identical
between the two clustering algorithms (see Figure 6).