GIVEN THE BIRDS, WHERE IS THE FLOCK?

Visual estimation of the location of collections of points

Keiji Ota[1,2,3,4*] Qihan Wu[5]   Pascal Mamassian[6]   Laurence T Maloney[3,4]

[1] Centre for Brain and Behaviour, Department of Psychology, Queen Mary University of London

[2] Institute of Cognitive Neuroscience, University College London

[3] Department of Psychology, New York University, New York, United States

[4] Center for Neural Science, New York University, New York, United States

[5] Department of Psychological and Brain Sciences, Johns Hopkins University

[6] Laboratoire des systèmes perceptifs, Département d'études cognitives, École normale supérieure, PSL University, CNRS, Paris, France

* Corresponding author

Keywords

Location estimation, Gestalt, perceptual organization, clustering, non-Gaussian distributions

Abstract

A key step in perceptual organization is segmentation of a scene into 'wholes' made of 'parts': birds form flocks, pedestrians form crowds. The 'parts' have spatial locations as does the 'whole' and we can ask, how do the locations of the 'parts' influence the perceived location of the 'whole'? The answer may depend on the nature of the parts, the processes that generate them: the influence of single birds on the location of a flock may be different from that of single pedestrians on the location of a crowd. We treated the 'parts' as samples from a probability density function (PDF) and asked participants to estimate the location of the generating PDF given a sample. The generating PDFs belonged to one of three location families – Gaussian, Laplacian or Uniform. Observers received training with each family and knew which family the generating PDF came from on each trial. We compared human performance to that of the Uniform Minimum Variance Unbiased Estimator (UMVUE) for each location family. We based our analyses on the measured *influence* of each sample point, a measure of how the observer made use of each sample point in estimating the center. Observers used different estimators for different families and the estimator chosen for samples from each family were close to the UMVUE for that family. How does the observer calculate approximate UMVUEs for the three location families considered? We propose that a critical step is to estimate the locations of visual clusters in the sample. The Visual Cluster Model accurately captured human performance across all three distributions. Our findings suggest that the observer's estimate of the location of the 'whole' is based not directly on the locations of the 'parts' but rather on the 'clusters' they form.

[289 words]

Introduction

The human visual system segments scenes into visual objects (Ullman, 1984; Ullman et al., 2002), adding visual structure to what are initially only patterns of light across the retinas. Such 'wholes made of parts' have their own spatial locations which the observer can be asked to estimate. If the observer is, for example, asked to saccade to a cloud of points, the saccade can be interpreted as an estimate of the center of the cloud (McGowan et al., 1998; Melcher & Kowler, 1999). The key question is, how is this estimate computed from the individual points? Birds in flight form a flock (Figure 1A) but typically no one bird marks the center of the flock. There is no 'correct' answer to the question as posed.

This and other phenomena such as border ownership (D'Angelo et al., 2025), object segmentation (Jeurissen et al., 2024; Papale et al., 2024) and shape perception (Nielsen & Connor, 2024) and more are part of 'middle vision' (Ullman, 1984), the stage in visual processing that follows encoding of initial visual information into retinotopic areas. These same phenomena are central to Gestalt psychology (Wagemans, Elder, et al., 2012; Wagemans, Feldman, et al., 2012). We examine one such phenomenon in detail: visual location of 'whole' given the locations of the 'parts' it contains.

We transform this visual location task into a parametric point estimation task (Lehmann, 1983) where observers are asked to estimate the location of a probability density function (PDF) given a sample from the PDF. We can compare human performance to performance judged optimal by various criteria. We will focus on minimum variance estimation.

The collection of points ('parts') form a sample drawn from a one-dimensional probability density function PDF). In Figure 1B, the red curves, dashed and solid, are

copies of the same PDF with the red, solid PDF being the PDF used to generate the

sample. They represent a *location family*, a collection of PDFs differing only in location (e.g.

Figure 1B). The colored dots are a sample from the solid PDF. We reformulate the location

estimation problem as a problem in parametric point estimation (Lehmann, 1983; Mood et

al., 1974) and compare human performance to optimal. *How does the observer estimate*

the center of the PDF given only the sample and knowledge of the location family which

the PDF belongs to?

Figure 1: Estimating the Location of a Collection of Points. A. A Flock of Birds. A
flock of birds in flight. **B. The one-dimensional Gaussian Location Task.** The dashed
and solid red curves are examples of Gaussian probability density functions (PDFs) with

unit variance for different values of the location parameter $\boldsymbol{\mu}$. All of the red curves together
comprise a *Gaussian location family*. The solid red curve is the actual PDF from which the
sample was drawn. The sample is composed of *N* positions and is plotted as red points
along the horizontal axis. The observer sees only the sample $X_1, ... , X_N$ and is asked to
estimate the value of the location parameter $\boldsymbol{\mu}$ corresponding to the PDF that was used to
generate the sample. **C. 1D Parametric Estimation.** The observer sees the individual
points and knows that the points are a sample from a PDF in the Gaussian location family
with unit variance. He estimates the unknown location of the generating PDF.

In detail: The observer sees a one-dimensional sample of points $X_1, ... , X_N$

plotted as red dots along a horizontal line and is asked to estimate the center of the PDF

from which the sample was drawn (solid red curve).

In the present study, we consider different families of probability density functions

(PDFs). One of these families is the Gaussian PDF, commonly used in visual modeling,

notably cue combination models (Landy et al., 2007; Oruç et al., 2003). A second

motivation for using Gaussian distributions in modeling visual judgments is that actual

visual and motor error is close to Gaussian in a wide class of everyday tasks such as

pointing and reaching (Ota et al., 2019; Tanae et al., 2021; Trommershauser et al., 2008).

Humans frequently encounter tasks involving Gaussian random variables and they may

tend to apply estimation rules and other statistical procedures that are appropriate when

distributions are Gaussian (Tassinari et al., 2006; Vilares et al., 2012). However, it is less

well known how humans behave when distributions are non-Gaussian (see (Maloney &

Thomas, 1991) for an exception).

Figure 1C summarizes what the observer in our experiment knows – the locations

of points and knowledge of the distributional family from which they are drawn. *Parametric*

point estimation methods (Lehmann, 1983; Mood et al., 1974) allow us to compute optimal

estimators for each PDF family based on criteria such as minimum variance for a wide

range of distributions.

Assuming for now that the PDF is Gaussian with fixed variance 1 and with

unknown *location* parameter μ, the PDF is

113
$$\phi_\mu(x) \;=\; \frac{1}{\sqrt{2\pi}}\; e^{-\frac{(x-\mu)^2}{2}} \qquad . \tag{1}$$

Several examples of PDFs from a *Gaussian location family* (Eq. 1) are plotted as dashed

red curves in Figure 1B. As μ is varied, the PDF moves left and right (hence the term

"location parameter"). The "true" PDF, the one from which the sample was actually drawn,

is plotted as a solid red curve.

Again, the observer's task is – given only the sample and the Gaussian constraint –

to estimate the unknown *location* μ of the true PDF. The estimator that the observer uses

is a function of the sample and may depend as well on the distributional assumption

(Figure 1C). The observer's estimate can be denoted $T_G^O(X_1, ..., X_n)$ or, if there is no

ambiguity, just T_G^O. "O" stands for the Observer, "G" for the Gaussian assumption.

While the observer has two sources of information (*distributional constraints* and

the *sample*) that inform their estimate $T_G^O(X_1, ..., X_n)$, it is usually the sample values that

take center stage, with the Gaussian assumption in the background. But what use – if any

– does the observer make of the distributional constraints? How are the parts combined to

estimate the location of the whole when the distribution generating the parts is not

Gaussian?

In Figure 2 we illustrate the Location Task for three choices of distributional family.

Figure 2A corresponds to the Gaussian case that we just discussed (Eq. 1). Figure 2B

illustrates a location task based on the Laplacian distribution[1], where the PDF is now

$$\varphi_\mu(x) \ = \ \frac{1}{2}e^{-|x-\mu|} \qquad .$$ (2)

The PDF is symmetric around the unknown location parameter μ. The observer's task is

still to estimate μ. Finally, the Uniform Location Task is based on a uniform distribution

(Figure 2C),

136
$$\varphi_\mu(x) \ = \ 1 \qquad |x-\mu| < \frac{1}{2}$$
$$\varphi_\mu(x) \ = \ 0 \qquad |x-\mu| \geq \frac{1}{2}$$
(3)

138
139
140   **Figure 2. Location Tasks. A. Gaussian Location Task. B. Laplacian Location Task. C.**
141   **Uniform Location Task.** Each plot shows a probability function and a sample, color coded.
142   The PDFs used in the experiment all had the same variance. See Methods and Materials.
143

144   We first assessed human performance in the three location tasks for the

145   distributions shown in Figure 2. In our experiment, the observer familiarizes himself with

146   the distributional families and the typical samples they generate. On every training trial,

---

[1] The actual PDFs used were always scaled to have the same variance. We present them in simplified form in Eqs. 2 and 3. See Methods.

they see a sample drawn from a PDF. The color of the points identifies the PDF location

family from which the PDF is drawn (as in Figure 2).

Uniformly Minimum Variance Unbiased Estimators (UMVUE). An estimator is any

function of the sample, $T(X_1, ..., X_n)$ and, since an estimator is a function of random

variables, it is itself a random variable with its own expected value $E[T]$ and variance

$Var(T)$.

A common criterion for a "good" estimator is that it is _unbiased_, i.e. $E[T] = \mu$. A

second common criterion is that the estimator should have the lowest possible variance. If

an estimator satisfies both of these two criteria for all values of μ then it is a _Uniformly_

Minimum Variance Unbiased Estimator (UMVUE) or, less formally, the _minimum variance_

estimator. Cue combination models (Landy et al., 1995; Oruç et al., 2003;

Trommershauser et al., 2011) use UMVUEs and there is evidence that human observers

do as well (Juni et al., 2010; Rashid & Chubb, 2022).

We can compute a measure of the _efficiency_ of any unbiased estimator T for a

task as the ratio of the variance of the UMVUE to that of the estimator. Since

$Var(T^{UMVUE}) \leq Var(T)$, the _efficiency_ of T

$$H = Var(T^{UMVUE})/Var(T)$$ (4)

is a value between 0 and 1.

First, we ask, how does the human visual system adapt its estimation rule

$T_G^O(X_1, ..., X_n)$ to location tasks based on each of the distributional families in Figure 2 –

if it adapts it at all? Second, we will compare human performance to optimal unbiased

estimators minimizing variance (UMVUEs) for each of the three location tasks in Figure 2.

One possible outcome is that observers may simply adopt the same estimator for

all three location tasks, effectively ignoring the distributional information. At the other

extreme, the observer might adopt the correct UMVUE estimator for each of the three

tasks. A third is that it may adopt an estimation strategy which we did not anticipate.

L-Estimators. For convenience, we will focus on a set of estimators referred to as L-

estimators (Lehmann, 1983). They are defined as weighted combinations of order

statistics

176
$$T^W(X_1, ..., X_n) = w_1 X_{(1)} + ... + w_n X_{(n)}$$
(5)

where the sum of the weights is constrained to be 1. The order statistics (Mood et al.,

1974)

are just the sample values renumbered from left to right. We can represent any L-estimator

by a plot of its weights (Figure 3). Arguably, the observer has no other way to combine the

points across trials than by their left-to-right order on the screen.

The UMVUEs for the Three Location Tasks. Parametric estimation comprises a

collection of mathematical techniques that allow us to identify optimal estimators including

UMVUEs for different estimation problems with different distributional families (Lehmann,

1983; Mood et al., 1974). The unbiased estimator T^+ minimizing variance for the

Gaussian task illustrated in Figure 1A is just the arithmetic mean of the sample (Lehmann,

1983; Mood et al., 1974). It is repeated in Eq. 6, written in the form of an L-estimator

188
$$T^+ = T^+(X_1, ...X_n) = \sum_{i=1}^{n} X_i \Big/ n = \sum_{i=1}^{n} \frac{1}{n} X_{(i)} .$$
(6)

This estimator is unbiased $E[T^+] = \mu$ and it minimizes the variance $E[(T^+ - \mu)^2]$.

Not every location task has an *UMVUE*. While the *UMVUE* for the Gaussian is the

sample *mean* (Eq. 6), the Laplacian has no closed-form solution for its *UMVUE*. We

computed the unbiased L-estimator that minimized variance by numerical methods

(exhaustive search) and plot it in Figure 3B, the *UMVUE* among L-estimators denoted

UMVUE$_L$. We use the term *UMVUE* to refer to either *UMVUE* or *UMVUE$_L$* when it is clear

from context which is intended.

The *UMVUE* for the uniform family is

$$T^u(X_1, ..., X_n) \quad = \quad \frac{X_{(1)} + X_{(n)}}{2} \quad , \qquad (7)$$

the average of the minimum and maximum values in the sample (the *average of extremes*).

We have three different *UMVUEs* each matched to the distribution family of a

location estimation task (Fig 3). Each is unbiased.

201
Figure 3: Uniformly Minimum Variance Unbiased Estimators (UMVUEs). A. Gaussian
Location Task. B. Laplacian Location Task. The *UMVUE$_L$* L-estimator estimated
numerically (the Laplacian has no *UMVUE*). **C. Uniform Location Task.** Three UMVUE
estimators are represented as L-estimators of weighted average of order statistics. The Y-
axis denotes weights (i.e., regression coefficients) on each sample point ordered from left
to right. UMVUE estimator for the Gaussian location task is the arithmetic mean of the
sample. The UMVUE for the Laplacian location task has the largest weight on the median.
The UMVUE for the Uniform location task is the average of extremes.
210
211
Influence. We can interpret the weights in an L-estimator as measures of the *influence* of

each point (each order statistic), a useful characterization of a statistical task (Juni et al.,

2010; Maloney & Landy, 1989; Ota & Maloney, 2024) that is important for research in

robust statistical estimation (Hampel et al., 1986; Huber, 1981).

In our experiment, we are presenting an observer with a sample whose order

statistics — left to right – are $X_{(1)}, ... X_{(i)}, ... , X_{(n)}$ and recording the observer's

response $T^O(X_{(1)}, ... X_{(i)}, ... , X_{(n)})$, the location estimate. The influence of the point at

position i on the location estimate is the partial derivative

$$I_i = \frac{dT^O}{dX_i} \qquad .$$ (8)

which allows us to measure the contribution of each point to the overall estimate. If the

location estimator is an L-estimator, then the influence estimates are just the weights in Eq.

(5).

To summarize, in this article we first examine how observers combine locations of

individual points to estimate the location of the generating PDF, an exemplary parametric

estimation problem in visual form. We then propose a model of human performance, the

Visual Cluster Model (VCM) of location estimation. We test the VCM model against

alternatives.

Results

The observers were first familiarized with the three distributional families (Gaussian, Laplacian, and Uniform) by viewing the typical samples generated for different sample sizes (Supplementary Figure1A; see Methods and Materials). In the main experiment observers were presented with samples of 9 points drawn from one of the three distributional families and asked to estimate the position of the center of the generating PDF given only 9 sample points and the knowledge of which distribution family had generated the sample. They were provided feedback concerning their visual estimate (Supplementary Figure1B). We confirmed that behavioral performance did not systematically change across trials (Supplementary Figure 2AB).

We know the UMVUE weights (influences) for each task (Figure 3) and we can estimate the observers' weights by linear regression (see Methods and Materials). Figure 4 (and Supplementary Figure 3A) illustrates the estimated weights for each participant and the average across participants. Observers were sensitive to the distributional constraints. Observers' influence measure markedly changed with changes in distributional family (interaction between the order of points and the distributional families by ANOVA on the estimated weights: $F[16, 304] = 44.53$, $p < 0.0001$, partial $\eta^2 = 0.701$).

250
Figure 4: Observers' Estimated Influence Measures Compared to UMVUE Influence
Measures. A. Gaussian Location Task. B. Laplacian Location Task. C. Uniform
Location Task. Influence (i.e. regression coefficients) of each point in samples (ordered
from left to right) on observer's visual estimates. Results for each observer are plotted as
faint grey lines. Mean results across observers are plotted as color-coded squares. Error
bar denotes 99.7% confidence interval (± 3 SEM). Weights employed by UMVUE are
taken from Figure 3 and replotted as dashed lines. For the Laplacian distribution,
observers' estimated influence measures are not significantly different from the $UMVUE_L$.
The observers' influence measures for the other two distributions deviate from those of
their respective UMVUEs.
261
262   Do observers' choice of estimators approximate the UMVUEs for each location

task? We compared measured influence with normative (UMVUE or $UMVUE_L$) influence

for each location task separately. For the Gaussian task, the normative estimator is just

the arithmetic mean of the sample. In contrast, the observer's estimated influences look w-

shaped and are significantly different from the normative influences (F [8, 152] = 19.56, $p <$

0.0001, partial η^2 = 0.507) by particularly placing larger weights on the median sample

point than UMVUE (Supplementary Figure 3B), meaning that observers do something

other than averaging points.

270   For the Uniform task, the measured influences are also different from normative

influences (F [8, 152] = 35.27, $p <$ 0.0001, partial η^2 = 0.650). Even though observers gave

most weight to the extreme sample points, they placed significantly less weight on them

than the UMVUE (Supplementary Figure 3B). For the Laplacian task, observers

approximated the UMVUE (F [8, 152] = 1.83, p = 0.076, partial η^2 = 0.088). We note that

there was no significant changes in the measured influences from the beginning to the end

of the experiment (Supplementary Figure 2C). In summary, the observers are sensitive to

the distributional constraints in the three location tasks – choosing significantly different

estimators for the three location tasks. The observers' estimators did not differ from the

UMVUE$_L$ for the Laplacian location task and roughly approximated the UMVUE for the

Uniform location task. We found a small but patterned deviation between the estimators

chosen for the Gaussian location task and the UMVUE for that family, pointing to a

systematic rule that observers employed other than averaging points.

The Visual Cluster Model (VCM)

Given a sample of points, which estimator will observers choose? Here, we considered the possibility that the visual system's choice of estimator is based entirely on the cluster structure of the samples (Sun et al., 2019). Intuitively, clusters convey information about the PDFs from which they are drawn. A cluster confined to an interval [a,b] will tend to have more points when the probability density across the interval is larger. We first illustrate the computation with an example.

In Figure 5A we plot a 9-point sample and in Figure 5B we partition the sample into $K = 5$ non-overlapping clusters denoted left to right as $C_1, C_2, …, C_5$ using a standard clustering algorithm described below. Clusters in our experiment have a minimum size of 1 element, and a maximum size of 9 (in which case, there is only one cluster). We assign a location c_j to the j^{th} cluster C_j, the midpoint of the endpoints of the cluster.

In our example, the largest cluster, C_4 contains three points. If we had to base our estimate of location on just one of the clusters in the cluster structure of the sample, it would plausibly be the 4th cluster. But there are competing clusters with either 1 or 2 points, and we can attempt to improve our estimator by weighting together the locations of the clusters with weights that depend on the clusters.

303
304
Figure 5: Visual Cluster Model. A. Gaussian Location task. A sample of 9 points is
drawn from a Gaussian distribution. Observers were asked to estimate the location of the
invisible center of the underlying distribution given only sample points. **B. Partition.** Visual
cluster model partition points (partitions shown as dashed vertical lines) into K clusters of
the sample, $C_1,...,C_K$. Each cluster is assigned a location $c_1,...,c_K$ defined as the average
of its largest and smallest points if the cluster contains more than one point. Otherwise, the
location of the single point is the location of the cluster. **C. Global Agreement.** Visual
cluster model assigns the log likelihood λ_j of the center $\boldsymbol{\mu}$ of the PDF to the location C_j of
the j^{th} cluster. A dashed curve represents the log likelihood values across the entire space
of the task. The log likelihood values $\lambda_1,...,\lambda_K$ are converted to the relative weights
$w_1,...,w_K$ via a softmax transformation. The visual cluster model estimates the position of
the center of the PDF as a weighted average of cluster locations $c_1,...,c_K$ with weights
$w_1,...,w_K$.
318
We considered variations on the model at each step but – to simplify the

presentation of the model – we first describe one version of the model and discuss

possible variations only after presentation of this base version of the model. One goal of

the model is to reduce the complexity of the computation (Lieder & Griffiths, 2019) by

relying on the cluster structure of the model (five clusters in our example) (Sun et al.,

2019) rather than the nine points.

Step 1: Partition. The visual system partitions points in the sample into a small set of non-

overlapping clusters. In Figures 5A and 5B, we apply a standard clustering algorithm, K-

means clustering (Hartigan & Wong, 1979), to a sample $X_1, \ldots, X_N$ from the Gaussian

distribution (Eq. 1). The clustering algorithm has one free parameter K (the number of

clusters) which is estimated from the data. In Figure 5B, we obtained $K = 5$. The result is

a partition into non-overlapping clusters $C_1, \ldots, C_K$ numbered from left to right, possibly

varying in number of points. We assign a location to each cluster $c_1, \ldots, c_K$ as the average

of its largest and smallest points (average of extremes) if the cluster contains more than

one point, otherwise the location of the single point if the cluster contains only one. The

first step is analogous to the cluster-of-samples representation developed by Sun et al.

(2019). We extend their model by introducing *global agreement*.

Step 2: Global agreement. How well does each cluster C_j at location c_j capture not just

the points in its own cluster but rather the entire sample of points $X_1, \ldots, X_N$? We

hypothesize that observers make use of the distributional constraint to assess the

likelihood of the location of the distribution generating the points. In Figure 5C, for each

cluster, we compute the log likelihood λ_j of the location parameter μ of the population

PDF with respect to the location c_j of the j^{th} cluster:

$$\lambda_j = \sum_{i=1}^{9} \log f_{\mu}(X_i \mid \mu = c_j) \quad . \qquad (8)$$

where f_μ is the likelihood function of the distribution chosen to generate the sample points,

with unit variance. This step results in a measure of the likelihood that the location c_j of

cluster j reflects the center of the distribution, taking into account all the points of the entire

sample. Therefore, we refer to it as *global agreement*. A dashed curve in Figure 5C shows

the log likelihood computed across the entire space of the task. In the Gaussian location

task, finding the location of the maximum log likelihood value will correspond to averaging

sample points. Instead of the performing the log likelihood computation over the entire

space, we reduced the complexity of computation (Lieder & Griffiths, 2019) by computing

the log likelihood value with respect to the locations c_j of the j^{th} clusters.

We use a softmax transformation with one parameter β, i.e., known as inverse

temperature (Reverdy & Leonard, 2016) to convert the log likelihood λ_j to weights

355
$$w_j = \frac{\exp(\beta\lambda_j)}{\sum_{j=1}^{K}\exp(\beta\lambda_j)} \tag{9}$$

The parameter β is a free parameter used to scale measures of global agreement. When

β is fixed at 0, the relative weights w_j are all 1/K: all clusters get equal weight. When β

increases, clusters having a large log-likelihood value gets relatively larger weights relative

to those with smaller log-likelihood values. In the limit as β grows, the weight of the cluster

with the largest log-likelihood converges to 1 while the other weights drop to 0.

On any given trial, the visual system's estimate of the position of the center of the

distribution is modelled as the weighted mean of the locations of the clusters with softmax

weights that depend on the log-likelihoods assigned to clusters (Figure 5C)

364
$$T^{VCM} = \sum_{j=1}^{K} w_j c_j + b \qquad . \tag{10}$$

A bias term b is added to account for the small but constant bias that we found in the

participants' visual estimates (on average, 2.07 mm, SD = 1.41 mm), possibly a visuo-

motor error.

The weight on each cluster is determined by the relative value of the measure of

global agreement (i.e., how accurately the center of the distribution is approximated)

compared to the measures of global agreement in other clusters. This is broadly consistent

with the concept of divisive normalization which is thought to be operated in the visual

cortex for the computation of visual perception (Carandini & Heeger, 2011) and the

encoding of value (Louie et al., 2013).

Factorial model comparison. We test two levels of the grouping parameter K. At the

first level, we will fix K at 9. At the second level, the grouping parameter K will be treated

as a free parameter and estimated from the data (maximum likelihood). Given that

samples from the three possible distributions are color-coded, the observer can select

different values K_G, K_L, K_U of the grouping parameter K for the three different

distributional families. These values will be estimated from the data. The observer's choice

of K value can be interpreted as top-down cognitive processes which control perceptual

segmentation given a prior knowledge of the distributional familiy.

For global agreement (β) we test three levels in the factorial design. At the first

level, we will fix β at 0 so all clusters get equal weights. At the second level, the parameter

β will be treated as a free parameter constrained to be the same value across the three

distributional families. Last, at the third level, we will fix it at 1. By this constraint, global

agreement is applied to the model fit but the β value is not informed from each observer's

data.

We built six models by combining two levels of partition and three levels of global

agreement and compare the models by a factorial model comparison (van den Berg et al.,

2014; Zhang et al., 2020). Figure 6A shows the summed AICc score across participants

for the six models. The two-stage visual cluster model (partition and global agreement)

outperformed the other five variants of the model. A group-level Bayesian model selection

(Rigoux et al., 2014; Stephan et al., 2009) showed that the protected exceedance

probability of the two-stage VCM, i.e. the probability for the model to outperform all the

other models was 99.9%. This model was also better than the normative model where

UMVUE was fitted to the observer's data. Furthermore, the three models based on

partitioning points (K_G, K_L, K_U estimated from the data) outperformed the other three

models without partitioning (K fixed at 9; the protected exceedance probability = 99.8%). A

model where partitioning was applied (K_G, K_L, K_U estimated from the data) while global

agreement was partially applied (β fixed at 1) outperformed a model where partitioning

was applied but global agreement was not (β fixed at 0), though the β value was not fitted

to the data in these two models (the protected exceedance probability = 87.1%). These

results support the claim that both partitioning and global agreement are essential

computations that underpin the observers' visual judgments.

406
Figure 6: Visual Cluster Model Compared to Human Performance. A. Factorial model
comparison. We built six models by combining two levels of partitioning (Step 1) and
three levels of global agreement (Step 2). The y-axis denotes the AICc score summed
across participants. The lower the AICc, the better the model. A dashed red line plots the
AICc score for the normative UMVUE. A grouping parameter K is the cluster size in K-
means clustering we used to fit to the data. A parameter β is inverse temperature in the
softmax transformation which converts the log likelihood values to the relative weights
(Figure 5). **B. Prediction of the Estimated Weights (Influence).** Regression weights
estimated from the data are taken from Figure 4 and replotted as colored squares. The
model prediction of the estimated weights for each location task was estimated using a
linear regression on the visual estimates recovered from the best Visual Cluster Model
(Partition applied × Global agreement applied). The prediction of the estimated weights
was averaged across observers for each task and was plotted as a black solid line.
Shaded gray area denotes 99.7% confidence interval (± 3 SEM).
421

We estimated the influence of each point in the sample on the visual estimates

generated by the two-stage VCM. The prediction of the influence measure by the model

captured human data well in all three distributional families (Figure 6B). Specifically, the

model produced a w-shaped influence pattern in the Gaussian task, a median-biased

influence in the Laplacian task, and the average of extremes in the Uniform task. It is

remarkable that a single model can generate such different estimators each tailored to a

distribution family.

Patterns of predicted influence by other variants of the model are summarized in

Supplementary Figure 4. When we applied the global agreement partially (β fixed at 1)

and had grouping parameters free, the model still produced distinct patterns of measured

influence in the three location tasks (Supplementary Figure 4F), suggesting that we are not

overfitting the data by estimating the global agreement parameter from the data. However,

without applying global agreement (β fixed at 0), we failed to properly fit the data

(Supplementary Figure 4A&D). The models without partition (K fixed at 9) also failed to fit

the data (Supplementary Figure 4A-C). These results again demonstrate that both

partitioning and global agreement are essential computations.

Finally, we tested whether our results depend on a choice of the clustering

algorithm. We repeated the model fit using a hierarchical clustering with single linkage

algorithm (Nielsen, 2016; Shetty & Singh, 2021) and found that the results were almost

identical (Supplementary Figure 5).

442
443

Discussion

A central task of visual perceptual organization is to model how the visual system

combines 'parts' into 'wholes'. When parts have spatial attributes such as location, how

does the visual system combine the parts into an estimate of the location of the whole?

We considered a statistical version of this problem drawn from parametric point estimation

(Lehmann, 1983). We asked observers to estimate the center of the PDFs of three

different location families of one-dimensional PDFs. Observers knew everything about the

PDF except for its location parameter which they were asked to estimate. In instructing the

observers, we used the neutral term 'center' to refer to what was in fact the mean, median,

and axis of symmetry of the PDF. The task is a paradigmatic statistical task: given a

sample, estimate the parameters of the PDF that generated it. It is also part of perceptual

organization.

We compare human performance to that of a Uniformly Minimum Variance

Unbiased Estimator (UMVUE) for that distribution. The UMVUE for each distribution is

unbiased and has the lowest possible variance among location estimators. The normative

minimum variance estimator is markedly different for the different distributional families we

considered, namely the Gaussian, the Laplacian, and the Uniform.

How does the observer carry out the task? For the Gaussian location family, for

example, the statistician need only compute the mean of the sample. The resulting

estimate is the UMVUE but, as we have seen, it is not what human observers do. We

sought an alternative computation that would reproduce what human observers do, and

that could be applied to estimation problems for the non-Gaussian distributions as well.

We propose that the visual system bases its estimates on the clusters in the sample and

integrates the locations of the clusters, weighting them by how well each cluster alone

accounts for the observed sample.

Using influence measures, we tested whether observers adopt the same estimator

for the three different distributions. We found that observers used different location

estimators for the three distributions. We also tested whether the estimator for each

distribution was the UMVUE for that distribution. The observers' rules were different from

UMVUE for Gaussian and Uniform location tasks but we could not reject the hypothesis

that observers used the UMVUE in the Laplacian location task.

In the Gaussian location task, observers exhibit a systematic bias that deviate from

equal weighting of each sample point, demonstrating a w-shaped influence pattern –

placing large weights on the median and the two extreme points. This result is

counterintuitive because it suggests that observers are not simply averaging visual

elements, despite averaging being an elementary statistical operation that they are

presumably familiar with. Deviations from equal weighting in the Gaussian location task

have also been confirmed in previous studies, which show that observer's estimates are

biased by outliers in a sample (Juni et al., 2010; Moreland & Boynton, 2017). However, the

influence patterns were flexibly adapted to the distributional constraints. In the Uniform

location task, the two extreme sample points exerted strong influence on the observer's

estimates, while their influences were minimal in the Laplacian. Intuitively, the extreme

points in a sample from the Laplacian distribution are poor indicators of the center of

Laplacian distribution. If observers were estimating the likelihood of the center, the

influence of these extreme points would be expected to be small in the Laplacian location

task.

It is implausible that the human visual system has different, explicit rules of

perceptual organization in our location task for any choice of location family. We wondered

whether a common estimation algorithm based on Gestalt structure could account for how

the visual system assigns locations to samples from arbitrary location families.

We developed a two-stage Visual Cluster Model (VCM). Our model comparison

analysis validated the two stages on the VCM. The first partition stage edits individual

visual points so that points can be grouped into a cluster which itself defines a location.

At the second stage (global agreement), the VCM evaluates how likely each cluster

approximates the location of the distribution generating the points. A cluster with a high

likelihood value is weighted more in the visual judgment than a cluster with a low likelihood

value. It is plausible that the visual system encodes such relative weights according to the

divisive normalization theory (Carandini & Heeger, 2011; Louie et al., 2013). However, to

apply the theory, the sample points would first have to be transformed to their order

statistics. The VCM then combines the cluster locations using weights that are

proportional to the likelihood values assigned to clusters. The distributional constraints

provided information that was necessary to estimate the likelihood of the location of the

center of the distribution (Eq. 8). We demonstrated that a two-stage VCM accounts for

distinct rules of the observer's visual judgments across all the three location tasks.

Sun et al (2019) also used a clustering algorithm to model the representation of

human visual experience. In their task, observers were asked to estimate the location of

the empirical mean or mode of the sample of 70 visual points, and points were drawn from

a mixture of distributions that had three different peaks. The nature of their stimuli likely

enhanced the visual segmentation of points beneath each peak, making clusters more

salient. In contrast, the cluster structure in our task may be visually less salient, as we

generated just 9 points from a unimodal (Gaussian, Laplacian, or Uniform) distribution.

Nevertheless, models without the partition stage did not explain the data well.

Gestalt psychologists (Koffka, 1935/2013) identified Gestalt rules underlying

perceptual organization (for review see (Kubovy & Gepshtein, 2003). Visual objects are

grouped together based on a similarity of spatial attributes and these new *Gestalten* are

assigned attributes including locations in space. The theory is descriptive and provides no

clear justification for why Gestalten such as clusters are part of our visual experience

(Jakel et al., 2016). The VCM offers two possible reasons for this.

First, the visual system can reduce the amount of information required to process

by summarizing parts. This becomes particularly advantageous as the number of visual

elements increases. It is not simply the clusters that are useful but the fact that there can

be many fewer clusters than sample points. Second, a cluster of points triggers useful

information for visual judgements beyond just spatial attributes. In the VCM, each cluster

defines its own location, which serves as an anchor where the likelihood of the center of

the generating PDF is evaluated. By combining these two advantages, the VCM reduces

the number of computations required to carry out the task analogous to the resource

rational principle in perception, cognition and decision-making (Lieder & Griffiths, 2019).

For instance, in Figure 5C, the likelihood of the location of the PDF underlying the sample

points is evaluated only at five cluster locations. Nevertheless, it approximates the

maximum likelihood estimation as if we applied a low-pass filter at the limited sampling

points. The resulting estimated likelihood function is not perfectly accurate. To compensate

for this, the VCM computes a weighted average of these sampling points based on their

estimated likelihoods. In this sense, Gestalten are not just fascinating visual illusions but

may also correspond to intermediate steps in optimal computations.

In Marr's framework of three levels of analysis (computational, algorithmic, or

implementational) (Marr, 1982), the VCM exists on the computational level, concerning

how we assign a location to 'whole' composed of 'parts' and what objective is optimized in

perceptual organization. The goal of the VCM can be interpreted as balancing task

accuracy with minimizing computational costs such as time (Griffiths et al., 2015). The

resource rational principle is considered a variant of Bayesian inference, which posits that

the visual system aims to identify the most plausible interpretation of the structure of the

image given its constituent visual elements (Froyen et al., 2015; Gershman et al., 2016;

Shivkumar et al., 2025).

How the VCM is implemented algorithmically or biologically is a separate question.

In particular, we implemented the first partition stage using two standard clustering

algorithms, a centroid-based K-means clustering (Hartigan & Wong, 1979) and a

connectivity-based hierarchical clustering (Nielsen, 2016; Shetty & Singh, 2021). We found

that both algorithms reproduced behavioral patterns equally well. It should be noted that

recent work has successfully modelled human perceptual experience from a clustering

perspective in tasks such as auditory streaming (Larigaldie et al., 2025), motion perception

(Gershman et al., 2016; Shivkumar et al., 2025), and the representation of uncertainty

(Sun et al., 2019). These studies employed a stochastic clustering approach called the

Chinese restaurant process, assuming that perceptual noise leads to variability in cluster

size. Such an approach may produce similar behavioral consequences as the clustering

algorithms we used.

In conclusion, we addressed a central question in perceptual organization

concerning how the 'whole' and its attributes are estimated from the attributes of individual

'parts'. We formalized a statistical version of this problem by presenting observers with

samples of points ('parts') drawn from three probability density functions (Gaussian,

Laplacian, and Uniform) and asking them to estimate the location of the center of the PDF

('whole'). We demonstrated that the observer's visual judgments can be explained by a

two-stage computational process: partition and global agreement. As such our findings

offer inspiration for building better models of perceptual organization concerning location

but also other spatial attributes such as shape, orientation, size, etc.

Methods and Materials

Participants

Twenty participants (mean age 22.9, range 18–29, 13 females, 7 males, 0 other) participated in the experiment. This study was approved by the University Committee on Activities Involving Human Subjects of New York University (IRB-FY2019-3450) and carried out in accordance with its approved guidelines. Informed consent was given by each participant before the experiment. None of the participants was aware of the hypotheses under test in the experiment. Participants received $12 per hour plus a performance-related bonus (average bonus: $16.90, range: $11–$24). They were informed that there could be a bonus. The experiment took approximately 2 hours.

Apparatus

Stimuli were displayed on a horizontal monitor (VPIXX, VIEWPIXX, 514 mm × 288 mm). The monitor resolution was 1920 × 1080 pixels with a 60-Hz refresh rate and we refer to location on the monitor by horizontal coordinates ranging from -257 mm to 257 mm and vertical coordinates -144 mm to 144 mm. The participants were seated at a viewing distance of 43 cm and manipulated a computer mouse to carry out tasks. All stimuli were presented and controlled using the Matlab Psychophysics Toolbox (Brainard, 1997; Pelli, 1997).

Training Task

Participants were first familiarized with the three distributional families: Gaussian, Laplacian, and Uniform (see Supplementary Figure 1A and Supplementary Video 1). In this training stage, participants were not yet asked to make any estimates but were asked to observe the population PDFs, the population means, and the samples drawn from these population distributions. On each trial, we plotted a PDF drawn from one of the three

distributional families and a sample from the same PDF. The origin (0,0) was set at the

vertical and horizontal center of the screen. The location $\boldsymbol{\mu}$ of the PDF was drawn

uniformly from the interval -100 mm and 100 mm. Following this, a sample of N points was

randomly drawn. The sample points were displayed underneath the shape of the PDF. The

points were discs with a radius of 1.5 mm and colored by the same color that was used to

draw the underlying PDF (for instance, red Gaussian; green Laplacian; blue Uniform). The

color codes were counter-balanced across participants.

The population variance σ^2 of all PDFs was fixed at 2500 mm^2. We added vertical

jitter to the vertical positions of the sample points to reduce the chance that sample points

would occlude one another. The variance of vertical jitter was fixed at 6.25 mm^2. To aid the

observer in interpreting the PDF and sample during training, we marked the location $\boldsymbol{\mu}$ of

the PDF by a white solid line segment and dashed lines (width: 2 mm, height: 35 mm).

During training, the sample size N was initially 300 and was gradually reduced to

50, 20 and finally 9. With 300 points the displayed sample could be readily matched to the

PDF from which it was drawn.

Presentation of the sample when N > 9 was extended across time: 18 additional

points were drawn every 100 ms from the underlying PDF until the required number of

points (300, 50, 20, or 9) points appeared on the screen. The sample points were

displayed for 2s. After an inter-trial interval of 1s, a new PDF with randomly chosen

location $\boldsymbol{\mu}$ was displayed together with a sample drawn from the PDF.

A distribution was chosen from one of the three distributional families (Gaussian,

Laplacian, and Uniform) and was repeated for five trials. In each trial, a new sample was

generated from the distribution chosen. After the presentation of 300 sample points in

groups of 15 = 5 x 3, the second block of 50 sample points started. The third block and the

fourth block used 20 and 9 points, respectively, giving 60 trials in total. The final sample

size ($N = 9$) was the one used in the main experimental task, the location task. The training

task provided substantial opportunity to observe typical Gaussian, Laplacian, and Uniform

samples while learning the color codes.

622   In the instructions, we used the following analogy:
623
624   On every trial, you will first see a white apple tree located somewhere on
625   the screen. You will then see a curve which tells you where the apples are most
626   likely to fall. The higher the curve is, the more likely an apple will fall below that
627   point on the curve. Where the curve is high, there probably will be more apples.
628   Where the curve is low, fewer. The density curve is always symmetric around the
629   apple tree. The horizontal location of the apple tree is not fixed but it will vary from
630   trial to trial along with the curve and the apples. The tree, the apples and the curve
631   will all move together from left to right on each trial. There are three types of
632   density curves from where apples will fall, each coded by color. One is bell-shaped
633   (red), the second is "pointy" (green), and the last is like a box (blue).
634
635
Visual Location Task [Main Experiment]

The stimuli in the visual location task were the same as in the visual training task with the

following differences: On each trial in the Visual Location Task, participants saw only a

colored-coded sample of N = 9 points randomly drawn from the Gaussian, Laplacian or

Uniform distribution. The PDF and the location of the PDF were not shown on the screen.

To help participants remember the three density curves, small icons representing the

shape of the three distributions were drawn near the top of the screen (see Supplementary

Figure 1B and Supplementary Videos 2&3).

644   Participants were asked to estimate the unknown position of the center (i.e.,

location μ) of the underlying PDF using only the positions of sample points. They could

move a white upward pointing arrow (10 mm) to any location on the screen using a mouse.

Participants set the arrow at a position where they believed the horizontal center of the

underlying PDF was located and clicked the mouse button to record their estimates. We

ignored the vertical displacement of the arrow in analyzing the observer's settings.

Following a response, we presented a white vertical line (35 mm) marking the

location of the underlying PDF as feedback on the error between the participant's

estimates and the true position of the center of the PDF. Participants received $500 - D^2$

points where D^2 is the squared magnitude of their error in mm. If the position of the

estimates perfectly matched the true center ($D^2 = 0$), the participant received 500 points.

Points received could be negative if the error in distance was above 22.4 mm or below -

22.4 mm. At the end of each trial, the estimation error (mm), the score (points) and the

cumulative score were presented as a graphical display for 1.5 s. Participants received a

bonus payment proportional to the total score they earned across all trials ($1 per 10,000

points). The estimator that maximized the participants' expected bonus for each

distribution family was the UMVUE for that distribution family.

We provided warm-up trials before the main experiment. During warm-up, the

sample size was initially 300 and gradually reduced to 50, 20, and 9. The warm-up task

became more difficult as the sample size was reduced. As in the training task, a

distribution was chosen from one of the three distributional families (Gaussian, Laplacian,

and Uniform) and was repeated for five trials. In each trial, a new sample was generated

from the distribution chosen, giving 15 = 5 x 3 trials for the first block of 300 sample points.

Then the second block of 50 sample points started. The third block and the fourth block

used 20 and 9 points, respectively, giving 60 warm-up trials in total. Following a short

break, the main experiment started. One block consisted of 10 trials. Samples from the

three distributions were interleaved across blocks. Each participant ran 90 blocks (30

blocks for each distribution) with a short break after every 6 blocks.

Uniformly Minimum Variance Unbiased Estimator among L-estimators

The Laplacian location family has no closed-form solution for its UMVUE. Therefore we

computed the unbiased L-estimator that minimized variance numerically as follows. We

denote the UMVUE among L-estimators as $UMVUE_L$.

Given the n × n covariance matrix Σ of the order statistics $X_1, ..., X_N$ we can

compute the choice of weights that leads to a minimum variance estimator as

680
$$w \propto \Sigma^{-1} e \qquad (11)$$

where $e = [1,1,...,1]'$, assuming that the correlations between the random variables are

non-zero (for proof, see Appendix A in Oruc et al., 2003), which is our case because the

random variables are ordered. We ran the numerical simulation by resampling the order

statistics 1,000,000 times and then computing the inverse of the covariance matrix and the

weights in Eq. 11. We normalized the weights so they sum to 1.

Measuring influence

Order statistics. We performed a regression analysis to estimate the influence of each

point in the sample on the participant's estimate of the position of the horizontal location of

the distribution (Gaussian, Laplacian, or Uniform) that had generated the sample. We

ordered 9 sample points in each sample in ascending order from the leftmost point to the

rightmost point. For each of the three distributions, we regressed the vector of the

participant's estimators $\mathbf{T^o}$ which contained 300 data points by the 300 by 9 matrix $\mathbf{X}$.

Columns were vectors of order statistics for each trial $\mathbf{X_{(1)}, ..., X_{(9)}}$. Our linear regression

model is thus $\mathbf{T^o = X\widehat{W}}$ where $\mathbf{\widehat{W}}$ is the estimated weight vector. We used an ordinary

least squares regression with the constraint that weights add to 1: $\sum_{i=1}^{9} \widehat{w}_i = 1$. We

estimated influence for each participant and each distribution family of the population

distribution. In addition, we estimated the weight vector of the visual cluster model by

regressing the vector of the visual estimates predicted by the VCM by the matrix **X**. For

each variant of the VCM, we retrieved their visual estimates from the best fit parameters in

each model (see *Model fitting and evaluation*). See Supplementary Figure 4 for the

estimated weights in each model. The influence measures are a sensitive way to uncover

how participants behave in carrying out the task and discover discrepancies between

human performance and optimal performance (Dal Martello et al., 2023; Ota et al., 2024;

Ota et al., 2025b; Ota et al., 2025a; Ota & Maloney, 2024).

Model fitting and evaluation

We fitted the model's visual estimates [Eq. 10] to the participant's estimates by minimizing

the negative log-likelihood of the observed estimates using Bayesian adaptive direct

search (BADS) (Acerbi & Ma, 2017). The data were collapsed across the three

distributional families. In the two-stage VCM, the grouping parameter K (i.e., the number

of clusters) in K-means clustering was estimated individually from each participant. The

global agreement parameter β and the bias term b were estimated respectively with the

following boundaries: $\beta \in [0,4]$, $b \in [-50,50]$. We grid searched K ranging from 1 to 9 in

steps of 1, optimized the other parameters for each value of K, and chose the

combination of K and other parameters that minimized negative log-likelihood. We also

used hierarchical clustering with single linkage to test whether the results of the VCM

depend on a clustering algorithm we chose. Instead of K, we used   as a

grouping parameter while other parameters remained the same. This parameter is a cutoff

threshold in millimeter. If the distance between two sample points or clusters is below a

threshold, these two are grouped into one cluster. To verify that we had found the global

minimum, we repeated the search process with different starting points. For model

comparison, we applied AICc—Akaike information criterion with a correction for finite

sample size—to each participant and each model as the information criterion for

goodness-of-fit (Burnham & Anderson, 2002; Hurvich & Tsai, 1989). AICc has a penalty

term which avoids potential overfitting and helps select the models that have fewer

parameters as Bayesian information criterion (BIC) does. Based on AICc values across

participants and across models, we computed the protected exceedance probabilities

(Rigoux et al., 2014; Stephan et al., 2009) using a Matlab function 'spm_BMS' in SPM 12

(https://www.fil.ion.ucl.ac.uk/spm/). The sign of AICc values was reversed by multiplying

with $-\frac{1}{2}$ such that an entry to the function 'spm_BMS' can be converted the log model

evidence (https://mbb-team.github.io/VBA-toolbox/wiki/BMS-for-groupstudies/).

Competing Interests

The authors declare no competing interests.

Author's Contributions

KO, QW, PM and LTM designed the experiment and analysis, QW and KO collected data. KO carried out the analyses. All authors contributed to developing and evaluating models and writing the article.

Acknowledgments

This research was supported by Grant-Aid for JSPS Fellows No. 17J07822 awarded to KO, by a Guggenheim Fellowship and a Fellowship from the Institute for Advanced Studies of Paris, awarded to LTM, and an ANR/NIH grant "Probabilistic models of perceptual grouping and segmentation in natural vision" (ANR-19-NEUC-0003-01) awarded to PM.

747 # Supplementary Information

Supplementary Figure 1. Training Task and Visual Location Task.

A. Training Task. Three distributional families were color-coded. On each trial, we presented one of the three PDFs with varying its location μ along the horizontal axis and a sample drawn from the same PDF. The sample size reduced from $N = 300$ to $N = 9$ between blocks. Participants were asked to observe a color-coded sample drawn from the

PDF with the same color code. **B. Visual Location Task**. On each trial, a sample of 9 points is drawn from one of the three distributional families with its location μ varied along the horizontal axis. Participants were asked to estimate the location of the invisible center of the PDF that had generated the sample by moving an arrow horizontally. Following a response, the true location of the center of the PDF was presented as a vertical line. A squared error and a score for a trial were also provided as feedback.

Supplementary Figure 2. Behavioral Performance did not Change Systematically Across Trials.

A. Total Score. The participant's total score in each location task is plotted across blocks. Data are averaged across all participants. The shaded areas indicate 99.7% confidence interval (± 3 SEM). Black horizontal lines are the theoretically maximum total score obtained by UMVUE that corresponds to each distribution family. Two-way within participant ANOVA, using the number of blocks (30) and the distribution family (3) as independent variables, shows neither main effect of the block (F [299, 5681] = 1.11, p = 0.095, partial η^2 = 0.055) nor a significant interaction between the block and the distribution (F [598, 11362] = 1.08, p = 0.091, partial η^2 = 0.054). **B. Squared Error.** The squared error between the participant's visual estimate and the true location of the center of the distribution is plotted versus trial. Two-way within-participant ANOVA, using the number of trials (300) and the distribution family (3) as independent variables, shows neither main effect of the block (F [29, 551] = 1.43, p = 0.069, partial η^2 = 0.070) nor a significant interaction between the block and the distribution (F [58, 1102] = 1.19, p =

0.155, partial η^2 = 0.059). **C. Estimated Weights (Influence).** To additionally confirm a
lack of learning effect over trials, we computed influence measures separately for the first,
the second, and the last 100 trials using a linear regression. The estimated weights are
averaged across all participants. The error bars indicate 99.7% confidence interval (± 3
SEM). A two-way within participant ANOVA, using the order of points (9) and the bin of
trials (3) as independent variables, shows no significant interaction between the order
index of the sample point and the trial bin in the Gaussian location task (F [16, 304] = 0.70,
p = 0.796, partial η^2 = 0.035), in the Laplacian location task (F [16, 304] = 0.74, p = 0.751,
partial η^2 = 0.038), nor in the Uniform location task (F [16, 304] = 1.22, p = 0.250, partial η^2
= 0.060).
789

Supplementary Figure 3. Pairwise Comparisons of the Estimated Weights.

A. The values of the estimated weights (influence measure) from the data are taken from Figure 4 and replotted as a bar graph as a function of the order statistics. **B.** Difference between the estimated weights and the weights employed by the UMVUE (for the Laplacian the UMVUE$_L$). In all panels, bars represent the average across participants. The error bars indicate 99.7% confidence interval (± 3 SEM).

801
802

Supplementary Figure 4. All Variants of the Visual Cluster Model.
The predictions of the estimated weights for each model in the factorial model comparison.
Regression weights estimated from the data are taken from Figure 4 and replotted as
colored squares. Mean model fits across observers are plotted as black solid lines while
shaded gray areas denote 99.7% confidence interval (± 3 SEM).

810
Supplementary Figure 5. Comparison of the Model Fit across Two Clustering Algorithms. A. A Comparison of AICc Scores. We adopted K-means clustering in the main text to fit the visual cluster model to the data. We repeated the clustering algorithm analysis using hierarchical clustering with single linkage. **B. Prediction of the Estimated Weights (Influence).** Regression weights estimated from the predictions of the VCM using hierarchical clustering. AICc scores and the estimated weights are almost identical between the two clustering algorithms (see Figure 6).

818
819

References

Acerbi, L., & Ma, W. J. (2017). Practical Bayesian optimization for model fitting with Bayesian adaptive direct search. *Advances in neural information processing systems*, *30*, 1834-1844.

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*, 433–436. https://doi.org/https://doi.org/10.1163/156856897X00357

Burnham, K. P., & Anderson, D. R. (2002). *Model Selection and Multimodel Inference* (2nd ed.). Springer.

Carandini, M., & Heeger, D. J. (2011). Normalization as a canonical neural computation. *Nat Rev Neurosci*, *13*(1), 51-62. https://doi.org/10.1038/nrn3136

D'Angelo, G., Voto, S., Iacono, M., Glover, A., Niebur, E., & Bartolozzi, C. (2025). Event-driven figure-ground organisation model for the humanoid robot iCub. *Nat Commun*, *16*(1), 1874. https://doi.org/10.1038/s41467-025-56904-9

Dal Martello, M. F., Ota, K., Pietralla, D. E., & Maloney, L. T. (2023). Detecting visual texture patterns in binary sequences through pattern features. *J Vis*, *23*(13), 1. https://doi.org/10.1167/jov.23.13.1

Froyen, V., Feldman, J., & Singh, M. (2015). Bayesian hierarchical grouping: Perceptual grouping as mixture estimation. *Psychol Rev*, *122*(4), 575-597. https://doi.org/10.1037/a0039540

Gershman, S. J., Tenenbaum, J. B., & Jakel, F. (2016). Discovering hierarchical motion structure. *Vision Res*, *126*, 232-241. https://doi.org/10.1016/j.visres.2015.03.004

Griffiths, T. L., Lieder, F., & Goodman, N. D. (2015). Rational use of cognitive resources: levels of analysis between the computational and the algorithmic. *Top Cogn Sci*, *7*(2), 217-229. https://doi.org/10.1111/tops.12142

Hampel, F. R., Ronchetti, E. M., & Rousseeuw, P. J. (1986). *Robust Statistics: The Approach Based on Influence Functions*. Wiley.

Hartigan, J. A., & Wong, M. A. (1979). Algorithm AS 136: A K-Means Clustering Algorithm. *Applied Statistics*, *28*(1). https://doi.org/10.2307/2346830

Huber, P. J. (1981). *Robust_statistics*. Wiley.

Hurvich, C. M., & Tsai, C.-L. (1989). Regression and time series model selection in small samples. *Biometrika*, *76*(2), 297-307. https://doi.org/10.1093/biomet/76.2.297

Jakel, F., Singh, M., Wichmann, F. A., & Herzog, M. H. (2016). An overview of quantitative approaches in Gestalt perception. *Vision Res*, *126*, 3-8. https://doi.org/10.1016/j.visres.2016.06.004

Jeurissen, D., van Ham, A. F., Gilhuis, A., Papale, P., Roelfsema, P. R., & Self, M. W. (2024). Border-ownership tuning determines the connectivity between V4 and V1 in the macaque visual system. *Nat Commun*, *15*(1), 9115. https://doi.org/10.1038/s41467-024-53256-8

Juni, M. Z., Singh, M., & Maloney, L. T. (2010). Robust visual estimation as source separation. *J Vis*, *10*(14), 2. https://doi.org/10.1167/10.14.2

Koffka, K. (1935/2013). *Principles of Gestalt psychology*. Routledge.

Kubovy, M., & Gepshtein, S. (2003). Perceptual grouping in space and in space-time: An exercise in phenomenological psychophysics. In R. Kimchi, M. Behrmann, & C. R. Olson (Eds.), *Perceptual organization in vision: Behavioral and neural perspectives* (pp. 57-98). Psychology Press.

Landy, M. S., Goutcher, R., Trommershauser, J., & Mamassian, P. (2007). Visual estimation under risk. *J Vis*, *7*(6), 4. https://doi.org/10.1167/7.6.4

Landy, M. S., Maloney, L. T., Johnston, E. B., & Young, M. (1995). Measurement and modeling of depth cue combination: in defense of weak fusion. *Vision Res*, *35*(3), 389-412. https://doi.org/10.1016/0042-6989(94)00176-m

Larigaldie, N., Yates, T., & Beierholm, U. R. (2025). Perceptual clustering in auditory streaming. *PLoS Comput Biol*, *21*(7), e1013189. https://doi.org/10.1371/journal.pcbi.1013189

Lehmann, E. L. (1983). *Theory of point estimation*. Springer.

Lieder, F., & Griffiths, T. L. (2019). Resource-rational analysis: Understanding human cognition as the optimal use of limited computational resources. *Behav Brain Sci*, *43*, e1. https://doi.org/10.1017/S0140525X1900061X

Louie, K., Khaw, M. W., & Glimcher, P. W. (2013). Normalization is a general neural mechanism for context-dependent decision making. *Proc Natl Acad Sci U S A*, *110*(15), 6139-6144. https://doi.org/10.1073/pnas.1217854110

Maloney, L. T., & Landy, M. S. (1989). A statistical framework for robust fusion of depth information. *Proceedings of the SPIE: Visual Communications and Image Processing IV*(1199), 1154-1163.

Maloney, L. T., & Thomas, E. A. C. (1991). Distributional assumptions and observed conservatism in the theory of signal detectability. *Journal of Mathematical Psychology*, *35*(4), 443-470. https://doi.org/10.1016/0022-2496(91)90043-s

Marr, D. (1982). *Vision: A computational investigation into the human representation and processing of visual information*. MIT Press.

McGowan, J. W., Kowler, E., Sharma, A., & Chubb, C. (1998). Saccadic localization of random dot targets. *Vision Res*, *38*(6), 895-909. https://doi.org/10.1016/s0042-6989(97)00232-0

Melcher, D., & Kowler, E. (1999). Shapes, surfaces and saccades. *Vision Res*, *39*(17), 2929-2946. https://doi.org/10.1016/s0042-6989(99)00029-2

Mood, A. M., Graybill, F. A., & C., B. D. (1974). *Introduction to the theory of statistics* (3rd ed.). McGraw-Hill.

Moreland, J. C., & Boynton, G. M. (2017). A neurophysiological explanation for biases in visual localization. *Atten Percept Psychophys*, *79*(2), 553-562. https://doi.org/10.3758/s13414-016-1251-z

Nielsen, F. (2016). Hierarchical Clustering. In *Introduction to HPC with MPI for Data Science* (pp. 195-211). https://doi.org/10.1007/978-3-319-21903-5_8

Nielsen, K. J., & Connor, C. E. (2024). How Shape Perception Works, in Two Dimensions and Three Dimensions. *Annu Rev Vis Sci*, *10*(1), 47-68. https://doi.org/10.1146/annurev-vision-112823-031607

Oruç, İ., Maloney, L. T., & Landy, M. S. (2003). Weighted linear cue combination with possibly correlated error. *Vision Research*, *43*(23), 2451-2468. https://doi.org/10.1016/s0042-6989(03)00435-8

Ota, K., Charles, L., & Haggard, P. (2024). Autonomous behaviour and the limits of human volition. *Cognition*, *244*, 105684. https://doi.org/10.1016/j.cognition.2023.105684

Ota, K., Christofilea, E., Charles, L., Daunizeau, J., & Haggard, P. (2025b). Freedom through understanding: instructed knowledge shapes voluntary action choices. *Preprint at PsyArXiv*. https://doi.org/https://doi.org/10.31234/osf.io/mgksv_v2

Ota, K., Ciston, A., Haggard, P., Gajdos, T., & Charles, L. (2025a). Integrating explicit reliability for optimal choices: effect of trustworthiness on decisions and metadecisions. *Preprint at bioRxiv*. https://doi.org/https://doi.org/10.1101/2025.01.12.632598

Ota, K., & Maloney, L. T. (2024). Dissecting Bayes: Using influence measures to test normative use of probability density information derived from a sample. *PLoS Comput Biol*, *20*(5), e1011999. https://doi.org/10.1371/journal.pcbi.1011999

Ota, K., Shinya, M., Maloney, L. T., & Kudo, K. (2019). Sub-optimality in motor planning is not improved by explicit observation of motor uncertainty. *Sci Rep*, *9*(1), 14850. https://doi.org/10.1038/s41598-019-50901-x

Papale, P., Zuiderbaan, W., Teeuwen, R. R. M., Gilhuis, A., Self, M. W., Roelfsema, P. R., & Dumoulin, S. O. (2024). V1 neurons are tuned to perceptual borders in natural scenes. *Proc Natl Acad Sci U S A*, *121*(46), e2221623121. https://doi.org/10.1073/pnas.2221623121

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: transforming numbers into movies. *Spatial Vision*, *10*(4), 437-442. https://doi.org/10.1163/156856897x00366

Rashid, J. A., & Chubb, C. (2022). On the flexibility of strategies for center estimation. *Vision Res*, *201*, 108125. https://doi.org/10.1016/j.visres.2022.108125

Reverdy, P., & Leonard, N. E. (2016). Parameter Estimation in Softmax Decision-Making Models With Linear Objective Functions. *IEEE Transactions on Automation Science and Engineering*, *13*(1), 54-67. https://doi.org/10.1109/tase.2015.2499244

Rigoux, L., Stephan, K. E., Friston, K. J., & Daunizeau, J. (2014). Bayesian model selection for group studies - revisited. *Neuroimage*, *84*, 971-985. https://doi.org/10.1016/j.neuroimage.2013.08.065

Shetty, P., & Singh, S. (2021). Hierarchical Clustering: A Survey. *International Journal of Applied Research*, *7*(4), 178-181. https://doi.org/10.22271/allresearch.2021.v7.i4c.8484

Shivkumar, S., DeAngelis, G. C., & Haefner, R. M. (2025). Hierarchical motion perception as causal inference. *Nat Commun*, *16*(1), 3868. https://doi.org/10.1038/s41467-025-58797-0

Stephan, K. E., Penny, W. D., Daunizeau, J., Moran, R. J., & Friston, K. J. (2009). Bayesian model selection for group studies. *Neuroimage*, *46*(4), 1004-1017. https://doi.org/10.1016/j.neuroimage.2009.03.025

Sun, J., Li, J., & Zhang, H. (2019). Human representation of multimodal distributions as clusters of samples. *PLoS Comput Biol*, *15*(5), e1007047. https://doi.org/10.1371/journal.pcbi.1007047

Tanae, M., Ota, K., & Takiyama, K. (2021). Competition Rather Than Observation and Cooperation Facilitates Optimal Motor Planning. *Frontiers in Sports and Active Living*, *3*. https://doi.org/10.3389/fspor.2021.637225

Tassinari, H., Hudson, T. E., & Landy, M. S. (2006). Combining priors and noisy visual cues in a rapid pointing task. *J Neurosci*, *26*(40), 10154-10163. https://doi.org/10.1523/JNEUROSCI.2779-06.2006

Trommershauser, J., Kording, K., & Landy, M. S. (2011). *Sensory cue integration*. Oxford University Press.

Trommershauser, J., Maloney, L. T., & Landy, M. S. (2008). Decision making, movement planning and statistical decision theory. *Trends Cogn Sci*, *12*(8), 291-297. https://doi.org/10.1016/j.tics.2008.04.010

Ullman, S. (1984). Visual routines. *Cognition*, *18*(1-3), 97-159. https://doi.org/10.1016/0010-0277(84)90023-4

Ullman, S., Vidal-Naquet, M., & Sali, E. (2002). Visual features of intermediate complexity and their use in classification. *Nat Neurosci*, *5*(7), 682-687. https://doi.org/10.1038/nn870

van den Berg, R., Awh, E., & Ma, W. J. (2014). Factorial comparison of working memory models. *Psychol Rev*, *121*(1), 124-149. https://doi.org/10.1037/a0035234

Vilares, I., Howard, J. D., Fernandes, H. L., Gottfried, J. A., & Kording, K. P. (2012). Differential representations of prior and likelihood uncertainty in the human brain. *Curr Biol*, *22*(18), 1641-1648. https://doi.org/10.1016/j.cub.2012.07.010

Wagemans, J., Elder, J. H., Kubovy, M., Palmer, S. E., Peterson, M. A., Singh, M., & von der Heydt, R. (2012). A century of Gestalt psychology in visual perception: I. Perceptual

959   grouping and figure-ground organization. *Psychol Bull*, *138*(6), 1172-1217.
960   https://doi.org/10.1037/a0029333
961 Wagemans, J., Feldman, J., Gepshtein, S., Kimchi, R., Pomerantz, J. R., van der Helm, P. A., & van
962   Leeuwen, C. (2012). A century of Gestalt psychology in visual perception: II. Conceptual
963   and theoretical foundations. *Psychol Bull*, *138*(6), 1218-1252.
964   https://doi.org/10.1037/a0029334
965 Zhang, H., Ren, X., & Maloney, L. T. (2020). The bounded rationality of probability distortion.
966   *Proc Natl Acad Sci U S A*, *117*(36), 22024-22034. https://doi.org/10.1073/pnas.1922401117
967
968
969

970