Cortical tracking of connected speech is interactively modulated by top-down predictions and bottom-up signal quality

James M. Webb[1,2] and Ediz Sohoglu[1]

       1.   School of Psychology, University of Sussex, Brighton, UK

    2.   MRC Cognition and Brain Sciences Unit, University of Cambridge, UK

Keywords: Predictive coding, Speech perception, Temporal Response Function, Cortical tracking, Top-down processing

Word count: 10,341

Number of figures: 8

Acknowledgements: This research was supported by a School of Psychology PhD studentship awarded to JW and School of Psychology start-up funds awarded to ES. We thank Yiming Zhang and Aine Glynn for assistance with data collection and Chris Racey for technical support.

Address correspondence to:

James Webb (james.webb@mrc-cbu.cam.ac.uk) or Ediz Sohoglu (E.Sohoglu@sussex.ac.uk)

Abstract

Prediction facilitates speech comprehension, but how predictions are combined with sensory input during perception remains unclear. Prior studies suggest that prediction error computations — which represent the difference between heard and expected speech sounds — play a central role in speech perception. However, these studies often rely on non-ecological listening conditions, involving isolated words predicted by artificial cues. In two experiments, we presented male and female participants with semantically coherent sentences that ended in words of varying predictability. We also manipulated the signal quality of the final word by applying time-specific degradation. Using linear encoding models of EEG responses, we found that neural representations of speech features were jointly influenced by top-down predictions and bottom-up signal quality. Specifically, for unpredicted final words, increasing signal quality resulted in enhanced neural tracking of spectral and temporal modulations. In contrast, for strongly predicted final words, greater signal quality led to reduced tracking of speech modulations. Computational simulations revealed that this interaction is consistent with prediction error computations, but not with alternative models such as signal sharpening. These findings extend the evidence for prediction error computations to more naturalistic listening situations.

Introduction

48   Because of the inherent ambiguity of naturalistic speech, listeners make use of prior
knowledge during speech perception. Prior knowledge encompasses not only linguistic
knowledge but also situational context and knowledge about the world. Understanding how
listeners integrate prior knowledge with sensory input is crucial for understanding the
mechanisms underlying speech perception.

It has been suggested that predictions are combined with the bottom-up speech
signal in a process of Bayesian inference (Davis & Sohoglu, 2020; Norris et al., 2016).
Under Bayesian inference, speech perception is a succession of inferences that combine
prior knowledge with incoming sensory data as the perceptual system attempts to find the
most likely interpretation of the speech signal. In doing so, the listener continuously adjusts
and refines their predictions given new sensory evidence.

Here we build on previous work seeking to establish how Bayesian inference is
implemented neurally. One possibility is that neural representations reflect a weighted
average of the sensory input and prior expectations (McClelland et al., 2014). Under this
account, more accurate predictions and higher signal quality should both act to enhance or
'sharpen' neural representations, just as they both act to enhance perceptual clarity.
Alternative models propose that sensory features are suppressed by predictions, with
unexpected features (prediction errors) prioritised for processing and updating predictions
(Gagnepain et al., 2012; Spratling, 2017). In predictive coding models, sharpened signal
representations and prediction errors are dually encoded in distinct neural populations
(Bastos et al., 2012; Rao & Ballard, 1999).

Using computational simulations, Blank and Davis (2016) demonstrate that prediction
errors are interactively modulated by prior expectations and signal quality. This is because
when predictions are accurate, prediction errors are more greatly suppressed as signal
quality increases. Yet when predictions are uninformative, increasing signal quality leads
instead to greater prediction errors as there is more information left 'unexplained'. Blank and
Davis (2016) observed exactly this interactive effect of prior expectation and signal quality
on multivoxel patterns in the superior temporal lobe. Using MEG and linear encoding
models, Sohoglu and Davis (2020) showed that this interaction is also apparent when
examining the extent to which the cortex 'tracks' speech acoustic features.

The findings above therefore suggest that neural responses encode prediction
errors, which imposes constraints on the underlying neural computations. They provide
direct support for predictive coding models and argue against models that only propose
sharpened signal computations. However, in this previous work, listeners heard single words
while prior knowledge was manipulated by presenting matching or nonmatching text before
the speech. This is far removed from real-world conditions where listeners need to combine
predictions with sensory input continuously (i.e. during perception of connected speech) and
often without the use of external cues. As such, these findings are susceptible to the
criticism that the prediction effects which occurred were encouraged by the experimental
design and may not be representative of naturalistic perception (Huettig & Mani, 2016).

In the two experiments reported here, listeners heard sentences in which strong or
weak predictions for the final word could be obtained from the preceding speech context
without external cues (see Figure 1A and 1B). To manipulate final word signal quality
independently of listeners' predictions, we developed a novel form of noise-vocoding that
allowed us to vary speech signal quality in a time-limited fashion i.e. separately during the
context and final word periods.

To examine how cortical tracking of speech is modulated by signal quality and prior
expectation, we regressed acoustic speech features against 64 channel EEG using
encoding models (Crosse et al., 2016). In a sharpened signal account, increasing signal
quality or prediction strength for the final word should result in improved tracking of the
heard word in neural responses (Figure 2C). Whereas in a prediction error account, there
should be an interaction effect such that increasing signal quality results in better tracking of
the heard word when final word predictions are weak and the opposite when predictions are
strong (Figure 2D).

Figure 1 Procedure. A) For Experiment 1, on each trial listeners heard a sentence with a weakly or strongly predicted final word. The final word was noise-vocoded using 2, 4, or 8 channels. The preceding sentence context was always highly intelligible (16 channel vocoded). Participants were required to rate the clarity of the final word in each sentence on a scale of 1 – 4. Example sentences are depicted along with final word cloze probabilities and context entropy. Time-frequency plots represent auditory spectrograms (Chi et al., 2005) for the sentence "In sailing you have to handle a lot of water". The vertical white line marks the onset of the final word (for visualisation purposes only as no silence was inserted between the context and final word). B) For Experiment 2, the final word was noise-vocoded using 4, 8, or 16 channels. The preceding sentence context was noise-vocoded using either 32 channels (highly intelligible) or 1 channel (unintelligible).

Figure 2 Computational simulations. A) *Model representations for the weakly predicted final word (/w O: t @/)*
in the sentence "In sailing you have to handle a lot of water", simulated in a high signal quality condition. Model
representations are visualised using word and segment clouds with larger text indicating higher probabilities and
segment labels denoting phonetic transcriptions in SAMPA format. (Top row) Word level representations show
posterior probabilities as each segment in the input is heard (only the ten words with the highest probabilities at
any one timepoint are shown for illustration purposes). Word posteriors provide predictions for which segment will
be heard next (second row, segment predictions shown in green). Segment predictions are then combined with
segment input probabilities ('Input', third row; shown in brown). **B)** *Segment predictions and input representations*
are combined through sharpened signal (multiplication) or prediction error (subtraction) computations with
outcomes depicted as purple and orange segment clouds, respectively (for the onset segment of water). **C)** *Mean*
pattern distances at final word onset (segment position 1) for the sharpened signal simulations. We simulated
Experiment 2 which comprised a more complete set of experimental conditions (including the unintelligible
context condition). Error bars represent the standard deviation. **D)** *Same as panel C but for the absolute*
prediction error.

Materials and Methods

Participants

All participants were native speakers of British English and had no history of hearing

impairment or neurological disease based on self-report. All participants were naive to the

purposes of the experiment. Different participants were recruited for the two experiments

and all were tested after being informed of the study's procedure, which was approved by

the University of Sussex Science and Technology Cross Schools Research Ethics

Committee. Participants were required to be between 18 and 35 years of age to take part.

The participants that were tested were between 18 and 29 years of age.

For Experiment 1, 34 participants were tested. One participant was excluded due to

failure to understand task instructions, and three participants were excluded due to technical

issues with the EEG recording. Therefore 30 participants were included in the final analysis,

of which 20 were female (mean = 21.06 years of age, SD = 2.15). Of the participants

included in the final analysis, one participant was left-handed.

For Experiment 2, 35 participants were tested. Four participants were excluded due

to technical issues with the EEG recording. Therefore 31 participants were included in the

final analysis, of which 19 were female (mean = 19.32 years old, SD = 1.05). Of the

participants included in the final analysis, three participants were left-handed.

Spoken stimuli

216 sentences were presented to each participant in spoken format. The sentences

were taken from Peelle et al. (2020), a study which reported completion norms from at least

100 participants for English written sentences of eight to ten words in length. From these

completion norms, Peelle et al. (2020) report final word cloze probabilities which are a widely

used measure of word predictability (Bloom & Fischler, 1980; Taylor, 1953) and are obtained

by computing the proportion of participants who completed the sentence with a particular

word.

For the 'strongly predicted' condition, we selected 108 sentences in which the final

word had a high cloze probability (ranging between 0.66 and 0.99; mean = 0.84, SD = 0.10).

For example, "He was late because he had gotten a flat **tyre**", which has a cloze probability

of 0.99. For the 'weakly predicted' condition, we selected 108 sentences in which the final

word had a low cloze probability (ranging between 0.02 and 0.10; mean = 0.07, SD = 0.02).

For example, "In sailing you have to handle a lot of **water**", which has a cloze probability of

0.03 (because participants tend to predict the alternative endings *ropes*, *wind* or *waves*). All

sentences were plausible and semantically coherent. Distributions of cloze probabilities are

shown in Figure 3A. Further examples of sentences are shown in Figure 1A.

In addition to cloze probabilities, Peelle et al. (2020) report a second measure of final

word predictability: entropy. Different to cloze probability (which relates to the prediction for a

single word), entropy relates to the distribution of predictions over multiple possible word

continuations and captures the constraint provided by sentence context prior to the final

word (measured in bits). Formally, entropy (*H*) is computed as follows:

169
$$H = -\sum_{i=1}^{n} p(x_i) log_2 p(x_i)$$

where p(x) is the probability distribution over words (measured here as the proportion of

participants completing the sentence with each word continuation).

Items with high entropy indicate sentence contexts that offer weak constraint as to

the identity of the final word whereas items with low entropy indicate sentence contexts with

strong constraints. In natural speech, these two measures of predictability are negatively

correlated (Gwilliams et al., 2020), although there are cases when both entropy and cloze

probability can be low. This occurs when hearing an unexpected word following a

constraining (low entropy) context. For example, after hearing the words "The little girl

tripped and immediately began to …", listeners will strongly predict the word *cry* and make

only weak predictions for other words. Accordingly, this sentence context is highly

constraining, and entropy is low. However, if this sentence ends instead with the word *fall*,

the final word is relatively unpredicted (low cloze probability) even though the context is

highly constraining. Thus, while both cloze probability and entropy are closely related

measures, they are not identical and together provide a more complete characterisation of

speech predictability.

In the current stimulus set, log cloze probability and entropy had a Pearson's

correlation coefficient of -.74. In the strongly predicted condition, entropy was relatively low

(ranging between 0.08 and 1.62; mean = 0.91, SD = 0.45) but in the weakly predicted

condition, entropy varied substantially (ranging between 0.55 and 5.43; mean = 2.85, SD =

1.04; see Figure 3A). So while the final word in the weakly predicted condition always had a

low cloze probability, this followed contexts varying in constraint.

After selecting the sentences, we recorded spoken versions from a male speaker of

southern British English. Recordings were acquired using an Audio Technica AT2035

condenser microphone and saved as 16-bit, 48 kHz wav files. The duration of the sentences

ranged from 2207 to 3978 ms (mean = 3006, SD = 376).

As shown in Figure 3B, the acoustic properties of the final word were well matched

between strongly and weakly predicted conditions. Using independent samples t-tests to

compare the strongly and weakly predicted conditions, we confirmed that there were no

reliable differences in final word duration ($t(214) = 1.76$, $p = .080$), intensity ($t(214) = 1.09$, p
$= .276$) and fundamental frequency ($t(214) = .228$, $p = .820$).

We used noise-vocoding to vary signal quality. The noise-vocoding procedure
(Shannon et al., 1995) superimposes the temporal-envelope from separate frequency
regions in the speech signal onto white noise filtered into corresponding frequency regions.
This allows parametric variation of signal quality (spectral detail), with increasing numbers of
channels associated with increasing intelligibility. Vocoding was performed using a custom
Matlab script (The MathWorks Inc), with the spectral channels spaced between 70 and 5000
Hz according to Greenwood's function (Greenwood, 1990). Envelope signals in each
channel were extracted using half-wave rectification and smoothing with a second-order low-
pass filter with a cut-off frequency of 30 Hz. The overall RMS amplitude was adjusted to be
the same across all audio files.

We adapted the standard noise-vocoding procedure to manipulate final word signal
quality independently of sentence context (i.e. the portion of the signal leading up to final
word onset). In Experiment 1, the sentence context portion of the sentence was noise-
vocoded using 16 spectral channels and therefore was highly intelligible (see Figure 1A).
The signal quality of the final word was manipulated by noise-vocoding using 2, 4 or 8
spectral channels. In Experiment 2, sentence context was noise-vocoded using either 32
channels (fully intelligible) or 1 channel (unintelligible) whilst the final word was noise-
vocoded using 4, 8 or 16 channels (see Figure 1B).

To achieve this separate noise-vocoding of the context and final word periods of the
sentence, we performed the following procedures. First, we noise-vocoded the entire
sentence (e.g. using 16 channels). Second, we noise-vocoded the same sentence using a
different number of channels (e.g. 2 channels). Third, we mixed the two signals using a
Hann window of 10 ms to transition from the 16 channel to 2 channel versions. The
combination of a Hann window and the stochastic nature of the noise carrier ensured that
there was no perceptible discontinuity between the two signals.

In Experiment 1, the assignment of sentences to final word signal quality conditions
was counterbalanced across participants. In Experiment 2, the assignment of sentences to
32 channel versus 1 channel context conditions was also randomised across participants.
For the 1 channel context condition, sentences were drawn equally from the strongly and
weakly predicted conditions.

Figure 3 Stimulus properties. A) Strongly predicted final words had higher cloze probabilities than weakly
predicted final words (upper graphs). In the strongly predicted condition, sentence contexts were also more
constraining on average (i.e. had lower entropy) than in the weakly predicted condition. B) There were no reliable
differences in final word duration, intensity, or pitch.

Procedure

Participants completed a clarity rating task in which they were required to rate the
clarity of the final word in each sentence. Participants were instructed to "*decide how clear*
the final word is on a scale of 1 to 4. This is a comparative task, so 1 = least clear when
compared to the other words; 4 = most clear when compared to the other words." For

Experiment 1, manipulations of final word signal quality (2 / 4 / 8 channels) and final word
prediction strength (strongly / weakly predicted) resulted in a 3 × 2 factorial design. For
Experiment 2, manipulations of final word signal quality (4 / 8 / 16 channels) and final word
prediction strength (strongly predicted / weakly predicted / 1 channel context) resulted in a 3
× 3 factorial design.

During trials, a fixation cross was always shown on screen, which consisted of a
white cross on a grey background. Each trial commenced with the presentation of a spoken
sentence, followed 1000 ms later with a cue for the participant to respond (consisting of the
fixation cross changing colour from white to black). Responses were recorded from the
participants left hand using the keyboard. The experimenter checked before the experiment
began that the participant was able to enter their intended response without looking at the
keyboard. Subsequent trials began 2000 (±0–100) ms after participants responded.

Both Experiments 1 and 2 consisted of six blocks of 72 trials each. In blocks 1 - 3, all
216 unique sentences were heard once in randomised order, with each block containing an
equal number of trials per condition. In blocks 4 - 6, each stimulus was repeated but in a
different randomised order. Before the experiment, participants completed two practice
sessions, each consisting of ten sentences. These contained equal numbers of strongly
predicted and weakly predicted trials.

Data acquisition and preprocessing

Sounds were presented via Sennheiser HD 380 Pro headphones and an M-Audio M-
Track solo external sound card**.** Stimulus delivery was controlled using PsychoPy software
(v2022.1.1 Open Science Tools Ltd).

EEG data were recorded with ASA-Lab using a 64 channel ANT Neuro amplifier with
a sampling rate of 1000 Hz and a 64 channel Waveguard EEG cap (ANT Neuro, Enschede),
with electrodes placed according to the extended 10-20 system and offline referenced to the
average across electrodes. Pre-processing of the EEG data was performed using the
SPM12 toolbox (Wellcome Trust Centre for Neuroimaging, London, UK) in MATLAB R2020b
(Mathworks, Inc. Natick, MA, USA) and data analyses were performed using custom
MATLAB scripts. EEG data were downsampled to 250 Hz and noisy channels reconstructed
from neighbouring channels. DC offsets were removed by subtracting the mean from each
channel. Robust detrending was then used to remove slow drifts (de Cheveigné &
Arzounian, 2018). Signal components corresponding to line noise (50 Hz) and the monitor
refresh rate (85 Hz) were removed using Zapline (de Cheveigné, 2020).

Independent components analysis was used to remove activity related to blinks and

eye movements. Identification of eye artefact components was achieved using an automatic

procedure based on multiple linear regression. Specifically, the signal from the vertical and

horizontal EOG sensors were used as predictor variables to regress against each ICA

component time-series. Prior to regression, EOG and ICA signals were first z-scored such

that each signal had a mean of zero and standard deviation of one. ICA components for

which R2 (variance explained) was above 0.25 was identified as eye-related activity and

subsequently projected out from the data.

For some participants, we removed blocks where the recording was excessively

noisy. For Experiment 1, a total of five blocks were removed (two blocks for two participants

and one block for one participant). For Experiment 2, one block was removed for each of two

participants.

Encoding Models

As in Sohoglu and Davis (2020), we used ridge regression to measure cortical

tracking of speech features (Brodbeck et al., 2018; Di Liberto et al., 2015; Ding & Simon,

2013; Holdgraf et al., 2017; Pasley et al., 2012). Our analysis approach is near-identical to

the one used in Sohoglu and Davis (2020). The analysis described below was done

separately for the context period (sentence onset to final word onset) and final word period

(final word onset to sentence offset).

Before model fitting, the EEG data were epoched at matching times as the feature

spaces (see below), and outlier trials removed. We then used the mTRF toolbox (Crosse et

al., 2016) to fit an encoding model that mapped from the stimulus features to the neural

time-series observed at each EEG sensor and at multiple time lags:

$$y = Sw + \varepsilon$$

Where y is the neural time-series recorded at each sensor, S is an $N_{samples}$ by $N_{features}$

matrix defining the stimulus feature space (concatenated over different lags), w is a vector of

model weights and ε is the model error. Model weights for positive and negative lags capture

the relationship between the speech feature and the neural response at later and earlier

timepoints, respectively. Encoding models were fitted with lags from -100 to 550 ms and

tested with a more restricted range of lags from 0 to 450 ms, to avoid contributions from

possible edge artefacts that can affect model weights.

To control for overfitting, we used ridge regression and varied the lambda parameter

(over 21 values as follows: 2^0, 2^1, 2^3, ... 2^{20}) which controls the degree to which strongly

positive or negative weights are penalised (Crosse et al., 2016). This lambda parameter was

optimized using a leave-one-trial-out cross-validation procedure. For each feature space,

sensor, condition, and participant, we fitted models using data from all but one trial. We then

averaged the model weights across trials and used the result to predict the EEG response of

the left-out trial. We computed model accuracy as the Pearson correlation between the

predicted and observed data and repeated this procedure such that model accuracies were

obtained for all trials. Before optimizing lambda, model accuracies were averaged across

trials and across sensors. The optimal lambda value was then selected as the mode of the

model accuracy distribution over participants and conditions (Holdgraf et al., 2016). Two

feature spaces were tested:

1.   Spectral and temporal modulations, capturing regular fluctuations in energy

across the frequency and time axes of the spectrogram (Chi et al., 2005;

Theunissen & Elie, 2014). We used the NSL toolbox in Matlab

(http://nsl.isr.umd.edu/downloads.html) to first compute a 128 channel 'auditory'

spectrogram (with constant Q and logarithmic centre frequencies between 180

and 7040 Hz), before filtering with 2D wavelet filters tuned to spectral

modulations of 0.5, 1, 2, 4, and 8 cycles per octave and temporal modulations of

1, 2, 4, 8, and 16 Hz. All other parameters were set to the default (frame

length = 12.5 ms, time constant = 12.5 ms and no nonlinear compression). Note

that temporal modulations can be positive or negative, reflecting the direction of

frequency sweeps (i.e. upward versus downward; Elliott & Theunissen, 2009).

This default representation is a very high-dimensional feature space: frequency ×

spectral modulation × temporal modulation × temporal modulation direction with

128 × 5 × 5 × 2 = 6400 dimensions, each represented for every 12.5 ms time

sample in the speech file. We therefore averaged over the 128 frequency

channels and positive- and negative-going temporal modulation directions. The

resulting feature space was a time-varying representation of spectral and

temporal modulation content comprised of 25 features (five spectral modulations

x five temporal modulations). The method and parameters for extracting this

feature space are identical to Sohoglu and Davis (2020).

2.   Broadband envelope, capturing time-varying acoustic energy in a broad 180–

7040 Hz frequency range. This feature space was obtained by summing the

spectral channels in the auditory spectrogram described above.

These feature spaces were obtained from the original clear versions of the spoken

stimuli (i.e. before noise-vocoding) and downsampled to 80 Hz to match the EEG sampling

rate. The feature spaces were then z-score transformed such that each time-series on every

trial had a mean of zero and standard deviation of 1. When examining encoding of the final

word, the audio signal was zero-padded after audio offset to match the duration of the

longest positive lag (i.e. 550 ms). This enabled information at the end of each spoken word

to inform the model fits for positive lags. No zero-padding was deemed necessary when

examining speech encoding during the sentence context period, given the longer duration of

the sentence context (average duration = 2,360 ms, SD = 255 ms) as compared with the

final word (average duration = 652 ms, SD = 117 ms).

To examine cortical tracking in individual neural frequencies, we computed the

coherence between the encoding model predictions and the observed EEG data (see

Donhauser & Baillet, 2020), using the same cross-validation scheme as for the model

accuracy analysis. Spectral coefficients were estimated using the Fourier transform and a

Hanning taper over a 5 second window. We analysed model coherences at individual neural

frequencies in steps of 0.2 Hz within the delta/theta range (0-8 Hz), which previous work has

implicated in cortical tracking of speech features (Di Liberto et al., 2018; Donhauser &

Baillet, 2020).

Source reconstruction of encoding model weights

To determine the underlying brain sources of the encoding model effects, we used a

distributed method of source reconstruction, implemented within the parametric empirical

Bayes framework of SPM12 (Henson et al., 2011; Litvak & Friston, 2008; Phillips et al.,

2005). The forward model was computed using a Boundary Element model and sensor

positions projected onto an MNI space template brain (sensor positions were as specified by

the ANT neuro template). For inversion of the forward model, we used the 'LOR' routine in

SPM12, which assumes that all sources are activated with equal *a priori* probability and with

weak correlation to neighbouring sources. This was applied to the encoding model weights

from -50 to 500 ms lags, averaged over all temporal modulations and over 2 to 8 cycles per

octave.

Source solutions were constrained to be consistent across subjects, which has been

shown to improve group-level statistical power (Litvak & Friston, 2008). In brief, this

procedure involves 1) realigning and concatenating sensor-level data across subjects 2)

estimating a single source solution for all subjects 3) using the resulting group solution as a

Bayesian prior on individual subject inversions. Thus, this method exploits the availability of

repeated measurements (from different subjects) to constrain source reconstruction.

Importantly, however, this procedure does not bias activation differences between conditions

in a given source.

To analyse condition-wise effects on source activity, we focus on the earliest period

(-50 to 50 ms) when an interaction between prediction strength and signal quality was

observed in sensor space. Source power from 0 to 40 Hz within this period was summarised

using a Morlet wavelet projector (Friston et al., 2006). Statistical maps of source activity are

displayed using an FDR corrected threshold of $p < .05$.

Computational modelling

To guide interpretation of the neural data, we simulated sharpened signal and

prediction error representations using a Bayesian model of spoken word recognition (Norris

& McQueen, 2008), as implemented in Sohoglu et al. (2024). At the word level (illustrated as

the green word clouds in Figure 2A), we computed a posterior distribution over a lexicon of

73,120 words, by combining word priors and likelihoods using Bayes rule. Word priors were

based on the cloze response probabilities provided by Peelle et al. (2020) while word

likelihoods were computed by combining segment input probabilities (derived from acoustic

similarities; see below for further details). This was done iteratively at each segment position

in the stimulus word.

Consider for example the sentence context "In sailing you have to handle a lot of …".

While *water* (SAMPA transcription: / w O: t @ /) is a plausible completion of this sentence,

this word is only weakly predicted ($p = 0.03$) in comparison with other words such as *ropes*

($p = 0.32$), *wind* ($p = 0.27$) or *waves* ($p = 0.12$). Following /w/ at segment position 1 in the

stimulus, word likelihoods (i.e. the sensory evidence) are updated. When combined with

word priors, this leads to higher posterior probabilities for words starting with the segment

/w/ (e.g. *water*, *wind*, *waves* etc.) and lower probabilities for other words (e.g. *ropes*, *sails*

etc.). At this point, *water* is not yet the most probable word because *wind* also matches the

sensory input and has a stronger prior probability ($p = 0.27$ versus $p = 0.03$). However,

following a further phoneme at segment position 2 (the vowel /O:/), word likelihoods are

again updated and combined with word priors, making *water* the most probable word. In this

way, we computed a word posterior distribution at each segment position in the stimulus

word.

The above computations perform Bayesian inference at the word level. In predictive

processing models, top-down predictions from higher hierarchical levels are propagated to

lower levels (Aitchison & Lengyel, 2017; Rao & Ballard, 1999; Spratling, 2017). Indeed,

previous evidence suggest that cortical responses to speech are well explained by predictive

computations occurring at the segment level (Brodbeck et al., 2022; Gagnepain et al., 2012).

To compute predictions for each upcoming segment (shown as green phonetic symbols in

Figure 2A), we summed lexical level posterior probabilities over words sharing the next

segment. This enabled the expression of predictions for each of 44 phonemes (i.e. the

model's phonological inventory) at each segment position. Returning to the example above,

following /w/ at segment position 1, predictions are made for the segment /I/ (for *wind*) but

also /O:/ (for *water*). Because *wind* is more strongly predicted by the sentence context than

water (p = 0.27 vs p = 0.03), the next segment prediction for /I/ is also stronger than for /O:/.

By segment position 2 however (after the vowel /O:/), sufficient sensory evidence has

accumulated to favour *water* as the most probable word candidate. In turn, this leads to a

strong prediction that the next segment is /t/. This example illustrates that predictions for

speech segments in the model are determined not only by word priors from sentence

context but also by accumulating sensory evidence as the speech signal unfolds.

Following the computation of these segment predictions, we generated two model

outputs differing in the way that sensory evidence for each of the 44 phoneme segments in

the model's phonological inventory was combined with the segment predictions. Under the

sharpened signals simulation, the model output was calculated by multiplying segment

predictions with segment input probabilities (normalising to sum to one). Under the

prediction error simulation, the model output was calculated by subtracting segment

predictions from the segment input probabilities. These computations were performed

iteratively for each segment position in the unfolding stimulus word.

Therefore, at each segment position in the unfolding stimulus word, sharpened

signals or prediction errors comprise a vector of 44 segments (the model's phonological

inventory). To summarise these vectors at each segment position, we computed the

Euclidean pattern distance between the vectors for all pairs of items within each condition

(see Sohoglu et al., 2024). For example, we computed the distance between the vector for

the onset segment of *water* with that of *beagle*; between *water* and *pass*; between *water* and

money; between *beagle* and *water*; between *beagle* and *pass* etc. Pattern distances were

computed for segment positions 1-3 only since fewer stimuli were available for later segment

positions. We then averaged the pattern distances for all stimuli presented to each

participant.

This pattern distance analysis of our simulations quantifies the amount of speech
information content in sharpened signals and prediction errors, with larger pattern distances
indicative of increased information content (Kriegeskorte & Kievit, 2013). We assume a
correspondence between this information content and the acoustic modulation features used
in the neural tracking analysis i.e. enhanced pattern distances associated with stronger
neural tracking.

The model's lexicon (including phonetic transcriptions) was derived from the CELEX
database (Baayen, 1993). For the unintelligible context condition, final word prior
probabilities in the model's lexicon were set to normalised word frequencies from CELEX.
For final words in strongly predicted and weakly predicted sentences, the prior probabilities
were set to the cloze response probabilities provided by Peelle et al. (2020). Any word in the
model's lexicon for which there was no response was set to a small non-zero prior
probability. Specifically, we set to $\frac{1}{n} \times freq$ where *n* is the size of the model's lexicon and
freq is a weighting factor based on normalised word frequency from CELEX. This adjustment
ensured there were no words with a prior probability of zero, which is ill-defined for Bayesian
inference (Davis & Sohoglu, 2020). Following this adjustment, prior word probabilities were
normalised to sum to one.

The sensory evidence for different words (i.e. likelihoods) was computed by applying
the product rule across the individual segment (input) probabilities spanning each word
(Norris & McQueen, 2008). Segment input probabilities were derived from the acoustic
similarity between individual speech segments. This means that an unfolding word's sensory
evidence is strong if its constituent segments match internal representations that are
acoustically dissimilar to other speech sounds in the language. It is also strong if there are
few word competitors sharing the same speech segments.

To derive segment input probabilities, acoustic representations were first extracted
from 4 channel noise-vocoded versions of the sentences, including both context and final
words. Acoustic representations were generated by computing a 128 channel 'auditory'
spectrogram for each segment using the NSL toolbox and averaging over time. Segment
onset times were obtained using a forced-alignment algorithm included as part of BAS
software (Kisler et al. 2017; https://clarin.phonetik.uni-
muenchen.de/BASWebServices/interface/WebMAUSGeneral).

In total there were 44 unique segments, averaged over 8065 repeated tokens
(median token count = 142). Acoustic representations were vectorized and averaged over

multiple productions of the same segment. We then obtained a between-segment similarity

matrix using negative Euclidean distances and normalised each row of this matrix using the

softmax function (combined with a temperature parameter) such that each row could be

interpreted as segment probabilities. We simulated the three levels of signal quality in

Experiment 2 by adjusting the temperature parameter so that the averaged probability of a

segment (i.e. the average probability over the on-diagonal elements in the segment matrix)

corresponded to .17, .66 and .94. These probabilities simulate the intelligibility levels

(proportion correct) observed in previous studies for the three levels of signal quality (4, 8

and 16 channels) used in Experiment 2 (e.g. McGettigan et al., 2014; Sohoglu et al., 2012).

Data availability statement

Stimuli, data and analysis scripts will be made available on OSF upon publication of

this manuscript.

Results

Overview of experiments

In two experiments, listeners heard sentences in which strong or weak predictions for

the final word could be obtained from the preceding sentence context (see Figure 1A and

1B). To manipulate final word signal quality independently of listeners' predictions, we used

noise-vocoding to vary spectral detail separately during the context and final word periods.

In Experiment 1 (Figure 1A), the sentence context portion was always highly

intelligible (16 channel vocoded) but the final word varied between 2, 4 and 8 channels. In

Experiment 2 (Figure 1B), we presented sentences in which the final word was noise-

vocoded with 4, 8 or 16 spectral channels, enabling a more extreme manipulation of signal

quality. In Experiment 2, we also presented the context portion of the sentences with either

32 spectral channels (highly intelligible) or 1 channel (unintelligible). The latter condition was

presented so that we could observe neural responses when listeners are unable to make

predictions for the final word.

Computational simulations: At word onset

To confirm that our experimental paradigm can distinguish sharpened signals from

prediction errors, we performed simulations of sharpened signal and prediction error

computations. Both sharpened signal and prediction error computations are derived from

posterior word probabilities, as estimated using Bayes theorem (see Methods). We applied

this model to the stimuli of Experiment 2 where signal quality and prediction strength varied

more extremely than in Experiment 1.

Example model outputs are shown in Figure 2A and 2B for the final word in the

weakly predicted sentence "In sailing you have to handle a lot of **water**". To summarise the

results of these simulations, we quantified how strongly speech content was represented in

simulated sharpened signals (Figure 2C) and prediction errors (Figure 2D). We achieved this

by computing the dissimilarity between model representations (Euclidean pattern distances)

for all pairs of items within each condition. We focus on the model's responses at final word

onset (segment position 1) as this is the earliest position at which predictions can be

combined with the speech input. In a subsequent section, we will present the model's

responses at later segment positions.

As shown in Figure 2C and 2D, whereas final word prediction strength and signal

quality both act to enhance sharpened signals, these manipulations have opposite effects on

prediction errors. The opposing effects on prediction errors take the form of a crossover

interaction. In particular, increasing signal quality results in increased prediction error when

the final word is unpredicted (unintelligible context and weakly predicted conditions). The

opposite effect – reduced prediction error with increasing signal quality – occurs when the

final word is strongly predicted. These simulations therefore confirm that our experimental

manipulations should produce different outcomes if neural responses reflect sharpened

signals versus prediction errors.

Experiment 1

Behaviour

In Experiment 1, the sentence context portion was always highly intelligible (16

channel vocoded) but the final word varied between 2, 4 and 8 channels (see Figure 1A). As

shown in Figure 4A, final word clarity ratings were enhanced not only by final word signal

quality ($F(1.32, 38.37) = 752.42$, $p < 0.001$) but also by final word prediction strength ($F(1,$

$29) = 83.42$, $p < 0.001$). There was also an interaction between final word prediction strength

and signal quality ($F(2, 58) = 9.68$, $p < 0.001$). Visual inspection of the data in Figure 4A

suggests that this interaction reflects an increased influence of prediction strength in the 2

channel and 4 channel conditions, as compared with the 8 channel condition. These results

confirm that both signal quality and prediction strength enhance speech clarity.

Figure 4 Behavioural results. A) *Ratings of final word clarity in Experiment 1, with each participant represented*

by a different line and group averages shown as thicker lines. Error bars show within-subject standard error of

the mean (Loftus & Masson, 1994). **B)** *Ratings of final word clarity in Experiment 2.*

Cortical tracking: Model accuracies

Previous results show that cortical tracking of speech is driven more by spectral and
temporal modulations than other speech features (Sohoglu & Davis, 2020). Moreover,
cortical tracking of speech modulations is affected by prediction congruency and signal
quality (Sohoglu & Davis, 2020). To confirm that this modulation feature space is also a
good model for the present EEG data, we compared model accuracy for the modulation
feature space with that of a baseline feature space (broadband envelope) that has been
widely used in previous cortical tracking studies (Crosse et al., 2016, 2021).

On a per-participant basis, model accuracies were averaged over conditions and the
20 sensors with the highest model accuracy were selected. This was done separately for the
modulation and envelope feature spaces. The modulation feature space explained EEG
neural responses more accurately than the envelope, both for the sentence context period
(Figure 5A; $t(29) = 13.00$, $p < .001$) and for the final word period (Figure 5B; $t(29) = 9.74$, $p <$
$.001$). This confirms that the modulation space is a good model for the present EEG data
and therefore in subsequent analyses, we report cortical tracking results using only the
modulation feature space.

We next examined how cortical tracking of speech modulations was affected by final
word prediction strength and signal quality, focussing first on the sentence context period
(Figure 5C). Note that speech features (modulations) were obtained from the original clear
versions of the spoken stimuli i.e. before noise-vocoding. This facilitated comparison of
model accuracies under different signal quality (vocoder channel) conditions, since any
model accuracy differences can be attributed to neural encoding rather than acoustic
differences attributable to the signal quality manipulation.

There was no main effect of final word prediction strength ($F(1, 29) = .002$, $p = .96$)
on model accuracies. Nor was there a main effect of final word signal quality ($F(1.98, 57.39)$
$= 1.69$, $p = .19$) or two-way interaction ($F(1.96, 56.88) = .96$, $p = .39$). Non-significant effects
involving final word signal quality were as expected in Experiment 1 because during
sentence context, the signal quality was always the same (16 channels). While in principle
there might have been an effect of prediction strength during this period driven by prediction
entropy (as explained in Methods), the results in Experiment 1 indicate no impact of
prediction on cortical tracking before the onset of the final word.

For the critical final word period (Figure 5D), there was a significant main effect of
prediction strength ($F_{(1, 29)} = 8.18$, $p = .008$), reflecting larger model accuracies in the
strongly predicted versus weakly predicted conditions. There was also a significant
interaction between final word prediction strength and signal quality ($F_{(1.99, 57.79)} = 3.32$, p
$= .04$). From visual inspection of Figure 5D, this significant interaction appears driven by an
increase in model accuracy with final word signal quality in the weakly predicted condition,
which was not apparent or perhaps even reversed in the strongly predicted condition.
However, follow-up testing shows that there was only a trend for a significant signal quality
effect in the weakly predicted condition ($F_{(1.64, 47.60)} = 2.56$, $p = .1$). In the strongly
predicted condition, there was also no significant effect of final word signal quality ($F_{(1.79,}$
$_{52.04)} = .46$, $p = .62$).

To summarise, our cortical tracking analysis for the critical final word period suggests
an interaction between prediction strength and signal quality. As explained in the
Introduction, an interaction is diagnostic of the prediction error account. However, the
precise form of the interaction revealed in the present experiment seems less conclusive. In
particular, we do not observe a decrease in speech representation with increasing signal
quality when predictions are strong. This is the key pattern that would favour prediction
errors over the sharpened signals account (see Figure 2C and 2D).

Figure 5 Cortical tracking (model accuracy) results for Experiment 1. A) *Condition-averaged model accuracies for the modulation and envelope feature spaces, during the sentence context period.* **B)** *Same as panel A but for the final word period.* **C)** *By-condition model accuracies for the modulation feature space, during the sentence context period. Sensor selections are indicated in the topography as the percentage of participants for which a sensor was selected. Individual participant data and error bars are shown after removing between-subject variance, suitable for repeated-measures comparisons (Loftus & Masson, 1994). Error bars represent standard error of the mean.* **D)** *Same as panel C but for the final word period.*

Experiment 2

In Experiment 1, we observed robust effects of final word prediction strength and signal quality on neural encoding of speech modulations. However, these results did not clearly distinguish sharpened signal from prediction error accounts. One explanation for this is the range of speech signal quality that listeners heard: the critical final word in each noise-vocoded sentence was presented with 2, 4 or 8 spectral channels. The clearest 8 channel condition is less clear than the equivalent condition in previous work (12 vocoder channels;

see Blank & Davis, 2016; Sohoglu & Davis, 2020) and may have limited the impact of signal

quality on neural representations.

Therefore, in Experiment 2 we presented sentences in which the final word was

noise-vocoded with 4, 8 or 16 spectral channels, enabling a more extreme manipulation of

signal quality (Figure 1B). In addition, we presented the context portion of the sentences with

either 32 spectral channels (highly intelligible) or 1 channel (unintelligible). By including a

condition in which the sentence context was unintelligible, we can observe neural responses

when listeners are unable to make any predictions before the final word is heard (Figure 1B).

Consequently, in Experiment 2 the manipulation of prediction strength was also more

extreme than in Experiment 1.

Behaviour

As shown in Figure 4B, final word clarity ratings were enhanced not only by final

word signal quality ($F_{(2, 60)} = 1{,}050.71$, $p < 0.001$) but also by final word prediction strength

($F_{(1.16, 34.69)} = 178.45$, $p < 0.001$). There was also an interaction between final word

prediction strength and signal quality ($F_{(3.12, 93.68)} = 10.21$, $p < 0.001$). These results are

essentially identical to that observed in Experiment 1. Follow-up comparisons show that final

word clarity ratings in the weakly predicted condition were higher than in the unintelligible

context condition ($F_{(1, 30)} = 155.36$, $p < 0.001$). In turn, clarity ratings were higher in the

strongly predicted than in the weakly predicted conditions ($F_{(1, 30)} = 205.03$, $p < 0.001$).

This suggests that prediction strength had a graded effect on speech clarity.

Cortical tracking: Model accuracies

As in Experiment 1, we examined how prediction strength and final word signal

quality affected cortical tracking of speech modulations. This was done separately for

sentence context and for final word periods.

For the sentence context period (Figure 6A), there was no main effect of final word

signal quality ($F_{(1.97, 59.03)} = .59$, $p = .56$) on model accuracies. Nor was there a two-way

interaction ($F_{(3.35, 100.65)} = .52$, $p = .69$). As in Experiment 1, non-significant effects

involving final word signal quality were as expected during the sentence context period i.e.

before the final word was heard. However, there was a significant main effect of final word

prediction strength ($F_{(1.73, 52.00)} = 8.78$, $p = .001$). Visual inspection of the data in Figure

6A indicates that this main effect is caused by higher model accuracies in the weakly

predicted and strongly predicted conditions, as compared with the unintelligible context

condition (in which no predictions for the final word could be made). This is to be expected

because in the unintelligible context condition, the speech was vocoded using 1 channel,

compared to 32 channels in the weakly and strongly predicted conditions. Therefore during

sentence context, greater signal quality (and, hence, greater intelligibility) results in

increased cortical tracking of speech modulations, consistent with previous work (Ahissar et

al., 2001; Luo & Poeppel, 2007; Peelle et al., 2013). Analysis of spectral coherence between

the encoding model's predictions and the observed EEG data (see Methods) may indicate

an origin in the low frequency (< 2 Hz) delta band but these coherence effects do not survive

FDR correction for multiple comparisons across frequencies (Figure 6C).

For the critical final word period (Figure 6B), there was a significant interaction effect

between final word prediction strength and signal quality ($F_{(3.63, 108.93)} = 11.54$, $p < .001$).

Given this interaction, we performed one-way ANOVAs to examine the effect of final word

signal quality separately for 1 channel (unintelligible), weakly predicted and strongly

predicted conditions. For the unintelligible context condition, model accuracies increased

with increasing final word signal quality ($F_{(1.93, 57.94)} = 15.04$, $p < .001$). For the weakly

predicted condition, there was no significant effect ($F_{(1.75, 52.47)} = .28$, $p = .73$). Critically,

in the strongly predicted condition, increasing final word signal quality had the opposite

effect on model accuracies as compared with the unintelligible context condition i.e. reduced

model accuracies with increasing signal quality ($F_{(1.85, 55.41)} = 5.43$, $p = .008$). These

results are more consistent with prediction errors than sharpened signals (compare with

Figure 2C and 2D). Analysis of spectral coherence (Figure 6D) indicates that this interactive

influence of final word prediction strength and signal quality on cortical tracking arises in the

low frequency (< 2 Hz) delta band ($p < .05$ FDR corrected for multiple comparisons across

frequencies).

Figure 6 Cortical tracking (model accuracy) results for Experiment 2. A) By-condition model accuracies for
the modulation feature space, during the sentence context period. Sensor selections are indicated in the
topography as the percentage of participants for which a sensor was selected. Individual participant data and
error bars are shown after removing between-subject variance, suitable for repeated-measures comparisons
(Loftus & Masson, 1994). Error bars represent standard error of the mean. B) Same as panel A but for the final
word period. C) Model coherence during the sentence context period. The heatmap indicates which frequencies
show coherence differences for selected contrasts (positive differences shown in red; negative differences in
blue; dark colours represent effects FDR corrected across frequency while light/transparent colours indicate
uncorrected differences). The blue line to the left shows model coherence averaged over conditions. D) Same as
panel C but for the final word period.

Cortical tracking: Model weight analysis

The analyses discussed in the section above reflect cortical tracking of speech
modulations over a range of time lags (0 to 450 ms). To examine the timecourse of the
neural interaction between final word prediction strength and signal quality, we analysed the

encoding model weights i.e. temporal response functions (TRFs). We first analysed TRFs in

sensor space, summarised as the RMS amplitude over sensors. Sensor selections were the

same as those used for the model accuracy analysis (previously shown in Figure 6A and

6B). All effects are reported after applying a p < .05 threshold with FDR correction for

multiple comparisons over lag and modulation features.

As shown in Figure 7A, TRF weight amplitudes during the sentence context period

were larger in the weakly and strongly predicted conditions versus the unintelligible (1

channel) context condition. This effect closely followed stimulus change (-50 to 50 ms lag;

shown as red patches) and extended into negative latencies. This latter observation may

suggest a predictive neural signal, reflecting e.g. pre-activation of speech features (Etard &

Reichenbach, 2019). However, as noted by Teoh et al. (2022), encoding models may not

always be as highly temporally resolved as they may appear, due to the autocorrelational

structure of speech. We therefore refrain from drawing strong conclusions concerning

negative latency effects. Regardless, the increase in TRF weights for the weakly and

strongly predicted conditions (in which speech was noise-vocoded using 32 channels),

suggests that differential tracking of speech due to spectral detail occurs within 50 ms of

stimulus change. This finding is consistent with previous work showing early cortical tracking

of acoustic features (e.g. speech envelope tracking within 30 ms; Brodbeck et al., 2018). At

a later latency (approximately 175 ms), TRF amplitudes were modulated in the opposite

direction i.e. decreased response for weakly/strongly predicted versus unintelligible context

conditions (shown as blue patches).

As shown in Figure 7B, TRF weight amplitudes during the final word period show a

pattern highly consistent with the previous model accuracy analysis. For the unintelligible

context condition, TRFs increased with increasing final word signal quality while the opposite

occurred in the strongly predicted condition i.e. reduced TRFs with increasing signal quality.

As with the previous model accuracy analysis, there was no effect of signal quality in the

weakly predicted condition. These results, as with the model accuracy analysis in Figure 6B,

are more consistent with the prediction error than sharpened signal account. Effects of

signal quality on TRFs are first apparent around stimulus change (-50 to 50 ms lag) but

continue into later lags (until around 400 ms).

We further localised the TRFs to the underlying brain sources (see Methods). For

this source analysis, we first averaged the weights over speech modulation features,

between 2 and 8 cycles per octave. It is this spectral modulation range that is most impacted

by noise-vocoding (degrading spectral fine structure; Sohoglu & Davis, 2020) and therefore

might signal mismatch with top-down predictions. This modulation range also shows an

interaction between final word prediction strength and signal quality in sensor space (shown

previously in Figure 7B). We further focus on the earliest period (-50 to 50 ms) as this period

may better capture the primary consequences of our experimental manipulations (as

opposed to secondary post-perceptual effects). For both the sentence context and final word

periods, changes in TRFs localise to perisylvian cortex bilaterally including the superior

temporal gyrus (shown in the cortex renderings at the bottom of Figure 7A and 7B). This

region has previously been implicated as a source of prediction errors during single word

processing (Blank & Davis, 2016; Gagnepain et al., 2012; Sohoglu et al., 2024).

To more selectively isolate the interaction effect between prediction strength and

signal quality during the final word period, we tested for the conjunction of the signal quality

effect (16 versus 4 channels) in the unintelligible and strongly predicted conditions. This

revealed a more focal effect in the posterior portion of the right superior temporal gyrus as

well as the left inferior partial lobule (Figure 7C).

Figure 7 TRF model weights in Experiment 2. A) TRF model weights during the sentence context period. The heatmap indicates which speech features and lags show weight differences for selected contrasts (positive differences shown in red; negative differences in blue; dark colours represent effects FDR corrected across speech features while light/transparent colours indicate uncorrected differences). Brain plots overlay source-transformed weights onto an MNI-template cortical surface, averaged from -50 to 50 ms lags and over selected speech features (2 to 8 cycles per octave and over all temporal modulations). B) Same as panel A but for the final word period. C) Same as panel B but for the conjunction contrast [16ch > 4ch (1ch context)] AND [16ch < 4ch (Strongly predicted)].

Computational simulations: Timecourse analysis

While the EEG results of Experiment 2 favour a prediction error account, one discrepancy between the simulated and observed data occurs in the weakly predicted condition. Simulated prediction errors at word onset increase with signal quality in the weakly predicted condition. However, cortical tracking does not vary (compare Figure 2D and Figure 6B). One possible explanation for this is apparent in the model outputs depicted in Figure 2A for the final word in "In sailing to have to handle a lot of **water**". For this item, predictions for the final word are weak (prior word probability of .03). However, by segment position 2 (after hearing the vowel /O:/), the unfolding sensory evidence is sufficient to rule out alternative word candidates and provide support in favour of the stimulus word (i.e. a higher posterior probability for the word *water*). This in turn strengthens predictions for subsequent stimulus segments in positions 3-4. Therefore, although this word is weakly predicted at word onset, it becomes more strongly predicted as the stimulus unfolds in time. This temporal build-up of prediction strength (in what is nominally a weakly predicted condition) could in turn produce a prediction error response similar to that observed in the strongly predicted condition. When averaged over segment position, changes in prediction error attributable to signal quality would then appear as an intermediate pattern between that of the unintelligible context condition (in which no predictions are possible) and that of the strongly predicted condition. This pattern could also be reflected in the EEG TRF analysis, which measures the time-averaged relationship between speech and neural responses i.e. over all segment positions.

To test this possibility, we examined simulated prediction errors not just at word onset (as previously depicted in Figure 2D), but for multiple segment positions (shown in Figure 8A). For completeness, we did the same for the sharpened signal simulations (Figure 8B). Note that the temporal dimension for this analysis is fundamentally different to the temporal (by lag) dimension of the TRF analysis (previously depicted in Figure 7). The by-lag analysis of TRF weights examined the magnitude of neural tracking at different time delays between speech and neural responses, averaged over the temporal extent of the final word (as explained above). By contrast, the present simulations examine processing segment-by-segment within the final word.

Consistent with the explanation above, prediction errors in the weakly predicted condition decrease rapidly during segment positions 2 and 3 when final word signal quality is high (16 channels). This decrease comes about because the increased sensory evidence in

the high signal quality condition enables more accurate predictions as the stimulus word

builds up over time. This produces a response in the weakly predicted condition that more

closely resembles the strongly predicted condition. When averaged over segment position

(shown in Figure 8C), prediction errors in the weakly predicted condition remain unchanged

with increasing signal quality, as observed in the EEG data (compare Figure 8C with Figure

6B).

Figure 8 Computational simulations by stimulus segment position. A) *Mean pattern distances for simulated prediction errors as a function of stimulus segment position. Error bars show the standard deviation.* **B)** *Same as panel A but for sharpened signals.* **C)** *Pattern distances for simulated prediction errors averaged over segment position.*

Discussion

In this study we sought to determine how top-down predictions are combined with the

sensory signal during perception of connected speech. In two experiments, we observed

additive effects of final word signal quality and prediction strength on clarity ratings. Yet

these manipulations had an interactive influence on final word neural tracking, which was

most clearly observed in Experiment 2. This interactive influence on neural tracking emerged

rapidly (within 50 ms of the ongoing speech signal), in low frequency delta frequencies and

localized to perisylvian cortex bilaterally, including the superior temporal gyrus.

We tested whether neural responses reflect sharpened signals or prediction errors.

As with previous work (Blank & Davis, 2016; Sohoglu & Davis, 2020), these computations

were instantiated through model simulation, which confirmed distinct neural outcomes for

sharpened signals versus prediction errors. In Experiment 1, while final word neural tracking

was reliably modulated by prediction strength, we failed to observe reliable effects of signal

quality. Overall, the pattern of results did not clearly favour either computation. However, in

Experiment 2 when signal quality and prediction strength varied more extremely, we

observed a clear crossover interaction on neural tracking of a form that appears highly

consistent with prediction errors. Taken together these results suggest that cortical

responses predominantly reflect the difference between neural representations of heard and

predicted speech sounds.

The present results complement previous work demonstrating neural signatures of

prediction error using fMRI (Blank & Davis, 2016) and MEG (Sohoglu & Davis, 2020).

However, in this previous work, listeners heard isolated words and made predictions using

external written cues. Thus, the present study goes beyond this previous work in

demonstrating the operation of prediction error computations in a more ecological setting.

The present paradigm is more naturalistic not only because of the use of sentences (versus

single words) but also because listeners' predictions were based on information intrinsic to

the speech signal rather than on external (i.e. written) cues. Our findings parallel other

recent work demonstrating prediction errors from speech-intrinsic information (Sohoglu et

al., 2024), albeit in the context of single word listening.

Our work joins several previous studies that have also investigated how speech

predictability modulates neural tracking of connected speech (Baltzell et al., 2017; Corcoran

et al., 2023; Di Liberto et al., 2018; Holdgraf et al., 2016; Karunathilake et al., 2023; Molinaro

et al., 2021). Many of these studies make use of the "pop-out" effect, which refers to the

marked increase in perceptual clarity that listeners experience when degraded speech is

presented shortly after hearing the undegraded version or seeing a written transcription
(Davis et al., 2005). Using this paradigm, previous intracranial (Holdgraf et al., 2016) and
scalp (Baltzell et al., 2017; Corcoran et al., 2023; Di Liberto et al., 2018) neurophysiology
studies are generally convergent in suggesting that top-down predictions enhance neural
tracking (although see Karunathilake et al., 2023). Aside from the non-ecological nature of
this experimental design (as it is rare in natural listening to hear exact repeats of an
utterance), it is notable that most of these studies presented speech at a fixed (low to
intermediate) level of signal quality. However, when signal quality is low, increased neural
tracking of predicted versus unpredicted speech is in fact consistent with both sharpened
signal and prediction error accounts (as can be seen in the computational simulations
depicted in Figure 2C and 2D). To adjudicate between sharpened signals and prediction
errors, we suggest that it is necessary to jointly manipulate top-down predictions and
bottom-up signal quality. Furthermore, as the results of Experiment 1 demonstrate, the
bottom-up signal quality must be manipulated over a sufficiently varied range, from highly
distorted to highly intelligible speech. Based on Experiment 1 alone, one might favour a
sharpened signal account, since the observed pattern (enhanced neural representation of
strongly versus weakly predicted stimuli) has previously been interpreted as reflecting
sharpened signal computations (Kok et al., 2012). However, by manipulating signal quality
more extremely in Experiment 2 and examining the impact on neural and simulated
representations, the present study demonstrates a cross-over interaction between prediction
strength and signal quality that clearly favours the prediction error account.

A key feature of our study was the use of time-limited noise-vocoding, in which
differing levels of noise-vocoding were applied to the sentence context and final word
periods. This was critical to enable a situation in which strong top-down predictions were met
with highly distorted speech input, as was the case in the low signal quality, strongly
predicted condition. This would not have been possible had we applied low signal quality
noise-vocoding to the entire sentence (Obleser & Kotz, 2010, 2011), since final words in
strongly predicted sentences would have become less predicted following a low signal
quality (less intelligible) sentence context. Therefore, it is only through time-limited noise-
vocoding that we were able to independently manipulate final word prediction strength and
signal quality, which as discussed above is critical for testing sharpened signal and
prediction error accounts.

In addition to the analysis of model accuracies, for Experiment 2 we also analysed
the model weights linking speech features with EEG responses at specific time lags i.e.
TRFs (Crosse et al., 2016; Holdgraf et al., 2017). The interactive influence of prediction

strength and signal quality on the TRFs closely lagged stimulus change (within 50 ms) and

localised to acoustic-phonetic regions in the superior temporal lobe. Early latency effects in

auditory regions support the proposal that prediction errors are evident already at lower

sensory levels of processing (Alink et al., 2010; Murray et al., 2002; Thomas et al., 2024)

and may signal graded (acoustic) mismatch between expected and heard speech sounds

(Sohoglu & Davis, 2016, 2020).

Complementing the temporal analysis discussed above, we also examined final word

neural tracking in individual neural frequencies. We observed neural tracking in low

frequency delta activity which peaked at an 'ultra low' peak frequency of 0.6 Hz. Within this

low frequency delta range, we observed the prediction error interaction between final word

signal quality and prediction strength. This low frequency locus is notable as many neural

tracking studies highpass filter neural responses above 1 Hz, which may attenuate a 1 Hz

prediction error signal given filter transition bandwidths (Widmann et al., 2015). One of the

notable exceptions to this is the MEG study reported by Donhauser and Baillet (2020) which

demonstrated a low frequency delta signal that tracked speech predictability (phoneme

surprisal) in TED talks (see also Klimovich-Gray et al., 2021; Mai & Wang, 2023; Slaats et

al., 2023; Weissbart et al., 2019). Considered in conjunction with the present results, we

suggest that low frequency neural activity may be particularly important for signalling

prediction error.

Finally, our computational simulations explain why neural tracking in the weakly

predicted condition diverges from the pattern we had initially expected under the prediction

error account. When examining simulated prediction errors at final word onset, increasing

signal quality should result in elevated prediction errors in the weakly predicted condition,

much like in the unintelligible context condition when no prediction is possible. However, in

both experiments we failed to observe a reliable effect of signal quality on final word neural

tracking in this condition. Follow-up simulations examined prediction error not only at word

onset but also at later segments. In the weakly predicted condition, these simulations

produced a pattern that, when averaged across segment positions, more closely resembled

the observed EEG data. This occurs because, although the final word may be weakly

predicted at its onset, it becomes more strongly predicted as sensory evidence accumulates,

simultaneously reducing segment predictions for competitor words.

These temporal dynamics mimic the lexical competition behaviour of cognitive

models of spoken word recognition (Marslen-Wilson & Tyler, 1980; McClelland & Elman,

1986; Norris, 1994). They are also reminiscent of the notion of 'explaining away' in predictive

coding models of vision (Spratling, 2016). In these models, new visual input (e.g. image of a

face) results in an iterative minimisation of prediction errors by top-down predictions until

competing interpretations are suppressed. Notably however, for a dynamic signal such as

speech, the cortex must not only minimise prediction errors for what has just been heard but

also for subsequent word segments (Millidge et al., 2024). It is this latter aspect that is

revealed by our simulations – prediction errors at word onset leading to updated predictions

for future word segments.

One limitation of the encoding analysis method utilised here is that we are unable to

examine neural tracking segment-by-segment as this would result in too few observations

for the linear regression. This precludes us from directly testing whether the computational

simulations match the EEG data on a segment-by-segment basis. Future work is therefore

needed to enable the linking of neural responses with specific moments in the speech

signal, potentially using alternative methods such as representational similarity analysis

(Kriegeskorte & Kievit, 2013). The temporal dynamics of the present simulations suggest

that this avenue of research is a potentially powerful means of understanding and testing

neural implementations of predictive processing.

References

Ahissar, E., Nagarajan, S., Ahissar, M., Protopapas, A., Mahncke, H., & Merzenich, M. M. (2001). Speech comprehension is correlated with temporal response patterns recorded from auditory cortex. *Proceedings of the National Academy of Sciences of the United States of America*, *98*(23). https://doi.org/10.1073/pnas.201400998

Aitchison, L., & Lengyel, M. (2017). With or without you: predictive coding and Bayesian inference in the brain. In *Current Opinion in Neurobiology* (Vol. 46). https://doi.org/10.1016/j.conb.2017.08.010

Alink, A., Schwiedrzik, C. M., Kohler, A., Singer, W., & Muckli, L. (2010). Stimulus predictability reduces responses in primary visual cortex. *Journal of Neuroscience*, *30*(8). https://doi.org/10.1523/JNEUROSCI.3730-10.2010

Baayen, R. H. , P. R. , & V. R. H. (1993). The CELEX lexical database (CD-ROM). In *Philadelphia Linguistics Data Consortium University of Pennsylvania (Vol. 358)*.

Baltzell, L. S., Srinivasan, R., & Richards, V. M. (2017). The effect of prior knowledge and intelligibility on the cortical entrainment response to speech. *Journal of Neurophysiology*, *118*(6). https://doi.org/10.1152/jn.00023.2017

Bastos, A. M., Usrey, W. M., Adams, R. A., Mangun, G. R., Fries, P., & Friston, K. J. (2012). Canonical Microcircuits for Predictive Coding. In *Neuron* (Vol. 76, Issue 4). https://doi.org/10.1016/j.neuron.2012.10.038

Blank, H., & Davis, M. H. (2016). Prediction Errors but Not Sharpened Signals Simulate Multivoxel fMRI Patterns during Speech Perception. *PLoS Biology*. https://doi.org/10.1371/journal.pbio.1002577

Bloom, P. A., & Fischler, I. (1980). Completion norms for 329 sentence contexts. *Memory & Cognition*, *8*(6). https://doi.org/10.3758/BF03213783

Brodbeck, C., Bhattasali, S., Cruz Heredia, A. A. L., Resnik, P., Simon, J. Z., & Lau, E. (2022). Parallel processing in speech perception with local and global representations of linguistic context. *ELife*, *11*. https://doi.org/10.7554/eLife.72056

Brodbeck, C., Hong, L. E., & Simon, J. Z. (2018). Rapid Transformation from Auditory to Linguistic Representations of Continuous Speech. *Current Biology*. https://doi.org/10.1016/j.cub.2018.10.042

Chi, T., Ru, P., & Shamma, S. A. (2005). Multiresolution spectrotemporal analysis of complex sounds. *The Journal of the Acoustical Society of America*, *118*(2). https://doi.org/10.1121/1.1945807

Corcoran, A. W., Perera, R., Koroma, M., Kouider, S., Hohwy, J., & Andrillon, T. (2023). Expectations boost the reconstruction of auditory features from electrophysiological responses to noisy speech. *Cerebral Cortex (New York, N.Y. : 1991)*, *33*(3). https://doi.org/10.1093/cercor/bhac094

Crosse, M. J., Di Liberto, G. M., Bednar, A., & Lalor, E. C. (2016). The multivariate temporal response function (mTRF) toolbox: A MATLAB toolbox for relating neural signals to

continuous stimuli. *Frontiers in Human Neuroscience*, *10*(NOV2016).
https://doi.org/10.3389/fnhum.2016.00604

Crosse, M. J., Zuk, N. J., Di Liberto, G. M., Nidiffer, A. R., Molholm, S., & Lalor, E. C. (2021).
Linear Modeling of Neurophysiological Responses to Speech and Other Continuous
Stimuli: Methodological Considerations for Applied Research. In *Frontiers in
Neuroscience* (Vol. 15). https://doi.org/10.3389/fnins.2021.705621

Davis, M. H., & Sohoglu, E. (2020). Three Functions of Prediction Error for Bayesian
Inference in Speech Perception. In *The Cognitive Neurosciences*.
https://doi.org/10.7551/mitpress/11442.003.0022

de Cheveigné, A. (2020). ZapLine: A simple and effective method to remove power line
artifacts. *NeuroImage*, *207*. https://doi.org/10.1016/j.neuroimage.2019.116356

de Cheveigné, A., & Arzounian, D. (2018). Robust detrending, rereferencing, outlier
detection, and inpainting for multichannel data. *NeuroImage*, *172*.
https://doi.org/10.1016/j.neuroimage.2018.01.035

Di Liberto, G. M., Lalor, E. C., & Millman, R. E. (2018). Causal cortical dynamics of a
predictive enhancement of speech intelligibility. *NeuroImage*, *166*.
https://doi.org/10.1016/j.neuroimage.2017.10.066

Di Liberto, G. M., O'Sullivan, J. A., & Lalor, E. C. (2015). Low-frequency cortical entrainment
to speech reflects phoneme-level processing. *Current Biology*, *25*(19).
https://doi.org/10.1016/j.cub.2015.08.030

Ding, N., & Simon, J. Z. (2013). Adaptive temporal encoding leads to a background-
insensitive cortical representation of speech. *Journal of Neuroscience*, *33*(13).
https://doi.org/10.1523/JNEUROSCI.5297-12.2013

Donhauser, P. W., & Baillet, S. (2020). Two Distinct Neural Timescales for Predictive
Speech Processing. *Neuron*, *105*(2). https://doi.org/10.1016/j.neuron.2019.10.019

Elliott, T. M., & Theunissen, F. E. (2009). The modulation transfer function for speech
intelligibility. *PLoS Computational Biology*, *5*(3).
https://doi.org/10.1371/journal.pcbi.1000302

Etard, O., & Reichenbach, T. (2019). Neural speech tracking in the theta and in the delta
frequency band differentially encode clarity and comprehension of speech in noise.
Journal of Neuroscience, *39*(29). https://doi.org/10.1523/JNEUROSCI.1828-18.2019

Friston, K., Henson, R., Phillips, C., & Mattout, J. (2006). Bayesian estimation of evoked and
induced responses. *Human Brain Mapping*, *27*(9), 722–735.
https://doi.org/10.1002/hbm.20214

Gagnepain, P., Henson, R. N., & Davis, M. H. (2012). Temporal predictive codes for spoken
words in auditory cortex. *Current Biology*, *22*(7).
https://doi.org/10.1016/j.cub.2012.02.015

Greenwood, D. D. (1990). A cochlear frequency-position function for several species—29
years later. *Journal of the Acoustical Society of America*, *87*(6).
https://doi.org/10.1121/1.399052

Gwilliams, L., Davis, M., & Davis, M. H. (2020). Extracting language content from speech
sounds: An information theoretic approach. *Hal*.

Henson, R. N., Wakeman, D. G., Litvak, V., & Friston, K. J. (2011). A Parametric Empirical
Bayesian Framework for the EEG/MEG Inverse Problem: Generative Models for Multi-
Subject and Multi-Modal Integration. *Frontiers in Human Neuroscience*, *5*(August), 1–
16. https://doi.org/10.3389/fnhum.2011.00076

Holdgraf, C. R., De Heer, W., Pasley, B., Rieger, J., Crone, N., Lin, J. J., Knight, R. T., &
Theunissen, F. E. (2016). Rapid tuning shifts in human auditory cortex enhance speech
intelligibility. *Nature Communications*, *7*. https://doi.org/10.1038/ncomms13654

Holdgraf, C. R., Rieger, J. W., Micheli, C., Martin, S., Knight, R. T., & Theunissen, F. E.
(2017). Encoding and decoding models in cognitive electrophysiology. In *Frontiers in
Systems Neuroscience* (Vol. 11). https://doi.org/10.3389/fnsys.2017.00061

Huettig, F., & Mani, N. (2016). Is prediction necessary to understand language? Probably
not. *Language, Cognition and Neuroscience*, *31*(1).
https://doi.org/10.1080/23273798.2015.1072223

Karunathilake, I. M. Dushyanthi., Kulasingham, J. P., & Simon, J. Z. (2023). Neural Tracking
Measures of Speech Intelligibility: Manipulating Intelligibility while Keeping Acoustics
Unchanged. *BioRxiv*.

Klimovich-Gray, A., Barrena, A., Agirre, E., & Molinaro, N. (2021). One Way or Another:
Cortical Language Areas Flexibly Adapt Processing Strategies to Perceptual and
Contextual Properties of Speech. *Cerebral Cortex*, *31*(9).
https://doi.org/10.1093/cercor/bhab071

Kok, P., Jehee, J. F. M., & de Lange, F. P. (2012). Less Is More: Expectation Sharpens
Representations in the Primary Visual Cortex. *Neuron*, *75*(2).
https://doi.org/10.1016/j.neuron.2012.04.034

Kriegeskorte, N., & Kievit, R. A. (2013). Representational geometry: Integrating cognition,
computation, and the brain. In *Trends in Cognitive Sciences* (Vol. 17, Issue 8).
https://doi.org/10.1016/j.tics.2013.06.007

Litvak, V., & Friston, K. (2008). Electromagnetic source reconstruction for group studies.
NeuroImage, *42*(4), 1490–1498. https://doi.org/10.1016/j.neuroimage.2008.06.022

Loftus, G. R., & Masson, M. E. J. (1994). Using confidence intervals in within-subject
designs. *Psychonomic Bulletin & Review*, *1*(4). https://doi.org/10.3758/BF03210951

Luo, H., & Poeppel, D. (2007). Phase Patterns of Neuronal Responses Reliably Discriminate
Speech in Human Auditory Cortex. *Neuron*, *54*(6).
https://doi.org/10.1016/j.neuron.2007.06.004

Mai, G., & Wang, W. S. Y. (2023). Distinct roles of delta- and theta-band neural tracking for
sharpening and predictive coding of multi-level speech features during spoken
language processing. *Human Brain Mapping*, *44*(17).
https://doi.org/10.1002/hbm.26503

Marslen-Wilson, W., & Tyler, L. K. (1980). The temporal structure of spoken language
understanding. *Cognition*, *8*(1). https://doi.org/10.1016/0010-0277(80)90015-3

McClelland, J. L., & Elman, J. L. (1986). The TRACE model of speech perception. *Cognitive
Psychology*.

McClelland, J. L., Mirman, D., Bolger, D. J., & Khaitan, P. (2014). Interactive activation and mutual constraint satisfaction in perception and cognition. *Cognitive Science*, *38*(6). https://doi.org/10.1111/cogs.12146

McGettigan, C., Rosen, S., & Scott, S. K. (2014). Lexico-semantic and acoustic-phonetic processes in the perception of noise-vocoded speech: Implications for cochlear implantation. *Frontiers in Systems Neuroscience*, *8*(FEB). https://doi.org/10.3389/fnsys.2014.00018

Millidge, B., Tang, M., Osanlouy, M., & Bogacz, R. (2024). Predictive Coding Networks for Temporal Prediction. *PLOS Computational Biology*, *20(4)*. https://doi.org/10.32470/ccn.2023.1262-0

Molinaro, N., Lizarazu, M., Baldin, V., Pérez-Navarro, J., Lallier, M., & Ríos-López, P. (2021). Speech-brain phase coupling is enhanced in low contextual semantic predictability conditions. *Neuropsychologia*, *156*. https://doi.org/10.1016/j.neuropsychologia.2021.107830

Murray, S. O., Kersten, D., Olshausen, B. A., Schrater, P., & Woods, D. L. (2002). Shape perception reduces activity in human primary visual cortex. *Proceedings of the National Academy of Sciences of the United States of America*, *99*(23). https://doi.org/10.1073/pnas.192579399

Norris, D. (1994). Shortlist: a connectionist model of continuous speech recognition. *Cognition*, *52*(3). https://doi.org/10.1016/0010-0277(94)90043-4

Norris, D., & McQueen, J. M. (2008). Shortlist B: A Bayesian Model of Continuous Speech Recognition. *Psychological Review*, *115*(2). https://doi.org/10.1037/0033-295X.115.2.357

Norris, D., McQueen, J. M., & Cutler, A. (2016). Prediction, Bayesian inference and feedback in speech recognition. *Language, Cognition and Neuroscience*, *31*(1). https://doi.org/10.1080/23273798.2015.1081703

Obleser, J., & Kotz, S. A. (2010). Expectancy constraints in degraded speech modulate the language comprehension network. *Cerebral Cortex*, *20*(3). https://doi.org/10.1093/cercor/bhp128

Obleser, J., & Kotz, S. A. (2011). Multiple brain signatures of integration in the comprehension of degraded speech. *NeuroImage*, *55*(2). https://doi.org/10.1016/j.neuroimage.2010.12.020

Pasley, B. N., David, S. V., Mesgarani, N., Flinker, A., Shamma, S. A., Crone, N. E., Knight, R. T., & Chang, E. F. (2012). Reconstructing speech from human auditory cortex. *PLoS Biology*, *10*(1). https://doi.org/10.1371/journal.pbio.1001251

Peelle, J. E., Gross, J., & Davis, M. H. (2013). Phase-locked responses to speech in human auditory cortex are enhanced during comprehension. *Cerebral Cortex*, *23*(6). https://doi.org/10.1093/cercor/bhs118

Peelle, J. E., Miller, R. L., Rogers, C. S., Spehar, B., Sommers, M. S., & Van Engen, K. J. (2020). Completion norms for 3085 English sentence contexts. *Behavior Research Methods*, *52*(4). https://doi.org/10.3758/s13428-020-01351-1

Phillips, C., Mattout, J., Rugg, M. D., Maquet, P., & Friston, K. J. (2005). An empirical Bayesian solution to the source reconstruction problem in EEG. *NeuroImage*, *24*(4), 997–1011. https://doi.org/10.1016/j.neuroimage.2004.10.030

Rao, R. P. N., & Ballard, D. H. (1999). Predictive coding in the visual cortex: A functional interpretation of some extra-classical receptive-field effects. *Nature Neuroscience*, *2*(1). https://doi.org/10.1038/4580

Shannon, R. V., Zeng, F. G., Kamath, V., Wygonski, J., & Ekelid, M. (1995). Speech recognition with primarily temporal cues. *Science*, *270*(5234). https://doi.org/10.1126/science.270.5234.303

Slaats, S., Weissbart, H., Schoffelen, J. M., Meyer, A. S., & Martin, A. E. (2023). Delta-Band Neural Responses to Individual Words Are Modulated by Sentence Processing. *Journal of Neuroscience*, *43*(26). https://doi.org/10.1523/JNEUROSCI.0964-22.2023

Sohoglu, E., Beckers, L., & Davis, M. H. (2024). Convergent neural signatures of speech prediction error are a biological marker for spoken word recognition. *Nat Commun*, *15, 9984*, 2023.10.03.560649. https://doi.org/10.1101/2023.10.03.560649

Sohoglu, E., & Davis, M. H. (2016). Perceptual learning of degraded speech by minimizing prediction error. *Proceedings of the National Academy of Sciences of the United States of America*, *113*(12). https://doi.org/10.1073/pnas.1523266113

Sohoglu, E., & Davis, M. H. (2020). Rapid computations of spectrotemporal prediction error support perception of degraded speech. *ELife*, *9*. https://doi.org/10.7554/eLife.58077

Sohoglu, E., Peelle, J. E., Carlyon, R. P., & Davis, M. H. (2012). Predictive top-down integration of prior knowledge during speech perception. *Journal of Neuroscience*, *32*(25). https://doi.org/10.1523/JNEUROSCI.5069-11.2012

Spratling, M. W. (2016). A neural implementation of Bayesian inference based on predictive coding. *Connection Science*, *28*(4). https://doi.org/10.1080/09540091.2016.1243655

Spratling, M. W. (2017). A review of predictive coding algorithms. In *Brain and Cognition* (Vol. 112). https://doi.org/10.1016/j.bandc.2015.11.003

Taylor, W. L. (1953). "Cloze Procedure": A New Tool for Measuring Readability. *Journalism Quarterly*, *30*(4). https://doi.org/10.1177/107769905303000401

Teoh, E. S., Ahmed, F., & Lalor, E. C. (2022). Attention Differentially Affects Acoustic and Phonetic Feature Encoding in a Multispeaker Environment. *Journal of Neuroscience*, *42*(4). https://doi.org/10.1523/JNEUROSCI.1455-20.2021

Theunissen, F. E., & Elie, J. E. (2014). Neural processing of natural sounds. In *Nature Reviews Neuroscience* (Vol. 15, Issue 6). https://doi.org/10.1038/nrn3731

Thomas, E. R., Haarsma, J., Nicholson, J., Yon, D., Kok, P., & Press, C. (2024). Predictions and errors are distinctly represented across V1 layers. *Current Biology*, *34*(10). https://doi.org/10.1016/j.cub.2024.04.036

Weissbart, H., Kandylaki, K. D., & Reichenbach, T. (2019). Cortical tracking of surprisal during continuous speech comprehension. *Journal of Cognitive Neuroscience*, *32*(1). https://doi.org/10.1162/jocn_a_01467

1105   Widmann, A., Schröger, E., & Maess, B. (2015). Digital filter design for electrophysiological
1106   data - a practical approach. *Journal of Neuroscience Methods*, *250*.
1107   https://doi.org/10.1016/j.jneumeth.2014.08.002

1108