Sensory sharpening and semantic prediction errors unify competing models of predictive processing in communication

Fabian Schneider[1,2]* and Helen Blank[1,2]

[1]Institute for Systems Neuroscience, University Medical Centre Hamburg-Eppendorf, Martinistr. 52, Hamburg, 20246, Hamburg, Germany.
[2]Faculty of Psychology, Ruhr University Bochum, Universitätsstr. 150, Bochum, 44801, North-Rhine Westphalia, Germany.

*Corresponding author(s). E-mail(s): f.schneider@uke.de;
Contributing authors: h.blank@uke.de;

Abstract

The human brain makes abundant predictions in speech comprehension that, in real-world conversations, depend on conversational partners. Yet, models diverge on how such predictions are integrated with incoming speech. Predictive coding proposes that the brain emphasises unexpected information via prediction errors, whereas Bayesian models emphasise expected information through sharpening. We reconcile these views through direct neural evidence from electroencephalography showing that both mechanisms operate at different hierarchical levels during speech perception. Across multiple experiments, participants heard identical ambiguous speech in different speaker contexts. Using speech decoding, we show that listeners learn speaker-specific semantic priors, which sharpen sensory representations by pulling them toward expected acoustic signals. In contrast, encoding models leveraging large language models reveal that prediction errors emerge at higher linguistic levels. These findings support a unified model of predictive processing, wherein sharpening and prediction errors coexist at distinct hierarchical levels to facilitate both robust perception and adaptive world models.

Keywords: predictive coding, Bayesian brain, speech comprehension, semantics, speaker-specificity

1 Introduction

The human brain continuously predicts incoming sensory inputs from generative models of the world, allowing for rapid and efficient perception[1,2]. In the domain of speech perception, predictive mechanisms have recently been demonstrated to operate across multiple levels, from low-level acoustic features to high-level semantic structure[3–5]. Yet, most studies have focused on speech perception in monologic contexts such as audiobooks, leaving open how predictive processes unfold in actual conversational settings, in which our main goal is to understand another person. In natural dialogue, predictions may track not only general linguistic statistics but also, crucially, leverage speaker-specific semantic priors—i.e., our expectations of what the other person is going to talk about. For example, if Jamie habitually talks about food, speaker-specific semantic predictions may be crucial for correctly comprehending *Jamie: I'm putting my beans/dreams on the back-burner*, particularly under common challenging listening conditions such as noisy environments or poor phone lines[6]. However, whether such speaker-specific predictions occur remains untested.

While prominent theories like hierarchical predictive coding (hPC) or the Bayesian brain propose that higher-level priors, such as semantic expectations, generate lower-level acoustic predictions to facilitate perception and ambiguity resolution[1,7], how priors are applied at a mechanistic level is highly debated[2,8]: In hPC, perception is primarily driven by minimising prediction error by preferentially encoding unexpected parts of the signal[4,9–11]. In contrast, the broader Bayesian brain framework emphasises sharpening, where perception is facilitated by enhancing expected components of the signal to optimise inference[12–14]. Reconciling these findings, it is plausible that both processes coexist—operating at different time points and hierarchical levels—to ensure robust perception and adaptive model updating[2,15,16]. However, evidence detailing how prediction error and sharpening are coordinated across these levels remains elusive.

Here, we provide direct evidence that speaker-specific semantic priors modulate neural processing by sharpening early auditory representations, while generating prediction errors at the level of semantics. In a series of experiments, participants learned to identify acoustically ambiguous words in different speaker contexts that were cued with different faces. We show that participants apply speaker-specific semantic priors when resolving ambiguities, reporting to hear the word consistent with the speaker's semantic context. Using stimulus reconstruction models[17] and representational similarity encoding[18] of recorded electroencephalography (EEG) responses, we show that these priors manifest in early sharpening of neural representations, with low-level acoustic content shifted toward the expected acoustic signal. Further, single-trial encoding models[19,20] leveraging speech-based large language models[21] reveal that speaker-specific prediction errors emerge at the higher semantic level instead, albeit with a relatively early modulation of the EEG signal. Finally, we employ real-time modeling of semantic priors using free-energy models[22] to show that participants flexibly deploy and discard speaker-specific priors, depending on

the probability of words under the prior. This dynamic interplay between flexible application of priors through low-level sharpening and high-level prediction errors provides new insights into how humans perceive and learn to adapt to individual speakers to maintain robust comprehension in acoustically ambiguous settings and critical evidence for a unified model of predictive processing in communication.

2 Results

To examine how listeners apply speaker-specific semantic priors, participants learned to associate six distinct faces with six unique semantic contexts—i.e., fashion, politics, arts, tech, nature, food—in two independent, preregistered experiments [23,24] (online $N_1 = 35$, EEG $N_2 = 35$, see Fig. 1a). Each trial began with a speaker's face that cued a speaker-specific semantic context. Participants then heard a degraded morphed word that combined two words—only one of which fit the speaker's semantic context—and subsequently selected the perceived word from the two words making up the morph written on the screen (see Fig. 1b). As morphing two words may not result in perfectly ambiguous sounds, we measured context-free perception of each morph in an independent, preregistered experiment [25] ($N = 40$) and used these results as control predictors for acoustic unambiguities in subsequent analyses. In addition, we degraded the spoken words with a vocoding technique [26] so that the voice sounded like a whisper and voice-identity information was removed (see Stimulus creation). This allowed us to avoid any voice differences and link the identical spoken input to different faces, as we were interested in testing the effect of semantic priors on the representation of speech. Speaker-specific feedback was provided visually by highlighting choices that were congruent or incongruent with the speaker in green or red, respectively, to ensure that each speaker was consistently linked to their semantic context (see Fig. 1b). To track participants' semantic expectations throughout the experiment, we computed trial-by-trial estimates of their semantic priors by fitting Gaussian distributions over semantic embeddings of the words they reported to hear through free-energy models in real-time (see Estimating real-time semantic models). To dissociate speaker-specific and general semantic priors, we fit these models either in a speaker-specific—i.e. one prior per speaker—or speaker-invariant manner—i.e. one general semantic prior across speakers (see Fig. 1d).

Critically, the same ambiguous morph (e.g., *sea-tea*) was presented in different speaker contexts (e.g., *nature-food*), allowing us to test whether perception and the underlying representation was pulled toward (i.e., sharpening) or away from the speaker priors (i.e., prediction error, see Fig. 1d,e). For example, the sharpened representation of the morph between *sea*-tea given a speaker who was associated with the semantic context *nature* would be more similar to *sea*, whereas the prediction error representation would be more similar to *tea* instead.

Fig. 1 **A** Stimuli. Sixty word pairs were created (e.g., *sea-tea*) where words within a pair sounded similar and could each be associated with one of six semantic contexts (e.g., *sea-tea* corresponding to *nature-food*). To decrease clarity and to induce ambiguity, words were slightly degraded to sound like a whisper and morphed into an intermediate acoustic signal between two words from two different contexts. Morphs were validated in a separate validation experiment (see Stimulus creation). **B** EEG part one with morphed words. Trials began with a fixation cross, followed by a visual speaker cue. Morphs were presented binaurally. Participants then indicated the word they had heard by button press. Finally, feedback was given in a speaker-specific manner such that each speaker could be associated with one specific semantic context. **C** Participants were more likely to report hearing a word when it was highly probable given the respective speaker (see Modeling choice behaviour). This preference increased over time. Lines are model predictions. Shaded areas around lines are 95%-confidence intervals. *** indicates $p \leq 1e^{-3}$. **D** We tested two potential forms of priors (large dots) that might influence neural responses to words (small dots): First, participants may apply one general, i.e., speaker-invariant prior reflecting general semantic expectations. Second, participants may learn and apply speaker-specific priors, i.e., six distinct priors, reflecting expectations about the individual speaker contexts. **E** In Bayesian models of the brain, there are two competing hypotheses about the application of priors: Firstly, prior expectations may pull neural representations towards the expected information (sharpening), i.e., when the speaker talking about nature is expected the representation of the morph (*sea-tea*) is shifted towards expected words (e.g., *sea*). Secondly, prior expectations may push neural representations towards more unexpected information (prediction error), i.e., when the speaker talking about nature is expected the representation of the morph (*sea-tea*) is shifted towards unexpected words (e.g., *tea*).

2.1 Behavioural analysis shows that listeners apply speaker-specific semantic priors

In experiment one, participants ($N_1 = 35$, see Participants) were cued with a speaker's face and subsequently listened to a degraded spoken word (EEG part

two, see Fig. 1b). They reported to hear the word consistent with the speaker's semantic context (generalised linear mixed model (GLMM), $\beta = 1.64, s.e. = 0.12, z = 13.11, p = 2.71e^{-39}$, odds-ratio $= 5.16$), and this effect increased over trials ($\beta = 0.43, s.e. = 0.03, z = 12.77, p = 2.41e^{-37}$, odds-ratio $= 1.54$). Correspondingly, participants relied on acoustic unambiguities initially (GLMM, $\beta = -0.62, s.e. = 0.11, z = -5.81, p = 6.26e^{-9}$, odds-ratio $= 0.54$), but reliance on these decreased over trials (GLMM, $\beta = 0.39, s.e. = 0.06, z = 6.09, p = 1.14e^{-9}$, odds-ratio $= 1.48$; see Supplementary Table 1, Supplementary Fig. 1).

In experiment two (different $N_2 = 35$, see Participants), we directly replicated these behavioural findings (see Fig. 1c, Supplementary Table 2, Supplementary Fig. 1) while also recording EEG responses. Together, these behavioural results provide strong evidence that listeners learn and apply speaker-specific semantic priors to aid disambiguation in speech perception (see Fig. 1d).

2.2 EEG analysis reveals that speaker-specific acoustic predictions sharpen sensory representations

Next we used EEG to investigate whether speaker-specific semantic priors modulate early sensory processing or high-level decision-making and whether they sharpen expected stimulus representations or induce prediction errors instead (see Fig. 1d,e), potentially across different time points and stages of the processing hierarchy. To determine whether speaker-specific semantic priors influence low-level sensory representations early into the neural processing hierarchy, we employed an approach combining stimulus reconstruction, representational similarity analysis (RSA), and similarity encoding.

First, gammatone filters, which model the human auditory system[27], were used to generate spectrograms reflecting the time-frequency representation of all morphed auditory stimuli. The high temporal resolution of EEG then enabled us to isolate sensory representations in the recorded neural data by correspondingly reconstructing gammatone spectrograms from EEG data following the presentation of the morphs (see Fig. 2a, Stimulus reconstruction of morphs). We confirmed that spectrogram reconstruction from EEG was successful, as reconstruction performance—measured as the correlation between reconstructed spectrograms from the EEG and audio spectrograms from the corresponding morphs—was above chance-level overall (two-sided one-sample t-test, $M = 0.06, s.d. = 0.02, t(34) = 17.06, p = 8.96e^{-17}$; see Fig. 2c) and in all individual frequency bands (two-sided one-sample t-test, all $p \leq 2.53e^{-6}$, see Supplementary Fig. 2, Supplementary Table 3).

In an RSA approach, we computed cosine similarities of the reconstructed spectrograms from EEG signals following presentation of the identical morph in different contexts (e.g., *sea-tea|nature, sea-tea|food*, see Fig. 2b) with the real audio spectrograms of the corresponding original words (e.g., *sea, tea*) to obtain a representational similarity matrix of the sensory representations (i.e., sensory RSM). To be able to assess the representational content in the

sensory RSM, we built two types of hypothesis RSMs: Firstly, we built acoustic hypothesis RSMs from spectrograms of clear words that were predictable from participants' speaker-specific and -invariant semantic priors. Specifically, we selected the five most probable words under a speaker prior and combined them into one probability-weighted audio spectrogram (for analysis of the influence of the number of predicted words, see Supplementary Figures 3-4, Supplementary Tables 4-5). Secondly, we generated semantic hypothesis RSMs by comparing the semantic embeddings of the congruent words with the current estimates of the speaker-specific and speaker-invariant semantic priors (see Fig. 2b). By means of encoding models, we tested whether sensory RSMs could be predicted from acoustic or semantic hypothesis RSMs beyond baseline RSMs that controlled for raw acoustics and general linguistic statistics of German, irrespective of the semantic priors in our experiment (see Fig. 2b; see also Encoding of representational similarity). We hypothesised that speaker-specific semantic priors generate predictions at the acoustic level, i.e., acoustic predictions, which either pull sensory representations towards the expected signal—i.e., make the representation more similar to the expected words (sharpening)— or push them away from it—i.e., render the representation more similar to the unexpected words (prediction error, see Fig. 1d,e).

Encoding models revealed an effect of both speaker-specific and speaker-invariant semantic priors on acoustic representations. The sensory RSMs were predicted more accurately when accounting for speaker-invariant and speaker-specific acoustic predictions (two-sided paired samples t-test, invariant-baseline: $t(34) = 22.40, p = 1.47e^{-20}$, specific-baseline: $t(34) = 25.12, p = 4.04e^{-22}$). Yet, speaker-specific acoustic predictions explained sensory RSMs better than speaker-invariant acoustic predictions, indicating an increased reliance on speaker-specific information (two-sided paired samples t-test, specific-invariant: $t(34) = 4.18, p = 2.11e^{-3}$). Crucially, combining both types of acoustic RSMs revealed their effects to be additive, with significantly better encoding than using either alone (two-sided paired samples t-test, both-baseline: $t(34) = 31.67, p = 2.33e^{-27}$, both-invariant: $t(34) = 17.87, p = 1.33e^{-17}$, both-specific: $t(34) = 15.03, p = 2.35e^{-15}$; see Fig. 2d). These findings suggest that predictions based on both speaker-invariant and speaker-specific semantic priors clearly shape the acoustic representations of heard words, though with a greater importance of speaker-specific priors.

Fig. 2 A Stimulus reconstruction models were used to decode acoustic signals $\hat{s}$ from neural activity X during presentation of the same morph s given both of its potential speaker contexts (e.g., *nature* and *food* for morph *sea-tea*, see Stimulus reconstruction of morphs). This allowed us to compare sensory content of neural representations directly in representational similarity analysis. **B** Sensory representational similarity matrices (RSMs) were computed from the reconstructions of the identical morph given two speaker contexts (e.g., *nature* and *food*) and the two spectrograms of the audio files of the original word pair. A set of hypothesis RSMs were computed from the raw morph, top-5 acoustic predictions, and the current semantic predictions. Encoding models were employed to test which combination of predictors best explained the similarity structure of decoded neural representations (see Encoding of representational similarity). **C** Stimulus reconstruction models performed significantly above chance level. The inlay shows the average pattern that reconstruction models decoded in z-scored EEG signals. **D** Encoding models revealed that both speaker-invariant and speaker-specific acoustic RSMs improved the similarity structure of decoded neural representations, and that purely semantic RSMs failed to do so. Encoding improvements are visualised relative to baseline models. Circles indicate group means with error bars on circles indicating 95%-confidence intervals thereof. Transparent dots indicate single subjects. ***, **, and * indicate $p \leq 1e^{-3}$, $p \leq 1e^{-2}$ and $p \leq 5e^{-2}$, respectively. Note that significantly worse performance indicates evidence against a specific model, not in favour of its antithesis. Bold black lines between groups indicate $p \leq 5e^{-2}$. All p-values were corrected using the Bonferroni-Holm procedure. **E** Time-resolved coefficients of speaker-specific acoustic RSMs in encoding models showed consistently positive signs, indicating that neural representations were sharpened towards the more expected information present in hypothesis RSMs. Lines represent means, with shaded areas around lines indicating 95%-confidence intervals. Bold black lines indicate $p \leq 5e^{-2}$. Grey dots represent the median on- and offsets of the first and last phonemes, respectively, with 95%-highest density intervals around them.

171   To assess the specificity of these predictions to the acoustic level, we
172 also tested whether purely semantic predictions would yield the same results.
173 We entered the semantic embeddings used for top-5 predictions as semantic

hypothesis RSMs in the model, but omitted the step of generating specific acoustic predictions from these embeddings. Critically, purely semantic hypothesis RSMs failed to improve encoding performance (two-sided paired samples t-test, invariant-baseline: $t(34) = -2.19, p = 0.25$, specific-baseline: $t(34) = -10.88, p = 1.66e^{-11}$, both-baseline: $M = t(34) = -7.93, p = 3.69e^{-8}$; see Fig. 2d). These results indicate that speaker-specific semantic priors alter sensory representations at the acoustic level.

Next, we asked how speaker-specific predictions are combined with the incoming sensory signals at the acoustic level. We examined whether the neural representations reflected sharpening or prediction error by using the best encoding model's β-coefficients—i.e., the model incorporating both speaker-invariant and -specific acoustic hypothesis RSMs. Our hypothesis RSMs were designed to reflect a pattern wherein more expected information is represented in positive values. In turn, due to the geometry of cosine similarities, this means that a negative sign inverts this pattern to represent more unexpected information (see Fig. 2e). Consequently, positive and negative coefficients correspond to sharpening and prediction error computations, respectively. Cluster-based permutation tests revealed significant positive coefficients for speaker-specific acoustic predictions ($p \leq 8.00e^{-4}$) which corresponded to a cluster between $165ms$-$1000ms$ ($M = 0.22, s.d. = 0.04$; see Fig. 2e). These findings demonstrate that speaker-specific semantic priors sharpen neural representations by pulling neural representations towards the expected acoustic signal.

Finally, to rule out that our results depend on the specific number of predicted words, we refit the best encoding model while systematically varying the number of top-k predictions from 1 to 19, as there were 20 words per speaker. This analysis revealed significant stepwise improvements in encoding performance, with diminishing returns for larger k (see Supplementary Fig. 3, Supplementary Table 4). We verified that our results were robust by repeating all previous analyses using $k = 19$ predictions (see Supplementary Fig. 4, Supplementary Table 5).

2.3 Speaker-specific semantic priors induce prediction error representations at higher levels

Building on our finding that speaker-specific semantic priors sharpen low-level sensory representations, we next examined whether prediction errors emerge at higher levels of the speech-processing hierarchy instead. To do this, we built encoding models [17,19,20] of single-trial EEG signals that allowed us to probe signatures of acoustic and semantic prediction errors in the broadband EEG response. Notably, modeling broadband EEG responses rather than decoded sensory representations allowed us to probe whether prediction errors still co-occurred at, for example, the acoustic level as a separate information theoretic signal without shifting sensory representations. Since single-trial EEG signals are strongly influenced by stimulus properties such as acoustic envelopes and edges and general information theoretic measures like general phonotactic, lexical and semantic prediction errors, irrespective of the priors in our

experiment[4,10], we implemented baseline encoding models to control for these general properties and language-specific prediction errors. However, measuring prediction errors for morphs at levels higher than acoustics presents a unique challenge, as these stimuli are ill-defined at the phoneme and word level. To address this, we utilised recent advances in speech-based large language models[21], which allowed us to approximate general prediction error signals by feeding the raw audio of the morphs into these models and extracting 5-dimensional subspace projections of their layer activations[28,29]. We verified that projected model activations were sensitive to general phonotactic, lexical and semantic prediction errors and selected the best layer through back-to-back decoding[30] (see Large language models as statistical surrogates, see also Supplementary Fig. 5). In line with prior research[4,10], we framed prediction errors in terms of surprisal—i.e., the negative log probability. We then tested whether single-trial EEG signals could be predicted from speaker-specific or -invariant acoustic or semantic surprisal beyond baseline models that included general stimulus properties and projected LLM activations that controlled for general surprisal, irrespective of the semantic priors in our experiment (see Fig. 3a, Encoding of single-trial EEG data).

Results revealed that prediction errors emerged only at higher levels and only with respect to speaker-specific semantic priors. Concretely, speaker-invariant surprisal failed to improve encoding performance, irrespective of the hierarchical level (two-sided paired samples t-test, acoustic-baseline: $t(34) = -1.58, p = 0.49$, semantic-baseline: $t(34) = 1.11, p = 0.55$, both-baseline: $t(34) = 0.16, p = 0.87$). Crucially, speaker-specific surprisal improved encoding performance, but only at the semantic level (two-sided paired samples t-test, acoustic-baseline: $t(34) = -6.30, p = 1.78e^{-6}$, semantic-baseline: $t(34) = 5.33, p = 1.90e^{-5}$, both-baseline: $t(34) = 1.81, p = 0.08$, see Fig. 3b). This suggests that while sharpening of speaker-specific representations occurs at the acoustic level, the brain computes prediction errors not at the acoustic level, but at the semantic level where predictions had been generated instead.

Fig. 3 A Speech-based large language models were employed to obtain control predictors for general phonotactic, lexical and semantic surprisal (see Large language models as statistical surrogates). Single-trial encoding of EEG responses was then applied to reconstruct observed EEG signals from control predictors and hypothesised speaker-invariant and speaker-specific surprisal predictors (see Encoding of single-trial EEG data). **B** Encoding models revealed that only speaker-specific semantic surprisal could significantly improve model performance. Encoding improvements are visualised relative to baseline models. Note that significant negative effects indicate that models failed to produce generalisable improvements. Circles indicate group means with error bars indicating 95%-confidence intervals thereof. Transparent dots represent subjects. ***, **, and * indicate $p \leq 1e^{-3}$, $p \leq 1^e-2$ and $p \leq 5e^{-2}$, respectively. Bold black lines between groups indicate $p \leq 5e^{-2}$. All p-values were corrected using the Bonferroni-Holm procedure. **C** Spatiotemporally resolved contributions of speaker-specific semantic surprisal were estimated using a knock-out procedure (see Estimating spatiotemporal contributions of predictors). Speaker-specific semantic surprisal explained variance significantly with a corresponding cluster spanning a wide array of channels between $150ms$-$630ms$. Lines indicate the mean of variance explained, with shaded areas around them representing 95%-confidence intervals. Bold black lines indicate $p \leq 5e^{-2}$. The topography shows variance explained within each sensor, with channels contributing to the cluster highlighted in black.

To probe the spatiotemporal dynamics of speaker-specific semantic surprisal, we systematically eliminated the influence of speaker-specific semantic surprisal from the full model at temporal lags $\tau = \{-0.1, ..., 0.8\}s$, and measured the change in encoding performance of the full model over the reduced model relative to total encoding improvement of the full model over the baseline model, which yields an estimate of the variance explained at any time point and channel (see Estimating spatiotemporal contributions of predictors). Cluster-based permutation tests revealed significant variance explained by speaker-specific semantic surprisal ($p \leq 1.80e^{-3}$) corresponding to a cluster spanning all sensors between $150ms$-$630ms$ (see Fig. 3c). This spatiotemporal cluster aligns with the interpretation that speaker-specific prediction errors emerge primarily at levels higher than acoustics within the linguistic hierarchy, such as at the phonological and semantic levels.

Finally, we verified the robustness of these findings in two complementary analyses. First, increasing the dimensionality of the LLM activation subspace to 10^{28} to ensure that results were not an artefact of under-specified control predictors yielded consistent results (see Supplementary Fig. 6, Supplementary

Table 6). Second, we also verified that deriving control predictors for general properties and prediction errors from the target word rather than the morph's activation in the LLM produced consistent results to ensure that effects were not an artefact of poor performance of the LLM for morphed words (see Supplementary Fig. 7, Supplementary Table 7). Together, these analyses confirm the reliability of our results and the emergence of speaker-specific prediction errors at the higher levels.

2.4 Flexible deployment of speaker-specific semantic priors

To test the flexibility of how speaker-specific semantic priors are applied during speech perception, we conducted an additional experimental task (EEG part two, see Fig. 4a) in which we manipulated the degree to which the incoming sensory evidence conflicted with the preceding priors. Using real-time semantic models, we selected clear words where $word_1$ and $word_2$ were either highly congruent or highly incongruent with the speaker's expected semantics (e.g., *salad* vs. *senate* for *food*). Participants identified vocoded, but unmorphed, words following a speaker cue (see Fig. 4a).

Participants were significantly slower in incongruent trials, suggesting increased surprisal or decisional conflict (linear mixed model (LMM), $\beta = 0.12, s.e. = 0.02, t(3847) = 6.86, p = 7.85e^{-12}$, see Fig. 4b; see also Modeling behaviour in congruent and incongruent trials). Crucially, reaction times scaled with the probability of a word given the speaker in congruent trials (estimated marginal trends (EMT), $\beta = -0.11, s.e. = 0.01, t(1620) = -9.19, p = 1.12e^{-19}$), but not in incongruent trials (EMT, $\beta = -0.01, s.e. = 0.01, t(2340) = -0.85, p = 0.39$; see Fig. 4b). For incongruent trials, this effect emerged only over trials (LMM, congruence $\times trial \times p$(word|speaker): $\beta = -3.49e^{-2}, s.e. = 1.74e^{-2}, z = -2.01, p = 0.04$). Thus, while participants continued to leverage speaker-specific priors, they seemed to discard them initially when encountering highly improbable words, incurring a switch cost.

Fig. 4 **A** EEG part two with congruent and incongruent words. A fixation cross was displayed, followed by the presentation of a visual speaker-cue. Highly congruent or incongruent vocoded words under the speaker prior were presented. Participants reported the word they heard. **B** Participants incurred a processing cost in incongruent trials. However, reaction times between groups indicate $p \leq 5e^{-2}$. Shaded areas around lines indicate 95%-confidence intervals. **C** Encoding models revealed a double dissociation: In incongruent trials, only speaker-invariant semantic surprisal significantly improved encoding performance, whereas in congruent trials only speaker-specific semantic surprisal significantly boosted encoding performance. Encoding improvements are visualised relative to baseline models. Significant negative effects indicate that models failed to produce generalisable improvements. Circles indicate group means with error bars on circles showing 95%-confidence intervals. Transparent dots show individual participants. Bold black lines between groups indicate $p \leq 5e^{-2}$. ***, **, and * represent $p \leq 1e^{-3}$, $p \leq 1e^{-2}$ and $p \leq 5e^{-2}$, respectively. The downward-facing triangles indicate the best models by congruence. All p-values were corrected using the Bonferroni-Holm procedure. **D** Knock-out analysis of coefficients revealed significant variance explained by speaker-invariant semantic surprisal in incongruent trials (top) as well as by speaker-specific semantic surprisal in congruent trials (bottom). Speaker-invariant semantic surprisal was associated with a cluster across all channels between $170ms$-$345ms$, and speaker-specific semantic surprisal was associated with a cluster across all channels between $190ms$-$635ms$. Lines indicate means with shaded areas representing 95%-confidence intervals. Inlaid topographies show variance explained across sensors, with sensors contributing to clusters marked in black. Bold black lines indicate $p \leq 5e^{-2}$.

EEG encoding models mirrored this pattern: In incongruent trials, only speaker-invariant semantic surprisal boosted encoding performance (semantic-baseline: $t(34) = 3.03, p = 1.88e^{-2}$; see Fig. 4c), whereas in congruent trials only speaker-specific semantic surprisal significantly improved encoding performance (semantic-baseline: $t(34) = 8.39, p = 3.39e^{-8}$; see Fig. 4c,

see also Supplementary Table 8). Knock-out analyses revealed significant variance explained by speaker-invariant semantic surprisal in incongruent trials ($p \leq 1.40e^{-3}$), corresponding to a cluster across all channels between $170ms$-$345ms$, and significant variance explained by speaker-specific semantic surprisal in congruent trials ($p \leq 1.40e^{-3}$), corresponding to a cluster across all channels between $190ms$-$635ms$ (see Fig. 4d). This double dissociation of semantic congruency and specificity of the semantic priors demonstrates that listeners dynamically deploy and discard speaker-specific priors depending on contextual plausibility.

3 Discussion

In this study, we investigated whether listeners utilise speaker-specific semantic priors to facilitate speech comprehension, and how such priors influence processing at different levels of the processing hierarchy. Specifically, we aimed to resolve a long-standing debate on whether predictive processing operates primarily via prediction error or sharpening mechanisms[1,9,13,15]. Our findings provide clear evidence for an integrated account in which both mechanisms coexist at distinct levels of the hierarchy, as suggested by more recent accounts of the Bayesian brain[15].

First, we demonstrate that listeners apply speaker-specific semantic priors to disambiguate acoustically ambiguous words (see Fig. 1c). Second, we show that these priors sharpen low-level sensory representations, actively shifting them towards the expected acoustic signal (see Fig. 1e, Fig. 2d,e). Third, while sharpening occurs at the acoustic level, prediction errors emerge at higher linguistic levels, such as semantics (see Fig. 3b,c Fig. 4c,d). Finally, we find that speaker-specific semantic priors are not applied indiscriminately: when the likelihood of a given input under a specific-speaker prior is exceedingly low, listeners flexibly discard the prior rather than generating extreme prediction errors and, consequently, potentially deleterious model updates (see Fig. 4c,d).

These findings align with recent refinements of Bayesian models of the brain, which propose that sharpening occurs at lower levels while prediction errors dominate higher levels of the neural hierarchy[2,15]. This nuanced view departs from traditional models of hPC, which posit that only prediction errors should be propagated within the hierarchy[1,7]. Instead, our results support a synergistic account, wherein sharpening enhances perceptual robustness while prediction errors may enable adaptive updating of internal models[15]. Patterns mirroring the co-occurence of sharpening and prediction error have recently been observed in vision[16], although here temporally-resolved evidence is lacking.

An important aspect of our results is the strong empirical support for sharpening at the acoustic level (see Fig. 2e). Notably, the temporal extent of sharpening suggests that sharpening is not constrained to times of high uncertainty—for example, only for the disambiguating phonemes of a morph

such as /t/ or /s/ for morph *tea-sea*—but occurs in parallel with the temporally unfolding acoustic signal instead. Sharpening at the acoustic level stands in contrast with previous findings emphasising the role of prediction error in speech processing[3,4,9,10,31]. This discrepancy may stem from methodological differences: whereas previous studies primarily analysed broadband EEG or BOLD responses, we employed speech decoding models[17] to isolate changes in low-level sensory representations. Supporting this view, evidence of sharpening in monologic contexts has previously been reported using similar approaches, albeit only for speech envelopes rather than low-level acoustic representations as captured with full spectrograms[12]. While our task was carefully constructed to test speaker-specific semantic priors facilitating speech comprehension, it is also conceivable that other tasks demanding attention towards unexpected features, such as deviation detection, might shift low-level representations towards prediction error representations[32]. Investigating predictive processing in natural speech by incorporating a wider array of methodologies may allow comparing and disentangling sharpening and prediction error computations at the acoustic level across monologic and dialogic contexts.

Interestingly, here we find that speaker-specific prediction errors emerge relatively early—with clusters around $150ms$-$630ms$ and $190ms$-$635ms$ after stimulus onset in the main task testing perception of morphed, i.e., ambiguous words, and the follow-up task testing congruent and incongruent words, respectively (see Fig. 3c, Fig. 4d). Differences in temporal extent of these clusters are difficult to interpret, given that cluster-based permutation testing does not guarantee significance at specific time points[33,34]. However, peak latencies showed no differences between tasks, with peaks consistently around $252ms$ post stimulus onset (see Supplementary Fig. 8). This is striking given that semantic prediction errors are typically thought to peak around $400ms$ post onset[35,36]. While semantic processing has previously been reported around $250ms$[37,38], an alternative interpretation may be that prediction errors induced by semantic priors arise at multiple intermediate and higher-level stages—first at the phonemic and then the semantic levels, which would be in agreement with the prolonged time course of speaker-specific prediction errors. While this would also be consistent with hPC where prediction errors are propagated along the processing hierarchy[1,15], there is a long-standing debate whether EEG components around this time can even be separated into functionally distinct phonemic and semantic components[35,39]. Given the limited size of the stimulus set in this study, we cannot derive appropriate estimates of speaker-specific phonemic surprisal, leaving this question open for future research. Crucially, this does not change the interpretation of our findings with respect to hierarchical processing in models of the Bayesian brain.

Our findings also highlight a key theoretical gap in predictive models: while it is commonly assumed that the brain constructs multiple types of priors at all levels of the processing hierarchy[1,7,15], the precise mechanism by which competing priors are selected remains unclear. The coexistence of priors at the same level—such as speaker-specific and speaker-invariant semantic

priors—may be crucial for tracking multiple relevant statistical regularities, yet our results suggest that not all priors are applied simultaneously. Instead, we find a double dissociation of prior congruency and specificity at higher levels of the neural hierarchy, where priors are selected dynamically based on their relative likelihood. Specifically, a speaker-specific prior was only applied when the incoming word was congruent with that prior. This has important implications for predictive coding models, particularly in the context of world model updates [1,7]: Firstly, allowing, for example, detection of a new semantic topic when listening to the identical speaker. Secondly, if all high-level priors were applied and updated indiscriminately, they would risk collapsing into a single, undifferentiated representation. Thus, priors must be selectively updated, potentially through precision-weighting mechanisms that govern their influence.

Most previous studies on predictive processing have primarily examined speech perception in monologic contexts such as audiobooks [3,4,10], leaving open the question of how semantic predictions may operate in speaker-specific conversational settings. Our study investigated how predictions are shaped not only by general linguistic statistics but also by speaker-specific characteristics. Thereby our approach extends and links to previous experimental findings showing that listeners adapt to individual speakers at, for example, the phonetic [40–42] and lexical levels [43–45]. Here we show for the first time that listeners also adapt to semantic patterns of individual speakers. As such, our findings also advance our understanding of how listeners may deal with common sources of uncertainty in the speech signal such as loud environments or poor phone lines [6].

Beyond theoretical implications, our findings have direct relevance for clinical applications, particularly in neural speech decoding and brain-computer interfaces (BCIs). Decoding approaches hold promise of restoring communicative abilities for patients with conditions such as aphasia, anarthria, or locked-in syndrome [46]. While recent advances have improved speech decoding accuracy [47–50], current methods remain data-intensive and lack the precision needed for seamless communication [49,50]. Our results suggest that incorporating individualised speaker-specific models could enhance decoding accuracy, particularly in interactive settings with clinicians or family members, where strong priors may shape communication. Furthermore, an intriguing question arising from our study is whether speaker-specific semantic priors also influence speech production. If listeners adjust their own speech to match their semantic expectations of a conversational partner, this adaptation could be leveraged in BCIs to improve bidirectional communication and hence may have significant implications for speech rehabilitation and augmentative communication technologies.

In conclusion, we show that listeners learn and apply speaker-specific semantic priors, which actively shape their perceptual experience and sharpen low-level sensory representations towards the expected acoustic signals. Prediction errors, in contrast, emerge at higher levels of the linguistic hierarchy,

supporting a complementary role of sharpening and prediction errors in predictive processing. These findings refine our understanding of predictive processing in the brain and suggest new directions for clinical applications, as in the development of dialogic brain-computer interfaces.

4 Methods

The series of experiments of this study was preregistered[23–25]. Across an online and subsequent EEG experiment, participants learned to associate six distinct speakers with six unique semantic contexts (see Fig. 1a). Participants heard identical degraded and morphed auditory stimuli given different speaker contexts (see Fig. 1b), allowing us to probe the influence of speaker-specific semantic priors on neural representations along the speech processing hierarchy (see Fig. 1d,e). In the EEG experiment, participants completed a subsequent follow-up task including degraded unmorphed words that were either particularly congruent or incongruent with their perceived semantic model of any given speaker, which allowed us to test the limits of prior application (see Fig. 4a).

4.1 Participants

In the validation experiment, 40 volunteers were recruited through Prolific and completed the experiment online (20 female, age range 19-40, $M = 28.35 \pm 6.27$). Participants that failed to pass an initial headphone test[51] or failed to respond on ten of the preceding twenty trials were excluded in real-time. A priori power analysis suggested that this would yield sufficient power for χ^2-tests to detect deviations by at least 0.15 from chance-level in individual morphs[25].

In experiment one, 35 different volunteers were recruited through Prolific and participated in the experiment online (17 female, age range 22-39, $M = 29.46 \pm 4.78$). Again, participants were excluded in real-time based on headphone and attention tests. Participants received £9/hr in compensation for their time. Sample size was determined through power simulations using PyMC5[52] and ArviZ[53] based on previous experimental data that indicated sufficient power to detect behavioural effects bigger than log odds 0.15[23].

In experiment two, 36 different volunteers completed the study in the EEG laboratory. One participant was excluded from the analysis due to excessive muscle-related artifacts. The final sample included 35 participants (20 female, age range 20-39, $M = 28.09 \pm 5.29$). Participants were compensated with 13€/hr. Sample size was determined through power simulations based on pilot recordings ($N = 2$) using PyTorch[54] that indicated sufficient power to detect moderate effect sizes in the neural data[24].

In all experiments, all participants were right-handed, native speakers of German, and reported no history of neurological disorders, ADHD, ASD,

dyslexia, impaired hearing, or face or colour blindness. All experimental procedures were approved by the Ethics Committee of the Chamber of Physicians in Hamburg and participants provided written informed consent.

4.2 Stimulus creation

An initial list of 210 target words was created by searching the neighbourhood of six semantic contexts (food, fashion, technology, politics, arts, and nature) seeded at the embedding of the context's label in a GloVe embedding pretrained on German Wikipedia articles[55,56]. For each target word, one alternative corresponding to a different semantic context was chosen. Targets and alternatives were chosen such that phonemic differences would be minimal, although not all formed minimal pairs (e.g., sea/tea in food/nature).

A professional female speaker produced two enunciations of all words (duration: $M = 970ms \pm 144ms$). Audio files were pitch-corrected to roughly 170Hz to minimise cues about gender using Praat[57] and sound pressure levels were normalised to $-20LUFS$ to control for loudness. Next, we used a combination of vocoding and morphing the words twice to obtain two optimal 50%-morphs per pair, each with different noise profiles. Specifically, audio files were vocoded using twelve bands of white noise to remove most of the remaining voice properties from the signal[26]. This level of noise-vocoding was chosen because it has previously been shown to be intelligible, particularly given prior knowledge[9]. From the recorded utterances, we generated four 50%-morphs using Tandem-STRAIGHT[58] after application of dynamic time warping[59,60] over constant-Q transformed[61] audio data that aligned targets and alternatives in time. We computed cosine similarities between morphs and clear words and selected the least biased morph per pair.

Within each pair, perception of a morph as one word or the other was controlled in a preregistered validation experiment[25]. Participants (see [Participants](#)) listened to all morphs and had to indicate which of the two visually presented options they had heard by button press. In total, participants completed 468 trials (6 contexts × 2 practice items + 2 repetitions × 120 morphs +2 repetitions × 6 contexts × 3 control items). Per morph, we computed a descriptive statistic κ that captured the remaining perceptual bias of participants to perceive one word or the other within the pair underlying each morph:

$$\kappa = \frac{p(\text{alternative}|\text{morph}) - \mu}{1 - \mu}$$

Note that μ represents chance level 0.50 here. We then dropped all morphs that did not meet $0.15 \geq \kappa \leq 0.85$ to remove biassed morphs that did not lead to ambiguous perception.

Next, for each target and alternative, the best semantic fits among the six candidate contexts were determined. To do this, we computed cosine similarities between all targets and all alternatives from all contexts (e.g., sea-tea= 0.12, sea-wattage= -0.06, sea-boat= 0.31, ...) and averaged them by

context (e.g., sea-nature= 0.38, sea-food= 0.14, sea-fashion= −0.08, ...). We then ranked each pair by the semantic fit to either potential contexts R_t, R_a and computed geometric means across ranks as $(R_t R_a)^{\frac{1}{2}}$ for each pair. We selected word pairs to minimise the geometric means, yielding a total of 60 pairs where word$_1$ was coherent with one of the six contexts and word$_2$ was coherent with another (see Fig. 1). As a result of this procedure, we obtained twenty words per context and a total of sixty morphs with two different noise profiles that showed no systematic perceptual biases (duration: $M = 867ms \pm 144ms$; for an overview, see Supplementary Fig. 9; Supplementary Table 9). For all, i.e., unmorphed and morphed, words we generated annotations of phoneme on- and offsets using MAUS[62].

Finally, a set of six face images was created using FaceGen[63] to obtain one visual cue per speaker-specific semantic context. Speaker images were crossed with six distinctive features (two types of glasses, scars, piercings each) to ease recognition and images were luminance-corrected.

4.3 Procedure

Stimuli were presented using jsPsych[64] in online experiments, whereas PsychoPy[65] was used in the EEG laboratory. Before all experiments, participants were introduced to the six speakers, each represented by a face and a one-sentence summary of their interests. The online experiment lasted ∼45 minutes, whereas the EEG experiment lasted ∼2.5 hours, including briefing, setup, passive listening (∼20 minutes, not reported here), EEG part one with morphed words (∼35 minutes), EEG part two with congruent and incongruent words (∼15 minutes) and debriefing.

All experiments followed the same trial structure: Each trial began with a fixation cross ($500ms$), followed by the visual presentation of a speaker ($750ms$). Next, a vocoded morph was played ($M = 867ms \pm 144ms$ and, in EEG, $400ms$ delay) in the online experiment and EEG part one, whereas a vocoded congruent or incongruent word was played in EEG part two ($M = 990ms \pm 147ms$ and $400ms$ delay). Participants were subsequently shown two word options—one congruent with the speaker's semantic context and one from a different context—and selected the word they perceived via button press (response window: $3000ms$ online, $2000ms$ in EEG). To reinforce speaker-specific semantic associations, participants received immediate speaker-specific feedback: their selection was highlighted in green if correct under the speaker and red if incorrect under the speaker ($750ms$, see Fig. 1b). Feedback was omitted in the EEG part two. The inter-trial interval was randomly jittered between $1.0s - 1.4s$. In the online experiment and EEG part one, participants completed a total of 270 trials (6 practice trials, 24 control trials, 2 repetitions × 2 contexts × 60 morphs main trials), with optional breaks every 20 trials. In EEG part two, participants completed 120 trials (60 congruents, 60 incongruents).

⁵⁵⁴ During the EEG experiment, real-time estimates of each participant's
⁵⁵⁵ semantic priors were computed using a free-energy approach that were lever-
⁵⁵⁶ aged for sampling of congruent and incongruent stimuli in part two (see
⁵⁵⁷ Estimating real-time semantic models). After completion of task one, individ-
⁵⁵⁸ ual semantic priors were used to sample subject- and speaker-specific word
⁵⁵⁹ pairs. Each pair contained one word strongly congruent with a speaker's seman-
⁵⁶⁰ tic context and another strongly incongruent. To maximize the difference in
⁵⁶¹ semantic fit, word pairs were selected based on the following criterion:

$$\arg \max_{\text{word, context}} p(\text{word}_1|\text{context}_a) - p(\text{word}_2|\text{context}_b)$$

⁵⁶² This ensured that word_1 was highly congruent with context_a, whereas word_2
⁵⁶³ was particularly incongruent with context_b. The sampling procedure also
⁵⁶⁴ ensured that each context contained ten congruent-incongruent word pairs.
⁵⁶⁵ This modification made the stimuli clearly identifiable as either congruent or
⁵⁶⁶ incongruent, allowing us to test how speaker-specific priors are applied when
⁵⁶⁷ word probability is either very high or very low for a given speaker.

4.4 EEG acquisition

⁵⁶⁹ EEG data were acquired using a 64-channel Ag/AgCl active electrode system
⁵⁷⁰ (ActiCap64; Brain Products) that was placed according to the extended 10-20
⁵⁷¹ system[66]. A total of sixty electrodes were placed centrally, with reference and
⁵⁷² ground electrodes at FCz and Iz, respectively. Four additional electrodes were
⁵⁷³ placed to record the vertical and horizontal electrooculogram. Recordings were
⁵⁷⁴ made with impedances $\leq 10k\Omega$. Data were sampled at $1000Hz$.

4.5 Estimating real-time semantic models

⁵⁷⁶ To dynamically track how participants formed and updated speaker-specific
⁵⁷⁷ semantic priors during the experiment, we employed a real-time modeling
⁵⁷⁸ approach based on free-energy optimisation[22]. This was done because the low
⁵⁷⁹ computational cost allowed us to continuously estimate trial-by-trial shifts in
⁵⁸⁰ participants' inferred semantic representations of speaker-specific and speaker-
⁵⁸¹ invariant priors π for any given speaker i in real-time. To do this, we sought
⁵⁸² to infer π by maximising $p(\pi|S)$ for some semantic input S.

⁵⁸³ For efficiency in model estimation, we reduced the original 300-dimensional
⁵⁸⁴ GloVe embeddings[55,56] to a 50-dimensional subspace that spanned all S.
⁵⁸⁵ Briefly, we preprocessed demeaned embeddings by applying principal com-
⁵⁸⁶ ponent analysis (PCA), and removing the top $D = 7$ components, and
⁵⁸⁷ projected data to 50 dimensions, followed by a second iteration of the PCA-
⁵⁸⁸ based preprocessing. This approach has been shown to improve embedding
⁵⁸⁹ quality[67,68].

⁵⁹⁰ For simplicity, we assumed that π follows a 50-dimensional Gaussian distri-
⁵⁹¹ bution per speaker, with mean μ_i and variance σ_i. Since finding exact solutions

for

$$p(\pi|S) = \frac{p(\pi)p(S|\pi)}{\int p(\pi)p(S|\pi)d\pi}$$

is prohibitively expensive to compute, we approximated only the most likely values of π, denoted ϕ, using a free-energy approach. This involved optimising the free-energy

$$F = \ln f(\phi; \mu_i, \sigma_i) + \ln f(S; \phi, \sigma)$$

where f denotes the density. We modeled this as a simple set of nodes comprising the current estimate ϕ, an error term for sensory inputs ε_S, and an error term for priors ε_p, evolving as

$$\dot{\phi} = \varepsilon_S - \varepsilon_p$$
$$\dot{\varepsilon}_S = S - \phi - \Sigma_S \varepsilon_S$$
$$\dot{\varepsilon}_p = \phi - \mu_i I - \Sigma_p \varepsilon_p$$

with parameter updates obtained via gradient ascent:

$$\frac{\partial F}{\partial \mu_i} = I \varepsilon_p, \quad \frac{\partial F}{\partial \Sigma_S} = \frac{1}{2}(\varepsilon_S^2 - \Sigma_S^{-1}), \quad \frac{\partial F}{\partial \Sigma_p} = \frac{1}{2}(\varepsilon_p^2 - \Sigma_p^{-1})$$

For further details on derivations, see [22].

Before the experiment, μ_i was initialised to the mean of the full GloVe space, and variances Σ_p and Σ_S were drawn from a uniform distribution. After each trial, posterior estimates were updated via Euler's method based on the semantic embedding of the word the participant reported. This approach was applied separately to both speaker-invariant and speaker-specific priors, with the former modelled using a single speaker across all contexts. Crucially, whenever prior estimates were used outside this estimation procedure, they were based on the posterior of the previous trial within that context to prevent incorporation of future information.

4.6 Modeling choice behaviour

Behavioural responses from experiments one and two were analysed in R (version 4.03)[69] using lme4[70] and emmeans[71]. Generalised linear mixed models were fit using the 'bobyqa' optimiser with a maximum of $2e^5$ iterations. To increase generalisability, a maximal model fitting procedure was followed[72,73] to identify the maximal random effects structure that allowed the model to converge without singular fit. Residuals within the identified maximal model were inspected using DHARMa[74].

Behavioral choices were modeled as

$$p(\text{chose word}) \sim t \times \kappa + t \times p(\text{word}|\text{speaker}) + (1|\text{participant})$$

where trial number t, perceptual bias κ and the probability of the word given the speaker $p(\text{word}|\text{speaker})$ were scaled to have zero mean and unit variance.

Note that probabilities of the word given the speaker were computed as the cosine similarity between the word's embedding and the priors (see Estimating real-time semantic models). For the random effects structure, we tested all reasonable permutations that included these predictors as well as the position of the word on screen, the semantic context, the speaker, and their distinguishing visual feature.

The maximal identifiable model included the following random effects structure for data from experiment one:

$$(0 + \kappa + p(\text{word}|\text{speaker})|\text{participant})+$$
$$(1|\text{speaker} \times \text{context}_1 \times \text{context}_2)+$$
$$(1|\text{participant} \times \text{context}_1 \times \text{context}_2)$$

and for data from experiment two:

$$(1 + t + \kappa + p(\text{word}|\text{speaker})|\text{participant} \times \text{context}) +$$
$$(1|\text{face} \times \text{feature})$$

Note that, while random effects structures differ slightly between experiments, all maximal models included the critical random slopes by κ and $p(\text{word}|\text{speaker})$.

4.7 Preprocessing EEG data

EEG data were preprocessed using MNE[75] following a preregistered[24], standard preprocessing pipeline[76]. Line noise was removed with a notch filter at $50Hz$ and harmonics. Channels were demeaned and visually inspected for excessive noise. Noisy channels were interpolated ($N = 0 \pm 1$). To identify rare excessive muscle activity, data were bandpass filtered ($110\text{-}140Hz$, IIR filter), epoched to -500 to $2500ms$, z-scored, and visually inspected. Bad trials were flagged. EEG data were then bandpass filtered ($0.5\text{-}50Hz$, IIR filter) and epoched (-500 to $2500ms$ relative to audio onset). Independent component analysis[77] was employed to remove ocular, cardiac, and muscle-related artifacts. Epochs were re-referenced to the global average and underwent a final visual inspection for trial selection (trials dropped in part one: $N = 8 \pm 6$, part two: $N = 5 \pm 3$). Crucially, this trial selection was applied only for single-trial EEG encoding models where severe artifacts would degrade measured encoding quality. To preserve the critical structure of identical morphs being perceived given different speaker contexts (see Fig. 1), no trials were dropped in the reconstruction-RSA-encoder approach. For single-trial modeling of EEG responses, we applied an additional lowpass filter ($\leq 15Hz$, IIR filter)[10]. All data were downsampled to $200Hz$ to speed-up subsequent analysis steps.

4.8 Stimulus reconstruction of morphs

To probe the content of low-level sensory representations, we decoded gamma-tone spectrograms from neural responses following presentation of a morph. To do this, gammatone spectrograms were extracted from raw audio signals at $200Hz$ across 28 logarithmically spaced frequency bands between $50 - 11025Hz$, analogous to previous work[78]. To improve estimation, spectrograms were smoothed with a $100ms$ boxcar kernel[79].

We then trained subject-level multivariate stimulus reconstruction models[17] mapping from neural data X to gammatones s:

$$\hat{s}(t) = \sum_n \sum_\tau r(t + \tau, n)g(\tau, n)$$

Here, $\hat{s}(t)$ is the reconstructed gammatone representation at time point t, $r(t + \tau, n)$ is the neural response X at t and channel n time-lagged by τ, and $g(\tau, n)$ is the spatial filter at lag τ. We used a time window of $\tau = \{0, ..., 250\}ms$. We solved for spatiotemporal filters G using sklearn[80], sklearn-intelex[81] and PyTorch[54]:

$$\arg\min_G \sum_t (s_t - G^T R_t)^2 + \alpha_G ||G||^2$$

where optimal ridge penalties α_G were found using leave-one-out cross-validation to test 20 logarithmically spaced values between $1e^{-5} - 1e^{10}$. Inputs X and s were standardised to have zero mean and unit variance. Models were estimated using 5-fold cross-validation. Out-of-sample performance was measured as the Pearson correlation between real spectrograms s and reconstructed spectrograms $\hat{s}$ in the held-out test set, averaged over frequency bins and time points. Decoded patterns were computed following[82]. To improve robustness, this procedure was repeated over 100 permutations of the data. Final estimates were obtained by averaging out-of-sample performance, decoded patterns and stimulus reconstructions.

Statistical inference. To determine overall reconstruction performance, we performed a two-sided one-sample t-test over performance averaged over frequency bands. Further, we tested reconstruction performance in individual frequency bands using two-sided one-sample t-tests. Bonferroni-Holm corrections were applied to adjust for multiple comparisons.

4.9 Encoding of representational similarity

To determine whether semantic expectations influenced the representation of morphed words at the acoustic level, we computed representational similarity matrices (RSMs)[18] comparing reconstructed spectrograms based on the recorded EEG data of the morphed stimuli with the real spectrograms of the audio files making up the respective morphs (e.g., /siː/ and /tiː/ for morph /‿iː/). The observed RSM for each morph n at time point t was defined as:

$$\text{RSM}(n, t) = \begin{bmatrix} f(/\text{\textipa{i:}}/|\text{nature}, /\text{si:}/) & f(/\text{\textipa{i:}}/|\text{food}, /\text{si:}/) \\ f(/\text{\textipa{i:}}/|\text{nature}, /\text{ti:}/) & f(/\text{\textipa{i:}}/|\text{food}, /\text{ti:}/) \end{bmatrix}$$

where f denotes cosine similarity computed over the frequency bins of gammatone spectrograms. This yielded an RSM of size $120 \times 2 \times 2 \times 200$ (morph pairs $\times$ contexts $\times$ words $\times$ time points) per participant. We then generated hypothesis RSMs to assess which representational structures best explained the observed RSMs. We formulated three core hypotheses to test how acoustic representations changed as a function of the speaker context (see Fig. 2b). For each prior-dependent hypothesis, predictions were derived from both speaker-specific and speaker-invariant priors.

Prior-independent morph-based representation. First, as a baseline, if presented morphed words are processed based on the pure, i.e., expectation-free, acoustics of the morph, representational similarity should reflect the direct comparison between the morph's gammatone spectrogram (e.g., /\text{\textipa{i:}}/) and the respective real spectrogram making up the morph (e.g., /si:/ and /ti:/).

Prior-dependent acoustic representation. If semantic priors influence the processing of the morphed words already at an acoustic stage, representational similarity should reflect expected acoustics derived from the semantic priors. We estimated these expectations by computing the top-k predicted words:

$$\arg\max_{\text{word}} \sum_i^k p(\text{word}_i|\text{speaker})$$

Normalised probabilities were then used to compute a prior-weighted spectrogram from the top-k words:

$$s(\text{predicted}|\text{speaker}) = \sum_i^k p(\text{word}_i|\text{speaker})s(\text{word}_i)$$

These hypothesised spectrograms were then compared with the respective real spectrograms making up the morph (e.g., /si:/ and /ti:/). Additionally, we computed a control predictor using randomly sampled priors to account for general linguistic expectations unrelated to the experiment that may arise due to the statistical regularities of speech more broadly.

Prior-dependent semantic representation. If semantic priors influence the processing of the morphed words at higher-level processing stages—for example, shifting acoustic representations uniformly per semantic context—representational similarity should reflect direct comparisons between the prior distribution of the speaker, $p(\text{speaker})$, and the word embeddings of the words making up the morph (e.g., *sea* and *tea*). As before, we computed an additional control predictor to capture more global statistical regularities.

To test whether speaker context shifted participants' perception of the same acoustic morphs, we built encoding models[19,20] mapping from hypothesised

722 RSMs X to observed RSMs y for each participant:

$$\hat{y}(t) = \beta_t X_t + \epsilon$$

723 where β_t are the encoding weights at time point t. We constructed a temporally
724 expanded design matrix D and temporally expanded outcomes Y, and solved
725 for the full encoding model β using sklearn[80], sklearn-intelex[81] and PyTorch[54]:

$$\arg\min_{\beta} \sum_i (Y_i - \beta^T D_i)^2 + \alpha_\beta ||\beta||^2$$

Ridge penalties α_β were optimised using leave-one-out cross-validation to
test 20 logarithmically spaced values between $1e^{-5} - 1e^{10}$[80]. Models were esti-
mated using 5-fold cross-validation with 50 repetitions[83] and all outcomes and
predictors were scaled to have zero mean and unit variance based on the train-
ing set to prevent data leakage. Out-of-sample performance was defined as the
Pearson correlation between observed RSMs $y(t)$ and reconstructed RSMs $\hat{y}(t)$
in the held-out test set[78,79]. To ensure coefficient comparability across models,
we normalised encoding weights as:

$$\hat{\beta}_{j,t} = \frac{\beta_{j,t}}{\max_t \sum_j |\beta_j|}$$

Thus, $\hat{\beta}_j$ represents the relative contribution of predictor j to the variance
explained[84], while meaningfully preserving signs.

Candidate models. Baseline models predicted sensory RSMs from
hypothesis RSMs based on audio spectrograms of morphs as well as audio
spectrograms and semantic embeddings from general language-specific expec-
tations. We then performed step-wise inclusion of speaker-specific and speaker-
invariant acoustic and semantic hypothesis RSMs.

Statistical inference. Encoding performance improvements for each
predictor were tested using two-sided paired t-tests, with Bonferroni-Holm cor-
rections applied for multiple comparisons. Significance of temporally resolved
variance explained by $\hat{\beta}$ was assessed through cluster-based permutation
tests[33]. To compensate for the number of predictors, Bonferroni corrections
were applied.

4.10 Large language models as statistical surrogates

For modeling of single-trial EEG responses, we required estimates of prior-
independent surprisal that are known to modulate neural responses[10]. Since
phonotactic, lexical, and semantic surprisal are undefined for morphed words,
we assessed how well these properties were captured by activations of
speech-based large language models. All morphs and an excerpt of a larger
narrative (Alice in Wonderland, produced by the same speaker) were fed into
'Wav2Vec2.0-large-xlsr-53-german'[21,85] using PyTorch[54] and Transformers[86].
Here, narrative data were included as an independent set of training data.

Layer-specific activations were extracted for each audio file. For computational efficiency, we performed layer-wise principle component analysis over narrative data and projected activations onto a 5-dimensional subspace. For layer selection and to confirm that the resulting activations included the relevant information theoretic measures, we built back-to-back decoding models[30]. In a first step, we built models mapping from layer activations X to observed measures y through a filter G:

$$\arg\min_G \sum_i (y_i - G^T X_i)^2 + \alpha_G ||G||^2$$

where y_i is a feature at trial i, X_i is the corresponding layer-specific activation and α_G is a regularisation parameter. These models were fit over the first half of the narrative data. The remaining half was then used to find the unique variance explained by each feature by mapping from decoded features $\hat{y}$ to observed features y through a filter H:

$$\arg\min_H \sum_i (y_i - H^T \hat{y}_i)^2 + \alpha_H ||H||^2$$

In both cases, we solved for filters G and H using sklearn[80] and PyTorch[54]. Optimal ridge penalties α_G, α_H were found using leave-one-out cross-validation to test 20 logarithmically spaced values between $1e^{-5}-1e^{10}$[80]. This approach was employed for all time points from $0ms$-$500ms$ following phoneme onset, averaging over time to obtain an estimate of the causal contribution of each feature. To improve robustness, this procedure was repeated for 50 permutations of the narrative data[83]. Finally, we computed the proportion of variance explained by each feature to facilitate interpretation[84]:

$$R^2 = \frac{H}{\max_L \sum_i^F H_i}$$

where L are all layers of the LLM and F refers to all features. We then ranked all layers per feature and took the geometric mean across features. The best layer was then selected by taking the median across permutations. For full results, please see Supplementary Fig. 5. Features were operationalised as follows:

Phonotactic surprisal. The probability of a phoneme given its preceding context was estimated using CLEARPOND[87]. At each word position, all phonotactically consistent words (e.g., /t/: *tea, tear, trousers, ...*) were identified, and the probability of the next phoneme (e.g., /iː/) given all observed next phonemes x was computed as:

$$p(\text{phoneme}) = N^{-1} \sum_i^N 1(x_i = \text{phoneme})$$

Lexical surprisal. The probability of a word was estimated using its relative frequency f in CLEARPOND[87] as $p(\text{word}) = \log_{10} f$.

Semantic surprisal. The probability of a word was derived from the cosine similarity of its GloVe embedding g relative to the mean embedding $\mathbb{E}[G]$:

$$p(\text{word}) = 1 + \frac{g \cdot \mathbb{E}[G]}{||g|| \; ||\mathbb{E}[G]||}$$

For all features, surprisal was defined as $-\log_2 p$. Results revealed that, across an array of d-dimensional projections of model activations, layer 19 (transformer layer 12) was consistently sensitive to prior-independent phonotactic, lexical and semantic surprisal (see Supplementary Fig. 5). Therefore, model activations from layer 19 were chosen as control predictors for modeling single-trial EEG responses of morphs.

4.11 Encoding of single-trial EEG data

To investigate whether participants showed neural signatures of speaker-specific acoustic or semantic surprisal, we built encoding models[17,19,20] mapping from stimulus features X to the recorded neural data y for each participant:

$$r(t,n) = \sum_\tau w(\tau, n) s(t - \tau) + \epsilon(t, n)$$

Here $r(t,n)$ is the reconstructed neural signal in channel n at time point t, $w(\tau, n)$ are the β-estimates at lag τ, $s(t-\tau)$ are the corresponding stimulus features, and $\epsilon(t, n)$ are the residuals. For τ, we chose a window between $-100ms$ and $800ms$. Note that coefficients $w(t,n)$ in these models are not strictly temporal response functions given that we used standardised (i.e., dense) design matrices which allowed us to model non-linearly additive effects of consecutive events, at the cost of interpreting coefficients in reference to baseline levels rather than as discrete events. We solved for the forward model W using sklearn[80] and PyTorch[54]:

$$\arg\min_W \sum_t (y_t - W^T S_t)^2 + \alpha_W ||W||^2$$

where optimal ridge penalties α_W were found using leave-one-out cross-validation to test 20 logarithmically spaced values between $1e^{-5} - 1e^{10}$. All models were estimated using 5-fold cross-validation with 50 repetitions[83] and all outcomes and predictors were scaled to have zero mean and unit variance based on the training set to prevent data leakage. Out-of-sample performance was defined as the Pearson correlation between observed neural signals $y(t,n)$ and reconstructions thereof $r(t,n)$ in the held-out test set[17].

Candidate models. Baseline models included predictors for acoustic envelopes

$$\text{envelope}(t) = \sum_i^F |s(i,t)|^{0.6}$$

where F are all frequency bands and t refers to time points in gammatone spectrogram s, as well as acoustic edges[88]

$$\text{edge}(t) = \sqrt{\frac{1}{2\Delta_t} \int_{t-\Delta_t}^{t+\Delta_t} \big(\text{envelope}(\tau) - \mathbb{E}[\text{envelope}(\tau)]\big)^2 d\tau}$$

where $\mathbb{E}[\text{envelope}(\tau)]$ is the mean envelope over $t \pm \Delta_t$. Baseline models also included either projected LLM activations or direct measures of phonotactic, lexical and semantic surprisal, relative to the target word (see Large language models as statistical surrogates).

We then performed step-wise inclusion of speaker-specific and speaker-invariant acoustic and semantic surprisal measures, derived from the predicted acoustic $s(\text{predicted}|\text{speaker})$ and semantic features $p(\text{speaker})$:

$$\text{surprisal}_{\text{acoustic}} = -\log_2\left[1 + f\big(s(\text{stimulus}), s(\text{predicted}|\text{speaker})\big)\right]$$
$$\text{surprisal}_{\text{semantic}} = -\log_2\left[1 + f\big(g, p(\text{speaker})\big)\right]$$

where f denotes cosine similarity and g represents the target word embedding.

Predictors were entered as impulse responses at phoneme or word onsets, depending on feature type. Projected LLM activations, lacking explicit linguistic segmentation, were entered as both.

Statistical inference. Encoding performance improvements were tested using two-sided paired t-tests, with Bonferroni-Holm corrections applied for multiple comparisons.

4.12 Estimating spatiotemporal contributions of predictors

To obtain a clearer view of the spatiotemporal contributions of the predictors of interest, we employed a knock-out procedure.

We first estimated the performance of the full model, r_{full}, by computing the Pearson correlation between the observed EEG signals $y(t, n)$ and reconstructed signals $\hat{y}(t, n|S)$, where S is the full time-resolved design matrix (see Encoding of single-trial EEG data). To isolate the influence of a given predictor at a specific time lag τ, we generated a knock-out design matrix S_τ in which the corresponding coefficient at τ was set to zero. We then computed the knock-out model's performance, $r_{\text{knock-out}}$, as the correlation between observed signals $y(t, n)$ and reconstructed signals $\hat{y}(t, n|S_\tau)$. The spatiotemporal contribution of the predictor at each lag was quantified as:

$$\Delta r_\tau = r_{\text{full}} - r_{\text{knock-out}}$$

To ensure robustness, models were trained using 5-fold cross-validation and evaluated over 50 permutations of the data. The estimated spatiotemporal

contributions Δr_τ were then averaged across folds and permutations. Finally, we normalised these contributions relative to the improvement of the full model over the baseline model's performance, r_{baseline}, yielding a spatiotemporally resolved measure of the variance explained:

$$R_\tau^2 = \frac{\Delta r_\tau}{\mathbb{E}[r_{\text{full}} - r_{\text{baseline}}]}$$

Statistical inference. Significance of spatiotemporal variance explained was tested using cluster-based permutation tests[33]. To compensate for the number of coefficients within each model, Bonferroni corrections were applied.

4.13 Modeling behaviour in congruent and incongruent trials

Reaction times were analysed in R (version 4.03)[69] using lme4[70] and emmeans[71]. Linear mixed models were fit with default parameters. A maximal modelling procedure was followed[72]. Residuals of the identified maximal model were inspected visually.

Reaction times were modeled as

$$\log \text{RT} \sim t \times \text{congruence} \times p(\text{word}|\text{speaker}) + (1|\text{participant})$$

where trial number t and the probability of the word given the speaker $p(\text{word}|\text{speaker})$ were scaled to have zero mean and unit variance. For the random effects structure, we included all reasonable permutations of these predictors as well as the position of the word on screen, the semantic context, the speaker and their distinguishing visual feature. The maximal identifiable model included:

$$(1 + t + p(\text{word}|\text{speaker})|\text{participant} \times \text{context}) +$$
$$(1|\text{participant} \times \text{position}) +$$
$$(1|\text{participant} \times \text{stimulus}) +$$
$$(1|\text{face} \times \text{feature})$$

Supplementary information. Supplementary tables and figures are provided in a separate document accompanying this manuscript.

Acknowledgments. We thank Kristin Derben for assistance with recruitment and data acquisition; Jan Ostrowski and Marike Christiane Maack for help with data acquisition; Annika Garlichs, Carina Ufer, Janika Becker, Maï-Carmen Requena-Komuro, and Philipp Schumann for valuable discussions and code review; and Antoniya Boyanova, Arjen Alink, and Ivana Tanasic for their feedback on the study and manuscript.

Funding. This work was funded by the Emmy Noether program of the Deutsche Forschungsgemeinschaft (German Research Foundation; Grant No DFG BL 1736/1-1).

Competing interests. The authors declare no competing interests.

Ethics approval. The research was approved by the local ethics committee.

Data and code availability. All code for the experiments, preprocessing, and analyses is available at: https://github.com/predcommlab/hearing_is_believing. Data are available from: https://osf.io/snxqm/.

Author contributions. F.S.: conceptualization, methodology, software, investigation, data curation, formal analysis, visualization, writing – original draft, writing – review and editing. H.B.: conceptualization, methodology, supervision, writing – review and editing, funding acquisition.

References

[1] Friston, K.: The free-energy principle: a unified brain theory? Nature Reviews Neuroscience **11**(2), 127–138 (2010). https://doi.org/10.1038/nrn2787. Accessed 2024-01-23

[2] de Lange, F.P., Heilbron, M., Kok, P.: How Do Expectations Shape Perception? Trends in Cognitive Sciences **22**(9), 764–779 (2018). https://doi.org/10.1016/j.tics.2018.06.002. Accessed 2022-10-11

[3] Caucheteux, C., King, J.-R.: Brains and algorithms partially converge in natural language processing. Communications Biology **5**(1), 134 (2022). https://doi.org/10.1038/s42003-022-03036-1. Accessed 2025-02-12

[4] Caucheteux, C., Gramfort, A., King, J.-R.: Evidence of a predictive coding hierarchy in the human brain listening to speech. Nature Human Behaviour **7**(3), 430–441 (2023). https://doi.org/10.1038/s41562-022-01516-2. Accessed 2025-01-16

[5] Brodbeck, C., Hong, L.E., Simon, J.Z.: Rapid Transformation from Auditory to Linguistic Representations of Continuous Speech. Current Biology **28**(24), 3976–39835 (2018). https://doi.org/10.1016/j.cub.2018.10.042. Accessed 2025-02-12

[6] Eisner, F., McQueen, J.M.: Speech Perception. In: Wixted, J.T. (ed.) Stevens' Handbook of Experimental Psychology and Cognitive Neuroscience, pp. 1–46. John Wiley & Sons, Inc., Hoboken, NJ, USA (2018). https://doi.org/10.1002/9781119170174.epcn301. https://onlinelibrary.wiley.com/doi/10.1002/9781119170174.epcn301 Accessed 2023-04-12

[7] Millidge, B., Seth, A., Buckley, C.L.: Predictive Coding: a Theoretical and Experimental Review (2021). https://doi.org/10.48550/ARXIV.2107.12979. Accessed 2023-11-13

[8] Aitchison, L., Lengyel, M.: With or without you: predictive coding and Bayesian inference in the brain. Current Opinion in Neurobiology **46**, 219–227 (2017). https://doi.org/10.1016/j.conb.2017.08.010. Accessed 2022-10-11

[9] Blank, H., Davis, M.H.: Prediction Errors but Not Sharpened Signals Simulate Multivoxel fMRI Patterns during Speech Perception. PLOS Biology **14**(11), 1002577 (2016). https://doi.org/10.1371/journal.pbio.1002577. Accessed 2023-06-28

[10] Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P., De Lange, F.P.: A hierarchy of linguistic predictions during natural language comprehension. Proceedings of the National Academy of Sciences **119**(32), 2201968119 (2022). https://doi.org/10.1073/pnas.2201968119. Accessed 2023-06-12

[11] Kuperberg, G.R., Brothers, T., Wlotko, E.W.: A Tale of Two Positivities and the N400: Distinct Neural Signatures Are Evoked by Confirmed and Violated Predictions at Different Levels of Representation. Journal of Cognitive Neuroscience **32**(1), 12–35 (2020). https://doi.org/10.1162/jocn_a_01465. Accessed 2024-01-22

[12] Corcoran, A.W., Perera, R., Koroma, M., Kouider, S., Hohwy, J., Andrillon, T.: Expectations boost the reconstruction of auditory features from electrophysiological responses to noisy speech. Cerebral Cortex **33**(3), 691–708 (2023). https://doi.org/10.1093/cercor/bhac094. Accessed 2025-05-26

[13] Kok, P., Jehee, J.M., de Lange, F.: Less Is More: Expectation Sharpens Representations in the Primary Visual Cortex. Neuron **75**(2), 265–270 (2012). https://doi.org/10.1016/j.neuron.2012.04.034. Accessed 2024-12-18

[14] Jaramillo, S., Zador, A.: Auditory cortex mediates the perceptual effects of acoustic temporal expectation. Nature Precedings (2010). https://doi.org/10.1038/npre.2010.5139.1. Accessed 2025-02-05

[15] Press, C., Kok, P., Yon, D.: The Perceptual Prediction Paradox. Trends in Cognitive Sciences **24**(1), 13–24 (2020). https://doi.org/10.1016/j.tics.2019.11.003. Accessed 2023-11-15

[16] Garlichs, A., Blank, H.: Prediction error processing and sharpening of expected information across the face-processing hierarchy.

Nature Communications **15**(1), 3407 (2024). https://doi.org/10.1038/s41467-024-47749-9. Accessed 2025-01-16

[17] Crosse, M.J., Di Liberto, G.M., Bednar, A., Lalor, E.C.: The Multivariate Temporal Response Function (mTRF) Toolbox: A MATLAB Toolbox for Relating Neural Signals to Continuous Stimuli. Frontiers in Human Neuroscience **10** (2016). https://doi.org/10.3389/fnhum.2016.00604. Accessed 2024-01-19

[18] Kriegeskorte, N.: Representational similarity analysis – connecting the branches of systems neuroscience. Frontiers in Systems Neuroscience (2008). https://doi.org/10.3389/neuro.06.004.2008. Accessed 2025-01-22

[19] Smith, N.J., Kutas, M.: Regression-based estimation of ERP waveforms: I . The rERP framework. Psychophysiology **52**(2), 157–168 (2015). https://doi.org/10.1111/psyp.12317. Accessed 2024-01-23

[20] Smith, N.J., Kutas, M.: Regression-based estimation of ERP waveforms: II . Nonlinear effects, overlap correction, and practical considerations. Psychophysiology **52**(2), 169–181 (2015). https://doi.org/10.1111/psyp.12320. Accessed 2024-11-25

[21] Baevski, A., Zhou, H., Mohamed, A., Auli, M.: wav2vec 2.0: A Framework for Self-Supervised Learning of Speech Representations. arXiv (2020). https://doi.org/10.48550/ARXIV.2006.11477. https://arxiv.org/abs/2006.11477 Accessed 2025-01-22

[22] Bogacz, R.: A tutorial on the free-energy framework for modelling perception and learning. Journal of Mathematical Psychology **76**, 198–211 (2017). https://doi.org/10.1016/j.jmp.2015.11.003. Accessed 2023-03-28

[23] Schneider, F., Blank, H.: (How) do listeners learn talker-specific semantic models? OSF Registries (2024). https://doi.org/10.17605/OSF.IO/UDSZC. https://osf.io/udszc/ Accessed 2025-02-06

[24] Schneider, F., Blank, H.: (How) do listeners learn and apply speaker-specific semantic models? (2024). osf.io/re96j Accessed 2025-01-30

[25] Schneider, F., Blank, H.: Do listeners learn talker-specific semantic models? Stimulus validation (2023). osf.io/3pr7t Accessed 2023-06-29

[26] Shannon, R.V., Zeng, F.-G., Kamath, V., Wygonski, J., Ekelid, M.: Speech Recognition with Primarily Temporal Cues. Science **270**(5234),

303–304 (1995). https://doi.org/10.1126/science.270.5234.303. Accessed 2023-06-28

[27] Patterson, R.D., Robinson, K., Holdsworth, J., McKeown, D., Zhang, C., Allerhand, M.: Complex Sounds and Auditory Images. In: Auditory Physiology and Perception, pp. 429–446. Elsevier, ??? (1992). https://doi.org/10.1016/B978-0-08-041847-6.50054-X. https://linkinghub.elsevier.com/retrieve/pii/B978008041847650054X Accessed 2025-03-06

[28] Anderson, A.J., Davis, C., Lalor, E.C.: Deep-learning models reveal how context and listener attention shape electrophysiological correlates of speech-to-language transformation. PLOS Computational Biology **20**(11), 1012537 (2024). https://doi.org/10.1371/journal.pcbi.1012537. Accessed 2025-03-26

[29] Goldstein, A., Grinstein-Dabush, A., Schain, M., Wang, H., Hong, Z., Aubrey, B., Nastase, S.A., Zada, Z., Ham, E., Feder, A., Gazula, H., Buchnik, E., Doyle, W., Devore, S., Dugan, P., Reichart, R., Friedman, D., Brenner, M., Hassidim, A., Devinsky, O., Flinker, A., Hasson, U.: Alignment of brain embeddings and artificial contextual embeddings in natural language points to common geometric patterns. Nature Communications **15**(1), 2768 (2024). https://doi.org/10.1038/s41467-024-46631-y. Accessed 2025-03-26

[30] King, J.-R., Charton, F., Lopez-Paz, D., Oquab, M.: Back-to-back regression: Disentangling the influence of correlated factors from multivariate observations. NeuroImage **220**, 117028 (2020). https://doi.org/10.1016/j.neuroimage.2020.117028. Accessed 2025-01-22

[31] Blank, H., Spangenberg, M., Davis, M.H.: Neural Prediction Errors Distinguish Perception and Misperception of Speech. The Journal of Neuroscience **38**(27), 6076–6089 (2018). https://doi.org/10.1523/JNEUROSCI.3258-17.2018. Accessed 2025-02-13

[32] Alink, A., Blank, H.: Can expectation suppression be explained by reduced attention to predictable stimuli? NeuroImage **231**, 117824 (2021). https://doi.org/10.1016/j.neuroimage.2021.117824. Accessed 2025-02-18

[33] Maris, E., Oostenveld, R.: Nonparametric statistical testing of EEG- and MEG-data. Journal of Neuroscience Methods **164**(1), 177–190 (2007). https://doi.org/10.1016/j.jneumeth.2007.03.024. Accessed 2024-01-23

[34] Sassenhagen, J., Draschkow, D.: Cluster-based permutation tests of MEG/EEG data do not establish significance of effect latency or location. Psychophysiology **56**(6), 13335 (2019). https://doi.org/10.1111/psyp.13335. Accessed 2025-02-12

[35] Lau, E.F., Phillips, C., Poeppel, D.: A cortical network for semantics: (de)constructing the N400. Nature Reviews Neuroscience **9**(12), 920–933 (2008). https://doi.org/10.1038/nrn2532. Accessed 2025-02-12

[36] Kutas, M., Federmeier, K.D.: Thirty Years and Counting: Finding Meaning in the N400 Component of the Event-Related Brain Potential (ERP). Annual Review of Psychology **62**(1), 621–647 (2011). https://doi.org/10.1146/annurev.psych.093008.131123. Accessed 2025-02-12

[37] Correia, J.M., Jansma, B., Hausfeld, L., Kikkert, S., Bonte, M.: EEG decoding of spoken words in bilingual listeners: from words to language invariant semantic-conceptual representations. Frontiers in Psychology **6** (2015). https://doi.org/10.3389/fpsyg.2015.00071. Accessed 2025-02-12

[38] Le, T.T., Luong, D.A.Q., Joo, H., Kim, D., Woo, J.: Differences in spatiotemporal dynamics for processing specific semantic categories: An EEG study. Scientific Reports **14**(1), 31918 (2024). https://doi.org/10.1038/s41598-024-83417-0. Accessed 2025-02-12

[39] Lewendon, J., Mortimore, L., Egan, C.: The Phonological Mapping (Mismatch) Negativity: History, Inconsistency, and Future Direction. Frontiers in Psychology **11**, 1967 (2020). https://doi.org/10.3389/fpsyg.2020.01967. Accessed 2024-01-22

[40] Theodore, R.M., Myers, E.B., Lomibao, J.A.: Talker-specific influences on phonetic category structure. The Journal of the Acoustical Society of America **138**(2), 1068–1078 (2015). https://doi.org/10.1121/1.4927489. Accessed 2023-06-29

[41] Krumbiegel, J., Ufer, C., Blank, H.: Influence of voice properties on vowel perception depends on speaker context. The Journal of the Acoustical Society of America **152**(2), 820–834 (2022). https://doi.org/10.1121/10.0013363. Accessed 2023-06-29

[42] Severijnen, G.G.A., Bosker, H.R., Piai, V., McQueen, J.M.: Listeners track talker-specific prosody to deal with talker-variability. Brain Research **1769**, 147605 (2021). https://doi.org/10.1016/j.brainres.2021.147605. Accessed 2023-06-29

[43] Dufour, S., Nguyen, N.: Does Talker-Specific Information Influence Lexical Competition? Evidence From Phonological Priming. Cognitive Science **41**(8), 2221–2233 (2017). https://doi.org/10.1111/cogs.12472. Accessed 2023-06-29

[44] Goldinger, S.D.: Echoes of echoes? An episodic theory of lexical access. Psychological Review **105**(2), 251–279 (1998). https://doi.org/10.1037/0033-295X.105.2.251. Accessed 2023-06-29

[45] McLennan, C.T., Luce, P.A.: Examining the Time Course of Indexical Specificity Effects in Spoken Word Recognition. Journal of Experimental Psychology: Learning, Memory, and Cognition **31**(2), 306–321 (2005). https://doi.org/10.1037/0278-7393.31.2.306. Accessed 2023-06-29

[46] Moses, D.A., Metzger, S.L., Liu, J.R., Anumanchipalli, G.K., Makin, J.G., Sun, P.F., Chartier, J., Dougherty, M.E., Liu, P.M., Abrams, G.M., Tu-Chan, A., Ganguly, K., Chang, E.F.: Neuroprosthesis for Decoding Speech in a Paralyzed Person with Anarthria. New England Journal of Medicine **385**(3), 217–227 (2021). https://doi.org/10.1056/NEJMoa2027540. Accessed 2023-06-12

[47] Mitchell, T.M., Shinkareva, S.V., Carlson, A., Chang, K.-M., Malave, V.L., Mason, R.A., Just, M.A.: Predicting Human Brain Activity Associated with the Meanings of Nouns. Science **320**(5880), 1191–1195 (2008). https://doi.org/10.1126/science.1152876. Accessed 2023-07-07

[48] Huth, A.G., Lee, T., Nishimoto, S., Bilenko, N.Y., Vu, A.T., Gallant, J.L.: Decoding the Semantic Content of Natural Movies from Human Brain Activity. Frontiers in Systems Neuroscience **10** (2016). https://doi.org/10.3389/fnsys.2016.00081. Accessed 2023-07-07

[49] Tang, J., LeBel, A., Jain, S., Huth, A.G.: Semantic reconstruction of continuous language from non-invasive brain recordings. Nature Neuroscience **26**(5), 858–866 (2023). https://doi.org/10.1038/s41593-023-01304-9. Accessed 2023-06-12

[50] d'Ascoli, S., Bel, C., Rapin, J., Banville, H., Benchetrit, Y., Pallier, C., King, J.-R.: Decoding individual words from non-invasive brain recordings across 723 participants. arXiv (2024). https://doi.org/10.48550/ARXIV.2412.17829. https://arxiv.org/abs/2412.17829 Accessed 2025-02-13

[51] Woods, K.J.P., Siegel, M.H., Traer, J., McDermott, J.H.: Headphone screening to facilitate web-based auditory experiments. Attention, Perception, & Psychophysics **79**(7), 2064–2072 (2017). https://doi.org/10.3758/s13414-017-1361-2. Accessed 2023-06-29

[52] Salvatier, J., Wiecki, T.V., Fonnesbeck, C.: Probabilistic programming in Python using PyMC3. PeerJ Computer Science **2**, 55 (2016). https://doi.org/10.7717/peerj-cs.55. Accessed 2023-04-12

[53] Kumar, R., Carroll, C., Hartikainen, A., Martin, O.: ArviZ a unified library for exploratory analysis of Bayesian models in Python. Journal of Open Source Software **4**(33), 1143 (2019). https://doi.org/10.21105/joss.01143. Accessed 2023-06-12

[54] Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G.,

Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., Bai, J., Chintala, S.: PyTorch: An Imperative Style, High-Performance Deep Learning Library (2019). https://doi.org/10.48550/ARXIV.1912.01703. Accessed 2023-06-29

[55] Pennington, J., Socher, R., Manning, C.: Glove: Global Vectors for Word Representation. In: Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP), pp. 1532–1543. Association for Computational Linguistics, Doha, Qatar (2014). https://doi.org/10.3115/v1/D14-1162. http://aclweb.org/anthology/D14-1162 Accessed 2023-02-10

[56] DeepsetAI: GloVe embeddings DE. https://gitlab.com/deepset-ai/open-source/glove-embeddings-de Accessed 2023-06-28

[57] Boersma, P., Weenink, D.: Praat: doing Phonetics by Computer. https://www.fon.hum.uva.nl/praat/ Accessed 2023-06-28

[58] Kawahara, H., Morise, M., Takahashi, T., Nisimura, R., Irino, T., Banno, H.: Tandem-STRAIGHT: A temporally stable power spectral representation for periodic signals and applications to interference-free spectrum, F0, and aperiodicity estimation. In: 2008 IEEE International Conference on Acoustics, Speech and Signal Processing, pp. 3933–3936 (2008). https://doi.org/10.1109/ICASSP.2008.4518514. ISSN: 2379-190X

[59] Sakoe, H., Chiba, S.: Dynamic programming algorithm optimization for spoken word recognition. IEEE Transactions on Acoustics, Speech, and Signal Processing **26**(1), 43–49 (1978). https://doi.org/10.1109/TASSP.1978.1163055. Accessed 2023-06-28

[60] Paliwal, K.K., Agarwal, A., Sinha, S.S.: A modification over Sakoe and Chiba's dynamic time warping algorithm for isolated word recognition. Signal Processing **4**(4), 329–333 (1982). https://doi.org/10.1016/0165-1684(82)90009-3. Accessed 2023-06-28

[61] Brown, J.C.: Calculation of a constant Q spectral transform. The Journal of the Acoustical Society of America **89**(1), 425–434 (1991). https://doi.org/10.1121/1.400476. Accessed 2023-06-28

[62] Kisler, T., Reichel, U., Schiel, F.: Multilingual processing of speech via web services. Computer Speech & Language **45**, 326–347 (2017). https://doi.org/10.1016/j.csl.2017.01.005. Accessed 2025-04-02

[63] FaceGen | 3D face maker software. https://facegen.com/index.htm Accessed 2023-06-29

[64] De Leeuw, J.R., Gilbert, R.A., Luchterhandt, B.: jsPsych: Enabling an Open-Source Collaborative Ecosystem of Behavioral Experiments. Journal of Open Source Software **8**(85), 5351 (2023). https://doi.org/10.21105/joss.05351. Accessed 2024-01-18

[65] Peirce, J., Gray, J.R., Simpson, S., MacAskill, M., Höchenberger, R., Sogo, H., Kastman, E., Lindeløv, J.K.: PsychoPy2: Experiments in behavior made easy. Behavior Research Methods **51**(1), 195–203 (2019). https://doi.org/10.3758/s13428-018-01193-y. Accessed 2025-01-31

[66] Klem, G.H., Lüders, H.O., Jasper, H.H., Elger, C.: The ten-twenty electrode system of the International Federation. The International Federation of Clinical Neurophysiology. Electroencephalography and Clinical Neurophysiology. Supplement **52**, 3–6 (1999)

[67] Raunak, V., Gupta, V., Metze, F.: Effective Dimensionality Reduction for Word Embeddings. In: Proceedings of the 4th Workshop on Representation Learning for NLP (RepL4NLP-2019), pp. 235–243. Association for Computational Linguistics, Florence, Italy (2019). https://doi.org/10.18653/v1/W19-4328. https://www.aclweb.org/anthology/W19-4328 Accessed 2023-02-10

[68] Mu, J., Bhat, S., Viswanath, P.: All-but-the-Top: Simple and Effective Postprocessing for Word Representations (2017). https://doi.org/10.48550/ARXIV.1702.01417. Accessed 2023-06-12

[69] Team, R.C.: R: A Language and Environment for Statistical Computing (2020). https://www.r-project.org/ Accessed 2023-06-29

[70] Bates, D., Mächler, M., Bolker, B., Walker, S.: Fitting Linear Mixed-Effects Models Using lme4. Journal of Statistical Software **67**(1) (2015). https://doi.org/10.18637/jss.v067.i01. Accessed 2023-04-12

[71] Lenth, R.V., Bolker, B., Buerkner, P., Giné-Vázquez, I., Herve, M., Jung, M., Love, J., Miguez, F., Riebl, H., Singmann, H.: emmeans: Estimated Marginal Means, aka Least-Squares Means (2023). https://cran.r-project.org/web/packages/emmeans/index.html Accessed 2023-06-29

[72] Barr, D.J., Levy, R., Scheepers, C., Tily, H.J.: Random effects structure for confirmatory hypothesis testing: Keep it maximal. Journal of Memory and Language **68**(3), 255–278 (2013). https://doi.org/10.1016/j.jml.2012.11.001. Accessed 2023-06-29

[73] Yarkoni, T.: The generalizability crisis. Behavioral and Brain Sciences **45**, 1 (2022). https://doi.org/10.1017/S0140525X20001685. Accessed 2023-01-18

[74] Hartig, F., Lohse, L.: DHARMa: Residual Diagnostics for Hierarchical (Multi-Level / Mixed) Regression Models (2022). https://cran.r-project.org/web/packages/DHARMa/index.html Accessed 2023-06-29

[75] Gramfort, A.: MEG and EEG data analysis with MNE-Python. Frontiers in Neuroscience **7** (2013). https://doi.org/10.3389/fnins.2013.00267. Accessed 2025-01-22

[76] Peng, W.: EEG Preprocessing and Denoising. In: Hu, L., Zhang, Z. (eds.) EEG Signal Processing and Feature Extraction, pp. 71–87. Springer, Singapore (2019). https://doi.org/10.1007/978-981-13-9113-2_5. http://link.springer.com/10.1007/978-981-13-9113-2$_5 Accessed 2025 - 02 - 12$

[77] Hyvarinen, A.: Fast and robust fixed-point algorithms for independent component analysis. IEEE Transactions on Neural Networks **10**(3), 626–634 (1999). https://doi.org/10.1109/72.761722. Accessed 2025-01-22

[78] Accou, B., Vanthornhout, J., Hamme, H.V., Francart, T.: Decoding of the speech envelope from EEG using the VLAAI deep neural network. Scientific Reports **13**(1), 812 (2023). https://doi.org/10.1038/s41598-022-27332-2. Accessed 2023-06-12

[79] Pasley, B.N., David, S.V., Mesgarani, N., Flinker, A., Shamma, S.A., Crone, N.E., Knight, R.T., Chang, E.F.: Reconstructing Speech from Human Auditory Cortex. PLoS Biology **10**(1), 1001251 (2012). https://doi.org/10.1371/journal.pbio.1001251. Accessed 2025-03-20

[80] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Müller, A., Nothman, J., Louppe, G., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., Duchesnay, : Scikit-learn: Machine Learning in Python (2012). https://doi.org/10.48550/ARXIV.1201.0490. Accessed 2025-01-22

[81] uxlfoundation/scikit-learn-intelex. Unified Acceleration (UXL) Foundation (2025). https://github.com/uxlfoundation/scikit-learn-intelex Accessed 2025-01-22

[82] Haufe, S., Meinecke, F., Görgen, K., Dähne, S., Haynes, J.-D., Blankertz, B., Bießmann, F.: On the interpretation of weight vectors of linear models in multivariate neuroimaging. NeuroImage **87**, 96–110 (2014). https://doi.org/10.1016/j.neuroimage.2013.10.067. Accessed 2025-01-31

[83] Valente, G., Castellanos, A.L., Hausfeld, L., De Martino, F., Formisano, E.: Cross-validation and permutations in MVPA: Validity of permutation strategies and power of cross-validation schemes. NeuroImage

238, 118145 (2021). https://doi.org/10.1016/j.neuroimage.2021.118145. Accessed 2025-03-20

[84] Gwilliams, L., King, J.-R., Marantz, A., Poeppel, D.: Neural dynamics of phoneme sequences reveal position-invariant code for content and order. Nature Communications **13**(1), 6606 (2022). https://doi.org/10.1038/s41467-022-34326-1. Accessed 2024-05-30

[85] facebook/wav2vec2-large-xlsr-53-german · Hugging Face (2024). https://huggingface.co/facebook/wav2vec2-large-xlsr-53-german Accessed 2025-01-22

[86] Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., Davison, J., Shleifer, S., von Platen, P., Ma, C., Jernite, Y., Plu, J., Xu, C., Scao, T.L., Gugger, S., Drame, M., Lhoest, Q., Rush, A.M.: HuggingFace's Transformers: State-of-the-art Natural Language Processing (2019). https://doi.org/10.48550/ARXIV.1910.03771. Accessed 2023-06-29

[87] Marian, V., Bartolotti, J., Chabal, S., Shook, A.: CLEARPOND: Cross-Linguistic Easy-Access Resource for Phonological and Orthographic Neighborhood Densities. PLoS ONE **7**(8), 43230 (2012). https://doi.org/10.1371/journal.pone.0043230. Accessed 2024-01-18

[88] Oganian, Y., Chang, E.F.: A speech envelope landmark for syllable encoding in human superior temporal gyrus. Science Advances **5**(11), 6279 (2019). https://doi.org/10.1126/sciadv.aay6279. Accessed 2025-01-31

A

60 word pairs → 2 contexts/pair
(e.g., *sea*, *tea*) ← (e.g., *nature*, *food*)

[tiː] [tiː]

vocode and morph

[ɛː]

speaker contexts:
— fashion — arts — nature
— politics — tech — food

B

0.50 s — fixation

0.75 s — cue: speaker_nature or speaker_food

≤ 0.87 s — morph of *sea* & *tea*

≤ 2.00 s — choice

0.75 s — feedback

C

— early
— late

p(chose word)

p(word|speaker) (z-score)

D

Speaker-invariant prior

· words ○ prior

Speaker-specific priors

· words ○ priors

Principal component$_2$

Principal component$_1$

E

Sharpening

sea
tea

— repr.|no prior
— repr.|nature prior

Prediction error

$\not{sea}$
tea

— repr.|no prior
— repr.|nature prior

Principal component$_2$

Principal component$_1$