Sensory sharpening and semantic prediction errors unify competing models of predictive processing in communication

Fabian Schneider[1,2*] and Helen Blank[1,2]

[1]Institute for Systems Neuroscience, University Medical Centre Hamburg-Eppendorf, Martinistr. 52, Hamburg, 20246, Hamburg, Germany.
[2]Faculty of Psychology, Ruhr University Bochum, Universitätsstr. 150, Bochum, 44801, North-Rhine Westphalia, Germany.

*Corresponding author(s). E-mail(s): f.schneider@uke.de;
Contributing authors: helen.blank@rub.de;

Abstract

The human brain makes abundant predictions in speech comprehension that, in real-world conversations, depend on conversational partners. Yet, tested models of predictive processing diverge on how such predictions are integrated with incoming speech: The brain may emphasise either expected information through sharpening or unexpected information through prediction error. We reconcile these views through direct neural evidence from electroencephalography showing that both mechanisms operate at different hierarchical levels during speech perception. Across multiple experiments, participants heard identical ambiguous speech in different speaker contexts. Using speech decoding, we show that listeners learn speaker-specific semantic priors, which sharpen sensory representations by pulling them toward expected acoustic signals. In contrast, encoding models leveraging pretrained transformers reveal that prediction errors emerge at higher linguistic levels. These findings support a unified model of predictive processing, wherein sharpening and prediction errors coexist at distinct hierarchical levels to facilitate both robust perception and adaptive world models.

Keywords: predictive coding, Bayesian brain, speech comprehension, semantics, speaker-specificity

1 Introduction

The human brain continuously predicts incoming sensory inputs from generative models of the world, allowing for rapid and efficient perception [1,2]. In the domain of speech perception, predictive mechanisms have recently been demonstrated to operate across multiple levels, from low-level acoustic features to high-level semantic structure [3–5]. Yet, most studies have focused on speech perception in monologic contexts such as audiobooks, leaving open how predictive processes unfold in actual conversational settings, in which our main goal is to understand another person. In natural dialogue, predictions may track not only general linguistic statistics but also, crucially, leverage speaker-specific semantic priors—i.e., our expectations of what the other person is going to talk about. For example, if Jamie habitually talks about food, speaker-specific semantic predictions may be crucial for correctly comprehending *Jamie: I'm putting my beans/dreams on the back-burner*, particularly under common challenging listening conditions such as noisy environments or poor phone lines [6]. However, whether such speaker-specific predictions occur remains untested.

While prominent theories like hierarchical predictive coding (hPC) propose that higher-level priors, such as semantic expectations, generate lower-level predictions, such as acoustic predictions, to facilitate perception and ambiguity resolution [1,7], how priors are applied at a mechanistic level is highly debated [2,8]: Empirically, prior work has reported enhancement of either expected components of the signal (sharpening), improving veridicality of representations [9–12], or unexpected parts of the signal (prediction error), improving informativeness of representations [13–16]. Yet, models of predictive processing typically assume distinct neuronal units for both sharpening and prediction error within regions [1,2]. Models tested in many empirical approaches, however, include only sharpening or prediction error components [9,11,12,15,16] and often do not track their dynamics jointly across time and levels of processing [10,13,14]. Therefore, it remains unclear how sharpening and prediction error computations are coordinated in function, over time, and across levels of the neural hierarchy [2,17]. Recent theoretical work predicts a hierarchical split: sharpening should dominate early sensory stages to stabilise perception, and prediction error should dominate later, higher-level stages to support adaptive updating of world models, but concrete evidence has been limited [18].

Here, we provide direct evidence that speaker-specific semantic priors modulate neural processing by sharpening early auditory representations, while generating prediction errors at the level of semantics. In a series of experiments, participants learned to identify acoustically ambiguous words in different speaker contexts that were cued with different faces. We show that participants apply speaker-specific semantic priors when resolving ambiguities, reporting to hear the word consistent with the speaker's semantic context. Using stimulus reconstruction models [19] and within-item composite representational similarity [20] regression of recorded electroencephalography (EEG) responses, we show that these priors manifest in early sharpening of neural representations, with low-level acoustic content shifted toward the expected acoustic signal. Further,

single-trial encoding models[21,22] leveraging pretrained transformers[23] reveal that speaker-specific prediction errors emerge at the higher semantic level instead, albeit with a relatively early modulation of the EEG signal. Finally, we employ real-time modeling of semantic priors using free-energy models[24] to show that participants flexibly deploy and discard speaker-specific priors, depending on the probability of words under the prior. This dynamic interplay between flexible application of priors through low-level sharpening and high-level prediction errors provides new insights into how humans perceive and learn to adapt to individual speakers to maintain robust comprehension in acoustically ambiguous settings and critical evidence for a unified model of predictive processing in communication.

2 Results

To examine how listeners apply speaker-specific semantic priors, participants learned to associate six distinct faces with six unique semantic contexts—i.e., fashion, politics, arts, tech, nature, food—in two independent, preregistered experiments[25,26] (online $N_1 = 35$, EEG $N_2 = 35$, see Fig. 1a). Each trial began with a speaker's face that cued a speaker-specific semantic context. Participants then heard a degraded morphed word that combined two words— only one of which fit the speaker's semantic context—and subsequently selected the perceived word from the two words making up the morph written on the screen (see Fig. 1b).

As morphing two words may not result in perfectly ambiguous sounds, we measured context-free perception of each morph in an independent, preregistered experiment[27] ($N = 40$) and used these results as control predictors for acoustic unambiguities in subsequent analyses. In addition, we degraded the spoken words with a vocoding technique[28] so that the voice sounded like a whisper and voice-identity information was removed (see Stimulus creation). This allowed us to avoid any voice differences and link the identical spoken input to different faces, as we were interested in testing the effect of semantic priors on the representation of speech.

Speaker-specific feedback was provided visually by highlighting choices that were congruent or incongruent with the speaker in green or red, respectively, to ensure that each speaker was consistently linked to their semantic context (see Fig. 1b). To track participants' semantic expectations throughout the experiment, we computed trial-by-trial estimates of their semantic priors by fitting Gaussian distributions over semantic embeddings of the words they reported to hear through free-energy models in real-time (see Estimating real-time semantic models). To be able to dissociate learning of speaker-specific semantics and general semantics across the experiment (e.g., learning what kinds of semantic contexts are included in the experiment across all speakers) or, to a lesser degree, sequence effects (e.g., responses at trial t biasing responses at trial $t+1$ irrespective of speaker-context), we fit two types of models: Firstly, modeling

speaker-specific semantic priors, i.e. one prior per individual speaker, and, secondly, estimating speaker-invariant semantic priors, i.e., one general semantic prior across all six speaker contexts (see Fig. 1d).

Critically, the same ambiguous morph (e.g., *sea-tea*) was presented in different speaker contexts (e.g., *nature-food*), allowing us to test whether perception and the underlying representation was pulled toward (i.e., sharpening) or away from the speaker priors (i.e., prediction error, see Fig. 1d,e). For example, an idealised sharpened representation of the morph between *sea*-tea given a speaker who was associated with the semantic context *nature* would be more similar to *sea* and related words, whereas the idealised prediction error representation would be more similar to *tea* and related words instead.

Fig. 1 **A** Stimuli. Sixty word pairs were created (e.g., *sea-tea*) where words within a pair sounded similar and could each be associated with one of six semantic contexts (e.g., *sea-tea* corresponding to *nature-food*). To decrease clarity and to induce ambiguity, words were slightly degraded to sound like a whisper and morphed into an intermediate acoustic signal between two words from two different contexts. Morphs were validated in a separate validation experiment (see Stimulus creation). **B** EEG part one with morphed words. Trials began with a fixation cross, followed by a visual speaker cue. Morphs were presented binaurally. Participants then indicated the word they had heard by button press. Finally, feedback was given in a speaker-specific manner such that each speaker could be associated with one specific semantic context. Faces were generated using FaceGen[29]. **C** Participants were more likely to report hearing a word when it was highly probable given the respective speaker (see Modeling choice behaviour). This preference increased over time. Lines are model predictions. Shaded areas around lines are 95%-confidence intervals. *** indicates $p \leq 1e^{-3}$. **D** We tested two potential forms of priors (large dots) that might influence neural responses to words (small dots): First, participants may apply one general, i.e., speaker-invariant prior reflecting general semantic expectations. Second, participants may learn and apply speaker-specific priors, i.e., six distinct priors, reflecting expectations about the individual speaker contexts. **E** In Bayesian models of the brain, there are two competing hypotheses about the application of priors: Firstly, prior expectations may pull neural representations towards the expected information (sharpening), i.e., when the speaker talking about nature is expected the representation of the morph (*sea-tea*) is shifted towards expected words (e.g., *sea*). Secondly, prior expectations may push neural representations towards more unexpected information (prediction error), i.e., when the speaker talking about nature is expected the representation of the morph (*sea-tea*) is shifted towards unexpected words (e.g., *tea*).

2.1 Behavioural analysis shows that listeners apply speaker-specific semantic priors

In experiment one, participants ($N_1 = 35$, see Participants) were cued with a speaker's face and subsequently listened to a degraded spoken word (see

Fig. 1b). We modelled the probability of reporting to have heard any word as a function of trial number, the word's probability given the speaker and remaining acoustic biases of morphs. Participants reported to hear the word consistent with the speaker's semantic context (generalised linear mixed model (GLMM), $\beta = 1.64, s.e. = 0.12, z = 13.11, p = 2.71e^{-39}, \text{odds-ratio} = 5.16$), and this effect increased over trials ($\beta = 0.43, s.e. = 0.03, z = 12.77, p = 2.41e^{-37}, \text{odds-ratio} = 1.54$). Correspondingly, participants relied on acoustic unambiguities initially (GLMM, $\beta = -0.62, s.e. = 0.11, z = -5.81, p = 6.26e^{-9}, \text{odds-ratio} = 0.54$), but reliance on these decreased over trials (GLMM, $\beta = 0.39, s.e. = 0.06, z = 6.09, p = 1.14e^{-9}, \text{odds-ratio} = 1.48$; see Supplementary Table 1, Supplementary Fig. 1).

In experiment two (different $N_2 = 35$, see Participants), we directly replicated these behavioural findings (see Fig. 1c, Supplementary Table 2, Supplementary Fig. 1) while also recording EEG responses. Together, these behavioural results demonstrate that listeners can learn and apply speaker-specific semantic priors to aid disambiguation in speech perception when speaker-context associations are reinforced with speaker-specific feedback (see Fig. 1d). These behavioural findings, cannot speak to the computational mechanisms at play, as speaker-specific feedback rendered consistent behavioural errors unlikely and neural mechanisms underlying representation may diverge from simple behavioural read-outs[17].

2.2 EEG analysis reveals that speaker-specific acoustic predictions sharpen sensory representations

Next we used EEG to investigate whether speaker-specific semantic priors modulate early sensory processing or high-level decision-making and whether they sharpen expected stimulus representations or induce prediction errors instead (see Fig. 1d,e), potentially across different time points and stages of the processing hierarchy. To determine whether speaker-specific semantic priors influence low-level sensory representations early into the neural processing hierarchy, we employed an approach combining stimulus reconstruction models and within-item composite representational similarity analysis (cRSA; see Regressing composite representational similarity).

First, gammatone filters, which model the human auditory system[30], were used to generate spectrograms reflecting the time-frequency representation of all morphed auditory stimuli. The high temporal resolution of EEG then enabled us to isolate sensory representations in the recorded neural data by correspondingly reconstructing gammatone spectrograms from EEG data following the presentation of the morphs (see Fig. 2a, Stimulus reconstruction of morphs). We confirmed that spectrogram reconstruction from EEG was successful, as reconstruction performance—measured as the correlation between reconstructed spectrograms from the EEG and audio spectrograms from the corresponding morphs—was above chance-level overall (two-sided one-sample t-test, $M = 0.06, s.d. = 0.02, t(34) = 17.06, p = 8.96e^{-17}$; see Fig. 2c) and in

all individual frequency bands (two-sided one-sample t-test, all $p \leq 2.53e^{-6}$, see Supplementary Fig. 2, Supplementary Table 3).

In a within-item cRSA approach, we computed cosine similarities of the reconstructed spectrograms from EEG signals following presentation of the identical morph in different contexts (e.g., *sea-tea|nature*, *sea-tea|food*, see Fig. 2b) with the real audio spectrograms of the corresponding original words (e.g., *sea*, *tea*) to obtain a similarity matrix of the composite sensory representations (i.e., sensory cRSM).

We therefore measured within-item similarity, as opposed to between-item similarity as used in conventional RSA[20]. This approach was chosen because conventional RSA requires a commitment to specific mathematical formulations of the proposed computations for the construction of hypothesis RDMs[20]. However, theories of predictive processing allow for extremely high degrees of freedom in the precise formulation of their computations[7,8,31–33] which have been repeatedly criticised for hindering falsification[34–36]. Our experimental design, instead, aimed at differentiating between families of computations (see Fig. 1a,b,d,e): Do sensory representations drift towards (i.e., common to sharpening computations) or away from predictions (i.e., common to prediction error computations)? Anchoring decoded representational content to real constituent acoustic spectrograms allowed us to directly test for directional shifts in representational content given the same auditory stimulus in different speaker contexts (see Regressing composite representational similarity) rather than testing geometric signatures of specific mathematical formulations in second-order comparisons used in conventional RSA[20]. While anchoring decoded representational content in real acoustic spectrograms may inflate absolute scores in cRSA regressions, relative explained variance between predictors on which our conclusions rely remain unbiased.

To be able to assess the representational content in sensory cRSMs, we built two types of hypothesis cRSMs: Firstly, we built acoustic hypothesis cRSMs from spectrograms of clear words that were predictable from participants' speaker-specific and -invariant semantic priors. Specifically, we selected the five most probable words under a speaker prior and combined them into one probability-weighted audio spectrogram (for analysis of the influence of the number of predicted words, see Supplementary Figures 3-4, Supplementary Tables 4-5). This was done because predictions in the brain are inherently distributional[1]: The brain cannot preminisce the target word at each trial, but predictions should reflect the distribution of predicted acoustic features instead (see Supplementary Methods 1.1). Secondly, we generated semantic hypothesis cRSMs by comparing the semantic embeddings of the constituent words (e.g., *sea*, *tea* for morph *sea-tea*) with the current estimates of the speaker-specific and speaker-invariant semantic priors from free-energy models (see Fig. 2b, see also Estimating real-time semantic models). Correlations between hypothesis cRSMs were confirmed to be low, ruling out significant variance inflation (see Supplementary Fig. 5). We systematically regressed hypothesis cRSMs on sensory cRSMs in a hierarchical manner to assess the unique contributions of each

hypothesis cRSM on sensory cRSMs, controlling for low-level acoustic features and general linguistic statistics that were independent of the semantic priors manipulated in our experiment (see Fig. 2b; see also Regressing composite representational similarity). We hypothesised that speaker-specific semantic priors generate predictions at the acoustic level, i.e., acoustic predictions, which either pull sensory representations towards the expected signal—i.e., make the representation more similar to the expected words (sharpening)— or push them away from it—i.e., render the representation more similar to the unexpected words (prediction error, see Fig. 1d,e).

cRSM regression revealed an effect of both speaker-specific and speaker-invariant semantic priors on acoustic representations. The sensory cRSMs were predicted more accurately when accounting for speaker-invariant and speaker-specific acoustic predictions (two-sided paired samples t-test, invariant-baseline: $t(34) = 22.40, p = 1.47e^{-20}$, specific-baseline: $t(34) = 25.12, p = 4.04e^{-22}$). Yet, speaker-specific acoustic predictions explained sensory cRSMs better than speaker-invariant acoustic predictions, indicating an increased reliance on speaker-specific information (two-sided paired samples t-test, specific-invariant: $t(34) = 4.18, p = 2.11e^{-3}$). Crucially, combining both types of acoustic cRSMs revealed their effects to be additive, with significantly better out-of-sample predictions than using either alone (two-sided paired samples t-test, both-baseline: $t(34) = 31.67, p = 2.33e^{-27}$, both-invariant: $t(34) = 17.87, p = 1.33e^{-17}$, both-specific: $t(34) = 15.03, p = 2.35e^{-15}$; see Fig. 2d). While differences in correlation coefficients reported here were relatively small, differences were highly consistent across participants, and absolute differences were comparable to those commonly reported in RSA [17,20]. These findings suggest that predictions based on both speaker-invariant and speaker-specific semantic priors clearly shape the acoustic representations of heard words, though with a greater importance of speaker-specific priors.

Fig. 2 A Stimulus reconstruction models were used to decode acoustic signals $\hat{s}$ from neural activity X during presentation of the same morph s given both of its potential speaker contexts (e.g., *nature* and *food* for morph *sea-tea*, see Stimulus reconstruction of morphs). This allowed us to compare sensory content of neural representations directly in a within-item composite representational similarity analysis (see Regressing composite representational similarity). Faces were generated using FaceGen [29]. **B** Composite sensory representational similarity matrices (cRSMs) were computed from the reconstructions of the identical morph given two speaker contexts (e.g., *nature* and *food*) and the two spectrograms of the audio files of the original word pair. A set of hypothesis cRSMs were computed from the raw morph, top-5 acoustic predictions, and the current semantic predictions. Hypothesis cRSMs were systematically regressed on sensory cRSMs to test which combination of predictors best explained the similarity structure of decoded neural representations (see Regressing composite representational similarity). **C** Stimulus reconstruction models performed significantly above chance level. The inlay shows the average pattern that reconstruction models decoded in z-scored EEG signals. **D** cRSM regression revealed that both speaker-invariant and speaker-specific acoustic cRSMs improved the similarity structure of decoded neural representations, and that purely semantic cRSMs failed to do so. Improvements in out-of-sample prediction are visualised relative to baseline models. Circles indicate group means with error bars on circles indicating 95%-confidence intervals thereof. Transparent dots indicate single subjects. ***, **, and * indicate $p \leq 1e^{-3}$, $p \leq 1e^{-2}$ and $p \leq 5e^{-2}$, respectively. Note that significantly worse performance indicates evidence against a specific model, not in favour of its antithesis. Bold black lines between groups indicate $p \leq 5e^{-2}$. All p-values were corrected using the Bonferroni-Holm procedure. **E** Time-resolved coefficients of speaker-specific acoustic cRSMs in regressions showed consistently positive signs, indicating that neural representations were sharpened towards the more expected information present in hypothesis cRSMs. Lines represent means, with shaded areas around lines indicating 95%-confidence intervals. Bold black lines indicate $p \leq 5e^{-2}$. Grey dots represent the median on- and offsets of the first and last phonemes, respectively, with 95%-highest density intervals around them.

To assess the specificity of these predictions to the acoustic level, we also tested whether purely semantic predictions would yield the same results.

We entered the semantic embeddings used for top-5 predictions as semantic hypothesis cRSMs in the model, but omitted the step of generating specific acoustic predictions from these embeddings. Critically, purely semantic hypothesis cRSMs failed to improve out-of-sample predictions (two-sided paired samples t-test, invariant-baseline: $t(34) = -2.19, p = 0.25$, specific-baseline: $t(34) = -10.88, p = 1.66e^{-11}$, both-baseline: $M = t(34) = -7.93, p = 3.69e^{-8}$; see Fig. 2d). These results indicate that speaker-specific semantic priors alter sensory representations at the acoustic level.

Next, we asked how speaker-specific predictions are combined with the incoming sensory signals at the acoustic level. We examined whether the neural representations reflected sharpening or prediction error by using the best regression model's β-coefficients—i.e., the model incorporating both speaker-invariant and -specific acoustic hypothesis cRSMs. Our hypothesis cRSMs were designed to reflect a pattern wherein more expected information is represented in positive values. In turn, due to the geometry of cosine similarities, this means that a negative sign inverts this pattern to represent more unexpected information (see Fig. 2e). Consequently, positive and negative coefficients in our models naturally correspond to sharpening and prediction error computations, respectively, which allowed us to directly test the directionality of the effect of acoustic predictions on sensory representations. Cluster-based permutation tests revealed significant positive coefficients for speaker-specific acoustic predictions ($p \leq 8.00e^{-4}$) which corresponded to a cluster between $165ms$-$1000ms$ ($M = 0.22, s.d. = 0.04$; see Fig. 2e). These findings demonstrate that speaker-specific semantic priors sharpen neural representations by pulling neural representations towards the expected acoustic signal.

We addressed several potential confounding factors: To rule out that our results depend on, firstly, the specific number of predicted words, we refit the best cRSM regression model while systematically varying the number of top-k predictions from 1 to 19, as there were 20 words per speaker. This analysis revealed significant stepwise improvements in out-of-sample performance, with diminishing returns for larger k (see Supplementary Fig. 3, Supplementary Table 4). We verified that our results were robust by repeating all previous analyses using $k = 19$ predictions (see Supplementary Fig. 4, Supplementary Table 5). Secondly, we confirmed that top-k acoustic predictions captured meaningful acoustic expectations of participants that could not be explained equally well by top-k predictions that were not participant-specific (see Supplementary Methods 1.1-1.2, Supplementary Fig. 6, Supplementary Table 6). Further, we replicated our key finding of the dominance of acoustic sharpening at the sensory level in a conventional between-item RSA using $k = 1$ to rule out results being dependent on, thirdly, anchoring of hypothesis and sensory cRSMs to the same real spectrograms or, fourthly, averaging of spectrogram features (see Supplementary Methods 1.3, Supplementary Fig. 7, Supplementary Table 7). Finally, we also verified results do not depend on the length of acoustic predictions (see Supplementary Methods 1.3, Supplementary Fig. 8, Supplementary Table 8).

2.3 Speaker-specific semantic priors induce prediction error representations at higher levels

Building on our finding that speaker-specific semantic priors sharpen low-level sensory representations, we next examined whether prediction errors emerge at higher levels of the speech-processing hierarchy instead. To do this, we built encoding models (i.e., multivariate temporal response functions[19,21,22], mTRFs) of single-trial EEG signals that allowed us to probe signatures of acoustic and semantic prediction errors in the broadband EEG response. Critically, modeling broadband EEG responses rather than decoded sensory representations allowed us to probe whether prediction errors still co-occurred at, for example, the acoustic level as a separate information theoretic signal without shifting sensory representations. Since single-trial EEG signals are strongly influenced by stimulus properties such as acoustic envelopes and edges and general information theoretic measures like general phonotactic, lexical and semantic prediction errors, irrespective of the priors in our experiment[4,15], we implemented baseline encoding models to control for these general properties and language-specific prediction errors.

However, measuring prediction errors for morphs at levels higher than acoustics presents a unique challenge, as these stimuli are ill-defined at the phoneme and word level. To address this, we utilised recent advances in pre-trained transformers[23], which allowed us to approximate general prediction error signals by feeding the raw audio of the morphs into these models and extracting 5-dimensional subspace projections of their layer activations[37,38]. Before feeding projected activations into encoding models, we verified that projected model activations were sensitive to general phonotactic, lexical and semantic prediction errors, and selected the best layer through back-to-back decoding[39]. This allowed us to disentangle the unique variance explained by each measure of prediction error in spite of existing correlations, in an independent auditory dataset (see Pretrained transformers as statistical surrogates, see also Supplementary Fig. 9).

In line with prior research[4,15], we framed prediction errors in terms of surprisal—i.e., the negative log probability. We then tested whether single-trial EEG signals could be predicted from speaker-specific or -invariant acoustic or semantic surprisal beyond baseline models that included general stimulus properties and projected LLM activations that controlled for general surprisal, irrespective of the semantic priors in our experiment (see Fig. 3a, Encoding of single-trial EEG data).

Results revealed that prediction errors emerged only at higher levels and only with respect to speaker-specific semantic priors. Concretely, speaker-invariant surprisal failed to improve encoding performance, irrespective of the hierarchical level (two-sided paired samples t-test, acoustic-baseline: $t(34) = -1.58, p = 0.49$, semantic-baseline: $t(34) = 1.11, p = 0.55$, both-baseline: $t(34) = 0.16, p = 0.87$). Crucially, speaker-specific surprisal improved encoding performance, but only at the semantic level (two-sided paired samples t-test, acoustic-baseline: $t(34) = -6.30, p = 1.78e^{-6}$, semantic-baseline: $t(34) =$

5.33, $p = 1.90e^{-5}$, both-baseline: $t(34) = 1.81, p = 0.08$, see Fig. 3b). This suggests that while sharpening of speaker-specific representations occurs at the acoustic level, the brain computes prediction errors not at the acoustic level, but at the semantic level where predictions had been generated instead.

Fig. 3 **A** Pretrained transformers were employed to obtain control predictors for general phonotactic, lexical and semantic surprise (see Pretrained transformers as statistical surrogates). Single-trial encoding of EEG responses was then applied to reconstruct observed EEG signals from control predictors and hypothesised speaker-invariant and speaker-specific surprisal predictors (see Encoding of single-trial EEG data). Faces were generated using FaceGen [29]. **B** Encoding models revealed that only speaker-specific semantic surprisal could significantly improve model performance. Encoding improvements are visualised relative to baseline models. Note that significant negative effects indicate that models failed to produce generalisable improvements. Circles indicate group means with error bars indicating 95%-confidence intervals thereof. Transparent dots represent subjects. ***, **, and * indicate $p \leq 1e^{-3}$, $p \leq 1^{e}-2$ and $p \leq 5e^{-2}$, respectively. Bold black lines between groups indicate $p \leq 5e^{-2}$. All p-values were corrected using the Bonferroni-Holm procedure. **C** Spatiotemporally resolved contributions of speaker-specific semantic surprisal were estimated using a knock-out procedure (see Estimating spatiotemporal contributions of predictors). Speaker-specific semantic surprisal explained variance significantly with a corresponding cluster spanning a wide array of channels between $150ms$-$630ms$. Lines indicate the mean of variance explained, with shaded areas around them representing 95%-confidence intervals. Bold black lines indicate $p \leq 5e^{-2}$. The topography shows variance explained within each sensor, with channels contributing to the cluster highlighted in black.

To probe the spatiotemporal dynamics of speaker-specific semantic surprisal, we systematically eliminated the influence of speaker-specific semantic surprisal from the full model at temporal lags $\tau = \{-0.1, ..., 0.8\}s$, and measured the change in encoding performance of the full model over the reduced model relative to total encoding improvement of the full model over the baseline model, which yields an estimate of the variance explained at any time point and channel (see Estimating spatiotemporal contributions of predictors). This knock-out procedure allowed us to directly test which temporal lags had a robust impact on encoding performance rather than having to rely on mTRF coefficients that may also reflect at least some degree of overfitting [40]. Cluster-based permutation tests revealed significant variance explained by speaker-specific semantic surprisal ($p \leq 1.80e^{-3}$) corresponding to a cluster

spanning all sensors between $150ms$-$630ms$ (see Fig. 3c). This spatiotemporal cluster aligns with the interpretation that speaker-specific prediction errors emerge primarily at levels higher than acoustics within the linguistic hierarchy, such as at the phonological and semantic levels.

Finally, we verified the robustness of these findings in two complementary analyses. First, increasing the dimensionality of the LLM activation subspace to 10^{37} to ensure that results were not an artefact of under-specified control predictors yielded consistent results (see Supplementary Fig. 10, Supplementary Table 9). Second, we also verified that deriving control predictors for general properties and prediction errors from the target word rather than the morph's activation in the LLM produced consistent results to ensure that effects were not an artefact of poor performance of the LLM for morphed words (see Supplementary Fig. 11, Supplementary Table 10). Together, these analyses confirm the reliability of our results and the emergence of speaker-specific prediction errors at the higher levels.

2.4 Flexible deployment of speaker-specific semantic priors

To test the flexibility of how speaker-specific semantic priors are applied during speech perception, we conducted an additional experimental task (EEG part two, see Fig. 4a) in which we manipulated the degree to which the incoming sensory evidence conflicted with the preceding priors. Using real-time semantic models, we selected clear words where $word_1$ and $word_2$ were either highly congruent or highly incongruent with the speaker's expected semantics (e.g., *salad* vs. *senate* for *food*). Participants identified vocoded, but unmorphed, words following a speaker cue (see Fig. 4a).

Participants were significantly slower in incongruent trials, suggesting increased surprise or decisional conflict (linear mixed model (LMM), $\beta = 0.10, s.e. = 0.02, t(1606) = 5.41, p = 7.30e^{-8}$, see Fig. 4b; see also Modeling behaviour in congruent and incongruent trials). Crucially, reaction times scaled with the probability of a word given the speaker in congruent trials (estimated marginal trends (EMT) at $\mathbb{E}\left[p(\text{word}|\text{speaker})\right]$, $\beta = -0.12, s.e. = 0.02, t(9) = -5.53, p = 3.33e^{-4}$), but not in incongruent trials (EMT, $\beta = -0.02, s.e. = 0.02, t(14) = -0.89, p = 0.39$; see Fig. 4b). For incongruent trials, this effect emerged only over trials (LMM, congruence$\times trial \times p$(word|speaker): $\beta = -0.03, s.e. = 0.02, t(3976) = -2.07, p = 3.83e^{-2}$). Thus, while participants continued to leverage speaker-specific priors, they seemed to discard them initially when encountering highly improbable words, incurring a switch cost.

Fig. 4 A EEG part two with congruent and incongruent words. A fixation cross was displayed, followed by the presentation of a visual speaker-cue. Highly congruent or incongruent vocoded words under the speaker prior were presented. Participants reported the word they heard. Face were generated using FaceGen[29]. **B** Participants incurred a processing cost in incongruent trials. However, reaction times scaled with speaker-specific semantic surprisal only in congruent trials. Circles indicate group means with error bars indicating 95%-confidence intervals. Transparent dots indicate single subjects. Bold black lines between groups indicate $p \leq 5e^{-2}$. Shaded areas around lines indicate 95%-confidence intervals. **C** Encoding models revealed a double dissociation: In incongruent trials, only speaker-invariant semantic surprisal significantly improved encoding performance, whereas in congruent trials only speaker-specific semantic surprisal significantly boosted encoding performance. Encoding improvements are visualised relative to baseline models. Significant negative effects indicate that models failed to produce generalisable improvements. Circles indicate group means with error bars on circles showing 95%-confidence intervals. Transparent dots show individual participants. Bold black lines between groups indicate $p \leq 5e^{-2}$. ***, **, and * represent $p \leq 1e^{-3}$, $p \leq 1e^{-2}$ and $p \leq 5e^{-2}$, respectively. The downward-facing triangles indicate the best models by congruence. All p-values were corrected using the Bonferroni-Holm procedure. **D** Knock-out analysis of coefficients revealed significant variance explained by speaker-invariant semantic surprisal in incongruent trials (top) as well as by speaker-specific semantic surprisal in congruent trials (bottom). Speaker-invariant semantic surprisal was associated with a cluster across all channels between $170ms$-$345ms$, and speaker-specific semantic surprisal was associated with a cluster across all channels between $190ms$-$635ms$. Lines indicate means with shaded areas representing 95%-confidence intervals. Inlaid topographies show variance explained across sensors, with sensors contributing to clusters marked in black. Bold black lines indicate $p \leq 5e^{-2}$.

EEG encoding models mirrored this pattern: In incongruent trials, only speaker-invariant semantic surprisal boosted encoding performance (semantic-baseline: $t(34) = 3.03, p = 1.88e^{-2}$; see Fig. 4c), whereas in congruent trials only speaker-specific semantic surprisal significantly improved encoding performance (semantic-baseline: $t(34) = 8.39, p = 3.39e^{-8}$; see Fig. 4c,

see also Supplementary Table 11). Knock-out analyses revealed significant
variance explained by speaker-invariant semantic surprisal in incongruent tri-
als ($p \leq 1.40e^{-3}$), corresponding to a cluster across all channels between
170ms-345ms, and significant variance explained by speaker-specific semantic
surprisal in congruent trials ($p \leq 1.40e^{-3}$), corresponding to a cluster across
all channels between 190ms-635ms (see Fig. 4d). This double dissociation of
semantic congruency and specificity of the semantic priors demonstrates that
listeners dynamically deploy and discard speaker-specific priors depending on
contextual plausibility.

3 Discussion

In this study, we investigated whether listeners utilise speaker-specific seman-
tic priors to facilitate speech comprehension, and how such priors influence
processing at different levels of the processing hierarchy. Specifically, we aimed
to resolve a long-standing debate on whether predictive processing operates
primarily via prediction error or sharpening mechanisms[1,10,13,18]. Our findings
provide clear evidence for an integrated account in which both mechanisms
coexist at distinct levels of the hierarchy, as suggested by more recent accounts
of the Bayesian brain[18].

First, we demonstrate that listeners can apply speaker-specific semantic
priors to disambiguate acoustically ambiguous words when speaker-context
associations are consistently reinforced through feedback (see Fig. 1c). Second,
we show that these priors sharpen low-level sensory representations, actively
shifting them towards the expected acoustic signal (see Fig. 1e, Fig. 2d,e).
Third, while sharpening occurs at the acoustic level, prediction errors emerge
at higher linguistic levels, such as semantics (see Fig. 3b,c Fig. 4c,d). Finally,
we find that speaker-specific semantic priors are not applied indiscriminately:
when the likelihood of a given input under a specific-speaker prior is exceed-
ingly low, listeners flexibly discard the prior rather than generating extreme
prediction errors and, consequently, potentially deleterious model updates (see
Fig. 4c,d).

These findings align with recent refinements of Bayesian models of the
brain, which propose that sharpening occurs at lower levels while prediction
errors dominate higher levels of the neural hierarchy[2,18]. This nuanced view
departs from traditional models of hPC, which posit that only prediction errors
should be propagated within the hierarchy[1,7]. Instead, our results support a
synergistic account, wherein sharpening enhances perceptual robustness while
prediction errors may enable adaptive updating of internal models[18].

This interpretation is supported by prior work in speech perception demon-
strating sharpening to occur at the sensory level[9,12]–though here explicit
source modeling is lacking–and prediction errors in regions associated with
higher-level processing such as phonology or semantics[13–15,41,42], though pre-
diction errors were also identified in regions typically associated with acoustics
exists[43]. Analogously, prior work in vision supports sharpening in sensory

regions such as V1[10,44], but there are conflicting reports about prediction errors through-out the processing hierarchy[17,45,46]. More recent work in vision suggests that both sharpening and prediction errors may occur in deep and superficial laminae of V1, respectively[47,48], which may partly explain conflicting prior findings and complement the view that sharpening and prediction errors co-occur in cortical layers but dominate at different levels of the neural hierarchy[17,18]. However, laminar differences remain untested in speech comprehension, and cannot fully explain discrepancies between dominance of sharpening or prediction errors without assuming some kind of gain modulation thereof[49].

Here, we report empirical support for sharpening at the acoustic level (see Fig. 2e). Notably, the temporal extent of sharpening suggests that sharpening is not constrained to times of high uncertainty—for example, only for the disambiguating phonemes of a morph such as /t/ or /s/ for morph *tea-sea*—but occurs in parallel with the temporally unfolding acoustic signal instead. Sharpening at the acoustic level stands in contrast with previous findings emphasising the role of prediction error in speech processing[3,4,13–15]. This discrepancy may stem at least partly from methodological differences: whereas previous studies primarily analysed broadband EEG or BOLD responses, we employed speech decoding models[19] to isolate changes in low-level sensory representations. Supporting this view, evidence of sharpening in monologic contexts has previously been reported using similar sensory decoding approaches[9,12], albeit only for speech envelopes rather than low-level acoustic representations as captured with full spectrograms.

Our task was carefully constructed to test facilitation of speech comprehension through speaker-specific semantic priors that were reinforced through explicit speaker-specific feedback. Therefore, it is also conceivable that other tasks demanding attention towards unexpected features, such as deviation detection, might shift low-level representations towards prediction error representations[49]. In complementary RSA analyses over decoded sensory representations, we also found some evidence of possible co-occurring prediction errors at the acoustic level that were, however, considerably weaker than sharpening responses (see Supplementary Figs. 7-8) and not apparent in the broadband EEG signal (see Figs. 3-4). This would be in line with the view that sharpening and prediction error computations co-occur in sensory regions at different laminae[47,48] where we might expect task- or context-based gain modulation[49] to dictate the dominance of sharpening or prediction error at the sensory level. We speculate that, even in this view, sharpening should dominate in natural, dialogic settings, in line with a synergistic account of sharpening and prediction errors[18].

Yet, while these supplementary RSA results hint at weakly co-occurring acoustic prediction error at the sensory level (see Supplementary Figs. 7-8), we do not find evidence thereof in regressions of sensory cRSMs (see Fig. 2d) or encoding models of broadband EEG responses (see Fig. 3). In the case of cRSM regression, this is expected given that supplementary RSA results

show acoustic sharpening to be considerably stronger than acoustic prediction errors (see Supplementary Fig. 7): When investigating the directionality of the representational shift overall, the stronger sharpening effect should dominate the weaker prediction error effect. That encoding models of broadband EEG responses do not support acoustic prediction errors (see Fig. 3d; Fig. 4) demonstrates the critical role that analysis granularity may play. As with sharpening, it is possible that multivariate sensory prediction errors are not easily detectable in commonly employed broadband encoding of univariate distance metrics[15,42]. In all, investigating predictive processing in natural speech by incorporating a wider array of methodologies–particularly, placing greater importance on representational content, laminar resolution of activity, and task-demands–may allow comparing and disentangling sharpening and prediction error computations at the acoustic level across monologic and dialogic contexts more thoroughly. Within regions, sharpening and prediction errors may be represented in deep and superficial layers, respectively[47,48], and across regions sharpening may dominate prediction errors at the sensory level[18] unless task-demands place greater importance on deviation detection[49].

Interestingly, here we find that speaker-specific prediction errors emerge relatively early—with clusters around $150ms$-$630ms$ and $190ms$-$635ms$ after stimulus onset in the main task testing perception of morphed, i.e., ambiguous words, and the follow-up task testing congruent and incongruent words, respectively (see Fig. 3c, Fig. 4d). Differences in temporal extent of these clusters are difficult to interpret, given that cluster-based permutation testing does not guarantee significance at specific time points[50,51]. However, peak latencies showed no differences between tasks, with peaks consistently around $252ms$ post stimulus onset (see Supplementary Fig. 12). This is striking given that semantic prediction errors are typically thought to peak around $400ms$ post onset[52,53]. While semantic processing has previously been reported around 250ms[54,55], an alternative interpretation may be that prediction errors induced by semantic priors arise at multiple intermediate and higher-level stages—first at the phonemic and then the semantic levels, which would be in agreement with the prolonged time course of speaker-specific prediction errors. While this would also be consistent with hPC where prediction errors are propagated along the processing hierarchy[1,18], there is a long-standing debate whether EEG components around this time can even be separated into functionally distinct phonemic and semantic components[52,56]. Given the limited size of the stimulus set in this study, we cannot derive appropriate estimates of speaker-specific phonemic surprisal, leaving this question open for future research. Crucially, this does not change the interpretation of our findings with respect to hierarchical processing in models of the Bayesian brain.

With respect to both sharpening and prediction error computations reported here, two further avenues are of interest that fall beyond the scope of this paper: Firstly, source estimates would allow identification of their neural loci which we would expect to peak in A1, reflecting early auditory processing, and more distributed frontal and temporoparietal sources, reflecting

later stages of semantic processing, respectively[52,53,57]. Secondly, theories of predictive coding have hypothesised distinct oscillatory signatures of predictions in lower and prediction errors in higher frequency bands[58,59] that may be investigated using MEG with individualised head casts to improve source estimates[60,61].

Our findings also highlight a key theoretical gap in predictive models: while it is commonly assumed that the brain constructs multiple types of priors at all levels of the processing hierarchy[1,7,18], the precise mechanism by which competing priors are selected remains unclear. The coexistence of priors at the same level—such as speaker-specific and speaker-invariant semantic priors—may be crucial for tracking multiple relevant statistical regularities, yet our results suggest that not all priors are applied simultaneously. Instead, we find a double dissociation of prior congruency and specificity at higher levels of the neural hierarchy, where priors are selected dynamically based on their relative likelihood. Specifically, a speaker-specific prior was only applied when the incoming word was congruent with that prior. This has important implications for predictive coding models, particularly in the context of world model updates[1,7]: Firstly, allowing, for example, detection of a new semantic topic when listening to the identical speaker. Secondly, if all high-level priors were applied and updated indiscriminately, they would risk collapsing into a single, undifferentiated representation. Thus, priors must be selectively updated, potentially through precision-weighting mechanisms that govern their influence.

Most previous studies on predictive processing have primarily examined speech perception in monologic contexts such as audiobooks[3,4,15], leaving open the question of how semantic predictions may operate in speaker-specific conversational settings. Our study investigated how predictions are shaped not only by general linguistic statistics but also by speaker-specific characteristics. Thereby our approach extends and links to previous experimental findings showing that listeners adapt to individual speakers at, for example, the phonetic[62–64] and lexical levels[65–67]. Here we show for the first time that listeners also adapt to semantic patterns of individual speakers. As such, our findings also advance our understanding of how listeners may deal with common sources of uncertainty in the speech signal such as loud environments or poor phone lines[6].

Beyond theoretical implications, our findings have direct relevance for clinical applications, particularly in neural speech decoding and brain-computer interfaces (BCIs). Decoding approaches hold promise of restoring communicative abilities for patients with conditions such as aphasia, anarthria, or locked-in syndrome[68]. While recent advances have improved speech decoding accuracy[69–72], current methods remain data-intensive and lack the precision needed for seamless communication[71,72]. Our results suggest that incorporating individualised speaker-specific models could enhance decoding accuracy, particularly in interactive settings with clinicians or family members, where strong priors may shape communication. Furthermore, an intriguing question

arising from our study is whether speaker-specific semantic priors also influence speech production. If listeners adjust their own speech to match their semantic expectations of a conversational partner, this adaptation could be leveraged in BCIs to improve bidirectional communication and hence may have significant implications for speech rehabilitation and augmentative communication technologies.

In conclusion, we show that listeners learn and apply speaker-specific semantic priors, which actively shape their perceptual experience and sharpen low-level sensory representations towards the expected acoustic signals. Prediction errors, in contrast, emerge at higher levels of the linguistic hierarchy, supporting a complementary role of sharpening and prediction errors in predictive processing. These findings refine our understanding of predictive processing in the brain and suggest new directions for clinical applications, as in the development of dialogic brain-computer interfaces.

4 Methods

The series of experiments of this study was preregistered[25–27]. Across an online and subsequent EEG experiment, participants learned to associate six distinct speakers with six unique semantic contexts (see Fig. 1a). Participants heard identical degraded and morphed auditory stimuli given different speaker contexts (see Fig. 1b), allowing us to probe the influence of speaker-specific semantic priors on neural representations along the speech processing hierarchy (see Fig. 1d,e). In the EEG experiment, participants completed a subsequent follow-up task including degraded unmorphed words that were either particularly congruent or incongruent with their perceived semantic model of any given speaker, which allowed us to test the limits of prior application (see Fig. 4a).

4.1 Participants

In the validation experiment, 40 volunteers were recruited through Prolific and completed the experiment online (20 female, age range 19-40, $M = 28.35 \pm 6.27$). Participants that failed to pass an initial headphone test[73] or failed to respond on ten of the preceding twenty trials were excluded in real-time. A priori power analysis suggested that this would yield sufficient power for χ^2-tests to detect deviations by at least 0.15 from chance-level in individual morphs[27].

In experiment one, 35 different volunteers were recruited through Prolific and participated in the experiment online (17 female, age range 22-39, $M = 29.46 \pm 4.78$). Again, participants were excluded in real-time based on headphone and attention tests. Participants received £9/hr in compensation for their time. Sample size was determined through power simulations using PyMC5[74] and ArviZ[75] based on previous experimental data that indicated sufficient power to detect behavioural effects bigger than log odds 0.15[25].

In experiment two, 36 different volunteers completed the study in the EEG laboratory. One participant was excluded from the analysis due to excessive muscle-related artifacts. The final sample included 35 participants (20 female, age range 20-39, $M = 28.09 \pm 5.29$). Participants were compensated with 13€/hr. Sample size was determined through power simulations based on pilot recordings ($N = 2$) using PyTorch[76] that indicated sufficient power to detect moderate effect sizes in the neural data[26].

In all experiments, all participants were right-handed, native speakers of German, and reported no history of neurological disorders, ADHD, ASD, dyslexia, impaired hearing, or face or colour blindness. All experimental procedures were approved by the Ethics Committee of the Chamber of Physicians in Hamburg and participants provided written informed consent.

4.2 Stimulus creation

An initial list of 210 target words was created by searching the neighbourhood of six semantic contexts (food, fashion, technology, politics, arts, and nature) seeded at the embedding of the context's label in a GloVe embedding pretrained on German Wikipedia articles[77,78]. For each target word, one alternative word corresponding to one of the other five semantic contexts was chosen. Targets and alternatives were chosen such that phonemic differences would be minimal, although not all formed minimal pairs (e.g., sea/tea in food/nature). We purposefully selected pairs of words with minimal acoustic differences, each of which fit into one of six semantic contexts. This allowed us to balance the stimuli symmetrically: Either member of a word pair was used as the target while the other served as the alternative, depending on the preceding context (e.g., target for *sea-tea|nature*: *sea*, but target for *sea-tea|food*: *tea*).

A professional female speaker produced two enunciations of all words (duration: $M = 970ms \pm 144ms$). Audio files were pitch-corrected to roughly 170Hz to minimise cues about gender using Praat[79] and sound pressure levels were normalised to $-20LUFS$ to control for loudness. Next, we used a combination of vocoding and morphing the words twice to obtain two optimal 50%-morphs per pair, each with different noise profiles. Specifically, audio files were vocoded using twelve bands of white noise to remove most of the remaining voice properties from the signal[28]. This level of noise-vocoding was chosen because it has previously been shown to be intelligible, particularly given prior knowledge[13]. From the recorded utterances, we generated four 50%-morphs using Tandem-STRAIGHT[80] after application of dynamic time warping[81,82] over constant-Q transformed[83] audio data that aligned targets and alternatives in time. We computed cosine similarities between morphs and clear words and selected the least biased morph per pair.

Within each pair, perception of a morph as one word or the other was controlled in a preregistered validation experiment[27]. Participants (see Participants) listened to all morphs and had to indicate which of the two visually

presented options they had heard by button press. In total, participants completed 468 trials (6 contexts × 2 practice items + 2 repetitions × 120 morphs +2 repetitions × 6 contexts × 3 control items). Per morph, we computed a descriptive statistic κ that captured the remaining perceptual bias of participants to perceive one word or the other within the pair underlying each morph:

$$\kappa = \frac{p(\text{alternative}|\text{morph}) - \mu}{1 - \mu}$$

Note that μ represents chance level 0.50 here. We then dropped all morphs that did not meet $0.15 \geq \kappa \leq 0.85$ to remove biassed morphs that did not lead to ambiguous perception.

Next, for each target and alternative, the best semantic fits among the six candidate contexts were determined to find the subset of word pairs that maximised the coherence of each semantic context. To do this, we computed cosine similarities between all targets and all alternatives from all contexts (e.g., sea-tea= 0.12, sea-wattage= −0.06, sea-boat= 0.31, ...) and averaged them by context (e.g., sea-nature= 0.38, sea-food= 0.14, sea-fashion= −0.08, ...). We then ranked each pair by the semantic fit to either potential contexts R_t, R_a and computed geometric means across ranks as $(R_t R_a)^{\frac{1}{2}}$ for each pair. We selected word pairs to minimise the geometric means, yielding a total of 60 pairs where word_1 was coherent with one of the six contexts and word_2 was coherent with another (see Fig. 1). As a result of this procedure, we obtained twenty words per context ($6 \times 20 = 120$ words overall), each of which was morphed with one other word, yielding sixty morphs with two different noise profiles that showed no systematic perceptual biases (duration: $M = 867ms \pm 144ms$; for an overview, see Supplementary Fig. 13; Supplementary Table 12). For all, i.e., unmorphed and morphed, words we generated annotations of phoneme on- and offsets using MAUS[84].

Finally, a set of six face images was created using FaceGen[29] to obtain one visual cue per speaker-specific semantic context. Speaker images were crossed with six distinctive features (two types of glasses, scars, piercings each) to ease recognition and images were luminance-corrected.

4.3 Procedure

Stimuli were presented using jsPsych[85] in online experiments, whereas PsychoPy[86] was used in the EEG laboratory. Before all experiments, participants were introduced to the six speakers, each represented by a face and a one-sentence summary of their interests. The online experiment lasted ∼45 minutes, whereas the EEG experiment lasted ∼2.5 hours, including briefing, setup, passive listening (∼20 minutes, not reported here), EEG part one with morphed words (∼35 minutes), EEG part two with congruent and incongruent words (∼15 minutes) and debriefing.

All experiments followed the same trial structure: Each trial began with a fixation cross (500ms), followed by the visual presentation of a speaker

(750ms). Next, a vocoded morph was played ($M = 867ms \pm 144ms$ and, in EEG, 400ms delay) in the online experiment and EEG part one, whereas a vocoded congruent or incongruent word was played in EEG part two ($M = 990ms \pm 147ms$ and 400ms delay). Participants were subsequently shown two word options—one congruent with the speaker's semantic context and one from a different context—and selected the word they perceived via button press (response window: 3000ms online, 2000ms in EEG). To reinforce speaker-specific semantic associations, participants received immediate speaker-specific feedback: their selection was highlighted in green if correct under the speaker and red if incorrect under the speaker (750ms, see Fig. 1b). Feedback was omitted in the EEG part two. The inter-trial interval was randomly jittered between $1.0s - 1.4s$. In the online experiment and EEG part one, participants completed a total of 270 trials (6 practice trials, 24 control trials, 2 repetitions $\times$ 2 contexts $\times$ 60 morphs main trials), with optional breaks every 20 trials. In EEG part two, participants completed 120 trials (60 congruents, 60 incongruents).

During the EEG experiment, real-time estimates of each participant's semantic priors were computed using a free-energy approach that were leveraged for sampling of congruent and incongruent stimuli in part two (see Estimating real-time semantic models). After completion of task one, individual semantic priors were used to sample subject- and speaker-specific word pairs. Each pair contained one word strongly congruent with a speaker's semantic context (i.e., context$_a$) and another word strongly incongruent with a different context (i.e., context$_b$). To maximize the difference in semantic fit, word pairs were selected based on the following criterion:

$$\arg \max_{\text{word, context}} p(\text{word}_1|\text{context}_a) - p(\text{word}_2|\text{context}_b)$$

This ensured that word$_1$ was highly congruent with context$_a$, whereas word$_2$ was particularly incongruent with context$_b$. The sampling procedure also ensured that each context contained ten congruent-incongruent word pairs. This modification made the stimuli clearly identifiable as either congruent or incongruent, allowing us to test how speaker-specific priors are applied when word probability is either very high or very low for a given speaker.

4.4 EEG acquisition

EEG data were acquired using a 64-channel Ag/AgCl active electrode system (ActiCap64; Brain Products) that was placed according to the extended 10-20 system[87]. A total of sixty electrodes were placed centrally, with reference and ground electrodes at FCz and Iz, respectively. Four additional electrodes were placed to record the vertical and horizontal electrooculogram. Recordings were made with impedances $\leq 10k\Omega$. Data were sampled at 1000Hz.

4.5 Estimating real-time semantic models

To dynamically track how participants formed and updated speaker-specific semantic priors during the experiment, we employed a real-time modeling approach based on free-energy optimisation[24]. This was done because the low computational cost allowed us to continuously estimate trial-by-trial shifts in participants' inferred semantic representations of speaker-specific and speaker-invariant priors π for any given speaker i in real-time. To do this, we sought to infer π by maximising $p(\pi|S)$ for some semantic input S.

For efficiency in model estimation, we reduced the original 300-dimensional GloVe embeddings[77,78] to a 50-dimensional subspace that spanned all S. Briefly, we preprocessed demeaned embeddings by applying principal component analysis (PCA), and removing the top $D = 7$ components, and projected data to 50 dimensions, followed by a second iteration of the PCA-based preprocessing. This approach has been shown to improve embedding quality[88,89].

For simplicity, we assumed that π follows a 50-dimensional Gaussian distribution per speaker, with mean μ_i and variance σ_i. Since finding exact solutions for

$$p(\pi|S) = \frac{p(\pi)p(S|\pi)}{\int p(\pi)p(S|\pi)d\pi}$$

is prohibitively expensive to compute, we approximated only the most likely values of π, denoted ϕ, using a free-energy approach. This involved optimising the free-energy

$$F = \ln f(\phi; \mu_i, \sigma_i) + \ln f(S; \phi, \sigma)$$

where f denotes the density. We modeled this as a simple set of nodes comprising the current estimate ϕ, an error term for sensory inputs ε_S, and an error term for priors ε_p, evolving as

$$\dot{\phi} = \varepsilon_S - \varepsilon_p$$
$$\dot{\varepsilon}_S = S - \phi - \Sigma_S \varepsilon_S$$
$$\dot{\varepsilon}_p = \phi - \mu_i I - \Sigma_p \varepsilon_p$$

with parameter updates obtained via gradient ascent:

$$\frac{\partial F}{\partial \mu_i} = I \varepsilon_p, \quad \frac{\partial F}{\partial \Sigma_S} = \frac{1}{2}(\varepsilon_S^2 - \Sigma_S^{-1}), \quad \frac{\partial F}{\partial \Sigma_p} = \frac{1}{2}(\varepsilon_p^2 - \Sigma_p^{-1})$$

For further details on derivations, see[24].

Before the experiment, μ_i was initialised to the mean of the full GloVe space, and variances Σ_p and Σ_S were drawn from a uniform distribution. After each trial, posterior estimates were updated via Euler's method based on the semantic embedding of the word the participant reported. This approach was applied separately to both speaker-invariant and speaker-specific priors, with the former modelled using a single speaker across all contexts. Crucially, whenever prior estimates were used outside this estimation procedure, they were

744 based on the posterior of the previous trial within that context to prevent
745 incorporation of future information.

4.6 Modeling choice behaviour

Behavioural responses from experiments one and two were analysed in R (ver-
sion 4.03)[90] using lme4[91] and emmeans[92]. Generalised linear mixed models
were fit using the 'bobyqa' optimiser with a maximum of $2e^5$ iterations. To
increase generalisability, a maximal model fitting procedure was followed[93,94]
to identify the maximal random effects structure that allowed the model to
converge without singular fit. Residuals within the identified maximal model
were inspected using DHARMa[95].

Behavioral choices were modeled as

$$p(\text{chose word}) \sim t \times \kappa + t \times p(\text{word}|\text{speaker}) + (1|\text{participant})$$

where trial number t, perceptual bias κ and the probability of the word given
the speaker $p(\text{word}|\text{speaker})$ were scaled to have zero mean and unit variance.
Note that probabilities of the word given the speaker were computed as the
cosine similarity between the word's embedding and the priors (see Estimating
real-time semantic models). For the random effects structure, we tested all rea-
sonable permutations that included these predictors as well as the position of
the word on screen, the semantic context, the speaker, and their distinguishing
visual feature.

The maximal identifiable model included the following random effects
structure for data from experiment one:

$$(0 + \kappa + p(\text{word}|\text{speaker})|\text{participant})+$$
$$(1|\text{speaker} \times \text{context}_1 \times \text{context}_2)+$$
$$(1|\text{participant} \times \text{context}_1 \times \text{context}_2)$$

765 and for data from experiment two:

$$(1 + t + \kappa + p(\text{word}|\text{speaker})|\text{participant} \times \text{context}) +$$
$$(1|\text{face} \times \text{feature})$$

766 Note that, while random effects structures differ slightly between experi-
767 ments, all maximal models included the critical random slopes by κ and
768 $p(\text{word}|\text{speaker})$.

4.7 Preprocessing EEG data

770 EEG data were preprocessed using MNE[96] following a preregistered[26], stan-
771 dard preprocessing pipeline[97]. Line noise was removed with a notch filter at
772 $50Hz$ and harmonics. Channels were demeaned and visually inspected for
773 excessive noise. Noisy channels were interpolated ($N = 0 \pm 1$). To identify

rare excessive muscle activity, data were bandpass filtered (110-140Hz, IIR filter), epoched to -500 to 2500ms, z-scored, and visually inspected. Bad trials were flagged. EEG data were then bandpass filtered (0.5-50Hz, IIR filter) and epoched (-500 to 2500ms relative to audio onset). Independent component analysis[98] was employed to remove ocular, cardiac, and muscle-related artifacts. Epochs were re-referenced to the global average and underwent a final visual inspection for trial selection (trials dropped in part one: $N = 8 \pm 6$, part two: $N = 5 \pm 3$). Crucially, this trial selection was applied only for single-trial EEG encoding models where severe artifacts would degrade measured encoding quality. To preserve the critical structure of identical morphs being perceived given different speaker contexts (see Fig. 1), no trials were dropped in the reconstruction-RSA-encoder approach. For single-trial modeling of EEG responses, we applied an additional lowpass filter ($\leq 15Hz$, IIR filter)[15]. All data were downsampled to 200Hz to speed-up subsequent analysis steps.

4.8 Stimulus reconstruction of morphs

To probe the content of low-level sensory representations, we decoded gammatone spectrograms from neural responses following presentation of a morph. To do this, gammatone spectrograms were extracted from raw audio signals at 200Hz across 28 logarithmically spaced frequency bands between $50 - 11025Hz$, analogous to previous work[99]. To improve estimation, spectrograms were smoothed with a 100ms boxcar kernel[100].

We then trained subject-level multivariate stimulus reconstruction models[19] mapping from neural data X to gammatones s:

$$\hat{s}(t) = \sum_n \sum_\tau r(t + \tau, n)g(\tau, n)$$

Here, $\hat{s}(t)$ is the reconstructed gammatone representation at time point t, $r(t + \tau, n)$ is the neural response X at t and channel n time-lagged by τ, and $g(\tau, n)$ is the spatial filter at lag τ. We used a time window of $\tau = \{0, ..., 250\}ms$. We solved for spatiotemporal filters G using sklearn[101], sklearn-intelex[102] and PyTorch[76]:

$$\arg \min_G \sum_t (s_t - G^T R_t)^2 + \alpha_G ||G||^2$$

where optimal ridge penalties α_G were found using leave-one-out cross-validation to test 20 logarithmically spaced values between $1e^{-5} - 1e^{10}$. Inputs X and s were standardised to have zero mean and unit variance. Models were estimated using 5-fold cross-validation. Out-of-sample performance was measured as the Pearson correlation between real spectrograms s and reconstructed spectrograms $\hat{s}$ in the held-out test set, averaged over frequency bins and time points. Decoded patterns were computed following[103]. To improve robustness, this procedure was repeated over 100 permutations of the data. Final estimates were obtained by averaging out-of-sample performance, decoded patterns and stimulus reconstructions.

Statistical inference. To determine overall reconstruction performance, we performed a two-sided one-sample t-test over performance averaged over frequency bands. Further, we tested reconstruction performance in individual frequency bands using two-sided one-sample t-tests. Bonferroni-Holm corrections were applied to adjust for multiple comparisons.

4.9 Regressing composite representational similarity

To determine whether semantic expectations influenced the representation of morphed words at the acoustic level, we computed within-item composite representational similarity matrices[20] comparing reconstructed spectrograms based on the recorded EEG data of the morphed stimuli with the real spectrograms of the audio files making up the respective morphs (e.g., /siː/ and /tiː/ for morph /‿iː/). The observed cRSM for each morph n at time point t was defined as:

$$\text{cRSM}(n,t) = \begin{bmatrix} f(/\text{‿iː}/|\text{nature}, /\text{siː}/) & f(/\text{‿iː}/|\text{food}, /\text{siː}/) \\ f(/\text{‿iː}/|\text{nature}, /\text{tiː}/) & f(/\text{‿iː}/|\text{food}, /\text{tiː}/) \end{bmatrix}$$

where f denotes cosine similarity computed over the frequency bins of gammatone spectrograms. This yielded an cRSM of size $120 \times 2 \times 2 \times 200$ (morph pairs × contexts × words × time points) per participant.

Note that this departs from conventional RSA[20] where RSMs are computed between items, which would have yielded an RSM of size $240 \times 240 \times 200$ (morphs × morphs × time points). Here, we opted for this approach because our research question and design pose a contrast at the within-item level: What is the direction in which predictions change the sensory representations of the same acoustic morph given different speaker contexts–towards or away from predictions (see Fig. 2)? Representational similarity allowed us to jointly model the influence of predictions in different modalities (i.e., acoustics and semantics), while anchoring decoded neural representations directly to real words allowed us to test this directly, without strong mathematical commitments to specific formulations underlying these computations that remain debated[8] but would have been required in a conventional second-order comparison through RSA[20]. Converging evidence from conventional RSA is presented in the supplement (see Supplementary Methods 1.3, Supplementary Fig. 7-8).

We then generated hypothesis cRSMs to assess which representational structures best explained the observed cRSMs. We formulated three core hypotheses to test how acoustic representations changed as a function of the speaker context (see Fig. 2b). For each prior-dependent hypothesis, predictions were derived from both speaker-specific and speaker-invariant priors. Both speaker-specific and -invariant hypotheses were therefore computed following the same procedure, with the only difference being the exact semantic prior distribution π–derived from speaker-specific or speaker-invariant free-energy models (see Estimating real-time semantic models)–that was used.

Prior-independent morph-based representation. First, as a baseline,
if presented morphed words are processed based on the pure, i.e., expectation-
free, acoustics of the morph, representational similarity should reflect the direct
comparison between the morph's gammatone spectrogram (e.g., /‿iː/) and the
respective real spectrogram making up the morph (e.g., /siː/ and /tiː/).

Prior-dependent acoustic representation. If semantic priors influence
the processing of the morphed words already at an acoustic stage, within-item
similarity should reflect expected acoustics derived from the semantic priors.
We estimated these expectations by computing the top-k predicted words:

$$\arg\max_{\text{word}} \sum_i^k p(\text{word}_i|\pi)$$

860 where π is a speaker-specific or -invariant semantic prior distribution
861 derived from free-energy models (see Estimating real-time semantic models).
862 Normalised probabilities were then used to compute a prior-weighted template
863 from the top-k words that reflected expected acoustic features:

$$s(\text{predicted}|\pi) = \sum_i^k p(\text{word}_i|\pi)s(\text{word}_i)$$

Since spectrogram magnitudes are inherently non-negative, there is no
destructive interference here. Instead, this weighted procedure aggregates spec-
tral energy from individual word predictions that together form an expected
template that reflects predicted acoustic features (see Supplementary Meth-
ods 1.1-1.2; see also Supplementary Fig. 6). Expected acoustic templates were
then compared with the respective real spectrograms making up the morph
(e.g., /siː/ and /tiː/).

Because language exhibits strong baseline predictability [3,104], we controlled
for general acoustic expectations that participants may have about German.
To do this, we repeated the exact procedure for top-k predictions outlined
above, but generated predictions from non-specific priors sampled from an
isotropic Gaussian around the vector space's centroid at every trial. Across
large numbers of trials and k, this therefore approximates general statistical
regularities of German, allowing us to control for general predictive processes
that were irrespective of our experiment.

Prior-dependent semantic representation. If semantic priors influ-
ence the processing of the morphed words at higher-level processing
stages—for example, shifting sensory representations uniformly per semantic
context—composite representational similarity should reflect direct compar-
isons between the prior distribution of the semantics given the speaker
$\pi(\text{speaker})$ or speaker-invariant prior π (see Estimating real-time semantic
models) and the word embeddings of the words making up the morph (e.g., *sea*
and *tea*). As before, we computed an additional control predictor to capture
more global statistical regularities.

Modeling approach. To test whether speaker context shifted participants' perception of the same acoustic morphs, we used ridge regressions mapping from hypothesis cRSMs X to sensory cRSMs y for each participant:

$$\hat{y}(t) = \beta_t X_t + \epsilon$$

where β_t are the coefficients at time point t. We constructed a temporally expanded design matrix D and temporally expanded outcomes Y, and solved for the full model β using sklearn[101], sklearn-intelex[102] and PyTorch[76]:

$$\arg\min_{\beta} \sum_i (Y_i - \beta^T D_i)^2 + \alpha_\beta ||\beta||^2$$

Ridge penalties α_β were optimised using leave-one-out cross-validation to test 20 logarithmically spaced values between $1e^{-5} - 1e^{10}$ [101]. Models were estimated using 5-fold cross-validation with 50 repetitions[105] and all outcomes and predictors were scaled to have zero mean and unit variance based on the training set to prevent data leakage. Out-of-sample performance was defined as the Pearson correlation between observed sensory cRSMs $y(t)$ and predicted sensory cRSMs $\hat{y}(t)$ in the held-out test set[99,100]. To ensure comparability across models, we normalised coefficients as:

$$\hat{\beta}_{j,t} = \frac{\beta_{j,t}}{\max_t \sum_j |\beta_j|}$$

Thus, $\hat{\beta}_j$ represents the relative contribution of predictor j to the variance explained[106], while meaningfully preserving signs.

Candidate models. Baseline models predicted sensory cRSMs from hypothesis cRSMs based on audio spectrograms of morphs as well as audio spectrograms and semantic embeddings from general language-specific expectations. We then performed step-wise inclusion of speaker-specific and speaker-invariant acoustic and semantic hypothesis cRSMs.

Statistical inference. Improvements in out-of-sample predictions for each hypothesis cRSM were tested using two-sided paired t-tests, with Bonferroni-Holm corrections applied for multiple comparisons. Significance of temporally resolved variance explained by $\hat{\beta}$ was assessed through cluster-based permutation tests[50]. To compensate for the number of predictors, Bonferroni corrections were applied.

4.10 Pretrained transformers as statistical surrogates

For modeling of single-trial EEG responses, we required estimates of speaker-prior independent surprisal that are known to modulate neural responses[15]. Since phonotactic, lexical, and semantic surprisal are undefined for morphed words, we assessed how well these properties were captured by activations of pretrained transformers in a separate analysis.

To achieve this, an excerpt of a larger narrative (Alice in Wonderland, produced by the same speaker)–wherein phonotactic, lexical, and semantic surprisal were well-defined–was fed into 'Wav2Vec2.0-large-xlsr-53-german'[23,107] using PyTorch[76] and Transformers[108]. Layer-specific activations were extracted for narrative data. For computational efficiency, we performed layer-wise principle component analysis over narrative data and projected activations onto a 5-dimensional subspace. For layer selection and to confirm that the resulting activations included the relevant information theoretic measures, we built back-to-back decoding models[39]. In a first step, we built models mapping from layer activations X to observed measures y through a filter G:

$$\arg \min_G \sum_i (y_i - G^T X_i)^2 + \alpha_G ||G||^2$$

where y_i is a feature at trial i, X_i is the corresponding layer-specific activation and α_G is a regularisation parameter. These models were fit over the first half of the narrative data. The remaining half was then used to find the unique variance explained by each feature by mapping from decoded features $\hat{y}$ to observed features y through a filter H:

$$\arg \min_H \sum_i (y_i - H^T \hat{y}_i)^2 + \alpha_H ||H||^2$$

In both cases, we solved for filters G and H using sklearn[101] and PyTorch[76]. Optimal ridge penalties α_G, α_H were found using leave-one-out cross-validation to test 20 logarithmically spaced values between $1e^{-5} - 1e^{10}$ [101]. This approach was employed for all time points from $0ms$-$500ms$ following phoneme onset, averaging over time to obtain an estimate of the causal contribution of each feature. To improve robustness, this procedure was repeated for 50 permutations of the narrative data[105]. Finally, we computed the proportion of variance explained by each feature to facilitate interpretation[106]:

$$R^2 = \frac{H}{\max_L \sum_i^F H_i}$$

where L are all layers of the LLM and F refers to all features. To identitfy the layer that was maximally sensitive to joint surprisal measures, we then ranked all layers per feature and took the geometric mean across features. The best layer was then selected by taking the median across permutations. For full results, please see Supplementary Fig. 9. Features were operationalised as follows:

Phonotactic surprisal. The probability of a phoneme given its preceding context was estimated using CLEARPOND[109]. At each word position, all phonotactically consistent words (e.g., /t/: *tea, tear, trousers, ...*) were identified, and the probability of the next phoneme (e.g., /iː/) given all observed

next phonemes x was computed as:

$$p(\text{phoneme}) = N^{-1} \sum_{i}^{N} 1(x_i = \text{phoneme})$$

Lexical surprisal. The probability of a word was estimated using its relative frequency f in CLEARPOND[109] as $p(\text{word}) = \log_{10} f$.

Semantic surprisal. The probability of a word was derived from the cosine similarity of its GloVe embedding g relative to the mean embedding $\mathbb{E}[G]$:

$$p(\text{word}) = 1 + \frac{g \cdot \mathbb{E}[G]}{||g|| \; ||\mathbb{E}[G]||}$$

For all features, surprisal was defined as $-\log_2 p$. Results revealed that, across an array of d-dimensional projections of model activations, layer 19 (transformer layer 12) was consistently sensitive to prior-independent phonotactic, lexical and semantic surprisal (see Supplementary Fig. 9).

Finally, we fed all morphs into the model and extracted model activations at layer 19. Model activations were projected into 5- and 10-dimensional subspaces and stored for later use as surrogate predictors that jointly controlled for measures of surprisal that were otherwise undefined for morphs when modeling single-trial EEG responses.

4.11 Encoding of single-trial EEG data

To investigate whether participants showed neural signatures of speaker-specific acoustic or semantic surprisal, we built encoding models[19,21,22] mapping from stimulus features X to the recorded neural data y through multivariate temporal response functions (mTRFs) for each participant:

$$r(t, n) = \sum_{\tau} w(\tau, n) s(t - \tau) + \epsilon(t, n)$$

Here $r(t, n)$ is the reconstructed neural signal in channel n at time point t, $w(\tau, n)$ are the β-estimates at lag τ, $s(t-\tau)$ are the corresponding stimulus features, and $\epsilon(t, n)$ are the residuals. For τ, we chose a window between $-100ms$ and $800ms$. Continuous predictors (e.g., acoustic envelopes, wav2vec2.0 activations) were averaged within each linguistic unit to create discrete predictors at the phoneme and word levels. For features without explicit segmentation (e.g., wav2vec2.0 activations), we constructed both phoneme- and word-level spike regressors in this way. We solved for the forward model W using sklearn[101] and PyTorch[76]:

$$\arg\min_{W} \sum_{t} (y_t - W^T S_t)^2 + \alpha_W ||W||^2$$

where optimal ridge penalties α_W were found using leave-one-out cross-validation to test 20 logarithmically spaced values between $1e^{-5} - 1e^{10}$. All

models were estimated using 5-fold cross-validation with 50 repetitions [105] and all outcomes and predictors were scaled to have zero mean and unit variance based on the training set to prevent data leakage. For predictors, standardisation was applied after lag expansion (i.e., each column of the lagged design matrix S_t was z-scored within the training fold) to ensure that ridge regularisation penalised all lags comparably. Out-of-sample performance was defined as the Pearson correlation between observed neural signals $y(t, n)$ and reconstructions thereof $r(t, n)$ in the held-out test set [19].

Candidate models. Baseline models included predictors for acoustic envelopes

$$\text{envelope}(t) = \sum_i^F |s(i, t)|^{0.6}$$

where F are all frequency bands and t refers to time points in gammatone spectrogram s, as well as acoustic edges [110]

$$\text{edge}(t) = \sqrt{\frac{1}{2\Delta_t} \int_{t-\Delta_t}^{t+\Delta_t} \big(\text{envelope}(\tau) - \mathbb{E}[\text{envelope}(\tau)]\big)^2 d\tau}$$

where $\mathbb{E}[\text{envelope}(\tau)]$ is the mean envelope over $t \pm \Delta_t$. Baseline models also included predictors controlling for general phonotactic, lexical and semantic surprisal. Generally, control predictors were derived from pretrained transformer activations (see Pretrained transformers as statistical surrogates). However, to rule out the possibility of performance of pretrained transformers given morphs confounding results, we also conducted a second set of analyses where control predictors were computed as direct measures of phonotactic, lexical and semantic surprisal by disambiguating the morph to the target word.

We then performed step-wise inclusion of speaker-specific and speaker-invariant acoustic and semantic surprisal measures, derived from the predicted acoustic $s(\text{predicted}|\text{speaker})$ and semantic features $p(\text{speaker})$:

$$\text{surprisal}_{\text{acoustic}} = -\log_2 \Big[1 + f\big(s(\text{stimulus}), s(\text{predicted}|\text{speaker})\big)\Big]$$
$$\text{surprisal}_{\text{semantic}} = -\log_2 \Big[1 + f\big(g, p(\text{speaker})\big)\Big]$$

where f denotes cosine similarity and g represents the target word embedding.

Predictors were entered as impulse responses at phoneme or word onsets, depending on feature type. Projected LLM activations, lacking explicit linguistic segmentation, were entered as both.

Statistical inference. Encoding performance improvements were tested using two-sided paired t-tests, with Bonferroni-Holm corrections applied for multiple comparisons. Specifically, we tested for within-participant differences between models, e.g. t(baseline, speaker-specific acoustic). Encoding performance of baseline models–measured as the Pearson correlation between observed neural responses y and reconstructions thereof r–was confirmed to

be above chance using one-sample t-tests (main task: $M = 0.18$, $s.e. = 0.01$, $t(34) = 26.48, p = 2.80e^{-24}$; exemplar task: $M = 0.15$, $s.e. = 0.01$, $t(34) = 20.92, p = 5.36^{-21}$).

4.12 Estimating spatiotemporal contributions of predictors

To obtain a clearer view of the spatiotemporal contributions of the predictors of interest, we employed a knock-out procedure.

We first estimated the performance of the full model, r_{full}, by computing the Pearson correlation between the observed EEG signals $y(t, n)$ and reconstructed signals $\hat{y}(t, n|S)$, where S is the full time-resolved design matrix (see Encoding of single-trial EEG data). To isolate the influence of a given predictor at a specific time lag τ, we generated a knock-out design matrix S_τ in which the corresponding coefficient at τ was set to zero. We then computed the knock-out model's performance, $r_{\text{knock-out}}$, as the correlation between observed signals $y(t, n)$ and reconstructed signals $\hat{y}(t, n|S_\tau)$. The spatiotemporal contribution of the predictor at each lag was quantified as:

$$\Delta r_\tau = r_{\text{full}} - r_{\text{knock-out}}$$

To ensure robustness, models were trained using 5-fold cross-validation and evaluated over 50 permutations of the data. The estimated spatiotemporal contributions Δr_τ were then averaged across folds and permutations. Finally, we normalised these contributions relative to the improvement of the full model over the baseline model's performance, r_{baseline}, yielding a spatiotemporally resolved measure of the variance explained:

$$R_\tau^2 = \frac{\Delta r_\tau}{\mathbb{E}[r_{\text{full}} - r_{\text{baseline}}]}$$

Statistical inference. Significance of spatiotemporal variance explained was tested using cluster-based permutation tests[50]. To compensate for the number of coefficients within each model, Bonferroni corrections were applied.

4.13 Modeling behaviour in congruent and incongruent trials

Reaction times were analysed in R (version 4.03)[90] using lme4[91] and emmeans[92]. Linear mixed models were fit with default parameters. A maximal modelling procedure was followed[93]. Residuals of the identified maximal model were inspected visually.

Reaction times were modeled as

$$\log \text{RT} \sim t \times \text{congruence} \times p(\text{word}|\text{speaker}) + (1|\text{participant})$$

where trial number t and the probability of the word given the speaker $p(\text{word}|\text{speaker})$ were scaled to have zero mean and unit variance. For the random effects structure, we included all reasonable permutations of these predictors as well as the position of the word on screen, the semantic context, the speaker and their distinguishing visual feature. The maximal identifiable model included:

$$(1 + t + p(\text{word}|\text{speaker})||\text{participant}$$
$$+ (1 + p(\text{word}|\text{speaker})||\text{context})$$
$$+ (1 + p(\text{word}|\text{speaker})||\text{stimulus})$$
$$+ (1 + p(\text{word}|\text{speaker})||\text{position})$$

Supplementary information.   Supplementary tables and figures are provided in a separate document accompanying this manuscript.

Acknowledgments.   We thank Kristin Derben for assistance with recruitment and data acquisition; Jan Ostrowski and Marike Christiane Maack for help with data acquisition; Annika Garlichs, Carina Ufer, Janika Becker, Maï-Carmen Requena-Komuro, and Philipp Schumann for valuable discussions and code review; and Antoniya Boyanova, Arjen Alink, and Ivana Tanasic for their feedback on the study and manuscript.

Funding.   This work was funded by the Emmy Noether program of the Deutsche Forschungsgemeinschaft (German Research Foundation; Grant No DFG BL 1736/1-1 awarded to H.B.).

Competing interests.   The authors declare no competing interests.

Ethics approval.   The research was approved by the local ethics committee.

Data and code availability. All code for the experiments, preprocessing, and analyses is available at: https://github.com/predcommlab/hearing_is_believing. Data are available from: https://osf.io/snxqm/.

Author contributions.   F.S.: conceptualization, methodology, software, investigation, data curation, formal analysis, visualization, writing – original draft, writing – review and editing. H.B.: conceptualization, methodology, supervision, writing – review and editing, funding acquisition.

References

[1] Friston, K.: The free-energy principle: a unified brain theory? Nat Rev Neurosci **11**(2), 127–138 (2010). https://doi.org/10.1038/nrn2787. Accessed 2024-01-23

[2] de Lange, F.P., Heilbron, M., Kok, P.: How Do Expectations Shape Perception? Trends in Cognitive Sciences **22**(9), 764–779 (2018). https://doi.org/10.1016/j.tics.2018.06.002. Accessed 2022-10-11

[3] Caucheteux, C., King, J.-R.: Brains and algorithms partially converge in natural language processing. Commun Biol **5**(1), 134 (2022). https://doi.org/10.1038/s42003-022-03036-1. Accessed 2025-02-12

[4] Caucheteux, C., Gramfort, A., King, J.-R.: Evidence of a predictive coding hierarchy in the human brain listening to speech. Nat Hum Behav **7**(3), 430–441 (2023). https://doi.org/10.1038/s41562-022-01516-2. Accessed 2025-01-16

[5] Brodbeck, C., Hong, L.E., Simon, J.Z.: Rapid Transformation from Auditory to Linguistic Representations of Continuous Speech. Current Biology **28**(24), 3976–39835 (2018). https://doi.org/10.1016/j.cub.2018.10.042. Accessed 2025-02-12

[6] Eisner, F., McQueen, J.M.: Speech Perception. In: Wixted, J.T. (ed.) Stevens' Handbook of Experimental Psychology and Cognitive Neuroscience, pp. 1–46. John Wiley & Sons, Inc., Hoboken, NJ, USA (2018). https://doi.org/10.1002/9781119170174.epcn301. https://onlinelibrary.wiley.com/doi/10.1002/9781119170174.epcn301 Accessed 2023-04-12

[7] Millidge, B., Seth, A., Buckley, C.L.: Predictive Coding: a Theoretical and Experimental Review (2021). https://doi.org/10.48550/ARXIV.2107.12979. Accessed 2023-11-13

[8] Aitchison, L., Lengyel, M.: With or without you: predictive coding and Bayesian inference in the brain. Current Opinion in Neurobiology **46**, 219–227 (2017). https://doi.org/10.1016/j.conb.2017.08.010. Accessed 2022-10-11

[9] Corcoran, A.W., Perera, R., Koroma, M., Kouider, S., Hohwy, J., Andrillon, T.: Expectations boost the reconstruction of auditory features from electrophysiological responses to noisy speech. Cerebral Cortex **33**(3), 691–708 (2023). https://doi.org/10.1093/cercor/bhac094. Accessed 2025-05-26

[10] Kok, P., Jehee, J.M., de Lange, F.: Less Is More: Expectation Sharpens Representations in the Primary Visual Cortex. Neuron **75**(2), 265–270 (2012). https://doi.org/10.1016/j.neuron.2012.04.034. Accessed 2024-12-18

[11] Jaramillo, S., Zador, A.: Auditory cortex mediates the perceptual effects of acoustic temporal expectation. Nat Prec (2010). https://doi.org/10.

1119   1038/npre.2010.5139.1. Accessed 2025-02-05

[12] Broderick, M.P., Anderson, A.J., Lalor, E.C.: Semantic Context Enhances the Early Auditory Encoding of Natural Speech. J. Neurosci. **39**(38), 7564–7575 (2019). https://doi.org/10.1523/JNEUROSCI. 0584-19.2019. Accessed 2025-02-12

[13] Blank, H., Davis, M.H.: Prediction Errors but Not Sharpened Signals Simulate Multivoxel fMRI Patterns during Speech Perception. PLoS Biol **14**(11), 1002577 (2016). https://doi.org/10.1371/journal.pbio.1002577. Accessed 2023-06-28

[14] Blank, H., Spangenberg, M., Davis, M.H.: Neural Prediction Errors Distinguish Perception and Misperception of Speech. J. Neurosci. **38**(27), 6076–6089 (2018). https://doi.org/10.1523/JNEUROSCI.3258-17.2018. Accessed 2025-02-13

[15] Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P., De Lange, F.P.: A hierarchy of linguistic predictions during natural language comprehension. Proc. Natl. Acad. Sci. U.S.A. **119**(32), 2201968119 (2022). https://doi.org/10.1073/pnas.2201968119. Accessed 2023-06-12

[16] Kuperberg, G.R., Brothers, T., Wlotko, E.W.: A Tale of Two Positivities and the N400: Distinct Neural Signatures Are Evoked by Confirmed and Violated Predictions at Different Levels of Representation. Journal of Cognitive Neuroscience **32**(1), 12–35 (2020). https://doi.org/10.1162/ jocn_a_01465. Accessed 2024-01-22

[17] Garlichs, A., Blank, H.: Prediction error processing and sharpening of expected information across the face-processing hierarchy. Nat Commun **15**(1), 3407 (2024). https://doi.org/10.1038/s41467-024-47749-9. Accessed 2025-01-16

[18] Press, C., Kok, P., Yon, D.: The Perceptual Prediction Paradox. Trends in Cognitive Sciences **24**(1), 13–24 (2020). https://doi.org/10.1016/j. tics.2019.11.003. Accessed 2023-11-15

[19] Crosse, M.J., Di Liberto, G.M., Bednar, A., Lalor, E.C.: The Multivariate Temporal Response Function (mTRF) Toolbox: A MATLAB Toolbox for Relating Neural Signals to Continuous Stimuli. Front. Hum. Neurosci. **10** (2016). https://doi.org/10.3389/fnhum.2016.00604. Accessed 2024-01-19

[20] Kriegeskorte, N.: Representational similarity analysis – connecting the branches of systems neuroscience. Front. Sys. Neurosci. (2008). https: //doi.org/10.3389/neuro.06.004.2008. Accessed 2025-01-22

[21] Smith, N.J., Kutas, M.: Regression-based estimation of ERP waveforms: I . The rERP framework. Psychophysiology **52**(2), 157–168 (2015). https://doi.org/10.1111/psyp.12317. Accessed 2024-01-23

[22] Smith, N.J., Kutas, M.: Regression-based estimation of ERP waveforms: II . Nonlinear effects, overlap correction, and practical considerations. Psychophysiology **52**(2), 169–181 (2015). https://doi.org/10.1111/psyp.12320. Accessed 2024-11-25

[23] Baevski, A., Zhou, H., Mohamed, A., Auli, M.: wav2vec 2.0: A Framework for Self-Supervised Learning of Speech Representations. arXiv (2020). https://doi.org/10.48550/ARXIV.2006.11477. https://arxiv.org/abs/2006.11477 Accessed 2025-01-22

[24] Bogacz, R.: A tutorial on the free-energy framework for modelling perception and learning. Journal of Mathematical Psychology **76**, 198–211 (2017). https://doi.org/10.1016/j.jmp.2015.11.003. Accessed 2023-03-28

[25] Schneider, F., Blank, H.: (How) do listeners learn talker-specific semantic models? OSF Registries (2024). https://doi.org/10.17605/OSF.IO/UDSZC. https://osf.io/udszc/ Accessed 2025-02-06

[26] Schneider, F., Blank, H.: (How) do listeners learn and apply speaker-specific semantic models? (2024). osf.io/re96j Accessed 2025-01-30

[27] Schneider, F., Blank, H.: Do listeners learn talker-specific semantic models? Stimulus validation (2023). osf.io/3pr7t Accessed 2023-06-29

[28] Shannon, R.V., Zeng, F.-G., Kamath, V., Wygonski, J., Ekelid, M.: Speech Recognition with Primarily Temporal Cues. Science **270**(5234), 303–304 (1995). https://doi.org/10.1126/science.270.5234.303. Accessed 2023-06-28

[29] FaceGen | 3D face maker software. https://facegen.com/index.htm Accessed 2023-06-29

[30] Patterson, R.D., Robinson, K., Holdsworth, J., McKeown, D., Zhang, C., Allerhand, M.: Complex Sounds and Auditory Images. In: Auditory Physiology and Perception, pp. 429–446. Elsevier, ??? (1992). https://doi.org/10.1016/B978-0-08-041847-6.50054-X. https://linkinghub.elsevier.com/retrieve/pii/B978008041847650054X Accessed 2025-03-06

[31] Spratling, M.W.: A review of predictive coding algorithms. Brain and Cognition **112**, 92–97 (2017). https://doi.org/10.1016/j.bandc.2015.11.003. Accessed 2025-09-08

[32] Heeger, D.J.: Theory of cortical function. Proc. Natl. Acad. Sci. U.S.A. **114**(8), 1773–1782 (2017). https://doi.org/10.1073/pnas.1619788114. Accessed 2025-09-08

[33] Lian, Y., Burkitt, A.N.: Relating sparse and predictive coding to divisive normalization. PLoS Comput Biol **21**(5), 1013059 (2025). https://doi.org/10.1371/journal.pcbi.1013059. Accessed 2025-09-08

[34] Bowers, J.S., Davis, C.J.: Bayesian just-so stories in psychology and neuroscience. Psychological Bulletin **138**(3), 389–414 (2012). https://doi.org/10.1037/a0026450. Accessed 2025-09-08

[35] Miłkowski, M., Litwin, P.: Testable or bust: theoretical lessons for predictive processing. Synthese **200**(6), 462 (2022). https://doi.org/10.1007/s11229-022-03891-9. Accessed 2025-09-08

[36] Bowman, H., Collins, D.J., Nayak, A.K., Cruse, D.: Is predictive coding falsifiable? Neuroscience & Biobehavioral Reviews **154**, 105404 (2023). https://doi.org/10.1016/j.neubiorev.2023.105404. Accessed 2025-09-08

[37] Anderson, A.J., Davis, C., Lalor, E.C.: Deep-learning models reveal how context and listener attention shape electrophysiological correlates of speech-to-language transformation. PLoS Comput Biol **20**(11), 1012537 (2024). https://doi.org/10.1371/journal.pcbi.1012537. Accessed 2025-03-26

[38] Goldstein, A., Grinstein-Dabush, A., Schain, M., Wang, H., Hong, Z., Aubrey, B., Nastase, S.A., Zada, Z., Ham, E., Feder, A., Gazula, H., Buchnik, E., Doyle, W., Devore, S., Dugan, P., Reichart, R., Friedman, D., Brenner, M., Hassidim, A., Devinsky, O., Flinker, A., Hasson, U.: Alignment of brain embeddings and artificial contextual embeddings in natural language points to common geometric patterns. Nat Commun **15**(1), 2768 (2024). https://doi.org/10.1038/s41467-024-46631-y. Accessed 2025-03-26

[39] King, J.-R., Charton, F., Lopez-Paz, D., Oquab, M.: Back-to-back regression: Disentangling the influence of correlated factors from multivariate observations. NeuroImage **220**, 117028 (2020). https://doi.org/10.1016/j.neuroimage.2020.117028. Accessed 2025-01-22

[40] Brodbeck, C., Das, P., Gillis, M., Kulasingham, J.P., Bhattasali, S., Gaston, P., Resnik, P., Simon, J.Z.: Eelbrain, a Python toolkit for time-continuous analysis with temporal response functions. eLife **12**, 85012

(2023). https://doi.org/10.7554/eLife.85012. Accessed 2025-09-11

[41] Rothermich, K., Kotz, S.A.: Predictions in speech comprehension: fMRI evidence on the meter–semantic interface. NeuroImage **70**, 89–100 (2013). https://doi.org/10.1016/j.neuroimage.2012.12.013. Accessed 2025-09-19

[42] Donhauser, P.W., Baillet, S.: Two Distinct Neural Timescales for Predictive Speech Processing. Neuron **105**(2), 385–3939 (2020). https://doi.org/10.1016/j.neuron.2019.10.019. Accessed 2025-09-08

[43] Sohoglu, E., Beckers, L., Davis, M.H.: Convergent neural signatures of speech prediction error are a biological marker for spoken word recognition. Nat Commun **15**(1), 9984 (2024). https://doi.org/10.1038/s41467-024-53782-5. Accessed 2025-09-19

[44] Cui, L., Bo, K., Xiong, C., Chen, Y., Keil, A., Ding, M.: Stimulus Repetition Induces a Two-Stage Learning Process in the Primary Visual Cortex. J. Neurosci. **45**(23), 1788242025 (2025). https://doi.org/10.1523/JNEUROSCI.1788-24.2025. Accessed 2025-09-19

[45] Richter, D., Heilbron, M., De Lange, F.P.: Dampened sensory representations for expected input across the ventral visual stream. Oxford Open Neuroscience **1**, 013 (2022). https://doi.org/10.1093/oons/kvac013. Accessed 2025-09-19

[46] Richter, D., Kietzmann, T.C., De Lange, F.P.: High-level visual prediction errors in early visual cortex. PLoS Biol **22**(11), 3002829 (2024). https://doi.org/10.1371/journal.pbio.3002829. Accessed 2025-09-19

[47] Aitken, F., Menelaou, G., Warrington, O., Koolschijn, R.S., Corbin, N., Callaghan, M.F., Kok, P.: Prior expectations evoke stimulus-specific activity in the deep layers of the primary visual cortex. PLoS Biol **18**(12), 3001023 (2020). https://doi.org/10.1371/journal.pbio.3001023. Accessed 2025-09-19

[48] Thomas, E.R., Haarsma, J., Nicholson, J., Yon, D., Kok, P., Press, C.: Predictions and errors are distinctly represented across V1 layers. Current Biology **34**(10), 2265–22714 (2024). https://doi.org/10.1016/j.cub.2024.04.036. Accessed 2025-09-19

[49] Alink, A., Blank, H.: Can expectation suppression be explained by reduced attention to predictable stimuli? NeuroImage **231**, 117824 (2021). https://doi.org/10.1016/j.neuroimage.2021.117824. Accessed 2025-02-18

[50] Maris, E., Oostenveld, R.: Nonparametric statistical testing of EEG- and

MEG-data. Journal of Neuroscience Methods **164**(1), 177–190 (2007). https://doi.org/10.1016/j.jneumeth.2007.03.024. Accessed 2024-01-23

[51] Sassenhagen, J., Draschkow, D.: Cluster-based permutation tests of MEG/EEG data do not establish significance of effect latency or location. Psychophysiology **56**(6), 13335 (2019). https://doi.org/10.1111/psyp.13335. Accessed 2025-02-12

[52] Lau, E.F., Phillips, C., Poeppel, D.: A cortical network for semantics: (de)constructing the N400. Nat Rev Neurosci **9**(12), 920–933 (2008). https://doi.org/10.1038/nrn2532. Accessed 2025-02-12

[53] Kutas, M., Federmeier, K.D.: Thirty Years and Counting: Finding Meaning in the N400 Component of the Event-Related Brain Potential (ERP). Annu. Rev. Psychol. **62**(1), 621–647 (2011). https://doi.org/10.1146/annurev.psych.093008.131123. Accessed 2025-10-07

[54] Correia, J.M., Jansma, B., Hausfeld, L., Kikkert, S., Bonte, M.: EEG decoding of spoken words in bilingual listeners: from words to language invariant semantic-conceptual representations. Front. Psychol. **6** (2015). https://doi.org/10.3389/fpsyg.2015.00071. Accessed 2025-02-12

[55] Le, T.T., Luong, D.A.Q., Joo, H., Kim, D., Woo, J.: Differences in spatiotemporal dynamics for processing specific semantic categories: An EEG study. Sci Rep **14**(1), 31918 (2024). https://doi.org/10.1038/s41598-024-83417-0. Accessed 2025-02-12

[56] Lewendon, J., Mortimore, L., Egan, C.: The Phonological Mapping (Mismatch) Negativity: History, Inconsistency, and Future Direction. Front. Psychol. **11**, 1967 (2020). https://doi.org/10.3389/fpsyg.2020.01967. Accessed 2024-01-22

[57] Hickok, G., Poeppel, D.: The cortical organization of speech processing. Nat Rev Neurosci **8**(5), 393–402 (2007). https://doi.org/10.1038/nrn2113. Accessed 2025-10-07

[58] Draganov, M., Galiano-Landeira, J., Doruk Camsari, D., Ramírez, J.-E., Robles, M., Chanes, L.: Noninvasive modulation of predictive coding in humans: causal evidence for frequency-specific temporal dynamics. Cerebral Cortex, 127 (2023). https://doi.org/10.1093/cercor/bhad127. Accessed 2023-06-12

[59] Aizenbud, I., Audette, N., Auksztulewicz, R., Basiński, K., Bastos, A.M., Berry, M., Canales-Johnson, A., Choi, H., Clopath, C., Cohen, U., Costa, R.P., De Filippo, R., Doronin, R., Errington, S.P., Gavornik, J.P., Gillon, C.J., Granier, A., Hamm, J.P., Hertäg, L., Kennedy, H., Kumar, S., Ladd, A., Ladret, H., Lecoq, J.A., Maier, A., McCarthy, P., Mei, J.,

Mejias, J., Mikulasch, F., Mudrik, N., Najafi, F., Nejad, K., Nejat, H., Oweiss, K., Petrovici, M.A., Priesemann, V., Rudelt, L., Ruediger, S., Russo, S., Salatiello, A., Senn, W., Sennesh, E., Sima, S., Uran, C., Vasilevskaya, A., Vezoli, J., Vinck, M., Westerberg, J.A., Wilmes, K., Xiong, Y.S.: Neural mechanisms of predictive processing: a collaborative community experiment through the OpenScope program. arXiv. Version Number: 1 (2025). https://doi.org/10.48550/ARXIV.2504.09614. https://arxiv.org/abs/2504.09614 Accessed 2025-10-07

[60] Meyer, S.S., Bonaiuto, J., Lim, M., Rossiter, H., Waters, S., Bradbury, D., Bestmann, S., Brookes, M., Callaghan, M.F., Weiskopf, N., Barnes, G.R.: Flexible head-casts for high spatial precision MEG. Journal of Neuroscience Methods **276**, 38–45 (2017). https://doi.org/10.1016/j.jneumeth.2016.11.009. Accessed 2025-10-07

[61] Bonaiuto, J.J., Rossiter, H.E., Meyer, S.S., Adams, N., Little, S., Callaghan, M.F., Dick, F., Bestmann, S., Barnes, G.R.: Non-invasive laminar inference with MEG: Comparison of methods and source inversion algorithms. NeuroImage **167**, 372–383 (2018). https://doi.org/10.1016/j.neuroimage.2017.11.068. Accessed 2025-10-07

[62] Theodore, R.M., Myers, E.B., Lomibao, J.A.: Talker-specific influences on phonetic category structure. The Journal of the Acoustical Society of America **138**(2), 1068–1078 (2015). https://doi.org/10.1121/1.4927489. Accessed 2023-06-29

[63] Krumbiegel, J., Ufer, C., Blank, H.: Influence of voice properties on vowel perception depends on speaker context. The Journal of the Acoustical Society of America **152**(2), 820–834 (2022). https://doi.org/10.1121/10.0013363. Accessed 2023-06-29

[64] Severijnen, G.G.A., Bosker, H.R., Piai, V., McQueen, J.M.: Listeners track talker-specific prosody to deal with talker-variability. Brain Research **1769**, 147605 (2021). https://doi.org/10.1016/j.brainres.2021.147605. Accessed 2023-06-29

[65] Dufour, S., Nguyen, N.: Does Talker-Specific Information Influence Lexical Competition? Evidence From Phonological Priming. Cogn Sci **41**(8), 2221–2233 (2017). https://doi.org/10.1111/cogs.12472. Accessed 2023-06-29

[66] Goldinger, S.D.: Echoes of echoes? An episodic theory of lexical access. Psychological Review **105**(2), 251–279 (1998). https://doi.org/10.1037/0033-295X.105.2.251. Accessed 2023-06-29

[67] McLennan, C.T., Luce, P.A.: Examining the Time Course of Indexical Specificity Effects in Spoken Word Recognition. Journal of Experimental

Psychology: Learning, Memory, and Cognition **31**(2), 306–321 (2005). https://doi.org/10.1037/0278-7393.31.2.306. Accessed 2023-06-29

[68] Moses, D.A., Metzger, S.L., Liu, J.R., Anumanchipalli, G.K., Makin, J.G., Sun, P.F., Chartier, J., Dougherty, M.E., Liu, P.M., Abrams, G.M., Tu-Chan, A., Ganguly, K., Chang, E.F.: Neuroprosthesis for Decoding Speech in a Paralyzed Person with Anarthria. N Engl J Med **385**(3), 217–227 (2021). https://doi.org/10.1056/NEJMoa2027540. Accessed 2023-06-12

[69] Mitchell, T.M., Shinkareva, S.V., Carlson, A., Chang, K.-M., Malave, V.L., Mason, R.A., Just, M.A.: Predicting Human Brain Activity Associated with the Meanings of Nouns. Science **320**(5880), 1191–1195 (2008). https://doi.org/10.1126/science.1152876. Accessed 2023-07-07

[70] Huth, A.G., Lee, T., Nishimoto, S., Bilenko, N.Y., Vu, A.T., Gallant, J.L.: Decoding the Semantic Content of Natural Movies from Human Brain Activity. Front. Syst. Neurosci. **10** (2016). https://doi.org/10.3389/fnsys.2016.00081. Accessed 2023-07-07

[71] Tang, J., LeBel, A., Jain, S., Huth, A.G.: Semantic reconstruction of continuous language from non-invasive brain recordings. Nat Neurosci **26**(5), 858–866 (2023). https://doi.org/10.1038/s41593-023-01304-9. Accessed 2023-06-12

[72] d'Ascoli, S., Bel, C., Rapin, J., Banville, H., Benchetrit, Y., Pallier, C., King, J.-R.: Decoding individual words from non-invasive brain recordings across 723 participants. arXiv (2024). https://doi.org/10.48550/ARXIV.2412.17829. https://arxiv.org/abs/2412.17829 Accessed 2025-02-13

[73] Woods, K.J.P., Siegel, M.H., Traer, J., McDermott, J.H.: Headphone screening to facilitate web-based auditory experiments. Atten Percept Psychophys **79**(7), 2064–2072 (2017). https://doi.org/10.3758/s13414-017-1361-2. Accessed 2023-06-29

[74] Salvatier, J., Wiecki, T.V., Fonnesbeck, C.: Probabilistic programming in Python using PyMC3. PeerJ Computer Science **2**, 55 (2016). https://doi.org/10.7717/peerj-cs.55. Accessed 2023-04-12

[75] Kumar, R., Carroll, C., Hartikainen, A., Martin, O.: ArviZ a unified library for exploratory analysis of Bayesian models in Python. JOSS **4**(33), 1143 (2019). https://doi.org/10.21105/joss.01143. Accessed 2023-06-12

[76] Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Köpf, A.,

Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., Bai, J., Chintala, S.: PyTorch: An Imperative Style, High-Performance Deep Learning Library (2019). https://doi.org/10.48550/ARXIV.1912.01703. Accessed 2023-06-29

[77] Pennington, J., Socher, R., Manning, C.: Glove: Global Vectors for Word Representation. In: Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP), pp. 1532–1543. Association for Computational Linguistics, Doha, Qatar (2014). https://doi.org/10.3115/v1/D14-1162. http://aclweb.org/anthology/D14-1162 Accessed 2023-02-10

[78] DeepsetAI: GloVe embeddings DE. https://gitlab.com/deepset-ai/open-source/glove-embeddings-de Accessed 2023-06-28

[79] Boersma, P., Weenink, D.: Praat: doing Phonetics by Computer. https://www.fon.hum.uva.nl/praat/ Accessed 2023-06-28

[80] Kawahara, H., Morise, M., Takahashi, T., Nisimura, R., Irino, T., Banno, H.: Tandem-STRAIGHT: A temporally stable power spectral representation for periodic signals and applications to interference-free spectrum, F0, and aperiodicity estimation. In: 2008 IEEE International Conference on Acoustics, Speech and Signal Processing, pp. 3933–3936 (2008). https://doi.org/10.1109/ICASSP.2008.4518514. ISSN: 2379-190X

[81] Sakoe, H., Chiba, S.: Dynamic programming algorithm optimization for spoken word recognition. IEEE Trans. Acoust., Speech, Signal Process. **26**(1), 43–49 (1978). https://doi.org/10.1109/TASSP.1978.1163055. Accessed 2023-06-28

[82] Paliwal, K.K., Agarwal, A., Sinha, S.S.: A modification over Sakoe and Chiba's dynamic time warping algorithm for isolated word recognition. Signal Processing **4**(4), 329–333 (1982). https://doi.org/10.1016/0165-1684(82)90009-3. Accessed 2023-06-28

[83] Brown, J.C.: Calculation of a constant Q spectral transform. The Journal of the Acoustical Society of America **89**(1), 425–434 (1991). https://doi.org/10.1121/1.400476. Accessed 2023-06-28

[84] Kisler, T., Reichel, U., Schiel, F.: Multilingual processing of speech via web services. Computer Speech & Language **45**, 326–347 (2017). https://doi.org/10.1016/j.csl.2017.01.005. Accessed 2025-04-02

[85] De Leeuw, J.R., Gilbert, R.A., Luchterhandt, B.: jsPsych: Enabling an Open-Source Collaborative Ecosystem of Behavioral Experiments. JOSS **8**(85), 5351 (2023). https://doi.org/10.21105/joss.05351. Accessed 2024-01-18

[86] Peirce, J., Gray, J.R., Simpson, S., MacAskill, M., Höchenberger, R., Sogo, H., Kastman, E., Lindeløv, J.K.: PsychoPy2: Experiments in behavior made easy. Behav Res **51**(1), 195–203 (2019). https://doi.org/10.3758/s13428-018-01193-y. Accessed 2025-01-31

[87] Klem, G.H., Lüders, H.O., Jasper, H.H., Elger, C.: The ten-twenty electrode system of the International Federation. The International Federation of Clinical Neurophysiology. Electroencephalogr Clin Neurophysiol Suppl **52**, 3–6 (1999)

[88] Raunak, V., Gupta, V., Metze, F.: Effective Dimensionality Reduction for Word Embeddings. In: Proceedings of the 4th Workshop on Representation Learning for NLP (RepL4NLP-2019), pp. 235–243. Association for Computational Linguistics, Florence, Italy (2019). https://doi.org/10.18653/v1/W19-4328. https://www.aclweb.org/anthology/W19-4328 Accessed 2023-02-10

[89] Mu, J., Bhat, S., Viswanath, P.: All-but-the-Top: Simple and Effective Postprocessing for Word Representations (2017). https://doi.org/10.48550/ARXIV.1702.01417. Accessed 2023-06-12

[90] Team, R.C.: R: A Language and Environment for Statistical Computing (2020). https://www.r-project.org/ Accessed 2023-06-29

[91] Bates, D., Mächler, M., Bolker, B., Walker, S.: Fitting Linear Mixed-Effects Models Using lme4. J. Stat. Soft. **67**(1) (2015). https://doi.org/10.18637/jss.v067.i01. Accessed 2023-04-12

[92] Lenth, R.V., Bolker, B., Buerkner, P., Giné-Vázquez, I., Herve, M., Jung, M., Love, J., Miguez, F., Riebl, H., Singmann, H.: emmeans: Estimated Marginal Means, aka Least-Squares Means (2023). https://cran.r-project.org/web/packages/emmeans/index.html Accessed 2023-06-29

[93] Barr, D.J., Levy, R., Scheepers, C., Tily, H.J.: Random effects structure for confirmatory hypothesis testing: Keep it maximal. Journal of Memory and Language **68**(3), 255–278 (2013). https://doi.org/10.1016/j.jml.2012.11.001. Accessed 2023-06-29

[94] Yarkoni, T.: The generalizability crisis. Behav Brain Sci **45**, 1 (2022). https://doi.org/10.1017/S0140525X20001685. Accessed 2023-01-18

[95] Hartig, F., Lohse, L.: DHARMa: Residual Diagnostics for Hierarchical (Multi-Level / Mixed) Regression Models (2022). https://cran.r-project.org/web/packages/DHARMa/index.html Accessed 2023-06-29

[96] Gramfort, A.: MEG and EEG data analysis with MNE-Python. Front. Neurosci. **7** (2013). https://doi.org/10.3389/fnins.2013.00267. Accessed

2025-01-22

[97] Peng, W.: EEG Preprocessing and Denoising. In: Hu, L., Zhang, Z. (eds.) EEG Signal Processing and Feature Extraction, pp. 71–87. Springer, Singapore (2019). https://doi.org/10.1007/978-981-13-9113-2_5. http://link.springer.com/10.1007/978-981-13-9113-2$_5$ $Accessed 2025 - 02 - 12$

[98] Hyvarinen, A.: Fast and robust fixed-point algorithms for independent component analysis. IEEE Trans. Neural Netw. **10**(3), 626–634 (1999). https://doi.org/10.1109/72.761722. Accessed 2025-01-22

[99] Accou, B., Vanthornhout, J., Hamme, H.V., Francart, T.: Decoding of the speech envelope from EEG using the VLAAI deep neural network. Sci Rep **13**(1), 812 (2023). https://doi.org/10.1038/s41598-022-27332-2. Accessed 2023-06-12

[100] Pasley, B.N., David, S.V., Mesgarani, N., Flinker, A., Shamma, S.A., Crone, N.E., Knight, R.T., Chang, E.F.: Reconstructing Speech from Human Auditory Cortex. PLoS Biol **10**(1), 1001251 (2012). https://doi.org/10.1371/journal.pbio.1001251. Accessed 2025-03-20

[101] Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Müller, A., Nothman, J., Louppe, G., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., Duchesnay, : Scikit-learn: Machine Learning in Python (2012). https://doi.org/10.48550/ARXIV.1201.0490. Accessed 2025-01-22

[102] uxlfoundation/scikit-learn-intelex. Unified Acceleration (UXL) Foundation (2025). https://github.com/uxlfoundation/scikit-learn-intelex Accessed 2025-01-22

[103] Haufe, S., Meinecke, F., Görgen, K., Dähne, S., Haynes, J.-D., Blankertz, B., Bießmann, F.: On the interpretation of weight vectors of linear models in multivariate neuroimaging. NeuroImage **87**, 96–110 (2014). https://doi.org/10.1016/j.neuroimage.2013.10.067. Accessed 2025-01-31

[104] Heilbron, M., Chait, M.: Great Expectations: Is there Evidence for Predictive Coding in Auditory Cortex? Neuroscience **389**, 54–73 (2018). https://doi.org/10.1016/j.neuroscience.2017.07.061. Accessed 2022-10-11

[105] Valente, G., Castellanos, A.L., Hausfeld, L., De Martino, F., Formisano, E.: Cross-validation and permutations in MVPA: Validity of permutation strategies and power of cross-validation schemes. NeuroImage **238**, 118145 (2021). https://doi.org/10.1016/j.neuroimage.2021.118145.

Accessed 2025-03-20

[106] Gwilliams, L., King, J.-R., Marantz, A., Poeppel, D.: Neural dynamics of phoneme sequences reveal position-invariant code for content and order. Nat Commun **13**(1), 6606 (2022). https://doi.org/10.1038/s41467-022-34326-1. Accessed 2024-05-30

[107] facebook/wav2vec2-large-xlsr-53-german · Hugging Face (2024). https://huggingface.co/facebook/wav2vec2-large-xlsr-53-german Accessed 2025-01-22

[108] Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R., Funtowicz, M., Davison, J., Shleifer, S., von Platen, P., Ma, C., Jernite, Y., Plu, J., Xu, C., Scao, T.L., Gugger, S., Drame, M., Lhoest, Q., Rush, A.M.: HuggingFace's Transformers: State-of-the-art Natural Language Processing (2019). https://doi.org/10.48550/ARXIV.1910.03771. Accessed 2023-06-29

[109] Marian, V., Bartolotti, J., Chabal, S., Shook, A.: CLEARPOND: Cross-Linguistic Easy-Access Resource for Phonological and Orthographic Neighborhood Densities. PLoS ONE **7**(8), 43230 (2012). https://doi.org/10.1371/journal.pone.0043230. Accessed 2024-01-18

[110] Oganian, Y., Chang, E.F.: A speech envelope landmark for syllable encoding in human superior temporal gyrus. Sci. Adv. **5**(11), 6279 (2019). https://doi.org/10.1126/sciadv.aay6279. Accessed 2025-01-31