Assessing the Performance of AF2 and AF3-Implementations on Antibody-Antigen Complexes

Serbulent Unsal,[1,2] Benjamin Holland,[1] Inci Sardag[3] and Emel Timucin ⬤[1,4,*]

[1]Antiverse, Antiverse ltd., sbarc/spark, Maindy Rd, CF24 4HQ, Cardiff, UK, [2]Faculty of Medicine, Karadeniz Technical University, Kanuni Campus, Trabzon, 61080, Turkey, [3]Department of Molecular Biology and Genetics, Bogazici University, 34342, Istanbul, Turkey and [4]Department of Molecular Biology and Genetics, Gebze Technical University, 41400, Gebze, Kocaeli, Turkey
*Corresponding author: emelt@gtu.edu.tr

Abstract

This study evaluates the performance of AF2, Boltz-1, Boltz-1x, Boltz-2, Chai-1, Protenix and ESMFold, on a curated dataset of 200 novel antibody-antigen (Ab-Ag) complexes. Our findings reveal that AF2 remains a strong predictor against newer AlphaFold3 (AF3)-inspired methods in Ab-Ag complex prediction. Chai-1 consistently ranks as the second-best performer across multiple success metrics. We observed diverse effects of recycling iterations, with AF2, Chai-1 and Protenix benefiting from increased cycles, unlike Boltz variants. We analyzed various model confidence scores, noting high precision from pDockQ2 and high recall from pTM. By integrating these two scores, we developed AntiConf, a novel metric that achieves superior performance for all methods in terms of precision and unique target recall. This work addresses current limitations in AI-based Ab-Ag complex prediction, showcasing the potential of AntiConf for future predictions and assessments of these complexes, and providing a guideline for improving the accuracy of Ab-Ag complex prediction.

Introduction

Antibodies (Abs) are central to adaptive immunity, functioning either as neutralizing agents and flagging antigens for clearance. Their therapeutic importance has grown considerably due to their involvement in a wide spectrum of successful immunotherapy applications in cancer, autoimmune disorders, and infectious diseases, transforming the landscape of modern medicine [1].

Structurally, antibodies are Y-shaped proteins composed of two identical heavy and two identical light chains stabilized by disulfide bonds. Monoclonal antibodies (mAbs) consist of paired heavy and light chains, whereas nanobodies (Nbs) are composed of a single variable heavy chain domain. In both mAbs and Nbs, antigen recognition is primarily mediated by three hypervariable loops known as the complementarity-determining regions (CDRs), collectively forming the paratope region [2–5]. Given the smaller size and extended CDR loops, Nbs can access epitopes often unreachable by mAbs [6, 7]. Among CDRs, the CDR H3 loop is the most diverse region in terms of structure, length and amino acid composition, and forms the highest number of antigen contacts [8–13]. The length and structure of the CDR H3 loop is known to affect the orientation and engagement of neighboring CDRs, thereby modulating the overall paratope architecture and specificity [8].

Experimental determination of multimer structures including Ab-Ag complexes is costly and time-intensive, underscoring the importance of computational methods as cost-effective alternatives to experiments [14]. Despite the growing availability of tools for designing antibodies and nanobodies, accurate prediction of antibody-antigen complex structures remains a major challenge [15–17]. Essentially, accurate modeling of the CDR H3 loop continues to pose significant difficulties [18, 19], making it a persistent bottleneck in generating high-resolution antibody-antigen complex structures [20].

Recent developments in deep learning-based structure prediction methods have raised the bar for computationally predicted multimeric structures. Essentially, AlphaFold2 (AF2) has shown striking success in predicting protein-protein complexes [21, 22]. AlphaFold3 (AF3) introduces a diffusion-based architecture [23] and has demonstrated improved accuracy over AF2 for predicting multimeric structures [23]. In parallel with the development of AF3, several AF3-inspired open-source models have emerged, each addressing distinct limitations of the original framework. Among these, Boltz-1 implements a deep learning model refining the AF3 framework with improved input processing, architectural adjustments, and a redesigned confidence model [24]. Chai-1, another AF3-inspired model with the same model architecture and training strategy with AF3, supports experimental restraints for enhanced accuracy and can function without MSAs [25]. Protenix, another refined reproduction of AF3, incorporates clarification and correction of ambiguous steps, typographical errors, and targeted adjustments informed by model behavior [26]. In addition to these AF3-inspired models, other approaches are also available such as ESMFold, which uses a transformer-based architecture bypassing multiple sequence alignment (MSA) generation [27]. While all these methods represent important steps forward in protein-protein complex prediction, their effectiveness for Ab-Ag systems needs further evaluations to identify where they succeed, and where performance gaps exist.

To this end, we assessed the performance of the new generation of AF3 methods including Boltz-1 [24], Boltz-1x (Boltz-steering) [24], Boltz-2 [28], Chai-1 [25], Protenix [26], ESMFold [27] along with AF2 (v2.3.2) [21], on a curated set of antibody-antigen complexes that are absent from the training data of these methods. For each complex, we generated 25 predictions and extensively evaluated their performance based on the scores including but not limited to ipTM, ipLDDT, iPAE, and pDockQ2. We introduced a novel score, AntiConf, developed by integrating pTM and pDockQ2, which consistently outperformed all evaluated metrics in terms of both precision and recall. Our findings highlight the strengths and limitations of AF2- and AF3-based approaches in modeling real-world antibody–antigen complexes, demonstrating AntiConf's potential for improving Ab-Ag complex predictions by AF2 and/or AF3-based methods.

Methods

Dataset Construction

We assembled a curated dataset of 200 Ab–Ag complexes by combining and refining data from two recent benchmarking studies [29, 30]. The first subset, consisting of 39 complexes from Yin et al. (2024) [29], was directly incorporated. The second subset was derived from the 210 complexes compiled by Hitawala et al. (2024) [30], after filtering out unbound antibody structures and complexes involving non-proteinaceous antigens. Additionally, we corrected metadata discrepancies in the original dataset, particularly those related to missing or unmodeled regions in the input sequences. Redundant entries representing alternative biological units of the same

PDB target were also removed, retaining only one representative per complex. The final dataset comprises 200 Ab–Ag complexes, including structures released after the training cutoff dates of AF2 and other prediction methods. All selected sequences were verified to have low sequence identity to training data, ensuring the inclusion of previously unseen antibody–antigen interactions. The full dataset is available at `https://doi.org/10.5281/zenodo.16404871`.

Complex Predictions

AF2 v2.3.2 was implemented through ColabFold [22, 31] using MMseqs2 [32] and the UniRef+Environmental database [33]. To generate a total of 25 predictions per complex, we used a different random seed for each prediction, producing five predictions for each AF2 prediction. Boltz-1 and Boltz-1x [24], Boltz-2 [28], Chai-1 [25] and Protenix [26] were used to generate 25 models for each target using a single seed. Before assembling the final model, different number of recycling iterations were tested for all methods except for ESMFold. For ESMFold, only a single model was generated for each target [27]. All predictions were conducted via Tamarind Bio [34].

Evaluation of Complex Model Accuracy

Model accuracy was assessed by DockQ v2 [35, 36] and Critical Assessment of Prediction of Interactions (CAPRI) classification system [37, 38]. CAPRI classification system groups models into discrete categories such as incorrect, acceptable, medium, and high using fixed cutoff values of three complex quality indicators of fraction of native contacts (f_{nat}), ligand backbone RMSD (lRMSD), and interface backbone RMSD (iRMSD). DockQ provides a continuous score that is calculated by combining these three indicators. Fixed DockQ thresholds, i.e 0.23, 0.49, 0.80, are also used to align with the respective CAPRI categories.

Calculation of Interface pLDDT and PAE

For each chain in the structure, a residue was classified as an interface residue if the distance between its Cα atom and the Cα atom of any residue from a neighboring chain was less than or equal to the defined threshold of 8 Å. Only Cα–Cα distances were considered to ensure consistency across all residue types. For each identified interface residue, the corresponding pLDDT score was extracted from the model files. PAE scores for each interacting chain pair were obtained from the corresponding interface region in the global PAE matrix. A normalized interface PAE score was computed using the formula from the ref. [39]. The ipLDDT and iPAE scores were computed for each chain and reported as the average for either the antigen alone or for all chains in the complex.

Calculation of pDockQ2 and pTMDockQ2

We calculated the pDockQ2 score, which combines ipLDDT and normalized iPAE. Specifically, the product of ipLDDT and normalized iPAE scores was fitted to a four-parameter sigmoid function to obtain the pDockQ2 score [39]:

$$\text{pDockQ2}(x) = \frac{L}{1 + \exp\left(-k(x - x_0)\right)} + b$$

where x represents the product of ipLDDT and normalized iPAE. The curve parameters were adopted from ref. [39] as follows: $L = 1.3103$, $x_0 = 84.7326$, $k = 0.0747$, and $b = 0.0050$.

Interface pLDDT, PAE and pDockQ2 calculations were performed using the `pdockq2.py` script available at `https://gitlab.com/ElofssonLab/afm-benchmark`.

A composite score was computed as a weighted linear combination of pTM and pDockQ2 scores as follows:

$$\text{AntiConf} = 0.3\text{pDockQ2} + 0.7\text{pTM}$$

Statistical Analysis

All statistical analyses were performed using Python libraries and `SciPy` packages. To evaluate classification performance, we calculated precision, recall, specificity, F1 score, and the area under precision-recall curve. Linear relationships between DockQ score and model metrics were assessed using the Pearson correlation. All reported statistical tests were two-sided, and significance was assessed at a threshold of 0.05.

Results and Discussion

Construction and Prediction of Ab-Ag Complex Dataset

We utilized a curated dataset of 200 antibody-antigen (Ab-Ag) complexes, building upon two prior benchmarking studies [29, 30]. This involved directly incorporating 39 complexes from one source [29] and refining the initial set of 210 Ab-Ag complexes from another source [30] by removing unbound antibody structures, non-proteinaceous antigens, and correcting for missing PDB regions. Redundant sequences, representing different biological units of the same PDB target, were also removed to ensure a unique biological unit per target. The final 200-complex dataset includes structures released after the training cutoffs of methods and thus features novel Ab-Ag interactions with minimal sequence identity to training sets.

We predicted these Ab-Ag complexes using seven different methods; AF2 (v2.3.2) [21], Boltz-1 [24], Boltz-1x (Boltz-steering) [24], Boltz-2 [28], Chai-1 [25], Protenix [26] and ESMFold [27]. Among these methods, Boltz-2 was evaluated on a subset of 18 complexes with deposition dates after its 2023 training cutoff to ensure fair assessment. For Protenix, predictions failed on 26 large complexes, limiting its evaluation to 174 cases. All other methods were successfully run on the full set of 200 complexes.

We initially examined the concordance between DockQ scores [35, 36] and CAPRI classification [38, 40]. Fig. S1 illustrate the distribution of DockQ scores across CAPRI categories for each method. While predictions showed a clear separation of DockQ among the CAPRI categories with progressively increasing DockQ scores from incorrect to high quality CAPRI classes for each method, some overlaps exist between incorrect-to-acceptable and acceptable-to-medium transitions. DockQ versus CAPRI accuracy investigation indicated that while DockQ scores and thresholds are robust and align with the respective CAPRI categories, classification near category boundaries can vary depending on the prediction method.

Success Rate Based on CAPRI Quality Assessment

Fig. 1 summarizes the success rates of six different structure prediction methods, AF2, Boltz1, Boltz-1x, Boltz-2, Chai-1, and Protenix for overall complex set, for antibody-antigen (Ab) interactions, and success for nanobody-antigen (Nb) interactions. For each case, we reported success rates based on the number of correctly predicted unique targets achieving at least acceptable accuracy, as well as those falling within each CAPRI category.

Fig. 1. Left panel shows the success rates of all methods across 200 complexes (Boltz-2: 18, Protenix: 174); middle panel shows success rates for antibody complexes (n = 124, Boltz-2: 11, Protenix: n = 107); right panel displays success rates for nanobody complexes (n = 76; Boltz-2: 7, Protenix: n = 67). Success rates represent the proportion of unique targets predicted by acceptable, medium, or high accuracy according to CAPRI criteria. Bars were annotated with the target counts.

For all complexes (Fig. 1-top row), AF2 achieved the highest success rate with 88 unique targets. AF2 was followed by Chai-1 (82 targets), Boltz-1 (66), Protenix (63), and Boltz-1x (59). AF2 also produced a significant number of high-quality models (42), demonstrating its ability to capture refined interfaces. Notably, despite being evaluated on fewer targets, Boltz-2 also yielded a large proportion of high-quality models, with no acceptable models. Chai-1 and Protenix were the second and third best methods to find high and medium quality models.

Consistent with previous reports on its poor performance with multimeric complexes [39, 41], ESMFold failed to produce any successful predictions for our Ab-Ag complex set, as evaluated by both CAPRI and DockQ criteria (Fig. S1). To confirm that these negative results was not due to implementation-related issues, we validated our ESMFold models for a small set of targets on a separate platform (`https://colab.research.google.com/github/sokrypton/ColabFold/blob/main/ESMFold.ipynb`). Results from both prediction platforms were consistent in terms of confidence scores and overall complex structures. Therefore, we reported that while ESMFold is highly accurate for monomeric structures [27], it showed no predictive performance for the specific Ab–Ag complexes examined here.

We calculated success rates focusing on specific interaction types, antibody (Ab) and nanobody (Nb) complexes (Fig. 1-middle/bottom rows). For Ab complexes (Fig. 1-middle), AF2

again emerged as the most successful method with a 47% (58/124) success rate. Second best performer was Chai-1 (39%, 48/124), which was closely followed by Protenix (38%, 41/107) and Boltz-1 (37%, 46/124). Notably, Boltz-1x showed a lower performance than Boltz-1, resulting in a total of 39 correctly predicted Ab complex targets (31%). Conversely, Boltz-2 showed a weaker performance, achieving only a 18% success rate (2/11) in the Ab category. When examining the CAPRI quality of these predictions, AF2 maintained its performance, yielding again substantial number of high and medium accuracy models. On the other hand, other methods, fall behind AF2's performance in predicting refined Ab complexes, particularly producing limited number of high quality models.

In the Nb-level assessment (Fig. 1-bottom row), Chai-1 yielded the highest success rate (45%, 34/76), outperforming AF2 (39%, 30/76), while all other methods generally showed lower performance on the Nb complexes compared to their performance on the Ab complexes. Along with this observation, AF2 was still the best method in producing the largest number of high quality models, which is closely followed by Chai-1. We note here that, the performance drop observed for Boltz-1x in the Ab cases was absent for Nb complexes, showing a similar level of success for both Boltz-1 variants. Despite the limited tested complexes, Boltz-2 showed a higher success in Nb category, correctly predicting 3 out 7 targets.

AF2 v2.3, an updated version of the model, incorporates pipeline and model modifications, including a 30% increase in training data up to PDB structures released by September 30, 2021 [42]. Previous benchmarking of AF2 v2.3.0 on a subset of our dataset showed approximately 43% overall success for top-25 models across individual CAPRI levels [29]. In our current benchmarking, however, AF2 v2.3.2 performed much better, achieving over 60% total success across CAPRI levels (Fig. 1-right), which close to the AFsample [43] in the same study [29]. While both versions yielded a comparable 38% success rate for the top-1 tier, AF2 v2.3.2 demonstrated higher success rates for the top-5 tier. These observed differences between the accuracies of two AF2 v2.3 versions could stem from variations in parameters, such as random seed initialization. Additionally, our use of ColabFold, which differs from the original AF2 pipeline in its construction and pairing of MSAs [31], might also contribute to this discrepancy.

Predictions were visualized for a Nb complex (Fig. 2). Consistent with the general success rates reported in Fig. 1, AF2 and Chai-1 achieved highly accurate predictions for this complex. In contrast, Protenix produced an incorrect prediction, despite yielding a marginally incorrect DockQ score. The Boltz variants demonstrated low accuracy for this particular nanobody complex.

Taken together, these results demonstrate that AF2 consistently performs well across different settings, particularly in generating high-quality complex and antibody models. Chai-1 emerges as a strong alternative, especially in Nb modeling. Protenix generally showed comparable success in Ab cases with Chai-1, while falling behind it in the Nb cases. Following these three methods, the Boltz variants show variable performance, with Boltz-1 outperforming Boltz-1x in the Ab category. Despite its being tested in a limited number of complexes, Boltz-2 outperformed earlier Boltz versions in the Nb category.

Effect of Interface Glycans on Success Rates

In our Ab-Ag complex dataset, we identified 41 interfaces containing glycan residues within 10 Å of the binding interface. Glycosylation, a key post-translational modification (PTM) for antibodies and nanobodies, significantly influences their activity, including their ability to bind target antigens and engage immune effector mechanisms [44]. These PTMs including

Fig. 2. Structural visualization for one complex (PDB ID: 7zk1). Top ranking models were selected for visualization.

glycosylation can also impact the accuracy of prediction methods. While AF3-based methods can account for glycosylation during complex modeling, we did not provide any PTM information to the models. Hence, to specifically test how the glycosylated interfaces affect success rates, we conducted an additional analysis to compute success rates for complexes both with and without interface glycans (Fig. S2-S3).

Our analysis revealed a general decline in prediction success for protein complexes harboring glycans within 10 Å of the binding interface, relative to those lacking interface glycans (Fig. S2). Protenix stood out as the least affected method, maintaining consistent success rates of 35% (11/31) for glycosylated and 36% (52/143) for non-glycosylated interfaces. Conversely, other methods exhibited reduced success with glycosylated interfaces. Interestingly, AF2 and Chai-1 produced a higher proportion of high-quality models for glycated complexes. In contrast, Boltz-1 variants yielded no high-quality models for glycated interfaces, highlighting their sensitivity to interface PTMs and suggesting that incorporating PTM information could enhance their performance.

To further demonstrate these trends, we examined a specific glycated complex, a nanobody and SARS-CoV-2 RBD complex (PDB ID: 7z2l) with an N-linked glycan at RBD's N343 within the binding interface (Fig. S3). Without prior glycosylation information, Boltz-1 variants and ESMFold failed to generate correct predictions for this complex. Conversely, AF2, Chai-1, and Protenix successfully produced medium or high-quality models in the absence of explicit glycation input.

Effect of Depth, Recycling Iterations and Random Seeds

We calculated success rates for the top-ranking tiers (Top1 and Top5). Fig. S4 displays the non-redundant target counts across all CAPRI categories, as well as for each individual category, similar to Fig. 1.

The depth of prediction, meaning the number of predicted models, positively impacted the performance of all tools, resulting in improved success rates. For example, the original AF3 method previously achieved a 60% success rate in antibody-antigen complex prediction using a 1,000-seed sampling strategy [23]. However, a recent benchmark reported a significantly lower success rate of ∼11% with single-seed sampling [30], underscoring the sensitivity of the method to sampling depth. Our findings similarly indicated that AF2 and all AF3-implementations responded well to an increased number of models in a given prediction (Fig. S4). As such, all methods showed an increase in correctly predicted unique targets as the number of models were increased for a single-seed prediction.

Recycling, which iteratively refines the model by reintroducing the outputs into the network for further optimization [21, 22], appears to be an important factor contributing to the success of Ab-Ag modeling [29]. To assess the impact of recycling on each model's performance, we compared predictions generated with three recycling iterations to those generated with 20 recycling iterations (Fig. S4). Increasing the number of recycling iterations from 3 to 20 led to an improvement in the performance of all methods, with Chai-1 being the most noticeable. Specifically, Chai-1's performance increased from 45 to 67 unique targets for the top 1 ranking models and similarly from 50 to 70 for the top 5 and from 70 to 82 for all 25 models (Fig. S4-top). Protenix's predictions also responded well to increased recycling iterations, leading to increase in the overall target count from 29 to 46 for top 1 tier and from 41 to 57 for the top 5 tier. Not as significant as Chai-1 and Protenix, Boltz-1 also led to improved success upon increased recycling iterations. However, AF2 and Boltz-1x were less responsive to changes in the recycling iterations. As such, AF2 showed slightly improved overall success for 20 recycles, while Boltz-1x showed a slight reduction in success rates. These findings indicate that while increased recycling generally enhances prediction accuracy in both AF2 and AF3 implementations, it may also induce shifts in the distribution of prediction outcomes, as evidenced by the results observed for the top-5 ranking predictions by Boltz.

We also evaluated the effect of random seed variability on AF2 performance by generating an alternative 3-recycle dataset (Fig. S4, AF2(3)*). While overall success, i.e. unique target count, remained similar in both 3-recycle runs, we noted that distribution of CAPRI quality levels differed upon changing the seed, suggesting that random seed selection can influence prediction accuracy.

The definition of "success" is critical for accurately evaluating method performance. We generally see a trend of reporting success as the unique target count for each CAPRI category in studies similar to ours [29, 30]. While quantifying the number of high/medium quality models within a prediction is valuable for understanding the models ability to produce refined models,

we stress that success rates or unique target counts calculated for each CAPRI category carries the risk of overestimating a method's overall performance on a given dataset. Our extensive analysis of success rates suggests that the success rate when reported as the sum of unique targets across each CAPRI category (Fig. 1-right) inflates the performance compared withe success rate computed from unique target counts with at least acceptable accuracy (Fig. 1-left). This inflation occurs because a single target might be counted in multiple CAPRI categories. For example, our benchmark reflected that AF2, when accounting for each CAPRI category individually, correctly predicted 124 targets (Fig. 1-right); however, only 88 of these were unique targets (Fig. 1-left).

Evaluation of Model Confidence Metrics as Predictors of Structural Accuracy

To evaluate how well model confidence metrics reflect structural accuracy, we analyzed the relationship between DockQ scores and the confidence measures, namely pTM, ipTM, model confidence, ipLDDT, normalized iPAE and the post hoc score pDockQ2 (Fig. 3). We also devised a new score named AntiConf for antibody confidence, as a weighted average of pTM and pDockQ2.

We reported a consistently stronger associations for the new score AntiConf for all methods except for Protenix. Notably, for AF2 AntiConf showed a notable increase in the strength of the association. While, ipLDDT consistently showed the weakest DockQ association for all methods, except for Boltz-2 which is represented by only a few data points. Following AntiConf, pDockQ2, which is derived from a curve fit of the product of ipLDDT and iPAE for the antigen chain [39] showed the second strongest correlations with DockQ for all methods (Figs. 3). As we compared the linear correlations for each method, AF2 correlations was consistently the strongest across all scores, which is followed by Chai-1 correlations. Overall, these evaluations implied the power of the composite score, AntiConf, in predicting model quality for these novel antigen-antibody interactions.

The ipTM is a key confidence metric used to evaluate protein–protein interactions by assessing the pTM scores of interface contacts [45]. Because ipTM may include non-interacting flexible regions as part of the interface, its values may not accurately reflect the core interaction region. To address this limitation, alternative scoring approaches considering only the residues directly involved in the interaction have been developed [46, 47]. Among these alternative ipTM scores, we included actifpTM scores for evaluation of AF2 predictions (Fig. S5). ActifpTM showed a weaker association with DockQ compared to ipTM, largely due to a subset of incorrect models with high actifpTM scores.

We next assessed ipLDDT and iPAE scores computed over the entire interface. Notably, the average ipLDDT scores computed over the entire interface correlated more strongly with DockQ compared to antigen-only ipLDDT scores (Fig. S6a), suggesting that averaging ipLDDT over the whole complex yields a more robust indicator of model quality for this Ab-Ag complex set. We additionally investigated iPAE scores computed over the full interface (Fig. S6b). Unlike the trend seen with ipLDDT, antigen-specific iPAE scores were better predictors of model quality than full-interface iPAE scores.

Examining the distributions of model scores across different cycling iterations, we observed that an upward trend in almost all scores for 20-recycle predictions with ipLDDT being the least affected score (Fig. S7). Importantly, we also noted an overestimation of all model scores in the AF3-inspired models compared with AF2, highlighting differences in the internal handling

Fig. 3. Scatter plots of DockQ scores and confidence metrics across six structure prediction methods. All correlations are significant ($p < 0.001$). ipLDDT, iPAE and pDockQ2 scores for obtained for the antigen chain only.

of these metrics by AF3-inspired models. Particularly, scores from Protenix's models were consistently overestimated compared with the scores from other methods.

Binary Classification Performance of Model and Interface Scores

To evaluate how effectively model confidence scores differentiate between correct and incorrect models, we conducted a binary classification analysis based on CAPRI-defined model quality. This allowed us to quantitatively assess the classification performance of various internal scores (pTM, ipTM, actifpTM, model confidence, ipLDDT, iPAE) and the post-hoc score pDockQ2 (Table S1). Using a threshold of 0.8 across all scores, we observed that AntiConf generally yielded the highest precision, except for Chai-1 and Protenix, where it was the second-best score, closely trailing pDockQ2. Notably, despite pDockQ2's higher precision in Chai-1 and Protenix, AntiConf demonstrated a remarkable increase in recall compared to pDockQ2, resulting in high

Table 1. Classification metrics based on the score threshold at precision 1

method	score	threshold	recall	F1	targets	recall$_{target}$
AF2 **(88)**	pTM	0.935	0.147	0.257	16	0.182
	ipTM	0.916	0.168	0.288	21	0.239
	model conf.	0.919	0.159	0.274	20	0.227
	iPAE	0.98	0.032	0.061	4	0.045
	ipLDDT	0.952	0.244	0.392	27	0.307
	pDockQ2	0.848	0.152	0.264	19	0.216
	AntiConf	0.879	0.235	0.381	27	0.307
Boltz-1 **(66)**	pTM	0.969	0.036	0.07	3	0.045
	ipTM	0.96	0.02	0.039	2	0.03
	model conf.	0.961	0.025	0.049	2	0.03
	iPAE	0.991	0.039	0.076	3	0.045
	ipLDDT	0.964	0	0	0	0
	pDockQ2	0.899	0.001	0.002	1	0.015
	AntiConf	0.914	0.085	0.157	4	0.061
Boltz-1x **(59)**	pTM	0.968	0.051	0.097	5	0.085
	ipTM	0.958	0.034	0.066	3	0.051
	model conf.	0.96	0.038	0.073	4	0.068
	iPAE	0.992	0.039	0.075	2	0.034
	ipLDDT	0.957	0.001	0.002	1	0.017
	pDockQ2	0.897	0.001	0.002	1	0.017
	AntiConf	0.913	0.082	0.152	4	0.068
Chai-1 **(82)**	pTM	0.962	0	0	0	0
	ipTM	0.919	0	0	0	0
	model conf.	0.928	0	0	0	0
	iPAE	0.956	0.223	0.365	21	0.256
	ipLDDT	0.968	0.017	0.034	1	0.012
	pDockQ2	0.753	0.141	0.247	13	0.159
	AntiConf	0.874	0.159	0.274	13	0.159
Protenix **(63)**	pTM	0.985	0.056	0.105	6	0.095
	ipTM	0.982	0	0	0	0
	model conf.	0.982	0.001	0.002	1	0.016
	iPAE	0.996	0.005	0.009	1	0.016
	ipLDDT	0.985	0	0	0	0
	pDockQ2	0.955	0.001	0.002	1	0.016
	AntiConf	0.976	0.001	0.002	1	0.016

F1 scores for both methods. We also computed the proportion of successfully predicted unique targets, termed $recall_{target}$, where AntiConf's performance was also noteworthy. Specifically, it returned 39 unique targets (from 88 correct predictions) with a precision of 0.961 for AF2. Similarly, it recovered 43 unique targets out of 82 positives with a precision of 0.972 in Chai-1. In comparison with the pDockQ2 which gives comparable precision to AntiConf, unique target

recall was notably higher in AntiConf, reflecting its potential in recalling higher number of targets without compromising precision.

Fig. 4. Precision, recall and target recall based on different thresholds starting from the lowest threshold that gives precision 1 (T) and decrementing it by 0.05, 0.10 and 0.15. Figs. S8-S12 re-illustrate this plot for each method, with the thresholds explicitly marked.

We also acknowledged the classification successes of pTM, ipTM, and model confidence, particularly their higher recall. However, it is crucial to recognize that in real-world applications, particularly when experimental validation is required, high precision (minimizing false positives) is often more critical than high recall. Nevertheless, AntiConf, integrating pTM and pDockQ2, offers a compelling solution to the reduced recall associated with the highly precise pDockQ2. Therefore, we highlight the power of AntiConf in scenarios where misclassifying incorrect structures as correct could lead to costly experimental follow-ups.

While we acknowledge that this dataset is extensive, it may not fully capture the complexity of real-world scenarios, which often involve a much larger and more diverse array of antibody-antigen interactions, including previously unseen ones. Thus, these assessments might underestimate the challenges posed by real-world applications, reflecting the need to test the performance of the metrics against different and more challenging scenarios.

To address these limitations, our second goal was to evaluate how robust AntiConf and other metrics are when we vary score thresholds. To do this, we first identified the lowest threshold for each score and method that resulted in a precision value of 1 (Table 1). This specific scenario, which guarantees 100% precision for each score, would naturally limit their recall performance. As expected, we observed significantly lower recall values for every score and method under these stringent conditions. Despite this demanding scenario, AntiConf demonstrated strong predictive value, maintaining high recall performance compared to other scores. While AntiConf was not always the top performer in terms of overall recall, it consistently achieved a high target recall, meaning it identified a large number of unique targets. For example, with AF2, AntiConf yielded the second-highest recall but ultimately identified the most unique targets (27), similar to ipLDDT, which had the highest recall.

To assess the robustness of these metrics, we evaluated their precision, recall, and target performance across varying thresholds (Fig.S13). We began with the lowest threshold (T) that achieved a precision of 1 and then progressively decreased T by 0.05, 0.10, and 0.15 (Figs. 4 and S8-S12). As anticipated, the recall performance for all scores monotonically increased with decreasing thresholds. However, a concurrent decrease in precision was observed for nearly all scores, with the notable exceptions of pDockQ2 and AntiConf. Both pDockQ2 and AntiConf maintained comparable precision levels even with a 0.15 decrease in the score threshold. Specifically, for a threshold decrement of 0.15, AntiConf achieved a precision of 0.96 and recalled 42 unique targets for AF2, whereas pDockQ2 recalled 33 targets with a precision of 0.95. In contrast, the same condition led to reduced precisions for other methods, ranging from 0.59 to 0.86. For AF3-inspired methods, excluding Protenix, AntiConf maintained a stable precision across varying thresholds while improving its recall and target recall. For Protenix, pDockQ2 (0.81) exhibited higher precision than AntiConf (0.67), though it still yielded a lower number of unique targets (25) than AntiConf (42). Given the systematic increase in Protenix's internal metrics compared to other methods, we underline that a refitted pDockQ2 and as well as AntiConf calculation might further ameliorate the performance of both metrics for this method.

We collectively evaluated the precision-recall performance of these scores by concatenating positive predictions from all methods, using the thresholds presented in Figs. S8-12. We conducted this analysis starting from the optimal precision-1 threshold and three incrementally lower thresholds. Using these thresholds, we combined the positives from each method into a single set for each score (Fig. 5).

Consistent with individual method assessments, the collective evaluation revealed that pDockQ2 and AntiConf were the top-performing scores. When predictions from all methods were

harmonized, these two metrics delivered the best recall and the highest number of unique targets. Both pDockQ2 and AntiConf systematically increased the number of correctly predicted unique targets and the recall rate while maintaining high precision. Notably, AntiConf consistently demonstrated the highest target recall among the two across all tested thresholds. This highlights its significant potential for evaluating future antibody-antigen (Ab-Ag) complexes predicted by any of these methods.

Fig. 5. Collective precision, recall and target recall performance of all methods based on corresponding thresholds calculated for thresholds starting from the lowest threshold that gives precision 1 (T) and decrementing it by 0.05, 0.10 and 0.15.

Conclusions

Recent advancements in AI-based structure prediction methods, originally designed for single protein structures, have also shown remarkable performance in predicting multimeric protein complexes. However, given that performance gaps still exist, especially for Ab-Ag complex predictions, our study provides a comprehensive comparative assessment of publicly available AF2 and AF3-implementations.

Our study primarily highlights the competitive performance of AF2 and Chai-1 in accurately identifying and refining Ab-Ag complexes. We found that increasing the number of recycling iterations boosts the performance of Chai-1, Protenix, and AF2, while Boltz-1 variants responded differently. Among various model confidence scores from interface-specific to template modeling scores, pDockQ2 demonstrated high precision potential, while pTM offered strong recall. By combining these, we developed a novel score called AntiConf, which stands out as the optimal metric for maximizing recall in challenging scenarios that demand high precision. We surmise that AntiConf holds significant promise for accurate determination of correct Ab-Ag complexes from predictions generated by AF2 and AF3-implementations.

While our work points out some limitations in AI-based Ab-Ag complex predictions particularly for Boltz-1 variants, it also demonstrates how current methodologies can be harmonized to maximize prediction accuracy. Combining different prediction methods, rather than relying on a single one, it is possible to extract a greater number of correct predictions.

We lastly underscore the importance of future, preferably large-scale, assessment studies to fully understand the generalizability of the confidence scores including AntiConf for estimating the quality of Ab-Ag complex predictions. Nonetheless, the thresholds reported for various confidence metrics in this study offer valuable guidelines for optimizing the performance of different methods for Ab-Ag complexes.

References

1. George J Weiner. Building better monoclonal antibody-based therapeutics. *Nature Reviews Cancer*, 15(6):361–370, 2015.
2. Cyrus Chothia and Arthur M Lesk. Canonical structures for the hypervariable regions of immunoglobulins. *Journal of molecular biology*, 196(4):901–917, 1987.
3. Bissan Al-Lazikani, Arthur M Lesk, and Cyrus Chothia. Standard conformations for the canonical structures of immunoglobulins. *Journal of molecular biology*, 273(4):927–948, 1997.
4. Daisuke Kuroda, Hiroki Shirai, Masato Kobori, and Haruki Nakamura. Systematic classification of cdr-l3 in antibodies: implications of the light chain subtypes and the vl–vh interface. *Proteins: Structure, Function, and Bioinformatics*, 75(1):139–146, 2009.
5. Jaroslaw Nowak, Terry Baker, Guy Georges, Sebastian Kelm, Stefan Klostermann, Jiye Shi, Sudharsan Sridharan, and Charlotte M Deane. Length-independent structural similarities enrich the antibody cdr canonical class model. In *MAbs*, volume 8, pages 751–760. Taylor & Francis, 2016.
6. Natalia E Ketaren, Peter C Fridy, Vladimir Malashkevich, Tanmoy Sanyal, Marc Brillantes, Mary K Thompson, Deena A Oren, Jeffrey B Bonanno, Andrej Šali, Steven C Almo, et al. Unique binding and stabilization mechanisms employed by and engineered into nanobodies. *bioRxiv*, pages 2023–10, 2023.
7. Uroš Zavrtanik, Junoš Lukan, Remy Loris, Jurij Lah, and San Hadži. Structural basis of epitope recognition by heavy-chain camelid antibodies. *Journal of molecular biology*,

430(21):4369–4386, 2018.

8. Yuko Tsuchiya and Kenji Mizuguchi. The diversity of h 3 loops determines the antigen-binding tendencies of antibody cdr loops. *Protein Science*, 25(4):815–825, 2016.

9. Cristian Regep, Guy Georges, Jiye Shi, Bojana Popovic, and Charlotte M Deane. The h3 loop of antibodies shows unique structural characteristics. *Proteins: Structure, Function, and Bioinformatics*, 85(7):1311–1318, 2017.

10. Jinrui Xu and Yang Zhang. How significant is a protein structure similarity with tm-score= 0.5? *Bioinformatics*, 26(7):889–895, 2010.

11. Gerald M Edelman. Antibody structure and molecular immunology. *Science*, 180(4088):830–840, 1973.

12. Susumu Tonegawa. Somatic generation of antibody diversity. *Nature*, 302(5909):575–581, 1983.

13. Robert M MacCallum, Andrew CR Martin, and Janet M Thornton. Antibody-antigen interactions: contact analysis and binding site topography. *Journal of molecular biology*, 262(5):732–745, 1996.

14. Mauricio Aguilar Rangel, Alice Bedwell, Elisa Costanzi, Ross J Taylor, Rosaria Russo, Gonçalo JL Bernardes, Stefano Ricagno, Judith Frydman, Michele Vendruscolo, and Pietro Sormanni. Fragment-based computational design of antibodies targeting structured epitopes. *Science Advances*, 8(45):eabp9540, 2022.

15. Dror Baran, M Gabriele Pszolla, Gideon D Lapidoth, Christoffer Norn, Orly Dym, Tamar Unger, Shira Albeck, Michael D Tyka, and Sarel J Fleishman. Principles for computational design of binding antibodies. *Proceedings of the National Academy of Sciences*, 114(41):10900–10905, 2017.

16. Jared Adolf-Bryfogle, Oleks Kalyuzhniy, Michael Kubitz, Brian D Weitzner, Xiaozhen Hu, Yumiko Adachi, William R Schief, and Roland L Dunbrack Jr. Rosettaantibodydesign (rabd): A general framework for computational antibody design. *PLoS computational biology*, 14(4):e1006112, 2018.

17. Patrick Chames, Marc Van Regenmortel, Etienne Weiss, and Daniel Baty. Therapeutic antibodies: successes, limitations and hopes for the future. *British journal of pharmacology*, 157(2):220–233, 2009.

18. Hedi Chen, Xiaoyu Fan, Shuqian Zhu, Yuchan Pei, Xiaochun Zhang, Xiaonan Zhang, Lihang Liu, Feng Qian, and Boxue Tian. Accurate prediction of cdr-h3 loop structures of antibodies with deep learning. *Elife*, 12:RP91512, 2024.

19. Mario S Valdés-Tresanco, Mario E Valdés-Tresanco, Daiver E Jiménez-Gutiérrez, and Ernesto Moreno. Structural modeling of nanobodies: a benchmark of state-of-the-art artificial intelligence programs. *Molecules*, 28(10):3991, 2023.

20. ML Fernández-Quintero, J Kraml, G Georges, and KR Liedl. Cdr-h3 loop ensemble in solution-conformational selection upon antibody binding. mabs 2019, 11 (6), 1077–1088. *DOI*, 10(19420862.2019):1618676.

21. John Jumper, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, Russ Bates, Augustin Žídek, Anna Potapenko, et al. Highly accurate protein structure prediction with alphafold. *nature*, 596(7873):583–589, 2021.

22. Richard Evans, Michael O'Neill, Alexander Pritzel, Natasha Antropova, Andrew Senior, Tim Green, Augustin Žídek, Russ Bates, Sam Blackwell, Jason Yim, et al. Protein complex prediction with alphafold-multimer. *biorxiv*, pages 2021–10, 2021.

23. Josh Abramson, Jonas Adler, Jack Dunger, Richard Evans, Tim Green, Alexander Pritzel, Olaf Ronneberger, Lindsay Willmore, Andrew J Ballard, Joshua Bambrick, et al. Accurate structure prediction of biomolecular interactions with alphafold 3. *Nature*, 630(8016):493–500, 2024.

24. Jeremy Wohlwend, Gabriele Corso, Saro Passaro, Mateo Reveiz, Ken Leidal, Wojtek Swiderski, Tally Portnoi, Itamar Chinn, Jacob Silterra, Tommi Jaakkola, et al. Boltz-1: Democratizing biomolecular interaction modeling. *bioRxiv*, pages 2024–11, 2024.

25. Chai Discovery team, Jacques Boitreaud, Jack Dent, Matthew McPartlon, Joshua Meier, Vinicius Reis, Alex Rogozhonikov, and Kevin Wu. Chai-1: Decoding the molecular interactions of life. *BioRxiv*, pages 2024–10, 2024.

26. ByteDance AML AI4Science Team, Xinshi Chen, Yuxuan Zhang, Chan Lu, Wenzhi Ma, Jiaqi Guan, Chengyue Gong, Jincai Yang, Hanyu Zhang, Ke Zhang, et al. Protenix-advancing structure prediction through a comprehensive alphafold3 reproduction. *bioRxiv*, pages 2025–01, 2025.

27. Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Robert Verkuil, Ori Kabeli, Yaniv Shmueli, et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science*, 379(6637):1123–1130, 2023.

28. Saro Passaro, Gabriele Corso, Jeremy Wohlwend, Mateo Reveiz, Stephan Thaler, Vignesh Ram Somnath, Noah Getz, Tally Portnoi, Julien Roy, Hannes Stark, David Kwabi-Addo, Dominique Beaini, Tommi Jaakkola, and Regina Barzilay. Boltz-2: Towards accurate and efficient binding affinity prediction. *bioRxiv*, 2025.

29. Rui Yin and Brian G Pierce. Evaluation of alphafold antibody–antigen modeling with implications for improving predictive accuracy. *Protein Science*, 33(1):e4865, 2024.

30. Fatima N Hitawala and Jeffrey J Gray. What has alphafold3 learned about antibody and nanobody docking, and what remains unsolved? *bioRxiv*, 2024.

31. Milot Mirdita, Konstantin Schütze, Yoshitaka Moriwaki, Lim Heo, Sergey Ovchinnikov, and Martin Steinegger. Colabfold: making protein folding accessible to all. *Nature methods*, 19(6):679–682, 2022.

32. Martin Steinegger and Johannes Söding. Mmseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. *Nature biotechnology*, 35(11):1026–1028, 2017.

33. Milot Mirdita, Lars von den Driesch, Clovis Galiez, Maria J. Martin, Johannes S"oding, and Martin Steinegger. Uniclust databases of clustered and deeply annotated protein sequences and alignments. *Nucleic Acids Res.*, 45(D1):D170–D176, 2017.

34. Tamarind Bio. State of the art computational tools for biology. `https://www.tamarind.bio/`, 2024. Accessed: 2025-04-27.

35. Sankar Basu and Björn Wallner. Dockq: a quality measure for protein-protein docking models. *PloS one*, 11(8):e0161879, 2016.

36. Claudio Mirabello and Björn Wallner. Dockq v2: improved automatic quality measure for protein multimers, nucleic acids, and small molecules. *Bioinformatics*, 40(10):btae586, 09 2024.

37. Marc F Lensink, Nurul Nadzirin, Sameer Velankar, and Shoshana J Wodak. Modeling protein-protein, protein-peptide, and protein-oligosaccharide complexes: Capri 7th edition. *Proteins: Structure, Function, and Bioinformatics*, 88(8):916–938, 2020.

38. Raúl Méndez, Raphaël Leplae, Leonardo De Maria, and Shoshana J Wodak. Assessment of blind predictions of protein–protein interactions: current status of docking methods.

Proteins: Structure, Function, and Bioinformatics, 52(1):51–67, 2003.

39. Wensi Zhu, Aditi Shenoy, Petras Kundrotas, and Arne Elofsson. Evaluation of alphafold-multimer prediction on multi-chain protein complexes. *Bioinformatics*, 39(7):btad424, 2023.

40. Joël Janin, Kim Henrick, John Moult, Lynn Ten Eyck, Michael JE Sternberg, Sandor Vajda, Ilya Vakser, and Shoshana J Wodak. Capri: a critical assessment of predicted interactions. *Proteins: Structure, Function, and Bioinformatics*, 52(1):2–9, 2003.

41. Hongtai Jing, Zhengtao Gao, Sheng Xu, Tao Shen, Zhangzhi Peng, Shwai He, Tao You, Shuang Ye, Wei Lin, and Siqi Sun. Accurate prediction of antibody function and structure using bio-inspired antibody language model. *Briefings in Bioinformatics*, 25(4), 2024.

42. DeepMind. Alphafold v2.3.0 technical note, 2022. Accessed [Date you accessed the document].

43. Björn Wallner. Afsample: improving multimer prediction with alphafold using massive sampling. *Bioinformatics*, 39(9):btad573, 2023.

44. Babette Wolf, Mateusz Piksa, Isabelle Beley, Agnes Patoux, Thierry Besson, Valerie Cordier, Bernd Voedisch, Patrick Schindler, Daniela Stöllner, Ludovic Perrot, et al. Therapeutic antibody glycosylation impacts antigen recognition and immunogenicity. *Immunology*, 166(3):380–407, 2022.

45. Saroja Weeratunga, Rachel S Gormal, Meihan Liu, Denaye Eldershaw, Emma K Livingstone, Anusha Malapaka, Tristan P Wallis, Adekunle T Bademosi, Anmin Jiang, Michael D Healy, et al. Interrogation and validation of the interactome of neuronal munc18-interacting mint proteins with alphafold2. *Journal of Biological Chemistry*, 300(1), 2024.

46. Julia K Varga, Sergey Ovchinnikov, and Ora Schueler-Furman. actifptm: a refined confidence metric of alphafold2 predictions involving flexible regions. *Bioinformatics*, 41(3):btaf107, 03 2025.

47. Roland L Dunbrack Jr. Rēs ipsae loquunt: What's wrong with alphafold's iptm score and how to fix it. *bioRxiv*, pages 2025–02, 2025.