`

SKiM-GPT: Combining Biomedical Literature-Based Discovery with Large Language Model Hypothesis Evaluation

Authors: Jack Freeman[1], Robert J. Millikin[1], Leo Xu[1], Ishaan Sharma[1], Bethany Moore[1], Cannon Lock[1], Kevin Shine George[1], Aviral Bal[1], Chitrasen Mohanty[1], Ron Stewart[1&]

&=Corresponding author.
Affiliations: 1-Morgridge Institute for Research, Madison, WI 53715 USA

Abstract

Background

Generating and testing hypotheses is a critical aspect of biomedical science. Typically, researchers generate hypotheses by carefully analyzing available information and making logical connections, which are then tested. The accelerating growth of biomedical literature makes it increasingly difficult to keep pace with connections between biological entities emerging across biomedical research. Recently developed automated means of generating hypotheses can generate many more hypotheses than can be easily tested. One such approach involves literature□based discovery (LBD) systems such as Serial KinderMiner (SKiM), which surfaces putative $A□B□C$ links derived from term co□occurrence. However, LBD systems leave three critical gaps: (i) they find statistical associations, not biological relationships; (ii) they can produce false□positive leads; and (iii) they do not assess agreement with a hypothesis in question. As a result, LBD search results often require costly manual curation to be of practical utility to the researcher. Large language models (LLMs) have the potential to automate much of this curation step, but standalone LLMs are hampered by hallucinations, lack of transparency in information sources, and the inability to reference data not included in the training corpus.

Results

We introduce **SKiM-GPT**, a retrieval-augmented generation (RAG) system that combines SKiM's co-occurrence search and retrieval with frontier LLMs to evaluate user-defined hypotheses. For every chosen A-B-C SKiM hit, SKiM-GPT retrieves appropriate PubMed abstract texts, filters out irrelevant abstracts with a fine-tuned relevance model, and

prompts an LLM to evaluate the user's hypothesis, given the relevant abstracts. Importantly, the

SKiM-GPT system is transparent and human-verifiable: it displays the retrieved abstracts, the

hypothesis score, and a justification for the score grounded in the texts and written in natural

language.

On a benchmark consisting of 14 disease-gene-drug hypotheses, SKiM-GPT achieves

strong ordinal agreement with four expert biologists (Cohen's κ = 0.84), demonstrating its ability

to replicate expert judgment.

Conclusions

SKiM-GPT is open-source (https://github.com/stewart-lab/skimgpt) and available

through a web interface (https://skim.morgridge.org), enabling both wet-lab and computational

researchers to systematically and efficiently evaluate biomedical hypotheses at scale.

Keywords: literature-based discovery (LBD); large language models (LLM); retrieval-

augmented generation (RAG); biomedical text mining; hypothesis evaluation; co-occurrence;

fine-tuning

Background

Literature-based discovery (LBD) is a field in which existing documented knowledge is

searched, typically in an automated or semi-automated way, to aid in formulating hypotheses and

finding novel discoveries by positing links between previously unconnected ideas (Smalheiser

2017). As the size of PubMed (currently over 37 million abstracts (Sayers et al. 2025)) and

similar text databases grow, manual knowledge cataloging and connection-making becomes

more difficult and LBD techniques become more important, as it is challenging for researchers to

keep up to date with all relevant literature domains. Typically, an LBD "discovery" is in the form

of an A-B-C relationship; A and B are two entities (genes, drugs, pathways, *etc.*) with an

association, as are B and C. These two associations may imply a (possibly indirect) relationship

between A and C, which may not yet be widely known. A classic example is fish oil as a

treatment for Raynaud's disease (Swanson 1987), discovered through their mutual link to blood

viscosity.

A major advantage of automated LBD methods is their ability to rapidly perform

hundreds or thousands of searches with different terms to identify latent associations at a scale

that would be impractical manually (*e.g.*, with Google Scholar). However, while existing LBD

methods can efficiently identify statistically significant associations between biomedical terms,

they generally lack a structured framework for evaluating whether these discovered associations

meaningfully support or contradict a specific scientific hypothesis. Tools such as Arrowsmith

(Torvik and Smalheiser 2007), Lion-LBD (Pyysalo et al. 2019), BITOLA (Hristovski et al.

2006), and our tool Serial KinderMiner (SKiM) (Millikin et al. 2023) primarily quantify the

strength of association without assessing relevance to or support of a hypothesis. See (Bhasuran

et al., 2025) for a recent review of LBD methodologies. Consequently, researchers still face a

significant burden of manually interpreting potentially thousands of associations, many of which

are irrelevant or spurious (Preiss and Stevenson 2017). Thus, methods capable of automated,

hypothesis-focused evaluation of LBD outputs are urgently needed.

Machine learning (ML), especially transformer-based large language models (LLMs),

provide opportunities for contextualizing LBD-identified relationships due to their increased

ability to capture nuanced semantic contexts compared to earlier approaches (Zhang et al., 2024;

Zhao et al., 2025). Our previous augmentation of SKiM with ML-generated knowledge graphs

showed promise but remained limited by sparse relationship annotations (Millikin et al., 2023).

However, LLMs, particularly the advancement of reasoning models (J. Wei et al. 2023), are

becoming increasingly capable of accurately parsing biomedical science texts. General-purpose

LLMs (OpenAI et al. 2024; Anil et al. 2024; DeepSeek-AI et al. 2025) achieve

state-of-the-art scores on biomedical reasoning and question-answering benchmarks (Rein et

al. 2023; Q. Chen et al. 2025; Jin et al. 2019). Furthermore, emerging multi-agent frameworks

capable of autonomously generating and evaluating hypotheses (Gottweis et al. 2025) underscore

a growing capability to not only surface potential discoveries but systematically assess their

potential. Other methods for evaluation of hypotheses include benchmarking against curated

datasets (Tyagin and Safro 2024) and utilizing knowledge graphs and transformer-based models

(Tyagin et al. 2021). Motivated by these advances, we wanted to integrate LLM-based

hypothesis evaluation into the SKiM workflow to enhance the interpretability and precision of

putative LBD discoveries, while reducing the costs of manual review required of researchers.

However, a known challenge with LLMs is their propensity to generate incorrect or

fabricated information ("hallucinations") (Maynez et al. 2020). Retrieval-augmented generation

(RAG) is a promising strategy to mitigate this issue by supplementing an LLM's parametric

(trained) memory with externally retrieved documents, providing a factual grounding for

generated responses (Gao et al. 2024; Lewis et al. 2021). By combining both parametric (trained)

and non-parametric (retrieved) sources, RAG reduces the frequency of hallucinations and

improves interpretability, especially for information-sensitive tasks such as question answering

and multi-hop reasoning (Pham and Vo 2024; Cao et al. 2023; Tonmoy et al. 2024).

Additionally, the recently developed scientific claim verification tool Valsci (Edelman &

Skolnick, 2025) highlights the importance of RAG in minimizing the citation hallucination rate

and reducing misclassifications of scientific claims as true or not. Our LBD tool, SKiM, serves

two purposes. First, it is an effective way to surface new literature-based putative discoveries

based on the co-occurrence model described above. Second, it provides a list of documents to be

inputted for RAG analysis by the frontier LLM. These documents can supplement the model's

knowledge and provide context not available to the LLM during its training. Additionally, our

RAG system, SKiM-GPT, displays these retrieved documents along with the LLM's reasoning to

the user, increasing transparency.

Still, the effectiveness of RAG depends on the quality and relevance of the retrieved

documents. Retrieving documents that are irrelevant, ambiguous, or only weakly related to the

hypothesis can introduce noise and misleading context, increasing the risk of inaccuracies and

hallucinations (Hsieh et al. 2024; Modarressi et al. 2025). This risk is especially acute in

biomedical literature, where terms frequently have multiple meanings and contexts can vary

significantly (C.-H. Wei et al. 2019; Sohn et al. 2008). Therefore, a dedicated relevance filtering

step is essential for RAG-based systems (J. Chen et al. 2024; Yu et al. 2024), ensuring that only

information directly pertinent to the hypothesis at hand is included in the LLM's context.

In summary, co-occurrence-based algorithms can discover novel associations without

explicitly evaluating hypotheses, resulting in substantial manual effort to interpret relationships,

manage high false-positive rates, and determine mechanistic context. LLMs have the potential to

alleviate these problems but suffer from frequent hallucinations and opaque decision-making.

SKiM-GPT's integrated approach leverages the complementary strengths of each tool, providing

increased interpretability and precision compared to SKiM alone, while grounding the LLM's

reasoning in the retrieved documents. SKiM-GPT is open-source on GitHub (

https://github.com/stewart-lab/skimgpt) and is available as a user-friendly web interface

(https://skim.morgridge.org). Our contributions include: (1) providing a generalized method to

improve the interpretability and false-positive rate of LBD systems; (2) providing an evaluation

benchmark for that method; and (3) providing a concrete open-source implementation with a

publicly accessible web interface.

Implementation

Figure 1. Overview of the SKiM-GPT workflow for hypothesis evaluation. Users input an A

term and lists of B and C terms to discover hidden links between A and C terms. In this example,

the user is interested in finding FDA-approved drugs that might be repurposed for Alzheimer's

disease, where one of the ~19000 protein-coding human genes provide the link between drug and

disease. SKiM is run to find potential A-B-C links. The A-B and B-C co-occurring abstracts

found by SKiM are then run through the relevance filter to only include abstracts likely relevant

to the hypotheses. Finally, these relevant abstracts and the hypotheses are evaluated by a frontier

LLM, and the hypotheses are scored. The rationale and abstracts used are included in the output

to provide full transparency.

The SKiM-GPT workflow is composed of three sequential steps: 1) identifying co-occurring

terms in PubMed abstracts ("Serial KinderMiner"), 2) filtering abstracts for relevance to a user-

defined hypothesis ("abstract filtering"), and 3) evaluating support for that hypothesis based on

the filtered abstracts ("hypothesis evaluation") (**Figure 1**). Each of these steps is described

below.

Serial KinderMiner. The Serial KinderMiner (SKiM) algorithm is detailed in (Millikin et al.

2023). Briefly, SKiM identifies indirect relationships between A and C terms through B-term

intermediates using co-occurrence modeling. Given user-defined lists of A, B, and C terms,

SKiM searches PubMed abstracts for these terms using exact string matching and applies

Fisher's Exact Test (FET) to assess statistical significance of A-B and B-C term pairs using

contingency tables of occurrence and co-occurrence counts (note that SKiM allows the use of

"and" (&) and "or" (|) operators to search for inexact phrase matches and synonyms; this helps in

cases when the user wants to search for pathways, biological processes, gene families and

synonyms, etc. See the **Supporting Information** section "Exact String Matches and Evaluating

Mechanism" for an example). A and C terms are considered putatively related if they share a

significant B-term intermediary. SKiM ranks results based on a prediction score derived from *p-*

values and term co-occurrence frequencies. In addition to statistical significance, abstracts

containing co-occurring A-B, B-C, and A-C term pairs are retrieved as input for the next step.

Relevance filtering. After the SKiM search is complete, the user defines a hypothesis template

into which the search terms can be inserted (*e.g.*, "Drug {c-term} treats disease {a-term} through

its interaction with gene {b-term}."). Abstract texts retrieved in the previous SKiM step are then

filtered to determine their relevance to this hypothesis. Relevance is assessed using a fine-tuned

language model based on the Phi-3 mini base architecture (Abdin et al. 2024), which outputs a

single token indicating whether an abstract is relevant or irrelevant ("1" or "0", respectively).

The primary goal of this step is to select abstracts that can be used to evaluate the hypothesis,

regardless of whether they support or contradict it. This relevance filtering step is critical, as

biomedical concepts frequently exhibit high ambiguity in free text (C.-H. Wei et al. 2019), and

exact string-matching approaches like SKiM frequently retrieve abstracts containing ambiguous

or irrelevant matches (Q. Chen et al. 2020). See **Supporting Information** section "Fine-Tuning

Methodology" for further details on the implementation of relevance filtering.

Hypothesis evaluation. The hypothesis evaluation scoring guidelines, the user's hypothesis, and

the relevant abstracts are then processed by a frontier LLM. Inclusion of the relevant abstracts

grounds the LLM's analysis in the evidence contained in the abstracts rather than relying on its

parametric memory. The LLM assigns a numerical score between -2 and 2, representing the

degree of support for the hypothesis according to the scoring guidelines, and provides

explanatory reasoning including references to the abstracts used to arrive at a score. For scoring

guidelines and an example prompt see **Supporting Information.**

SKiM-GPT web API server implementation. SKiM-GPT was implemented as an open-source

Python package (https://github.com/stewart-lab/skimgpt) and incorporated into the existing

SKiM web API server (Millikin et al., 2023) as a new job type. Briefly, the SKiM web API

server uses a job queue system in which jobs are submitted to the server via HTTP request and

are put into the work queue. Workers retrieve the jobs and do the requisite processing (in this

case, using the SKiM-GPT python package to perform the relevance filtering and hypothesis

evaluation steps). The job's status and results can be retrieved via HTTP request. The server is

intended to be run as a multi-container Docker application; Python code and Docker build scripts

can be found at https://github.com/stewart-lab/fast_km . A public website for running SKiM and

SKiM-GPT queries that uses this API can be found at https://skim.morgridge.org .

Score alignment evaluation. Fourteen disease-gene-drug combinations were chosen from

statistically significant SKiM hits (twelve by RM; two by RS), intended to represent a wide

variety of scores (i.e., -2 to +2). Two of these examples were chosen because they were false-

positive SKiM hits (pancreatic cancer-CCK-gant61, diabetes-AHR-stauvidine). The rationale for

why these examples were chosen was not shared with the other co-authors until the scoring was

completed. The primary motivation behind these choices was to provide a set of examples to

assess how the system performed under relatively diverse scoring conditions.

Results

Score Alignment Evaluation

To assess how SKiM-GPT scores align with those of human evaluators, we gave four expert computational biologists (JF, RM, IS, RS) the task of evaluating a series of drug repurposing hypotheses and then compared those human scores to SKiM-GPT's. Fourteen distinct disease-gene-drug combinations were generated for this task from statistically significant SKiM hits. Human and LLM evaluators scored the supporting abstracts on a scale from -2 (strongly refutes the hypothesis) to $+2$ (strongly supports the hypothesis). SKiM-GPT generated scores from 10 independent runs per hypothesis to get a score distribution for each hypothesis (see **Figure 2** for an example output).

ABC Hypothesis: Erlotinib treats Breast Cancer through its effect on EGFR

Score: +1 Point – Reasoning:

1. Interaction 1 – Erlotinib → EGFR
 • All abstracts that mention Erlotinib describe it as an epidermal-growth-factor-receptor tyrosine-kinase inhibitor.
   – "Erlotinib, an EGFR inhibitor" (PMID: 41121964).
   – Erlotinib used as the reference drug in EGFR-kinase assays (PMIDs: 41151328, 41154639).
   – Erlotinib suppression of EGFR activity is functionally evident in cell systems (PMID: 41132131).
 • Direction: Erlotinib inhibits EGFR.

2. Interaction 2 – EGFR → Breast-cancer biology
 • Multiple breast-cancer studies show that down-regulating or pharmacologically blocking EGFR curbs tumour growth or proliferation:
   – A furanone derivative that "significantly suppressed EGFR expression" reduced tumour volume in a triple-negative breast-cancer xenograft (PMID: 41124879).
   – A carrier-free nanonetwork that co-delivers the EGFR inhibitor gefitinib exhibits "superior antiproliferative effects" in breast-cancer models (PMID: 41158712).
   – Virtual screening identified natural products that bind EGFR and are selectively cytotoxic to breast-cancer lines (PMID: 41167062).
 • Direction: Inhibition of EGFR is beneficial to breast-cancer control.

 • A minority, mechanistically specialised study shows that forced EGFR activation by EGF-decorated nanoparticles can also kill certain EGFR-high breast-cancer cells (PMID: 41140511), and another report notes that EGFR activity is required for extrusion of oncogenic Ras cells, so Erlotinib blocks that protective extrusion (PMID: 41132131). These observations introduce some uncertainty but do not provide dominant evidence that EGFR inhibition is harmful to breast-cancer therapy overall.

3. Indirect chain of reasoning
 • Because Erlotinib inhibits EGFR (Step 1) and EGFR inhibition tends to inhibit breast-cancer growth (Step 2), it is logical that Erlotinib could treat breast cancer through its action on EGFR.
 • The bulk of evidence aligns with the hypothesis, but two pieces (PMIDs: 41140511, 41132131) show contexts in which EGFR activation or non-canonical EGFR signalling can also have anti-tumour or tumour-suppressive roles, preventing us from claiming unequivocal, contradiction-free support.

4. Scoring decision
 • According to the provided guidelines, consistent yet mildly contradicted support corresponds to "likely supported" = +1.
 • There is more evidence in favour (EGFR inhibition helps breast cancer; Erlotinib is an EGFR inhibitor) than against, but some conflicting mechanistic findings prevent a +2.

Therefore, the hypothesis "Erlotinib treats Breast Cancer through its effect on EGFR" is likely supported, warranting a score of +1.

Figure 2. Screenshot of the web interface after evaluating the A-B-C hypothesis "Erlotinib treats Breast Cancer through its effect on EGFR".

Without relevance filtering, SKiM-GPT showed substantial agreement with human evaluators (**Figure 3A**; root mean square error (RMSE) = 0.57, quadratic-weighted Cohen's κ (QWK) = 0.84 (Fleiss and Cohen 1973), intraclass correlation coefficient (ICC (2,1)) = 0.91

(Koo & Li, 2016). Directional concordance between SKiM-GPT's median score and human

median score occurred in 13 out of 14 hypotheses (93%), and the median SKiM-GPT score fell

within the human score range in 12 of 14 cases (79%).

A relevance filtering step was added to ensure that human and SKiM-GPT evaluators

based their decisions on abstracts directly pertinent to the hypotheses (see **Relevance Filtering**

Evaluation below). This filtering step removes irrelevant or contextually ambiguous abstracts

retrieved by SKiM (*e.g.*, "AHR" can refer to the "aryl hydrocarbon receptor" gene or the

"adjusted hazard ratio" measure). With relevance filtering, agreement between SKiM-GPT and

human evaluators remained high (**Figure 3B**; RMSE = 0.64, QWK= 0.84, ICC (2,1) = 0.91),

with directional concordance of 100% (14/14) and median scores falling within the human

evaluators' range in 12 of 14 cases (86%).

Figure 3. Comparison between human expert and SKiM-GPT hypothesis evaluation scores

across 14 disease–gene–drug hypotheses. The hypotheses were scored in a range from −2

(strongly refuted) to +2 (strongly supported) based on the provided abstracts. **(A)** *Without*

relevance filtering. For each hypothesis, red violins show the distribution of SKiM-GPT scores

obtained from 10 independent runs; overlaid red dots are the individual run values. Blue violins

show the distribution of the four expert scores, with overlaid blue symbols marking each

evaluator's score. Horizontal lines inside violins mark medians. Median SKiM-GPT scores

largely agreed with human evaluators (directional concordance = 93%; within-range agreement =

86%; RMSE = 0.57). In cases where the distributions are narrow, there is generally little

subjective interpretation needed; the score is fairly obvious. In less obvious cases, the

distributions are wider because the scores are more subjective or uncertain. **(B)** *With relevance*

filtering. Same plotting conventions as in (A). With relevance filtering, SKiM-GPT median

scores maintained strong agreement with human evaluators (directional concordance = 100%,

within-range agreement = 86%; RMSE = 0.64) compared to no relevance filtering.

Relevance Filtering Evaluation

To evaluate relevance classification performance, we compared the pretrained base and

fine-tuned models using a set of 177 abstract–hypothesis pairs (140 manually annotated from

Figure 3 literature and 37 LLM-generated ["synthetic"] abstracts). Each pair was labeled as

either 0 ("Not Relevant") or 1 ("Relevant") and split into 105 training and 72 test pairs. The

pretrained model achieved 0.68 accuracy, 0.70 precision, 0.92 recall, and an F1 of 0.80, while

the fine-tuned model improved performance to 0.86 accuracy, 0.85 precision, 0.96 recall, and an

F1 of 0.90 (Figure 4A–B). The fine-tuned model misclassified only two relevant abstracts as

irrelevant, reflecting a deliberate design choice to favor a low false-negative rate so that nearly

all potentially useful evidence is retained for downstream hypothesis evaluation. Next, we

measured the model's performance on an out-of-distribution abstract set to assess the

generalizability of the relevance filter to hypotheses not observed during training. In this

evaluation, abstracts containing possible drug-drug interactions (DDIs) (**Figure 4C**) and

functional gene interactions (FGIs) (**Figure 4D**) were generated with GPT-4 and labeled with a 1

or 0, as above. The model's precision 0.90 and recall 1.0 on this out-of-training data indicates the

ability to generalize across biomedical domains. For more information on generating synthetic

text and descriptions of relevance categories, see **Supporting Information** and **Figures S1A-B.**

Figure 4. Evaluation of the relevance-filtering model. (**A**) *Pretrained base model (Phi-3-mini-4k-instruct) performance confusion matrix.* Confusion matrix showing performance of the pretrained base model on the 72-abstract test set. The model correctly retained 44 of 48 relevant abstracts and correctly discarded 5 of 24 irrelevant abstracts (accuracy = 0.68; precision = 0.70; recall = 0.92; F1 = 0.80). (**B**) *Fine-tuned model performance confusion matrix.* Evaluation of the relevance filtering model on the 72-abstract test set shows that 46 of 48 relevant abstracts were correctly retained, while 16 of 24 irrelevant abstracts were correctly discarded (accuracy = 0.86;

precision = 0.85; recall = 0.96; F1 = 0.90). Two relevant abstracts were incorrectly discarded,

and eight irrelevant abstracts were incorrectly retained, reflecting the design choice to favor low

false-negative rates so that almost all useful evidence reaches the hypothesis evaluation stage.

(C, D) *Generalization to unseen interaction types.* Bar charts report per-category accuracy on

100 GPT-4-generated abstracts describing drug–drug interactions **(C)** and functional gene

interactions **(D)** that were absent from training. Blue bars indicate contexts expected to be

relevant to the hypothesis; orange bars indicate background or non-interaction scenarios that

should be rejected as irrelevant.

Cost Estimation

One way to understand the discrepancy between the vast amount of published biomedical

literature and the human bandwidth available to read and interpret it is through an analysis of the

cost difference between human and SKiM-GPT evaluation. Human evaluators required an

average of 8.42 ± 1.20 hours per person to read 159 abstracts, incurring an estimated cost of

$336.80 per person (assuming $40/hour) (**Table 1**). In contrast, the SKiM-GPT system evaluated

the same set of abstracts in 0.23 ± 0.03 hours, with a cost of $8.62 (the OpenAI API call cost).

This represents a 97% reduction in evaluation time and a 97% decrease in monetary cost when

using SKiM-GPT compared to manual human analysis.

Table 1. Cost difference between human and SKiM-GPT evaluation

Number of Abstracts	Human Evaluation Time (hours)	SKiM-GPT Evaluation Time (hours)	Human Evaluation Monetary Cost (USD)	SKiM-GPT Evaluation Monetary Cost (USD)
159	8.42 ± 1.20	0.23 ± 0.03	$336.80	$8.62

302 **Table 1.** Cost estimation for human experts and SKiM-GPT to evaluate 159 biomedical

303 abstracts. SKiM-GPT took 0.23 ± 0.03 hours to review the given text corpus at a cost of \$8.62 in

304 API calls, whereas human experts required 8.42 ± 1.20 hours (est. \$336.80, assuming \$40/hour).

305 SKiM-GPT was 97% faster and 97% less expensive compared to human experts.

Retrieved Text vs Memory

We next assessed the potential problem of parametric-knowledge leakage in SKiM-GPT's

evaluations through a series of controlled experiments. "Parametric-knowledge leakage" refers to

the LLM's undesired reliance on internal parametric memory to evaluate a hypothesis instead of

external information (*i.e.*, the abstracts). The desired behavior for SKiM-GPT's hypothesis

evaluation is to rely only on the provided, contextually relevant literature, rather than pre-

existing model biases. To assess leakage, we had SKiM-GPT evaluate three different hypotheses

that assess the efficacy of FDA-approved breast cancer drugs (**Figure 5A**) in improving breast

cancer patient outcomes. Synthetic (*i.e.*, fake) abstracts were generated to imply neutral,

negative, and positive relationships between each drug and breast cancer patient outcomes and

supplied to SKiM-GPT. When the positive hypothesis was evaluated without any retrieved

abstracts, SKiM-GPT produced strongly positive scores, confirming expected leakage from the

training data (**Figure 5B**). SKiM-GPT strongly supported neutral hypotheses when provided

with neutral abstracts (**Figure 5C**), negative hypotheses when supplied with negative abstracts

(**Figure 5D**), and positive hypotheses when provided with positive abstracts (**Figure 5B**),

indicating that SKiM-GPT grounds its analysis in the provided texts even in cases where its

parametric memory conflicts with those texts **(Figure 5C and 5D)**. When using the five most

cited real abstracts, the positive scores indicated correct agreement with the positive hypothesis

(**Figure 5B**). Additionally, we evaluated parametric-knowledge leakage using real abstracts; two

examples are provided in the **Supporting Information** section "Time-Slicing Parametric-

Knowledge Leakage Evaluation".

A) FDA-approved Breast Cancer Drugs

Drug Name	Approval Year
Capivasertib	2023
Elacestrant	2023
Pembrolizumab	2020
Sacituzumab govitecan-hziy	2020
Margetuximab	2020
Alpelisib	2019
Fam-trastuzumab deruxtecan-nxki	2019
Talazoparib	2018
Olaparib	2018
Abemaciclib	2017
Ribociclib	2017
Neratinib	2017
Palbociclib	2015
Ado-trastuzumab emtansine	2013
Pertuzumab	2012
Everolimus	2012
Lapatinib	2007
Trastuzumab	1998
Toremifene	1997
Anastrozole	1995

Figure 5. Parametric-knowledge leakage test of SKiM-GPT on 20 FDA-approved breast cancer drugs. **(A)** Reference table listing each drug and its FDA approval year. **(B-D)** Each point represents the hypothesis support score for each drug. Violin plots with y-axis jittered points depict score distributions across conditions on the x-axis, where "Negative," "Neutral," and "Positive" denote synthetic abstract sentiment and "Real text" denotes retrieved PubMed abstracts while "No text" denotes no added abstracts. **(B)** *Positive hypothesis condition.* Without any provided abstracts ("No text"), when asked whether each drug "improves breast-cancer patient outcomes," SKiM-GPT assigns positive scores (median = +2), indicating that parametric (trained) memory is biased towards positive scores in these cases as expected ("parametric-knowledge leakage"). **(C)** *Neutral hypothesis condition.* Feeding synthetic abstracts that state no relationship exists between the drug and breast cancer patient outcomes increases scores for neutral hypotheses (median = +2) for all drugs, indicating the model grounds its judgment in the supplied context rather than internal bias. **(D)** *Negative hypothesis condition.* Providing synthetic abstracts that refute drug efficacy results in increased scores for negative hypotheses (median = +2). Together, panels B–D indicate that SKiM-GPT's scores mirror the sentiment of the abstracts rather than the LLM's training data.

LBD False-Positive Removal Evaluation

Co-occurrence-based LBD search systems like SKiM measure how frequently search terms occur together in a corpus of text. These frequency measures (i.e. *p*-values) do not describe how or why these terms co-occur. The addition of relevance filtering and frontier LLM hypothesis evaluation allows ranking of true-positives in the co-occurrence-based LBD hit list,

and removal of false-positives. Above, we have discussed examples where relevance filtering

removes false-positive hits owing to semantic ambiguity (*e.g.*, the "AHR" search term can refer

to "aryl hydrocarbon receptor" or "adjusted hazard ratio"). In these cases, false-positive abstracts

are removed via relevance filtering. In other cases, SKiM may primarily retrieve abstracts in

which the terms correctly refer to the user's intended meaning, but the retrieved abstract texts

disagree with the user's hypothesis and is thus a different type of false-positive LBD hit.

To test whether SKiM-GPT can remove false-positives and rank true-positives, we

queried SKiM using "breast cancer" as the A-term, a comprehensive list of human genes as B-

terms, and a comprehensive list of FDA-approved drugs as C-terms. The hypothesis used for

evaluation was "*{C-term} treats {A-term} through its effect on {B-term}.*" The top 20 highest-

ranked A-B-C hits by *p*-value (see **Supporting Information** for methodological details) are

reported in **Table 2**. Manual evaluation of these top 20 hits indicated that SKiM-GPT correctly

classified 19 of them, confirming 16 true drug-gene treatment links (positive scores) and

correctly discarding three false positives (zero or negative scores). In the one case where SKiM-

GPT was unable to correctly classify, the gene name SLN returned no relevant abstracts, as the

abbreviation SLN can also stand for "sentinel lymph node" which is often a term associated with

cancers.

Table 2. SKiM-GPT's ability to filter a list of SKiM co-occurrence hits.

A-B-C Relationship	Score	Label	Comments
Breast Cancer - BCL2 - VENETOCLAX	+1	TP	

Breast Cancer - BRCA1 - OLAPARIB	+2	TP	
Breast Cancer - BRCA2 - OLAPARIB	+2	TP	
Breast Cancer - CDK4 - ABEMACICLIB	+2	TP	
Breast Cancer - CDK4 - FULVESTRANT	-1	TN	FULVESTRANT doesn't treat breast cancer via CDK4 directly.
Breast Cancer - CDK4 - PALBOCICLIB	+2	TP	
Breast Cancer - EGFR - AFATINIB	+1	TP	Only mildly effective in some breast cancer cases
Breast Cancer - EGFR - CETUXIMAB	+1	TP	
Breast Cancer - EGFR - CRIZOTINIB	-2	TN	CRIZOTINIB doesn't act directly through EGFR and is not known to have indirect effects on the EGFR pathway. It may be able to combine with EGFR inhibitors to treat breast cancer
Breast Cancer - EGFR - DACOMITINIB	+1	TP	Not a primary treatment. Sometimes used when other treatments fail
Breast Cancer - EGFR - ERLOTINIB	+1	TP	Only effective for some breast cancer patients
Breast Cancer - EGFR - GEFITINIB	+1	TP	Only effective for some breast cancer patients
Breast Cancer - EGFR - PANITUMUMAB	+1	TP	PANITUMUMAB can treat aggressive forms of inflammatory breast cancer via EGFR inhibition.
Breast Cancer - EGFR - PEMETREXED	-1	TN	Plausible mechanism but mostly used for NSCLC
Breast Cancer - ESR1 - FULVESTRANT	+1	TP	
Breast Cancer - MTOR - EVEROLIMUS	+2	TP	

Breast Cancer - MTOR - TEMSIROLIMUS	+2	TP	
Breast Cancer - PIK3CA - ALPELISIB	+1	TP	
Breast Cancer - RAD51 - OLAPARIB	+1	TP	While OLAPARIB doesn't act directly via RAD51, RAD51 deficiency allows OLAPARIB's effectiveness
Breast Cancer - SLN - ISOSULFAN BLUE	N/A	False N/A	No relevant abstracts were found; should get a negative score because ISOSULFAN BLUE doesn't treat breast cancer via SLN gene.

Table 2. Assessment of SKiM-GPT's ability to remove false-positive hits in an LBD search. "Breast Cancer" was used as the A-term, a list of human genes as B-terms, and FDA-approved drugs as C-terms. The hypothesis "*{C-term} treats {A-term} through its effect on {B-term}*" was used to evaluate the top 20 hits ranked by *p*-value. For each SKiM A-B-C hit (column 1), SKiM-GPT scores the provided hypothesis from –2 (strongly refutes) to +2 (strongly supports) after relevance filtering (column 2). Scores were classified as a true-positives (TP) or true-negatives (TN) based on current clinical or mechanistic evidence (column 3). The comments (column 4) contain context-specific notes. SKiM-GPT correctly classified 19 of 20 hits, confirming 16 valid drug–gene treatment links and correctly discarding three false positives.

Discussion

Recent advances in natural language processing have enabled increasingly context-aware automated parsing of the biomedical literature at scale, rather than relying on simple text search and manual validation. SKiM-GPT pairs SKiM's co-occurrence search and retrieval with a relevance filter and an LLM-based hypothesis evaluator. This three-stage workflow discards many of the spurious associations as documented in earlier LBD studies (Gopalakrishnan et al.

2019; Cheerkoot-Jalim and Khedo 2021), anchors each evaluation in the provided literature, and

produces quantitative and qualitative support that aligns with expert judgement. While earlier

tools such as KinderMiner and SKiM excel at finding associations between entities by surfacing

statistically enriched term pairs (Kuusisto et al. 2017; Millikin et al. 2023), SKiM□GPT defines

relationships and provides the precision that co□occurrence models lack, without exposing it to

the hallucinations and other issues such as lack of transparency, opaqueness of reasoning, and

parametric-knowledge leakage that plague stand□alone LLMs.

The platform is freely accessible as both a command□line utility and a web application (

https://skim.morgridge.org/), with the web interface meant to be usable by anyone at any skill

level. Some example goals of this system are to 1) discover new, potentially meaningful

connections between biomedical concepts and assess their plausibility for downstream

experimental validation, 2) evaluate a new hypothesis that the user has, 3) re-examine or

benchmark existing hypotheses using time-sliced or current literature evidence. Some examples

of potential SKiM-GPT uses include but are not limited to prioritizing drug repurposing

candidates, interrogating functional gene or drug–drug interactions, assembling gene□regulatory

networks, identifying pathways that link genes, and/or refining cell□type annotations in

single□cell atlases without manually scouring the literature. While many associations are likely

established in literature, SKiM-GPT may also find novel A-B-C links that can lead to new

hypotheses and discoveries. For more information on identifying novel A-B-C links see

Supporting information section "How to Identify Novel Hypotheses Returned by SKiM-GPT".

At present SKiM□GPT analyzes only PubMed titles and abstracts, leaving valuable

insights in full-text articles, figures, and tables inaccessible. It also lacks support for non-textual

modalities such as microscopy images, clustering plots, and single-cell embeddings. Moreover,

large-scale screens can be expensive due to reliance on commercial LLM APIs. To address these

limitations, we plan to implement an open-source hypothesis evaluator model, eliminating

dependence on proprietary models and their API costs. We also plan to extend retrieval beyond

abstracts to full-text articles and other structured data, and to reduce future inference costs

through model quantization and routing techniques. Additionally, negative or inconclusive

results are less likely to be published, and these unpublished results would be invisible to SKiM-

GPT; this may skew SKiM-GPT's scores, especially in the case where few abstracts are

available to score a hypothesis. Regularization or a Bayesian prior may help address this issue.

We would also like to modify the relevance filter to rank the retrieved texts by a

continuous relevance score and taking the top N with some minimum relevance score, rather

than using a binary classifier for relevant/irrelevant and taking N. This may help make some

hypotheses easier to score; some examples of difficult-to-score hypotheses in **Figure 3** could be

a good starting point for fine-tuning this new relevance filtering model.

SKiM☐GPT couples high☐recall retrieval with context☐aware LLM reasoning to

surface the most plausible mechanistic relationships hidden in an ever☐growing corpus of

biomedical literature, making hypothesis evaluation 97% faster and 97% less expensive for both

dry☐ and wet☐lab researchers.

Availability and Requirements

429
430   Project Name: SKiM-GPT.

431
432   Project home page: https://skim.morgridge.org/ (user-facing website);
433   https://github.com/stewart-lab/skimgpt (application code).

434
Operating system(s): Platform independent.

Programming language: Python.

Other requirements: To run SKiM-GPT from the command line, Python 3.10 or higher is

required along with other requirements outlined in requirements.txt. Additionally, a user must

have an account with OSPool or other HTCondor systems with GPU access; to use the tool on

the website, no requirements except a web browser.

License: MIT.

Any restrictions to use by non-academics: No restrictions.

List of abbreviations

RMSE – Root mean square error

ICC – Intraclass correlation coefficient

LLM – Large language model

RAG – Retrieval-augmented generation

LBD – Literature-based discovery

KM – KinderMiner (two-term co-occurrence search)

SKiM – Serial KinderMiner (A-B-C three-term co-occurrence framework)

GPT – Generative pre-trained transformer

HTTP – Hypertext transfer protocol

API – Application programming interface

DDI – Drug-drug interaction

FGI – Functional gene interaction

QWK – Quadratic weighted kappa

FET – Fisher's exact test

474   Declarations

475   Ethics approval and consent to participate

476   **Not applicable.** This work analyzed publicly available biomedical abstracts and did not involve
477   human participants.

478   Consent for publication

479   **Not applicable.** The manuscript does not contain any individual person's data.

480   Availability of data and materials

481   The SKiM-GPT package is open-source on GitHub (https://github.com/stewart-lab/skimgpt) All
482   synthetic text data, term lists, and relevance filter misclassifications are available (
483   https://github.com/stewart-lab/skimgpt/tree/paper) This data is also included in the additional
484   file "SKiM_GPT_supplementary_Data.zip".

485   Competing interests

486   The authors declare **no competing interests**.

487   Funding

488   This research was supported by the Morgridge Institute for Research.

489   Authors' Contributions

490   JF, LX, KG, RM, and RS developed SKiM-GPT. JF, RM, and RS designed the study and
491   evaluations. JF, RM, IS, and RS evaluated the hypotheses. LX and JF trained and integrated the
492   relevance filter. JF and IS created the synthetic datasets. BM, JF and RM provided statistical
493   support. CL, AB, KG, RM and JF built the web interface. CM ran the dimensionality reduction
494   experiment. JF, RM, IS and RS wrote the manuscript.

495   Acknowledgements

496   We thank the Center for High Throughput Computing (CHTC) at UW–Madison for GPU
497   resources and the Morgridge Institute for Research Computing staff for infrastructure support.
498   We thank Alicia Williams for editorial assistance.

References

Abdin, Marah, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen
    Bach, Amit Bahree, et al. 2024. "Phi-3 Technical Report: A Highly Capable Language
    Model Locally on Your Phone." arXiv. https://doi.org/10.48550/arXiv.2404.14219.

Anil, Rohan, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan
    Schalkwyk, et al. 2024. "Gemini: A Family of Highly Capable Multimodal Models."
    arXiv. https://doi.org/10.48550/arXiv.2312.11805.

Bhasuran, B., Murugesan, G., & Natarajan, J. (2025). Literature-Based Discovery (LBD):
    Towards Hypothesis Generation and Knowledge Discovery in Biomedical Text Mining.
    Medinformatics. https://doi.org/10.47852/bonviewMEDIN52025348

Cao, Hejing, Zhenwei An, Jiazhan Feng, Kun Xu, Liwei Chen, and Dongyan Zhao. 2023. "A
    Step Closer to Comprehensive Answers: Constrained Multi-Stage Question
    Decomposition with Large Language Models." arXiv.
    https://doi.org/10.48550/arXiv.2311.07491.

Cheerkoot-Jalim, Sudha, and Kavi Kumar Khedo. 2021. "Literature-Based Discovery
    Approaches for Evidence-Based Healthcare: A Systematic Review." *Health and
    Technology* 11 (6): 1205–17. https://doi.org/10.1007/s12553-021-00605-y.

Chen, Jiawei, Hongyu Lin, Xianpei Han, and Le Sun. 2024. "Benchmarking Large Language
    Models in Retrieval-Augmented Generation." *Proceedings of the AAAI Conference on
    Artificial Intelligence* 38 (16): 17754–62. https://doi.org/10.1609/aaai.v38i16.29728.

Chen, Qingyu, Yan Hu, Xueqing Peng, Qianqian Xie, Qiao Jin, Aidan Gilson, Maxwell B.
    Singer, et al. 2025. "Benchmarking Large Language Models for Biomedical Natural
    Language Processing Applications and Recommendations." *Nature Communications* 16
    (1): 3280. https://doi.org/10.1038/s41467-025-56989-2.

Chen, Qingyu, Kyubum Lee, Shankai Yan, Sun Kim, Chih-Hsuan Wei, and Zhiyong Lu. 2020. "BioConceptVec: Creating and Evaluating Literature-Based Biomedical Concept Embeddings on a Large Scale." *PLoS Computational Biology* 16 (4): e1007617. https://doi.org/10.1371/journal.pcbi.1007617.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, et al. 2025. "DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning." arXiv. https://doi.org/10.48550/arXiv.2501.12948.

Edelman, B., & Skolnick, J. (2025). Valsci: An open-source, self-hostable literature review utility for automated large-batch scientific claim verification using large language models. *BMC Bioinformatics*, *26*(1), 140. https://doi.org/10.1186/s12859-025-06159-4

Fleiss, Joseph L., and Jacob Cohen. 1973. "The Equivalence of Weighted Kappa and the Intraclass Correlation Coefficient as Measures of Reliability." *Educational and Psychological Measurement* 33 (3): 613–19. https://doi.org/10.1177/001316447303300309.

Gao, Yunfan, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, Meng Wang, and Haofen Wang. 2024. "Retrieval-Augmented Generation for Large Language Models: A Survey." arXiv. https://doi.org/10.48550/arXiv.2312.10997.

Gopalakrishnan, Vishrawas, Kishlay Jha, Wei Jin, and Aidong Zhang. 2019. "A Survey on Literature Based Discovery Approaches in Biomedical Domain." *Journal of Biomedical Informatics* 93 (May):103141. https://doi.org/10.1016/j.jbi.2019.103141.

Gottweis, Juraj, Wei-Hung Weng, Alexander Daryin, Tao Tu, Anil Palepu, Petar Sirkovic, Artiom Myaskovsky, et al. 2025. "Towards an AI Co-Scientist." arXiv. https://doi.org/10.48550/arXiv.2502.18864.

Hristovski, Dimitar, Carol Friedman, Thomas C Rindflesch, and Borut Peterlin. 2006.

"Exploiting Semantic Relations for Literature-Based Discovery." *New York*, 349–53.

Hsieh, Cheng-Ping, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. 2024. "ÌRULER: What's the Real Context Size of Your Long-Context Language Models?"

Jin, Qiao, Bhuwan Dhingra, Zhengping Liu, William Cohen, and Xinghua Lu. 2019. "PubMedQA: A Dataset for Biomedical Research Question Answering." In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, edited by Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan, 2567–77. Hong Kong, China: Association for Computational Linguistics. https://doi.org/10.18653/v1/D19-1259.

Koo, T. K., & Li, M. Y. (2016). A Guideline of Selecting and Reporting Intraclass Correlation Coefficients for Reliability Research. *Journal of Chiropractic Medicine*, *15*(2), 155. https://doi.org/10.1016/j.jcm.2016.02.012

Kuusisto, Finn, John Steill, Zhaobin Kuang, James Thomson, David Page, and Ron Stewart. 2017. "A Simple Text Mining Approach for Ranking Pairwise Associations in Biomedical Applications." *AMIA Joint Summits Translational Science Proceedings* 2017 (July 26): 166–74. https://doi.org/10.48550/arXiv.1906.05255.

Lewis, Patrick, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, et al. 2021. "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks." arXiv. https://doi.org/10.48550/arXiv.2005.11401.

Maynez, Joshua, Shashi Narayan, Bernd Bohnet, and Ryan McDonald. 2020. "On Faithfulness and Factuality in Abstractive Summarization." In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, edited by Dan Jurafsky, Joyce Chai, Natalie Schluter, and Joel Tetreault, 1906–19. Online: Association for

Computational Linguistics. https://doi.org/10.18653/v1/2020.acl-main.173.

Millikin, Robert J., Kalpana Raja, John Steill, Cannon Lock, Xuancheng Tu, Ian Ross, Lam C.

Tsoi, et al. 2023. "Serial KinderMiner (SKiM) Discovers and Annotates Biomedical

Knowledge Using Co-Occurrence and Transformer Models." *BMC Bioinformatics* 24 (1):

412. https://doi.org/10.1186/s12859-023-05539-y.

Modarressi, Ali, Hanieh Deilamsalehy, Franck Dernoncourt, Trung Bui, Ryan A. Rossi,

Seunghyun Yoon, and Hinrich Schütze. 2025. "NoLiMa: Long-Context Evaluation

Beyond Literal Matching." arXiv. https://doi.org/10.48550/arXiv.2502.05167.

OpenAI, Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden

Low, et al. 2024. "OpenAI O1 System Card." arXiv.

https://doi.org/10.48550/arXiv.2412.16720.

Pham, Duy Khoa, and Bao Quoc Vo. 2024. "Towards Reliable Medical Question Answering:

Techniques and Challenges in Mitigating Hallucinations in Language Models." arXiv.

https://doi.org/10.48550/arXiv.2408.13808.

Preiss, Judita, and Mark Stevenson. 2017. "Quantifying and Filtering Knowledge Generated by

Literature Based Discovery." *BMC Bioinformatics* 18 (7): 249.

https://doi.org/10.1186/s12859-017-1641-9.

Pyysalo, Sampo, Simon Baker, Imran Ali, Stefan Haselwimmer, Tejas Shah, Andrew Young,

Yufan Guo, et al. 2019. "LION LBD: A Literature-Based Discovery System for Cancer

Biology." *Bioinformatics (Oxford, England)* 35 (9): 1553–61.

https://doi.org/10.1093/bioinformatics/bty845.

Rein, David, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien

Dirani, Julian Michael, and Samuel R. Bowman. 2023. "GPQA: A Graduate-Level

Google-Proof Q&A Benchmark." arXiv. https://doi.org/10.48550/arXiv.2311.12022.

Sayers, Eric W, Jeffrey Beck, Evan E Bolton, J Rodney Brister, Jessica Chan, Ryan Connor,

Michael Feldgarden, et al. 2025. "Database Resources of the National Center for

Biotechnology Information in 2025." *Nucleic Acids Research* 53 (D1): D20–29.

https://doi.org/10.1093/nar/gkae979.

Smalheiser, Neil R. 2017. "Rediscovering Don Swanson: The Past, Present and Future of

Literature-Based Discovery." *Journal of Data and Information Science (Warsaw,*

Poland) 2 (4): 43–64. https://doi.org/10.1515/jdis-2017-0019.

Sohn, Sunghwan, Donald C. Comeau, Won Kim, and W. John Wilbur. 2008. "Abbreviation

Definition Identification Based on Automatic Precision Estimates." *BMC Bioinformatics*

9 (1): 402. https://doi.org/10.1186/1471-2105-9-402.

Swanson, Don R. 1987. "Two Medical Literatures That Are Logically but Not Bib-

Liographically Connected." *Annals of the Rheumatic Diseases* 38 (4): 228–33.

Tonmoy, S. M. Towhidul Islam, S. M. Mehedi Zaman, Vinija Jain, Anku Rani, Vipula Rawte,

Aman Chadha, and Amitava Das. 2024. "A Comprehensive Survey of Hallucination

Mitigation Techniques in Large Language Models." arXiv.

https://doi.org/10.48550/arXiv.2401.01313.

Torvik, Vetle I., and Neil R. Smalheiser. 2007. "A Quantitative Model for Linking Two

Disparate Sets of Articles in MEDLINE." *Bioinformatics* 23 (13): 1658–65.

https://doi.org/10.1093/bioinformatics/btm161.

Tyagin, Ilya, Ankit Kulshrestha, Justin Sybrandt, Krish Matta, Michael Shtutman, and Ilya Safro.

2021. *Accelerating COVID-19 Research with Graph Mining and Transformer-Based*

Learning. *Proceedings of SIGKDD (CIKM'21)*. Vol. 1. Association for Computing

Machinery. http://arxiv.org/abs/2102.07631.

Tyagin, Ilya, and Ilya Safro. 2024. "Dyport: Dynamic Importance-Based Biomedical Hypothesis

Generation Benchmarking Technique." *BMC Bioinformatics* 25 (1).

https://doi.org/10.1186/s12859-024-05812-8.

Wei, Chih-Hsuan, Kyubum Lee, Robert Leaman, and Zhiyong Lu. 2019. "Biomedical Mention

Disambiguation Using a Deep Learning Approach." arXiv.

https://doi.org/10.48550/arXiv.1909.10416.

Wei, Jason, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi,

Quoc Le, and Denny Zhou. 2023. "Chain-of-Thought Prompting Elicits Reasoning in

Large Language Models." arXiv. https://doi.org/10.48550/arXiv.2201.11903.

Yu, Yue, Wei Ping, Zihan Liu, Boxin Wang, Jiaxuan You, Chao Zhang, Mohammad Shoeybi,

and Bryan Catanzaro. 2024. "RankRAG: Unifying Context Ranking with Retrieval-

Augmented Generation in LLMs." arXiv. https://doi.org/10.48550/arXiv.2407.02485.

Zhang, Y., Chen, X., Jin, B., Wang, S., Ji, S., Wang, W., & Han, J. (2024). A Comprehensive

Survey of Scientific Large Language Models and Their Applications in Scientific

Discovery. In Y. Al-Onaizan, M. Bansal, & Y.-N. Chen (Eds.), *Proceedings of the 2024*

Conference on Empirical Methods in Natural Language Processing (pp. 8783–8817).

Association for Computational Linguistics. https://doi.org/10.18653/v1/2024.emnlp-

main.498

Zhao, W. X., Zhou, K., Li, J., Tang, T., Wang, X., Hou, Y., Min, Y., Zhang, B., Zhang, J., Dong,

Z., Du, Y., Yang, C., Chen, Y., Chen, Z., Jiang, J., Ren, R., Li, Y., Tang, X., Liu, Z., …

Wen, J.-R. (2025). *A Survey of Large Language Models* (No. arXiv:2303.18223). arXiv.

https://doi.org/10.48550/arXiv.2303.18223