Compositionality of social gaze in the prefrontal-amygdala circuits

Guangyao Qi[1], Olga Dal Monte[1,2], Siqi Fan[1,3], Steve W. C. Chang[1,4,5,6]*

[1] Department of Psychology, Yale University, New Haven, CT 06520, USA.
[2] Department of Psychology, University of Turin, 10124 Torino, Italy.
[3] The Laboratory of Neural Systems, The Rockefeller University, New York, NY 10065, USA.
[4] Department of Neuroscience, Yale University School of Medicine, New Haven, CT 06510, USA.
[5] Kavli Institute for Neuroscience, Yale University School of Medicine, New Haven, CT 06510, USA.
[6] Wu Tsai Institute, Yale University, New Haven, CT 06510, USA.
*Correspondence: steve.chang@yale.edu

Summary

Each social gaze can be deconstructed into primitive components, including gaze content, social state, and gaze duration. To reduce dimensionality and facilitate generalization, the brain needs to represent primitive components in an abstract format. We examined the compositional aspects of social gaze primitives in the brain when macaques were engaged in real-life social gaze interaction. Interactive social gaze behavior was determined by how primitives were combined, rather than by their independent sums, providing evidence for behavioral compositionality. The amygdala and the anterior cingulate cortex represented content and state in an abstract format and orthogonally to one another, whereas the dorsomedial prefrontal and orbitofrontal cortices exhibited limited generalization. Linear mixed selective neurons facilitated the abstraction underlying generalization. The content and state information had distinct communicative patterns across the prefrontal-amygdala circuits to minimize interference, which was mediated by linear mixed selectivity neurons. Our findings provide the neural grammar supporting the compositionality of social gaze.

Keywords: Compositionality, social gaze, amygdala, anterior cingulate cortex, orbitofrontal cortex, dorsomedial prefrontal cortex, social interaction, naturalistic behavior

Introduction

In humans and nonhuman primates, social behaviors are powerfully guided by gaze dynamics of the interacting individuals [1–4]. In social gaze interaction, functionally unique components, or primitives, underlie each social gaze event, where different combinations of these gaze primitives produce drastically different functional meanings. Every social gaze event can be described with respect to multiple primitives, including the target of the social gaze ('content'), the level of social engagement in which the gaze takes place as a proxy to an internal state guiding these social gaze behaviors [5–7] ('state'), and the length of that gaze fixation ('duration'). These primitives can be functionally separable [8–10] and, importantly, may underlie the flexibility found in social gaze interaction. For example, briefly glancing at an object while disengaged may signal disinterest or distraction, whereas holding that same gaze at the object when highly engaged could indicate shared attention or an invitation to interact with that object [11,12]. Similarly, a quick look at the partner's face during high engagement may serve as a cue for turn-taking, while the same gaze during low engagement might be interpreted as a mere monitoring behavior [13,14]. Thus, the compositional nature of social gaze primitives may contribute to the complexity and richness of social gaze functions.

Compositional theories suggest that cognitive processes are built from shared components that can be flexibly recombined to generate a wide range of behaviors [15–19]. However, it remains elusive if and how the brain computes social gaze primitives to support potential compositional processing. More specifically, it remains unknown whether structured relationships in firing patterns, such as representational neural geometry, exist among these primitives that could support compositional processing.

Theoretical studies demonstrate that low-dimensional or abstract representational geometry supports good generalization but low separability, and high-dimensional representational geometry supports high separability but poor generalizability [20,21]. Importantly, compositional processes benefit from abstraction and orthogonal representations of primitives, as such representations can help reduce interference and enhance robustness to noise [16,22,23]. How might the brain represent social gaze primitives in an abstract format that reduces dimensionality and facilitates generalization? To realize flexible control of social gaze interaction, the relevant neural populations not only need to distinctively represent social gaze information, but also structure the firing patterns of the population of neurons across different primitives through abstraction [21], with the ultimate goal of communicating the relevant information across neural networks. From the perspective of neural representations of social gaze primitives, the trade-off between separability and generalizability is therefore critical.

Here we investigated the compositionality of social gaze by examining the neural representations of three specific social gaze primitives - gaze content, social state, and gaze duration - in the primate prefrontal-amygdala circuits during real-life social gaze interactions taking place between pairs of macaques [3,8,24]. We applied representational geometry analysis to test the generalization of social gaze primitives, tested the single-neuron basis of generalization, and examined the directional flow of the content and state information in the prefrontal-amygdala networks. Neural populations in the basolateral amygdala and the anterior cingulate gyrus orthogonally represented content and state in an abstract, generalizable, format and maintained their separability, whereas neurons in the dorsomedial prefrontal cortex and the orbitofrontal cortex exhibited limited generalization. At the single-neuron level, linear mixed selectivity cells facilitated the abstraction underlying the generalization. Finally, we found distinct routing of content and state information across the four brain regions. Together, our results reveal novel insights into how the brain represents social gaze primitives to support compositional computations for guiding social gaze interaction.

Results

Combinations of social gaze primitives determine interactive social gaze behavior

We hypothesized that the brain represents social gaze in a compositional manner. To test this hypothesis, we first decomposed social gaze into three specific gaze primitives: content (i.e., target of the gaze), state (i.e., social engagement level at the time of the gaze), and duration (i.e., duration of the gaze) (Fig. 1A). We then examined how neural populations in four distinct brain regions in the primate prefrontal-amygdala circuits – the basolateral amygdala (BLA), anterior cingulate gyrus (ACCg), orbitofrontal cortex (OFC), and dorsomedial prefrontal cortex (dmPFC) – represented these primitives during social gaze interaction (Fig. 1B). In the experimental setting (Fig. S1), pairs of macaques (M1 with neural recording, and M2 serving as partner monkeys) freely interacted with gaze without any imposed task constraints.

Over the course of a 40-min session in each day (8 runs, 5-min each), the frequency of gaze fixations on the face and the object robustly fluctuated over time (Fig. 1C1), likely signifying dynamic changes

in social engagement, which we use to operationally define 'social state'. Because social state is a covert, internal state that cannot be observed directly, we inferred it from overt behavior [25] by treating the moment-to-moment frequency of face- and object-directed gaze fixations as a behavioral proxy for the underlying level of social engagement. To quantify these fluctuations, we divided each 5-min run into three 100-sec segments resulting in a total of 24 segments per session. We then calculated normalized social gaze bouts as an index of social state for each segment (Fig. 1C2; Methods). We selected a 100-sec window because it offers the highest temporal resolution that still reliably captures social-state dynamics in the data, while ensuring each window contains at least one face-directed and one object-directed gaze bout for subsequent analyses. The 'high' and 'low' social states were then categorized based on whether the social state index (Methods) was higher or lower than each session's median social state index (Fig. 1C2). Notably, these classified states were not associated with pupil sizes (mean Fisher Z-transformed correlation = –0.0016; $P = 0.97$, one-sample t-test against zero; Fig. S2), suggesting that social engagement states do not simply index general arousal levels. Instead, these states may reflect a category of an internal state [25] that can vary independently from processes faithfully indexed by pupil dynamics [26,27]. Similarly, the 'high' and 'low' gaze durations were categorized as whether the gaze duration index of each gaze event was higher or lower than each session's median gaze duration index (Fig. S3A; Methods). Finally, the gaze content was determined by the target of each gaze event (Fig. S3B; face or object).

To examine behavioral correlates of compositionality in social gaze behavior, we asked how different combinations of gaze primitives of the recorded monkeys (M1) influenced the partner's (M2) social gaze behaviors. Here we hypothesized that M1's primitive components not only influence the partner's social gaze behavior, but also distinct combinations of these primitives have different influences on them. If so, these behavioral results will support the productivity aspects of compositionality.

To test these hypotheses, we applied a generalized linear mixed-effects model (GLMM) to predict the probability of M2's gaze to M1's face (M2's social gaze) based on different combinations of M1's social gaze primitives (Methods). This model included fixed effects for M1 content, M1 state, and M1 duration, as well as all possible two-way and three-way interactions among these primitives. We observed significant main effects of M1 content ($z = 6.47$, $P < 0.001$, Wald z-test) and M1 state ($z = 3.08$, $P = 0.002$) on the probability of M2's social gaze occurrence, while M1 duration alone exhibited a trend effect on this probability ($z = 1.20$, $P = 0.23$) (Fig. 1D). Crucially, in addition to the main effects, we observed significant interactions – there was a negative interaction between M1 state and M1 content ($z = –2.21$, $P = 0.027$), indicating that the combined effect of these two primitives was sublinear. Further, M1 content and M1 duration also showed a significant interaction ($z = –1.98$, $P = 0.048$), indicating that the influence of M1 content on M2's social gaze probability was modulated by the temporal characteristics of M1's fixation duration.

Predicted probabilities from the GLMM revealed that the partner monkeys (M2) were more likely to initiate social gaze (gaze to M1's face) when M1 was in a high social state ($P < 0.001$, Tukey-adjusted) and when M1 looked at M2's face ($P < 0.001$) (Fig. 1E, top panel). By contrast, the influence of M1 duration on M2's gaze behavior was not reliable ($P = 0.54$). Interaction analyses revealed that the combination of high M1 state and M1 face content did not further amplify M2's social gaze probability as expected under simple additivity (Fig. 1E, bottom panel). Specifically, when M1 was fixating on the object, M2 was more likely to look at M1 if M1 was in a high social state compared to a low social state ($P < 0.001$). However, when M1 was fixating on the face, M2's likelihood of looking at M1 did not differ between high and low social states of M1 ($P = 0.624$). Moreover, compared to M1's object-directed gaze, M1's face-directed gaze generally encouraged M2 to look at M1 (Fig. 1E, top left), but this increase in M2's social gaze was selective to when M1 was in a low state ($P < 0.001$ vs. $P = 0.282$ when M1 was in a high state; Fig. 1E, bottom left).

In a complementary analysis, we also examined how M1's social gaze primitives predicted M2's social state itself. Notably, M1's social state exhibited a significantly negative association with M2's social state ($z = -2.85$, $P = 0.004$, Wald z-test) (Fig. S4) such that when M1 looked at M2 more frequently (i.e., high M1 social state), M2 looked at M1 less often (low M2 social state), and vice versa. This finding aligns well with the tendency of rhesus macaques to observe each other's faces while avoiding excessive direct eye contact [3,28,29].

Taken together, these behavioral findings first demonstrate that social gaze behaviors are shaped by the compositional structure of social gaze primitives. Social state and gaze content play distinct roles in shaping the partner's social gaze behavior. Specifically, partner's social gaze behaviors were nonlinearly mapped to the combinations of social gaze primitives, supporting unique functional correlates with respect to how the social gaze primitives are combined.

Figure 1. Social gaze primitives combinatorially guide real-life social gaze interaction. (A) Social gaze primitives encompass gaze content (identifying the subject of the gaze), social state (indicating the level of social engagement), and gaze duration (measuring how long the gaze persists). **(B)** Social gaze interaction paradigm. Pairs of monkeys sat face-to-face while both their eye positions were tracked. The recorded monkey (M1) freely gazed at the partner monkey (M2) or the object. **(C)** Social state. C1

upper: two example 5-min runs showing high social engagement with an elevated rate of gaze to the partner's face over the object. C1 lower: two example runs showing low social engagement with an elevated rate of gaze to the object over the partner's face. C1 lower left: an example of how each run was divided into multiple segments. C2: (Left) Normalized social gaze (face) bouts fraction across runs and sessions. (Right) Social states across runs and sessions based on median separation. Each run was equally divided into 100-sec segments, and the normalized social bouts were calculated for each segment. The vertical color bars on the left of each heatmap indicates the recorded subject (M1) identity across sessions (red marks: sessions 1–13 and 16 from Monkey L; cyan marks: sessions 14–15 and 17–42 from Monkey K). **(D)** Fixed effects estimates from the generalized linear mixed-effects model (GLMM) predicting the occurrence of M2's social gaze based on M1's social gaze primitives and their compositions (Methods). Each point represents a fixed effect (log-odds estimate) with 95% confidence intervals. Asterisks indicate significance levels based on Type III Wald chi-square tests. The reference conditions for all predictors were defined as M1 state = Low, M1 content = Object, M1 duration = Short. **(E)** Predicted probabilities (back-transformed from the logit scale) of M2 social gaze as a function of M1 content, M1 state, M1 duration, and the compositions of these social gaze primitives. (Top three panels) Main effects for M1 content (Object vs. Face), M1 state (Low vs. High), and M1 duration (Short vs. Long). (Bottom two panels) Two-way interactions: M1 state × M1 content and M1 content × M1 duration. Predicted probabilities are shown by M1 state, separately by content (Object vs. Face). Vertical lines on the bars indicate 95% confidence intervals. Horizontal lines with asterisks denote significant pairwise differences. Significance was tested using pairwise Wald z-tests on marginal mean differences (Tukey-adjusted), which account for covariance; thus, significance may occur even when 95% confidence intervals overlap. * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$.

Neural coding of social gaze primitives in the prefrontal cortex and the amygdala supports the compositionality hypothesis

To test the neural encoding of each gaze primitive, we generated three hypothesized representational dissimilarity matrices (RDMs), in which each hypothesized RDM was orthogonal to the others (Fig. 2A). To examine the encoding of social gaze primitives in BLA, ACCg, dmPFC, and OFC in the RDM space (Fig. 2B), we generated the brain RDMs for each region by first averaging the firing rates of individual neurons within each gaze event condition (i.e., 8 combination conditions of gaze content, social state, and gaze duration; Methods) (Fig. 2C). We then computed pairwise Euclidean distances between condition-level population vectors across the eight conditions (Methods). After generating brain RDMs, we used a generalized linear model (GLM) (Fig. 2D) to test the encoding of social gaze primitive RDMs.

According to the encoding model, the gaze content was widely encoded in all tested neural populations (Fig. 2D). The social state information was encoded in BLA, ACCg, and dmPFC but the evidence of that was only weak in OFC (Fig. 2D). However, none of the four brain regions reliably represented gaze duration (Fig. 2D), even though the duration had interactive behavioral effects with the content and state (Fig. 1D). We found similar results with more strict regression analyses (Fig. S5). We will therefore focus on the representation of state and content in the four neural populations.

Figure 2. Encoding of social gaze primitives by the four neural populations in the prefrontal-amygdala circuits. (**A**) Three hypothesized representational dissimilarity matrices (RDMs) for testing the neural encoding of social gaze primitives. (**B**) An illustration of the four neural populations examined. ACCg, anterior cingulate gyrus; BLA, basolateral amygdala; dmPFC, dorsomedial prefrontal cortex; OFC, orbitofrontal cortex. (**C**) The neural RDM results from the recorded brain areas. (**D**) Encoding of the three social gaze primitives in the four neural populations based on the encoding GLM model (Methods). $* P < 0.05$; $** P < 0.01$; $*** P < 0.001$ with permutation test.

A neural ensemble can encode the social gaze primitives through a variety of representational formats. Here we focused on examining evidence in support of the compositional processing of social gaze by testing whether the representations of social gaze primitives are distinct from one another and if the primitives can support generalization across conditions [16,19]. Specifically, we tested three key predictions derived from the compositionality hypothesis [18,30–32] (Fig. 3A, Fig. S6): (*i*) that neural representations of social state and gaze content are distinct; (*ii*) that state and content are encoded along orthogonal axes; and (*iii*) that these representations generalize across conditions, such that state information can be used across different contents and content information can be used across different states. To test these predictions, we used a population decoding-based geometry analysis [33] of social states and gaze content (Fig. 3A).

All four tested brain areas could reliably decode both gaze content and social state (Fig. 3B). Although we methodologically decomposed the primitives in an orthogonal manner (Fig. 2A), the neural representations for the content and state may still be representationally shared in these neural

populations. To test if their neural representations are indeed not shared (prediction (*i*)), we applied a cross-primitives decoding analysis by training a linear gaze content decoder and testing it for social state, and vice versa (Fig. 3B; Methods). It was clear from this analysis that the decoder could not cross-decode different social gaze primitives. All the tested decoding accuracies were close to the chance level (Fig. 3B). The absence of cross-primitives decodability (test of prediction (*i*)) supports that gaze content and social state representations are not representationally shared.

Next, we tested the orthogonality between the neural representations of gaze content and social state (prediction (*ii*)) by performing a neural state space analysis [34] (Methods). For each brain region, condition-specific population vectors were derived from mean firing rates across four sub-conditions (high/low social state × face/object content). Two encoding axes – one for content and the other for state – were defined based on the average firing rate differences among relevant conditions. We then calculated the angle between these axes to quantify the degree of independence between the two representations. This orthogonality test directly quantifies the independence of the population codes for these two primitives, going beyond separability to test how distinct their encoding subspaces are. Only BLA and ACCg passed the orthogonality test (Fig. 3C; BLA: 84.94°, $P = 0.11$; ACCg: 87.70°, $P = 0.71$, permutation test). By contrast, dmPFC (68.79°, $P = 0.006$) and OFC (77.99°, $P = 0.025$) had less orthogonal representations. These results support that social state and gaze content representations are orthogonal and not shared in BLA and ACCg.

Finally, to examine whether the neural representation of state or content is structured in an abstract format and can be generalized to new conditions (prediction (*iii*)) (e.g., a linear decoder for state in face-directed events can be used in unseen object-directed events), we performed a cross-condition generalization analysis of social gaze primitives (Fig. 3A). To test for state generalization, we trained a state decoder in one content (looking at face or object) and tested the decoder performance in another untrained content (object or face, respectively). For content generalization, we trained a content decoder in one state (high or low social engagement) and tested the decoder in another untrained state (low or high, respectively). The average testing decoding accuracy was used to measure generalization ability.

Multidimensional scaling of the RDMs revealed that BLA represents social gaze primitives most abstractly compared to the other brain regions (Fig. 3D left panel). In these multidimensional scaling results, conditions that form more clearly separated and planar groupings suggest more abstract and lower-dimensional representations. BLA encoded both content and state in distinct low-dimensional subspaces (Fig. 3D left panel). By contrast, representations in ACCg, dmPFC, and OFC were less abstract, with less aligned subspaces for content or state (Fig. 3D left panel). The quantifications of the generalization results indicate that both BLA and ACCg could generalize gaze content and social state (i.e., high content and state generalization performance in Fig. 3D right panel), whereas dmPFC and OFC could only generalize social state and gaze content, respectively (i.e., high state-only or content-only generalization) (Fig. 3D right panel). Furthermore, the shattering dimensionality analysis, another way to measure the dimensionality of neural geometry [33], demonstrated that all four brain regions did not reduce their separability for each sub-condition (high state-face, low state-face, high state-object, low state-object) (Fig. 3D right panel). Taken together, BLA and ACCg represented gaze content and social state in an abstract format, maintaining their separability, while dmPFC and OFC were only able to generalize either social state or gaze content, but not both.

Figure 3. Tests of the three predictions from the compositionality hypothesis of social gaze in the prefrontal-amygdala circuits. (A) Schematic of a compositional encoding hypothesis, showing the three testable predictions. Neural population responses to four conditions (content/state: face/high, object/high, face/low, object/low) are distributed along orthogonal axes in neural state space. Color (orange = face, green = object) and fill (solid = high state, open = low state) distinguish the two dimensions. See Methods and Fig. S6 for more details on the three predictions from the hypothesis. **(B)** Cross-primitives decoding results. n.s., not significant; * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$ with permutation test. **(C)** Orthogonality tests between the content axis and state axis. Left: Angle between the gaze content coding axis and social state coding axis, estimated from condition differences

(Methods). Right: Projection of mean firing rates during the gaze period onto a two-dimensional neural subspace spanned by the first two components from PCA. The dots indicate four different gaze events: face/high (gaze to face in high social state), face/low (gaze to face in low social state), object/high (gaze to object in high social state), and object/low (gaze to object in low social state). **(D)** The neural geometry of social gaze primitives in BLA, ACCg, dmPFC, and OFC. Left, Multidimensional scaling (MDS) analysis derived from the brain RDMs (Fig. 2C). Large and small circles indicate long and short gaze duration, respectively. Orange and green circles indicate face and object gaze content, respectively. Filled and hollow circles indicate high and low states, respectively. Content planes are color-filled, whereas state planes are outlined in solid and dashed lines. Right, Cross-condition generalization performances of gaze content and social state, as well as the neural separability of any two conditions across four experimental conditions (content/state: face/high, face/low, object/high, and object/low). Content. gen.: content generalization. State. gen.: state generalization. Shattering dim.: shattering dimensionality. Error bar: shuffle data ± SD. n.s., not significant; Ⅰ $P < 0.1$; * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$ with permutation test.

Linear mixed selectivity neurons facilitate the generalization of social gaze primitives

Is there a relationship between single-neuron encoding and the population-level generalization of content and state? Previous work proposed that linear mixed selectivity neurons, whose activity reflects weighted combinations of multiple independent variables, may arise through abstraction and support generalization across conditions [35]. These neurons can preserve condition-relevant information in low-dimensional but in flexible formats, which makes them ideal for supporting transferable computations. Identifying such neurons in the prefrontal-amygdala populations that generalize both content and state could therefore reveal the single-neuron basis for compositional representations of social gaze. Because only BLA and ACCg generalized *both* social state and gaze content together, we hypothesized that neurons with linear mixed selectivity in these regions support content and state generalization. To determine single-neuron encoding schema, we combined a two-step modeling approach: a standard linear regression (FR ~ content + state) to assess main effects, followed by a comparison with a non-linear model including an interaction term (FR ~ content + state + content:state) to test for the interaction (Fig. 4A; Methods). We classified each neuron into having (*i*) pure content selectivity, (*ii*) pure state selectivity, (*iii*) linear mixed selectivity, or (*iv*) nonlinear mixed selectivity (Fig. 4B, one proportion Z test with 0.05, $P < 0.05$).

All four areas contained substantial proportions of pure content and pure state neurons (Fig. 4B-C; Fig. S7), consistent with their ability to decode both content and state (Fig. 3B). Consistent with our hypothesis, only BLA and ACCg exhibited a significant proportion of cells with linear mixed selectivity (Fig. 4B). To investigate whether linear mixed neurons specifically contribute to generalization, we compared the generalization ability for population when including versus excluding cells with linear mixed selectivity. Crucially, the cross-condition generalization performance for both gaze content and social state was significantly decreased in BLA and ACCg when removing the linear mixed selectivity cells (Fig. 4D), suggesting that linear mixed selectivity encoding in single cells facilitates the generalization of social gaze primitives.

Figure 4. Contributions of linear mixed selectivity neurons to the generalization of social gaze primitives. (A) Diagram of the single-neuron classification procedure for identifying cells with pure selectivity, linear mixed selectivity, and nonlinear mixed selectivity. **(B)** Neuronal classifications from the four populations in the prefrontal-amygdala circuits. * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$ with one proportion Z test with 0.05. **(C)** Three example cells in BLA showing pure content selectivity (left), pure state selectivity (middle), and linear mixed selectivity (right). The peri-stimulus time histograms (PSTHs) of these same three BLA cells are shown in the upper panel of Fig. S7. Horizontal brackets indicate significant main effects of either gaze content (face vs. object, purple) or social state (high vs. low, blue) based on linear regressions in **(A)**. Error bar: mean ± SEM. * $P < 0.05$; *** $P < 0.001$. **(D)** Generalization performance of gaze content and social state (n-matched population), with or without linear mixed selectivity cells. Error bar: shuffle data ± SD. Permutation tests were used for each column. Wilcoxon signed-rank tests were used to compare the columns. Ɨ $P < 0.1$; * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$.

Distinct communication subspaces are used for different social gaze primitives in the prefrontal-amygdala circuits

The results so far inform how the prefrontal cortex and amygdala support the compositionality of social gaze at the levels of single neurons and populations. Ultimately, the flow of information across multiple brain areas is critical for guiding social behavior. Here we thus asked how the representations of social gaze primitives are communicated among the four areas to support compositional principles. We hypothesized that the prefrontal-amygdala networks route distinct primitive components via separate communication subspaces to minimize information interference and enable flexible composition.

To test this hypothesis, we conducted a canonical correlation analysis (CCA) to identify correlations within a 'communication subspace' among the four brain regions as an index of neural communication [36–38]. Importantly, for examining content information communication, we aligned the content information but misaligned the state information for the tested pairs of regions, and vice versa for examining state information communication. The zero-lagged CCA analysis indicated that the content communication was relatively dynamic and gaze event-dependent, in which the content communication only emerged during and after gazing at the target content (Fig. 5A upper panel). In some pairs of areas (dmPFC-BLA and OFC-ACCg), this communication was exclusively present while the monkeys gazed at the target content. By contrast, the state communication, between BLA and dmPFC and also between BLA and ACCg, was consistent over time, emerging before each gaze event and continuing after gazing at the target content (face or object) (Fig. 5A lower panel).

We next determined the directionality of functional interactions with respect to content and state information. We performed CCA on each pair of time points using population neural firing rates from pairs of regions (Fig. S8, Fig. S9). If shared neural activity arises at different times across the pairs of regions, we expect to observe a systematic temporal offset. To measure the temporal offset, for each pair of brain regions, we assessed if correlations were stronger for negative or positive lags by calculating a directionality index, which was derived from the sum of correlation coefficients for lags of 200 msec relative to gazing at the target.

For the content information, dmPFC led OFC and BLA; OFC led ACCg and BLA; and ACCg led BLA (Fig. 5B upper panel). By contrast, for the state information, BLA led ACCg and dmPFC (Fig. 5B lower panel). Notably, after removing the linear mixed selectivity cells from these analyses, the functional connectivity between BLA and dmPFC no longer showed significant functional connectivity for the content communication and the directionality for the state communication disappeared (Fig. S10). These results support the critical role of linear mixed selectivity cells in facilitating the communications of social gaze primitives. Taken together, these results suggest that content information flows from dmPFC to BLA, whereas state information flows from BLA to both dmPFC and ACCg.

Figure 5. Functional connectivity and directional communication patterns of social gaze primitives in the prefrontal-amygdala circuits. (A) Dynamic functional connectivity in the prefrontal-amygdala circuits for gaze content (upper panel) and social state (lower panel) information, respectively, based on CCA. Gaze period: when the eye gaze is on the face or the object. Pre-gaze period: 200 msec before the eye gaze is on the face or the object. Post-gaze period: 200 msec after the eye gaze is on the face or the object. * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$ with permutation test. **(B)** Directionality of the content (upper panel) and the state (lower panel) information for each pair of brain regions based on CCA lags. Error bar: mean ± SEM. * $P < 0.05$; *** $P < 0.001$ with Wilcoxon signed-rank tests.

Discussion

From behavioral modeling, neural geometry analysis, and communication subspace analysis, we found multiple lines of evidence corroborating that social gaze encoding in the prefrontal-amygdala circuits follows a process akin to compositionality – that is, complex social signals are constructed from a set of simpler, reusable primitives, and crucially, different combinations of these primitives produce distinct meanings [31,39,40]. First, behavioral modeling demonstrated that social gaze behaviors emerge from the nonlinear interaction of the three primitives – gaze content, social state, and gaze duration jointly shaped the conspecific's social gaze behavior. For example, although both high social engagement and face-directed gaze increased social gaze probability, their joint effect was sub-additive,

and the influence of content varied depending on fixation duration. This demonstrates that the same primitives, when combined differently, yield different social meanings, consistent with the principle of compositional productivity [15,18]. This productivity, where slight variations in the combination of primitives (e.g., changing gaze content or social state) result in different behavioral interpretations, is a feature of compositional systems [18,41].

Primate social life demands rapid assembly of moment-to-moment gaze cues into coherent signals [2,42]. Our study decomposed these computations into three primitives and demonstrated that these primitives are not processed in isolation (Fig. 1D). Instead, social gaze interactions critically depended on specific nonlinear combinations of them. Face-directed gaze and high social engagement state each boosted the probability of social gaze, yet their joint impact was sub-additive (Fig. 1E). Further, the effect of face content itself varied with fixation duration (Fig. 1E). Mechanistically, the sub-additive interaction between social engagement state and face-directed gaze suggests a capacity limit or value normalization [43] in the receiver: that is, once a monkey is already highly socially engaged, an additional face-directed gaze adds little information, and vice versa. Such nonlinear interactions indicate that receivers interpret the combinatorial structure of social gaze primitives rather than relying on any single primitive in isolation. This is consistent with the principles of compositionality, where complex meaning emerges from the combination of simpler, meaningful parts [15,18]. Compositionality is a hallmark of human language, in which words and syntax combine to express infinite meanings [39,44]. Similar structure has also been observed in bonobo vocalization [30], where call combinations yield novel meanings, and in human facial expressions [45], where distinct facial signals combine to modulate the interpretations of speaker's intent. These parallel findings suggest that, like other communication systems, social gaze may also follow compositional principles, whereby the combination of distinct gaze primitives – such as gaze content, social state, and gaze duration –yields richer and more flexible meanings than any single feature alone.

Second, our study provides evidence that BLA and ACCg abstract social content and social state through a compositional manner (Fig. 2, Fig. 3). Based on the compositionality theory, three kinds of neural relationships between content representation and state representation were tested: (*i*) separability, (*ii*) orthogonality and (*iii*) generalizability. Prediction (*i*) is the minimal prerequisite: if the neural patterns for content and state were identical, a compositional code could not exist. Prediction (*ii*) strengthens this claim: orthogonality is a stricter form of distinctness—orthogonal axes are always distinct, whereas distinct axes are not necessarily orthogonal. Additionally, prediction (*iii*) does not strictly rely on perfect orthogonality, but cross-condition decoding is more robust when the axes approach orthogonality, because it demonstrates the reusable nature of the primitive components across different conditions. Our results suggest that only BLA and ACCg passed all the three predictions. This supports the theoretical prediction that compositional representations require distinct, abstract encodings of primitives that can flexibly generalize across novel combinations [15–17,19].

Both content and state signals were widely implemented in BLA, ACCg, dmPFC, and OFC, whereas gaze duration signals were largely absent. Importantly, only BLA and ACCg mapped the content and state onto nearly orthogonal axes and maintained that separation across conditions. Supporting this view, ACCg neurons have been shown to represent social identity even when it is task-irrelevant, consistent with context-independent social coding [46]. These results are well aligned with the predictions from the compositionality hypothesis [18,30–32]. Linear classifiers trained on one content generalized state to a novel content, and vice-versa, only in these two regions, revealing an abstract, reusable code for both primitives. This orthogonal, generalizable structure is a key signature of factorized representations, where different variables are encoded along independent neural dimensions [47]. Such factorization allows the brain to recombine previous representations in new conditions and therefore supports the generative capacity required for compositional systems. Our findings suggest

that BLA and ACCg provide a neural substrate for factorized representation of social gaze primitives, enabling efficient abstraction and reuse of gaze content and social state across varied social scenarios. Furthermore, these findings align with broader theories of cognitive maps, which suggest that the brain encodes diverse information, such as space, value, and social context, using structured, abstract representations that support generalization. Similar principles have been observed in the hippocampus, where neurons form reusable value maps [48] and represent individual and group identity across modalities [49]. Our results suggest that the prefrontal–amygdala circuits may use comparable compositional strategies to guide social gaze.

Third, single-cell analysis uncovered an enrichment of linear mixed selectivity neurons in BLA and ACCg (Fig. 4). This aligns with computational models in which mixed selectivity neurons create high-dimensional, conjunctive representations that preserve the identity of individual primitives while enabling flexible binding, a mechanism essential for compositional encoding [50,51]. Consistent with theories suggesting that such cells expand representational dimensionality while preserving abstraction [35], removing these cells abolished cross-condition generalization in both regions (Fig. 4). Thus, mixed selectivity neurons appear to provide the combinatorial "glue" that binds distinct primitives without letting them interfere. On the other hand, dmPFC and OFC exhibited more limited codes. Both dmPFC and OFC retained the ability to generalize along one dimension – dmPFC for state and OFC for content even though neither region contained a significant proportion of linear mixed-selectivity neurons with respect to the three social gaze primitives. In dmPFC and OFC, the generalization persisted even after removing the few linear mixed selectivity neurons that were present, suggesting that generalization is not solely driven by linear mixed selectivity. Other mechanisms may contribute, such as structured population dynamics that support context-dependent coding [52], or projection-specific population codes, where distinct subpopulations encode different variables depending on their downstream targets [20]. Although dmPFC generalized state but not content, it has previously been linked to abstract representations of agent identity [53], suggesting that the coding scheme of dmPFC may be highly context-dependent. Overall, these findings suggest a division of labor in which BLA and ACCg supply a compositional scaffold that other areas tap into selectively. By demonstrating that BLA and ACCg encode social gaze primitives in an orthogonal, generalizable format that leverages linear mixed selectivity, our work reveals a neural grammar that can recombine different social gaze primitives into many social messages. Similar compositional logics may underlie more complex social signals, and their breakdown could help explain social-cognitive dysfunction [54,55].

Fourth, content and state information were routed through distinct prefrontal–amygdala channels, providing these associative brain regions a flexible code for social gaze interaction. Communication subspace analysis revealed that content and state are transmitted through separate, time-resolved prefrontal–amygdala pathways: state signals flowed early from the amygdala to the prefrontal cortex, while content signals emerged later and flowed in the reverse direction (Fig. 5). Therefore, the prefrontal–amygdala circuits do not broadcast a single, undifferentiated "gaze signal". Instead, this anatomically and temporally segregated routing may reflect a neural implementation of compositional structure, where distinct primitives are independently processed and dynamically recombined to support context-dependent social communication [57]. Additionally, linear mixed selectivity neurons facilitated the communications of content and state information. While our task did not isolate communicative intent, the presence of compositional signatures in spontaneous gaze behavior suggests that this framework may capture core principles of social signal construction, regardless of whether the gaze is explicitly communicative.

State-related population activity was shared early and persistently between BLA ↔ dmPFC and BLA ↔ ACCg, emerging before the animal fixates the target and persisting thereafter (Fig. 5A). By contrast, content-related activity was exchanged later and only during or after the target was viewed.

Moreover, content coupling between dmPFC and BLA and between OFC and ACCg faded once the fixation has ended. This finding is consistent with the notion that state information has a longer timescale, whereas content information is deployed on demand for the actual act of looking at a shorter timescale. Furthermore, lagged CCA informed the communication directions of gaze content and social state (Fig. 5B). For state communication, information flowed from BLA to dmPFC and ACCg. However, for content communication, the stream reversed: dmPFC and OFC led both BLA and ACCg, with ACCg leading BLA. Notably, removing linear mixed selectivity neurons eliminated dmPFC–BLA coupling for content and also abolished BLA's leading role for state communication, implicating these cells as the key components for transmitting primitives from one area to another (Fig. S10). Our results point to a clear division of labor, in which BLA broadcasts a running signal about how socially engaged the animal is, while dmPFC and OFC provide detailed information about what the animal is looking at, perhaps as a feedback-like process. These directional, primitive-specific routings provide a neural network basis for flexibly recombining gaze primitives as social context unfolds.

It is worth noting some limitations of our work. While gaze duration was included as a third primitive, its contribution differed from content and state in both behavior and neural coding. Behaviorally, longer fixations modestly increased the likelihood of the partner's social gaze, and only with respect to its interaction with content (Fig. 1E): face-directed gazes had extra influence when their gaze durations were short, whereas object-directed gazes mattered more when they were sustained. This crossover effect hints that duration may function as a gain control – prolonged looks may amplify otherwise low-salience cues (objects), whereas short, rapid looks may prevent face cues from saturating the receiver's response system. None of the four regions showed reliable encoding of duration once content and state were accounted for (Fig. 2). One possibility is that temporal integration occurs elsewhere such as in the superior temporal or parietal cortices that accumulate evidence over hundreds of milliseconds [58–60] (but see [61]).

Additionally, unlike human language, which has rich context to test the productivity aspect of compositionality [18,31], we assessed only two dimensions of interpretation: the probability of partners' social gaze and their social state in response to different combinations of social gaze. While this provides a first step, it does not fully capture the generative capacity of social gaze signals. Furthermore, because our task did not require explicit communication or cooperation between individuals, the observed gaze patterns may reflect attentional dynamics rather than communicative intent. In this light, not all gaze events are likely to be communicative; many may serve perceptual or exploratory functions. Those that do carry communicative intent may rely on a distinct set of organizing principles, potentially involving a more constrained set of gaze components but greater flexibility in their timing and transitions. Future studies could investigate whether gaze encoding and its compositional structure change in contexts that demand joint action or intentional singling [62,63]. Such paradigms would be especially informative for testing whether social gaze representations are related to higher-order social cognitive functions such as theory of mind, the ability to infer others' mental states from gaze and context [64]. Finally, the gaze primitives identified here may not have fixed meanings on their own. Instead, their meaning may come from how they change and interact over time. This suggests that the 'grammar' of social gaze could be dynamic, like tone of voice [30] or gesture [65], where meaning depends on the flow and timing of signals, not just their individual features.

Accumulating evidence supports that social information is widely represented in the primate brain [8,66–70], with behavioral variables related to social gaze interaction encoded across multiple neural networks [8,9,71–76]. Future work should explore how compositional processes extend to a broader range of social, behavioral, and emotional responses—including facial expressions [45,77,78], gestures [65], and homeostatic responses such as body temperature or heart rate [79,80], and how primitives from different behavioral domains may combine to generate complex and rich social behaviors.

Methods

Experimental Procedures

Animals and behavioral task procedures

A total of five rhesus macaques (*Macaca mulatta*) were involved in the study. Neural data were collected from two adult males (M1; Monkey L: 8 years, 15.7 kg; Monkey K: 7 years, 10 kg). The recorded animals (M1) interacted with three partner animals (M2) (four males and one female; Monkeys C, H, E, L; ages 7–8 years), resulting in six distinct social dyads (L–C, L–H, L–E, K–L, K–H, K–E). All monkeys were unrelated, housed in the same colony, and maintained on a 12-hr light/dark cycle with unrestricted food access and controlled fluid access during testing. Procedures adhered to NIH guidelines and were approved by Yale Institutional Animal Care and Use Committee and in compliance with the National Institutes of Health Guide for the Care and Use of Laboratory Animals. No animals were excluded from our analyses.

On each recording session (day), M1 and M2 sat in primate chairs (Precision Engineering, Inc.), 100 cm apart, facing each other (Fig. S1). Eye positions and pupil size were recorded simultaneously from all M1 and M2 monkeys using EyeLink 1000 cameras (SR Research). A standard 5-point screen calibration plus a custom face calibration (using LED markers for eyes, mouth, and face using the face calibration board by the faces of the conspecifics involved; Fig. S1) [8,24] were performed before each session, controlled by Psychtoolbox [81] and EyeLink toolbox [82] in MATLAB (MathWorks). Nonsocial objects (monkey toys) were placed on the M1's side (Fig. 1B). In a given session, two monkeys spontaneously interacted with gaze in 8-10 consecutive 5-min runs, with a no-vision break between every run (3-min on average) in which they had no visual access to one another. During each social interaction run, middle monitors separating the monkeys were lowered via a remote control, allowing spontaneous face-to-face gaze interactions. During each no-vision break, the middle monitors were raised remotely to block the visual access to one another (Fig. S1). Since some days had only 8 runs, we included the data from the first 8 runs from each day to ensure consistency in data analysis, resulting in a total of 42 sessions (Monkey L: 14 sessions, sessions 1-13, 16; Monkey K: 28 sessions, sessions 14, 15, 17-42) (Fig.1C2).

Electrophysiological data collection

Each M1 (recorded monkey) was implanted with a headpost and a recording chamber targeting BLA, dmPFC (Brodmann 8Bm, F6), ACCg (32, 24a, 24b), and OFC (11, 13m) [83]. MRI and stereotaxic coordinates guided the chamber placements. Single-unit activity was recorded using 16-channel axial array electrodes (U- or V-Probes, Plexon) using a 64-channel Plexon system. Electrodes were lowered via a motorized microdrive (NaN Instruments) through guide tubes, and recordings began after a 30-minute settling period. Signals were band-pass filtered (250 Hz–8 kHz), digitized at 40 kHz using a Plexon OmniPlex system, and spike-sorted using MountainSort [84]. In total, we recorded 537 BLA, 236 ACCg, 187 dmPFC, and 241 OFC units across both monkeys (monkey L and monkey K: 225 and 312 BLA cells, 109 and 127 ACCg cells, 92 and 95 dmPFC cells, and 102 and 139 OFC cells, respectively) [8].

Behavioral Data Analysis

Social gaze primitives

To study the subcomponents of social gaze, we decomposed social gaze into three primitives for a given gaze bout: gaze content, social state, and gaze duration (Fig. 1A). Each gaze event was defined as when M1 looked at M2's face (face bout) or object (object bout). From each day's calibration, the face region of interest (ROI) was defined by the four corners of a monkey's face, with the object ROI having the same surface area as the face ROI. Fixations were identified using EyeMMV toolbox [85] implemented in MATLAB. We detected fixations using spatial and duration parameters. Specifically, we used t1 = 1.18 and t2 = 0.59 degrees of visual angle for the spatial tolerances, and a minimum continuous duration of 70 msec.

For each gaze bout, social states were defined as each monkey exhibiting either high social engagement (high) or low social engagement (low). This analysis was done for each M1 separately (Fig.1C2). The high social engagement was operationally defined as M1 being more likely to look at M2's face relative to the object, while the low social engagement was defined as M1 being more likely to look at the object relative to M2's face. To calculate the social states at a resolution for capturing natural fluctuations, we first divided each of the eight 5-min runs into three segments (100-sec each) (Fig. 1C1). We selected 100-sec segments as it provided the highest temporal resolution while still reliably capturing state-like dynamics. For each segment, we calculated the social state index as the normalized fraction of face bouts as:

$$Social\ state\ index\ =\ (face\ bouts)/(face\ bouts + object\ bouts), \quad\quad (1)$$

where face bouts and object bouts were defined as the number of face and object bouts during each segment, respectively (Eq. 1). To categorize social state as a binary variable for further analysis, each segment was labeled as either having a high or a low state depending on whether the social state index was above or below the median value of these indices within that session. Similarly, for the gaze duration, each gaze bout was labeled as either having a long or a short duration depending on whether its duration was above or below the median value of the gaze durations within that session. Finally, the gaze content reflected whether the monkeys were looking at the partner's face or the nonsocial object.

Pupil size

To examine the relationship between pupil size and social engagement state, we computed the Pearson correlation between pupil size and the social state index. Pupil size was recorded from the monkeys using EyeLink 1000 cameras (EyeLink 1000, SR Research). Pupil size data were min-max normalized with a [0, 1] range using a 100-Hz sampling rate. To align with the segment structure used for defining state variables, we examined the mean pupil size from each segment.

General linear mixed-effects modeling of M2's social gaze

To test how different M1's social gaze primitives and their combinations influence M2's social gaze behavior, we modeled the likelihood of M2's social gaze using a generalized linear mixed-effects model (GLMM) with a binomial distribution and logit link function, implemented using the `lme4` package in R (Eq. 2). Fixed effects included M1 content (Content), M1 state (State), and M1 duration (Duration), as well as all their two-way and three-way interactions. Random intercepts were included for session, M1 identity, and M2 identity, to account for repeated measurements and the hierarchical structure of the data. The model was defined as:

$$logit(Pr(Y_{ijk} = 1))\ =\ \beta_0 + \beta_1 Content_{ijk} + \beta_2 State_{ijk} + \beta_3 Duration_{ijk} +$$
$$\beta_4 State_{ijk} Content_{ijk} + \beta_5 State_{ijk} Duration_{ijk} + \beta_6 Content_{ijk} Duration_{ijk} +$$

$$\beta_7 State_{ijk} Content_{ijk} Duration_{ijk} + u_i + v_j + w_k \qquad (2)$$

where Y_{ijk} denotes the binary outcome of M2's social gaze (1 means M2 gazed at M1's face within 1 sec after M1's gaze event ended; 0 means M2 did not gaze at M1's face within 1 sec after M1's gaze event ended) for an observation made on session i, with M1 participant j and M2 participant k; and u_i, v_j, $w_k \sim N(0, \sigma^2)$ represent random intercepts for sessions, M1, and M2, respectively.

Fixed effects were evaluated using Type III Wald chi-square tests via the 'car' package in R. Post hoc pairwise comparisons were conducted on the estimated marginal means (EMMs) using the 'emmeans' package in R. Wald z-tests were applied to test the significance of the estimated differences between conditions. Importantly, the standard errors of these differences account for the covariance structure of the mixed-effects model, including random effects. Multiple comparisons were corrected using the Tukey HSD adjustment. Notably, the reported 95% confidence intervals for marginal means represent uncertainty around the group-level predictions, whereas the significance tests rely on the precision of the estimated differences; thus, statistical significance may be detected even when confidence intervals overlap visually.

In a complementary analysis, we performed an additional GLMM to assess how M1's social gaze primitives influenced M2's social state. The M2's social state was defined using the same methods as previously described for M1. Because M2 did not have a physical object, however, we used the matching area corresponding to M1's object zone from M2's perspective as the nonsocial reference region. The same fixed and random effect structure was used, with the binary outcome defined as whether M2 was in a high versus low social engagement state within a 100-sec window following M1's gaze event.

Neural Data Analysis

Preprocessing of single-unit data

To estimate continuous time-dependent firing rates, timestamps of spiking events were resampled at 1 KHz and converted into binary spikes. Spike trains were then convolved with a symmetric Hann kernel (sample rate: 100 Hz; kernel width: 0.3 sec) in MATLAB. The resulting firing rates were then min–max normalized to the [0, 1] range. The peri-stimulus time histograms (PSTHs) were then calculated for three periods of interest around each gaze bout: (i) the pre-gaze period (200 msec before the gaze event to the face or object), (ii) the gaze period (during the gaze event), (iii) the post-gaze period (200 msec after the end of the gaze event). We used the averaged firing rate during these three periods for further analysis.

Encoding model of representational dissimilarity matrix (RDM)

To investigate how social gaze primitives are encoded by the four neural populations, we applied a general linear model (GLM) to characterize the representational structure of neural population activity during each gaze event (i.e., gaze period). We examined whether three primitives – gaze content, social state, and gaze duration – could explain neural dissimilarity patterns across conditions (see below). Each of these primitives was represented as a representational dissimilarity matrix (RDM), resulting in three hypothetical RDMs that were predictors in the regression analysis (Fig. 2A).

To construct the RDMs of each brain region, we began by categorizing each gaze event according to the three primitives, yielding eight unique event conditions ([content/state/duration]: face/high/long, object/high/long, face/high/short, object/high/short, face/low/long, object/low/long, face/low/short, and object/low/short). For each neuron, we computed its average firing rate in the gaze period on a gaze event-by-gaze event basis. These averaged firing rates were saved in a 3D array, with dimensions corresponding to neuron, condition, and gaze event number. Neural activity was analyzed separately for each brain region of interest (ROI), including BLA, ACCg, dmPFC, and OFC. To generate a neural RDM for each brain region, we first averaged each neuron's firing rate across all gaze events within each condition, resulting in one condition-level population vector per ROI. Pairwise Euclidean distances were then computed between these eight vectors to form an 8×8 neural RDM. These dissimilarity matrices were normalized to a [0, 1] range. These neural RDMs were used to visualize the representational geometry of each brain area by projecting them onto the first three dimensions using multidimensional scaling (MDS) (Fig. 3D).

To evaluate the contribution of each primitive, we applied multiple linear regression. The upper triangular values (excluding the diagonal) of the neural RDM were vectorized and used as the dependent variable. The three hypothetical model RDMs (for content, state, and duration) (Fig. 2A) were also vectorized as independent variables. The regression model was specified as (Eq. 3):

$$RDM_{brain} = \beta_0 + \beta_1 RDM_{content} + \beta_2 RDM_{state} + \beta_3 RDM_{duration} \tag{3}$$

We used ordinary least squares regression to estimate the beta coefficients, allowing us to quantify how strongly each variable contributed to the neural dissimilarity structure during the gaze time window.

To assess statistical significance, we conducted a permutation-based shuffle analysis. For each brain region, the condition labels in the neural data were randomly shuffled 1,000 times while keeping the structure of the hypothetical RDMs fixed. For each shuffled dataset, we recomputed the neural RDM and re-ran the GLM, generating null distributions of the regression coefficients. We then compared the observed coefficients from the unshuffled data to these null distributions and computed two-tailed empirical p-values as (Eq. 4):

$$p = \frac{(number\ of\ shuffled\ coefficients \geq |observed\ coefficients|)}{(number\ of\ shuffles)} \tag{4}$$

Population decoding analyses

Content decoding

For population decoding of content, we used linear Support Vector Machine (SVM) classifiers implemented from the scikit-learn toolbox [86]. All the recorded neurons were included, regardless of their content selectivity. The classifiers were trained to distinguish between face and object content using neural population activity recorded during individual gaze events from each brain area, treating each event as an observation for decoding. To construct a pseudo-population, data from all recording sessions were pooled, and only neurons with more than 10 gaze events for each content condition were included. A 5-fold cross-validation was used, where the dataset was randomly divided into five subsets, with the classifier trained on four subsets and tested on the remaining one subset. This was repeated

five times to calculate average decoding accuracy. The entire cross-validation procedure was repeated 1,000 times, and the final decoding accuracy was computed as the mean across all repetitions. Statistical significance was assessed by comparing this mean accuracy to a null distribution generated from label-shuffled data. Decoding was considered significant if the mean accuracy exceeded the 95th percentile of the null distribution.

State decoding

Neurons with more than 10 gaze events in each state group (high and low state groups, same as for the content decoding analysis described above) were selected for the state decoding. The decoding procedure was the same as described for the content decoding procedure, except that the gaze events were sorted and labeled by high and low state groups. Statistical significance was assessed by comparing this mean accuracy to a null distribution generated from label-shuffled data. Decoding was considered significant if the mean accuracy exceeded the 95th percentile of the null distribution.

Cross-primitives decoding

To assess whether the neural representation of content is shared with state, we performed cross-primitives decoding (Fig. S6B). If the representations of these variables are not shared (see below for the additional orthogonality test), we expect the cross-primitives decoding to be poor. Specifically, we trained a linear SVM classifier to decode content (face vs. object) using only gaze events labeled by content and then tested the classifier's ability to decode state (high vs. low) using the state-labeled gaze events, and vice versa. All procedures were the same as those described for the content and state decoding analyses. A 5-fold cross-validation approach was used, repeated 1,000 times. Only neurons with at least 10 gaze events in each relevant condition were included. Statistical significance was determined by comparing the observed decoding accuracy to a null distribution generated from label-shuffled data, with decoding considered significant if accuracy exceeded the 95th percentile of the null distribution.

Cross-conditions decoding

To examine whether the neural representation of state or content is structured in an abstract format and can be generalized to new conditions (e.g., a linear decoder for state in face-directed events can be used in unseen object-directed events), we performed a cross-condition generalization analysis of social gaze primitives (distinct from the cross-primitives decoding described before) (Fig. S6D). The procedure followed the same approach as described for the content and state decoding analyses, using linear SVM classifiers with 5-fold cross-validation repeated 1,000 times. For each neuron, we trained the classifier to decode one variable (e.g., content: face vs. object) using neural activity from single gaze events that occurred under one condition (e.g., high state) and tested the classifier on gaze events for the other condition (e.g., low state). The average decoding accuracy across both state conditions (i.e., training on high state and testing on low state, and vice versa) was defined as the content generalization performance. The same procedure was used to compute state generalization performance across content conditions (i.e., training on face and testing on object, and vice versa). Only neurons with more than 10 gaze events in each relevant condition were included. Statistical significance was assessed by comparing decoding accuracy to a null distribution generated from label-shuffled data, with significance determined by exceeding the 95th percentile of the null distribution.

Neural state space analysis

To test the orthogonality between content and state information representations, we computed condition-specific population vectors and quantified the geometry of their representational structure using neural state space analyses (Fig. S6C) [33]. Neural spiking data were organized as a 3D matrix of shape (neurons × conditions × gaze events), with four sub-conditions defined by a 2×2 factorial design: content (face vs. object) and state (high vs. low). For each neuron and condition, the mean firing rate was computed for different gaze events, yielding four condition-specific population activity vectors per region (content/state): face/high, object/high, face/low, and object/low. Two encoding axes were defined to represent neural selectivity for content and social state. The content axis was defined as the mean firing rate difference between face and object conditions, averaged across state levels (Eq. 5):

$$Content\ axis\ =\ \frac{(Fr_{face\_high}-Fr_{object\_high})+(Fr_{face\_low}-Fr_{object\_low})}{2} \tag{5}$$

The state axis was defined as the mean firing rate difference between high and low state conditions, averaged across content levels (Eq. 6):

$$State\ axis\ =\ \frac{(Fr_{face\_high}-Fr_{face\_low})+(Fr_{object\_high}-Fr_{object\_low})}{2} \tag{6}$$

The angle between these axes was calculated using subspace angles from the SciPy library, which computes the principal angle between subspaces. The resulting angle (in degrees) quantifies the degree of independence between content and state representations within the neural population. To assess the statistical significance of the observed angle, a permutation test (1,000 iterations) was used. On each iteration, condition labels were randomly permuted across conditions within each neuron. The content and state axes were then re-estimated, and the angle between them was calculated. The permutation p-value was defined as the proportion of iterations in which the permuted angle was smaller than or equal to the observed angle.

To visualize the structure of neural representations in a reduced dimensional space, principal component analysis (PCA) was applied to the matrix of condition vectors after mean-centering across conditions. The first two principal components were used to project the condition vectors and the content/state axes. Projected content and state vectors were normalized to unit length and plotted as arrows originating from the origin.

Shattering dimensionality analysis

To examine the neural separability among four kinds of gaze events or sub-conditions (face gaze in high state, object gaze in high state, face gaze in low state, and object gaze in low state), we conducted a decoding-based shattering dimensionality (SD) analysis [38]. For each combination of two kinds of gaze events (in total six combinations from four sub-conditions), the decoding procedure followed the same approach as described for the content and state decoding analyses, using linear SVM classifiers with 5-fold cross-validation repeated 1,000 times. The averaged accuracy from six decoding procedures was reported as SD. The larger value means that sub-conditions in that brain region are more separable. Statistical significance was assessed by comparing decoding accuracy to a null distribution generated from label-shuffled data by the same decoding procedure, with significance determined by exceeding the 95th percentile of the null distribution.

Single-cell classification

To determine the content or state selectivity of individual cells (Fig. 4A), we first performed a linear regression on averaged firing rates during gaze time using the model (FR ~ content + state) for each cell, testing for main effects of content and state (Fig. 4A). Duration was not included because the encoding model (Eq. 3) confirmed that it cannot be significantly represented in all four brain areas. Based on the resulting p-values, neurons were classified into different categories.

If p(content) < 0.05 and p(state) ≥ 0.05, the neuron was classified as a pure content-selective cell. If p(state) < 0.05 and p(content) ≥ 0.05, the neuron was classified as a pure state-selective cell. If both p(content) < 0.05 and p(state) < 0.05, the neuron was classified as a candidate mixed selectivity cell. To further distinguish between linear and non-linear forms of mixed selectivity, we compared the initial linear regression model to an extended regression model that included the interaction term using a nested model comparison approach. Cells with significant interaction effects (p(interaction) < 0.05) were designated as having non-linear mixed selectivity. Cells without a significant interaction effect (p(interaction) ≥ 0.05) were classified as showing linear mixed selectivity. This procedure resulted in four categories:

> (i) Pure content selectivity: significant main effect of content only.
> (ii) Pure state selectivity: significant main effect of state only.
> (iii) Linear mixed selectivity: significant main effects of both state and content, but no significant interaction.
> (iv) Non-linear mixed selectivity: significant interaction between state and content.

Canonical Correlation Analysis (CCA)

To test how content and state information flowed through the prefrontal-amygdala circuit, we applied canonical correlation analysis (CCA) [86] to examine the relationships between population activity in BLA, ACCg, dmPFC, and OFC. First, spiking activity from any two brain regions was aligned based on matching behavioral conditions – specifically, face vs. object for content information communication, and high vs. low state for state information communication. For content information analysis, trials were aligned such that face events in one region corresponded to face events in the other region, and similarly for object events; however, state information was not aligned. Conversely, for state information analysis, high and low state trials were aligned across regions, while content (face vs. object) was not aligned. We then performed a PCA across gaze events to reduce the dimensionality and to obtain the first 10 PCs for each brain region. The gaze events were then divided into 5 equal parts (training set and testing set) for cross-validation (5-fold cross-validation). The PCs of the training set of each brain region were used to perform canonical correlation analysis (CCA) to obtain the first pair of canonical correlation components (L2 regularization, λ=0.5). The PCs of the testing set from each brain region were then projected onto the first pair of canonical correlation components, and the correlation was determined by the Pearson correlation coefficient between these projections from each region. This analysis was performed for each pair of three periods (pre-gaze, gaze, and post-gaze) to generate a 3x3 cross-validated correlation coefficient matrix (Figs. S8-S9). For each iteration, 50 gaze events per condition (i.e., face and object gaze events for content communication; high and low state gaze events for state communication) were randomly selected from each brain region using bootstrapping. This process was repeated 1,000 times, and the resulting correlation matrices were averaged to produce the final heatmap. To test the functional connectivity between each pair of brain areas, gaze event labels within each region were independently shuffled to disrupt the condition alignment between regions. The correlation analysis described above was then repeated 1,000 times to generate a null distribution. Functional connectivity between two regions was considered significant if the mean Pearson correlation coefficient exceeded the 95th percentile of the null distribution.

To quantify the lead-lag relationship in information exchange between brain regions, we computed a directionality index defined as (Eq. 7):

$$Directionality\ index = (\rho_- - \rho_+)/(\rho_- + \rho_+),\qquad\qquad(7)$$

where ρ_- and ρ_+ denote the sum of min-max normalized correlation coefficients at negative and positive time lags, respectively [87]. A positive index (from region A to region B) indicates that region A leads the region B in directional information flow, whereas a negative index suggests that region B leads region A. To assess statistical significance, we tested whether the directionality index of each pair of brain areas is significantly different from 0 with a Wilcoxon signed-rank test.

General notes on statistics

Overall, all statistical analyses were performed using MATLAB (MathWorks), Python (scikit-learn, statsmodels), and R (lme4, car, emmeans). Two-tailed tests were used unless otherwise noted. Significance thresholds were set at $p < 0.05$. Permutation testing was used to assess significance for model fits and decoding performance. For each test, 1,000 permutations were performed to generate null distributions, and empirical p-values were calculated accordingly. Cross-validation procedures and data shuffling methods are described in detail above in the respective sections.

Resource Availability

Behavioral and neural data presented in this paper and the analysis codes will be available through https://github.com/changlabneuro/social_gaze_compositionality upon acceptance of the manuscript.

Acknowledgments

This work was supported by the National Institute of Mental Health (R01MH110750, R01MH120081, R01MH128190). We are extremely grateful to Ilker Yildirim and Sylvia Blackmore for providing helpful feedback about this work and on the manuscript.

Author contributions

G.Q. and S.W.C.C. conceptualized the study, O.D.M. and S.F. collected the data, and G.Q. and S.W.C.C. analyzed and wrote the original manuscript. All the authors contributed to reviewing and editing the manuscript.

Declaration of interests

The authors declare no conflict of interest.

References

1. Pfeiffer, U.J., Vogeley, K., and Schilbach, L. (2013). From gaze cueing to dual eye-tracking: novel approaches to investigate the neural correlates of gaze in social interaction. Neurosci. Biobehav. Rev. *37*, 2516–2528.

2. Emery, N.J. (2000). The eyes have it: the neuroethology, function and evolution of social gaze. Neurosci. Biobehav. Rev. *24*, 581–604.

3. Dal Monte, O., Piva, M., Morris, J.A., and Chang, S.W.C. (2016). Live interaction distinctively shapes social gaze dynamics in rhesus macaques. J. Neurophysiol. *116*, 1626–1643.

4. Nummenmaa, L., and Calder, A.J. (2009). Neural mechanisms of social attention. Trends Cogn. Sci. *13*, 135–143.

5. Anderson, D.J. (2016). Circuit modules linking internal states and social behaviour in flies and mice. Nat. Rev. Neurosci. *17*, 692–704.

6. Calhoun, A.J., Pillow, J.W., and Murthy, M. (2019). Unsupervised identification of the internal states that shape natural behavior. Nat. Neurosci. *22*, 2040–2049.

7. Chen, P., and Hong, W. (2018). Neural Circuit Mechanisms of Social Behavior. Neuron *98*, 16–30.

8. Dal Monte, O., Fan, S., Fagan, N.A., Chu, C.-C.J., Zhou, M.B., Putnam, P.T., Nair, A.R., and Chang, S.W.C. (2022). Widespread implementations of interactive social gaze neurons in the primate prefrontal-amygdala networks. Neuron *110*, 2183-2197.e7.

9. Mosher, C.P., Zimmerman, P.E., and Gothard, K.M. (2014). Neurons in the monkey amygdala detect eye contact during naturalistic social interactions. Curr. Biol. *24*, 2459–2464.

10. Shepherd, S.V., Deaner, R.O., and Platt, M.L. (2006). Social status gates social attention in monkeys. Curr Biol *16*, R119-20.

11. Tomasello, M., Carpenter, M., Call, J., Behne, T., and Moll, H. (2005). Understanding and sharing intentions: the origins of cultural cognition. Behav Brain Sci *28*, 675–691; discussion 691-735.

12. Frischen, A., Bayliss, A.P., and Tipper, S.P. (2007). Gaze cueing of attention: visual attention, social cognition, and individual differences. Psychol Bull *133*, 694–724.

13. Rossano, F. (2012). Gaze in Conversation. In The Handbook of Conversation Analysis (John Wiley & Sons, Ltd), pp. 308–329.

14. Kendon, A. (1967). Some functions of gaze-direction in social interaction. Acta Psychol (Amst) *26*, 22–63.

15. Frankland, S.M., and Greene, J.D. (2020). Concepts and Compositionality: In Search of the Brain's Language of Thought. Annu Rev Psychol *71*, 273–303.

16. Tafazoli, S., Bouchacourt, F.M., Ardalan, A., Markov, N.T., Uchimura, M., Mattar, M.G., Daw, N.D., and Buschman, T.J. (2024). Building compositional tasks with shared neural subspaces. bioRxiv. https://doi.org/10.1101/2024.01.31.578263.

17. Yang, G.R., Joglekar, M.R., Song, H.F., Newsome, W.T., and Wang, X.-J. (2019). Task representations in neural networks trained to perform many cognitive tasks. Nat. Neurosci. *22*, 297–306.

18. Lake, B.M., Ullman, T.D., Tenenbaum, J.B., and Gershman, S.J. (2017). Building machines that learn and think like people. Behav Brain Sci *40*, e253.

19. Park, J., Holmes, C.D., and Snyder, L.H. (2025). Compositional architecture: Orthogonal neural codes for task context and spatial memory in prefrontal cortex. bioRxiv. https://doi.org/10.1101/2025.02.25.640211.

20. Fusi, S., Miller, E.K., and Rigotti, M. (2016). Why neurons mix: high dimensionality for higher cognition. Curr Opin Neurobiol *37*, 66–74.

21. Badre, D., Bhandari, A., Keglovits, H., and Kikumoto, A. (2021). The dimensionality of neural representations for control. Current Opinion in Behavioral Sciences *38*, 20–28.

22. Flesch, T., Juechems, K., Dumbalska, T., Saxe, A., and Summerfield, C. (2022). Orthogonal representations for robust context-dependent task performance in brains and neural networks. Neuron *110*, 4212–4219.

23. Bayones, L., Zainos, A., Alvarez, M., Romo, R., Franci, A., and Rossi-Pool, R. (2024). Orthogonality of sensory and contextual categorical dynamics embedded in a continuum of responses from the second somatosensory cortex. Proc Natl Acad Sci U S A *121*, e2316765121.

24. Fan, S., Dal Monte, O., Nair, A.R., Fagan, N.A., and Chang, S.W.C. (2024). Closed-loop microstimulations of the orbitofrontal cortex during real-life gaze interaction enhance dynamic social attention. Neuron. https://doi.org/10.1016/j.neuron.2024.05.004.

25. Flavell, S.W., Gogolla, N., Lovett-Barron, M., and Zelikowsky, M. (2022). The emergence and influence of internal states. Neuron *110*, 2545–2570.

26. Grujic, N., Polania, R., and Burdakov, D. (2024). Neurobehavioral meaning of pupil size. Neuron *112*, 3381–3395.

27. Joshi, S., and Gold, J.I. (2020). Pupil size as a window on neural substrates of cognition. Trends Cogn. Sci. *24*, 466–480.

28. Mosher, C.P., Zimmerman, P.E., and Gothard, K.M. (2011). Videos of conspecifics elicit interactive looking patterns and facial expressions in monkeys. Behav. Neurosci. *125*, 639–652.

29. McFarland, R., Roebuck, H., Yan, Y., Majolo, B., Li, W., and Guo, K. (2013). Social interactions through the eyes of macaques and humans. PLoS One *8*, e56437.

30. Berthet, M., Surbeck, M., and Townsend, S.W. (2025). Extensive compositionality in the vocal system of bonobos. Science *388*, 104–108.

31. Fodor, J.A., and Pylyshyn, Z.W. (1988). Connectionism and cognitive architecture: a critical analysis. Cognition *28*, 3–71.

32. Kriete, T., Noelle, D.C., Cohen, J.D., and O'Reilly, R.C. (2013). Indirection and symbol-like processing in the prefrontal cortex and basal ganglia. Proc Natl Acad Sci U S A *110*, 16390–16395.

33. Bernardi, S., Benna, M.K., Rigotti, M., Munuera, J., Fusi, S., and Salzman, C.D. (2020). The Geometry of Abstraction in the Hippocampus and Prefrontal Cortex. Cell *183*, 954-967.e21.

34. Churchland, M.M., Cunningham, J.P., Kaufman, M.T., Foster, J.D., Nuyujukian, P., Ryu, S.I., and Shenoy, K.V. (2012). Neural population dynamics during reaching. Nature *487*, 51–56.

35. Tye, K.M., Miller, E.K., Taschbach, F.H., Benna, M.K., Rigotti, M., and Fusi, S. (2024). Mixed selectivity: Cellular computations for complexity. Neuron *112*, 2289–2303.

36. Steinmetz, N.A., Zatka-Haas, P., Carandini, M., and Harris, K.D. (2019). Distributed coding of choice, action and engagement across the mouse brain. Nature *576*, 266–273.

37. Semedo, J.D., Jasper, A.I., Zandvakili, A., Krishna, A., Aschner, A., Machens, C.K., Kohn, A., and Yu, B.M. (2022). Feedforward and feedback interactions between visual cortical areas use different population activity patterns. Nat Commun *13*, 1099.

38. Qi, G., Fang, W., Li, S., Li, J., and Wang, L. (2022). Neural dynamics of causal inference in the macaque frontoparietal circuit. Elife *11*. https://doi.org/10.7554/eLife.76145.

39. Jackendoff, R. (2002). Foundations of Language: Brain, Meaning, Grammar, Evolution (Oxford University Press, USA).

40. Behrens, T.E.J., Muller, T.H., Whittington, J.C.R., Mark, S., Baram, A.B., Stachenfeld, K.L., and Kurth-Nelson, Z. (2018). What Is a Cognitive Map? Organizing Knowledge for Flexible Behavior. Neuron *100*, 490–509.

41. Franklin, N.T., Norman, K.A., Ranganath, C., Zacks, J.M., and Gershman, S.J. (2020). Structured Event Memory: A neuro-symbolic model of event cognition. Psychol Rev *127*, 327–361.

42. Mitani, J.C., Call, J., Kappeler, P.M., Palombit, R.A., and Silk, J.B. eds. (2012). The Evolution of Primate Societies Illustrated edition. (University of Chicago Press).

43. Carandini, M., and Heeger, D.J. (2011). Normalization as a canonical neural computation. Nat Rev Neurosci *13*, 51–62.

44. Chomsky, N. (1995). The Minimalist Program (MIT Press).

45. Trujillo, J.P., and Holler, J. (2024). Conversational facial signals combine into compositional meanings that change the interpretation of speaker intentions. Sci Rep *14*, 2286.

46. Simon, J., Iv, and Rich, E.L. (2024). Neural populations in macaque anterior cingulate cortex encode social image identities. Nat Commun *15*, 7500.

47. Chang, L., and Tsao, D.Y. (2017). The Code for Facial Identity in the Primate Brain. Cell *169*, 1013-1028.e14.

48. Knudsen, E.B., and Wallis, J.D. (2021). Hippocampal neurons construct a map of an abstract value space. Cell *184*, 4640-4650.e10.

49. Tyree, T.J., Metke, M., and Miller, C.T. (2023). Cross-modal representation of identity in the primate hippocampus. Science *382*, 417–423.

50. Rigotti, M., Barak, O., Warden, M.R., Wang, X.-J., Daw, N.D., Miller, E.K., and Fusi, S.

(2013). The importance of mixed selectivity in complex cognitive tasks. Nature *497*, 585–590.

51. Barak, O., Rigotti, M., and Fusi, S. (2013). The sparseness of mixed selectivity neurons controls the generalization-discrimination trade-off. J Neurosci *33*, 3844–3856.

52. Mante, V., Sussillo, D., Shenoy, K.V., and Newsome, W.T. (2013). Context-dependent computation by recurrent dynamics in prefrontal cortex. Nature *503*, 78–84.

53. Báez-Mendoza, R., Mastrobattista, E.P., Wang, A.J., and Williams, Z.M. (2021). Social agent identity cells in the prefrontal cortex of interacting groups of primates. Science *374*, eabb4149.

54. Peelen, M.V., Atkinson, A.P., and Vuilleumier, P. (2010). Supramodal representations of perceived emotions in the human brain. J Neurosci *30*, 10127–10134.

55. Pelphrey, K.A., Morris, J.P., and McCarthy, G. (2005). Neural basis of eye gaze processing deficits in autism. Brain *128*, 1038–1048.

56. Semedo, J.D., Zandvakili, A., Machens, C.K., Yu, B.M., and Kohn, A. (2019). Cortical Areas Interact through a Communication Subspace. Neuron *102*, 249-259.e4.

57. Dal Monte, O., Chu, C.C.J., Fagan, N.A., and Chang, S.W.C. (2020). Specialized medial prefrontal-amygdala coordination in other-regarding decision preference. Nat Neurosci *23*, 565–574.

58. Huk, A.C., and Shadlen, M.N. (2005). Neural activity in macaque parietal cortex reflects temporal integration of visual motion signals during perceptual decision making. J Neurosci *25*, 10420–10436.

59. Puce, A., Allison, T., Bentin, S., Gore, J.C., and McCarthy, G. (1998). Temporal cortex activation in humans viewing eye and mouth movements. J Neurosci *18*, 2188–2199.

60. Hanks, T.D., Kopec, C.D., Brunton, B.W., Duan, C.A., Erlich, J.C., and Brody, C.D. (2015). Distinct relationships of parietal and prefrontal cortices to evidence accumulation. Nature *520*, 220–223.

61. Kuzmanovic, B., Georgescu, A.L., Eickhoff, S.B., Shah, N.J., Bente, G., Fink, G.R., and Vogeley, K. (2009). Duration matters: dissociating neural correlates of detection and evaluation of social gaze. Neuroimage *46*, 1154–1163.

62. Tognoli, E., Zhang, M., Fuchs, A., Beetle, C., and Kelso, J.A.S. (2020). Coordination Dynamics: A Foundation for Understanding Social Behavior. Front Hum Neurosci *14*, 317.

63. Moeller, S., Unakafov, A.M., Fischer, J., Gail, A., Treue, S., and Kagan, I. (2023). Human and macaque pairs employ different coordination strategies in a transparent decision game. Elife *12*. https://doi.org/10.7554/eLife.81641.

64. Qi, G., and Chang, S.W.C. (2025). Social behavior in primates and its neural correlates. In Reference Module in Neuroscience and Biobehavioral Psychology (Elsevier).

65. Goldin-Meadow, S., and Alibali, M.W. (2013). Gesture's role in speaking, learning, and creating language. Annu Rev Psychol *64*, 257–283.

66. Sliwa, J., and Freiwald, W.A. (2017). A dedicated network for social interaction processing in

the primate brain. Science *356*, 745–749.

67. Li, J., Aoi, M.C., and Miller, C.T. (2024). Representing the dynamics of natural marmoset vocal behaviors in frontal cortex. Neuron *112*, 3542-3550.e3.

68. Cléry, J.C., Hori, Y., Schaeffer, D.J., Menon, R.S., and Everling, S. (2021). Neural network of social interaction observation in marmosets. Elife *10*. https://doi.org/10.7554/eLife.65012.

69. McMahon, E., Bonner, M.F., and Isik, L. (2023). Hierarchical organization of social action features along the lateral visual pathway. Curr. Biol. *33*, 5035-5047.e8.

70. Park, S.H., Koyano, K.W., Russ, B.E., Waidmann, E.N., McMahon, D.B.T., and Leopold, D.A. (2022). Parallel functional subnetworks embedded in the macaque face patch system. Sci. Adv. *8*, eabm2054.

71. Ramezanpour, H., and Thier, P. (2020). Decoding of the other's focus of attention by a temporal cortex module. Proc. Natl. Acad. Sci. U. S. A. *117*, 2663–2670.

72. Shepherd, S.V., and Freiwald, W.A. (2018). Functional Networks for Social Communication in the Macaque Monkey. Neuron *99*, 413-420.e3.

73. Shepherd, S.V., Klein, J.T., Deaner, R.O., and Platt, M.L. (2009). Mirroring of attention by neurons in macaque parietal cortex. Proc. Natl. Acad. Sci. U. S. A. *106*, 9489–9494.

74. Gilardeau, S., Cirillo, R., Jazayeri, M., Dupuis, C., Wirth, S., and Duhamel, J.-R. (2021). Two functions of the primate amygdala in social gaze. Neuropsychologia *157*, 107881.

75. Pryluk, R., Shohat, Y., Morozov, A., Friedman, D., Taub, A.H., and Paz, R. (2020). Shared yet dissociable neural codes across eye gaze, valence and expectation. Nature *586*, 95–100.

76. Sliwa, J., Planté, A., Duhamel, J., and Wirth, S. (2016). Independent neuronal representation of facial and vocal identity in the monkey hippocampus and inferotemporal cortex. Cereb. Cortex *26*, 950–966.

77. Fernández-Dols, J.-M., and Russell, J.A. (2017). The Science of Facial Expression (Oxford University Press).

78. Waller, B.M., Kavanagh, E., Micheletta, J., Clark, P.R., and Whitehouse, J. (2024). The face is central to primate multicomponent signals. Int. J. Primatol. *45*, 526–542.

79. Barrett, L.F., and Simmons, W.K. (2015). Interoceptive predictions in the brain. Nat Rev Neurosci *16*, 419–429.

80. Critchley, H.D., and Harrison, N.A. (2013). Visceral influences on brain and behavior. Neuron *77*, 624–638.

81. Brainard, D.H. (1997). The Psychophysics Toolbox. Spat. Vis. *10*, 433–436.

82. Cornelissen, F.W., Peters, E.M., and Palmer, J. (2002). The Eyelink Toolbox: eye tracking with MATLAB and the Psychophysics Toolbox. Behav. Res. Methods Instrum. Comput. *34*, 613–617.

83. Paxinos, G., Petrides, M., and Evrard, H.C. (2023). The Rhesus Monkey Brain in Stereotaxic Coordinates (Academic Press).

84. Chung, J.E., Magland, J.F., Barnett, A.H., Tolosa, V.M., Tooker, A.C., Lee, K.Y., Shah, K.G., Felix, S.H., Frank, L.M., and Greengard, L.F. (2017). A Fully Automated Approach to Spike Sorting. Neuron *95*, 1381-1394.e6.

85. Krassanakis, V., Filippakopoulou, V., and Nakos, B. (2014). EyeMMV toolbox: An eye movement post-analysis tool based on a two-step spatial dispersion threshold for fixation identification. J. Eye Mov. Res. *7*. https://doi.org/10.16910/jemr.7.1.1.

86. Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Müller, A., Nothman, J., Louppe, G., et al. (2012). Scikit-learn: Machine Learning in Python. arXiv [cs.LG]. https://doi.org/10.48550/ARXIV.1201.0490.

87. Stoll, F.M., and Rudebeck, P.H. (2024). Decision-making shapes dynamic inter-areal communication within macaque ventral frontal cortex. Curr Biol *34*, 4526-4538.e5.

Supplemental Information

Figure S1. Experimental setup and face calibration. Related to Fig. 1B. **(A–B)** Setup for real-life social gaze interaction, with two monkeys positioned face-to-face. The central monitors could be remotely raised or lowered via a hydraulic system to control visual access. **(C–D)** Custom LED face calibration board with lights aligned to key facial landmarks (eyes, mouth, corners). Two versions fit different face sizes. LED colors in **(D)** are illustrative; actual lights used a single color. **(E)** An example calibration result showing gaze-to-LED position mapping (colored squares).

Figure S2. Correlation between pupil size and social state. Related to Fig. 1C. **(A)** Normalized social gaze (face) bouts fraction across runs and sessions (red marks: sessions 1–13 and 16 from Monkey L; cyan marks: sessions 14–15 and 17–42 from Monkey K). **(B)** Normalized pupil size (min-max normalized to the [0, 1] range within each session) across runs and sessions (red marks: sessions 1–13 and 16 from Monkey L; cyan marks: sessions 14–15 and 17–42 from Monkey K). Note that the white segment in the pupil size matrix means the pupil data was missing. **(C)** Line plots showing the relationship between normalized pupil size and the fraction of social gaze bouts across runs within each session. Each line represents a single session. **(D)** Histogram of session-wise Pearson correlation coefficients (Fisher Z-transformed) between pupil size and social bout fraction. The red dashed line marks the mean correlation (-0.0016), indicating no systematic relationship between pupil size and social engagement across sessions ($P = 0.97$, one sample t-test with 0).

Figure S3. Distributions of gaze duration and gaze content. Related to Fig. 1. **(A)** The distributions of gaze durations from all 42 sessions by session. Each gaze bout was labeled as a short (open bar) or long (filled bar) duration event based on whether its duration was lower or higher than the median of duration in a given session. **(B)** Distributions of gaze content across all 42 sessions.

Figure S4. M1's social state negatively predicts M2's social engagement. Related to Fig. 1D. **(A)** Fixed effects estimates from the generalized linear mixed-effects model (GLMM) predicting the occurrence of M2's social state based on M1's social gaze primitives and their compositions (Methods). Each point represents a fixed effect (log-odds estimate) with 95% confidence intervals. Asterisks indicate significance levels based on Type III Wald chi-square tests. The reference conditions for all predictors were defined as M1 state = Low, M1 content = Object, M1 duration = Short. **(B)** Predicted probabilities (back-transformed from the logit scale) of M2 high social state as a function of M1 content. Vertical lines on the bars indicate 95% confidence intervals. Horizontal lines with asterisks denote significant pairwise differences. Significance was tested using pairwise Wald z-tests on marginal mean differences (Tukey-adjusted), which account for covariance; thus, significance may occur even when 95% confidence intervals overlap. ** $P < 0.01$.

Figure S5. Encoding of the three social gaze primitives in the four neural populations based on a partial regression approach. Related to Fig. 2D. Shown are partial regression coefficients between brain RDM and social gaze primitives RDM. * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$ with permutation test.

Figure S6. A hypothesis testing the compositionality of social gaze primitives at the neural population level with the three testable predictions. Related to Fig. 3. To evaluate whether neural populations represent social gaze in a compositional manner, we tested three predictions derived from the compositionality hypothesis: (i) social state and gaze content are represented distinctly; (ii) their neural encoding axes are orthogonal; and (iii) these representations generalize across conditions. Illustrated are theoretical schematics and population-level decoding analyses used to test these predictions. (**A**) Schematic of a compositional encoding hypothesis. Neural population responses to four conditions (content/state: face/high, object/high, face/low, object/low) are distributed along orthogonal axes in neural state space. Color (orange = face, green = object) and fill (solid = high state, open = low state) distinguish the two dimensions. (**B**) Cross-primitives decoding for separability test. A linear SVM classifier trained to decode one variable (e.g., content: face vs. object) using content-labeled gaze events was tested on trials labeled by the other variable (e.g., state: high vs. low), and vice versa. (**C**) Neural state space analysis for testing orthogonality. Content and state encoding axes were defined by condition-wise firing rate differences. An angle close to 90 between them indicates content and state along the orthogonal axis. (**D**) Cross-conditions decoding for the generalization test. Left: A linear SVM trained to decode face vs. object in one state condition (e.g., low state) successfully generalizes to the other state (e.g., high state), supporting the idea that content representations are reused across states (i.e., content generalization). Right: A linear SVM trained to decode high vs. low state in one content condition (e.g., face) successfully generalizes to the other content (e.g., object), supporting the idea that state representations are reused across content (i.e., state generalization).

Figure S7. Example PSTHs for pure content-, pure state-, and linear mixed selectivity neurons in BLA, ACCg, dmPFC, and OFC. Related to Fig. 4B-C. Peri-stimulus time histograms (PSTHs) show normalized firing rates (min-max normalized to the [0, 1] range within each neuron) aligned to gaze onset (time 0) for example neurons classified as pure content-selective (**A**), pure state-selective (**B**), and linear mixed-selective (**C**). Each column shows representative neurons from a different brain region for each classification, respectively. For each representative neuron, its averaged firing rate during gaze events in each condition (face in high state, face in low state, object in high state, and object in low state) was plotted below its corresponding PSTH. Horizontal brackets indicate significant main effects of either gaze content (face vs. object, purple) or social state (high vs. low, blue) based on linear regressions in Fig. 4A. * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$. For the bar plots, error bars represent mean ± SEM across trials. For the PSTHs plots, shaded areas represent ±SEM across trials. Orange and green curves correspond to face and object gaze targets, respectively, with solid lines indicating high-state trials and dashed lines indicating low-state trials. Face High: solid orange; Face Low: dashed orange; Object High: solid green; Object Low: dashed green.

Figure S8. Averaged cross-temporal correlation matrices for content information. Related to Fig. 5A. * *P* < 0.05; ** *P* < 0.01; *** *P* < 0.001 with permutation test.

Figure S9. Averaged cross-temporal correlation matrices for state information. Related to Fig. 5A. * *P* < 0.05; ** *P* < 0.01; *** *P* < 0.001 with permutation test.

Figure S10. Functional connectivity of social gaze primitives when excluding linear mixed selectivity cells. Related Fig. 5. (**A**) Dynamic functional connectivity in the prefrontal-amygdala circuits for gaze content (upper panel) and social state (lower panel) information after removing linear mixed cells, respectively. Gaze period: when the eye gaze is on the face or the object. Pre-gaze period: 200 msec before the eye gaze is on the face or the object. Post-gaze period: 200 msec after the eye gaze is on the face or the object. * $P < 0.05$; ** $P < 0.01$; *** $P < 0.001$ with permutation test. (**B**) Directionality of the content (upper panel) and the state (lower panel) information after removing linear mixed cells for each pair of brain regions. Error bar: mean ± SEM. *** $P < 0.001$ with Wilcoxon signed-rank tests.