Involuntary feedback responses reflect a representation of partner actions

Seth R. Sullivan[1], John H. Buggeln[1,3], Jan A. Calalo[2], Truc T. Ngo[1], Jennifer A. Semrau[1,3,4,5], Michael J. Carter[6,†], Joshua G.A. Cashaback[1,2,3,4,5,†]

[1] Department of Biomedical Engineering, University of Delaware
[2] Department of Mechanical Engineering, University of Delaware
[3] Biomechanics and Movement Science Program, University of Delaware
[4] Department of Kinesiology & Applied Physiology, University of Delaware
[5] Interdisciplinary Neuroscience Graduate Program, University of Delaware
[6] Department of Kinesiology, McMaster University
[†] co-senior authors

Abbreviated Title:

Feedback responses reflect partner actions

Funding:

National Science Foundation (NSF #2146888) awarded to JGAC
National Sciences and Engineering Research Council (NSERC) of Canada (RGPIN-2018-05589) awarded to MJC

Correspondence:

Seth Sullivan
Biomedical Engineering
University of Delaware
Newark, DE 19711, U.S.A
Email: sethsullivan99@gmail.com

Joshua G. A. Cashaback, PhD
Biomedical Engineering
University of Delaware
STAR Campus, Room 201J
Newark, DE 19711, U.S.A
Email: cashabackjga@gmail.com

Abstract

We have a remarkable ability to seamlessly and rapidly coordinate actions with others, from double dutch to dancing. Humans use high-level partner representations to jointly control voluntary actions, while other work shows lower-level involuntary feedback responses to sudden visual perturbations. Yet, it is unknown if a high-level partner representation can be rapidly expressed through lower-level involuntary sensorimotor circuitry. Here we test the idea that a partner representation influences involuntary visuomotor feedback responses during a cooperative sensorimotor task. Using two experiments and dynamic game theory predictions, we show that involuntary visuomotor feedback responses reflect a partner representation and consideration of a partner's movement cost (i.e., accuracy and energy). Collectively, our results suggest there is top-down modulation from high-level partner representations to lower-level sensorimotor circuits, enabling fast and flexible feedback responses during jointly coordinated actions.

Introduction

To successfully coordinate voluntary actions, humans form a representation of others to consider their partner's goals[1,2,3] and movement costs (i.e., accuracy and energy).[4,5] Other work has shown that the sensorimotor system modulates involuntary feedback responses based on the structure of the individual's own goal.[6] Yet it is unknown if the sensorimotor system uses a partner representation to tune these rapid and involuntary feedback responses. Investigating the influence of high-level partner representations on lower-level involuntary sensorimotor responses is crucial to understanding how humans achieve coordinated interactions during rapid movements.

A representation of a partner to consider both their goals and costs has been shown to influence voluntary movements. Behavioural work examining human-human sensorimotor interactions has suggested that a partner representation influences reaction time,[7] action planning,[2,5] and reaching movements.[1,2,4,8,9,10] While work with a single individual has shown that humans minimize a self movement cost,[11,12,13,14] work with multiple individuals suggests that humans will select voluntary actions that minimize a joint cost that considers both self and a partner.[5] While these past works have broadened our understanding of voluntary coordinated actions, it remains unknown if a high-level partner representation and consideration of the partner's cost can influence lower-level involuntary sensorimotor feedback responses.

Elegant work has shown that the sensorimotor system has a remarkable ability to generate rapid and involuntary feedback responses—prior to voluntary control—that are tuned by task dynamics and goals.[6,15,16,17] Nashed and colleagues (2012) had participants reach to either a narrow target (task-relevant) or wide target (task-irrelevant).[6] The narrow target was task-relevant since participants needed to correct for lateral deviations to successfully hit the target. The wide target was task-irrelevant since participants did not need to correct for lateral deviations to hit their target. As early as 70 ms following a mechanical perturbation, they found greater muscular feedback responses when

reaching to a narrow task-relevant target compared to a wide task-irrelevant target. Like-
wise, pioneering work by Franklin and Wolpert (2008) demonstrated that sensorimotor
circuits also generate involuntary feedback responses to visual perturbations between
180 - 230 ms.[17] To measure involuntary feedback responses, they laterally constrained a
participant's hand within a rigid force channel and recorded the lateral hand force in re-
sponse to a lateral cursor jump. They found that these rapid and involuntary visuomotor
feedback responses are also tuned according to relevant and irrelevant task demands.
While considerable work has examined visuomotor feedback responses of a human act-
ing alone, it is unknown whether the sensorimotor system uses a partner representation
to tune involuntary visuomotor feedback responses.

Across two experiments, we tested the overarching idea that a high-level partner rep-
resentation influences lower-level involuntary sensorimotor circuits. Human pairs were
required to move a jointly controlled cursor into their own target. We manipulated the
width of both participant targets to be either task-relevant or task-irrelevant. We mea-
sured visuomotor feedback responses following either a cursor (**Experiment 1**) or target
jump (**Experiment 2**). We made *a priori* predictions using four unique dynamic game
theory models. Each of these models tested a specific hypothesis on whether visuomo-
tor feedback responses reflect: i) a partner representation and, if so, ii) a weighting of the
partner cost. Collectively, our empirical and computational work provides novel insights
into how humans rapidly control their actions with others.

Results

Experimental Design

In **Experiment 1** (n = 48) and **Experiment 2** (n = 48), participants completed a joint
reaching task with a partner (**Fig. 1A**). Participants had vision of their own cursor, a
partner's cursor, and a center cursor. The center cursor was at the midpoint of their
own cursor and their partner's cursor. They also viewed their own self target and their
partner's target on their screen. Participants were instructed to move and stabilize the

center cursor in the self target within a time constraint. Participants received the message

'Good', 'Too Slow', or 'Too Fast' if they stabilized within their self target between 1400 -

1600 ms, > 1600 ms, or <1400 ms respectively. They were explicitly informed that their

success in the task was determined by moving and stabilizing the center cursor only

within the self target. Therefore, the instructions and timing constraints did not enforce

participants to work together.

We manipulated the width of both the self and partner target (**Fig. 1B**) to be either

narrow (task-relevant) or wide (task-irrelevant). The narrow target is task-relevant since

participants would need to correct for lateral deviations to hit their target. The wide tar-

get is task-irrelevant since participants do not need to correct for lateral deviations to hit

their target. Thus, we used a 2 (Partner Irrelevant or Partner Relevant) x 2 (Self Irrelevant

or Self Relevant) repeated measures experimental design with four blocked experimen-

tal conditions: i) *partner-irrelevant/self-irrelevant*, ii) *partner-relevant/self-irrelevant*, iii)

partner-irrelevant/self-relevant, and iv) *partner-relevant/self-relevant*.

The goal of **Experiment 1** and **Experiment 2** was to determine if a representation

of a partner and consideration of their costs influences involuntary visuomotor feedback

responses. To address this goal, we had participants perform non-perturbation trials,

perturbation trials, and probe trials in each experimental condition. In both the non-

perturbation trials and perturbation trials, participants reached freely in the lateral and

forward dimensions. However, in perturbation trials (**Fig. 1C-D**) either the center cursor

(**Experiment 1**) or both targets (**Experiment 2**) jumped 3 cm to the right or left when the

center cursor moved 25% of the forward distance to the targets. In probe trials (**Fig. 1E-**

F), both participants were constrained by a force channel and could only move along the

forward dimension. Here they experienced the cursor or target jump for 250 ms before

returning to the original lateral position. Critically, as a metric of visuomotor feedback

responses, we measured the lateral force participants applied against the channel in

response to center cursor or target jumps.

Figure 1: Experimental Design. A) In both experiments, each participant in the pair grasped the handle of a robotic manipulandum and made reaching movements in the horizontal plane. An LCD projected images (start position, targets, cursors) onto a semi-silvered mirror. Each trial began with each participant's hand (dark grey circle) within their respective start position (white circle). After a short and random time delay, the self target appeared as a filled dark grey rectangle and the partner target appeared as an unfilled light grey rectangle. Simultaneously, the center cursor (green circle) and partner cursor (light grey circle) also appeared on the screen. After a constant time delay of 500 ms, participants heard a tone that cued them to begin their reach. Participants were instructed to move the center cursor into their own target. Each participant received independent feedback once the center cursor was stabilized within their own target.

B) Experimental Conditions. We manipulated the width of both the self and partner targets to be either narrow (task-relevant) or wide (task-irrelevant). The narrow target is task-relevant since participants would need to correct for lateral deviations to successfully complete their task. The wide target is task-irrelevant since participants do not need to correct for lateral deviations to successfully complete their task. Human pairs performed four blocked experimental conditions: i) *partner-irrelevant/self-irrelevant* ii) *partner-relevant/self-irrelevant* iii) *partner-irrelevant/self-relevant* iv) *partner-relevant/self-relevant*. **C-D) Perturbation Trials.** On a subset of trials, the center cursor in (**C**) **Experiment 1** or both targets in (**D**) **Experiment 2** jumped 3 cm laterally to the left or right. **E-F) Visuomotor Probe Trials.** On a subset of trials, the center cursor in **Experiment 1** (**E**) or both targets in **Experiment 2** (**F**) jumped 3 cm laterally for 225 ms, then jumped 3 cm back to the original lateral position. During these probe trials, the hand of both participants in the pair was constrained to a force channel. Here we measured each participant's visuomotor feedback responses as the force (N) they applied to the wall of the stiff force channel.

Dynamic Game Theory Model

We generated *a priori* predictions of hand trajectories and visuomotor feedback responses for each of the experimental conditions using a dynamic game theory model (**Fig. 2A**). We modelled our task as a linear quadratic game of the form

$$x_{k+1} = Ax_k + B_1 u_{1,k} + B_2 u_{2,k}. \tag{1}$$

x_k is the state (e.g., position) of the system at time step k, A represents the task dynamics, u_1 and u_2 are the control signals, and B_1 and B_2 converts the control signals to a force that produces movement. Here the subscripts 1 and 2 respectively refers to controller 1 and 2, representing a pair of participants in our task. Throughout, we describe the model with controller 1 as the self and controller 2 as the partner.

Controller 1 and 2 select their own control signal u_1^* or u_2^*, which considers their respective costs. We can define individual cost functions J_1 and J_2 as:

$$J_1 = \frac{1}{2} \sum_{k=0}^{N-1} \left(x_k^T Q_1 x_k + u_{1,k}^T R_{11} u_{1,k} \right) + \frac{1}{2} x_N^T Q_{1,N} x_N \tag{2}$$

$$J_2 = \frac{1}{2} \sum_{k=0}^{N-1} \left(x_k^T Q_2 x_k + u_{2,k}^T R_{22} u_{2,k} \right) + \frac{1}{2} x_N^T Q_{2,N} x_N \tag{3}$$

Here J_1 is the individual cost for controller 1 (e.g., self) and J_2 is the individual cost for controller 2 (e.g., partner). N is the final step, which represents the end of a trial. The term Q penalizes deviations of the center cursor relative to each target.

Figure 2: Control Model Framework and Hypotheses. A) Control Model. Human pairs were modelled as controllers within a dynamic game theory framework. Here we depict the feedback control loop from the perspective of one participant (i.e. the self). The self and partner control policy each generate a motor command to produce jointly controlled movement. An efference copy of the motor command passes through an internal model (representation of dynamics) to generate predicted states. Each controller also receives noisy and delayed sensory feedback on the states (e.g., position of the self and partner hand, center cursor, and self and partner targets). Both the self and partner controllers have a state estimator that combines the predicted state and sensory feedback in a statistically optimal manner to produce estimated states. The estimated states are used by the control policy to generate motor commands on each time step. **B) Hypotheses.** The dynamic game theory framework allowed us to test four distinct hypotheses. The hypotheses test whether the control policy: i) has a representation of a partner, and ii) considers only a self cost or joint (self + partner) cost of accuracy and energy. **No Partner Representation & Self Cost Hypothesis:** The sensorimotor system has a control policy that does not use a representation of a partner, and only considers a self cost. **Partner Representation & Self Cost Hypothesis:** The sensorimotor system has a control policy that uses a representation of a partner, but only considers a self cost. **Partner Representation & Equal Joint Cost Hypothesis:** The sensorimotor system has a control policy that uses a representation of a partner, and equally considers both a self cost and partner cost (i.e., equal joint cost). **Partner Representation & Weighted Joint Cost Hypothesis:** The sensorimotor system has a control policy that uses a representation of a partner, and that weights the self cost greater than the partner cost (i.e., weighted joint cost). Each of the four hypotheses generate unique predictions of human hand movement (**Fig. 3A-P**) and visuomotor feedback responses (**Fig. 4**).

109   Depending on the experimental condition, we modelled i) a task-relevant target using

110   a higher value of Q, and ii) a task-irrelevant target using a lower value of Q. The term

111 R penalizes the control signal (u), which would relate to an energetic cost. Further, we

112 define a joint cost function as:

$$J_1^{\alpha_1} = J_1 + \alpha_1 J_2 \tag{4}$$

$$J_2^{\alpha_2} = J_2 + \alpha_2 J_1, \tag{5}$$

113 where $\alpha_i \in [0,1]$ determines the degree to which controller i considers their partner's

114 cost function.

115   The optimal control signal for controller 1 ($u_{1,k}^*$) and controller 2 ($u_{1,k}^*$) is determined

116 by the time-varying feedback gains F_1 and F_2 that minimize the joint cost function $J_1^{\alpha_1}$

117 and $J_2^{\alpha_2}$ respectively:

$$u_{1,k}^* = -F_{1,k}\hat{x}_{1,k} \tag{6}$$

$$u_{2,k}^* = -F_{2,k}\hat{x}_{2,k} \tag{7}$$

Here, $\hat{x}_{i,k}$ for $i = \{1,2\}$ is controller i's posterior estimate of the state (see **Methods**). The

feedback gains F_1 and F_2 constitute a Nash equilibrium solution to the linear quadratic

game defined by eqs. 1-5. Throughout, the feedback gains determine hand movement

and visuomotor feedback responses. The Nash equilibrium solution F_1 that minimizes

$J_1^{\alpha_1}$ can utilize knowledge of the partner's control policy F_2 through the coupled algebraic

Riccati equations (see **Supplementary C**).

Modelling partner representation. A partner representation is defined as knowl-

edge of the partner's control policy F_2. That is, a person accounts for their partner's

actions. No partner representation would reflect the case where F_1 is selected under

the assumption that $F_2 = 0$. More simply, a person does not account for their partner's

actions.

Modelling self and partner cost. We also modelled the degree to which a person

considers their self cost, or some joint cost of both self and partner. In **Eq. 19**, α_1 deter-

mines the degree to which controller 1 considers its partner's cost. $\alpha_1 = 0$ reflects only a

self cost, which would imply a person does not consider their partner's cost. Conversely,

$\alpha_1 = 1$ reflects an equal joint cost that would imply a person considers their self cost and partner cost equally. Finally, $\alpha_1 = 0.5$ reflects a higher weighting on the self cost than the partner cost, implying that a person primarily considers their own cost and to a lesser extent their partner's cost.

Through our computational framework, we considered four alternative hypotheses, each testing how a partner representation and consideration of a partner's cost influences sensorimotor behaviour (**Fig. 2B-E**): i) No Partner Representation & Self Cost, ii) Partner Representation & Self Cost, iii) Partner Representation & Equal Joint Cost, iv) Partner Representation & Weighted Joint Cost. For each experimental condition, we used these four models to make *a priori* predictions of reaching trajectories (**Fig. 3**) and visuomotor feedback responses (**Fig. 4**).

Hand and Center Cursor Trajectories

Model Trajectories

To make *a priori* predictions of voluntary motor behaviour, we simulated center cursor jump perturbation trials (**Fig. 3A-P**) and target jump perturbation trials (**Supplementary Fig. C**). The hand trajectory predictions for each of the four models on leftward cursor jump perturbation trials are shown for each condition in **Fig. 3A-P**.

In the *partner-relevant/self-irrelevant* condition, we predicted that the self controller in the No Partner Representation & Self Cost (**Fig. 3B**) and Partner Representation & Self Cost model (**Fig. 3F**) would not make a lateral correction for a cursor jump. Conversely, in the same *partner-relevant/self-irrelevant* condition, we predicted that the self controller in the Partner Representation & Equal Joint Cost (**Fig. 3J**) and Partner Representation & Weighted Joint Cost model (**Fig. 3N**) would make a lateral correction for a cursor jump.

Empirical Trajectories

An exemplar pair (**Fig. 3Q-T**) and group average (**Fig. 3U-X**) hand and center cursor trajectories are shown for each experimental condition in **Experiment 1**. Note that

Figure 3: Model and Experiment 1 and Center Cursor Trajectories. Predicted hand and center cursor positions during left cursor jumps for each condition and model: **A-D)** No Partner Representation & Self Cost, **E-H)** Partner Representation & Self Cost, **I-L)** Partner Representation & Equal Joint Cost, and **M-P)** Partner Representation & Weighted Joint Cost.

Collectively, the self cursor in models with only a self cost do not laterally deviate to correct for the cursor jump in the *partner-relevant/self-irrelevant* condition. In contrast, the self cursor in models that consider a self and partner cost laterally deviate to correct for the cursor jump in the *partner-relevant/self-irrelevant* condition. **Q-T)** Individual hand and center cursor positions of an exemplar pair for each condition in **Experiment 1**. Thin traces represent each trial. Thick traces represent the average across trials for the human pair. **U-X)** Group average hand and center cursor positions in **Experiment 1**. Traces represent the mean and shaded regions reflect ± 1 standard error of the mean. The group average behaviour in **Experiment 1** closely aligns with the Partner Representation & Weighted Joint Cost model, suggesting that voluntary behaviour reflects a partner representation and consideration of a partner's cost.

while both participants in the pair began each trial to the right of the center cursor (see

Fig. 1A), we refer to one of the participants as the 'self' and the other participant as

the 'partner' (see **Methods** for details). In the *partner-irrelevant/self-irrelevant* condition

(**Fig. 3Q,U**), neither participant laterally deviated to correct for the cursor jump since

both targets were irrelevant. In the *partner-relevant/self-irrelevant* condition (**Fig. 3R,V**),

the self cursor laterally deviated less than the partner cursor. In the *partner-irrelevant/self-*

relevant condition (**Fig. 3S,W**), the self cursor laterally deviated more than the partner

cursor. Finally, in the *partner-relevant/self-relevant* condition (**Fig. 3T,X**), both the self

and partner cursor had a similar amount of lateral deviation.

Visuomotor Feedback Responses

The group average trajectories in both **Experiment 1**, **Experiment 2**, and final lateral

hand deviation (see **Supplementary A**) aligned closest with the Partner Representation

& Weighted Joint Cost model (**Fig. 3M-P**). Together, the model predictions and empir-

ical hand trajectories support the notion that voluntary sensorimotor control reflects a

partner representation and a consideration of the partner's cost.

Model Visuomotor Feedback Responses

We also simulated probe trials by constraining the models to a force channel and cal-

culating the force the models produce in response to the cursor jump (see **Methods:**

Dynamic Game Theory Model). For each model and condition, **Fig. 4** shows the vi-

suomotor feedback responses over time in response to cursor jump probe trials. The

inset within each of the subplots displays the average visuomotor response between

180-230 ms, which aligns with the involuntary time epoch.[17]

Figure 4: Model Visuomotor Feedback Responses. Model predictions of visuomotor feedback responses (y-axis) over the time from probe onset (x-axis) for each condition considering the **(A)** No Partner Representation & Self Cost, **(B)** Partner Representation & Self Cost, **(C)** Partner Representation & Equal Joint Cost, and **(D)** Partner Representation & Weighted Joint Cost models. Solid lines reflect the average visuomotor feedback response to probe trials and shaded error bars reflect ±1 standard deviation of the mean. The inset axis shows the mean visuomotor feedback response between (180 - 230 ms), which aligns with the involuntary time epoch.[17] Across the different models, a greater visuomotor feedback response in the *partner-relevant/self-irrelevant* condition compared to *partner-irrelevant/self-irrelevant* condition implies that there is a partner representation and a consideration of the partner's cost. Likewise, a lower feedback response in the *partner-relevant/self-relevant* condition relative to the *partner-irrelevant/self-relevant* condition would indicate a partner representation, as well as a higher weighting of the self cost compared to the partner cost.

Models that only consider the self cost predict no change in visuomotor feedback re-

sponses between the *partner-relevant/self-irrelevant* and *partner-irrelevant/self-irrelevant*

condition (**Fig. 4A,B**). Thus, models that only consider a self cost do not help their part-

ner achieve their goal. Conversely, models that consider both a self and partner cost

predict a greater visuomotor feedback response in the *partner-relevant/self-irrelevant*

condition compared to the *partner-irrelevant/self-irrelevant* condition (**Fig. 4C,D**). That

is, models that consider a joint cost attempt to help a partner achieve their goal. If the

involuntary sensorimotor circuits leverage a partner representation and consideration

of partner costs, we would expect to see an increased visuomotor feedback response

in the *partner-relevant/self-irrelevant* condition compared to the *partner-irrelevant/self-*

irrelevant condition.

If there is a partner representation, there are different visuomotor feedback response

predictions when the self controller has an equal joint cost versus a weighted joint cost.

In the Partner Representation & Equal Joint Cost model, the self controller is willing

to spend the same amount of energy to help their partner or itself achieve a goal. As

a result, this model predicts no difference between the *partner-relevant/self-irrelevant*,

partner-irrelevant/self-relevant and *partner-relevant/self-relevant* conditions (**Fig. 4C**).

On the contrary, the self controller in the Partner Representation & Weighted Joint

Cost model primarily spends energy to achieve its own goal, while spending compara-

tively less energy to help a partner achieve their goal. During the *partner-irrelevant/self-*

relevant condition, the self controller is only expecting a partial visuomotor feedback

response from the partner since the partner has an irrelevant target. But in the *partner-*

relevant/self-relevant condition, the self controller is expecting a comparatively greater

visuomotor feedback response from the partner since the partner also has a relevant

target. Therefore, the Partner Representation & Weighted Joint Cost model predicts a

greater visuomotor feedback response in the *partner-irrelevant/self-relevant* condition

compared to the *partner-relevant/self-relevant* condition (**Fig. 4D**).

Experiment 1 Visuomotor Feedback Responses

Here we show group level visuomotor feedback responses over time (**Fig. 5A**), and

the average visuomotor feedback response during the involuntary (180-230 ms), semi-

involuntary (230-300 ms), and voluntary (300-400 ms) epochs.

Figure 5: Visuomotor Feedback Responses in Experiment 1. A) Visuomotor feedback response (y-axis) over time (x-axis), where 0 ms corresponds to the initial cursor jump. Solid lines represent the group average visuomotor feedback response for each condition. Shaded regions represent ± 1 standard error. Vertical grey lines separate involuntary (180 - 230 ms), semi-involuntary (230 - 300 ms), and voluntary (300-400 ms) visuomotor feedback responses. Average **B)** involuntary, **C)** semi-involuntary, and **D)** and voluntary visuomotor feedback response for each condition. Box and whisker plots show 25%, 50%, and 75% quartiles. **B)** We see significant differences in involuntary visuomotor feedback responses between each condition, matching the predictions of the Partner Representation & Weighted Joint Cost model (see **Fig. 4D**). Crucially, a greater involuntary visuomotor feedback response in the *partner-relevant/self-irrelevant* condition compared to the *partner-irrelevant/self-irrelevant* condition (p < 0.001) suggests a partner representation and some consideration of the partner's cost. Further, a smaller involuntary visuomotor feedback response in the *partner-relevant/self-relevant* condition compared to the *partner-irrelevant/self-relevant* condition (p = 0.002) suggests a higher weighting of the self cost compared to the partner cost. Taken together, our results support the idea that involuntary visuomotor feedback responses express a representation of a partner, while using a joint cost that more heavily weights the self cost over the partner cost.

There was a significant interaction between self target and partner target (F[1,47]

= 60.42, p < 0.001) on involuntary visuomotor feedback responses in **Experiment 1**.

Interestingly, we found a significantly greater involuntary visuomotor feedback responses

in the *partner-relevant/self-irrelevant* condition compared to the *partner-irrelevant/self-*

irrelevant condition (p < 0.001, $\hat{\theta}$ = 90.84). Crucially, these results support the idea that

the involuntary sensorimotor circuits have a partner representation and a consideration

of the partner's cost.

Further, there was a significantly different involuntary visuomotor feedback response

between the *partner-relevant/self-relevant* and *partner-irrelevant/self-relevant* conditions

(p = 0.002, $\hat{\theta}$ = 59.33). A lower involuntary visuomotor feedback response in the *partner-*

relevant/self-relevant condition compared to the *partner-irrelevant/self-relevant* condi-

tion further suggests a partner representation, as well as a greater weighting of the self

cost compared to the partner cost.

Fig. 5C and **Fig. 5D** show the semi-involuntary and voluntary visuomotor feedback

responses. We also found a significant interaction between self target and partner target

for semi-involuntary (F[1,47] = 78.66, p < 0.001) and voluntary (F[1,47] = 78.50, p <

0.001) visuomotor feedback responses. Follow-up mean comparisons showed the same

significant differences in both the semi-involuntary and voluntary visuomotor feedback

responses, as seen in the involuntary visuomotor feedback responses.

The involuntary, semi-involuntary, and voluntary visuomotor feedback responses in

each condition closely match the predictions of the Partner Representation & Weighted

Joint Cost model (compare **Fig. 4D** to **Fig. 5**). Remarkably, the results in **Experiment**

1 suggest that a partner representation and consideration of a partner's cost not only

influence voluntary behaviour, but also involuntary sensorimotor circuits.

Experiment 2 Visuomotor Feedback Responses

Here we show group level visuomotor feedback responses over time (**Fig. 6A**), and the

average visuomotor feedback response during the involuntary (180-230 ms),

Figure 6: Visuomotor Feedback Responses in Experiment 2. A) Visuomotor feedback response (y-axis) over time (x-axis), where 0 ms corresponds to the initial target jump. Solid lines represent the group average visuomotor feedback response for each condition. Shaded regions represent $\pm$ 1 standard error. Vertical grey lines separate involuntary (180 - 230 ms), semi-involuntary (230 - 300 ms), and voluntary (300-400 ms) visuomotor feedback responses. Average **B)** involuntary, **C)** semi-involuntary, and **D)** and voluntary visuomotor feedback response for each condition. Box and whisker plots show 25%, 50%, and 75% quartiles. **B)** Critically, a greater involuntary visuomotor feedback response in the *partner-relevant/self-irrelevant* condition compared to the *partner-irrelevant/self-irrelevant* condition (p < 0.001) suggests a partner representation and some consideration of the partner's cost.

semi-involuntary (230-300 ms), and voluntary (300-400 ms) epochs.

We found a significant interaction between self target and partner target (F[1,47]

= 20.88, p < 0.001) for involuntary visuomotor feedback responses in **Experiment 2**.

Follow-up mean comparisons again showed a significant increase in the visuomotor feed-

back response in the *partner-relevant/self-irrelevant* condition compared to the *partner-*

irrelevant/self-irrelevant condition (p < 0.001, $\hat{\theta}$ = 79.21). As shown in **Experiment 1**,

these **Experiment 2** results further support the idea that the involuntary sensorimotor

circuits have a partner representation and a consideration of the partner's cost.

Between the *partner-irrelevant/self-relevant* condition and the *partner-relevant/self-*

relevant conditions, we did not find a significant difference (p = 0.274, $\hat{\theta}$ = 53.69). Nev-

ertheless, the involuntary visuomotor feedback responses in each condition still most

closely matched the predictions of the Partner Representation & Weighted Joint Cost

model. Further, we also found a significant interaction between self target and part-

ner target for the semi-involuntary (F[1,47] = 68.82, p < 0.001) and voluntary (F[1,47] =

132.59, p < 0.001) visuomotor feedback responses. Aligning with the results from **Exper-**

iment 1, we found a significant difference between the *partner-irrelevant/self-relevant*

condition and *partner-relevant/self-relevant* condition for the semi-involuntary (**Fig. 6C**;

p < 0.001, $\hat{\theta}$ = 62.28) and voluntary (**Fig. 6D**; p < 0.001, $\hat{\theta}$ = 73.65) visuomotor feed-

back responses. Taken together, the visuomotor feedback responses in **Experiment**

1 and **Experiment 2** closely match the Partner Representation & Weighted Joint Cost

model predictions. Remarkably, the involuntary visuomotor feedback responses across

two experiments supports our hypothesis that a high-level partner representation and a

consideration of a partner's cost influences low-level involuntary sensorimotor circuits.

263 Discussion

Our primary finding across two experiments was that a partner representation and con-

sideration of a partner's cost influences involuntary visuomotor feedback responses. Specif-

ically, involuntary visuomotor feedback responses closely matched the hypothesis that

the sensorimotor system uses a partner representation and weighted joint cost, where

the self cost is prioritized more than the partner cost. Taken together, our empirical

results and computational modelling support the idea that a high-level partner repre-

sentation and a joint cost influences lower-level involuntary sensorimotor circuits.

In this paper, we demonstrated how a representation of a partner and consideration

of their costs influences rapid and involuntary visuomotor feedback responses during a

cooperative sensorimotor reaching task. In **Experiments 1 and 2**, we found that partic-

ipants displayed increased involuntary visuomotor feedback responses when there was

a relevant partner target and an irrelevant self target, compared to when both targets

were irrelevant. Aligned with model predictions, these findings suggest that involuntary

feedback responses reflect a partner representation and a joint cost. In **Experiment 1**,

we found a significant decrease in involuntary visuomotor feedback responses to cursor

jumps when both the self and partner target was relevant, compared to the condition

with an irrelevant partner target and relevant self target. The different involuntary vi-

suomotor feedback responses between these conditions suggests that the sensorimotor

system uses a partner representation and weighted joint cost to modulate involuntary

visuomotor feedback responses. Interestingly, this result suggests that the sensorimotor

system modulates involuntary visuomotor feedback responses based on a prediction of

a partner's control policy. Further, it highlights that high-level partner representations

modulate lower-level sensorimotor circuits and are rapidly expressed via involuntary vi-

suomotor feedback responses.

In **Experiment 1** and **Experiment 2** we found the same significant differences be-

tween conditions for the semi-involuntary and voluntary visuomotor feedback responses.

However, in **Experiment 2**, we did not see a decrease in involuntary visuomotor feed-

back responses to target jumps when both self and partner targets were relevant, com-

pared to an irrelevant partner target and relevant self target. One possibility for this

finding is that there may be longer visuomotor feedback response latencies to target

jumps compared to cursor jumps.[18,19,20] Interestingly, it may also be the case that visuo-

motor feedback responses to a self target jump are expressed at a different latency than

responses to a partner target jump.

Overall, we found greater involuntary visuomotor feedback responses for a relevant self target compared to an irrelevant self target. This finding aligns with single-person studies that examined how the relevancy of a mechanical or visual perturbation to the behavioural goal influences rapid feedback responses, prior to volitional control. Nashed and colleagues (2012) showed larger long-latency muscular responses (50-100 ms) to mechanical perturbations when reaching to a narrow (circular) relevant target compared to a wide (rectangular) irrelevant target.[6] Further, Franklin and colleagues (2008) showed greater involuntary visuomotor feedback responses to a relevant visual perturbation compared to an irrelevant visual perturbation.[17] Both of these prior studies suggest that the sensorimotor system can tune involuntary feedback responses based on higher-level task goals. Our novel experimental paradigm has extended these findings to understand how humans integrate their own goal with their partner's goal during jointly controlled actions. Importantly, we found that involuntary visuomotor processes can express not only an individual goal, but also an integrated representation of both the self and partner goals.

Optimal feedback control has been a powerful framework to understand how the nervous system selects movements.[11,12,21,22] Past work, including our own,[23] has extended optimal feedback control to human-human interaction by having two separate optimal feedback controllers interact.[24] In these works the control policy for each of the controllers was selected in isolation. That is, the controllers do not select a control policy using knowledge of the partner's control policy (i.e., partner representation). The dynamic game theory framework further extends the separate feedback controller approach by allowing each controller to select a control policy using a partner representation. This dynamic game theory framework has successfully been used to model human-robot[25] and human-human sensorimotor interactions.[26,27] The aforementioned studies have suggested people form a partner representation in their control policy to produce voluntary

movements. Critically, we are the first to our knowledge to measure a proxy of the control policy, assessing how a partner representation influences rapid and involuntary visuomotor feedback responses. Our dynamic game theory model supports the hypothesis that involuntary visuomotor feedback responses reflect a partner representation and joint cost. It would also be interesting to investigate whether other rapid feedback responses, such as the long-latency stretch response, can also express a partner representation.

Both the optimal feedback control and dynamic game theory frameworks view human movement as a process of minimizing a cost function. This cost function is designed such that the controller (i.e., sensorimotor system) achieves some goal state, such as accurately hitting a target, while minimizing an energetic cost. Not correcting for deviations along an irrelevant dimension reduces energetic cost. In our paper, we extended this concept to understand not only how the sensorimotor system considers its own self cost, but also a joint cost that considers both the self cost and partner cost. In both experiments we found increased involuntary visuomotor feedback responses in the relevant partner target and irrelevant self target condition compared to both targets being irrelevant. That is, we found that participant's visuomotor feedback responses reflected a consideration of not only the relevancy of their own self target (i.e, self cost), but also that of their partner (i.e., partner cost). This result suggests that involuntary visuomotor feedback responses reflect the sensorimotor system's willingness to sacrifice energy to help a partner.

Classic and contemporary theories of action selection, such as Gibson's theory of affordances[28] and the affordance competition hypothesis,[29] propose that the sensorimotor system selects movements based on opportunities for action that emerge from the fit between an individual's capabilities and surrounding environment. Our finding that humans sacrifice energetic cost to support a partner's goal extends this perspective by suggesting that the sensorimotor system may also consider "social affordances", which depend not only on one's own goals but also those of others. An interesting future

direction would be to explore how the overlap of the self and partner goals might influ-
ence the degree to which humans help one another during collaborative, cooperative,
and competitive sensorimotor interactions.

The nervous system can form representations of both self and others. Research
studying reaching movements for a single individual has shown that the nervous system
forms a representation of one's own limb dynamics[30,31,32] and environment,[16,33] which
are expressed prior to and following volitional control. Additionally, it has been well-
established that the human sensorimotor system can form representations of others.[7,34,35]
Ramnani and Miall (2004) showed evidence using fMRI that the human brain even has a
dedicated system to predict the actions of others.[36] Behavioural evidence for these part-
ner representations have been shown across cognitive[37,38] and perceptual[39,40] decision-
making, response time,[7] and reaching[1,27,41] tasks. Behaviourally, Schmitz and colleagues
(2017) observed that an obstacle in the partner's movement path influenced one's own
voluntary reach trajectory.[1] Computational and empirical work from Chackochan and
Sanguinetti (2019) suggested that humans use a representation of their partner to select
movement trajectories during a reaching task where they are haptically connected to
a partner.[27] While neural data, behavioural experiments, and computational modelling
have suggested that partner representations influence voluntary reaching movements,
to our knowledge none have examined whether a representation of others can be ex-
pressed at an involuntary timescale.

The neural basis of upper limb control has been well-studied. For the upper limb, neu-
ral recordings in monkeys have shown that activity in the primary motor cortex (M1) re-
flects visuospatial representations including target goals.[42] High-level visuospatial repre-
sentations can be rapidly expressed via the muscular long-latency reflex and involuntary
visuomotor feedback responses. These lower-level sensorimotor feedback responses are
prior to volitional control. The long-latency reflex involves a transcortical pathway with
contributions from likely both cortical and subcortical circuitry.[43,44] It has also been shown

that both cortical and subcortical (e.g., superior colliculus) regions are involved when responding to visual perturbations.[45,46,47,48] Collectively these studies suggest top-down projections from high-level cortical representations to lower-level sensorimotor circuits,[49] enabling fast and flexible feedback responses.

Just as the sensorimotor system forms representations of its own actions and goals, it has also been shown to represent the actions of others. Observing the actions of others increases neural activity in motor regions such as primary motor and the dorsal premotor cortex.[41,50,51,52,53] These so-called 'mirror neurons' may help the sensorimotor system understand the actions of others[54,55] (but see Hayes et al. (2010)[56] for an alternative perspective). Importantly, activation of primary motor and premotor regions have also been shown during the prediction of others' actions, even without directly observing the movement.[36] Other work has shown that the cerebellum, which uses a self representation (i.e., internal model) to predict future motor actions,[57,58,59] may also form an internal model of others to predict their future actions.[60,61] Therefore, the neural circuitry for the representations of others' actions and for the control of movement seems to be tightly linked.[62,63] In light of these findings, our work suggests that there is top-down modulation from high-level circuits involved with partner representations to lower-level sensorimotor circuitry. That is, the nervous system appears to leverage high-level partner representations in lower-level sensorimotor circuits to anticipate and respond to a partner's future actions. Future work could use neural recordings while non-human primates perform a cooperative sensorimotor interaction task to further understand how a representation of others might influence the control of movement. From an evolutionary perspective,[64,65] it would be interesting to know where along the phylogenetic history a high-level representation of others regulates lower-level sensorimotor circuits involved with rapid and involuntary feedback responses.

Across two experiments and a computational model, we showed that involuntary visuomotor feedback responses reflect a partner representation and consideration of a

404 partner's cost. Our novel results suggest that high-level partner representations influ-
405 ence lower-level involuntary sensorimotor circuitry. Our paradigm offers a powerful new
406 window to probe how human sensorimotor interactions are influenced by cognitive pro-
407 cesses, theory of mind, and social dynamics.

Methods

Participants

96 participants participated across two experiments. 24 pairs (48 individuals) partici-
pated in **Experiment 1** and 24 pairs (48 individuals) participated in **Experiment 2**. All
participants reported they were free from musculoskeletal injuries, neurological condi-
tions, or sensory impairments. In addition to a base compensation of $5.00, we informed
them they would receive a performance-based compensation of up to $5.00. Each par-
ticipant received the full $10.00 once they completed the experiment irrespective of their
performance. All participants provided written informed consent to participate in the ex-
periment and the procedures were approved by the University of Delaware's Institutional
Review Board.

Apparatus

For both experiments we used two end-point KINARM robots (**Fig. 1A**; BKIN Technolo-
gies, Kingston, ON). Each participant was seated on an adjustable chair in front of one of
the end-point robots. Each participant grasped the handle of a robotic manipulandum
and made reaching movements in the horizontal plane. A semi-silvered mirror blocked
the vision of the upper limb, and also reflected virtual images (e.g., targets, cursors) from
an LCD to the horizontal plane of hand motion. In all experiments the participant's own
(self) cursor was aligned with the position of their hand. Kinematic data were recorded
at 1,000 Hz and stored offline for data analysis.

Experimental Design

We designed two experiments where participants used knowledge of both their own and
partner's target to successfully complete a jointly coordinated reaching task. During both

experiments, each participant viewed a self cursor that was aligned with their hand and

another cursor that represented their partner's position. They also saw a center cursor at

the midpoint between their cursor and their partner's cursor. Finally, they also observed

both their own target and their partner's target. The center cursor and both targets were

laterally aligned to the center of each participant's screen. Both targets were 25 cm

forward from the start position.

Both participants began each trial with their hand placed 13 cm to the right of the

center cursor. Each participant observed their partner's cursor, which was reflected over

the center line that intersected the center cursor and the targets. Thus, both participants

viewed a mirrored position of their partner. By mirroring both partners, this allowed each

participant to view themselves on the right side of the center cursor and their partner on

the left side of the center cursor. Further, it allowed for control of the center cursor in a

smooth and intuitive manner as if their partner was sitting beside them.

The center cursor was at the midpoint between the participant's hands, except during

Experiment 1 perturbation and probe trials when the center cursor was laterally jumped

(see further below). The movement of each participant contributed to half the movement

of the center cursor. For example, if one participant moved forward 6 cm and their

partner did not move, then the center cursor would move 3 cm forward. Likewise, if

one participant moved 6 cm to the right and their partner did not move, then the center

cursor would move 3 cm to the right.

At the start of a trial, the robot guided each participant's self cursor to their respective

start circle. The white start circle (diameter 2 cm) was displayed 13 cm to the right of

the initial center cursor location for both participants. After a constant delay of 700

ms the partner cursor, center cursor, self target, and partner target appeared on the

screen (**Fig. 1A**). Then after a constant delay of 750 ms, participants heard a tone that

indicated they should begin their reach. Both participants in the pair were instructed to

move the center cursor into their self target. To complete a trial, each participant had to

stabilize the center cursor within their self target for 500 ms. Participants received timing

feedback based on the time between the start tone and completing the trial. Participants

received the message 'Good', 'Too Slow', or 'Too Fast' if they stabilized within their

self target between 1400 - 1600 ms, > 1600 ms, or <1400 ms respectively. They were

explicitly informed that their timing feedback depended on the center cursor entering

and stabilizing within *only* their own target. For example, if the center cursor entered and

stabilized within the participant's self target at 1500 ms, but entered and stabilized within

the partner target at 1700 ms, then the participant would receive "Good" feedback and

their partner would receive "Too Slow" feedback. Therefore, the instructions and timing

constraints did not enforce participants to work together.

The goal of **Experiment 1** and **Experiment 2** was to study how a representation

of a partner's goal influences involuntary visuomotor feedback responses. Therefore, in

experimental blocks we manipulated the width of both the self and partner goal to be

either narrow (1.05 cm) or wide (20 cm). The narrow target reflects a task-relevant goal

because a participant must correct for lateral deviations of the center cursor to success-

fully complete their task. The wide target reflects a task-irrelevant goal because a partic-

ipant does not have to correct for lateral deviations of the center cursor to successfully

complete their task. Both targets had a height of 1.25 cm and were aligned horizontally

and vertically throughout both experiments. Human pairs performed four blocked con-

ditions in a two-way, repeated measures experimental design: i) *partner-irrelevant/self-*

irrelevant ii) *partner-relevant/self-irrelevant* iii) *partner-irrelevant/self-relevant* iv) *partner-*

relevant/self-relevant (**Fig. 1B**). The order of the experimental conditions was fully coun-

terbalanced in both **Experiment 1** and **Experiment 2**.

For both experiments, participants first performed a familiarization block of trials,

and then 4 experimental blocks that were separated by a washout block. The self and

partner targets were 10 cm in width and 1.25 cm in height in both familiarization and

washout blocks. Participants performed 50 non-perturbation trials (see below) during

the familiarization block. They performed 25 non-perturbation trials during each of the

three washout blocks

Each human pair completed four experimental blocks, where for a block they ex-

perienced the i) *partner-irrelevant/self-irrelevant*, ii) *partner-relevant/self-irrelevant*, iii)

partner-irrelevant/self-relevant, or iv) *partner-relevant/self-relevant* condition. In the ex-

perimental blocks, participants experienced 81 non-perturbation trials, 40 perturbation

trials, and 30 probe trials.

Non-Perturbation Trials

493 During non-perturbation trials, the cursor center was always at the midpoint between

494 the human pair. There was neither center cursor (**Experiment 1**) nor target jumps (**Ex-**

495 **periment 2**).

Perturbation Trials

During perturbation trials within an experimental block, the center cursor (**Experiment**

1) or both targets (**Experiment 2**) jumped to either the left (20 trials) or right (20 trials)

once the center cursor crossed 25% of the distance to the goals (6.25 cm forward from the

start position; **Fig. 1C-D**). The cursor or target jump was a 3 cm linear shift in the lateral

position over 25 ms. The center cursor remained laterally displaced for the duration of

the trial. Thus, participants were required to correct for the center cursor or target jump

to successfully complete their task when they had a self-relevant target. However, they

would not have to correct for the center cursor or target jump to successfully complete

their task when they had a self-irrelevant target.

Probe Trials

During probe trials within an experimental block, the center cursor (**Experiment 1**) or

both targets (**Experiment 2**) jumped to either the left (10 trials) or the right (10 trials)

once the center cursor crossed 25% of the distance to the goals (6.25 cm forward from the

start position; **Fig. 1E-F**). We also included 10 null probe trials where the center cursor or

both targets did not jump. Here, both participants in the pair were constrained to a force

channel that allowed forward hand movement, but prevented lateral hand movement.

The center cursor or target jump was a 3 cm linear shift in the lateral position over 25 ms.

The center cursor or target remained displaced for 200 ms and then linearly shifted back

to the original lateral position over 25 ms. Critically, as a metric of visuomotor feedback

responses, we measured the lateral force participants applied against the channel in

response to center cursor or target jumps.

During an experimental block, the non-perturbation trials, perturbation trials, and

probe trials were randomly interleaved such that each set of 15 trials contained 8 non-

perturbation trials, 2 left perturbation trials, 2 right perturbation trials, 1 left probe trial, 1

right probe trial, and 1 neutral probe trial. Participants performed 10 sets of trials within

a block. We also ensured the first trial of an experimental condition was not a probe

trial by adding a non-perturbation trial to the start of each experimental condition. In

total, participants performed 729 reaches consisting of 50 non-perturbation trials in the

familiarization block, 75 non-perturbation trials across the three washout blocks, as well

as 480 non-perturbation trials, 240 perturbation trials, and 120 probe trials across the

four experimental blocks.

Dynamic Game Theory Model

We used a dynamic game theory model to predict movement behaviour and visuomotor

feedback responses of human pairs. Dynamic game theory is a multi-controller extension

of the typical optimal feedback control framework that describes a single controller.[11]

This framework has previously been used to model human movement during collabora-

tive tasks.[25,27,66] Here, we modelled our experiments as a linear-quadratic game with two

players (controllers).[67] Each controller had direct control of its own hand and attempted

to move the center cursor toward its own self target.

System Dynamics

537 Each hand in the linear-quadratic game was modelled as a point mass. Throughout,

538 the subscript i refers to each controller, where $i = \{1, 2\}$. We describe the model with

539 controller 1 as the self and controller 2 as the partner. The continuous-time dynamics of

540 the point mass representing the hand of controller 1 were as follows:

$$m\ddot{p}_1 = -b\dot{p}_1 + f_1 \tag{8}$$

$$\tau \dot{f}_1 = u_1 - f_1 \tag{9}$$

where m_1 is the mass of the hand, p_1 is the two-dimensional position vector of the point

mass, b is the viscous constant, f_1 is the two-dimensional controlled forces, and u_1 is

the two-dimensional control signal for controller 1. m was set to 1.5 kg, b was set to 0.1

N·s·m^{-1} and the time constant of the linear filter (τ) was set to 20 ms. These parameters

were identical for controller 1 and controller 2. The parameters were selected so that

the model visuomotor feedback response magnitudes closely matched the measured

visuomotor feedback response magnitudes.

Controllers 1 and 2 each move their hand and interact to move the center cursor (cc).

The dynamics of the center cursor are:

$$\dot{p}_{cc} = \frac{\dot{p}_1 + \dot{p}_2}{2}. \tag{10}$$

550 The state vector x is

$$x = [p_1,\ \dot{p}_1,\ f_1,\ p_2,\ \dot{p}_2,\ f_2,\ p_{cc},\ p_{target}]^T \tag{11}$$

551 where each element in the vector contains an x and y dimension. T is the transpose

552 operator. The system dynamics were transformed into a system of first order differential

553 equations and discretized. The linear-quadratic state space model is

$$x_{k+1} = Ax_k + B_1u_{1,k} + B_2u_{2,k}. \tag{12}$$

Here x_k is the state vector at time k and A is the dynamics matrix. B_i maps the control

vector $u_{i,k}$ of player i to muscle force $f_{i,k}$ at time k. A, B_1, and B_2 are fully defined in

Supplementary C.

State Feedback Design

Each controller receives delayed sensory feedback of its own hand position, velocity,

and force, as well as the partner's hand position and velocity. Further, each controller

receives delayed sensory feedback of the center cursor position and target position. To

incorporate sensory delays, we augmented the state vector with previous states:[23,68]

$$x_k^{aug} = [x_k, \ x_{k-1}, \ ... \, , x_{k-n_{\delta v}}]^T. \tag{13}$$

562 Here δv = 110 ms (corresponding to $n_{\delta v} = 11$ time steps when discretized) to reflect

563 the transmission delay associated with vision and aligned the model and experimental

564 visuomotor response onset times. The sensory states available to controller 1 are

$$y_{1,k} = C_1^{aug} x_k^{aug} + \omega_{1,k} \tag{14}$$

where y_1 is the vector of delayed state observations and $\omega_{1,k}$ is a sensory noise vector.

C_1^{aug} is an observation matrix designed to selectively observe some of the delayed states.

The observation matrices C_1^{aug} and C_2^{aug} and noise vector $\omega_{1,k}$ are fully defined in **Sup-**

plementary C. We drop the superscript aug to minimize extra notation going forward.

Like previous work, we used a linear Kalman filter to model participants sensory esti-

mates of the state variables. The posterior state estimate $\hat{x}_{1,k}$ of controller 1 is obtained

using an online filter of the form:

$$\hat{x}_{1,k} = \bar{x}_{1,k} + K_{1,k}(y_{1,k} - H_1 \bar{x}_{1,k}) \tag{15}$$

$$\bar{x}_{1,k} = A\hat{x}_{1,k-1} + B_1 u_{1,k} + B_2 u_{2,k}. \tag{16}$$

Here $\bar{x}_{1,k}$ is the prior prediction of the state. That is, we assume the sensorimotor sys-

tem obtains a prior prediction of the states using an accurate internal model of the state

dynamics, which includes a prediction of the partner's motor command. The prior pre-

diction uses the previous posterior estimate ($\hat{x}_{1,k-1}$), the efference copy (u_1), and the

prediction of the partner's motor command (u_2).

The prior prediction of the state is updated using sensory measurements to obtain

the posterior estimate $\hat{x}_1$ (**Eq. 15**). The sequence of Kalman gains K_1 and K_2 were

updated recursively (**Supplementary C**).

Control Design

The goal of each controller i is to move the state of the system from an initial state x_0 to a

target state x^{target} at the final time step N by each minimizing a quadratic cost functional

J_i:

$$J_1 = \frac{1}{2} \sum_{k=0}^{N-1} \left(x_k^T Q_1 x_k + u_{1,k}^T R_{11} u_{1,k} \right) + \frac{1}{2} x_N^T Q_{1,N} x_N \tag{17}$$

$$J_2 = \frac{1}{2} \sum_{k=0}^{N-1} \left(x_k^T Q_2 x_k + u_{2,k}^T R_{22} u_{2,k} \right) + \frac{1}{2} x_N^T Q_{2,N} x_N. \tag{18}$$

Here J_1 is the individual cost for controller 1 (e.g. self) and J_2 is the individual cost for controller 2 (e.g. partner). The quadratic costs penalize deviations from the target state at the final step ($Q_{i,N}$) and controller i's control signals (R_{ii}). We then define the joint cost functions as

$$J_1^{\alpha_1} = J_1 + \alpha_1 J_2 \tag{19}$$

$$J_2^{\alpha_2} = J_2 + \alpha_2 J_1, \tag{20}$$

where $\alpha_i \in [0, 1]$ determines the degree to which controller i considers their partner's costs.

The optimal control signal for controllers 1 and 2 is defined as

$$u_{1,k}^* = -F_{1,k} \hat{x}_{1,k} \tag{21}$$

$$u_{2,k}^* = -F_{2,k} \hat{x}_{2,k}, \tag{22}$$

where $\hat{x}_{i,k}$ is the posterior estimate and $F_{i,k}$ is the time-varying feedback gain for controller i. The feedback gains $F_{i,k}$, also known as the control policy, are the Nash equilibrium solution to the linear quadratic game described by **Eq. 11** and **Eqs. 16-19**.[67] See **Supplementary C** for details.

Modelling Different Control Policies

We tested four different control policies, each reflecting a hypothesis about how a partner representation and consideration of a partner's cost influences visuomotor feedback responses. In our modelling framework, a partner representation indicates knowledge of the partner's control policy. Further, we can also vary whether a controller considers only their own self cost, or both a self and partner cost (i.e., joint cost). We tested the following four models: i) No Partner Representation & Self Cost, ii) Partner Representation & Self Cost, iii) Partner Representation & Equal Joint Cost, and iv) Partner Representation

& Weighted Joint Cost.

The No Partner Representation & Self Cost model implies that the sensorimotor sys-

tem does not use a control policy that has a representation of a partner. Mathematically,

we set $F_{2,k} = 0$ for all t when calculating the feedback gains for controller 1. That is, if

there is no partner representation, then controller 1 does not account for the partner's

control policy when selecting its own control policy. Since there is no partner represen-

tation, the model can only consider a self cost (i.e., $\alpha_1 = 0$).

The Partner Representation & Self Cost model suggests that the sensorimotor system

uses a control policy that has a partner representation, but only considers a self cost. That

is, controller 1 will produce movements using knowledge of how their partner will move.

Further, controller 1 will only produce movements that lead to a minimal self cost, without

consideration of the partner's cost. A self cost is obtained by setting $\alpha_1 = 0$ in **Eq. 19**.

The Partner Representation & Equal Joint Cost model implies that the sensorimotor

system uses a control policy that has a partner representation, and equally weights the

self and partner costs. Here controller 1 will produce movements that uses knowledge

of how their partner will move. Further, controller 1 will produce movements that lead

to an equal minimization of both the self and partner cost. That is, one is willing to

potentially spend additional energy so that a partner reaches their goal. An equal joint

cost is obtained by setting $\alpha_1 = 1.0$ in **Eq. 19**.

The Partner Representation & Weighted Joint Cost model implies that the sensorimo-

tor system uses a control policy that has a partner representation, and partially weights

the partner cost. Again, controller 1 will produce movements that uses knowledge of

how their partner will move. However, controller 1 will produce movements that pri-

marily minimize the self cost and to a lesser extent the partner cost. That is, one will

mostly spend energy to reach their own goal, but will still spend some energy to help

their partner. A weighted joint cost that weighs the self cost higher than the partner cost

is obtained by setting $\alpha_1 = 0.5$ in **Eq. 19**.

Model Simulations

We simulated each of the self and partner target structures from the experiment: i) *partner-irrelevant/self-irrelevant*, ii) *partner-relevant/self-irrelevant*, iii) *partner-irrelevant/self-relevant*, and iv) *partner-relevant/self-relevant*. For relevant targets, we set the x-dimension of the center cursor position in the final state cost matrix $Q_{i,N}$ to 40000 for $i = \{1, 2\}$. That is, controller i incurs a cost and will correct for lateral deviations of the center cursor away from a relevant target. For irrelevant targets, we set the x-dimension of the center cursor position in the final state cost matrix $Q_{i,N}$ to 100 for $i = \{1, 2\}$. That is, controller i does not incur a cost for lateral deviations of the center cursor if their target is irrelevant. For a full description of Q_1 and Q_2, see **Supplementary C**

We simulated 100 perturbation trials per condition to predict the position trajectories. Perturbation trials were simulated by jumping the center cursor laterally to the left by 3 cm once the center cursor reached 25% of the forward distance to the target.

We also simulated 100 probe trials per condition to predict visuomotor feedback responses. Probe trials were simulated by jumping the center cursor 3 cm laterally for 250 ms, then jumping it back to the original lateral position. To simulate a force channel, we set the x-force element in the B_1 and B_2 matrices to 0. Thus, the controllers could only move the center cursor in the forward dimension. We were able to calculate the applied force for controller 1 in the lateral dimension using the original B_1 matrix. That is, the applied force traces shown in **Fig. 4** is $B_1 u_1$ in the x-dimension over time. Aligned with the literature on involuntary visuomotor feedback responses, we calculated the average feedback response from the model during the 180 - 230 ms epoch.

Data Analysis

We analyzed the results from the non-perturbation, perturbation, and probe trials for the experimental conditions. We recorded both hand positions and the center cursor position during all trials, as well as the force applied by the robot to the hand during the probe trials. All kinematic and kinetic data were filtered with a 5th-order, low-pass

657 Butterworth filter with a 14-hz cutoff frequency.

Visuomotor Feedback Responses

The recorded forces applied by both participants in the pair during visual probe trials

were time-aligned with the cursor or target jump onset. The delay of the LCD for presen-

tation of visual feedback was determined to be 42 ms. Visuomotor feedback responses

in this study are presented relative to the onset of the actual perturbation time. That is,

the LCD delay has been taken into account such that visuomotor feedback responses

were aligned relative to the time the visual signal was actually presented to participants

on their display. We define the visuomotor feedback response (N) as the difference

between the recorded force during a left cursor probe and a right cursor probe.[17] To

investigate the involuntary visuomotor feedback response, we calculated the average

force response for each participant during the 180 - 230 ms time window.[17] We also cal-

culated the average force response during the 230 - 300 ms window and 300 - 400 ms

window. The 230 - 300 ms window may contain a mixture of involuntary and voluntary

responses, which we term as the semi-involuntary visuomotor feedback response. The

300 - 400 ms window is the voluntary visuomotor feedback response.

Final Lateral Hand Deviation

We calculated the final lateral hand deviation as a metric of a participant's voluntary

corrective response to perturbation trials. Final lateral hand position was determined as

the x-position of each participant at the end of each trial. To calculate final lateral hand

deviation, we took the difference between the average final lateral hand position during

non-perturbation trials and the average final lateral hand position during perturbation

trials (see **Supplementary B**).

Statistical Analysis

For both experiments, we used a 2 (Self Irrelevant or Self Relevant) x 2 (Partner Irrele-

vant or Partner Relevant) repeated-measures ANOVA for each dependent variable. We

followed up the omnibus tests with mean comparisons using nonparametric bootstrap

hypothesis tests (n = 1,000,000).[69,70,71,72,73] Mean comparisons were Holm-Bonferroni

corrected to account for multiple comparisons. We computed the common language

effect sizes ($\hat{\theta}$) for all mean comparisons. Significance threshold was set at α = 0.05.

References

1. Schmitz, L., Vesper, C., Sebanz, N., & Knoblich, G. (2017). Co-Representation of Others' Task Constraints in Joint Action. *Journal of Experimental Psychology: Human Perception and Performance*, 43 (8), 1480–1493.

2. Vesper, C., Schmitz, L., & Knoblich, G. (2017). Modulating Action Duration to Establish Nonconventional Communication. *Journal of Experimental Psychology: General*, 146 (12), 1722–1737.

3. Kourtis, D., Knoblich, G., Woźniak, M., & Sebanz, N. (2014). Attention Allocation and Task Representation during Joint Action Planning. *Journal of Cognitive Neuroscience*, 26 (10), 2275–2286.

4. Vesper, C., van der Wel, R. P. R. D., Knoblich, G., & Sebanz, N. (2011). Making Oneself Predictable: Reduced Temporal Variability Facilitates Joint Action Coordination. *Experimental Brain Research*, 211 (3-4), 517–530.

5. Török, G., Stanciu, O., Sebanz, N., & Csibra, G. (2021). Computing Joint Action Costs: Co-Actors Minimize the Aggregate Individual Costs in an Action Sequence. *Open Mind* , 1–13.

6. Nashed, J. Y., Crevecoeur, F., & Scott, S. H. (2012). Influence of the Behavioral Goal and Environmental Obstacles on Rapid Feedback Responses. *Journal of Neurophysiology*, 108 (4), 999–1009.

7. Sebanz, N., Knoblich, G., & Prinz, W. (2003). Representing Others' Actions: Just like One's Own? *Cognition*, 88 (3), 11–21.

8. Vesper, C., Schmitz, L., Safra, L., Sebanz, N., & Knoblich, G. (2016). The Role of Shared Visual Information for Joint Action Coordination. *Cognition*, 153 , 118–123.

9. Leibfried, F., Grau-Moya, J., & Braun, D. A. (2015). Signaling Equilibria in Sensorimotor Interactions. *Cognition*, 141 , 73–86.

10. Kourtis, D., Woźniak, M., Sebanz, N., & Knoblich, G. (2019). Evidence for We-Representations during Joint Action Planning. *Neuropsychologia*, 131 (April), 73–83.

11. Todorov, E., & Jordan, M. I. (2002). Optimal Feedback Control as a Theory of Motor Coordination. *Nature Neuroscience*, 5 (11), 1226–1235.

12. Scott, S. H. (2004). Optimal Feedback Control and the Neural Basis of Volitional Motor Control. *Nature Reviews Neuroscience*, 5 (7), 532–544.

13. Tanis, D., Calalo, J. A., Cashaback, J. G. A., & Kurtzer, I. L. (2023). Accuracy and Effort Costs Together Lead to Temporal Asynchrony of Multiple Motor Commands. *Journal of Neurophysiology*, 129 (1), 1–6.

14. Knill, D. C., Bondada, A., & Chhabra, M. (2011). Flexible, Task-Dependent Use of Sensory Feedback to Control Hand Movements. *The Journal of Neuroscience*, 31 (4), 1219–1237.

15. Calalo, J. A., Roth, A. M., Lokesh, R., Sullivan, S. R., Wong, J. D., Semrau, J. A., & Cashaback, J. G. A. (2023). The Sensorimotor System Modulates Muscular Co-Contraction Relative to Visuomotor Feedback Responses to Regulate Movement Variability. *Journal of Neurophysiology*, 129 (4), 751–766.

16. Franklin, S., Wolpert, D. M., & Franklin, D. W. (2017). Rapid Visuomotor Feedback Gains Are Tuned to the Task Dynamics. *Journal of Neurophysiology*, 118 (5), 2711–2726.

17. Franklin, D. W., & Wolpert, D. M. (2008). Specificity of Reflex Adaptation for Task-Relevant Variability. *The Journal of Neuroscience*, 28 (52), 14165–14175.

18. Scott, S. H. (2016). A Functional Taxonomy of Bottom-Up Sensory Feedback Processing for Motor Actions. *Trends in Neurosciences*, 39 (8), 512–526.

19. Smeets, J., & Brenner, E. (2003). Fast Corrections of Movements with a Computer Mouse. *Spatial Vision*, 16 (3), 365–376.

20. Dimitriou, M., Wolpert, D. M., & Franklin, D. W. (2013). The Temporal Evolution of Feedback Gains Rapidly Update to Task Demands. *Journal of Neuroscience*, 33 (26), 10898–10909.

21. Todorov, E. (2004). Optimality Principles in Sensorimotor Control. *Nature Neuroscience*, 7 (9), 907–915.

22. Calalo, J. A., Ngo, T. T., Sullivan, S. R., Strand, K., Buggeln, J. H., Lokesh, R., Roth, A. M., Carter, M. J., Kurtzer, I. L., & Cashaback, J. G. (2025). Online Movements Reflect Ongoing Deliberation. *The Journal of Neuroscience* , e1913242025.

23. Lokesh, R., Sullivan, S. R., St. Germain, L., Roth, A. M., Calalo, J. A., Buggeln, J., Ngo, T., Marchhart, V. R. F., Carter, M. J., & Cashaback, J. G. A. (2023). Visual Accuracy Dominates over Haptic Speed for State Estimation of a Partner during Collaborative Sensorimotor Interactions. *Journal of Neurophysiology*, 130 (1), 23–42.

24. Takagi, A., Usai, F., Ganesh, G., Sanguineti, V., & Burdet, E. (2018). Haptic Communication between Humans Is Tuned by the Hard or Soft Mechanics of Interaction. *PLoS Computational Biology*, 14 (3), 1–17.

25. Li, Y, Carboni, G, Gonzalez, F, Campolo, D, & Burdet, E (2019). Differential Game Theory for Versatile Physical Human–Robot Interaction. 1 ,

26. De Vicariis, C., Chackochan, V. T., Bandini, L., Ravaschio, E., & Sanguineti, V. (2024). Computational Joint Action: Dynamical Models to Understand the Development of Joint Coordination. *PLOS Computational Biology*, 20 (10), ed. by Zhu, L.: e1011948.

27. Chackochan, V. T., & Sanguineti, V. (2019). Incomplete Information about the Partner Affects the Development of Collaborative Strategies in Joint Action. *PLoS Computational Biology*, 15 (12), 1–23.

28. Gibson, J. J. (2014). *The Theory of Affordances:(1979)*. New York: Routledge.

29. Cisek, P. (2007). Cortical Mechanisms of Action Selection: The Affordance Competition Hypothesis. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 362 (1485), 1585–1599.

30. Kurtzer, I. L., Pruszynski, J. A., & Scott, S. H. (2008). Long-Latency Reflexes of the Human Arm Reflect an Internal Model of Limb Dynamics. *Current Biology*, 18 (6), 449–453.

31. Miall, R. C., & King, D. (2008). State Estimation in the Cerebellum. *Cerebellum*, 7 (4), 572–576.

32. Lillicrap, T. P., & Scott, S. H. (2013). Preference Distributions of Primary Motor Cortex Neurons Reflect Control Solutions Optimized for Limb Biomechanics. *Neuron*, 77 (1), 168–179.

33. Cothros, N., Wong, J. D., & Gribble, P. L. (2006). Are There Distinct Neural Representations of Object and Limb Dynamics? *Experimental Brain Research*, 173 (4), 689–697.

34. Sebanz, N., & Knoblich, G. (2021). Progress in Joint-Action Research. *Current Directions in Psychological Science*, 30 (2), 138–143.

35. Sebanz, N., & Knoblich, G. (2009). Prediction in Joint Action: What, When, and Where. *Topics in Cognitive Science*, 1 (2), 353–367.

36. Ramnani, N., & Miall, R. C. (2004). A System in the Human Brain for Predicting the Actions of Others. *Nature Neuroscience*, 7 (1), 85–90.

37. Xiang, Y., Vélez, N., & Gershman, S. J. (n.d.). Collaborative Decision Making Is Grounded in Representations of Other People's Competence and Effort , ().

38. Bicho, E., Erlhagen, W., Louro, L., & Costa E Silva, E. (2011). Neuro-Cognitive Mechanisms of Decision Making in Joint Action: A Human–Robot Interaction Study. *Human Movement Science*, 30 (5), 846–868.

39. Atmaca, S., Sebanz, N., & Knoblich, G. (2011). The Joint Flanker Effect: Sharing Tasks with Real and Imagined Co-Actors. *Experimental Brain Research*, 211 (3), 371–385.

40. Bahrami, B., Olsen, K., Latham, P. E., Roepstorff, A., Rees, G., & Frith, C. D. (2010). Optimally Interacting Minds. *Science*, 329 (5995), 1081–1085.

41. Yoshida, K., Saito, N., Iriki, A., & Isoda, M. (2011). Representation of Others' Action by Neurons in Monkey Medial Frontal Cortex. *Current Biology*, 21 (3), 249–253.

42. Pruszynski, J. A., Kurtzer, I., & Scott, S. H. (2008). Rapid Motor Responses Are Appropriately Tuned to the Metrics of a Visuospatial Task. *Journal of Neurophysiology*, 100 (1), 224–238.

43. Pruszynski, J. A., Omrani, M., & Scott, S. H. (2014). Goal-Dependent Modulation of Fast Feedback Responses in Primary Motor Cortex. *The Journal of Neuroscience*, 34 (13), 4608–4617.

44. Pruszynski, J. A., Kurtzer, I., Nashed, J. Y., Omrani, M., Brouwer, B., & Scott, S. H. (2011). Primary Motor Cortex Underlies Multi-Joint Integration for Fast Feedback Control. *Nature*, 478 (7369), 387–390.

45. Day, B. L. (2001). Evidence for Subcortical Involvement in the Visual Control of Human Reaching. *Brain*, 124 (9), 1832–1840.

46. Corneil, B. D., & Munoz, D. P. (2014). Overt Responses during Covert Orienting. *Neuron*, 82 (6), 1230–1243.

47. Pruszynski, J. A., Lillicrap, T. P., & Scott, S. H. (2010). Complex Spatiotemporal Tuning in Human Upper-Limb Muscles. *Journal of Neurophysiology*, 103 (1), 564–572.

48. Kozak, R. A., & Corneil, B. D. (2021). High-Contrast, Moving Targets in an Emerging Target Paradigm Promote Fast Visuomotor Responses during Visually Guided Reaching. *Journal of Neurophysiology*, 126 (1), 68–81.

49. Contemori, S., Loeb, G. E., Corneil, B. D., Wallis, G., & Carroll, T. J. (2021). The Influence of Temporal Predictability on Express Visuomotor Responses. *Journal of Neurophysiology*, 125 (3), 731–747.

50. Kilner, J., & Lemon, R. (2013). What We Know Currently about Mirror Neurons. *Current Biology*, 23 (23), R1057–R1062.

51. Cook, R., Bird, G., Catmur, C., Press, C., & Heyes, C. (2014). Mirror Neurons: From Origin to Function. *Behavioral and Brain Sciences*, 37 (2), 177–192.

52. Cattaneo, L., & Rizzolatti, G. (2009). The Mirror Neuron System. *Archives of Neurology*, 66 (5),

53. Bruni, S., Gerbella, M., Bonini, L., Borra, E., Coudé, G., Ferrari, P. F., Fogassi, L., Maranesi, M., Rodà, F., Simone, L., Serventi, F. U., & Rozzi, S. (2017). Cortical and Subcortical Connections of Parietal and Premotor Nodes of the Monkey Hand Mirror Neuron Network. *Brain Structure and Function* ,

54. Rizzolatti, G., Cattaneo, L., Fabbri-Destro, M., & Rozzi, S. (2014). Cortical Mechanisms Underlying the Organization of Goal-Directed Actions and Mirror Neuron-Based Action Understanding. *Physiological Reviews*, 94 (2), 655–706.

55. Umiltà, M., Kohler, E., Gallese, V., Fogassi, L., Fadiga, L., Keysers, C., & Rizzolatti, G. (2001). I Know What You Are Doing. *Neuron*, 31 (1), 155–165.

56. Heyes, C. (2010). Where Do Mirror Neurons Come From? *Neuroscience & Biobehavioral Reviews*, 34 (4), 575–583.

57. Kawato, M. (1999). Internal Models for Motor Control and Trajectory Planning. *Current Opinion in Neurobiology*, 9 (6), 718–727.

58. Wolpert, D. M., Miall, R., & Kawato, M. (1998). Internal Models in the Cerebellum. *Trends in Cognitive Sciences*, 2 (9), 338–347.

59. Ebner, T. J., & Pasalar, S. (2008). Cerebellum Predicts the Future Motor State. *The Cerebellum*, 7 (4), 583–588.

60. Sokolov, A. A., Miall, R. C., & Ivry, R. B. (2017). The Cerebellum: Adaptive Prediction for Movement and Cognition. *Trends in Cognitive Sciences*, 21 (5), 313–332.

61. Sokolov, A. A. (2018). The Cerebellum in Social Cognition. *Frontiers in Cellular Neuroscience*, 12 ,

62. Miall, R. C. (2003). Connecting Mirror Neurons and Forward Models: *NeuroReport*, 14 (17), 2135–2137.

63. Wolpert, D. M., Doya, K., & Kawato, M. (2003). A Unifying Computational Framework for Motor Control and Social Interaction. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 358 (1431), 593–602.

64. Cisek, P. (2022). Evolution of Behavioural Control from Chordates to Primates. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 377 (1844),

65. —   (2019). Resynthesizing Behavior through Phylogenetic Refinement. *Attention, Perception, & Psychophysics*, 81 (7), 2265–2287.

66. De Vicariis, C., Chackochan, V. T., & Sanguineti, V. (2022). Game Theory and Partner Representation in Joint Action: Toward a Computational Theory of Joint Agency. *Phenomenology and the Cognitive Sciences* ,

67. Başar, T., & Olsder, G. J. (1999). *Dynamic Non-Cooperative Game Theory*. 2nd. SIAM's Classics in Applied Mathematics.

68. Crevecoeur, F., Sepulchre, R., Thonnard, J.-L., & Lefèvre, P. (2011). Improving the State Estimation for Optimal Control of Stochastic Processes Subject to Multiplicative Noise. *Automatica*, 47 (3), 591–596.

69. Cashaback, J. G. A., Lao, C. K., Palidis, D. J., Coltman, S. K., McGregor, H. R., & Gribble, P. L. (2019). The Gradient of the Reinforcement Landscape Influences Sensorimotor Learning. *PLOS Computational Biology*, 15 (3), ed. by Haith, A. M.: e1006839.

70. Lokesh, R., Sullivan, S., Calalo, J. A., Roth, A., Swanik, B., Carter, M. J., & Cashaback, J. G. A. (2022). Humans Utilize Sensory Evidence of Others' Intended Action to Make Online Decisions. *Scientific Reports*, 12 (1), 8806.

71. Roth, A. M., Lokesh, R., Tang, J., Buggeln, J. H., Smith, C., Calalo, J. A., Sullivan, S. R., Ngo, T., Germain, L. S., Carter, M. J., & Cashaback, J. G. (2024). Punishment Leads to Greater Sensorimotor Learning But Less Movement Variability Compared to Reward. *Neuroscience*, 540 , 12–26.

72. Roth, A. M., Calalo, J. A., Lokesh, R., Sullivan, S. R., Grill, S., Jeka, J. J., Van Der Kooij, K., Carter, M. J., & Cashaback, J. G. A. (2023). Reinforcement-Based Processes Actively Regulate Motor Exploration along Redundant Solution Manifolds. *Proceedings of the Royal Society B: Biological Sciences*, 290 (2009), 20231475.

73. Cashaback, J. G. A., McGregor, H. R., Mohatarem, A., & Gribble, P. L. (2017). Dissociating Error-Based and Reinforcement-Based Loss Functions during Sensorimotor Learning. *PLOS Computational Biology*, 13 (7), ed. by Faisal, A. A.: e1005623.

Supplementary A: Target Jump Trajectories

Supplementary Figure 1: Model and Experimental Hand and Center Cursor Trajectories. Predicted hand and center cursor positions during right target jumps for each condition and model: **A-D)** No Partner Representation & Self Cost, **E-H)** Partner Representation & Self Cost, **I-L)** Partner Representation & Equal Joint Cost, and **M-P)** Partner Representation & Weighted Joint Cost. Collectively, the self cursor in models with only a self cost do not laterally deviate to correct for the cursor jump in the *partner-relevant/self-irrelevant* condition. In contrast, the self cursor in models that consider a self and partner cost laterally deviate to correct for the cursor jump in the *partner-relevant/self-irrelevant* condition. **Q-T)** Individual hand and center cursor positions of an exemplar pair for each condition in **Experiment 2**. Thin traces represent each trial. Thick traces represent the average across trials for the human pair. **U-X)** Group average hand and center cursor positions in **Experiment 2**. Traces represent the mean and shaded regions reflect ±1 standard error of the mean. The group average behaviour in **Experiment 2** closely aligns with the Partner Representation & Weighted Joint Cost model, suggesting that voluntary behaviour reflects a partner representation and consideration of a partner's cost.

Supplementary B: Final Lateral Hand Deviation

We calculated final lateral hand deviation for each participant as the average absolute difference between the endpoint hand position on regular trials and perturbation trials. **Supplementary Fig. 2** shows the predicted final lateral hand deviation from each of the four models. **Supplementary Fig. 3** shows the final lateral hand deviation in **Experiment 1** (**Supplementary Fig. 3A**) and **Experiment 2** (**Supplementary Fig. 3B**). We found a significant interaction between partner target and self target for both **Experiment 1** ($F[1,47] = 60.99$, $p < 0.001$) and **Experiment 2** ($F[1,47] = 42.66$, $p < 0.001$). Follow-up mean comparisons showed the same significant differences for **Experiment 1** and **Experiment 2**. The empirical results of final lateral hand position most closely match the Partner Representation & Weighted Joint Cost model, suggesting that participants form a partner representation and consider a weighted joint cost.

Supplementary Figure 2: Model Final Hand Lateral Deviation. Final lateral hand deviation for **A)** No Partner Representation & Self Cost **B)** Partner Representation & Self Cost **C)** Partner Representation & Equal Joint Cost **D)** Partner Representation & Weighted Joint Cost. The final lateral hand deviation was calculated as the mean of the absolute value of the difference between the final hand position on non-perturbation trials and the final hand position on perturbation trials.

Supplementary Figure 3: Experimental Final Hand Lateral Deviation. Final lateral hand deviation for **A)** Experiment 1 and **B)** Experiment 2. The final lateral hand deviation was calculated as the mean of the absolute value of the difference between the final hand position on non-perturbation trials and the final hand position on perturbation trials. We saw significant differences between each of our statistical comparisons for both **Experiment 1** and **Experiment 2**. The results for both experiments closely match the Partner Representation & Weighted Joint Cost model (**Supplementary Fig. 2D**), showing that voluntary behaviour considers a partner representation and a weighted joint cost.

¹⁴ # Supplementary C: Modelling

¹⁵ ## Linear Quadratic Game

¹⁶ As a reminder, we modelled our task as a linear quadratic game of the form

$$x_{k+1} = Ax_k + B_1u_{1,k} + B_2u_{2,k} + \Sigma_u. \tag{1}$$

¹⁷ Here the subscripts 1 and 2 respectively refers to controller 1 and 2, representing a pair
¹⁸ of participants in our task. x_k is the state (e.g., position) of the system at time step k, A
¹⁹ represents the task dynamics, u_1 and u_2 are the control signals, and B_1 and B_2 converts
²⁰ the control signals to a force that produces movement. Σ_u is a covariance matrix that
²¹ inputs additive noise to the system, representing noisy control signals (defined further
²² below). Throughout, we describe the model with controller 1 as the self and controller
²³ 2 as the partner.

²⁴ Controller 1 and 2 select their own control signal u_1^* or u_2^*, which considers their re-
²⁵ spective costs. We can define an individual cost function J_1 and J_2 as:

$$J_1 = \frac{1}{2} \sum_{k=0}^{N-1} \left(x_k^\mathsf{T} Q_{1,k} x_k + u_{1,k}^\mathsf{T} R_{11} u_{1,k} \right) + \frac{1}{2} x_N^\mathsf{T} Q_{1,N} x_N \tag{2}$$

$$J_2 = \frac{1}{2} \sum_{k=0}^{N-1} \left(x_k^\mathsf{T} Q_{2,k} x_k + u_{2,k}^\mathsf{T} R_{22} u_{2,k} \right) + \frac{1}{2} x_N^\mathsf{T} Q_{2,N} x_N. \tag{3}$$

²⁶ Here J_1 is the individual cost for controller 1 (e.g., self) and J_2 is the individual cost for
²⁷ controller 2 (e.g., partner). N is the final step, which represents the end of a trial. The
²⁸ term Q penalizes deviations of the center cursor relative to each target. We modelled i) a
²⁹ task-relevant target using a higher value of Q, and ii) a task-irrelevant target using a lower
³⁰ value of Q. The term R_{ii} penalizes controller i's control signals, which can be thought of
³¹ as an energetic cost. See further below and **Table 1** for the fully defined matrices Q and

32 R. We define a joint cost function as:

$$J_1^{\alpha_1} = J_1 + \alpha_1 J_2 \tag{4}$$

$$J_2^{\alpha_2} = J_2 + \alpha_2 J_1, \tag{5}$$

33 where $\alpha_i \in [0, 1]$ determines the degree to which controller i considers their partner's

34 cost function. Specifically, the term α_i was applied to both the partner's state cost and

35 energetic cost:

$$Q_{1,k}^{\alpha_1} = max(Q_{1,k}, \alpha_1 Q_{2,k}) \tag{6}$$

$$Q_{2,k}^{\alpha_2} = max(Q_{2,k}, \alpha_2 Q_{1,k}) \tag{7}$$

$$R_{12} = \alpha_1 R_{11} \tag{8}$$

$$R_{21} = \alpha_2 R_{22}. \tag{9}$$

$Q_1^{\alpha_1}$ reflects how much controller 1 considers controller 2's state cost (i.e., controller 1's

partner stabilizing the center cursor in the partner target). $Q_2^{\alpha_2}$ reflects how much con-

troller 2 considers controller 1's state cost (i.e., controller 2's partner stabilizing the center

cursor in the partner target). Specifically, we reasoned that each controller would only

consider their partner's state cost if their partner's state cost was higher (i.e. higher value

of an element in Q) . We implemented this logic with the max function in **Eqs. 6-7**.

That is, for controller 1, if the self target was relevant then $Q_{1,k}^{\alpha_1} = Q_{1,k}$ and if the self

target was irrelevant and partner target was relevant then $Q_{1,k}^{\alpha_1} = \alpha Q_{2,k}$. Additionally, R_{12}

reflects how much controller 1 considers controller 2's energetic cost of movement by

multiplying alpha by its own energetic cost. Likewise, R_{21} reflects how much controller

2 considers controller 1's energetic cost of movement. We can rewrite the joint cost

functions in **Eqs. 4-5** in the quadratic form as:

$$J_1^{\alpha_1} = \frac{1}{2} \sum_{k=0}^{N-1} \left(x_k^\mathsf{T} Q_{1,k}^{\alpha_1} x_k + u_{1,k}^\mathsf{T} R_{11} u_{1,k} + u_{2,k}^\mathsf{T} R_{12} u_{2,k} \right) + \frac{1}{2} x_N^\mathsf{T} Q_{1,N}^{\alpha_1} x_N \tag{10}$$

$$J_2^{\alpha_2} = \frac{1}{2} \sum_{k=0}^{N-1} \left(x_k^\mathsf{T} Q_{2,k}^{\alpha_2} x_k + u_{2,k}^\mathsf{T} R_{22} u_{2,k} + u_{1,k}^\mathsf{T} R_{21} u_{1,k} \right) + \frac{1}{2} x_N^\mathsf{T} Q_{2,N}^{\alpha_2} x_N. \tag{11}$$

48 **Linear Quadratic Game - Matrices**

$$x = \begin{bmatrix} p_{1,x} & v_{1,x} & f_{1,x} & p_{1,y} & v_{1,y} & f_{1,y} & p_{2,x} & v_{2,x} & f_{2,x} & p_{2,y} & v_{2,y} & f_{2,y} & p_{cc,x} & p_{cc,y} & p_{ct,x} & p_{ct,y} \end{bmatrix}^\mathsf{T}$$

$$x_0 = \begin{bmatrix} 0.13 & 0 & 0 & 0 & 0 & 0 & -0.13 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0.25 \end{bmatrix}^\mathsf{T}$$

49 x_0 reflects the initial state at the start of each simulation, matching the experimental
50 design.

$$A = \begin{bmatrix}
0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & \frac{-b}{m} & \frac{1}{m} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & \frac{-1}{\tau} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & \frac{-b}{m} & \frac{1}{m} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & \frac{-1}{\tau} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & \frac{-b}{m} & \frac{1}{m} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \frac{-1}{\tau} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \frac{-b}{m} & \frac{1}{m} & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \frac{-1}{\tau} & 0 & 0 & 0 & 0 \\
0 & 0.5 & 0 & 0 & 0 & 0 & 0 & 0.5 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0.5 & 0 & 0 & 0 & 0 & 0 & 0.5 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0
\end{bmatrix}$$

$$B_1 = \begin{bmatrix} 0 & 0 & \frac{1}{\tau} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & \frac{1}{\tau} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}^\mathsf{T}$$

$$B_2 = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \frac{1}{\tau} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \frac{1}{\tau} & 0 & 0 & 0 & 0 \end{bmatrix}^{\mathsf{T}}$$

$$\Sigma_u = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & \sigma_u^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & \sigma_u^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_u^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_u^2 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}$$

$$Q_{1,k} = 0_{17\times17}, \; k = [0, ..., N-1]$$

$$Q_{1,N} = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & w_v & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & w_f & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & w_y & 0 & 0 & 0 & 0 & 0 & -w_y & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & w_v & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & w_f & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & -w_y & 0 & 0 & 0 & 0 & 0 & w_y & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & w_{1,cc_x} & 0 & -w_{1,cc_x} & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & w_{cc_y} & 0 & -w_{cc_y} \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{1,cc_x} & 0 & w_{1,cc_x} & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{cc_y} & 0 & w_{cc_y} \end{bmatrix}$$

$$Q_{2,k} = 0_{17\times17}, \; k = [0, ..., N-1]$$

$$Q_{2,N} = \begin{bmatrix}
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & w_y & 0 & 0 & 0 & 0 & 0 & -w_y & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & w_v & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & w_f & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & -w_y & 0 & 0 & 0 & 0 & 0 & w_y & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & w_v & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & w_f & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & w_{2,cc_x} & 0 & -w_{2,cc_x} & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & w_{cc_y} & 0 & -w_{cc_y} \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{2,cc_x} & 0 & w_{2,cc_x} & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -w_{cc_y} & 0 & w_{cc_y}
\end{bmatrix}$$

57   Writing out xQ_ix from the cost function J_i gives the state cost:

$$StateCost_1 = w_v * (v_{1,x}^2 + v_{1,y}^2) + w_f * (f_{1,x}^2 + f_{1,y}^2)$$

$$+ w_y * (p_{1,y} - p_{2,y})^2 + w_{1,cc_x} * (p_{cc,x} - p_{ct,x})^2 + w_{cc_y} * (p_{cc,y} - p_{ct,y})^2$$

$$StateCost_2 = w_v * (v_{2,x}^2 + v_{2,y}^2) + w_f * (f_{2,x}^2 + f_{2,y}^2)$$

$$+ w_y * (p_{1,y} - p_{2,y})^2 + w_{2,cc_x} * (p_{cc,x} - p_{ct,x})^2 + w_{cc_y} * (p_{cc,y} - p_{ct,y})^2$$

58   The control costs for controller 1 and controller 2 are:

$$R_{11} = \begin{bmatrix} r & 0 \\ 0 & r \end{bmatrix} \qquad R_{22} = \begin{bmatrix} r & 0 \\ 0 & r \end{bmatrix}.$$

59   Note that all the parameter weightings for the state and control costs are held constant

60   across all experimental conditions except for w_{1,cc_x} and w_{2,cc_x} which reflected the width

61   of the target. For values of all parameters, see **Table 1**.

62 Control Policy

63 The optimal control signal for controller 1 ($u^*_{1,k}$) and controller 2 ($u^*_{1,k}$) is determined by

64 the time-varying feedback gains F_1 and F_2 that minimize the joint cost function $J^{\alpha_1}_1$ and

65 $J^{\alpha_2}_2$ respectively:

$$u^*_{1,k} = -F_{1,k}\hat{x}_{1,k} \tag{12}$$

$$u^*_{2,k} = -F_{2,k}\hat{x}_{2,k} \tag{13}$$

66 Here, $\hat{x}_{i,k}$ for $i = \{1, 2\}$ is controller i's posterior estimate of the state (see **Methods** in the

67 main manuscript). The feedback gains F_1 and F_2 constitute a Nash equilibrium solution

68 to the linear quadratic game defined above (from Basar and Olsder Chapter 6, Corollary

69 6.1):[1]

$$F_{1,k} = (R_{11} + B_1^\mathsf{T} P_{1,k} B_1)^{-1}(B_1^\mathsf{T} P_{1,k} A - B_1^\mathsf{T} P_{1,k} B_2 F_{2,k}) \tag{14}$$

$$F_{2,k} = (R_{22} + B_2^\mathsf{T} P_{2,k} B_2)^{-1}(B_2^\mathsf{T} P_{2,k} A - B_2^\mathsf{T} P_{2,k} B_1 F_{1,k}). \tag{15}$$

70 Importantly, note that the solution $F_{1,k}$ contains the term $B_1^\mathsf{T} P_{1,k} B_2 F_{2,k}$ demonstrating

71 knowledge of the partner's feedback gains $F_{2,k}$. In our modeling framework, this knowl-

72 edge of the partner's control policy reflects a partner representation.

73   Here, $P_{i,k}$ is the solution to the set of coupled Riccati equations derived via dynamic

74 programming for a linear quadratic game.

$$P_{1,k} = S_k^\mathsf{T} P_{1,k+1} S_k + F_{1,k}^\mathsf{T} R_{11} F_{1,k} + F_{2,k}^\mathsf{T} R_{12} F_{2,k} + Q^\alpha_{1,k} \tag{16}$$

$$P_{2,k} = S_k^\mathsf{T} P_{2,k+1} S_k + F_{2,k}^\mathsf{T} R_{22} F_{2,k} + F_{1,k}^\mathsf{T} R_{21} F_{1,k} + Q^\alpha_{2,k} \tag{17}$$

$$\text{where } S_k = A - B_1 F_{1,k} - B_2 F_{2,k}$$

75 Note that $P_{i,N} = Q_{i,N}$ where N is the final timestep, and $P_{i,k}$ is recursively solved back-

76 wards in time.

State Estimation and Sensory Delays

78 Each controller receives delayed sensory feedback of its own hand position, velocity,

79 and force, as well as the partner's hand position and velocity. Further, each controller

80 receives delayed sensory feedback of the center cursor position and target position. To

81 incorporate sensory delays, we augmented the state vector with previous states.[2,3]

$$x_k^{aug} = [x_k,\ x_{k-1},\ \dots,x_{k-n_{\delta v}}]^\mathsf{T} \tag{18}$$

82 Here δv = 110 ms to reflect the transmission delay associated with vision and aligned the

83 model and experimental visuomotor response onset times. This value was converted

84 into time steps in our program ($n_{\delta v} = 11$). To accommodate the augmented state vector,

85 we also augmented A, B_i, and Q_i:

$$A^{aug} = \begin{bmatrix} A & 0_{n_x \times n_{xd}} \\ I_{n_{xd}} & 0_{n_{xd} \times n_x} \end{bmatrix}$$

$$B^{aug} = \begin{bmatrix} B \\ 0_{n_{xd} \times n_u} \end{bmatrix}$$

$$Q^{aug} = \begin{bmatrix} Q & 0_{n_x \times n_{xd}} \\ 0_{n_{xd} \times n_x} & 0_{n_{xd} \times n_{xd}} \end{bmatrix}$$

Here n_x is the total number of states (16), n_u is the number of control states (2), and n_{xd}

is the total number of time delayed states ($n_x \cdot n_{\delta v} = 176$). I_p is the square identity matrix

with n_{xd} rows and n_{xd} columns. 0 is a matrix with all zeros of the specified dimensions.

B^{aug} is designed so the controllers only act on the current (non-delayed) state. Q^{aug} is

designed so the controllers only incur a cost on the current (non-delayed) state.

The sensory states available to controller i is

$$y_1 = C_1^{aug} x_k^{aug} + \omega_{1,k} \tag{19}$$

$$y_2 = C_2^{aug} x_k^{aug} + \omega_{2,k} \tag{20}$$

92   where y_1, y_2 are the vectors of delayed state observations for controller 1 and 2 respec-
93   tively. $\omega_{1,k}$ and $\omega_{2,k}$ are each noise vectors whose elements are drawn from a Gaussian
94   distribution with zero mean and covariance according to:

$$\Sigma = \begin{bmatrix}
\sigma_p^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & \sigma_v^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & \sigma_f^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & \sigma_p^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & \sigma_v^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & \sigma_f^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & \sigma_p^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_v^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_f^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_p^2 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_v^2 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_f^2 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_p^2 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_p^2 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_p^2 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_p^2
\end{bmatrix} \tag{21}$$

95   See **Table 1** for the measurement noise values used in σ.

96   C_i^{aug} is an observation matrix designed to selectively observe some of the delayed
97   states. First we define C_1 and C_2:

$$C_1 = \begin{bmatrix}
1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1
\end{bmatrix}$$

$$C_2 = \begin{bmatrix}
1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1
\end{bmatrix}$$

99   Here controller i observes all states except their partner's force production in both the

x and y dimension. We augment both observation matrices to only observe the delayed state.

$$C_i^{aug} = \begin{bmatrix} 0_{14 \times p} & C_i \end{bmatrix}$$

To minimize extra notation, we drop the aug superscript moving forward. Like previous work, we used a linear Kalman filter to model participants sensory estimates of the state variables.[4] The posterior state estimate $\hat{x}_{1,k}$ of controller 1 is obtained using an online filter of the form:

$$\hat{x}_{1,k} = \bar{x}_{1,k} + K_{1,k}(y_{1,k} - H_1\bar{x}_{1,k}) \tag{22}$$

$$\bar{x}_{1,k} = A\hat{x}_{1,k-1} + B_1 u_{1,k} + B_2 u_{2,k} + \bar{\omega}_{1,k}. \tag{23}$$

Here $\bar{x}_{1,k}$ is the prior prediction of the state corrupted by Gaussian noise $\bar{\omega}_{1,k}$ with zero mean and standard deviation of $1e\text{-}5$. We assume the sensorimotor system obtains a noisy prior prediction of the states using an internal model of the state dynamics, which includes a prediction of the partner's motor command. The prior prediction uses the previous posterior estimate ($\hat{x}_{1,k-1}$), the efference copy (u_1), and the prediction of the partner's motor command (u_2).

The prior prediction of the state is updated using sensory measurements to obtain the posterior estimate $\hat{x}_1$ (**Eq. 22**). The sequence of Kalman gains K_1 and K_2 were updated recursively according to the classic algorithm:

$$P_{i,k+1}^{prior} = A_d P_{i,k}^{post} A_d^{\mathsf{T}} + V_{i,k} \tag{24}$$

$$S_{i,k+1} = C_i P_{i,k+1}^{prior} C_i^{\mathsf{T}} + W_{k+1} \tag{25}$$

$$K_{i,k+1} = P_{i,k+1}^{prior} C_i^{\mathsf{T}} S_{i,k+1}^{-1} \tag{26}$$

$$P_{i,k+1}^{post} = (I - K_{i,k+1}C_i)P_{i,k+1}^{prior} \tag{27}$$

115   W is the measurement covariance matrix defined as:

$$
W = \begin{bmatrix}
\sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_w^2
\end{bmatrix}
$$

116   Both controllers used the same measurement covariance matrix W. V_i is the process
117   covariance matrix for controller i defined as:

$$
V_1 = \begin{bmatrix}
\sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2
\end{bmatrix}
$$

$$V_2 = \begin{bmatrix}
\sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & \sigma_z^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2 & 0 \\
0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \sigma_s^2
\end{bmatrix}$$

119 The process covariance is higher on the partner's states to more heavily weigh sensory

120 information about the partner's states than the prediction of the partner's states.

Simulating Perturbation and Probe Trials

We Euler integrated the state equation with a step size of $h = 0.01$. Based on the state

cost, the controllers were required to move the center cursor into either a relevant or

irrelevant target. They were required to stop the center cursor in the target at final time

$T = 0.8s$ (final timestep of $N = 79$). Just like the experiment, perturbations were im-

plemented by shifting the center cursor -3cm or target +3 cm when the center cursor

crossed 25% of the forward distance to the target. On probe trials, we simulated a force

channel by setting the x-force element in the B_1 and B_2 matrices to 0. Thus, the con-

trollers could only move the center cursor in the forward dimension. We were able to

calculate the applied force for controller 1 in the lateral dimension using the original B_1

matrix. During probe trials, the center cursor or target laterally shifted 3 cm when the

center cursor crossed 25% of the distance to the target (6.25 cm), then shifted back to

the original lateral position after 250 ms.

Table 1. Model Parameters

Symbol	Value	Description
h	0.01 s	Simulation time step
T	0.8 s	Total movement duration
N	79	Final discretized time step
m	1.5 kg	Hand mass
b	0.1 N·s/m	Hand damping coefficient
τ	20 ms	Muscle time constant
δv	110 ms	Visual feedback delay
$w_{cc_x}^{rel}$	40000	Penalty on center cursor hitting a relevant target in x-dimension
$w_{cc_x}^{irrel}$	100	Penalty on center cursor hitting an irrelevant target in x-dimension
w_{cc_y}	40000	Penalty on center cursor y-position
w_v	8000	Penalty on hand velocity
w_f	40	Penalty on force production
w_y	4000	Penalty on difference in y-position between controllers 1 and 2
r	1e-5	Energy cost parameter
σ_p^2	1e-4	Position measurement noise
σ_v^2	1e-3	Velocity measurement noise
σ_f^2	1e-1	Force measurement noise
σ_u^2	1e-2	Control signal noise
σ_w^2	1e-2	Measurement covariance value
σ_s^2	3e-4	Process covariance value on self
σ_z^2	3e-2	Process covariance value on partner
-	250 ms	Duration of probe perturbation
-	0.03 m	Size of cursor/target jump
-	0.0625 m	y-position of center cursor at cursor/target jump onset

Supplementary References

1. Başar, T., & Olsder, G. J. (1999). *Dynamic Non-Cooperative Game Theory*. 2nd. SIAM's Classics in Applied Mathematics.

2. Lokesh, R., Sullivan, S. R., St. Germain, L., Roth, A. M., Calalo, J. A., Buggeln, J., Ngo, T., Marchhart, V. R. F., Carter, M. J., & Cashaback, J. G. A. (2023). Visual Accuracy Dominates over Haptic Speed for State Estimation of a Partner during Collaborative Sensorimotor Interactions. *Journal of Neurophysiology*, 130 (1), 23–42.

3. Crevecoeur, F., Sepulchre, R., Thonnard, J.-L., & Lefèvre, P. (2011). Improving the State Estimation for Optimal Control of Stochastic Processes Subject to Multiplicative Noise. *Automatica*, 47 (3), 591–596.

4. Todorov, E., & Jordan, M. I. (2002). Optimal Feedback Control as a Theory of Motor Coordination. *Nature Neuroscience*, 5 (11), 1226–1235.