1 **Energy Landscape Analysis with Automated Region-of-Interest**
2 **Selection via Genetic Algorithms**
3

Koichiro Mori

Graduate School of Life and Medical Sciences, Doshisha University, Kyoto, Japan

Tomoyuki Hiroyasu

Department of Biomedical Sciences and Informatics, Doshisha University, Kyoto, Japan

Satoru Hiwa (corresponding author)

Department of Biomedical Sciences and Informatics, Doshisha University, Kyoto, Japan

E-mail: shiwa@mail.doshisha.ac.jp

Postal address: 1-3 Tatara Miyakodani, Kyotanabe, Kyoto 610-0394, Japan

Abstract

Understanding brain dynamics is essential for advancing cognitive and clinical

neuroscience. Energy landscape analysis (ELA), based on the pairwise maximum entropy

model, is a powerful framework to characterize brain activity as transitions among discrete

states defined by regional activity patterns. However, traditional approaches require a

predefined set of regions of interest (ROIs), usually chosen based on prior knowledge from

hypothesis-driven studies, which introduces subjectivity and may overlook previously

unknown patterns. To overcome this limitation, we developed a new ELA framework

enhanced by automated ROI selection using genetic algorithm optimization, called

ELA/GAopt. ELA/GAopt employs a genetic algorithm to select ROI subsets that maximize

model fitting accuracy while accounting for individual variability. We applied ELA/GAopt to

two independent resting-state functional magnetic resonance imaging datasets. In Scenario

1, we tested how well the method generalizes using the Creativity dataset (OpenNeuro:

ds002330), which includes 66 healthy adults (29 males, 36 females, and one non-binary

individual; average age 26.6 ± 4.3 years). ELA/GAopt was performed on a discovery set

($n = 31$), and the optimized ROI sets were validated on a test set ($n = 30$). Over 100

independent optimization runs, the selected ROI sets achieved significantly higher objective

function values than randomly chosen ROI sets (permutation test, $p < 0.05$, false

discovery-rate corrected). The similarity of local minimum states between discovery and

test sets was also significantly higher for ELA/GAopt than for random selection ($p < 0.05$).

These results confirm the reproducibility and generalizability of the proposed approach. In

Scenarios 2–4, we analyzed data from 293 participants in the Autism Brain Imaging Data

Exchange II dataset, including 157 with autism spectrum disorder (ASD) and 136 typically

developing controls (CTL) from discovery cohort A and validated findings in an independent

cohort (54 ASD and 72 CTL participants). ELA/GAopt showed that ASD participants tend to

visit local minima characterized by global co-activation of selected ROIs, especially within

sensory-motor and visual networks. Additionally, ROI sets optimized for one group (ASD or

CTL) did not generalize across groups, with significant differences in the number and

structure of local minima (Mann–Whitney U test, $p < 0.05$, false discovery-rate corrected).

These findings demonstrate that ELA/GAopt offers a robust, data-driven approach to

modeling brain state dynamics, minimizing biases from predefined ROI selection. It

improves reproducibility and could aid in discovering neuroimaging biomarkers for clinical

conditions.

Keywords

Functional MRI, Autism spectrum disorder, Brain dynamics, Energy landscape analysis,

Genetic algorithm

Introduction

Interpreting system behavior from multidimensional observation data is essential in various scientific fields, including neuroscience. Energy landscape analysis (ELA) is one such method that applies the Ising model to multidimensional data, introducing the concept of energy to each pattern and visualizing the stability and transitions of emerging patterns as an energy landscape. The Ising model, also known as the pairwise maximum entropy model (pMEM),[1,2] was initially introduced in statistical physics to explain the properties of magnetic materials. It is highly versatile and facilitates the interpretation of system dynamics as interactions between paired elements. The energy landscape derived from observed multidimensional data enables a bird's-eye view of the system's dynamics. A notable application in neuroscience was introduced by Watanabe et al.,[3] who applied the ELA to functional MRI (fMRI) data, establishing a data-driven approach to extract brain dynamics from neuroimaging data. Subsequently, Ezaki et al.[4] investigated fundamental issues of ELA for neuroimaging data and developed the Energy Landscape Analysis Toolbox (ELAT). Their contributions have made ELA applicable to diverse neuroimaging datasets, including various neurological conditions and disorders,[1,5,6] and significantly advanced understanding in the neuroscience field.[1,3–5,7–14]

Despite its success, the current ELA paradigm faces several challenges due to its analytical constraints, including the length of data and the selection of the region of interest (ROI). The ELA requires sufficient data length to ensure the accurate fitting of the pMEM, which necessitates an exponential increase in the required data length with the number of variables, roughly doubling for each additional variable. Masuda et al.[15] estimated that the practical upper limit for the number of ROIs (i.e., data dimension) that can be included in ELA without compromising accuracy is around 10 to 15, depending on the available data length.[15]

In contrast, whole-brain parcellation typically yields hundreds of regions, depending on the atlas used (e.g., 116 for the AAL,[16] 264 for the Power atlas,[17] and 100 to 1000 for the Schaefer 2018 atlas[18,19]). Therefore, analysts are required to narrow down the candidate ROIs substantially. Common approaches include selecting regions implicated in relevant cognitive processes based on prior studies or choosing representative regions from well-known functional networks. However, these approaches inherently reflect existing knowledge, introducing selection bias and reducing the data-driven nature of ELA. Thus, while ELA is conceptually a data-driven method,[4,15] the practical constraints of the data length and ROI selection often render it partially hypothesis-driven—an issue that

undermines the objectivity and exploratory potential of the analysis.

To overcome this limitation, we propose a genetic algorithm-based optimization framework

for automatically selecting ROI subsets that ensure sufficient pMEM fitting accuracy while

preserving the data-driven nature of ELA. Genetic algorithms (GAs) are a class of heuristic

optimization techniques inspired by natural selection and evolution. They are widely used to

obtain approximate solutions for nonlinear optimization problems, including neuroimaging

applications.[20–23] In our proposed approach, the pre-selection of ROIs is formulated as a

combinatorial optimization problem. The objective function incorporates both the pMEM

fitting accuracy and the inter-individual variability of the model parameters, and the optimal

subset is selected from the complete set of whole brain regions. This procedure eliminates

the need for manually selecting ROIs based on expert judgment or prior knowledge,

thereby enabling a fully data-driven implementation of ELA—an advancement that has not

been previously achieved in this field. Here, we refer to this automated method as

ELA/GAopt and evaluate its effectiveness using large-scale, open-access fMRI datasets,

demonstrating its applicability across both cognitive and translational neuroscience

domains.

Specifically, to validate the effectiveness of our approach, we apply it to two large-scale

open neuroimaging datasets. First, we assess its generalizability by testing whether the

brain state dynamics identified using the proposed method are reproducible on the dataset

of healthy participants. Then, we investigate its applicability to clinical neuroscience by

analyzing resting-state fMRI data from individuals with autism spectrum disorder (ASD) and

typically developing controls (CTL). This analysis enables us to investigate whether the

method can identify condition-specific patterns in brain state transitions. These applications

demonstrate the potential of our approach to enhance the objectivity and reliability of brain

dynamics modeling, thereby contributing to data-driven knowledge discovery in cognitive

and translational neuroscience.

112 Materials and methods

113 Overview of ELA/GAopt: Energy landscape analysis with automated ROI
114 selection via genetic algorithms

The proposed ELA/GAopt framework aims to automate the selection of ROIs in ELA

through a combinatorial optimization approach. It involves iteratively selecting ROI subsets,

performing ELA, particularly fitting the pMEM, and evaluating the results until specified

conditions are met.

To solve this combinatorial optimization problem, we employ a GA. GAs are heuristic

optimization techniques characterized by multipoint exploration enabling the generation of

multiple candidate solutions (i.e., ROI subsets) in parallel. Each solution is evaluated using

a fitness function that quantifies the goodness of the solution, which is based on the ELA

output in this case. This strategy helps avoid local optima and improves the robustness of

the search process.

A schematic overview of ELA/GAopt in neuroimaging data is presented in Figure 1. The

following sections describe each component of the framework and detailed analysis

procedures.

Figure 1 Schematic overview of ELA/GAopt framework.

Framework of ELA

Binarization of multidimensional time series data

The input to ELA is an *N*-dimensional discrete time series obtained from *N* ROIs:

$$\{\boldsymbol{x}(1), \dots, \boldsymbol{x}(t_{\max})\}$$

where $\boldsymbol{x}(t) \in \mathbb{R}^N$ for $t \in \{1, \dots, t_{\max}\}$ is the ROI signal vector at time t, and $t_{\max}$ is the

total number of time points (i.e., the length of the observed time series), Each vector $\boldsymbol{x}(t)$

is defined as:

$$\boldsymbol{x}(t) = \big(x_1(t), \dots, x_N(t)\big)$$

In ELA, multidimensional signals at each time point are converted into binary patterns.

Each ROI signal $x_i(t)$ is binarized using a threshold θ_i, where $i \in \{1, \dots, N\}$. The binarized

value $\sigma_i(t) \in \{-1, +1\}$ is defined as:

142
$$\sigma_i(t) = \begin{cases} +1 & \text{if } x_i(t) > \theta_i \\ -1 & \text{otherwise} \end{cases}$$

143 The full binarized vector at each time point t is:

144
$$\boldsymbol{\sigma}(t) = \big(\sigma_1(t), \dots, \sigma_N(t)\big)$$

Each $\sigma_i(t)$ represents the binary activation state of the i-th ROI at time t, where $+1$
indicates "active" and -1 indicates "inactive". Thus, the signal pattern at time t is given by
the N-dimensional binary vector $\boldsymbol{\sigma}(t)$, also referred to as an activity pattern or active
pattern. For notational simplicity, the time index t may be omitted where appropriate. In
total, there are 2^N possible activity patterns, representing all binary combinations of ROI
states.

Fitting a pMEM
A pMEM is fitted to binarized time series data to estimate the energy associated with each
observed signal pattern. For neuroimaging data, this allows modeling the distribution and
dynamics of brain states based on observed frequencies of binary activation patterns. First,
we compute the empirical distribution $P_{\text{empirical}}(\boldsymbol{\sigma})$ which represents the relative frequency
of each activity pattern observed in the data (Figure 1D). Let $\boldsymbol{\sigma}^{(1)}, \dots, \boldsymbol{\sigma}^{(2^N)}$ denote all
possible binary activity patterns. Then, $P_{\text{empirical}}(\boldsymbol{\sigma})$ is simply the proportion of time points
where pattern $\boldsymbol{\sigma}$ occurs, calculated by:

159
$$\sum_{k=1}^{2^N} P_{\text{empirical}}\big(\boldsymbol{\sigma}^{(k)}\big) = 1$$

160 That is, the empirical frequency distribution $P_{\text{empirical}}(\boldsymbol{\sigma})$ is calculated by counting how
161 many times each of the 2^N possible binary patterns appear in the binarized time series
162 and dividing by the total number of time points. The empirical mean signal pattern of the i-
163 th ROI is:

164
$$\langle \sigma_i \rangle_{\text{empirical}} = \frac{1}{t_{\max}} \sum_{t=1}^{t_{\max}} \sigma_i(t)$$

165 The empirical pairwise correlation between the i-th and j-th ROIs is:

166
$$\langle \sigma_i \sigma_j \rangle_{\text{empirical}} = \frac{1}{t_{\max}} \sum_{t=1}^{t_{\max}} \sigma_i(t)\sigma_j(t)$$

167 The pMEM estimates a probability distribution $P(\boldsymbol{\sigma})$ that matches these first- and second-
168 order moments while maximizing entropy. The result is the Boltzmann distribution:

169
$$P(\boldsymbol{\sigma}) = \frac{e^{-E(\boldsymbol{\sigma})}}{\sum_{k=1}^{2^N} e^{-E(\boldsymbol{\sigma}^{(k)})}}$$

170   Equivalently, the distribution can be expressed in terms of model parameters $\boldsymbol{h}$ and $\boldsymbol{J}$ as:

171
$$P(\boldsymbol{\sigma}|\boldsymbol{h},\boldsymbol{J}) = \frac{e^{-E(\boldsymbol{\sigma}|\boldsymbol{h},\boldsymbol{J})}}{\sum_{\{\sigma\prime\}} e^{-E(\sigma\prime|\boldsymbol{h},\boldsymbol{J})}}$$

172   with the energy function:

173
$$E(\boldsymbol{\sigma}|\boldsymbol{h},\boldsymbol{J}) = -\sum_{i=1}^{N} h_i \sigma_i - \frac{1}{2}\sum_{i=1}^{N}\sum_{i=1,j\neq1}^{N} J_{ij}\sigma_i\,\sigma_{ij}$$

This formulation models the energy of each pattern based on ROI-wise signal tendencies
(h_i) and pairwise interactions among ROIs (J_{ij}).

In this study, the model parameters $\boldsymbol{h}$ and $\boldsymbol{J}$ were estimated by pseudo-likelihood
maximization, following the implementation described by Ezaki et al.[4] Full details of the
fitting procedure, including gradient ascent optimization, are available in their original
publication. Specifically, we used a Python implementation of the ELA toolbox developed by
Oku (https://github.com/okumakito/elapy).[24]

Accuracy metrics for pMEM fitting
To evaluate the quality of the fitted pMEM, we used the Shannon entropy-based and the
Kullback-Leibler (KL) divergence-based metrics. In this study, the arithmetic mean of these
two metrics was used. Definitions of the accuracy metrics are described in Appendix 1 of
the Supplementary materials.

Personalization of pMEM via temperature optimization
In standard ELA, individual data is concatenated into a group-level dataset to estimate a
single set of $\boldsymbol{h}$ and $\boldsymbol{J}$ parameters representing group characteristics. Although it is
theoretically possible to fit pMEM to individual data, this approach is rarely adopted in
practice because it requires a large amount of data to achieve stable estimation. For
example, in typical fMRI datasets, the number of time points per individual is often
insufficient to reliably estimate all parameters of the model. Therefore, pMEM is typically
estimated using concatenated group-level data for robustness and accuracy. However,
when individual variability needs consideration, personalization of the pMEM becomes
essential. Ruffini et al.[25] proposed a two-step pMEM parameter optimization method in
which the inverse temperature parameter β, which characterizes the Boltzmann
distribution, is optimized for each individual data while keeping the group-derived $\boldsymbol{h}$ and $\boldsymbol{J}$
parameters fixed. This approach allows group-level trends to be captured by $\boldsymbol{h}$ and $\boldsymbol{J}$,
while individual differences are represented by β. The detailed procedure is described in
Appendix 2 of the Supplementary materials.

Energy landscape and local minimum

By fitting a pMEM to the observed time series, the energy associated with any given

pattern $\boldsymbol{\sigma}$ can be estimated. Since each pattern $\boldsymbol{\sigma}$ lies in a high-dimensional binary space

defined over N ROIs, its neighboring patterns are those that differ from $\boldsymbol{\sigma}$ by exactly one

bit (i.e., Hamming distance = 1). For example, consider $\boldsymbol{\sigma} = (1, 1, -1, 1)$ with $N = 4$. This

pattern has four neighbors obtained by flipping each element. These N neighbors form

vertices of an N-dimensional hypercube surrounding $\boldsymbol{\sigma}$. This structure allows us to

interpret the temporal dynamics as transitions among vertices within this energy-defined

space (that is, energy landscape).

Under the Boltzmann distribution, states with lower energy tend to appear more frequently,

making local minima in the energy landscape particularly important. In ELA, such local

minima are interpreted as representative signal patterns (states). The dynamics between

these stable patterns, that is, how the system transitions from one to another, provide

insights into the system structure. Moreover, the characteristics of the constructed energy

landscape can be visualized using a contour plot, which highlights the energy barriers

between local minima, as shown in Figure 1E.

Automated ROI selection using a genetic algorithm

We introduce a mechanism to automatically determine the optimal subset of ROIs within

the aforementioned ELA framework. In this study, we formulate ROI selection as a

combinatorial optimization problem. The goal is to select a subset of ROIs that maximizes

the quality of the pMEM fitting while capturing individual variability.

A critical aspect of combinatorial optimization is defining the objective function, which

quantifies how well a candidate solution satisfies the desired properties. In this work, we

define the objective function as the sum of:

● The fitting accuracy of the pMEM is represented by the similarity between the model

and empirical distributions.

● The variance of the personalized inverse temperature parameter (β) across all

participants, derived from the individualized Boltzmann distribution.

Let $\boldsymbol{x} \in \{0,1\}^d$ be a binary vector encoding the selection of d ROIs available, where

$x_k = 1$ if the k-th ROI is selected and zero otherwise, and $N \leq d$ is the total number of

ROIs to select. Then, the optimization problem is formulated as:

232
$$\text{Maximize } f(\boldsymbol{x}) = r(\boldsymbol{x}) + \frac{1}{n}\sum_{k=1}^{m}(\beta_k(\boldsymbol{x}) - \bar{\beta})^2$$

233
$$\text{subject to } \sum_{k=1}^{d} x_k = N$$

Here, $r(\boldsymbol{x})$ denotes a pMEM fitting accuracy when ROIs specified by $\boldsymbol{x}$ are used, and

$\beta_k(\boldsymbol{x})$ is the optimized inverse temperature for the k-th participant using the selected ROI

subset $\boldsymbol{x}$. The mean value of $\beta_k(\boldsymbol{x})$ for m participants is denoted by $\bar{\beta}$. The constraint

ensures that exactly N ROIs are selected from the d available candidates.

This objective function can be flexibly determined based on the analysis goals. For

example, if the analyst expects the pMEM model parameters to correlate with data

features, such correlations can be included as an additional term in the objective function.

The above definition of the objective function is a general example that can be used for

various purposes. By optimizing this function with a GA, the proposed framework enables

data-driven selection of ROI subsets.

For the implementation of a GA, we used a standard evolutionary framework based on

Holland's original design,[26] using the Deap library.[27] We employed tournament selection,

two-point crossover, and bit-flip mutation. To ensure the feasibility of the solutions, we

incorporated a repair strategy called Lamarckian repair,[28] which iteratively modifies

infeasible solutions until they satisfy the specified constraints. Specifically, if the number of

selected ROIs exceeds the prescribed limit, a subset of ROIs with a value of 1 (i.e.,

indicating selection) is randomly chosen and flipped to 0. The GA iteratively explored the

optimal combinations of the ROIs for ELA. The full implementation details and parameter

settings are provided in Supplementary Algorithm 1 and Supplementary Table 1.

Datasets

254   To evaluate the performance and generalizability of the proposed ELA/GAopt framework,

255   we applied it to two independent resting-state fMRI datasets. In the following sections, we

256   overview the datasets used, including their preprocessing methods, as well as the analysis

257   scenarios that utilize these datasets.

Creativity Dataset

We employed a publicly available dataset related to creativity, hosted on OpenNeuro

(dataset ID: ds002330).[29] A total of 66 healthy adults completed a neuroimaging session

and four creativity assessments: the Abbreviated Torrance Test for Adults (ATTA) in verbal

and visual formats, the Creative Behavior Inventory (CBI), and the Creative Achievement

Questionnaire (CAQ). One participant did not complete the ATTA due to logistical reasons.

The sample consisted of 29 males, 36 females, and one non-binary individual, with a mean

age of 26.6 years (SD = 4.3).

266 MRI data included T1- and T2-weighted structural images, resting-state fMR images, and
267 diffusion-weighted images (DWIs). After excluding participants with missing ATTA scores or
268 insufficient data quality, the final analytic sample included 61 participants. These were
269 stratified into a discovery set ($n = 31$) and a test set ($n = 30$) based on their ATTA verbal
270 scores. The descriptive characteristics of two subsets are provided in Supplementary Table
271 2.

ABIDE II Dataset

273 We used data from the Autism Brain Imaging Data Exchange II (ABIDE II), which provides
274 a large multi-site resting-state fMRI and anatomical dataset for investigating ASD. Data
275 from 17 sites were included after excluding two sites due to preprocessing incompatibility.
276 The original dataset included 1,114 participants (ASD: 521, CTL: 593); 81 participants were
277 removed due to preprocessing issues, resulting in a final sample of 1,033 participants.

278 Each remaining participant provided at least one resting-state fMRI scan and a high-
279 resolution T1-weighted structural image. Basic demographic and cognitive data (e.g., age,
280 sex, IQ) were available for all individuals. Detailed acquisition protocols and site-specific
281 procedures are described in the related publications.[30,31]

282 To balance site-specific variance, we grouped the dataset into three cohorts of
283 approximately 300 participants each (A, C, and D) and an additional cohort (B) of around
284 100 participants used for independent validation. The distribution of participants across
285 sites and cohorts is provided in Supplementary Table 3.

Data preprocessing

287 Details of image preprocessing of two independent datasets are described in Appendix 3
288 of the Supplementary Materials.[32–34] Additionally, we used different atlases for each
289 dataset: the Dosenbach atlas for Creativity Dataset ($d = 160$),[35–39] and the Power 264
290 atlas for ABIDE II Dataset ($d = 264$),[17] respectively. The BOLD time courses were
291 extracted from the spherical mask with a 4 mm radius centered at each ROI coordinate,
292 then averaged within the ROI. The average time courses were considered representative of
293 brain activity in each ROI. Finally, the ROI-averaged activity data was then binarized using
294 the threshold of the time-averaged value of each activity for the ELA input.

Statistical analysis

Scenario 1: Validation of generalizability of ELA/GAopt using the Creativity

dataset

298 The objective of Scenario 1 was to evaluate whether the proposed automated ROI

selection method avoids overfitting and selection bias. We first applied ELA/GAopt to the

discovery dataset in 100 independent runs, each with a different initial GA population,

resulting in 100 optimized ROI sets. Following Ezaki et al (2017)[4], who demonstrated that

the accuracy of pMEM fitting scales with $l/2^N$ (i.e., the average number of visits per

activity pattern), the number of ROIs in Scenario 1 was fixed at 10 ($N = 10$). They reported

that each activity pattern should be visited approximately 5 and 16 times on average to

achieve accuracies of 0.8 and 0.9, respectively. For the $l = 9170$ data points in this

scenario, choosing $N = 10$ ($2^{10} = 1024$) yields $l/2^N \approx 9.0$ visits per pattern, which lies

between 5 and 16; thus, we expect an accuracy between 0.8 and 0.9.

With the resulting ROIs chosen by ELA/GAopt for 100 trials, a one-tailed binomial test was

performed to assess whether each brain region was selected more frequently than

expected by chance. False discovery rate (FDR) correction was performed for multiple

comparisons. To quantify the effect size for these binomial comparisons, Cohen's h was

calculated. This process ensured the detection of consistently selected ROIs for multiple

GA optimization runs.

Next, each of the 100 optimized ROI sets was applied to the test dataset using standard

ELA. In parallel, we generated 100 randomly selected ROI sets, each also consisting of 10

ROIs, and applied them to both the discovery and test datasets using the same ELA

procedure. In total, this yielded two groups of ROI sets, optimized, and randomly selected,

for comparative analysis.

We tested two hypotheses: 1) the optimized ROI sets provide better objective function

values (i.e., the sum of pMEM fitting accuracy and inter-individual variance of the inverse

temperature) than random sets, and this advantage generalizes to the test data, and 2) the

local minimum patterns identified in the discovery dataset are reproducible in the test

dataset.

For Hypothesis 1, we compared the objective function values of the optimized and random

ROI sets on the test dataset using permutation testing. Specifically, the objective values

from both sets were pooled and the group labels (optimized vs. random) were shuffled

10,000 times to generate a null distribution. For each permutation, the mean objective

value for each group was computed. A p-value was then derived by comparing the actual

difference in mean objective values between the optimized and random groups to this null

distribution. Statistical significance was assessed at $p < 0.05$. In addition, effect size

(Cohen's d) was calculated to quantify the observed differences between optimized and

random ROI sets.

For Hypothesis 2, we quantified the similarity of local minimum patterns between the

discovery and test datasets. Each pattern among the 2^N possible signal patterns (for N

ROIs) were assigned a unique ID. For each ELA run, we generated an ID vector indicating

the presence (1) or absence (0) of each pattern as a local minimum in the estimated energy

landscape. We then calculated the Hamming distance between ID vectors from the

discovery and test datasets for each ROI set. A smaller Hamming distance indicates

greater reproducibility of the local minimum patterns. The Hamming distances of the

optimized and random ROI sets were compared using a permutation test (with 10,000

permutations), with significance assessed at $p < 0.05$. In addition, Cohen's d was

computed to quantify the effect size of the difference in the Hamming distance. All

permutation tests were one-tailed.

Scenario 2: Group-level comparison of brain dynamics on the ABIDE II Dataset

Scenario 2 investigated whether the different brain dynamics of two separate groups were

observed on the single energy landscape constructed using ELA/GAopt on the

concatenated dataset. Specifically, we aimed to observe group-specific brain dynamics on

the energy landscape estimated on the mixed dataset of ASD and CTL groups, in a fully

data-driven manner using ELA/GAopt. To confirm this, we extract the local minimum

patterns more frequently visited in each group.

A total of 293 participants (ASD group: 157 and CTL group: 136, from Cohort A) were

used as the discovery set. An independent dataset of 126 participants (ASD: 54, CTL: 72,

Cohort B) was used for validation. The number of selected ROIs for the ABIDE II dataset in

Scenarios 2 was fixed at 13, following the same procedure as in Scenario 1. The

ELA/GAopt was performed 100 times for each of the 293 participants. Then, we evaluated

how frequently each ROI was selected across trials. To determine whether specific ROIs

were selected more frequently than expected by chance, a binomial test was performed for

each ROI. The test assessed whether the observed selection frequency exceeded the

expected frequency under a null hypothesis of random selection. The resulting p-values

were corrected for multiple comparisons using FDR correction, and statistically significant

ROIs (FDR-adjusted $p < 0.05$, one-tailed) were identified. To quantify the magnitude of

deviation from chance-level selection, Cohen's h was calculated as the effect size. These

ROIs were considered consistently important across trials and served as the basis for

further group comparisons.

To perform group-level comparisons of local minimum patterns, we selected

representative ELA/GAopt trials in which all selected ROIs were among those identified as

statistically significant in the above binomial tests. These representative trials then
estimated energy landscapes, and the probability of visiting each local minimum was
computed for all individuals.

To compare these probabilities between the ASD and CTL groups, we applied the Mann-
Whitney U test for each identified local minimum (FDR-adjusted $p < 0.05$, two-tailed). To
quantify group difference magnitude, we also calculated the effect size (r) based on the Z-
statistic from the Mann-Whitney U test. To evaluate the robustness of observed group-
level differences, the same analysis was repeated on an independent validation dataset
(Cohort B), following the same ROI configuration and statistical testing procedures.

Scenarios 3 and 4: Estimation of ASD- or CTL-optimized energy landscapes on
the ABIDE II Dataset
In Scenario 3, we investigated whether a set of ROIs optimized for the ASD group could
yield distinctive brain state characteristics. To this end, ELA/GAopt was executed 100 times
for the ASD group (131 participants, Cohort C) to identify ROIs optimized for this group.
The number of selected ROIs was fixed at 12, following the same procedure as in Scenario
1. As in Scenario 2, we assessed the selection frequency of each ROI across trials and
identified consistently selected ROIs using a binomial test (FDR-adjusted $p < 0.05$, one-
tailed). For these binomial tests, Cohen's h was calculated as the effect size.

The resulting ASD-optimized ROI set was then applied to an independent CTL dataset
(175 participants from Cohort C) to evaluate whether the same ROI configuration would
produce distinct energy landscape characteristics. Specifically, the number of local minima
identified in the CTL group was compared to that in the ASD group using the Mann-Whitney
U test. To quantify the magnitude of group differences, we also calculated the effect size
(r) based on the Z-statistic from the Mann-Whitney U test (two-tailed). We hypothesized
that if the ASD-optimized ROIs reflect ASD-specific brain state dynamics, applying them to
CTL data would result in significantly different energy landscape structures—particularly in
the number or configuration of local minima—between the two groups.

Scenario 4 mirrored this procedure for the CTL group. ELA/GAopt was conducted 100
times for CTL participants (168 individuals, Cohort D), and the resulting CTL-optimized ROI
set was applied to an independent ASD dataset (140 participants, Cohort D). ROI selection
analysis and statistical testing were conducted in the same manner as in Scenario 3. We
hypothesized that if the CTL-optimized ROIs captured control-specific dynamics, applying
them to ASD data would similarly yield distinct energy landscape structures.

Computational environment

401   We used a computing workstation equipped with an Intel Core (TM) i9-14900K CPU, a 7.7

402   GHz 24-core processor, and an NVIDIA GeForce RTX 4080 16GB GPU for ELA/GAopt

403   execution.

Result

Scenario 1

Supplementary Figure 1 shows the convergence of the objective function with ELA/GAopt

over 1000 generations for 100 runs with different starting populations. As the optimization

problem was formulated as a maximization task, the objective function value increased with

each generation. All runs converged to a range between 1.00 and 1.10.

Based on the 100 ELA/GAopt runs, a binomial test was conducted to assess whether

each ROI was selected more frequently than expected by chance. Eighteen ROIs were

statistically significant after FDR correction ($p < 0.05$), as listed in Figure 2 and

Supplementary Table 4, which also includes the anatomical coordinates and associated

functional networks for each ROI. Additionally, the distribution of selected ROIs across the

100 runs is presented in Supplementary Figure 2, which shows the total number of times

each ROI was selected.

Figure 2 Selection frequency of each ROI across 100 runs of ELA/GAopt (Scenario

1).

To test the reproducibility of the local minimum patterns across datasets, we calculated the

Hamming distance between ID vectors of the discovery and test datasets. Figure 3A and D

show that the Hamming distances were significantly smaller for the optimized ROIs

compared to the randomly selected ROIs (permutation test, 10,000 permutations, $p =$

0.0025, FDR-corrected, Cohen's d: 0.408), indicating greater pattern stability with the

optimized ROIs.

Finally, Figure 3B, C, E, and F summarize the comparison of the objective function values

in both the discovery and test sets. Permutation testing revealed that the values for the

optimized ROI sets were significantly higher than those of the randomly selected sets in the

discovery set ($p < 0.001$, FDR-corrected, Cohen's d: 5.63). Crucially, this significant

advantage also generalized to the independent test set ($p < 0.001$, FDR-corrected,

Cohen's d:2.51), confirming the generalizability and effectiveness of the proposed ROI

selection framework.

Figure 3 Reproducibility of local minimum patterns across discovery and test

datasets.

Scenario 2

Supplementary Figure 4 illustrates the convergence of the objective function over 1000

generations during ELA/GAopt, conducted in 100 independent runs with different initial

populations. As with Scenario 1, the optimization process consistently improved the

objective function value, with most runs converging by the end of the generation window.

Based on the ROI selection results from the 100 runs, we performed a statistical analysis

using a binomial test to determine whether each brain region was selected more frequently

than expected by chance. The resulting p-values were adjusted using the FDR correction

to account for multiple comparisons. Brain regions identified as significant are presented in

Figure 4 and Supplementary Table 5.

Additionally, the overall distribution of ROI selections across the 100 trials is presented in

Supplementary Figure 5. The selection frequency indicates how often ROIs from each

functional network were selected during the automated ROI selection process in

ELA/GAopt.

Figure 4 Selection frequency of each ROI across 100 runs of ELA/GAopt (Scenario

2).

To compare the probability of visiting each local minimum between the ASD and CTL

groups, a representative trial was selected from the 100 ELA/GAopt runs. Since the

objective function values were sufficiently high across all trials, they were not suitable as

selection criteria. Instead, we focused on two trials where all selected ROIs were identified

as being significantly more frequently selected than expected by chance, based on the

binomial test with FDR correction ($p < 0.05$).

In the first representative trial, 13 ROIs were selected (Figure 5A), and 12 distinct local

minimum states were identified in Cohort A (Figure 5A, left panel). To assess group

differences in the probability of visiting each of the four most prominent local minima (as

listed in Table 1), Mann-Whitney U tests were conducted, followed by FDR correction.

Significant between-group differences were observed (FDR-corrected $p < 0.05$).

To validate the robustness of these findings, the same analysis was repeated on the

independent validation dataset (Cohort B). In this cohort, six distinct local minimum states

were observed Figure 5A, right panel), and notably, the local minimum state common to

both cohorts (shared the same state number). These validation results supported the

conclusion that the ASD group exhibited a higher probability of visiting a local minimum

characterized by the simultaneous activation of all selected ROIs.

A second representative trial was similarly identified based on ROI selection consistency

(Figure 5B). In this trial, 13 ROIs were selected, and 10 unique local minimum states were

observed in Cohort A (Figure 5B, left panel). Mann-Whitney U tests revealed significant

differences in the occurrence probability for seven states between groups ($p < 0.05$, FDR

corrected; see Table 2). Again, several states were more frequently visited by the ASD

group, while others were predominant in the CTL group.

Validation on Cohort B confirmed the presence of seven local minima (Figure 5B, right

panel), with overlapping state numbers across cohorts. Group differences in visiting specific

states (notably States 2) were replicated, further supporting the generalizability of the

observed ASD-specific dynamics.

Figure 5. Observed local minimum states for representative trials 1 (A) and 2 (B).

Table 1. Frequency of local minimum occurrence in representative trial 1 (Significant results in bold; FDR-corrected p-value).

		probability of appearance			
State number	Cohort	ASD	CTL	p-value (FDR corrected)	Effect size r

State number	Cohort	ASD	CTL	p-value (FDR corrected)	Effect size r
1	A	0.367	0.361	0.436	0.0531
1	B	0.464	0.466	**0.00386**	-0.276
2	A	0.349	0.344	**0.00897**	0.179
2	B	0.463	0.461	**0.00386**	0.285
3	A	0.106	0.111	0.0536	-0.129
4	A	0.104	0.107	0.0888	-0.114
5	A	0.0175	0.0176	0.432	-0.0577
5	B	0.0156	0.0152	0.767	-0.0266
6	A	0.0168	0.0174	0.498	-0.0435
6	B	0.00662	0.00734	**2.41E-10**	-0.588
7	A	0.00784	0.00846	**0.00941**	-0.173
7	B	0.0297	0.0293	0.742	-0.0446
8	A	0.00797	0.00820	0.0526	-0.134
8	B	0.0210	0.0207	0.143	0.149
9	A	0.00665	0.00741	**0.00897**	-0.194
10	A	0.00751	0.00801	**0.00897**	-0.179
11	A	0.00562	0.00552	0.290	0.0760
12	A	0.00444	0.00460	0.699	-0.0226

486 **Table 2 Frequency of local minimum occurrence in representative trial 2 (Significant**
487 **results in bold; FDR-corrected p-values)**

State number	Cohort	probability of appearance		p-value (FDR corrected)	Effect size r
		ASD	CTL		
1	A	0.369	0.365	0.540	0.0359
1	B	0.472	0.475	**3.09E-05**	-0.396
2	A	0.355	0.351	**0.00740**	0.174
2	B	0.461	0.456	**2.08E-08**	0.529
3	A	0.0948	0.0984	**0.0380**	-0.130
4	A	0.0950	0.0981	0.162	-0.0851
5	A	0.0193	0.0202	**0.0319**	-0.137
6	A	0.0197	0.0215	**0.000559**	-0.235
7	A	0.0105	0.0109	**0.007399**	-0.174
7	B	0.00863	0.00894	**0.0167**	-0.240
8	A	0.0127	0.0127	0.0584	0.116
8	B	0.00828	0.00828	0.815	-0.0386

9	A	0.0121	0.0109	**0.00937**	0.165
9	B	0.0137	0.0136	0.815	0.0347
10	A	0.0125	0.0117	**0.00684**	0.187
11	B	0.0203	0.0209	0.894	-0.0121
12	B	0.0166	0.0174	0.815	-0.0641

Scenarios 3 and 4

Supplementary Figures 6 and 8 show the convergence of the objective function across
1000 generations during 100 independents ELA/GAopt runs for the ASD and CTL groups,
respectively. To evaluate the consistency of selected ROIs, binomial tests were performed
on the selection results from each group's 100 runs. Statistically significant ROIs after FDR
correction are presented in Figure 6 and Supplementary Tables 6 (ASD) and 7 (CTL). The
selection frequency distribution across all ROI candidates is shown in Supplementary
Figures 7 (ASD) and 9 (CTL), reflecting how often each ROI was selected over 100
optimization trials.

Using the ASD-optimized ROIs from Cohort C, we estimated energy landscapes for both
ASD and CTL groups. The number of local minima obtained for each group was computed,
and a group comparison was performed using the Mann-Whitney U test. The test revealed
that the ASD group exhibited a significantly lower number of local minima than the CTL
group ($U_{200} = 4238.5$, $p = 0.043$, effect size r: 0.13), suggesting that the ASD-optimized
ROI configuration captures group-specific features of brain state dynamics.

Conversely, using the CTL-optimized ROIs from Cohort D, the CTL group exhibited
significantly fewer local minima than the ASD group ($U_{200} = 5924.5$, $p = 0.019$, effect size
r: 0.16), again suggesting that the CTL-optimized ROIs capture group-specific differences
in brain state dynamics.

Figure 6 Selection frequency of each ROI across 100 runs of ELA/GAopt (Scenarios 3
and 4).

Discussion

Overview and advantages of the proposed method

The ELA/GAopt framework proposed in this study integrates energy landscape analysis
with genetic algorithm-based feature selection, enabling objective, data-driven identification

of meaningful ROIs for the given dataset. By automating ROI selection based on pMEM

fitting accuracy and inter-individual variability of the personalized inverse temperature

parameter of pMEM, ELA/GAopt enhances reproducibility and objectivity in brain dynamics

modeling.

Traditional ROI selection approaches in neuroimaging studies often depend on

established anatomical or functional priorities derived from previous research. While such

hypothesis-driven selection improves consistency across studies, it may also introduce

confirmation bias, limiting the analysis framework to existing knowledge and potentially

missing emergent patterns not captured by prior findings.

In contrast, ELA/GAopt mitigates this bias by enabling fully data-driven ROI selection. This

allows the model to explore brain region combinations not considered a priori, thereby

expanding the search space for novel insights into brain dynamics. Such exploratory

capacity is particularly crucial for advancing our understanding of complex and

heterogeneous conditions, such as ASD. Hereafter, we discuss the results obtained in

multiple scenarios to demonstrate the effectiveness and clinical applicability of our

proposed ELA/GAopt.

530   Evaluation of reproducibility (Scenario 1)

Scenario 1 evaluated the generalizability of ELA/GAopt using the publicly available

Creativity dataset (OpenNeuro: ds002330), which includes resting-state fMRI data.

ELA/GAopt was applied to the discovery set, and the optimized ROI sets were

subsequently applied to the test set. These ROI sets achieved similarly high objective

function values in both datasets (Figure 3B, C, E, and F; $p < 0.05$, FDR-corrected),

demonstrating that ELA/GAopt avoids overfitting and yields generalizable ROI selection.

Moreover, the similarity of local minimum states between the discovery and test sets was

significantly higher (Hamming distance difference was smaller) for ROI sets selected by

ELA/GAopt than for randomly selected ROIs (Figure 3A and D; $p < 0.05$, FDR-corrected).

Because local minimum represents stable brain states, this result suggests ELA/GAopt

effectively identifies ROI sets capturing stable, reproducible patterns.

Reproducibility is a critical issue in neuroimaging research, especially for clinical

translation. Traditional ROI-based analyses may underestimate reproducibility because

fMRI signals are inherently non-stationary and exhibit considerable inter-individual and

temporal variability.[40,41] In contrast, ELA/GAopt potentially enhances repeatability by

excluding noisy or irrelevant features during ROI selection. Importantly, the objective

function of ELA/GAopt explicitly considers inter-individual variance (i.e., inverse

temperature parameter of pMEM), which may further promote reproducibility in group-level

energy landscape analyses. These improvements enhance the robustness of the findings

and increase the potential for future clinical applications, including biomarker discovery and

personalized modeling of brain dynamics.

Furthermore, the ROIs selected by ELA/GAopt were primarily centered in the occipital

network. These regions play a central role in visual processing and are known to exhibit

characteristic activity patterns even during the resting state.[42] Additionally, the angular

gyrus, precuneus, and inferior temporal lobe, belonging to the default mode network

(DMN), were also selected as ROIs. These areas are implicated in self-referential thought

and memory integration, and are suggested to play a central role in resting-state brain

activity.[43]

A noteworthy aspect of the ELA/GAopt-based ROI selection is that, compared to the

default mode network, which has frequently been the focus of traditional resting-state brain

activity studies, motor-related regions less frequently addressed and not mentioned in the

original data sources were also selected.[29,44] These regions, which have been mainly

studied concerning task-related activities, motor execution,[45] and postural control,[46] were

found to potentially show important patterns of activity even in the resting state. Region

selection aligns with prior research indicating that the dynamic coordination of multiple

networks constitutes the human brain's resting-state activity.[44,47] This finding also

encourages a reevaluation of the roles of new brain regions and network structures. The

ELA/GAopt successfully identified these areas in a data-driven manner.

Detection of ASD-specific dynamics (Scenarios 2–4)

Scenarios 2, 3, and 4 employed the ABIDE II dataset to investigate whether ELA/GAopt

could detect ASD-specific features in brain state dynamics.

In Scenario 2, ROIs selected by ELA/GAopt were mainly located within the sensory

somatomotor hand network (Figure 4). Significant group differences in specific local minima

probability were observed between the ASD and typically developing (CTL) groups (Table

1, Table 2 and Figure 5; $p < 0.05$, FDR-corrected). Notably, ASD participants more

frequently visited local minimum characterized by the co-activation of all selected ROIs.

This dynamic signature was replicated in an independent validation cohort (Cohort B),

providing support for its robustness.

These findings are consistent with prior reports that identified local overconnectivity and

long-range underconnectivity as characteristic features of brain organization in individuals

with ASD.[48] The predominance of globally 'active' local minimum suggests excessive

synchronization of neural activity in ASD, potentially reducing the flexibility of brain state

transitions. This observation aligns with previous ELA studies showing overstability of

neural dynamics,[13] and increased functional connectivity among visual and sensorimotor

networks in infants with ASD, which correlated with symptom severity.[49] Moreover, manifold

learning studies identified connectivity patterns in sensorimotor networks as discriminative

features for distinguishing ASD from schizophrenia.[50]

Taken together, these results suggest that ASD is associated with a distinct neurodynamic

profile characterized by reduced state variability and increased co-activation within specific

functional networks. The ELA/GAopt demonstrated its effectiveness in uncovering such

network-specific dynamic biomarkers in a fully data-driven manner.

Scenario 3 further evaluated this hypothesis by applying the ROI set optimized for the

ASD group to the CTL group. The ROI sets optimized for the ASD group primarily consisted

of visual network regions, as indicated in Figure 6. The application of the ASD-optimized

ROIs to the ELA on the CTL group led to a significant increase in the number of observed

local minima in CTL participants ($p < 0.05$), indicating that ASD-optimized ROIs poorly

capture the neurodynamic patterns of typically developing individuals. This supports

previous work suggesting that ASD is characterized by atypical over-coupling of visual

networks, which may limit brain state transitions.[51,52]

Scenario 4 provided a complementary test by applying CTL-optimized ROIs to the ASD

group. Similarly, the number of local minima observed in ASD participants was significantly

increased ($p < 0.05$). Considering the results in Scenario 3, they suggest that the two

groups exhibit fundamentally different brain state dynamics and network configurations.

This further strengthens previous findings that ASD and CTL groups possess distinct

neurodynamic architectures.[13,48–51,53]

These inter-application results suggest that ELA/GAopt can identify ROI sets that are not

only discriminative but also specific to particular neurodevelopmental conditions. This

highlights its potential utility for biomarker discovery and the study of condition-specific

brain state dynamics.

With these results, our proposed ELA/GAopt demonstrates strong potential as a data-

driven framework for identifying meaningful brain dynamics and holds promise for future

applications in both basic and translational neuroscience research.

613   Data Availability

614   All the datasets used in this study are publicly available. The source codes of the

615   proposed method are available on our GitHub repository (https://github.com/MIS-Lab-

616   Doshisha/ela-gaopt).

618   Acknowledgements

619   We acknowledge the significant contributions of ABIDE-II and its primary source of

620   funding: NIMH 5R21MH107045.

622   Funding

623   T.H. and S.H. were supported by JSPS KAKENHI Grant Number JP24K03028.

625   Competing Interests

626   The authors declare there are no competing interests.

628   References

1.   Saberi M, Rieck JR, Golafshan S, et al. The brain selectively allocates energy to

functional brain networks under cognitive control. *Sci Rep*. 2024;14:32032.

doi:10.1038/s41598-024-83696-7

2.   Watanabe T, Hirose S, Wada H, et al. A pairwise maximum entropy model accurately

describes resting-state human brain networks. *Nat Commun*. 2013;4:1370.

doi:10.1038/ncomms2388

3.   Watanabe T, Hirose S, Wada H, et al. Energy landscapes of resting-state brain

networks. *Front Neuroinformatics*. 2014;8. doi:10.3389/fninf.2014.00012

4.   Ezaki T, Watanabe T, Ohzeki M, Masuda N. Energy landscape analysis of

neuroimaging data. *Philos Trans R Soc Math Phys Eng Sci*.

2017;375(2096):20160287. doi:10.1098/rsta.2016.0287

5.   Xing L, Guo Z, Long Z. Energy landscape analysis of brain network dynamics in

Alzheimer's disease. *Front Aging Neurosci*. 2024;16:1375091.

doi:10.3389/fnagi.2024.1375091

6. Yamashita A, Rothlein D, Kucyi A, Valera EM, Esterman M. Brain state-based

detection of attentional fluctuations and their modulation. *NeuroImage*.

2021;236:118072. doi:10.1016/j.neuroimage.2021.118072

7. Kondo HM, Terashima H, Ezaki T, Kochiyama T, Kihara K, Kawahara JI. Dynamic

Transitions Between Brain States Predict Auditory Attentional Fluctuations. *Front*

Neurosci. 2022;16:816735. doi:10.3389/fnins.2022.816735

8. Watanabe T, Masuda N, Megumi F, Kanai R, Rees G. Energy landscape and

dynamics of brain activity during human bistable perception. *Nat Commun*.

2014;5:4765. doi:10.1038/ncomms5765

9. Kang J, Pae C, Park HJ. Graph-theoretical analysis for energy landscape reveals the

organization of state transitions in the resting-state human cerebral cortex. *PLOS*

ONE. 2019;14(9):e0222161. doi:10.1371/journal.pone.0222161

10. Kang J, Jeong SO, Pae C, Park HJ. Bayesian estimation of maximum entropy model

for individualized energy landscape analysis of brain state dynamics. *Hum Brain*

Mapp. 2021;42(11):3411-3428. doi:10.1002/hbm.25442

11. Jeong SO, Kang J, Pae C, et al. Empirical Bayes estimation of pairwise maximum

entropy model for nonlinear brain state dynamics. *NeuroImage*. 2021;244:118618.

doi:10.1016/j.neuroimage.2021.118618

12. Ezaki T, Sakaki M, Watanabe T, Masuda N. Age-related changes in the ease of

dynamical transitions in human brain activity. *Hum Brain Mapp*. 2018;39(6):2673-

2688. doi:10.1002/hbm.24033

13. Watanabe T, Rees G. Brain network dynamics in high-functioning individuals with

autism. *Nat Commun*. 2017;8(1):16048. doi:10.1038/ncomms16048

14. Hosaka Y, Hieda T, Li R, Hayashi K, Jimura K, Matsui T. Surrogate data analyses of

the energy landscape analysis of resting-state brain activity. *Front Neural Circuits*.

2025;19:1500227. doi:10.3389/fncir.2025.1500227

15. Masuda N, Islam S, Aung ST, Watanabe T. Energy landscape analysis based on the

Ising model: Tutorial review. *PLOS Complex Syst*. 2025;2(5):e0000039.

doi:10.1371/journal.pcsy.0000039

16. Tzourio-Mazoyer N, Landeau B, Papathanassiou D, et al. Automated anatomical

labeling of activations in SPM using a macroscopic anatomical parcellation of the MNI

MRI single-subject brain. *NeuroImage*. 2002;15(1):273-289.

doi:10.1006/nimg.2001.0978

17. Power JD, Cohen AL, Nelson SM, et al. Functional network organization of the human

brain. *Neuron*. 2011;72(4):665-678. doi:10.1016/j.neuron.2011.09.006

18.   Schaefer A, Kong R, Gordon EM, et al. Local-Global Parcellation of the Human

Cerebral Cortex from Intrinsic Functional Connectivity MRI. *Cereb Cortex*.

2018;28(9):3095-3114. doi:10.1093/cercor/bhx179

19.   Yeo BTT, Krienen FM, Sepulcre J, et al. The organization of the human cerebral

cortex estimated by intrinsic functional connectivity. *J Neurophysiol*.

2011;106(3):1125-1165. doi:10.1152/jn.00338.2011

20.   Hiwa S, Obuchi S, Hiroyasu T. Automated Extraction of Human Functional Brain

Network Properties Associated with Working Memory Load through a Machine

Learning-Based Feature Selection Algorithm. *Comput Intell Neurosci*.

2018;2018(1):4835676. doi:10.1155/2018/4835676

21.   Szenkovits A, Meszlényi R, Buza K, Gaskó N, Lung RI, Suciu M. Feature Selection

with a Genetic Algorithm for Classification of Brain Imaging Data. In: Stańczyk U,

Zielosko B, Jain LC, eds. *Advances in Feature Selection for Data and Pattern*

Recognition. Vol 138. Intelligent Systems Reference Library. Springer International

Publishing; 2018:185-202. doi:10.1007/978-3-319-67588-6_10

22.   Spedding AL, Di Fatta G, Cannataro M. A Genetic Algorithm for the selection of

structural MRI features for classification of Mild Cognitive Impairment and Alzheimer's

Disease. In: *2015 IEEE International Conference on Bioinformatics and Biomedicine*

(BIBM). IEEE; 2015:1566-1571. doi:10.1109/BIBM.2015.7359909

23.   Wutzl B, Leibnitz K, Rattay F, Kronbichler M, Murata M, Golaszewski SM. Genetic

algorithms for feature selection when classifying severe chronic disorders of

consciousness. *PloS One*. 2019;14(7):e0219683. doi:10.1371/journal.pone.0219683

24.   Oku M. okumakito/elapy. Published online May 30, 2025. Accessed July 7, 2025.

https://github.com/okumakito/elapy

25.   Ruffini G, Damiani G, Lozano-Soldevilla D, et al. LSD-induced increase of Ising

temperature and algorithmic complexity of brain dynamics. *PLoS Comput Biol*.

2023;19(2):e1010811. doi:10.1371/journal.pcbi.1010811

26.   Baeck T, Fogel DB, Michalewicz Z, eds. *Evolutionary Computation 1: Basic Algorithms*

and Operators. CRC Press; 2018. doi:10.1201/9781482268713

27.   Fortin FA, Rainville FMD, Gardner MA, Parizeau M, Gagné C. DEAP: Evolutionary

Algorithms Made Easy. *J Mach Learn Res*. 2012;13(70):2171-2175.

28.   Ishibuchi H, Kaige S, Narukawa K. Comparison Between Lamarckian and Baldwinian

Repair on Multiobjective 0/1 Knapsack Problems. In: Coello Coello CA, Hernández

Aguirre A, Zitzler E, eds. *Evolutionary Multi-Criterion Optimization*. Springer;

2005:370-385. doi:10.1007/978-3-540-31880-4_26

29.   Sunavsky A, Poppenk J. Neuroimaging predictors of creativity in healthy adults.
NeuroImage. 2020;206:116292. doi:10.1016/j.neuroimage.2019.116292

30.   Di Martino A, Yan CG, Li Q, et al. The autism brain imaging data exchange: towards a
large-scale evaluation of the intrinsic brain architecture in autism. *Mol Psychiatry*.
2014;19(6):659-667. doi:10.1038/mp.2013.78

31.   Di Martino A, O'Connor D, Chen B, et al. Enhancing studies of the connectome in
autism using the autism brain imaging data exchange II. *Sci Data*. 2017;4:170010.
doi:10.1038/sdata.2017.10

32.   thebrisklab/ABIDE_Preprocessing. Published online October 21, 2024. Accessed April
4, 2025. https://github.com/thebrisklab/ABIDE_Preprocessing

33.   Nilearn. Nilearn. Accessed September 3, 2024. https://nilearn.github.io/index.html

34.   Wang HT, Meisler SL, Sharmarke H, et al. Continuous Evaluation of Denoising
Strategies in Resting-State fMRI Connectivity Using fMRIPrep and Nilearn. *BioRxiv*
Prepr Serv Biol. Published online July 2023:2023.04.18.537240.
doi:10.1101/2023.04.18.537240

35.   Dosenbach NUF, Nardos B, Cohen AL, et al. Prediction of Individual Brain Maturity
Using fMRI. *Science*. 2010;329(5997):1358-1361. doi:10.1126/science.1194144

36.   Dosenbach NUF, Visscher KM, Palmer ED, et al. A Core System for the
Implementation of Task Sets. *Neuron*. 2006;50(5):799-812.
doi:10.1016/j.neuron.2006.04.031

37.   Dosenbach NUF, Fair DA, Miezin FM, et al. Distinct brain networks for adaptive and
stable task control in humans. *Proc Natl Acad Sci*. 2007;104(26):11073-11078.
doi:10.1073/pnas.0704320104

38.   Fair DA, Cohen AL, Power JD, et al. Functional Brain Networks Develop from a "Local
to Distributed" Organization. *PLOS Comput Biol*. 2009;5(5):e1000381.
doi:10.1371/journal.pcbi.1000381

39.   Fox MD, Snyder AZ, Vincent JL, Corbetta M, Van Essen DC, Raichle ME. The human
brain is intrinsically organized into dynamic, anticorrelated functional networks. *Proc*
Natl Acad Sci U S A. 2005;102(27):9673-9678. doi:10.1073/pnas.0504136102

40.   Song X, Panych LP, Chou YH, Chen NK. A Study of Long-Term fMRI Reproducibility
Using Data-Driven Analysis Methods. *Int J Imaging Syst Technol*. 2014;24(4):339-349.
doi:10.1002/ima.22111

41.   Song X, Panych LP, Chen NK. Data-Driven and Predefined ROI-Based Quantification
of Long-Term Resting-State fMRI Reproducibility. *Brain Connect*. 2016;6(2):136-151.
doi:10.1089/brain.2015.0349

42.   Zhang H, Tian J, Liu J, Li J, Lee K. Intrinsically organized network for face perception

during the resting state. *Neurosci Lett*. 2009;454(1):1-5.

doi:10.1016/j.neulet.2009.02.054

43. Andrews-Hanna JR, Smallwood J, Spreng RN. The default network and self-

generated thought: component processes, dynamic control, and clinical relevance.

Ann N Y Acad Sci. 2014;1316(1):29-52. doi:10.1111/nyas.12360

44. Greicius MD, Krasnow B, Reiss AL, Menon V. Functional connectivity in the resting

brain: a network analysis of the default mode hypothesis. *Proc Natl Acad Sci U S A*.

2003;100(1):253-258. doi:10.1073/pnas.0135058100

45. Sahin N, Mohan S, Maralani PJ, et al. Assignment Confidence in Localization of the

Hand Motor Cortex: Comparison of Structural Imaging With Functional MRI. *Am J*

Roentgenol. 2016;207(6):1263-1270. doi:10.2214/AJR.15.15119

46. Smith JA, Tain R, Sharp KG, et al. Identifying the neural correlates of anticipatory

postural control: A novel fMRI paradigm. *Hum Brain Mapp*. 2023;44(10):4088-4100.

doi:10.1002/hbm.26332

47. Seitzman BA, Snyder AZ, Leuthardt EC, Shimony JS. The State of Resting State

Networks. *Top Magn Reson Imaging TMRI*. 2019;28(4):189-196.

doi:10.1097/RMR.0000000000000214

48. Fu S, Wang X, Chen Z, et al. Abnormalities in brain complexity in children with autism

spectrum disorder: a sleeping state functional MRI study. *BMC Psychiatry*.

2025;25:257. doi:10.1186/s12888-025-06689-4

49. Chen B, Linke A, Olson L, et al. Greater functional connectivity between sensory

networks is related to symptom severity in toddlers with autism spectrum disorder. *J*

Child Psychol Psychiatry. 2021;62(2):160-170. doi:10.1111/jcpp.13268

50. Hao X, Wang J, He Z, et al. Multi-Cluster Self-Paced Diverse Learning and Feature

Fusion for Autism Spectrum Disorder Identification With Resting-State fMRI. *IEEE*

Trans Emerg Top Comput Intell. 2024;8(6):3860-3873.

doi:10.1109/TETCI.2024.3377551

51. Yamasaki T, Maekawa T, Fujita T, Tobimatsu S. Connectopathy in Autism Spectrum

Disorders: A Review of Evidence from Visual Evoked Potentials and Diffusion

Magnetic Resonance Imaging. *Front Neurosci*. 2017;11:627.

doi:10.3389/fnins.2017.00627

52. Sadeghian F, Hasani H, Jafari M. Feature Selection Based on Genetic Algorithm in

the Diagnosis of Autism Disorder by fMRI. *Casp J Neurol Sci*. 2021;7(2):74-83.

doi:10.32598/CJNS.7.25.5

53. Kozhemiako N, Nunes AS, Vakorin V, Iarocci G, Ribary U, Doesburg SM. Alterations

in Local Connectivity and Their Developmental Trajectories in Autism Spectrum

Disorder: Does Being Female Matter? *Cereb Cortex N Y N 1991*. 2020;30(9):5166-

5179. doi:10.1093/cercor/bhaa109

Figure legends

Figure 1 Schematic overview of ELA/GAopt framework.

The proposed framework ELA/GAopt combines energy landscape analysis (ELA) with a

genetic algorithm (GA)-based optimization for automatic region of interest (ROI) selection.

(**A**) Candidate ROI sets are generated as binary vectors by the GA, where each gene

indicates whether a specific ROI is selected (1) or not (0). (**B**) Brain activity data are

extracted from the selected ROIs. (**C**) The brain activity data are binarized (active: 1 or

inactive: -1) to form discrete activation patterns over time. (**D**) The frequency of

occurrence of each available activation pattern is analyzed. (**E**) A pairwise maximum

entropy model (pMEM) is fitted to the binarized time series data to estimate the energy

associated with each observed signal pattern. The resulting energy landscape visualizes

the probability and energy of each activation pattern, characterizing brain dynamics. (**F**) A

two-step pMEM parameter optimization method, in which the inverse temperature

parameter—which defines the Boltzmann distribution—is optimized for each individual

dataset while keeping the group-derived pMEM parameters fixed. (**G**) The ELA-derived

parameters (e.g., model accuracy and personalized parameters) are fed back into the GA

as a fitness score to evaluate each candidate ROI set. The GA then iteratively updates the

ROI sets through selection, crossover, mutation, and repair operations.

Figure 2 Selection frequency of each ROI across 100 runs of ELA/GAopt (Scenario

1).

The bar graph illustrates the frequency with which each ROI was selected across 100

independent optimization runs. A binomial test was used to determine if the frequency of

each ROI was higher than chance, and 18 ROIs were found to be statistically significant

($p < 0.05$, FDR-corrected) and indicated in the figure. The ROIs are arranged in order from

most to least frequently selected. Their anatomical locations are also displayed on the

glass brain plot. The circle size in the brain plot represents the frequency at which each

ROI was chosen, with larger circles indicating higher frequencies.

Figure 3 Reproducibility of local minimum patterns across discovery and test

datasets.

(A - C) Visualization of the distributions of the difference in means between optimized ROIs

and randomly selected ROIs generated from 10,000 permutations. The solid dashed line

indicates the observed difference in means. (D - F) The horizontal bar within the colored

area indicates the median, and the top and bottom of the colored area represent the 75th

and 25th percentiles, respectively. Whiskers extend to the minimum and maximum values

within 1.5 times the interquartile range. Asterisks denote statistical significance ($*$:$p < 0.05$).

(D) The Hamming distances between ID vectors of the discovery ($n = 31$) and test ($n = 30$)

datasets. The Hamming distances were significantly smaller for the optimized ROIs

compared to the randomly selected ROIs (permutation test, $p = 0.0025$, FDR-corrected,

Cohen's $d = 0.408$). (E) The objective function values in the discovery data for the

optimized ROI sets were significantly higher than those of the randomly selected sets

(permutation test, $p < 0.001$, FDR-corrected, Cohen's $d = 5.63$). (F) The significant

advantage of optimized ROI sets also generalized to the test set when compared to

randomly selected sets (permutation test, $p < 0.001$, FDR-corrected, Cohen's $d = 2.51$).

The dataset included optimized ROIs ($n = 100$), randomly selected ROIs ($n = 100$).

Figure 4 Selection frequency of each ROI across 100 runs of ELA/GAopt (Scenario

2).

The bar graph illustrates the frequency with which each ROI was selected in 100

independent optimization runs. A binomial test was used to determine if the selection

frequency of each ROI was higher than chance, and 14 ROIs were found to be statistically

significant ($p < 0.05$, FDR-corrected), as shown in the figure. The ROIs are arranged in

order from most to least frequently selected. Their anatomical locations are also displayed

on the glass brain plot. The circle size in the brain plot represents the frequency of each

ROI's selection, with larger circles indicating higher frequencies.

Figure 5 Observed local minimum states for representative trials 1 (A) and 2 (B).

State numbers are assigned to indicate unique binary activity patterns.

Figure 6 Selection frequency of each ROI across 100 runs of ELA/GAopt (Scenarios 3

and 4).

The bar graph illustrates the frequency with which each ROI was selected across 100

independent optimization runs. A binomial test was performed to determine whether the

frequency of each ROI exceeded chance levels. As a result, 16 ROIs were identified as

statistically significant in Scenario 3 and 22 ROIs in Scenario 4 ($p < 0.05$, FDR-corrected).

The ROIs are sorted in descending order of selection frequency. Their anatomical locations

are also displayed on the glass brain plot. The circle size in the brain plot represents the

frequency of each ROI's selection, with larger circles indicating higher frequencies.

G Candidate ROI sets generation by GA

ROI sets: **#1** **#2** **#3**

	#1	#2	#3
x_1	1	0	1
x_2	0	0	0
x_3	1	1	0
x_4	0	1	0
x_5	1	0	0
⋮			
x_n	1	0	1

$f(\boldsymbol{x})$ 0.85   0.91   **0.95**

Objective function (fitness) values

Return the ELA parameters to GA for evaluating the candidate ROI set.
e.g.,
• Accuracy of pMEM fitting
• Personalized pMEM parameters

Give a candidate ROI set

Energy Landscape Analysis

A
● Selected ROI
● Unselected ROI

Regions of Interest (ROI) selection based on the candidate ROI set

B Time

Extraction of brain activity data from selected ROIs

C Time
1
-1

Binarization of brain activity data

D

Pattern	1	2	3	...	2^N
σ_1	-1	1	1	...	-1
σ_2	-1	-1	1	...	1
σ_3	-1	-1	-1	...	1
⋮	⋮	⋮	⋮		⋮
σ_N	-1	-1	-1	...	1
$P(\boldsymbol{\sigma})$	0.08	0.10	0.12		0.05

Frequency analysis of each activation pattern

E
Energy barrier in the state transition

Energy
E_1 E_2

● Active (1)   ● Inactive (-1)

Energy landscape construction using pMEM fitting

F
Participants

Personalization of pMEM via inverse temperature optimization

* : p < 0.05

A

Discovery **Test**

Uncertain 2
Sensory Somatomotor Hand 18
Sensory Somatomotor Hand 19
Sensory Somatomotor Hand 21
Sensory Somatomotor Hand 23
Sensory Somatomotor Hand 24
Sensory Somatomotor Hand 27
Sensory Somatomotor Hand 36
Sensory Somatomotor Hand 37
Uncertain 142
Sensory Somatomotor Hand 28
Sensory Somatomotor Hand 34
Sensory Somatomotor Hand 35

1 2 3 4 5 6 7 8 9 10 11 12   2 1 7 8 5 6

Local minimum states (in representative trial 1)

B

Discovery **Test**

Uncertain 2
Sensory Somatomotor Hand 18
Sensory Somatomotor Hand 19
Sensory Somatomotor Hand 23
Sensory Somatomotor Hand 24
Sensory Somatomotor Hand 27
Sensory Somatomotor Hand 31
Sensory Somatomotor Hand 36
Sensory Somatomotor Hand 37
Uncertain 142
Sensory Somatomotor Hand 28
Sensory Somatomotor Hand 34
Sensory Somatomotor Hand 35

1 2 3 4 5 6 7 8 9 10   1 2 11 12 9 7 8

Local minimum states (in representative trial 2)

Active (+1) Inactive (-1)

Number of times selected in 100 trials (Scenario 3)

Number of times selected in 100 trials (Scenario 4)