When Firing Rate Falls Short: Spike Synchrony Reliably Disentangles Stimulus Saliency and Familiarity

Viktoria Zemliak[1,*], Gordon Pipa[1,2], Pascal Nieters[1]

[1]Institute of Cognitive Science, Osnabrück University, Osnabrück, Germany

[2]Frankfurt Institute of Advanced Studies, Frankfurt, Germany

[*]Corresponding author: vzemliak@uos.de

Abstract

Whether neural computation relies on firing rate or spike timing has been debated for decades, with no definitive resolution. Here, using a recurrent spiking network simulation and realistically varying stimulus saliency, we demonstrate that the two mechanisms are complementary: rate reliably detects stimulus class, spike synchrony reliably detects stimulus familiarity. This division of labor is necessary: rate coding fails to distinguish novel high-saliency from familiar low-saliency stimuli, while synchrony succeeds. We validate this complementary coding across a biologically realistic V1 model and an abstract associative memory network, demonstrating robustness across connectivity regimes and memory loads. Crucially, when inputs are already temporally coordinated through familiarity in a previous network layer, spike synchrony alone can encode both stimulus identity and familiarity. Our findings reconcile the rate-timing debate: familiar stimuli exploit efficient synchrony-based codes reinforced by recurrent connectivity across the cortical hierarchy, while novel stimuli depend on rate codes.

Keywords: spiking networks; spike synchrony; temporal coding; familiarity detection; recurrent networks; associative memory.

Introduction

Is the firing frequency of action potentials sufficient to understand how neurons compute and communicate, or is the timing of individual spikes crucially important? Rate codes offer compelling advantages: they reliably correlate with experimental stimuli and behavior [1-3], are the basis of numerous theoretical and data-driven mean-field and plasticity analyses [4-6], and approximate successful deep learning networks [7]. Yet these advantages come at a cost: individual spikes carry little information, making rate codes inefficient and potentially inadequate to account for behavior on fast timescales [8-9]. Timing codes achieve high efficiency by encoding information in the precise order of spikes [10], time-to-first-spike in a stimulus response [11], rhythmic oscillations [12], bursting patterns [13], and spike synchrony [14]. While spike train variability challenges the reliability of timing codes [15], this variability may reflect meaningful recurrent interactions [16] or be mitigated by the relative nature of timing codes [17]. Thus, whether and to what extent brains rely on timing or rate information remains a fundamental yet unresolved question in neuroscience.

Rather than viewing rate and timing as competing alternatives, we propose they encode distinct, complementary information about stimuli. We designed a stimulus detection task with two key challenges: encoding stimulus identity across different saliency levels and distinguishing familiar from unfamiliar stimuli. Here we focus on absolute familiarity, whether stimuli match established patterns in recurrent connectivity, rather than relative familiarity from recent exposure, as these involve distinct neural mechanisms [18]. Two critical cases are particularly difficult but important to distinguish: highly familiar but weak stimuli and unfamiliar, but highly salient stimuli. A faint rustle from a known predator or a loud, unknown sound might evoke similar firing rates yet require fundamentally different responses. While sensory representations are generally believed to be encoded in firing rates [1-3], recent evidence suggests that absolute familiarity manifests as spike synchrony emerging from strong recurrent connections [19-21]. This suggests a complementary scheme where rate and spike-time coding coexist in the same network, each carrying distinct information about the stimulus.

We tested this complementary coding hypothesis using two recurrent spiking networks: a biologically realistic V1-like model and an abstract associative memory network. Across both models, synchrony reliably detected stimulus familiarity despite varying input saliency – a task where rate coding failed. Conversely, firing rates accurately identified which neurons encoded the stimulus, regardless of familiarity. This division of labor proved robust across connectivity

81 regimes and was most pronounced in energy-efficient, sparse firing regimes. When familiar
82 stimuli induce synchronized activity, this synchrony could propagate through a network,
83 enabling pattern classification using synchrony. Our findings suggest that rate and timing codes
84 work together, potentially reconciling the longstanding debate between these coding schemes.

85 Results

86 Experimental setup

We examined how neural circuits simultaneously encode stimulus identity and familiarity under
realistic conditions of varying stimulus saliency. Stimulus saliency and familiarity are two kinds
of meta-information about incoming stimuli, in addition to information about the specific content
of perceptions, such as which objects are depicted on an image. They provide higher-level
context about its relevance for processing and decision making.

Saliency reflects bottom-up sensory characteristics of stimuli, such as contrast and intensity.
This distinguishes saliency from relevance or priority, which involve top-down attention
modulation [22]. Visual contrast and intensity influence firing rates across various brain areas,
particularly in thalamus which provides feedforward input to visual cortex [23], analogously to
feedforward input in our simulations. Thus, stimulus saliency modeled as input firing rate varies
significantly in our experiments, simulating real-world conditions.

Familiarity indicates whether a stimulus matches stored memories from prior experience. We
focus on absolute familiarity linked to stable lifelong memories, rather than relative familiarity
memory which reflects recent exposure [24]. Familiarity memory is essential for adaptive
behavior and decision-making in both living and artificial agents, facilitating the recollection of
well-known stimuli or, vice versa, the encoding of new stimuli in memory [24-25]. Lifelong
absolute familiarity memory was suggested to be encoded in recurrent (lateral) connections in
computational models [19-21]. One example is V1, where strong lateral connections are formed
between neurons with similar receptive fields and in closer proximity to each other [26-27],
which aligns with Gestalt-like statistics of natural visual stimuli [28-29]. Another prominent
example is the hippocampal region CA3, where pyramidal neurons form ensembles which
strengthen with experience and participate in associative memory recall [30]. Consequently,

recurrent connections reflect the acquired experience and influence the level of spike synchrony
[31-32].

Neural networks processing stimuli must simultaneously identify what each stimulus is,
determine stimulus familiarity, and do so robustly across varying levels of stimulus saliency. In
our experiments, we therefore varied saliency and familiarity in a stimulus detection task (Fig.
1). While output firing rate responds to both stimulus dimensions, spike synchrony can
selectively reflect input familiarity [19]. This selectivity becomes crucial when saliency varies:
firing rate alone cannot reliably distinguish between new but highly salient stimuli (Fig. 1B) and
familiar but weak stimuli (Fig. 1C), as both can produce similar rate responses. In contrast,
spike synchrony reliably differentiates these cases because synchrony is highly sensitive to
recurrent connections that have been strengthened by repeated exposure to familiar stimuli [20-
21]. Thus, we hypothesized that spike-time coding via synchrony can provide complementary
information to rate coding.

Figure 1. Distinguishing *salient new* inputs from weak *familiar* inputs is difficult

Input stimuli can be divided into 4 groups based on their meta-information: **A**. Familiar and salient, **B**.
New and salient, **C**. Familiar but not salient (weak), **D**. New and not salient. Saliency is represented by
the input firing rate, and familiarity by strength of recurrent connectivity. The difficult case to distinguish is
between conditions B and C: When saliency varies, output firing rate (spike count) is similar between
both, once driven by higher recurrent excitation, once by higher external excitation.. However, we
hypothesize that they can be distinguished reliably by spike synchrony.

To test our hypothesis, we conducted a series of experiments in which recurrent spiking
networks had to detect input familiarity and, in some cases, identify the subset of neurons
receiving external stimulation (see Fig. 2B and the next two sections for experimental details).
To predict familiarity, we used the network's spiking activity in response to a stimulus sample.
We trained a univariate logistic regression classifier for binary classification (1 = familiar, 0 =
new), using either firing rate or spike synchrony as predictors. Firing rate was quantified as the
average spike count (SC), and spike synchrony as Rsync (see Methods).

For each sample in the simulations, external input was delivered to a subset of neurons –
weakly interconnected for new stimuli and strongly interconnected for familiar ones – in a form
of Poisson spike trains via one-to-one feedforward connections. These trains were
asynchronous, uncorrelated, and maintained a constant rate within a sample. The input rate
itself was drawn from a uniform distribution, with the range defining the input rate variability.
Thus, in both experiments, input saliency (rate) varied across samples, for both new and familiar
stimuli. Each dataset comprised 320 samples: 160 familiar and 160 new (see Fig. 2A).

Figure 2. Familiarity detection and pattern classification on a dataset of new and familiar patterns
with varying saliency. Dataset & experimental pipeline

In the network diagrams, teal and orange colors represent strongly connected clusters which encode
familiar patterns.. **A**. Experimental procedure for both network models (V1 and associative memory
model): 160 new and 160 familiar stimuli in random order, with varied saliency (input rate). Familiar
patterns corresponded to network clusters, new stimuli did not.**B**. The abstract model of associative
memory encodes multiple familiar stimuli. It first has to identify which neurons receive the feedforward
input and then use this group of neurons to detect pattern familiarity.

Familiarity detection under increasing input variability in a V1-type network

First, we tested our hypothesis in a 800-neurons recurrent spiking network that modeled connectivity of excitatory horizontal connections in V1, with connections and weight distribution based on experimental observations (see Methods). Familiar input patterns in the network were represented by clusters of 40 spatially neighboring neurons with similarly tuned receptive fields and strong mutual connectivity, consistent with cluster analysis of neurons in L2/3 of V1 [33-34]. This reflects the core principle of Hebbian plasticity in V1: neurons that are frequently co-activated tend to develop stronger synaptic connections over time which reflects acquired visual experience [35-36]. We assumed that prior experience with repeatedly occurring visual patterns lead to the emergence of tightly connected neuronal clusters. Therefore, we considered inputs matching one cluster of tightly connected neurons as familiar, whereas we considered patterns that innervated neurons across clusters as new inputs.

Input familiarity detection is more robust using spike synchrony. We measured how classification accuracy in familiarity detection depended on measuring spike synchrony and spike count in either: (global) all neurons in the model, or (local) the subset of neurons receiving external feedforward input (Fig. 3A). Both features perform better when evaluated for the group of neurons receiving the feedforward stimulus input rather than globally for an entire network.

Figure 3. Familiarity detection for V1 model at different saliency (input rate) variability shows advantage for local synchrony-based decoding

Cross-validated performance of Rsync- and spike count-based classifiers for detecting input familiarity
from all neuron activity and from the activity of externally stimulated neurons, averaged over 10 trials.
Every trial includes 360 data samples, input saliency (firing rate) variability changed from 0 (50 Hz) to 40
(10-90 Hz). **A**. Averaged F1 score for different input saliency (firing rate) variability. Rsync-based
familiarity detection outperforms spike count for higher rate variability. **B**. Kernel-density-estimation plots
of synchrony and spike count of stimulated neurons in response to new and familiar stimuli. Rsync shows
a clear separation across levels of saliency, whereas distributions for spike count start overlapping
heavily. **C**. Example spike raster plots of 500 ms of network activity in response to weak (10 Hz input rate)
and salient (90 Hz input rate), new and familiar stimuli, with spike synchrony and average population
spike count for every condition.

For spike count this difference was minor, while synchrony benefits significantly from a localized
measurement. Local synchrony-based familiarity classification performance remains
impressively robust under conditions of significant saliency variability (up to 40 Hz) which
strongly supports the role of spike timing in encoding input familiarity.

Distributions of spike synchrony are well-separated in all conditions. We also examined
the distributions of spike synchrony and spike count among stimulated neurons (Fig. 3B). Spike
synchrony distributions remained well-separated across all input variability conditions, while
spike count distributions became indistinguishable under higher input variability. This
demonstrates that spike synchrony is a reliable indicator of familiarity in dynamic environments:
firing activity becomes more temporally coherent upon encountering a familiar stimulus (Fig.
3C).

Pattern classification and familiarity detection under increasing memory load

To investigate the computational potential of a complementary rate and spike synchrony coding
scheme, we conducted a familiarity detection experiment under the conditions of input rate
variability 40 Hz emulating high variability in stimulus saliency (for details see Methods). Here, a
5000-neuron SNN model followed more abstract connectivity principles: We generated *n*
familiar and *n* new binary input patterns, each defined by a subset of 100 externally stimulated
neurons. For familiar patterns, each neuron formed strong excitatory connections with other

neurons from the same pattern with probability 0.4, thus creating clustered representations. The
quick emergence of such clusters and their use for familiarity recognition has been
demonstrated in rate [37], excitatory spiking [21], and balanced E-I [38] networks. We
additionally implemented cross-pattern inhibitory connections similar to associative memory
networks [39-40]. The probability of inhibitory connections was 0.02. All connection weights
were randomly drawn from the same log-normal weight distributions as in the V1 experiment for
consistency. In sum, each neuron formed outgoing excitatory connections within its cluster and
inhibitory connections with neurons from the other clusters. The resulting network performed
two tasks:

1) Input pattern classification. This was achieved by selecting an input pattern with the
highest SC or Rsync out of n familiar + n new patterns.
2) Familiarity detection of the pattern identified from SC (Fig. 4).

Figure 4. Familiarity detection and pattern classification in the associative memory model shows
distinct roles for spike count and synchrony

Cross-validated performance of Rsync- and spike count-based classifiers for detecting a stimulated group
of neurons (input pattern class) and the familiarity of a pattern which they are encoding, averaged over 10
trials. Every trial includes 360 data samples, input saliency (firing rate) variability across samples was 40
Hz. **A**. Averaged F1 score for different amounts of pre-encoded patterns and **B.** Wilcoxon test for
significant differences between Rsync and spike count and Cohen's d for the effect size demonstrate that,
across memory load (number of encoded patterns in the network) Rsync outperforms spike count in
familiarity detection, but falls behind in pattern classification. This strongly supports a complementary
coding scheme using Rsync for familiarity and SC for pattern classification. **C**. Spike raster plots of 500

ms of network activity under memory load 100 in response to weak (10 Hz input rate) and salient (90 Hz

input rate), new and familiar stimuli, with synchrony and average population spike count.

Rate reliably detects stimulus class, synchrony reliably detects familiarity. Nearly all new

and familiar stimulated patterns were detected with 100% accuracy using average spike count,

enabling familiarity detection from identified neurons. The Wilcoxon test showed significant

superiority of spike count over Rsync for the classification of a stimulated pattern (Fig. 5B). This

is particularly true for novel stimuli, which are exceedingly difficult to classify from spike

synchrony. In contrast to classification, spike synchrony performed significantly better in a

familiarity detection task under the maximum input saliency (input rate) variability 40 Hz (input

rate range 10-90 Hz). The effect size measured as Cohen's d was the strongest for the most

challenging experiment condition: 500 pre-encoded familiar patterns (Fig. 4B). However, Rsync

has an important limitation in terms of familiarity classification: it strongly relies on accurate

pattern classification. Spike count and spike synchrony thus provide complementary information

about the stimulus — its content and familiarity, respectively.

Both familiarity detection metrics show declining performance as the number of familiar patterns

stored in the network increases. This effect aligns with the results of Zemliak et al. [21], who

attribute it to growing overlap between clusters representing familiar patterns. In the next

section, we show how this effect can be counteracted by regulating the proportion of excitatory

and inhibitory connections.

250 Rate and synchrony codes across different connectivity regimes

To ensure that the advantage of spike synchrony in familiarity detection was not due to a

specific parameter setting, we systematically varied the proportions of excitatory and inhibitory

connections. We compared the performance of rate-based and synchrony-based familiarity and

pattern classification across a broad range of connectivity regimes and for different numbers of

familiar patterns stored in networks of 1000 neurons. Weight amplitudes and distributions

consistent with previous simulations. The experimental parameter space was defined by two

variables: the proportion of log-normally distributed excitatory connections within each pattern,

and the proportion of log-normally distributed cross-pattern inhibitory connections. This allowed

for a controlled comparison of network performance across different connectivity regimes (Fig.

5).

Fig 5. Familiarity detection and pattern classification across connectivity parameters

Cross-validated performance of Rsync- and spike count-based classifiers, for every combination of the proportion of in-pattern excitatory connections and cross-pattern inhibitory connections. Averaged over 10 trials, every trial includes 360 data samples, input saliency (firing rate) variability across samples 40 Hz. **A.** shows F1-scores for familiarity detection, **B.** shows macro F1-scores in pattern classification. Spike count performs better at pattern classification, while synchrony excels at familiarity detection, especially for more encoded patterns. Correspondingly, familiarity detection with Rsync is robust across multiple connectivity regimes and pattern classification with spike count is highly robust across connectivity regimes.

Synchrony is a more reliable predictor for familiarity detection across connectivity regimes. Rsync outperformed spike count in familiarity classification across all tested parameter combinations and exhibited consistently high performance across a broader range of connectivity regimes (Fig. 6A). This robustness to network connectivity is important. First, connectivity can change due to plasticity encoding new patterns in the excitatory population. Second, changing the level of competition between patterns modulates the density of inhibitory connections. Therefore, Rsync remains a reliable familiarity detection metric, even when the precise connectivity structure is variable or uncertain. In contrast, spike count-based familiarity detection fails when the number of encoded patterns increases. This is due to the overlap between patterns increasing, which increases connectivity between pattern clusters and results in higher output spike counts even when patterns are not familiar. In this regime, spike count was also more sensitive to the balance between excitatory and inhibitory connections, making it less reliable when connectivity is dynamic or noisy.

Rate is a more reliable predictor for pattern classification across connectivity regimes. In contrast to its role in familiarity detection, spike count outperforms Rsync in classifying incoming patterns, regardless of the network's connectivity structure (Fig. 5B). Rsync is less reliable in detecting new patterns, particularly when they overlap with familiar ones. This is because familiar patterns tend to evoke strong synchronous firing, reflecting the presence of established recurrent connections. New patterns, by contrast, typically have weaker within-pattern connectivity, leading to lower levels of recurrent input. Since new patterns are characterized by weak and scarce recurrent connectivity and in the presence of noisy input Rsync is driven by strong recurrent dynamics, its ability to distinguish between new patterns is limited. Spike count is directly influenced by feedforward drive, which means that it is better suited to identifying which specific pattern is currently active even when the pattern is unfamiliar. In summary, spike count more effectively classifies the input, while Rsync provides a stronger signal of how well the input matches the network's learned connectivity.

Rate identifies neurons encoding a pattern, synchrony in that group encodes familiarity. Familiarity detection using synchrony is only reliable when measured locally, i.e. restricted to the neurons encoding the pattern in the network. Under a global decoding scheme, Rsync-based familiarity detection performance declined as the number of stored patterns increased (see Supplementary Fig. S2). Rate, on the other hand, reliably does identify the correct pattern encoding population, where synchrony can then be measured for familiarity detection. This underscores the benefit of combining rate and spike-time coding.

Figure 6. Network activity across connectivity parameters

Network activity is measured as the average output firing rate, for combinations of the proportion of in-pattern excitatory connections and cross-pattern inhibitory connections, with input saliency (firing rate) variability across samples 40 Hz. **A**. Average output firing rate. **B.** Distribution of output rate for parameter combinations that lead to F1 > 0.75 on the familiarity detection task. For 150 patterns, there is no parameter regime which would lead to this performance in a spike count familiarity detector. For networks with 10, 50, and 100 neurons, the distribution of Rsync values is significantly lower than that of spike count values (Mann-Whitney U test, $p < 0.005$ for all comparisons), showing that Rsync networks use spike-time codes and are more efficient.

Optimal networks for complementary codes are balanced and sparse. Successful execution of both tasks – familiarity detection and pattern classification – depended on balanced excitation and inhibition at each neuron (BI Index avg. 0.04, see also Supplementary Fig. S1) [41]. At higher memory loads, this balance shifted slightly towards increased excitation and reduced inhibition. This adjustment compensates for greater between-pattern overlap, which increases cross-pattern inhibitory competition that would otherwise prevent persistent

recurrent excitation necessary for successful encoding of familiarity. Individually, both Rsync

and spike count performed best when total excitation and inhibition for every neuron was

balanced (see also Supplementary Fig. S1).

Configurations with the best performance for familiarity detection from Rsync yield consistently
significantly lower overall network activity compared to those performing best in spike count-
based detection, regardless of memory load (Fig. 6). This matches the expectation that spike-
timing codes can be more efficient, at least for familiarity detection, whereas spike count,
encoding complementary information about the stimulus, will generally be less efficient. In our
experiments, we consistently used rate coded poisson inputs. The efficiency of synchrony
codes for familiarity forces the question if and when synchrony can also code for stimulus
class, which we discuss next.

These results demonstrate that networks can simultaneously leverage both coding schemes
with overlapping optimal parameter regimes. Importantly, these findings emerged despite using
asynchronous Poisson inputs – an inefficient coding strategy due to sustained high firing rates
and lack of coordinated temporal structure [9]. Nevertheless, our networks generated
temporally coordinated output responses for familiar stimuli. Given this transformation
capability from asynchronous to synchronous, we next examined how networks respond when
inputs themselves possess temporal structure.

From rate to synchrony coding

Our experiments showed that familiarity decoding under varied saliency relies on spike
synchrony, whereas pattern classification depends primarily on rate coding. This suggests that
stimulus content is propagated via firing rate, whereas spike synchrony conveys familiarity
meta-information. This raises a natural question: Which coding strategy can networks employ
once synchrony emerges through recurrent activity in response to familiar inputs? Hence, we
repeated previous experiments on both familiarity detection and pattern classification, but
increased synchrony of inputs (measured with Rsync, see methods for full experimental
details)under the assumption that this input was synchronized in a preceding area.

Figure 7. Temporal coordination of inputs enables reliable pattern classification with Rsync

A. Average Rsync values of inputs range from 0.08 to 0.75. **B**. Rsync and SC (spike count) reliability (the number of parameter configurations yielding F1 > 0.95) and maximal performance (maximum F1 across the configurations) for classification of patterns of different synchrony: 0.1, 0.2, 0.6, 1.0. Averaged over 10 trials, every trial includes 360 data samples, input saliency (firing rate) variability across samples 40 Hz. The more synchronized the inputs are, the more reliably Rsync can be used to classify them. **C**. F1 on Rsync-based pattern classification across the parameter configurations for input synchronization values: 0.1, 0.2, 0.6, 1.0.

Synchrony can detect stimulus class when temporal coordination of inputs increases. In our experiment, temporal synchronization of input patterns did not significantly affect familiarity detection performance: Rsync consistently outperformed spike count across a wide range of parameter configurations (see Supplementary Fig. S3). Similarly, spike count-based classification of patterns remained stable regardless of the degree of input synchrony (see Supplementary Fig. S4). However, Rsync-based pattern classification was sensitive to input synchronization: while it did not successfully classify fully decoherent Poisson inputs (see Fig. 5), it was able to classify patterns correctly when input synchrony increased (Fig. 7B-C). Under low memory loads − i.e., when fewer than 150 patterns were stored − Rsync reliably achieved high classification accuracy even with modest input synchrony. When inputs were perfectly synchronized, Rsync maintained high accuracy across nearly all parameter configurations.These findings suggest that, once neural activity synchronizes, temporal coherence can propagate through the sensory hierarchy, allowing both stimulus identity and familiarity to be decoded from spike synchrony alone.

Synchrony appears to be an especially effective code for familiar patterns. When a pattern has been encountered before and induced Hebbian plasticity, strengthened recurrent connections lead to more synchronized responses, which Rsync can classify reliably. This synchrony can propagate through subsequent layers, allowing both class identity and familiarity to be decoded from the temporal structure of spike trains. In contrast, new patterns − activating neurons with weaker recurrent connectivity − produce more asynchronous responses, making spike count a more reliable signal. Thus, our results support the hypothesis that neural networks employ a complementary coding strategy: Familiar stimuli are encoded through efficient temporal codes,

383 through synchrony while novel stimuli not yet encountered by the network are encoded through

384 rate.

Discussion

In this study, we have shown that synchrony and rate have complementary functions in a
recurrent spiking neural network. Synchrony outperforms spike count as a measure of stimulus
familiarity when input salience (modeled as varied input firing rate) changes, while spike count
more reliably performs pattern classification. Both have important behavioral implications.
Accurate pattern classification supports memory retrieval and generalization across contexts,
while familiarity detection helps identify environmental changes, enables adaptation, and
enables quick detection of known dangerous or rewarding stimuli. Our findings demonstrate that
neural networks can simultaneously encode what a stimulus is and how familiar it is by
leveraging distinct computational strategies, suggesting that the longstanding debate between
rate and timing codes may be resolved through their functional complementarity.

The effectiveness of spike synchrony familiarity detection depends critically on where and how it
is measured within the network. Our results show that spike synchrony responds more to
recurrent connections than input rate, while output rate fails to separate these contributions.
Synchrony is most effective locally, when measured from the subset of neurons receiving strong
feedforward input. However, this creates an important limitation: identifying this specific group of
neurons is difficult from synchrony alone, particularly for novel stimuli. Instead, spike count is
required to reliably identify that neural population. This limitation directly arises from synchrony's
dependence on recurrent connectivity: novel inputs engage weakly connected neurons that
haven't yet formed a cluster, which then fails to generate synchronous activity necessary for
reliable classification. At the same time, novel inputs that overlap with familiar input patterns
sometimes recruit the population coding for the overlapped familiar stimulus, resulting in
spurious synchrony that leads to false-positive classifications. In contrast, spike count is always
primarily influenced by feedforward drive, making it a reliable predictor of stimulus identity
regardless of its familiarity to the network. Previous work by our group [21] demonstrated that
spike count can also be extremely efficient for relative familiarity detection of sequentially
presented stimuli encoded with continuous plasticity. Under the more realistic condition of varied
input saliency, this is no longer true. Here, our results align with and extend Brette's theory of
synchrony as a mechanism for invariant coding [42].

These mechanistic limitations change fundamentally when inputs are already synchronized
rather than delivered as asynchronous Poisson spike trains. Under such conditions, network
synchrony can reliably perform both familiarity detection and pattern classification functions. In
this case, even weakly connected clusters coding for novel stimuli behave like strong ones; not
by engaging recurrent connectivity, as familiar inputs do, but by achieving reliable activation
through precise spike timing in the input. Thus, once activity synchronizes at a certain
processing level, all information about the stimulus can be further propagated via synchrony
coding. This result is consistent with anatomical and functional connectivity in the visual
processing system in the brain. Early sensory areas like LGN are predominantly driven by
vertical (feedforward or feedback) connections and lack lateral excitatory inputs [43], favouring
rate-based representations. Conversely, higher cortical areas are increasingly densely
connected laterally from V1 [44-45], though V2 [46] to IT [47]. This anatomical gradient suggests
a natural functional transformation from purely rate-coded representations in early areas to
increasingly synchrony and timing-based representations in higher-order cortical regions, in
particular as stimuli become more familiar across that hierarchy.

In addition to a potential gradient along the sensory processing hierarchy, the complementarity
of synchrony and rate codes also suggests complementary functional responses for processing
familiar and novel stimuli. From the perspective of Bayesian modeling and predictive coding
frameworks, familiar inputs match prior expectations, while novel inputs require prediction
updates through synaptic plasticity [48]. Since recurrent connectivity can store prior experience
in strongly connected clusters [19-20, 38], synchrony-based familiarity encoding likely supports
completion and retrieval of familiar patterns by leveraging this encoded experience. This aligns
with previous modeling work exploring phase-coded patterns as associative memory [49-50]
and empirical evidence supporting the role of phase synchrony in memory formation and
retrieval [51-52]. Conversely, strong novel stimuli induce strongly connected clusters through
Hebbian plasticity in various network architectures [21, 37]. Importantly, this functional division
also confers metabolic advantages: synchrony-based familiarity detection operates with lower
overall firing activity, enabling more energy-efficient processing of familiar stimuli while reserving
metabolically expensive rate-based plasticity for novel information that requires learning.
Therefore, the idea of a complementary code for stimulus identity and familiarity also suggests a
functional division: synchrony-mediated pattern completion for familiar stimuli versus rate-
mediated plasticity induction for novel stimuli – a promising avenue for future investigations.

Understanding how our results relate to existing empirical work requires distinguishing between
different types of familiarity. Most studies examine relative familiarity, the effect of recent
exposure [53-54], whereas we model lifelong absolute familiarity as the match between stimulus
patterns and learned recurrent connectivity. Our models exhibit increased activity for familiar
stimuli, contrasting with empirical findings on relative familiarity recorded in multiple cortical
areas, including V2, the inferotemporal cortex (IT), the perirhinal cortex (PrC), and the prefrontal
cortex, where familiar stimuli lead to repetition suppression [55-57]. However, multiple studies
have reported that the electrophysiological markers of lifelong absolute familiarity are distinct
from those of relative familiarity [58-59], which suggests a different underlying mechanism and
explains the different activity patterns. Consistent with this distinction, a recent V1 study showed
that phase-reversing familiar visual stimuli elicit an initial increase in V1 firing rate, followed by
prolonged suppression [60], suggesting that familiarity-induced excitation can precede strong
inhibition. Thus, the increased activity in response to familiar stimuli in our model may also be
attributed to our simple implementation of inhibition that lacks explicit dynamic interactions
between excitatory and inhibitory neurons. Future work could therefore explore more detailed
inhibitory circuitry, which could enable repetition suppression caused by complex inhibitory
circuits.

The complementary coding strategy suggested here optimizes both efficiency and robustness in
neural computation. Spike synchrony excels at familiarity detection and operates efficiently with
few spikes required across varying stimulus saliency levels, but it has a critical limitation: it
consistently misclassifies novel stimuli because synchrony depends on established recurrent
connections that novel patterns lack. Firing rate coding solves this problem by providing robust
stimulus classification regardless of connectivity strength. This suggested that we can select
network configurations that optimize for both. The result is a division of labor where synchrony
efficiently handles familiarity detection while rate coding ensures robust classification of all
stimuli − both familiar and novel − within a single, energy-efficient network architecture. This
complementary relationship thus provides a mechanistic framework for how neural circuits can

simultaneously achieve computational efficiency and the flexibility needed to process dynamic

sensory environments.

475 Methods

476 Familiarity detection

477   To classify stimulus familiarity, we extracted group-level features from simulated spike trains: a
478   rate-based (Eq. 1) and a synchrony-based measure capturing temporal dynamics (Eq. 2).

$$SC(P,T) = \frac{1}{P}\sum_{i=1}^{P} SC_i(T) \tag{1}$$

$$R_{sync}(P,T) = \frac{\widehat{Var}\left[\langle A_i(t)\rangle_{i\in P}\right]_{t\in T}}{\left\langle \widehat{Var}\left[A_i(t)\right]_{t\in T}\right\rangle_{i\in P}} \tag{2}$$

Here, P defines the externally-stimulated neuron population representing one encoded pattern,
and $T = 500$ ms is a time interval for measuring spike count or synchrony. Eq. 1 describes
population spike count SC, which is measured as an average spike count of all neurons in the
population representing one pattern.

In Eq. 2, Rsync measures spike synchrony by comparing the variance of the population mean
activity to the average variance of individual neurons. A_i is an activation trace of neuron i from
neural population P. To compute activation traces, raw binary spike trains were first convolved
with an exponential kernel $k(t) = \exp(-t/\tau)$, with timescale $\tau = 5$ ms. If all neurons fire in
perfect synchrony, their activity traces are identical, so the variance of the mean field equals
that of individual neurons, yielding $Rsync = 1$. Likewise, if neurons fire independently, the
mean field gets averaged out and flattened, and $Rsync \to 0$. Unlike pairwise correlations,
$Rsync$ is a group measure which scales to populations of any size.

For each model, we defined network connectivity structure, selected neurons for performance

measurements and reported F1 scores obtained through 10-fold cross-validation. We also show

baseline scores for random predictions.

Pattern classification

In addition to familiarity detection, we performed multi-class pattern classification to identify

which stimulus pattern the network was currently representing. Each dataset contained 160

novel and 160 familiar patterns, resulting in 320 classification instances per run. For this task,

classification was independent of familiarity: the goal was to recover the identity of the

stimulated population of neurons from the output activity.

We applied a simple maximum-response rule using both rate-based (spike count, Eq. 1) and

synchrony-based (Rsync, Eq. 2) metrics. Spike count and synchrony were computed

separately for each candidate neural population. The population yielding the maximal value of

either measure was taken as the classification result − decoded pattern identity. This winner-

take-all procedure produces a one-of-N classification, where N is the total number of new and

familiar predefined patterns. Once the population was classified, i.e. selected by the max-rule,

familiarity detection was performed only for that population, as described in the previous

section.

Spiking model

512   In our experiments, we used spiking recurrent networks (SNNs) composed of Leaky Integrate-

513   and-Fire (LIF) neurons. The membrane potential of neurons evolves according to the equation

$$\tau_m \frac{dV_i}{dt} = -(V_i - E_L) + RI_i(t)$$

514   (3)

515   Here, dV is an update of membrane potential per timestep $dt = 1.0$ ms, resting potential $E_L = -65$

516   mV, membrane time constant $\tau = 10$ ms. The firing threshold in the model is set to -55 mV, and the

517   refractory period equals 3 ms. $I_i(t)$ are the synaptic currents arriving at the soma:

$$RI_i(t) = \tau_m \left(I_i^f(t) + I_i^E(t) + I_i^I(t) + \eta_k(t) \right)$$

(4)

$$I_i^E(t) = \sum_j w_{ij}^E S_j^E(t), I_i^I(t) = \sum_j w_{ij}^I S_j^I(t)$$

(5)

$$I_i^f(t) = \sum_j w^f S_j^f(t)$$

(6)

These currents include summed input from feedforward, recurrent excitatory and recurrent

connections, scaled by corresponding PSP efficacy values w^f, w_{ij}^E and w_{ij}^I. $S_j(t)$ denotes a

presynaptic spike arrival as the Dirac delta function $S_j(t) = \delta(t - t_j)$. All feedforward weights are

equal and set to 3. We did not simulate separate excitatory and inhibitory neuron populations.

Instead, each neuron projects both excitatory and inhibitory outputs, defined by two distinct

recurrent connectivity matrices. External input is delivered via one-to-one feedforward connections,

modeled as a Poisson process.

Additionally, we model random fluctuations of the membrane potential due to stimulus independent

background activity by including the Gaussian white noise term $\langle \eta_k(t) \rangle$ equal 0.6 with σ^2 equal 0.4

mV. The membrane noise is uncorrelated across neurons and time and biases neurons towards

firing so that they can be driven effectively by very sparse Poisson inputs within our 500 ms

simulation time. We chose maximal $\langle \eta_k(t) \rangle$ and σ^2 values under which neurons only fire upon

receiving external input, despite the noise. Thus, neurons' membrane potentials were consistently

kept in a subthreshold state.

535   V1 model connectivity

Each neuron in the model has a receptive field defined by spatial and orientation selectivity. The

model is designed to recognize 8 orientation angles (from 0° to 180° in 22.5° steps) using 800

neurons, each tuned to a specific orientation. These neurons are arranged in a 10×10 grid

representing a visual field. We measure distance between neurons as Chebyshev distance −

the maximum difference along any coordinate dimension, appropriate for a 2D grid setup. Each

unit of difference corresponds to 100 μm.

Fig 8. An example of V1 model connectivity

A fragment (200 neurons) of a heatmap, connection weights distribution, connection probabilities of the excitatory connectivity matrix of the: **A**. excitatory connectivity matrix, **B**. inhibitory connectivity matrix.

Excitatory connections exhibit 10% sparseness and follow a log-normal weight distribution, consistent with measurements of pyramidal neuron connectivity in layers 2/3 of V1 [27, 61]. Connection probability depends on both spatial proximity and receptive field similarity. While most connections form over short distances, the model also includes a small number of strong long-range recurrent connections, in line with empirical observations [62].

Inhibitory connections are modeled after Parvalbumin expressing (PV) interneurons – the prevalent type of inhibitory interneurons in layers 2/3 of V1. These neurons exhibit weak orientation selectivity [63], in our model simplified to no orientation selectivity, as in Taylor et al. [64]. The inhibitory connectivity depends on distance, follows log-normal distribution [61, 65] and has a total sparseness of 6% (20% within 300 μm). As a result, our V1 model has a broad, non-selective inhibitory mechanism that serves primarily to regulate overall excitatory activity, which could otherwise destabilize the recurrent network.

Synchronized input generation

To control the level of input synchronization, we generated patterns using the following procedure: (1) identical Poisson spike trains were first generated and assigned to all neurons within a given pattern; (2) all spike events were then jittered independently across all stimulated neurons within a specified time window. By varying the width of this window, we systematically modulated the resulting input synchrony (Table 1), measured as Rsync (see Eq 2).

Input Rsync (mean ± sd)	Temporal jitter window
1.0 ± 0.0	0
0.55 ± 0.04	5
0.2 ± 0.06	20
0.1 ± 0.03	50

Table 1. Input synchrony

Temporal jitter window values used to generate patterns with specific levels of input Rsync, averaged over 100 trials for each jitter value.

Data and code availability

All original data in the work was programmatically generated. The code for data generation, analysis and visualization of the presented results can be found at https://github.com/rainsummer613/snn-saliency-familiarity-coding.

Acknowledgments

We thank the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) for funding the Priority Programme SPP 2262 *Memristive Devices Toward Smart Technical Systems* (422738993). The high-performance computing cluster used for the simulations was also funded by the DFG (456666331) and the Ministry for Science and Culture of Lower Saxony (MWK). The funders had no role in study design, data collection and analysis, decision to publish, or preparation of the manuscript.

Author Contributions

V.Z. and P.N. conceived and designed the study. V.Z. implemented the computational models, conducted analyses, and prepared all visualizations. P.N. and G.P. supervised the research and provided resources. V.Z. and P.N. wrote the initial draft, and all authors contributed to review and editing of the manuscript. Funding was acquired by G.P.

References

1. Hubel, D. H., & Wiesel, T. N. (1959). Receptive fields of single neurones in the cat's striate cortex. *The Journal of physiology*, *148*(3), 574.

2. Georgopoulos, A. P., Schwartz, A. B., & Kettner, R. E. (1986). Neuronal population coding of movement direction. *Science, 233*(4771), 1416-1419.

3. Chang, L., & Tsao, D. Y. (2017). The code for facial identity in the primate brain. *Cell, 169*(6), 1013-1028.

4. Wilson, H. R., & Cowan, J. D. (1972). Excitatory and inhibitory interactions in localized populations of model neurons. *Biophysical journal, 12*(1), 1-24.

5. Bienenstock, E. L., Cooper, L. N., & Munro, P. W. (1982). Theory for the development of neuron selectivity: orientation specificity and binocular interaction in visual cortex. *Journal of Neuroscience, 2*(1), 32-48.

6. Hopfield, J. J. (1984). Neurons with graded response have collective computational
properties like those of two-state neurons. *Proceedings of the national academy of*
sciences, *81*(10), 3088-3092.

7. Rueckauer, B., Lungu, I. A., Hu, Y., Pfeiffer, M., & Liu, S. C. (2017). Conversion of
continuous-valued deep networks to efficient event-driven networks for image
classification. *Frontiers in neuroscience*, *11*, 682.

8. Softky, W. R., & Koch, C. (1993). The highly irregular firing of cortical cells is
inconsistent with temporal integration of random EPSPs. *Journal of neuroscience*,
13(1).

9. Thorpe, S., Delorme, A., & Van Rullen, R. (2001). Spike-based strategies for rapid
processing. *Neural networks*, 14(6-7).

10. Panzeri, S., Ince, R. A., Diamond, M. E., & Kayser, C. (2014). Reading spike timing
without a clock: intrinsic decoding of spike trains. *Philosophical Transactions of the*
Royal Society B: Biological Sciences, 369(1637), 20120467.

11. Celebrini, S., Thorpe, S., Trotter, Y., & Imbert, M. (1993). Dynamics of orientation coding
in area V1 of the awake primate. *Visual neuroscience*, 10(5), 811-825.

12. Buzsaki, G., & Draguhn, A. (2004). Neuronal oscillations in cortical networks. *Science*,
304(5679), 1926-1929.

13. Naud, R., & Sprekeler, H. (2018). Sparse bursts optimize information transmission in a
multiplexed neural code. *Proceedings of the National Academy of Sciences*, 115(27),
E6329-E6338.

14. Singer, W. (1999). Neuronal synchrony: a versatile code for the definition of relations?
Neuron, 24(1).

15. Shadlen, M. N., & Newsome, W. T. (1998). The variable discharge of cortical neurons:
implications for connectivity, computation, and information coding. *Journal of*
neuroscience, *18*(10), 3870-3896.

16. Brette, R. (2015). Philosophy of the spike: rate-based vs. spike-based theories of the
brain. Frontiers in systems neuroscience, 9.

17. Masquelier, T. (2013). Neural variability, or lack thereof. *Frontiers in computational neuroscience*, *7*, 7.

18. Yang, H., McRae, K., & Köhler, S. (2023). Perirhinal cortex automatically tracks multiple types of familiarity regardless of task-relevance. *Neuropsychologia*, *187*, 108600.

19. Korndörfer, C., Ullner, E., García-Ojalvo, J., & Pipa, G. (2017). Cortical spike synchrony as a measure of input familiarity. *Neural computation*, 29(9).

20. Zemliak, V., Mayer, J., Nieters, P., & Pipa, G. (2024). Spike synchrony as a measure of Gestalt structure. *Scientific Reports*, 14(1).

21. Zemliak, V., Pipa, G., & Nieters, P. (2025). Continual familiarity decoding from recurrent connections in spiking networks. *bioRxiv*, 2025-01.

22. Fecteau, J. H., & Munoz, D. P. (2006). Salience, relevance, and firing: a priority map for target selection. *Trends in cognitive sciences*, 10(8).

23. Rathbun, D. L., Alitto, H. J., Warland, D. K., & Usrey, W. M. (2016). Stimulus contrast and retinogeniculate signal processing. *Frontiers in neural circuits*, 10, 8.

24. Yonelinas, A. P., Kroll, N. E. A., Dobbins, I. G., & Soltani, M. (1999). Recognition memory for faces: When familiarity supports associative recognition judgments. *Psychonomic bulletin & review*, *6*(4), 654-661.

25. Bülthoff, I., & Newell, F. N. (2006). The role of familiarity in the recognition of static and dynamic objects. *Progress in Brain Research*, *154*, 315-325.

26. Ts'o, D. Y., Gilbert, C. D., & Wiesel, T. N. (1986). Relationships between horizontal interactions and functional architecture in cat striate cortex as revealed by cross-correlation analysis. *Journal of neuroscience*, 6(4).

27. Cossell, L., Iacaruso, M. F., Muir, D. R., Houlton, R., Sader, E. N., Ko, H., ... & Mrsic-Flogel, T. D. (2015). Functional organization of excitatory synaptic strength in primary visual cortex. *Nature*, 518(7539), 399-403.

28. Sigman, M., Cecchi, G. A., Gilbert, C. D., & Magnasco, M. O. (2001). On a common circle: natural scenes and Gestalt rules. *Proceedings of the National Academy of Sciences*, 98(4).

29. Onat, S., König, P., & Jancke, D. (2011). Natural scene evoked population dynamics
across cat primary visual cortex captured with voltage-sensitive dye imaging. *Cerebral*
cortex, 21(11).

30. Nakazawa, K., Quirk, M. C., Chitwood, R. A., Watanabe, M., Yeckel, M. F., Sun, L. D.,
... & Tonegawa, S. (2002). Requirement for hippocampal CA3 NMDA receptors in
associative memory recall. *Science*, 297(5579), 211-218.

31. König, P., Engel, A. K., Löwel, S. & Singer, W. Squint affects synchronization of
oscillatory responses in cat visual cortex. *Eur. J. Neurosci.* **5**(5), 501–508 (1993).

32. Stettler, D. D., Das, A., Bennett, J. & Gilbert, C. D. Lateral connectivity and contextual
interactions in macaque primary visual cortex. *Neuron* **36**(4), 739–750 (2002).

33. Baker, C. M., & Gong, Y. (2023). Identifying properties of pattern completion neurons in
a computational model of the visual cortex. *PLoS Computational Biology*, 19(6),
e1011167.

34. Carrillo-Reid, L., Han, S., Yang, W., Akrouh, A., & Yuste, R. (2019). Controlling visually
guided behavior by holographic recalling of cortical ensembles. *Cell*, 178(2), 447-457.

35. Galuske, R. A., & Singer, W. (1996). The origin and topography of long-range intrinsic
projections in cat visual cortex: a developmental study. *Cerebral Cortex*, 6(3), 417-430.

36. Schmidt, K. E., Galuske, R. A., & Singer, W. (1999). Matching the modules: Cortical
maps and long□range intrinsic connections in visual cortex during development.
Journal of neurobiology, 41(1), 10-17.

37. Tyulmankov, D., Yang, G. R., & Abbott, L. F. (2022). Meta-learning synaptic plasticity
and memory addressing for continual familiarity detection. *Neuron*, 110(3), 544-557.

38. Litwin-Kumar, A., & Doiron, B. (2014). Formation and maintenance of neuronal
assemblies through synaptic plasticity. *Nature communications*, *5*(1), 5319.

39. Hopfield, J. J. (1982). Neural networks and physical systems with emergent collective
computational abilities. *Proceedings of the national academy of sciences*, 79(8), 2554-
2558.

40. Kim, G., & Kim, P. (2025). Selective inhibition in CA3: A mechanism for stable pattern completion through heterosynaptic plasticity. *PLOS Computational Biology*, *21*(7), e1013267.

41. van Vreeswijk, C., & Sompolinsky, H. (1996). Chaos in neuronal networks with balanced excitatory and inhibitory activity. Science, 274(5293), 1724–1726.

42. Brette, R. (2012). Computing with neural synchrony. *PLoS computational biology*, 8(6), e1002561.

43. Derrington, A. (2001). The lateral geniculate nucleus. *Current Biology*, *11*(16), R635-R637.

44. Cossell, L., Iacaruso, M. F., Muir, D. R., Houlton, R., Sader, E. N., Ko, H., ... & Mrsic-Flogel, T. D. (2015). Functional organization of excitatory synaptic strength in primary visual cortex. *Nature*, 518(7539), 399-403.

45. Chavane, F., Sharon, D., Jancke, D., Marre, O., Frégnac, Y., & Grinvald, A. (2011). Lateral spread of orientation selectivity in V1 is controlled by intracortical cooperativity. *Frontiers in systems neuroscience*, *5*, 4.

46. Levitt, J. B., Yoshioka, T., & Lund, J. S. (1994). Intrinsic cortical connections in macaque visual area V2: evidence for interaction between different functional streams. *Journal of Comparative Neurology*, *342*(4), 551-570.

47. Hu, D., Sato, T., Rockland, K. S., Tanifuji, M., & Tanigawa, H. (2025). Relationship between functional structures and horizontal connections in macaque inferior temporal cortex. *Scientific Reports*, *15*(1), 3436.

48. Li, T. E., Tang, M., & Bogacz, R. (2025). Predictive Coding Model Detects Novelty on Different Levels of Representation Hierarchy. *Neural computation*, *37*(8), 1373-1408.

49. Scarpetta, S., & Giacco, F. (2013). Associative memory of phase-coded spatiotemporal patterns in leaky Integrate and Fire networks. *Journal of Computational Neuroscience*, 34.

50. Frady, E. P., & Sommer, F. T. (2019). Robust computation with rhythmic spike patterns. *Proceedings of the National Academy of Sciences*, 116(36).

51. Clouter, A., Shapiro, K. L., & Hanslmayr, S. (2017). Theta phase synchronization is the
glue that binds human associative memory. *Current Biology*, 27(20).

52. Fell, J., & Axmacher, N. (2011). The role of phase synchronization in memory
processes. *Nature reviews neuroscience*, *12*(2), 105-118.

53. Bogacz, R., & Brown, M. W. (2003). Comparison of computational models of familiarity
discrimination in the perirhinal cortex. *Hippocampus*, *13*(4), 494-524.

54. Kazanovich, Y., & Borisyuk, R. (2021). A computational model of familiarity detection for
natural pictures, abstract images, and random patterns: Combination of deep learning
and anti-Hebbian training. *Neural Networks*, *143*, 628-637.

55. Huang, G., Ramachandran, S., Lee, T. S., & Olson, C. R. (2018). Neural correlate of
visual familiarity in macaque area V2. *Journal of Neuroscience*, *38*(42), 8967-8975.

56. Anderson, B., Mruczek, R. E., Kawasaki, K., & Sheinberg, D. (2008). Effects of familiarity
on neural activity in monkey inferior temporal lobe. *Cerebral cortex*, 18(11).

57. Rainer, G., & Miller, E. K. (2000). Effects of visual experience on the representation of
objects in the prefrontal cortex. *Neuron*, 27(1).

58. Gimbel, S. I., Brewer, J. B., & Maril, A. (2017). I know I've seen you before:
distinguishing recent-single-exposure-based familiarity from pre-existing familiarity.
Brain Research, *1658*, 11-24.

59. Duke, D., Martin, C. B., Bowles, B., McRae, K., & Köhler, S. (2017). Perirhinal cortex
tracks degree of recent as well as cumulative lifetime experience with object concepts.
Cortex, *89*, 61-70.

60. Hayden, D. J., Finnie, P. S., Thomazeau, A., Li, A. Y., Cooke, S. F., & Bear, M. F.
(2023). Electrophysiological signatures of visual recognition memory across all layers of
mouse V1. *Journal of Neuroscience*, *43*(44), 7307-7321.

61. Hage, T. A., Bosma-Moody, A., Baker, C. A., Kratz, M. B., Campagnola, L., Jarsky, T.,
... & Murphy, G. J. (2022). Synaptic connectivity to L2/3 of primary visual cortex
measured by two-photon optogenetic stimulation. *elife*, 11, e71103.

62. Bosking, W. H., Zhang, Y., Schofield, B., & Fitzpatrick, D. (1997). Orientation selectivity
and the arrangement of horizontal connections in tree shrew striate cortex. *Journal of*
neuroscience, 17(6), 2112-2127.

63. Niell, C. M., & Stryker, M. P. (2008). Highly selective receptive fields in mouse visual
cortex. *Journal of Neuroscience*, 28(30).

64. Taylor, L., Zenke, F., King, A. J., & Harper, N. S. (2024). Temporal prediction captures
key differences between spiking excitatory and inhibitory V1 neurons. *bioRxiv*, 2024-05.

65. Znamenskiy, P., Kim, M., Muir, D. R., Iacaruso, M. F., Hofer, S. B., & Mrsic-Flogel, T. D.
(2018). Functional selectivity and specific connectivity of inhibitory neurons in primary
visual cortex. *bioRxiv* 294835.