Accurate and scalable multi-disease classification from adaptive immune repertoires

Running title: Scalable Multi-Disease Classification

Natnicha Jiravejchakul[1,2], Ayan Sengupta[3], Songling Li[1,2], Debottam Upadhyaya[3], Mara A.

Llamas-Covarrubias[4], Florian Hauer[3], Soichiro Haruna[2], and Daron M. Standley[1,2]

[1]Department of Systems Immunology, Immunology Frontier Research Institute (IFReC), The

University of Osaka, 3-1 Yamadaoka, Suita, Osaka, 565-0871, Japan

[2]Department of Genome Informatics, Research Institute for Microbial Diseases (RIMD), The

University of Osaka, 3-1 Yamadaoka, Suita, Osaka, 565-0871, Japan

[3]MyImmune Corporation, 251 Little Falls Drive, Wilmington, DE 19808, United States

[4]Department of Human Host Defense, Comprehensive Education and Research Center for

Infectious Diseases (CiDER), 1-10 Yamadaoka, Suita, Osaka, 565-0871, Japan

*Corresponding author: standley@biken.osaka-u.ac.jp

Summary

Background Machine learning models trained on paratope-similarity networks have shown

superior accuracy compared with clonotype-based models in binary disease classification.

However, the computational demands of paratope networks hinder their use on large datasets and

multi-disease classification.

Methods We reanalyzed publicly available T cell receptor (TCR) repertoire data from 1,421

donors across 15 disease groups and a large control group, encompassing approximately 81

million TCR sequences. To address computational bottlenecks, we replaced the paratope-

similarity network approach (Paratope Cluster Occupancy or PCO) with a new pipeline Fast

Approximate Clustering Techniques (FACTS) which comprises of four main steps: (1) high-

dimensional vector encoding of sequences; (2) efficient clustering of vectors; (3) donor-level

feature construction from cluster distributions; and (4) gradient-boosted decision tree

classification for multi-class disease prediction.

Findings FACTS processed 10^7 sequences in under 120 CPU hours. Using only TCR data, and

evaluated with 3-fold cross-validation, it achieved a mean ROC AUC of 0.99 across 16 disease

classes. Compared with the recently reported Mal-ID model, FACTS achieved higher donor-

level classification accuracy for BCR (0.840 vs. 0.740), TCR (0.862 vs. 0.751), and combined

BCR+TCR datasets (0.898 vs. 0.853). FACTS also preserved biologically meaningful signals, as

shown by unsupervised t-SNE projections revealing distinct disease-associated and age-

associated clusters.

Interpretation Paratope-based encoding with FACTS-derived features provides a scalable and

biologically grounded approach for adaptive immune receptor (AIR) repertoire classification.

The resulting classifier achieves superior multi-disease diagnostic performance while

maintaining interpretability, supporting its potential for clinical and population-scale health

profiling.

Funding This study was supported by the Japan Society for the Promotion of Science (JSPS)

KAKENHI [JA23H034980] and by the Japan Agency for Medical Research and Development

(AMED) [JP21am0101001].

Research in context

Evidence before this study

T and B cell receptor (TCR and BCR) repertoires encode lifelong immunological memory and antigen-specific responses, making them valuable for disease diagnosis and prediction. Existing machine learning (ML) models for adaptive immune receptor (AIR) repertoires often rely on clonotype-based representations, which limit shared receptor detection between donors and thus reduce cross-individual disease signature detection. Most models also lack robust multi-disease, population-scale performance. Our previous work showed that representing repertoires as paratope-similarity networks increased the fraction of shared receptors and improved disease classification. However, their computational complexity has limited their scalability for the large datasets required in multi-disease classification.

Added value of this study

We introduce a unified ML framework integrating paratope similarity with scalable sequence encoding. Applied to TCR repertoires from 1,421 donors across 15 diseases and one control group, the approach maintained high performance while efficiently processing 81 million sequences on standard CPU infrastructure. Compared to Mal-ID, our paratope-encoded method achieved significantly higher donor-level accuracy and revealed biologically meaningful disease- and age-associated patterns.

Implications of all the available evidence

Our paratope-encoded, scalability-enhanced model offers high accuracy, and interpretability for multi-disease classification, bringing AIR repertoire-based diagnostics closer to clinical translation and potentially guiding precision immunotherapy and immune-based therapeutic discovery for a wide range of disease.

1 Introduction

B and T lymphocytes generate diverse antigen receptors through somatic V(D)J gene recombination[1,2]. The resulting B-cell receptors (BCRs) and T-cell receptors (TCRs), collectively known as adaptive immune receptors (AIRs), record a lifelong molecular record of antigen encounters. AIRs can be profiled through a routine blood draw, followed by standard sequencing, offering a minimally invasive, hypothesis-free source of disease biomarkers that can detect immune perturbations before clinical symptoms appear. AIR repertoire analysis, therefore, holds promise for early and personalized disease detection, prognosis, and the discovery of immune-based therapeutics[3,4].

In recent years, machine learning (ML) has emerged as a powerful approach for identifying disease-specific signatures from AIR repertoires, as reviewed by Mhanna *et al.*[5]. While binary classifiers have been effective in distinguishing specific disease from health, such models do not reflect the complexity of the immune system, which responds to diverse pathogens and disease conditions. Multi-disease classification, as exemplified by the recently introduced Mal-ID program on 6 disease/healthy classes, is thus both more realistic and clinically relevant[6]. However, training such ML models requires larger and more heterogeneous datasets, increasing computational demands and making efficiency a critical factor for clinical translation.

Most existing ML models rely on clonotype-based repertoire representations in which sequences that share the same V-gene and possess identical, or highly similar, complementarity-determining region 3 (CDR3) sequences are grouped together[3,7]. Due to the immense diversity of BCRs and TCRs, the proportion of clonotypes shared between donors is extremely low. Studies report approximately 1–6% overlap in IGH clonotypes and around 8–13% in TCRβ clonotypes across healthy donors[8,9]. This sparsity limits the generalizability and sensitivity of clonotype-centric approaches.

Paratope-based representations address this limitation by focusing on receptor residues likely to interact with antigens or peptide–MHC complexes[10,11]. This avoids combining categorial germline gene annotations with continuous amino acid sequences and extends analysis beyond CDR3 to include CDR1 and CDR2, enabling statistically robust sequence comparisons. Notably,

paratope clusters are typically antigen- and epitope-specific. In prior work, grouping BCRs by

paratope similarity (80% sequence identity and 90% alignment coverage) yielded clusters in

which more than 95% of antibodies recognized the same antigen, with epitope-specific

neutralizing antibodies co-clustering as well[12]. Paratope similarity networks were shown to

provide superior features for binary disease classification, outperforming state-of-the-art

clonotype-based models such as DeepRC and immuneML[13]. However, constructing such

networks requires all-against-all similarity comparison, limiting scalability to datasets with fewer

than 10^6 sequences.

In this study, we developed a scalable paratope-based feature construction pipeline to enable

multi-disease classification across large AIR datasets. We replaced computationally intensive

paratope similarity graphs with an efficient sequence encoding and clustering strategy called Fast

Approximate Clustering Techniques (FACTS). To validate FACTS, we reanalyzed publicly

available TCR repertoire data from 1,421 donors across 15 disease groups and one large control

group. Compared to our previous method, Paratope Cluster Occupancy (PCO), FACTS

dramatically reduced computational time while maintaining high classification performance,

achieving a mean three-fold ROC AUC of 0.99. On the six-class Mal-ID benchmark, FACTS

achieved comparable TCR-only accuracy (86.2%) to the Mal-ID model using both BCR and

TCR data (85.3%). Moreover, unsupervised embedding projections revealed disease- and

demographic-associated clusters, supporting FACTS as a robust, scalable, and interpretable

framework for repertoire-based diagnostics with potential for clinical and population-scale

applications.

2 Methods

Dataset curation and preprocessing

Adaptive immune receptor (AIR) sequencing data from a total of 1,421 donors were obtained from publicly available studies spanning 16 disease groups, including healthy individuals, patients with autoimmune disease, infectious disease, cancer, and vaccinated donors. Data for healthy donors, human immunodeficiency virus (HIV) infection, influenza vaccination, coronavirus disease 2019 (COVID-19), systemic lupus erythematosus (SLE), and type 1 diabetes (T1D) were sourced from the Mal-ID public dataset[6] (Supplementary Table 1). Samples labeled as "HIV-negative" were excluded from the healthy donor group in our study. Data for the remaining 10 disease groups, as well as additional healthy donors, were obtained from 12 published studies[14-25] (Supplementary Table 1). No original sequencing data were generated in this study, and ethical approval for secondary analysis was not required by the authors' institution.

Paratope extraction

In the first step of the FACTS pipeline, paratope regions were extracted from raw AIR sequences using ANARCI[26], with residue numbering assigned according to the IMGT scheme[27]. For each BCR and TCR sequence, paratopes were defined as all positions within CDR1, CDR2, and CDR3, concatenated to form a single pseudo-sequence used in all downstream encoding and clustering steps.

Sequence encoders

Following paratope extraction, each pseudo-sequence was transformed into a fixed length embedding using a protein language model. A proprietary encoder for TCR sequence was developed, adopting a Transformer-based encoder-only architecture trained on large-scale, publicly available AIR datasets. Training employed the masked language modelling (MLM) objective from BERT[28], in which random amino acid tokens are masked, and the model is optimized to predict the missing residues. Novel training strategies were implemented to incorporate structural features relevant to receptor–antigen interactions. For the TCR encoder model, weights were initialized from ESM-2[29] and fine-tuned on TCR datasets using paratope-focused sequence inputs. The resulting TCR encoder generated dense vector embeddings for

163 each paratope pseudo-sequence, which were subsequently used for clustering and classification.

164 By default, FACTS uses IgBert[30] for encoding BCR sequences.

Clustering of sequence embeddings

To group similar paratope embeddings, MiniBatchKMeans, a memory- and time-efficient variant

of k-means, was applied using the scikit-learn[31] implementation with k ranging from 100 to

1,000. A batch size of 1,024 was used, and initial centroids were seeded with the k-means++

initializer to improve stability. Clustering quality was assessed across the k range using inertia

(within-cluster sum of squares) and silhouette coefficient scores[32]. MiniBatchKMeans scales

approximately as $O(N \log k)$ per pass through the dataset, enabling efficient clustering of tens of

millions of paratope embeddings without prohibitive computational cost.

Construction of donor-level features

176 Following clustering, donor-level feature vectors were generated by aggregating cluster

177 membership data. For each donor, the frequency distribution of clustered paratope embeddings

178 was computed as the proportion of sequences assigned to each cluster. Inter-cluster mutual

179 information was also calculated. This produced a fixed-length vector representing each donor's

180 immune repertoire, which served as input for downstream classification.

Classification models and statistical analysis

All classification models were trained using the XGBoost[33] implementation in soft probability

mode. Model performance was assessed using three-fold cross-validation with donor-level

stratification to prevent donor overlap between folds. Evaluation metrics included accuracy,

ROC AUC, macro-averaged F1 score (macro F1), sensitivity, and specificity. Paired AUC values

were compared using the Wilcoxon signed-rank test. Ninety-five percent confidence intervals

(CIs) for performance metrics were calculated via bootstrap resampling (n = 10,000 iterations).

Benchmarking sequence encoders

The proprietary MyImmune TCR encoder was benchmarked against open-source protein and

immune receptor language models, including TCRBert[34], ESM-2[29], ProtTrans[35], SCEPTR[36], and

UniTCR[37]. For BCR sequences, six publicly available encoders; IgBERT[30], AntiBERTa2[38],

AntiBERTy[39], ESM-2[29], ProtTrans[35], and AbLang[40], were evaluated. Details of each encoder are

provided in Supplementary Table 2. Each model was integrated into our pipeline using identical

clustering and classification procedures, differing only in the embedding step. Benchmarking

was performed on TCR and BCR datasets from the Mal-ID cohort[6] (499 donors for TCR, and

550 donors for BCR dataset, across five disease classes and one healthy control group.

3 Results

Scalable paratope-based classification pipeline

We developed a scalable machine learning framework to classify AIR repertoire data using

paratope-derived sequence features. Previously, these features were computed by combining

paratope clusters with a paratope similarity graph, denoted Paratope Cluster Occupancy (PCO)[13]

(Figure 1A). To avoid the all-against-all comparisons required for graph construction, we

reversed the workflow: sequences were first encoded as vectors, then efficiently clustered using

these vector representations. We term this approach Fast Approximate Clustering Techniques

(FACTS) (Figure 1B).

The pipeline begins with the extraction of paratope regions from BCR or TCR sequences,

represented as pseudo-sequences composed of the concatenated CDR1, CDR2, and CDR3. These

sequences are encoded, and the resulting embeddings are clustered using k-means (k = 50-500).

A silhouette coefficient score[32] is used to determine a good starting point for choosing the

number of clusters k. Donor-level feature vectors are constructed from cluster frequency

distributions and inter-cluster mutual information. These features are then used to train gradient-

boosted decision tree models for multi-class disease classification.

The use of FACTS qualitatively improved the scalability compared with PCO (Figure 2). Two

PCO implementations were tested: one using an exact all-against-all comparison[13] and one using

an MMSEQS-based approximation[41]. Even with MMSEQS acceleration, PCO runtimes

increased quadratically with input size (R^2 = 0.9997). In contrast, FACTS scaled linearly when

using a small number of clusters: at k = 50, runtime increased to 115 ms per 1,000 sequences (R^2

= 0.9957); at k = 500, runtime rose to 1,158 ms per 1,000 sequences (R^2 = 0.9195), reflecting the

added cost of inter-cluster comparisons. Processing 5 million sequences required approximately

1.9 CPU-hours using FACTS, compared to about 324 CPU-hours with MMSEQS-accelerated

PCO. This demonstrated an approximate 170-fold improvement in efficiency and scaled linearly

with increasing data size.

Encoded paratope features achieve robust multi-disease TCR repertoire classification

To assess classification performance, we reanalyzed publicly available TCR repertoire data

comprising 1,421 donors across 16 disease classes (Supplementary Table 1). The classifier

achieved a mean ROC AUC of 0.99 in three-fold cross-validation (Figure 3A). Per-disease

AUCs were consistently high: the lowest was for healthy controls (0.94), followed by influenza-

vaccinated donors (0.97), with all other disease classes greater than 0.98 (Figure 3B). The model

achieved high sensitivity (0.9867 ± 0.0007) with moderately high specificity (0.7785 ± 0.0203)

(Figure 3C; Supplementary Figure 1).

The dataset included most of the Mal-ID benchmark, enabling direct comparison with the Mal-

ID framework (499 donors for TCR and 550 donors for BCR dataset, five disease classes, and

one healthy control group). Using overall donor-level accuracy, our method outperformed Mal-

ID for all input types: BCR (84% vs 74%), TCR (86% vs 75.1%), and combined BCR+TCR

(89.8% vs 85.3%) (Figure 3D). Our TCR-only model achieved accuracy comparable to Mal-ID's

combined-input model, which represents a significant simplification in the input requirements for

FACTS. ROC AUCs for the Mal-ID subset were as follows: 0.9718 (BCR), 0.9747 (TCR), and

0.9833 (BCR+TCR) (Supplementary Figure 2).

MyImmune encoder for multi-disease TCR classification

We next evaluated alternative encoders within the FACTS pipeline using the Mal-ID dataset.

All encoders followed the same classification procedure, differing only in embedding generation.

For BCR sequences, among publicly available BCR encoders, IgBERT achieved the highest

performance (accuracy: $82.0\% \pm 3.7\%$; ROC AUC: 0.9736 ± 0.0092). Our TCR encoder,

referred to as MyImmune, achieved the highest performance for TCR data (accuracy: $86.2\% \pm$

6.2%; ROC AUC: 0.9775 ± 0.0097), outperforming TCRBert, ProtTrans, ESM-2, and SCEPTR

(Table 1). These results support the use of paratope-based classification and demonstrate that

MyImmune, combined with FACTS, enables highly accurate TCR-based disease classification.

Encoded paratope representations capture biologically meaningful structures of TCR

repertoires

To assess biological relevance, we visualized donor-level embeddings from encoded TCR

paratope sequences using t-SNE. In the full dataset (1,421 donors, 16 disease classes),

projections showed clear separation between disease groups, indicating that paratope-based

features capture disease-specific immune signatures (Figure 4A; Supplementary Figure 3). A

batch effect was observed in the autoimmune hepatitis (AIH) dataset, likely reflecting

differences in experimental protocols across publicly available studies (Supplementary Figure 4).

Restricting analysis to the Mal-ID TCR subset (n = 499 donors), which was collected and

processed using a standardized protocol, removed obvious batch effects and maintained strong

disease group separation (Figure 4B). The t-SNE projection also revealed older individuals (Z <

5) and younger individuals (Z > 5) clustered separately. Statistically significant age differences

were found within both healthy controls and SLE donors (Figure 4C), suggesting that paratope

features capture clinically relevant variation beyond disease labels. Similar, although not

statistically significant, trends were observed in other disease groups.

4 Discussion

This study presents a scalable, accurate, and interpretable framework for multi-disease

classification using AIR repertoires. By introducing the FACTS pipeline with paratope-focused

sequence representations, we achieved major improvements in processing speed compared with

our previous paratope similarity network approach, without compromising accuracy. This

improvement in efficiency is critical as the computational cost precluded the use of the PCO

approach on larger datasets like the Mal-ID benchmark. Applied to an even larger TCR dataset

of 1,421 donors spanning 16 disease classes, the FACTS framework demonstrated strong

classification performance. In direct comparison with Mal-ID on its six-class benchmark subset,

donor-level accuracy for single-chain inputs (BCR or TCR) was markedly higher with our

approach, suggesting that paratope-based features may have distinct advantages over clonotype-
based features.

Paratopes, comprising the CDR1, CDR2, and CDR3 regions, represent AIR residues capable of
directly interacting with antigens. Previous work has shown that paratope sequences can reflect
convergent immune responses across individuals[13], and that BCR clusters are highly antigen- and
epitope-specific[12]. Other studies have demonstrated that antibodies binding the same epitope
converge in paratope space and can be identified using deep learning predictors such as
ParaPred[42] and structure-aware tools like Ab-Ligity[43].

Here, by reversing the order of clustering and similarity comparison in our previous pipeline, we
improved training runtime without loss of accuracy. Rather than computing pairwise similarities
first, we encoded sequences into vector representations, then performed clustering in this reduced
space. The embeddings, generated using protein language models trained on natural amino acid
sequences, capture biochemical and structural properties. Such embeddings have recently been
used in various immune repertoire analyses[30,34,38,39,43]. MiniBatchKMeans clustering was then
applied to group encoded paratope sequences, enabling efficient processing of up to hundreds of
millions of sequences. Donor-level features were derived from cluster frequency distributions
and inter-cluster mutual information, which were subsequently used for classification. The
integration of these steps produced a fast, scalable pipeline for immune repertoire-based disease
classification.

Benchmarking demonstrated that the MyImmune TCR paratope encoder further enhanced
classification performance. Compared with multiple publicly available TCR protein language
models, MyImmune consistently achieved the highest accuracy on the Mal-ID cohort,
reinforcing the value of paratope-aware representation learning in repertoire-based diagnostics.

Beyond classification accuracy, the learned feature space preserved biologically meaningful
structures. Unsupervised t-SNE projections revealed clustering by disease cohort and age
associations, particularly among healthy and SLE donors, suggesting that paratope features
capture clinically relevant immune signatures beyond discrete disease classification. However,
batch effects were evident in the full 1,421-donor dataset, especially in the AIH dataset, which
likely reflects variability in experimental protocols. These challenges underscore the importance

of using well-matched, prospectively collected datasets to validate findings in clinically

controlled settings.

Overall, our findings show that paratope-encoded representations, when combined with the

FACTS pipeline, enable accurate, scalable, and biologically meaningful classification of immune

repertoires, supporting their potential for clinical translation and population-scale immune

profiling.

Contributors

N.J., A.S., F.H., and D.M.S. conceived and designed the study.

A.S., S.L., D.U., and M.L. acquired the data and performed the formal analysis.

N.J., A.S., H.S., and D.M.S. contributed to the result interpretation and critical discussion.

N.J. and D.M.S. drafted the original manuscript and prepared the figures and tables.

All authors contributed to the manuscript revision, reviewed the final version, and approved it for

submission.

Data sharing statement

All AIR-seq datasets used in this study are publicly available, and no individual-level data were

collected specifically for this investigation. The source and access information for each dataset

are detailed in Supplementary Table 1. This study was not subject to an institutional protocol and

did not require participant consent. Processed donor-level feature matrices will be made

available upon submission. Custom code for paratope extraction and model training is

proprietary but can be shared with editors and qualified academic investigators upon request

under a material transfer agreement.

Declaration of interests

A.S. and F.H. are employees and shareholders of MyImmune Corporation. D.M.S. is a

shareholder in MyImmune Corporation. All other authors declare no competing interests.

Acknowledgements

We thank all members of the Systems Immunology Lab at Osaka University for their helpful

discussions and support. This work was supported by the Japan Society for the Promotion of

Science (JSPS) KAKENHI Grant [JA23H034980], the Japan Agency for Medical Research and

Development (AMED) Grant [JP21am0101001], and the Kishimoto Foundation Fellowship

(N.J.).

Reference

1.   Schatz DG, Swanson PC. V(D)J recombination: mechanisms of initiation. *Annu Rev Genet* 2011; **45**: 167–202.

2.   Victora GD, Nussenzweig MC. Germinal centers. *Annu Rev Immunol* 2012; **30**: 429–57.

3.   Emerson RO, DeWitt WS, Vignali M, et al. Immunosequencing identifies signatures of cytomegalovirus exposure history and HLA-mediated effects on the T cell repertoire. *Nat Genet* 2017; **49**(5): 659–65.

4.   Robins HS, Campregher PV, Srivastava SK, et al. Comprehensive assessment of T-cell receptor beta-chain diversity in alphabeta T cells. *Blood* 2009; **114**(19): 4099–107.

5.   Mhanna V, Bashour H, Lê Quý K, et al. Adaptive immune receptor repertoire analysis. *Nature Reviews Methods Primers* 2024; **4**(1): 6.

6.   Zaslavsky ME, Craig E, Michuda JK, et al. Disease diagnostics using machine learning of B cell and T cell receptor sequences. *Science* 2025; **387**(6736): eadp2407.

7.   Chen Y, Ye Z, Zhang Y, et al. A Deep Learning Model for Accurate Diagnosis of Infection Using Antibody Repertoires. *J Immunol* 2022; **208**(12): 2675–85.

8.   Briney B, Inderbitzin A, Joyce C, Burton DR. Commonality despite exceptional diversity in the baseline human antibody repertoire. *Nature* 2019; **566**(7744): 393–7.

9.   Nikolich-Zugich J, Slifka MK, Messaoudi I. The many important facets of T-cell repertoire diversity. *Nat Rev Immunol* 2004; **4**(2): 123–32.

10.   Richardson E, Galson JD, Kellam P, et al. A computational method for immune repertoire mining that identifies novel binders from different clonotypes, demonstrated by identifying anti-pertussis toxoid antibodies. *MAbs* 2021; **13**(1): 1869406.

11.   Xu Z, Li S, Rozewicki J, et al. Functional clustering of B cell receptors using sequence and structural features. *Molecular Systems Design & Engineering* 2019; **4**(4): 769–78.

12.   Saputri DS, Ismanto HS, Nugraha DK, et al. Deciphering the antigen specificities of antibodies by clustering their complementarity determining region sequences. *mSystems* 2023; **8**(6): e0072223.

13.   Xu Z, Ismanto HS, Saputri DS, et al. Robust detection of infectious disease,
autoimmunity, and cancer from the paratope networks of adaptive immune receptors. *Brief*
Bioinform 2024; **25**(5).
14.   Pothuri VS, Hogg GD, Conant L, et al. Intratumoral T-cell receptor repertoire
composition predicts overall survival in patients with pancreatic ductal adenocarcinoma.
Oncoimmunology 2024; **13**(1): 2320411.
15.   Formenti SC, Rudqvist NP, Golden E, et al. Radiotherapy induces responses of lung
cancer to CTLA-4 blockade. *Nat Med* 2018; **24**(12): 1845–51.
16.   Wu L, Zhu J, Rudqvist NP, et al. T-Cell Receptor Profiling and Prognosis After
Stereotactic Body Radiation Therapy For Stage I Non-Small-Cell Lung Cancer. *Front Immunol*
2021; **12**: 719285.
17.   Zuckerbrot-Schuldenfrei M, Aviel-Ronen S, Zilberberg A, Efroni S. Ovarian cancer is
detectable from peripheral blood using machine learning over T-cell receptor repertoires.
Briefings in Bioinformatics 2024; **25**(2): bbae075.
18.   Komech EA, Pogorelyy MV, Egorov ES, et al. CD8+ T cells with characteristic T cell
receptor beta motif are detected in blood and expanded in synovial fluid of ankylosing
spondylitis patients. *Rheumatology (Oxford)* 2018; **57**(6): 1097–104.
19.   Shugay M, Bagaev DV, Turchaninova MA, et al. VDJtools: Unifying Post-analysis of T
Cell Receptor Repertoires. *PLoS Comput Biol* 2015; **11**(11): e1004503.
20.   Luoma AM, Suo S, Wang Y, et al. Tissue-resident memory and circulating T cells are
early responders to pre-surgical cancer immunotherapy. *Cell* 2022; **185**(16): 2918–35.e29.
21.   Robert L, Tsoi J, Wang X, et al. CTLA4 blockade broadens the peripheral T-cell receptor
repertoire. *Clin Cancer Res* 2014; **20**(9): 2424–32.
22.   Yusko E, Vignali M, Wilson RK, et al. Association of Tumor Microenvironment T-cell
Repertoire and Mutational Load with Clinical Outcome after Sequential Checkpoint Blockade in
Melanoma. *Cancer Immunol Res* 2019; **7**(3): 458–65.
23.   Schultheiß C, Simnica D, Willscher E, et al. Next-Generation Immunosequencing
Reveals Pathological T-Cell Architecture in Autoimmune Hepatitis. *Hepatology* 2021; **73**(4):
1436–48.
24.   Zhang Y, Zhu Y, Wang J, et al. A comprehensive model based on temporal dynamics of
peripheral T cell repertoire for predicting post-treatment distant metastasis of nasopharyngeal
carcinoma. *Cancer Immunol Immunother* 2022; **71**(3): 675–88.
25.   Aterido A, López-Lasanta M, Blanco F, et al. Seven-chain adaptive immune receptor
repertoire analysis in rheumatoid arthritis reveals novel features associated with disease and
clinically relevant phenotypes. *Genome Biol* 2024; **25**(1): 68.
26.   Dunbar J, Deane CM. ANARCI: antigen receptor numbering and receptor classification.
Bioinformatics 2016; **32**(2): 298–300.
27.   Lefranc MP, Pommie C, Ruiz M, et al. IMGT unique numbering for immunoglobulin and
T cell receptor variable domains and Ig superfamily V-like domains. *Dev Comp Immunol* 2003;
27(1): 55–77.
28.   Devlin J, Chang M-W, Lee K, Toutanova K. BERT: Pre-training of Deep Bidirectional
Transformers for Language Understanding, 2019.
29.   Lin Z, Akin H, Rao R, et al. Evolutionary-scale prediction of atomic-level protein
structure with a language model. *Science* 2023; **379**(6637): 1123–30.
30.   Kenlay H, Dreyer FA, Kovaltsuk A, Miketa D, Pires D, Deane CM. Large scale paired
antibody language models. *PLOS Computational Biology* 2024; **20**(12): e1012646.

31.   Pedregosa F, Varoquaux G, Gramfort A, et al. Scikit-learn: Machine learning in Python.
Journal of Machine Learning Research 2011; **12**: 2825–30.
32.   Monshizadeh M, Khatri V, Kantola R, Yan Z. A deep density based and self-determining
clustering approach to label unknown traffic. *Journal of Network and Computer Applications*
2022; **207**: 103513.
33.   Chen T, Guestrin C. XGBoost: A scalable tree boosting system. Proceedings of the 22nd
ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. San
Francisco, CA, USA: Association for Computing Machinery; 2016. p. 785–94.
34.   Wu KE, Yost KE, Daniel B, et al. TCR-BERT: learning the grammar of T-cell receptors
for flexible antigen-binding analyses. Proceedings of the 18th Machine Learning in
Computational Biology Meeting. —: PMLR; 2023. p. 194–229.
35.   Elnaggar A, Heinzinger M, Dallago C, et al. ProtTrans: Towards Cracking the Language
of Life's Code Through Self-Supervised Deep Learning and High Performance Computing. *IEEE*
Transactions on Pattern Analysis and Machine Intelligence 2021; —(—): 1–.
36.   Nagano Y, Pyo AGT, Milighetti M, et al. Contrastive learning of T cell receptor
representations. *Cell Systems* 2025; **16**(1).
37.   Gao Y, Dong K, Gao Y, et al. Unified cross-modality integration and analysis of T-cell
receptors and T-cell transcriptomes by low-resource-aware representation learning. *Cell*
Genomics 2024; **4**(5): 100553——.
38.   Barton J. Enhancing Antibody Language Models with Structural Information
(AntiBERTa2-CSSP). (preprint/discussion); 2023.
39.   Ruffolo JA, Gray JJ, Sulam J. Deciphering antibody affinity maturation with language
models and weakly supervised learning. *arXiv preprint* 2021.
40.   Olsen TH, Moal IH, Deane CM. AbLang: an antibody language model for completing
antibody sequences. *Bioinformatics Advances* 2022; **2**(1): vbac046.
41.   Steinegger M, Soding J. MMseqs2 enables sensitive protein sequence searching for the
analysis of massive data sets. *Nat Biotechnol* 2017; **35**(11): 1026–8.
42.   Liberis E, Velickovic P, Sormanni P, Vendruscolo M, Lio P. Parapred: antibody paratope
prediction using convolutional and recurrent neural networks. *Bioinformatics* 2018; **34**(17):
2944–50.
43.   Wong WK, Robinson SA, Bujotzek A, et al. Ab-Ligity: identifying sequence-dissimilar
antibodies that bind to the same epitope. *MAbs* 2021; **13**(1): 1873478.
453

Figure 1. Scalable paratope-based classification pipelines for immune repertoire data.
(**a**) The original paratope cluster occupancy (PCO) framework. After TCR/BCR sequencing, paratope regions (CDR1, CDR2, and CDR3) are defined and clustered. A paratope similarity network is constructed via all-against-all comparisons of paratope sequences, and donor-level features are derived from both clusters and networks. These features are then used to train a classification model. (**b**) The proposed fast approximate clustering techniques (FACTS). Instead of pairwise comparison, paratope sequences are first encoded into vector embeddings before clustering. Donor-level features are constructed from cluster frequencies and inter-cluster relationships. This reverse-order approach avoids the computational cost of paratope graph construction and enables scalable training of classification models.

Figure 2. Runtime comparison between PCO and FACTS pipelines.
CPU time (in seconds) is plotted against the number of sequences processed for four methods. The original PCO pipeline using exact paratope similarity (PCO_Exact, red stars) shows quadratic runtime scaling with input size due to its all-against-all comparison step. A faster variant using MMseqs2 (PCO_MMSeqs, orange circles) improves efficiency but still scales nonlinearly. In contrast, the FACTS approach achieves near-linear scaling, with FACTS configured for 50 clusters (blue squares) and 500 clusters (purple triangles) showing minimal runtime increase over 5 million sequences. The FACTS pipeline achieves up to ~170-fold speedup compared to the exact PCO method, making it suitable for large-scale repertoire analysis.

Figure 3. Encoded paratope features enable accurate multi-disease classification of TCR repertoires. (**a**) Receiver operating characteristic (ROC) curve showing overall performance of the paratope-based classifier on a 1,421-donor dataset comprising 16 disease classes, including healthy controls. The model achieved a mean ROC AUC of 0.99 with consistent performance across cross-validation folds. (**b**) One-vs-rest ROC curves for each individual class showing a robust performance across all disease classes. **(c)** Confusion matrix from one of the three cross-validation folds, illustrating donor-level classification results across the 16 disease classes. Disease labels corresponding to each class ID are provided in Supplementary Table 1. **(d)** Comparative performance between our paratope-based model ("MyImmune") and the original clonotype-based Mal-ID framework on the Mal-ID cohort, consisting of 550 donors for BCR and 499 donors for TCR dataset across six disease classes. Accuracy was computed as donor-level classification accuracy, representing the proportion of correctly classified donors.

BCR Encoders	Accuracy	AUROC	F1 score
IgBert	0.8400 ± 0.0306	0.9718 ± 0.0073	0.8386 ± 0.0386
Antiberta2	0.7920 ± 0.0497	0.9693 ± 0.0080	0.7809 ± 0.0241
AntiBERTy	0.7500 ± 0.0173	0.9555 ± 0.0108	0.7546 ± 0.0132
ESM-2 8M	0.7440 ± 0.0522	0.9501 ± 0.0158	0.7407 ± 0.0526
ProtTrans	0.7360 ± 0.0371	0.9537 ± 0.0108	0.8057 ± 0.0514
ESM-2 150M	0.7320 ± 0.0228	0.9473 ± 0.0063	0.7281 ± 0.0369
ESM-2 650M	0.7000 ± 0.0283	0.9386 ± 0.0076	0.7031 ± 0.0366
AbLang	0.6940 ± 0.0207	0.9398 ± 0.0030	0.6880 ± 0.0403

TCR Encoders	Accuracy	AUROC	F1 score
MyImmune Encoder	**0.8619 ± 0.0616**	**0.9775 ± 0.0097**	**0.8300 ± 0.0728**
TCRBert	0.8578 ± 0.0453	0.9735 ± 0.0108	0.8201 ± 0.0533
ESM-2 8M	0.8439 ± 0.0552	0.9755 ± 0.0104	0.8153 ± 0.0586
ProtTrans	0.8438 ± 0.0458	0.9715 ± 0.0110	0.8057 ± 0.0514
SCEPTR: Large model	0.8438 ± 0.0375	0.9747 ± 0.0121	0.8135 ± 0.0425
ESM-2 150M	0.8318 ± 0.0595	0.9742 ± 0.0103	0.7969 ± 0.0673
SCEPTR: Beta-chain only model	0.8317 ± 0.0282	0.9727 ± 0.0105	0.7905 ± 0.0241
SCEPTR: Default model	0.8238 ± 0.0452	0.9709 ± 0.0111	0.7902 ± 0.0597
UniTCR	0.6875 ± 0.0594	0.9299 ± 0.0121	0.6163 ± 0.0777

Table 1. Sequence encoders form multi-disease classification
Accuracy, AUROC, and F1 score (mean ± standard deviation) are shown for each encoder using the FACTS pipeline on the Mal-ID cohort (550 donors for BCR and 499 donors for TCR dataset across 6 disease classes).

Figure 4. Encoded TCR paratope representations reveal disease- and age-associated structure.
(**a**) t-SNE projection of donor-level TCR paratope embeddings across 1,421 donors from 16 disease classes. (**b**) t-SNE projection of the encoded TCR paratope sequences from the Mal-ID cohort at donor level (n = 499 donors, 6 disease classes). (**c**) Age association across clusters for each disease group in the Mal-ID cohort. Donors clustered along the third t-SNE axis (Z) based on age, with older individuals enriched in the Z < 5 region and younger donors in Z > 5. Statistical comparisons between clusters were performed using unpaired t-tests; **** indicates p < 0.0001.