EEG decodability of facial expressions and their stereoscopic depth cues in immersive virtual reality

Felix Klotzsche[1,2], Ammara Nasim[1,3], Simon M. Hofmann[1,4], Arno Villringer[1], Vadim Nikulin[1], Werner Sommer[2,5,6], Michael Gaebler[1]

[1] Max Planck Institute for Human Cognitive and Brain Sciences, Department of Neurology, Leipzig, Germany

[2] Humboldt-Universität zu Berlin, Department of Psychology, Germany

[3] Carl von Ossietzky Universität Oldenburg, Germany

[4] Fraunhofer Institute for Telecommunications, Heinrich Hertz Institute (HHI), Department of Artificial Intelligence, Berlin, Germany

[5] Department of Physics and Life Science Imaging Center, Hong Kong Baptist University, Hong Kong, China

[6] Faculty of Education, National University of Malaysia, Kuala Lumpur, Malaysia

Corresponding author

Felix Klotzsche
Stephanstr. 1A
04103 Leipzig
Germany
klotzsche@cbs.mpg.de

Keywords

Face perception, depth perception, EEG, immersive virtual reality, emotional expressions, multivariate decoding, eye movements

Abstract

Face perception typically occurs in three-dimensional space, where stereoscopic depth cues enrich the perception of facial features. Yet, most neurophysiological research on face processing relies on two-dimensional displays, potentially overlooking the role of stereoscopic depth information. Here, we combine immersive virtual reality (VR), electroencephalography (EEG), and eye tracking to examine the neural representation of faces under controlled manipulations of stereoscopic depth. Thirty-four participants viewed computer-generated faces with neutral, happy, angry, and surprised expressions in frontal view under monoscopic and stereoscopic viewing conditions. Using time-resolved multivariate decoding, we show that EEG signals in immersive VR conditions can reliably differentiate facial expressions. Stereoscopic depth cues elicited a distinct and decodable neural signature, confirming the sensitivity of our approach to depth-related processing. Yet, expression decoding remained robust across depth conditions, indicating that under controlled frontal viewing, the neural representation of behaviorally distinguishable facial expressions is invariant to binocular depth cues. Eye tracking showed that expression-related gaze patterns contained comparable information but did not account for neural representations, while depth information was absent in gaze patterns—consistent with dissociable representational processes. Our findings demonstrate the feasibility of EEG-based neural decoding in fully immersive VR as a tool for investigating face perception in naturalistic settings and provide new evidence for the stability of expression representations across depth variations in three-dimensional viewing conditions.

Introduction

Faces are among the most relevant visual input for humans. They play a crucial role in social communication, enabling us to recognize and distinguish individuals, as well as to infer detailed semantic information about them, such as their emotional states (Bruce & Young, 1986; Jack & Schyns, 2015). Humans are able to detect subtle differences between faces and facial expressions, although they are composed of relatively few key features (e.g., one mouth, one nose, two eyes) and share a similar configuration. Moreover, faces and the emotions they convey are processed and evaluated more rapidly than other objects of comparable visual complexity (Willis & Todorov, 2006). The sophisticated processing of facial stimuli is supported by a hierarchical cortical network, ranging from retinotopic areas in the early visual cortex, which process single features, to face-specific visual areas like the fusiform face area (FFA) that encode view-invariant, abstract representations of faces (Calder & Young, 2005; Duchaine & Yovel, 2015; Freiwald et al., 2016; Haxby et al., 2000).

In the real world, humans constantly process faces in complex, three-dimensional (3D) settings. However, laboratory studies of face perception usually simplify these experiences, relying on two-dimensional (2D) stimuli presented on flat screens. Such conditions omit key features of natural vision—for example, binocular depth information. Binocular disparity is a visual feature which is automatically and (seemingly) effortlessly extracted from the retinal inputs and integrated into a percept with stereoscopic depth: Each eye captures a slightly different image, which the cerebral cortex integrates—together with further visual cues such as relative size, blur, shading, perspective, texture gradients, or motion as well as with sensory signals from other modalities—to gain depth information about the shape of an object or the configuration of a scene (Parker, 2007; Welchman, 2016). During this fusion into a stereoscopic representation, coarse percepts change and refine over time (Menz & Freeman, 2003). Among the various available depth cues, binocular information plays a special role for the subjective experience of stereoscopic depth (Barry, 2010; Vishwanath, 2014). However, binocular disparity information is neither necessary (Vishwanath & Hibbard, 2013) nor sufficient (Cumming & Parker, 1997) for a subjective impression of stereoscopic depth. The precise contribution of binocular disparity information for the brain's processing of complex stimuli like faces—and, in particular, how it interacts with the representation of other visual features of the same object—is still unclear.

As humans often encounter faces at close range—where binocular disparity provides important
cues (Cutting & Vishton, 1995)—depth information may play a key role in face processing. Indeed,
stereoscopic depth modulates the recognition and representation of faces and facial expressions:
It improves participants' ability to recognize the same person from different viewpoint angles or
distances (Burke et al., 2007; C. H. Liu & Ward, 2006; H. Liu et al., 2020). C. H. Liu et al. (2006)
observed impaired performance when recognition conditions differed from encoding conditions in
the availability of spatial depth cues (stereoscopic vs monoscopic), suggesting that neural
encoding depends on whether faces are processed with or without stereoscopic depth
information. Hakala et al. (2015) demonstrated that stereoscopically presented facial expressions
evoke stronger emotional responses than their monoscopic counterparts, with natural depth cues
amplifying negative reactions to angry faces. Children (3–6 years old) are faster in recognizing
emotional facial expressions in stereoscopic as compared to monoscopic conditions (Wang et al.,
2017). Collectively, these findings suggest that stereoscopic depth cues can shape natural face
processing, highlighting the importance of binocular information in how humans perceive and
respond to faces and their expressions.

Here, we used electroencephalography (EEG) in combination with immersive virtual reality (VR)
and eye tracking to investigate how the human brain processes faces and facial expressions in
the presence of stereoscopic depth cues. Due to its high temporal resolution, EEG is a powerful
tool for studying the temporal dynamics of face perception (for reviews see Brunet, 2023; Rossion,
2014). Previous EEG research has identified several characteristic components of the event-
related potential (ERP), each emerging within a specific time window and reflecting a distinct
processing stage of cortical face processing: The earliest component associated with face
processing, is the P1 component (80–120 ms) which has been linked to low-level visual analysis
of faces (Rossion & Caharel, 2011). It is followed by the N170 (130–200 ms), generated in the
fusiform gyrus (Gao et al., 2019), which encodes structural face recognition and differentiates
facial expressions and identities (Rossion & Jacques, 2012). Around 250–300 ms after stimulus
onset, the Early Posterior Negativity (EPN) indexes reflexive attentional orienting toward
emotional contents and its selection for further processing (Schindler & Bublatzky, 2020). Finally,
the Late Positive Complex (LPC; 400–600 ms) reflects higher-order cognitive evaluation of faces
and other stimuli of motivational relevance (Schacht & Sommer, 2009; Schupp et al., 2006).

These well-established ERP components provide informative temporal markers of the sequential
stages of face processing in the human brain. However, because they are typically derived by

averaging over predefined electrode clusters, they may overlook more subtle, spatially distributed patterns of neural activity. Multivariate decoding—used to probe whether specific stimulus information is present in high-dimensional neurophysiological signals (e.g., Kamitani & Tong, 2005; for a recent review, see Peelen & Downing, 2023)—extends this approach by exploiting the full spatiotemporal structure of the EEG data and optimally weighting channels on the level of the individual participant (Carrasco et al., 2024; Grootswagers et al., 2017). By doing so, it can offer greater sensitivity, detecting stimulus-specific information embedded in distributed activity patterns—information that might not be apparent in classical ERP analyses.

In the following, we refer to such decodable information as *representation*. While this usage is controversial (see Fallon et al., 2023, for an overview), it aligns with how the term is commonly used by many neuroscientists—where *representation* is often approximated with *decodability* and reflects mutual information between a pattern of brain activity and an experimental variable of interest (Hebart & Baker, 2018).[1] Neuroscientists use decodability as a proxy for determining *where* and *when* information about a feature is available in the brain (Grootswagers et al., 2017). EEG-based decoding offers high temporal resolution, enabling researchers to track the sequential stages at which such information emerges. Quantifying the contribution of individual EEG channels to decoding performance permits a coarse spatial interpretation of the underlying signals. Subsequent source reconstruction can map these patterns to their cortical generators, thereby identifying the brain regions most relevant for the representation of the decoded feature.

In the present study, we applied this approach to investigate facial expression representations while selectively manipulating the presence of stereoscopic depth cues. To achieve this, we used immersive VR with head mounted displays (HMDs) to deliver binocular stimulation. Immersive VR is increasingly adopted by cognitive and perceptual scientists—not only for its ability to present stereoscopic depth (Choi et al., 2023; Draschkow, 2022; Tarr & Warren, 2002; Thurley, 2022) but also because the computer-generated stimulation of the (almost) entire visual field enables high levels of experimental control and facilitates various opportunities for stimulus modification. Building on these developments, cognitive neuroscientists have begun combining immersive VR

---

[1] Successfully decoding a stimulus feature suggests that the decodable information is present in the recorded data and—given some necessary assumptions about their origin—also available in the identified physiological sources (e.g., brain regions at a given moment in time). This does not imply that the brain (e.g., other brain regions) actually makes use of this information—which would be a necessary requirement for a *representation* in a more strict interpretation (Kriegeskorte & Douglas, 2019; Ritchie et al., 2019).

with EEG to investigate neural processing of face stimuli under 3D viewing conditions (Nolte et al., 2024; Sagehorn et al., 2023; Sagehorn, Johnsdorf, et al., 2024; Sagehorn, Kisker, et al., 2024; Schubring et al., 2020).

However, combining HMDs with EEG recordings presents several challenges. Placing the HMD over an EEG cap introduces additional sources of noise, potentially obscuring signals of interest (Tauscher et al., 2019; Weber et al., 2021). Larger stimulus eccentricities due to the wider field of view compared to conventional computer screens can affect visually evoked ERP components (Klotzsche et al., 2023). In addition, while conventional laboratory studies often restrict eye movements to control retinotopic stimulus presentations, VR paradigms typically permit free exploration of the environment, which leads to eye movement-related artifacts and confounds in the EEG data and may require different analytical approaches (Nolte et al., 2024, 2025). Finally, little is known about how the mere addition of binocular depth alters the neural processing of relevant stimuli. Overall, it remains unclear to what extent findings from conventional 2D screen-setups generalize to 3D settings that include stereoscopic depth information.

The present study had two main objectives. First, we addressed a methodological challenge: whether time-resolved EEG decoding can recover facial expression information in an immersive VR setup, where signal quality and noise sources differ from conventional laboratory settings. Second, we examined whether the neural representations of facial expressions are modulated by the presence of stereoscopic depth cues—examining both whether depth information alters expression-related activation patterns and whether stereoscopic depth itself is a decodable feature in the EEG. To contextualize these findings, we performed complementary source reconstruction and eye-tracking analyses to characterize neural and eye movement-related origins of both facial expression and stereoscopic depth cue representations.

171
Figure 1: Experimental paradigm and decoding analysis. **(a)** In each trial of the emotion recognition task,
participants fixated centrally before a face stimulus was presented for 1,000 ms. Subsequently, they
selected the recognized emotional expression using the VR controller. **(b)** Face stimuli were presented
either with (right) or without (left) stereoscopic depth information. For the stereoscopic condition, a 3D model
of the face was rendered using two slightly offset virtual cameras (a "binocular VR camera rig"), providing
binocular depth cues. For the monoscopic condition, the same 3D model was first rendered from a single
virtual camera to produce a flat 2D texture, eliminating stereoscopic disparity. This texture was then
presented to both eyes via the binocular VR camera, removing binocular depth cues while maintaining all
other visual properties. **(c)** Overview of all stimulus combinations: three different face identities (rows)
expressing four different emotional facial expressions (columns: happy, angry, surprised, neutral). Face
identity was irrelevant for the emotion recognition task. Face models were originally created and evaluated
by Gilbert et al. (2021). **(d)** Schematic of the decoding approach: A multivariate linear classifier (logistic
regression) was trained on successive time windows of EEG data, treating each channel as a feature. The
emotional expression shown in the respective trial served as the classification label. Using a 5-fold cross-
validation, the classifier was tested repeatedly on 80% of the trials and its predictions were validated on the
remaining 20%. This procedure yielded decoding performance scores per time window, reflecting the
amount of available stimulus information in the EEG data at the corresponding time in the epoch.

189
190

Figure 2: Time-resolved classification performance for different decoding targets and conditions. **(a)** Classification performance (mean ± 1 SEM) of the decoder distinguishing between the four facial expressions, trained separately for the mono- and stereoscopic viewing conditions, as well as on data pooled across both depth conditions. Horizontal lines at the bottom indicate clusters where decoding was significantly above chance. Shaded rectangles in the background mark relevant ERP time windows associated with face processing. **(b)** Selection of three (out of six) binary contrasts which underlie the multiclass classification in (a). *Angry vs neutral*: Highest decoding performance. *Happy vs surprised*:

classification performance lacks an early peak and only rises later in the trial. *Angry vs surprised*: Lowest
(but still significant) decoding performance. **(c)** Average performance per time window, depth condition (*top*;
colors as in (a)), and binary contrast (*bottom*; *: selection and colors as in (b)). Thick bars: mean ± 1 SEM.
(d) Time resolved classification performance (mean ± 1 SEM) for the task-irrelevant decoding targets:
identity of the stimulus face (*top*) and presence vs absence of stereoscopic depth information (*bottom*).
ROC-AUC: area under the receiver operating characteristic.
204

Results

EEG Decoding

Decodability of facial expressions

Information about the observed facial expression was decodable from the EEG data, indicated by
a decoding performance significantly above chance-level (Figure 2). For multi-class decoding
(distinguishing between the four facial expressions: neutral, angry, happy, and surprised), we
observed a large interval with above-chance decoding performance extending from 94 ms after
stimulus onset until the onset of the response panel (1,000 ms after stimulus onset). The highest
decoding performance (ROC-AUC; average of individual maxima: M = 0.61, SD = 0.03, 95% CI
[0.60, 0.62]) was observed for most participants at a median (Mdn) delay of 414 ms (SD = 315.81,
95% CI [306.25, 521.75]).
216

Figure 2, Supplementary Figure S3, and Supplementary Table ST1 show the decoding results for
the binary decoders which were trained to distinguish between pairs of emotions. For each
contrast, we found at least one significant cluster, demonstrating above chance-level decoding
also for all binary classifiers. Descriptively, different emotion pairs exhibited distinct pairwise-
decoding profiles, varying in average decoding performances and temporal dynamics (e.g., the
contrast between angry and neutral emotions showed higher and earlier average decodability
compared to the contrast between angry and surprised). To investigate the decoding performance
over time, we compared the ROC-AUC scores averaged within four time windows corresponding
to the P1, N170, EPN, and LPC components commonly used in EEG research on face processing.
We found a significant main effect of the time window on the ROC-AUC ($F(3,96) = 22.01$, $p <$
$.001$) which was driven by a significantly lower decoding performance in the P1-window compared

to all other time windows. The remaining time windows did not differ significantly for the multiclass

decoding approach. For the binary classifiers (contrasting pairs of facial expressions), we

observed again a significant main effect of time window ($F(3,96) = 21.13$, $p < .001$), a significant

main effect of contrast ($F(5,160) = 9.43$, $p < .001$), as well as a significant interaction ($F(15,480)$

$= 9.02$, $p < .001$). The P1-window yielded the lowest decoding performance across all binary

decoders. Only for one out of the six contrasts ("surprised-vs-happy"), the decoding performance

was significantly above chance during this time window. All other time windows did not differ in

their average ROC-AUC (across all binary contrasts) and were not significantly above chance

level in the P1 window. In the remaining time windows, all contrasts, except for "angry-vs-

surprised" in the LPC window, performed significantly above chance level. The decoders

distinguishing "angry-vs-neutral" and "angry-vs-happy" showed significantly higher decoding

performance than the other binary classifiers. This difference was most pronounced in the N170

and the LPC time windows. Details are depicted in Figure 2 and Supplementary Figure S4.

The role of stereoscopic depth cues

We did not observe different classification performances (decoding the observed facial

expression) for the monoscopic and the stereoscopic viewing conditions. The multiclass decoders

validated on trials with and without stereoscopic depth information differed neither in terms of the

maximal decoding performance (mono: M = 0.61, SD = 0.02, 95% CI [0.60, 0.62]; stereo: M =

0.61, SD = 0.03, 95% CI [0.60, 0.62]; $t(32) = -0.49$, $p = .627$) nor for the latency of the peak

decoding performance (mono: Mdn = 384.00 ms, SD = 287.71, 95% CI [285.83, 482.17]; stereo:

Mdn = 524.00 ms, SD = 386.06, 95% CI [392.28, 655.72]; $t(32) = -1.04$, $p = .305$). This was

confirmed by a cluster-corrected comparison of the decoding performance at each time-point

which did not indicate a significant difference between the two depth conditions. In a four-by-two

rmANOVA which modeled the average decoding performance as a function of the time window

(four levels: P1, N170, EPN, LPC) and the depth condition (two levels: mono- and stereoscopic),

only time window was a significant predictor ($F(3,96) = 17.82$, $p < .001$), but neither depth

condition ($F(1,32) = 1.55$, $p = .222$) nor its interaction with time window ($F(3,96) = 1.00$, $p = .395$).

Also for all the binary classifiers (distinguishing pairs of emotions), we observed no significant

differences between the two depth conditions, neither for peak decoding performance nor for its

latency (Table ST1).

To scrutinize further whether any information about the presence or absence of stereoscopic

depth cues was present in the EEG data, we made the depth condition itself the decoding target

of a binary classifier (i.e., decoding whether the data came from a trial in the mono- or the

stereoscopic condition). Figure 2d shows the time-resolved decoding performance of this

decoder. Above-chance decodability was indicated by a long interval of significant decoding

performance starting 114 ms after stimulus onset (end: 714 ms) and multiple shorter intervals at

later time points in the epoch. On average, a peak decoding score of M = 0.65 (SD = 0.07, 95%

CI [0.62, 0.67]) was observed for most participants at Mdn = 184 ms after stimulus onset.

Descriptively, the decoding performance peaked early (peak decoding time: Mdn = 184 ms, SD

= 204.17, 95% CI [114.34, 253.66]) and continuously decreased toward the end of the epoch. We

observed a similar temporal profile of the decoding performance when classifying the identity of

the stimulus face (rows in Figure 1c)—another task-irrelevant stimulus feature—from the EEG

data (peak decoding score M = 0.60, SD = 0.03, 95% CI [0.59, 0.61]; peak decoding time: Mdn =

134 ms, SD = 244.62, 95% CI [50.54, 217.46]; Figure 2d). Classifiers trained only on trials from

one of the viewing conditions (with or without stereoscopic depth information) performed equally

well when tested on trials from the same or the other ("cross-decoding") depth condition (see

Supplementary Figure S5).

Source reconstruction

Figure 3 depicts the spatial patterns (Haufe et al., 2014) underlying the decoders and a

reconstruction of the associated cortical sources. Classification of task-relevant features (facial

expression) as well as task-irrelevant features (identity, depth condition) primarily involved

occipital, parietal, and temporal sources. Early after stimulus onset (P1, N170, EPN windows),

the most informative sources for facial expression classification were located in the primary and

early visual cortex. At later stages (LPC window), sources in the parietal cortex became more

prominent contributors. Supplementary Table ST2 lists the most relevant sources for the binary

classifiers, which distinguish between pairs of facial expressions. Supplementary Figure S9

visualizes the associated cortical source reconstructions. For the contrasts with the highest

decoding performance ("angry-vs-neutral" and "angry-vs-happy"), primary and early visual

cortices remained the most informative sources, even during the LPC time window. In contrast,

the other pairwise comparisons between two emotional expressions showed more variable

results, with regions along both the ventral and dorsal processing streams playing dominant roles.

The most informative sources for the classifier trained to distinguish trials with and without

stereoscopic depth information were located along the ventral visual processing stream and in

the MT+ complex (see Figure 3 and Supplementary Figure S8). Similarly, the decoding of face

identity relied primarily on signals originating from the ventral visual processing stream during the

N170 time window (Supplementary Figure S8). In contrast, during the two later time windows

(EPN and LPC), identity decoding shifted to rely most on information from parietal regions (see

Supplementary Table ST2 for an overview).

Figure 3: Spatial patterns and localized sources related to decoding (a) facial expressions and (b) the availability of stereoscopic depth information. **(a)** *Top*: Classification of the four facial expressions. Spatial patterns of the classifier (top row) and their projection onto the cortical surface using eLORETA (second and third row) for the four time windows. Colors indicate the absolute, normalized weight of each sensor or cortical parcel (warmer colors represent higher absolute weights). In the topographies, the six most informative channels (top 10%) are highlighted in yellow. Projections on the cortical surface are masked to show only the top 5% most informative parcels. Second row: Lateral view on both hemispheres. Third row: View on occipital and parietal cortices of the right hemisphere. Colored lines on the cortex mark the outlines of relevant regions (see (c)). *Bottom*: Time course of decoding performance for multiclass classification of the four emotional expressions (as in Figure 2). **(b)** As in (a) [in reversed order], but for the classifier trained to distinguish between trials with and without stereoscopic depth information. **(c)** Outlines of relevant cortical regions, following the reduced parcellation atlas by Glasser et al. (2016) and Mills (2016). *SPC: Superior Parietal Cortex; MT+: MT+ Complex and Neighboring Visual Areas; VSVC: Ventral Stream Visual Cortex; EVC: Early Visual Cortex; PVC: Primary Visual Cortex (V1)*.

Eye Tracking

Saccade and fixation patterns

To check if the dynamics of the EEG decoding performance can be explained by eye movements, we analyzed the concurrently recorded eye tracking data (combined gaze between left and right eye) for a subsample of participants (n=17), for whom eye tracking data were available. Figure 4b shows the average fixation heatmaps on the face stimuli separately for the different facial expressions. Supplementary Figure S6 shows the corresponding heatmaps separately for each of the four time windows. Participants mostly kept fixation at the center of the face. Towards later time windows (after about 200 ms), there was a notable shift of fixations towards the lower half of the face. This observation was supported by a 4x2x4 MANOVA which modeled the average fixation position as a function of facial expression, depth condition, and time window. The multivariate result was significant for the predictor time window (Wilk's lambda = 0.93, $F(6, 1022)$ = 6.14, $p < .001$) but not for the other predictors or any interaction. Univariate follow-up analyses (rmANOVA and post-hoc t-tests) demonstrated that vertical fixation locations differed significantly

between the LPC time window and all other time windows. No significant differences were
observed among the remaining time windows, and averaged horizontal fixation positions did not
differ significantly across any time window.

In a generalized linear model (GLM; Poisson, log-linear) modeling the number of saccades
(Pseudo R² = 0.90, Supplementary Table ST3) only time window was a significant predictor (Wald
$\chi^2(3) = 115.81$, p < .001). Neither facial expression (Wald $\chi^2(3) = 2.42$, p = .491) nor depth condition
(Wald $\chi^2(1) = 1.47$, p = .225) or any interactions explained significant amounts of variance. The
average saccade amplitude did not differ significantly between facial expressions, depth
conditions, or time windows (all p-values > .150). Furthermore, the model did not explain a
substantial portion of the variance in the data (Gaussian, log-linear GLM; Pseudo R² = 0.03).
Figure 4c shows the distribution of saccade directions as a function of the time window and
expression. A MANOVA which modeled the average saccade direction (two-dimensional,
spherical coordinates), indicated a significant main effect of time window (Wilk's lambda = 0.96,
F(6, 968) = 3.22, p = .004) and a significant interaction between time window and emotional
expression (Wilk's lambda = 0.94, F(18, 968) = 1.65, p = .04), but no significant effects for the
other predictors.

Figure 4: Eye tracking analyses and comparison with the EEG decoding results. **(a)** *Top left*: Exemplary gaze trace (one trial) on a stimulus face. Saccades are plotted in red, fixations in blue. The fixation cross preceding the stimulus was displayed at (0,0). *Top right*: Vertical component of the same gaze trace over time. *Bottom left*: Horizontal gaze component over time. *Bottom right*: Saccade rate (saccades per second) over the time of the trial across all trials and participants. Colors like in (b) and (c). We observed a dip in saccade rate right after stimulus onset, followed by a sharp increase peaking during the EPN time window. **(b)** Heatmaps showing fixation distributions within the first second after stimulus onset, across all trials and participants, separated by emotional expression. **(c)** Circular histograms of saccade directions (polar angles relative to the preceding fixation), plotted per time window and emotional expression (colors like in (b)). Saccade counts are normalized by the length of the time window. Most saccades occurred during the time window of the EPN (an ERP component associated with reflexive attention to the stimulus), predominantly in downward (especially for angry and surprised faces) or lateral directions. **(d)** Decoding performance of classifiers trained on the gaze data (spherical coordinates) for different decoding targets. EEG-based decoding performance is overlaid in gray for comparison (in the subset of participants with eye tracking data). Horizontal bars at the bottom of each plot indicate time points with decoding significantly above chance level. Red bars mark significant differences in performance between eye tracking and EEG-based decoding (two-sided, cluster-corrected *t*-test). Note, EEG decoding results shown here are based on the subsample with eye tracking data (n=17), resulting in lower scores compared to Figures 1 and 2.

Decodability from gaze data

As for the EEG data, we trained another set of time-resolved, linear classifiers to test the decodability of relevant attributes—however, now from the two-dimensional gaze data (i.e., the orientation of the combined eyes in spherical coordinates). Using cluster-corrected permutation testing, we demonstrated significant decoding performance for the classifier which successfully distinguished between the four emotional expressions. This was indicated by a cluster of significant decoding scores which started 230 ms after stimulus onset and extended to the end of the epoch (1,000 ms). The highest decoding performance (ROC AUC; M = 0.59, SD = 0.03, 95% CI [0.57, 0.60]) was observed for most participants at Mdn = 700 ms (SD = 230.04, 95% CI [590.65, 809.35]). Using the four time windows which we also used to bin the EEG data (P1, N170, EPN, LPC), we found a significant effect of the time window on the decoding performance $(F_{(3,48)} = 26.78, p < .001)$, with significant pairwise differences between all time windows apart from P1 vs N170 and EPN vs LPC (in other words, no differences between the two early and between the two late time windows). Only for the two later time windows, EPN and LPC, the performance of the decoder was significantly above chance level.

We also found significant decoding performance for all binary classifiers (pairwise distinction of facial expressions) supported by cluster-corrected permutation testing against chance-level. Further, a rmANOVA comparing the average decoding performance across the binary contrasts and the four time windows revealed significant main effects for the the decoding contrast $(F_{(5,80)} = 3.12, p = .013)$ and the time window $(F_{(3,48)} = 29.70, p < .001)$, but no significant interaction

(F(15,240) = 1.50, p = .106). Post-hoc tests (pairwise t-tests, Bonferroni corrected) showed
significant differences in the decoding performance between all time windows, apart from P1 and
N170 which did not differ significantly. Later time windows yielded higher decoding performances
than early time windows. The post-hoc pairwise comparisons of the contrasts did not reveal any
significant differences (after Bonferroni correction).

Stereoscopic information

As for the EEG data, the classifier performance when decoding facial expressions from eye
tracking data did not differ between monoscopic and stereoscopic viewing conditions. For the
decoding of the facial expressions, there were no significant differences in peak performance
(mono: M = 0.60, SD = 0.03, 95% CI [0.58, 0.61]; stereo: M = 0.59, SD = 0.03, 95% CI [0.57,
0.60]; t(16) = 1.88, p = .079) or timing (mono: Mdn = 741.67 ms, SD = 268.15, 95% CI [614.20,
869.14]; stereo: Mdn = 650.00 ms, SD = 301.43, 95% CI [506.71, 793.29]; t(16) = 1.11, p = .283).
This finding was indirectly supported by a non-significant cluster-based permutation test
contrasting the time-resolved performances for expression decoding in the mono- and the
stereoscopic condition. Similarly, no binary classifier showed significant performance differences
between the two depth conditions.
In contrast to the EEG data, a separate classifier trained to explicitly differentiate between the two
depth conditions (monoscopic vs stereoscopic) based on the time-resolved eye-tracking data did
not perform above chance level (see Figure 4d). However, a classifier trained to differentiate
between the face identities achieved above chance-level decoding, indicated by a cluster of time-
points with significant decoding accuracy, beginning at 242 ms after stimulus onset and continuing
until the onset of the response panel (peak decoding score: M = 0.60, SD = 0.03, 95% CI [0.58,
0.61]; peak decoding time: Mdn = 550.00 ms, SD = 231.29, 95% CI [440.05, 659.95]; Figure 4d).

The relationship between EEG and eye tracking based decoding performances

On the group level, there was no significant correlation between the performance of the decoder
trained to distinguish facial expressions based on EEG data and the one based on eye tracking
data. This applied to peak decoding performance (r(15) = 0.059, p = .821), latency of the peak
performance (r(15) = -0.160, p = .540), and average decoding performance across the
observation window (r(15) = -0.031, p = .907). Decoding performance based on EEG data
surpassed decoding based on eye tracking data early in the trial, as indicated by a significant
cluster between 94 and 224 ms (see Figure 4d, left). For the remaining time of the observation
window, there was no significant difference between EEG and eye tracking based decoding of

facial expressions. By contrast, the decoders for facial *identity* displayed a different relationship

between their performance profiles (see Figure 4d, middle): the EEG-based decoding again

ramped up earlier than the eye tracking-based decoding (first significant cluster: 164–194 ms),

but at later stages, eye tracking-based decoding outperformed EEG-based decoding (second

significant cluster with opposite-signed cluster mass: 384–1,000 ms). In decoding the depth

condition, the classifier trained on EEG data outperformed the classifier trained on eye tracking

data (significant clusters: 114–224 ms and 244–474 ms), with the latter never reaching a

performance level above chance.

Behavior

We compared the emotion ratings provided by the participants with the objective categorization

of the facial expression (i.e., the FACS ratings provided by Gilbert et al., 2021). The results are

shown in the form of confusion matrices in Supplementary Figure S1. Recognition rates differed

across the emotional expressions (F(3,96) = 6.81, *p* < .001) but were high for all expressions

(correct: M = 90.73%, SD = 16.98, 95% CI [89.06, 92.41]). The lowest recognition level was found

for neutral faces (correct: M = 80.32%, SD = 25.12, 95% CI [71.75, 88.89]) which were classified

second most frequently as "other" (confusion rate: M = 17.39%, SD = 23.51, 95% CI [9.37, 25.41]).

We did not observe a difference in recognition rate for the mono- (M = 90.96 %, SD = 16.79, 95%

CI [88.10, 93.82]) and the stereoscopic depth conditions (M = 90.51 %, SD = 17.32, 95% CI

[87.55, 93.46]). Accordingly, there was neither a significant main effect of depth condition (F(2,

64) = 1.85, p = .165) nor a significant interaction with the emotional expression (F(6, 192) = 1.37,

p = .230).

To control for the experienced level of intensity, at the end of the experiment, we asked

participants to rate for each of the 24 stimuli (4 emotions, 3 face identities, 2 depth conditions;

Figure 1c) the intensity of the displayed emotional facial expression using the 9-point SAM scale

for arousal (Supplementary Figure S2). We observed a significant main effect of emotion (F(3,93)

= 118.95, p < .001): Angry faces received the highest intensity ratings (M = 7.82, SD = 0.93, 95%

CI [7.50, 8.14]), while neutral faces received the lowest (M = 2.69, SD = 1.66, 95% CI [2.11, 3.26]).

Happy (M = 4.60, SD = 1.47, 95% CI [4.09, 5.11]) and surprised faces (M = 6.15, SD = 0.96, 95%

CI [5.81, 6.48]) fell in between. Neither the main effect of the depth condition (F(1,31) = 0.01, p =

.932) nor its interaction with the emotional expression was significant (F(3,93) = 0.34, p = .794).

Discussion

We investigated the neurocognitive processes underlying the recognition of facial expressions in immersive VR and if the presence of stereoscopic depth cues changes the neural representations of face stimuli. In each trial, we showed a computer-generated face, which displayed one out of four facial expressions. As the main measure of interest we used time-resolved, multivariate decoding from EEG data to infer how much information about the stimulus is present in the brain signals. Our main decoding target was the emotional expression shown by the face—which the participants had to indicate at the end of each trial. Facial expressions could be decoded from EEG data with robust above-chance accuracy. At the same time, the decoding performance was not influenced by the availability of stereoscopic depth information. We demonstrate that information about the presence of stereoscopic depth cues is present in the EEG signals nevertheless: With a separate classifier we could successfully distinguish mono- from stereoscopic trials. The temporal profile of this decoding differed from decoding the expressions but resembled the temporal profile of decoding the identity of the stimulus face, another task-irrelevant feature. We therefore conclude that in neurocognitive processing of face stimuli, stereoscopic depth information is treated like other task-irrelevant stimulus features and—at least as long as the behavioral task can be easily solved without integrating this information—it does not modify the (measurable) neurophysiological representation.

Successful decoding of emotional expression

Our decoding results reveal that the EEG data recorded in our VR setup contained information about the emotional expression of the stimulus faces. Previous studies have demonstrated that similar linear EEG classifiers could distinguish between different facial expressions presented as grayscale, two-dimensional images on conventional computer screens (Smith & Smith, 2019). Our results replicate and extend these findings by showing that time-resolved multivariate decoding yields comparable results when using naturalistic, 3D face stimuli in immersive VR settings. Such setups are gaining interest in human perception and cognition research for their ability to provide more naturalistic stimulation—closer to how people perceive and experience the world—thereby potentially improving the generalizability of experimental findings to real-world contexts (Cisek & Green, 2024). Yet, VR also introduces substantial challenges compared to the traditional, more restrictive setups. For example, combining EEG with a VR headset can lower the signal-to-noise ratio by introducing artifacts from mechanical pressure on the electrodes, muscular activity caused by head movements or headset weight, or electrical noise from the

device and its cables (Tauscher et al., 2019; Weber et al., 2021). Despite these challenges, our
study shows that EEG signal quality in controlled VR settings is sufficient to reliably discriminate
between facial expressions and identities by using linear classifiers applied to an observer's EEG
data. In this context, multivariate decoding is especially valuable, condensing high-dimensional
EEG data into a one-dimensional, time-resolved, and interpretable metric—decoding
performance—via optimized, data-driven weighting of EEG channels. Cross-validation ensures
that the classification results are generalizable and not due to overfitting. In contrast, traditional
ERP analysis rely on strong a priori assumptions (e.g., preselected electrodes) and often require
extensive post-hoc corrections for multiple comparisons, yet rarely employ cross-validation. Prior
studies have shown that multivariate decoding offers higher sensitivity than conventional ERP
analyses (Carrasco et al., 2024; Grootswagers et al., 2017), which is particularly relevant for data
prone to low signal-to-noise ratios. Future VR studies on face processing in immersive contexts
may build on our findings to inform their methodological choices and anticipate effect sizes.
Consistent with the findings by Smith & Smith (2019), our EEG decoding results showed distinct
patterns for task-relevant and task-irrelevant features: emotional expression (task-relevant)
yielded sustained decodability after it surpassed chance level, whereas the decoding performance
for task-irrelevant features (here: face identity and availability of stereoscopic depth cues) peaked
early, followed by temporal decline (Figure 2).

The role of stereoscopic depth cues

We hypothesized that 3D viewing—by more closely approximating natural perceptual contexts—
would elicit more robust and distinct neural representations, thereby enhancing decoding
performance. Contrary to this prediction, we found no significant differences in decoding
performance between the two conditions for either a task-relevant (expression) or a task-irrelevant
(identity) decoding target. Stereoscopic information did not enhance decoding performance, alter
its temporal dynamics, or affect the spatial distribution of the classifier weights. These findings
were corroborated by cross-condition generalization tests (cross-decoding), where classifiers
trained and tested on stereoscopic trials performed equally well when tested on monoscopic trials,
and vice versa (Supplementary Figure S5). If 3D and 2D percepts relied on fundamentally
different neural activation patterns, we would expect reduced generalization across conditions.
However, our results provide no evidence for such a difference, suggesting that the
neurophysiological activation patterns underlying facial expression categorization remain largely
consistent regardless of the presence of stereoscopic depth information.

If the subjective percepts in the two conditions are markedly different, why do the underlying
neural activation patterns associated with the decoded features show no significant differences?
Importantly, our main analyses employed activation patterns optimized for decoding specific
target variables (facial expression, face identity), not representing the brain's holistic response to
the stimuli. Within this scope, 3D and 2D conditions did not show differences. However, when
directly decoding the presence of stereoscopic depth cues, we identified significant distinctions in
the neural responses, peaking around 180 ms after stimulus onset and subsequently declining—
similar to the temporal profile for decoding face identity, another task-irrelevant feature (Figure
2d). We thereby demonstrate that the distinction between viewing conditions with and without
stereoscopic depth cues was detectable in our neurophysiological data. This adds to previous
findings regarding binocular depth processing gained with different methods (from single cell
recordings in non-human primates to fMRI in humans; for an overview see Welchman, 2016) and
stimuli (from face pictures; Chou et al., 2021; to abstract random dot motion; Parker, 2007). Our
study addresses a relevant research gap by demonstrating that EEG data in a VR setup with
naturalistic, computer-generated stimuli can track stereoscopic depth processing. To our
knowledge, this is the first study demonstrating that face stimuli differing only in stereoscopic
depth cues can be differentiated through EEG decoding while investigating potential interference
with the representation of other stimulus features.

Cortical sources

In an exploratory analysis, we applied source reconstruction to project the spatial patterns
associated with the decoders back onto the cortical surface. For the classification of emotional
expressions, primary and early visual cortices contributed most substantially, especially shortly
after stimulus onset (P1, N170, and EPN windows). This dominance was particularly evident in
the binary contrasts with the highest decoding performance ("angry-vs-neutral", "angry-vs-happy";
see Supplementary Figure S9 and Supplementary Table ST2). In contrast, lower-performing
binary classifiers (e.g., "angry-vs-surprised"), relied primarily on regions in lateral occipital and
posterior inferotemporal cortex. This suggests that decoding was more reliable when information
about the contrast was also present in primary or early visual cortices. This aligns with previous
studies which found that early visual cortices, which mostly process low-level stimulus features,
support effective visual input decoding (Kamitani & Tong, 2005; Lützow Holm et al., 2024; Wilson
et al., 2024). Accordingly, the contrasts with the highest decoding performance expressed the
most salient visual differences between the involved faces. For example, angry faces were
characterized by a widely opened mouth showing both rows of teeth, whereas neutral and happy

faces had a closed mouth with no teeth visible. The decoding of these contrasts may have relied

heavily on these low-level feature representations. Nevertheless, contrasts with more subtle low-

level visual differences still yielded above chance-level decoding, primarily drawing on brain

regions higher in the visual processing hierarchy. When two facial expressions lacked sufficient

differences in their low-level visual features, decoding appeared to rely more on signals from

cortical areas known to process abstract features of facial expressions. Overall, our findings

indicate that also for naturalistic face stimuli the decoding-based approach does not simply exploit

arbitrary features, rely solely on low-level visual features, or exclusively depend on abstract

representations of the observed facial expression.

Running the source reconstruction separately for the mono- and stereoscopic conditions yielded

only slightly different distributions across the cortical surfaces as compared to running it on the

pooled data (see Supplementary Table ST2). We attribute these variations to the fact that splitting

the data set leads to less robust source estimates and therefore a higher variance. Overall, we

did not observe a systematic difference between the distribution of sources in the mono- as

compared to the stereoscopic viewing condition, congruent with the numeric decoding results.

The decoder trained to explicitly categorize the depth condition (i.e., separating mono- from

stereoscopic trials) mostly relied on information from areas in the ventral visual stream. Also, the

decoding of the different face identities was mostly informed by areas in the ventral visual

stream—in particular during the N170 time window where the decoding performance was highest.

This aligns with previous findings that the N170 reflects activity of the fusiform face area (Gao et

al., 2019) and neighbouring ventral areas which process information relevant for distinguishing

different faces (Eimer, 2011; Grill-Spector et al., 2017; Kanwisher & Yovel, 2006).

Our spatially resolved source reconstruction has limitations: We used a common average head

model without individual anatomical brain scans, relied on the canonical locations in the 10-20

system without participant-specific registration, and faced potential spatial distortions (i.e.,

electrode displacement) from the VR headset worn over the EEG cap. Despite these constraints,

we successfully recorded and analyzed spatially interpretable signals that meaningfully map onto

the cortical surface.

Computer-generated faces as stimuli

We used computer-generated stimuli, unlike most EEG studies on human face processing which

have typically relied on standardized photographs (e.g., from the Chicago Face Database; Ma et

al., 2015). Computer-generated stimuli can be precisely tailored to the specific requirements of each study whereas photographs are less modifiable and challenging to alter without introducing visible distortions. For example, to produce gradual (i.e., parametrically adjustable) versions of facial expressions, "morphing" between versions of two existing images has been used (Steyvers, 1999). In recent years, more complex generative algorithms have gained momentum which allow for the creation of artificial but increasingly naturalistic face stimuli both in 2D and 3D (e.g., Barthel et al., 2025; Feng et al., 2021). Here, we used 3D models and predefined blend shape modifications to generate a set of static facial expressions. These expressions had been evaluated in 2D (i.e., rendering 2D images of the generated 3D models) by an independent sample of both experts and non-experts (Gilbert et al., 2021), ensuring participants could clearly distinguish them—increasing the likelihood of obtaining separable EEG signals. Our results establish that robust EEG decoding is achievable in immersive VR when using clearly distinguishable face stimuli, serving as a foundation for future studies using more ambiguous facial stimuli to explore how these affect both behavioral responses and EEG decodability.

Behavioral recognition

Participants were clearly able to recognize the displayed emotional facial expressions. We designed the stimuli by selecting facial expressions (i.e., FACS configurations) with empirically validated high recognition rates (Gilbert et al., 2021), minimizing ambiguities in decoding arising from subjective indecisiveness. This approach ensured that potential challenges encountered during neural decoding could be ascribed to a lack of information in the EEG signal itself (e.g., low signal-to-noise ratio), rather than to the relevant information not being encoded in the first place. While future studies using more ambiguous facial expressions may reveal additional aspects of stereoscopic information processing, here we sought to minimize the risk of uninterpretable null results due to non-significant decoding scores. A prior EEG decoding study using clearly distinguishable facial expressions achieved only modest above-chance performance (Smith & Smith, 2019), and VR-EEG setups are likely to exacerbate noise-related reductions in effect size. We therefore prioritized maximizing decoding feasibility in VR-EEG as a foundational step for subsequent work, with a special focus on the introduction of stereoscopic depth cues.

Building on our results and effect sizes, future studies can now more confidently work their way towards more ambiguous facial expressions while studying the concurrent neurophysiology. We cannot exclude the possibility that for more ambiguous facial expressions, for which decoding is more difficult (both for the human observer and the EEG decoder), stereoscopic depth cues

become more critical. Similarly, in computer vision-based recognition of human facial
expressions, it has been shown that, particularly for low-intensity expressions, models
incorporating 3D information outperform those using only 2D information (Savran et al., 2012).

Emotional intensity of the stimuli

Participants' subjective ratings at the end of the experiment indicated differences in emotional
intensity between the facial expressions and the different identities. Stereoscopic depth had no
influence on the intensity ratings.

While the stimulus intensity may partially explain the EEG decoding results, for example, through
arousal contagion (Herrando & Constantinides, 2021), this alone cannot fully account for the
results. While emotional arousal has widespread effects in the human brain which can be read
out by similar decoding approaches (Hofmann et al., 2021), these are typically not localized in
early visual cortices—one of the most informative brain areas in the present study. Furthermore,
face identity was decodable with similar accuracy to expressions despite substantially weaker
differences between the identities in terms of emotional intensity. Finally, stereoscopic viewing
conditions were successfully differentiated based on the EEG, despite no differences in the
emotional intensity ratings between with and without stereoscopic depth cues.
However, the above argumentation may hold less for later times in the trial (>500 ms after stimulus
onset), during which the decoding performance declined for the task-irrelevant decoding targets
(identity and depth condition) while it was constant for the decoding of the facial expressions.
Also, some of the most informative sources shifted from early visual cortex to parietal and ventral
temporal regions, which have been found to be modulated by emotional arousal (Greene et al.,
2014; Lettieri et al., 2019; Wade-Bohleber et al., 2020). This suggests that early decoding reflects
visual feature processing, while later stages may incorporate emotional arousal effects.

Eye tracking results and their relation to the EEG results

The EEG decoding might have been influenced by eye movements (Mostert et al., 2018), as
participants could freely explore the faces (for 1,000 ms) after initial central fixation. Analyses of
fixation locations and saccade parameters revealed that the saccade rate peaked around the EPN
time window, with later fixations targeting the lower face—consistent with previous findings
(Schurgin et al., 2014). Saccade direction, especially in the later part of the trial, was modulated
by the facial expression—also consistent with previous findings (Calvo et al., 2018; Schurgin et
al., 2014; Vaidya et al., 2014). Time-resolved linear classifiers showed comparable decoding

640 performances from eye tracking and EEG data (Figure 4)—with similar temporal profiles—raising

641 the question of whether EEG decoding might, in the end, simply reflect eye movements rather

642 than neurophysiological representations of stimulus features (see (Mostert et al., 2018), for a

643 more detailed discussion of this argument and potential underlying mechanisms).

645 Importantly, multiple analyses indicate that eye movements do not fully account for the observed

646 EEG patterns. First, if the decodable activity in the EEG data was directly caused by eye

647 movements (e.g., due to eyeball motion or by retinal image shifts), both time series should be

648 perfectly time-aligned or show a slight lead for eye tracking signals. Instead, we observed a

649 different pattern: eye tracking decodability consistently lagged behind EEG signals by 100–200

650 ms (see Figure 4d). This delay cannot be attributed to temporal imprecision during data recording.

651 To compensate for potential lag in eye tracking data recorded with the HTC Vive Pro Eye, we

652 post-hoc aligned it with the EEG time series, by cross-correlating the eye tracking data with the

653 electrooculogram channels. We identified and corrected a similar delay as reported by Stein et

654 al. (2021). Stimulus information was therefore decodable from EEG *before* the concurrent eye

655 tracking data, making it implausible that eye movements caused the patterns we observed in the

656 EEG. Second, if EEG decodability were merely a byproduct of the eye movements, decoding

657 scores from both modalities should be correlated (e.g., participants with highly/late decodable eye

658 movements should exhibit high/late EEG decoding peaks). Contrary to this assumption, we found

659 no systematic relationship between EEG and eye tracking-based decoding metrics on the

660 participant level (see Supplementary Figure S7). Finally, while the decoding performance curves

661 for EEG and eye tracking look similar when classifying facial expressions, the patterns differ for

662 the task-irrelevant decoding targets (Figure 3d). Most prominently, the depth condition—while well

663 decodable from EEG—was entirely undecodable from eye tracking data. These dissociations

664 make it unlikely that EEG decoding in our data set merely reflects eye movements. While the

665 similarity in some dynamics suggests shared information between the modalities, the

666 dissociations strongly indicate that EEG decoding provides complementary insights, capturing

667 aspects of neurocognitive processing beyond what eye tracking data alone can reveal—for

668 example, the presence or absence of stereoscopic depth information.

669 Conclusion

670 In sum, our results demonstrate that emotional facial expressions can be reliably decoded from

671 EEG in immersive VR, with no clear advantage observed under conditions involving stereoscopic

depth cues. While the presence of stereoscopic depth elicited distinct neural signatures, it did not affect the decodability of other, orthogonal face features—whether task-relevant or irrelevant. This suggests that, in controlled facial emotion recognition tasks using clearly distinguishable, static stimuli, the brain treats stereoscopic depth like other independent stimulus features—at least from the perspective of decodable EEG representations. Our findings establish a methodological foundation for EEG-based decoding in immersive VR and invite future research to explore how richer, more ambiguous, or dynamic face stimuli might leverage stereoscopic depth information in behaviorally and neurophysiologically meaningful ways.

Methods

Participants

We acquired data from 34 healthy, young, female adults (age: M = 26.65, SD = 4.56, 5 left-handed). Persons wearing glasses could not participate in the study to facilitate compatibility with the eye tracker. We ensured intact stereoscopic vision in all participants using a Titmus test (*Fly-S Stereo Acuity Test*, Vision Assessment Corporation, Hamburg, Germany). The study was approved by the ethics committee of the Department of Psychology at the Humboldt-Universität zu Berlin and participants provided their written consent prior to participation. Participants were compensated with 12 € per hour.

The final sample consisted of data from 33 participants for the EEG analyses (incomplete data for 1 participant) and 17 participants for the eye tracking control analyses (due to technical failure, no eye tracking data were stored for the remaining 16 participants).

Setup

We recorded participants' electroencephalogram (EEG) and electrooculogram (EOG) using a LiveAmp amplifier (BrainProducts GmbH, Gilching) and 60 active electrodes according to the 10-20 system in an electrode cap (actiCAP snap; BrainProducts). Four EOG electrodes were placed below the eyes and next to the outer canthi. All electrodes were referenced to electrode FCz (ground: FPz). EEG and EOG were sampled at a rate of 500 Hz and using a hardware-based low-pass filter at 131 Hz (third-order sinc filter, −3 dB cutoff). We ensured that at the beginning of the experiment, the impedances of all electrodes were below 25 kΩ.

During the VR part of the study, participants were seated and wore a VR headset (HTC Vive Pro Eye, HTC, Taiwan) with an integrated eye tracker (sampling rate: 120 Hz). We adjusted the headset at the beginning of the experiment to match the interpupillary distance of the participant. The VR headset was positioned on top of the EEG cap (covered by a disposable shower cap). The flat design of the actiCAP snap electrodes, combined with the cushioning of the HTC Vive Pro's back section, facilitated an even weight distribution, minimizing excessive pressure on any individual electrode. A custom facial interface cushion with recesses at designated locations prevented pressure on the frontal EEG electrodes (Fp1/2).

Software

For the implementation of the experiment, we used the Unity game engine (v2020.3.3f1; Unity Technologies) in combination with SteamVR (Valve Corporation) and ran it on a VR-ready PC (Intel Core i9-9900K, 3.6 GHz, 32 GB RAM, NVIDIA RTX 2080Ti GPU, Windows 10). The computer was connected to the EEG amplifier via an analog port (D-SUB 25) to enable synchronization of the EEG data with the experimental events. We used the EDIA toolbox (Klotzsche et al., 2025)—an extension of the Unity Experiment Framework (v2.3.4; Brookes, 2017/2019; Brookes et al., 2020)—for structuring the experiment, recording events, and tracking the behavior (incl. eye movements). The eye tracker was interfaced using the SRanipal SDK and EDIA to allow for sampling the eye tracking data at 120 Hz. To synchronize the data streams (i.e., stimulus onset events, eye tracking, EEG), we used custom C# scripts to send analog triggers (EEG) and store associated timestamps (eye tracking and event data). We recorded EEG and EOG data using the BrainVision Recorder software (v1.22.0101; BrainProducts). Before and after the VR-based part of the experiment, participants filled in questionnaires implemented in SoSciSurvey (Leiner, 2019). Data analysis was performed using Python (v3.10.4), Scikit-learn (v1.5.1; Pedregosa et al., 2011), SciPy (v1.14.0; Virtanen et al., 2020), statsmodels (v0.14.2; Seabold & Perktold, 2010), and NumPy (v1.26.4; Harris et al., 2020).

Stimuli

The stimulus set entailed computer-generated faces from three digital humans, each showing four different facial expressions (angry, happy, neutral, surprised; see Figure 1c), yielding 12 static face stimuli in total. We generated the faces using the open-source software makehuman and the FACSHuman plugin (Gilbert et al., 2021), based on material provided by the first author of the plugin. Gilbert et al. (2021) provide validations of 2D, grayscale versions of these stimuli. Two independent raters, professionally trained in the Facial Action Coding System (FACS; Ekman &

Friesen, 1978), had approved the adherence of the emotional expressions to the FACS criteria

and their recognizability was demonstrated in a sample of naïve participants in an online

experiment (Gilbert et al., 2021). For the present study, we selected the four emotional

expressions which were best recognized and distinguished from one another in this validation

experiment. We chose only female faces and we manually masked the hair and the ears of the

3D models (using the Blender software; v2.93, Blender Development Team, 2021) to decrease

task-unrelated differences between the stimuli. Each face stimulus measured approximately 24

cm in vertical height (from the crown of the head to the base of the neck), roughly matching the

dimensions of an adult human face in physical reality. We presented the faces against a gray

background and at a distance of 1.37 virtual meters from the perspective of the participant, so

that for the observer each face spanned approximately 10 degrees of visual angle (dva) along its

vertical axis. Stimuli were presented centrally in the visual field in a way that the virtual head

frontally faced the participant irrespective of the orientation of the participant's head (i.e., in *local*

space). Head movements, therefore, did not lead to displacements of the stimuli within the visual

field. For the 3D condition, we displayed the regular three-dimensional model of the face stimuli,

yielding a stereoscopic view in the VR headset. The VR software renders two slightly different

viewpoints of the scene to the displays in the headset, thereby enabling stereoscopic depth cues.

In the 2D condition, we replaced the 3D model by a two-dimensional "portrait shot" taken by a

single cyclopean (virtual) camera and displayed as a 2D plane (canvas) in the Unity scene. The

2D image was size- and position-aligned with the (invisible) 3D head model and then rendered to

the displays in the headset, yielding an impression very similar to the rendering in the 3D

condition, just without stereoscopic depth information (Figure 1b). The percept in the 2D condition

was comparable to viewing a life-size portrait picture from a distance of 1.37 m.

Task

In the main task of the experiment, participants performed an emotion recognition task (Figure

1a). In each trial, after a fixation period of 500 ms, we displayed for 1,000 ms a single face stimulus

centrally in the visual field of the participant. After the offset of the face, the participant was

presented with five response buttons arranged in a cross-like fashion centrally in the visual field

(see Figure 1a). The buttons displayed the four facial expression categories (neutral, angry,

happy, surprised) as well as the option "other". Using a VR controller, participants indicated their

response by pointing a ray toward the corresponding virtual button. The assignment of the buttons

to the positions on the cross was randomized across trials. Participants could therefore only

decide where to press once the buttons were visible, thus avoiding preparatory activity during the

presentation of the face stimulus. The next trial started immediately after the response or
automatically 5,000 ms after stimulus offset.

In 50% of the trials, the face stimuli were shown with stereoscopic depth information. In the
remaining trials, the 2D version of the face was presented. The experimental manipulations (facial
expression, identity, depth condition) were fully interleaved and pseudorandomized, ensuring a
uniform distribution of all experimental conditions within each block. Participants completed six
experimental blocks with 120 trials each, yielding 720 trials in total. After each block, the
experiment was paused and participants could take a short break (incl. removal of the VR headset
and re-calibration of the eye tracker).

Before the start of the first block, participants completed 24 training trials to get familiar with the
task and the stimuli. In these trials, each combination of face identity, facial expression, and depth
condition was shown once in a random sequence. Data from the training trials were not analyzed.
After the main block of the experiment, participants performed an intensity rating of all face stimuli.
To this end, all 24 combinations of face identity, facial expression, and depth condition were
shown in a random sequence in the VR headset. This time, the face stimulus was visible
permanently (until the participant had responded) above a 9-point self-assessment manikin (SAM)
scale (Bradley & Lang, 1994) that allowed the participant to indicate the intensity (i.e., the degree
of emotional arousal) of the displayed facial expression (see Supplementary Figure S2).
Participants selected the according level with the VR controller. No EEG or eye tracking data were
recorded for this part.

EEG preprocessing

We processed the EEG data with MNE-Python (v1.2.3; Gramfort et al., 2013). First, we identified
and rejected channels which were noisy throughout the experiment based on their power
spectrum and visual inspection. Using ICA decomposition (extended Infomax), we then removed
artifacts caused by blinks and eye movements. For fitting the ICA solution, we used a separate
copy of the data which we filtered between 1 and 40 Hz (FIR filter with a Hamming window of
length 1651 samples, lower/upper passband edge: 1.00/40.00 Hz, lower/upper transition
bandwidth: 1.00/10.00 Hz, lower/upper −6 dB cutoff frequency: 0.50/45.00 Hz). From this copy,
we extracted epochs of 1,300 ms in length, starting 300 ms before and ending 1,000 ms after the
onset of the face stimuli. Epochs with particularly noisy EEG signals were identified using the
autoreject software (v0.4.3; Jas et al., 2017) and removed before fitting the ICA weights. Based

on their correlation with the bipolar EOG channels and visual inspection, we identified
components related to blinks and other eye movements. Using only the remaining ICA weights
(i.e., setting the weights of affected channels to zero), we cleaned a separate version of the data.
This dataset was filtered between 0.1 and 40 Hz (FIR filter with Hamming window of length 16,501
samples, lower/upper passband edge: 0.10/40.00 Hz, lower/upper transition bandwidth:
0.10/10.00 Hz, lower/upper −6 dB cutoff frequency: 0.05/45.00 Hz) to preserve slow ERP
components. Again, we extracted epochs of 1,300 ms in length, starting 300 ms before and ending
1,000 ms after the onset of the face stimuli. For baseline-correction, we subtracted the mean
voltage during a 200 ms baseline interval (i.e., the 200 ms before stimulus onset) from each
epoch. Subsequently, we used the autoreject package for local (i.e., per participant, sensor, and
epoch) interpolation and trial rejection.

EEG decoding

We trained and cross-validated time-resolved linear classifiers on the EEG data to test the
decodability of the facial expressions from the participant's brain activity. A separate decoding
model was validated for each participant using all available EEG channels. The samples used for
training and testing the classifier were formed by averaging mini-batches of three trials from the
same class. Using averaged data from mini-batches has been found to improve the performance
of classifiers trained on EEG data due to suppression of noise (Adam et al., 2020; Grootswagers
et al., 2017). Along the time-dimension, we downsampled the signal using a moving average of
five samples (10 ms) with no overlap. For each time point, we then trained a logistic regression
model (solver: liblinear, L2-regularization: $\lambda = 1.0$) on the data from all 60 EEG sensors and
assessed its decoding performance by means of a stratified 5-fold cross-validation. In each fold,
the model was trained on 80% of the mini-batches and tested on the remaining 20% while we
kept the class proportions equal between train and test sets. Comparing the model predictions
with the ground truth (FACS ratings of the facial expressions) in the test set, we calculated the
area under the receiver operating characteristic (ROC-AUC) to assess the model's decoding
performance. To obtain a robust estimate, we performed this decoding procedure 50 times for
each participant and time point—varying the random allocation of trials into mini-batches and
randomly splitting samples into train and test sets. An overall decoding score per time point and
participant was obtained by averaging the ROC-AUC scores across all repetitions.

We conducted cluster-based permutation tests on the group-level to determine whether the
decoding performance was significantly above chance-level during the first second after stimulus

onset. To this end, we calculated a one-sided paired t-test for each time point, testing if the actual

decoding score was significantly higher than chance (ROC-AUC = 0.5). The cluster-based

permutation procedure allowed for a correction of the number of tests (i.e., the number of time

points). For a physiological interpretation of the decoding results, we calculated the *patterns* of

the classifier (by multiplying the covariance of the EEG data with the filter weights; Haufe et al.,

2014) for each time point.

To test the decodability of the facial expression (i.e., a four-class classification problem), we

trained the above-mentioned model by applying a *one-vs-rest* (i.e., one vs the three remaining

conditions) multi-class extension of the binary classifier. We further evaluated separate models

for each two-sided contrast (i.e., six pairwise contrasts between the four emotional expressions)

for enhanced interpretability.

We calculated the mean decoding score within four distinct time windows, based on canonical

ERP components associated with face expression processing (P1, N170, EPN, LPC), to facilitate

the interpretability of the decoding results across time. Using repeated-measures analyses of

variance (rmANOVAs) and post-hoc *t*-tests (Bonferroni corrected), we modeled the decoding

performance as a function of the *time window* (four levels) and the binary decoding *contrast* (six

levels).

To test whether the presence of stereoscopic depth cues impacts the decodability, we performed

the same decoding procedure separately with data from the mono- and stereoscopic depth

conditions. We then compared the resulting decoding performances at each time window using

two-sided, paired *t*-tests with cluster-correction. We also compared the monoscopic and the

stereoscopic depth condition in terms of the peak decoding performance (highest decoding

performance across all time points) and its latency using paired, two-sided *t*-tests. Further, we

used a rmANOVA with the factors *time window* (P1, N170, EPN, LPC) and *depth condition* (mono-

vs stereoscopic) to model the decoding scores. Finally, we used the same decoding procedure to

make the *depth condition* itself the decoding target (i.e., predicting if a sample was measured

under mono- or stereoscopic viewing conditions), as well as the *identity* of the stimulus face (three

classes; see Figure 1c)—both task-irrelevant features of the stimulus.

Source reconstruction

We applied source reconstruction to project the spatial patterns obtained from the decoding process onto the cortical surface. Specifically, we used exact low-resolution tomography analysis (eLORETA; Pascual-Marqui, 2007) to localize the sources corresponding to the extracted components. The reconstruction utilized the standard average forward model from FreeSurfer (Fischl et al., 1999) as provided by MNE-Python, restricting the solution to dipoles with fixed orientations perpendicular to the cortical surface. Using eLORETA, we constructed spatial filters for each voxel from the leadfield matrix. The sources were then computed by multiplying the demixing matrix with the spatial patterns (Haufe et al., 2014) derived from the classifiers trained in EEG channel space. For multiclass classifiers, this procedure was performed separately for each underlying binary (one-vs-rest) classifier, and the normalized source time courses were averaged (per time point) to produce a single overall source time course for the multiclass decoder. To determine the most informative source within the canonical ERP time windows, we calculated the average weight of each vertex over the respective time intervals, identified the vertex with the highest average weight, and classified its corresponding brain region using the reduced parcellation atlas (23 labels per hemisphere) provided by Glasser et al. (2016) and Mills (2016).

Eye tracking analyses

We analyzed the eye tracking data (combined gaze data for left and right eye as provided by the eye tracking SDK) in a subsample of 17 participants (due to a technical error no eye tracking data were recorded for the remaining participants). To compensate for the internal processing time of the eye tracker—specifically, the delay between recording an eye tracking sample and the moment when the corresponding sample is provided by the eye tracking SDK (Stein et al., 2021)—and to ensure temporal alignment of the eye tracking data with the EEG data, we first performed a cross-correlation between the eye tracking data and the EOG channels of the EEG data. This yielded a temporal offset between the two signals of on average 60 ms (SD = 3.80, range: 50–67 ms); this delay was corrected by subtracting it from the timestamps in the eye tracking samples. We performed a baseline-correction procedure on a trial-by-trial basis, in which we subtracted the mean gaze position during the 200 ms time window before the onset of the stimulus face from the gaze positions in the entire trial. Furthermore, we identified blinks using the algorithm based on the dynamics of the pupil dilation values suggested by Kret & Sjak-Shie (2019), which specifically looks for rapid changes in pupil size. We then linearly interpolated the gaze values during the times of identified blinks (plus a safety margin of 100 ms on each side).

We applied the same decoding approach as we used for the EEG data: we trained and evaluated

a time-resolved linear classifier with a similar architecture (L2-regularized logistic regression;

$\lambda = 1.0$; repeated randomized 5-fold cross-validation) for each participant. Here, we decoded the

target variables (e.g., facial expressions, depth conditions, face identities) from the time-resolved,

two-dimensional gaze direction. To this end, we converted the gaze vector (i.e., viewing direction)

into spherical coordinates: phi (vertical) and theta (horizontal component). In contrast to the EEG-

decoding, we did not apply downsampling nor mini-batching for the decoding from eye tracking

data because, in comparison to EEG, eye tracking data are substantially less prone to

measurement noise and single-trial data are more reliable.

In exploratory analyses, we analyzed the gaze behavior by classifying saccades and fixations on

a single trial level. Saccade detection was based on a velocity-based algorithm with noise-

dependent threshold (i.e., 5 SDs velocity threshold and minimum duration of 3 samples; Engbert

et al., 2015; Engbert & Kliegl, 2003; Engbert & Mergenthaler, 2006). For these analyses, we

excluded saccades with amplitudes smaller than 2 degrees of visual angle. This exclusion

criterion was implemented due to the limitations in precision and sampling rate of the eye tracker

within the VR headset, which make the classification and description of smaller saccades

unreliable. For fixations, we retained only those with a duration of at least 50 milliseconds. To

calculate the fixation heatmaps in Figure 4, we followed the recommendation provided by Le Meur

& Baccino (2013): On the subject-level, we calculated the average spherical coordinates for each

fixation, binned the fixations into spatial bins of a width and height of 0.1 dva, and convolved the

resulting two-dimensional histogram (across all trials of the respective condition) with a two-

dimensional gaussian kernel (*SD* = 1 dva for both dimensions and default parameters for the

method "gaussian_kernel" from the SciPy Python module). We calculated a 4x2x4 MANOVA

which modeled the average fixation position (two-dimensional, spherical coordinates) as a

function of the face's expression (neutral, angry, happy, surprised), depth condition (mono,

stereo), and time window (P1, N170, EPN, LPC). We used the same model to analyze the (two-

dimensional) saccade directions. Further, we applied Generalized Linear Models (GLM) to model

the number of saccades (Poisson, log-linear link function) and the saccade amplitude (Gaussian,

log-linear) as a function of emotional expression, time window, and depth condition.

Behavioral data

We compared participants' behavioral categorizations of each trial's facial expression with the

objective categorizations based on the FACS values to calculate confusion matrices

(Supplementary Figure S1). Due to the high level of agreement, we used the FACS categories as

ground truth for the further analyses. To test for differences in the recognition performance

between the mono- and the stereoscopic depth condition, we calculated a rmANOVA, modeling

the recognition scores (i.e., the values on the diagonal of the confusion matrices in Supplementary

Figure S1) as a function of the depth condition (two levels), the emotional expression (four levels),

and their interaction. Finally, we modeled the intensity ratings from the last part of the experiment

(based on the 9-point SAM scale) using a rmANOVA with the factors emotional expression and

depth condition.

Supplementary Material

Supplementary information is available in a separate file.

Further information

Data availability

The data that support the findings of this study are openly available in "Edmond – the Open Research Data Repository of the Max Planck Society" at https://doi.org/10.17617/3.CQ2VXX. The code for data analysis can be found at https://github.com/eioe/vr2f.

Acknowledgements

We thank Michael Gilbert for his support and guidance regarding the stimulus material, particularly for providing the original 3D face models from his validation study. We are also grateful to Jeroen de Mooij for his assistance and expertise in implementing the experiment in Unity. This research was supported by the cooperation between the Max Planck Society and the Fraunhofer Gesellschaft (grant: project NEUROHUM), by the German Federal Ministry of Education and Research (BMBF/BMFTR) under grants 13GW0206, 13GW0488, 16SV9156, and by the Deutsche Forschungsgemeinschaft (DFG) under grants 502864329 and 542559580. Relevant parts of this work were conducted at the Max Planck Dahlem Campus of Cognition (MPDCC) of the Max Planck Institute for Human Development, Berlin, Germany.

CrediT statement

Felix Klotzsche: Conceptualization, Data curation, Formal Analysis, Investigation, Methodology, Software, Visualization, Writing – original draft, Writing – review & editing;
Ammara Nasim: Conceptualization, Data curation, Investigation, Methodology, Writing – review & editing;
Simon M. Hofmann: Conceptualization, Methodology, Software, Writing – review & editing;
Arno Villringer: Funding Acquisition, Resources, Supervision;
Vadim Nikulin: Formal Analysis, Methodology, Supervision, Writing – review & editing;
Werner Sommer: Conceptualization, Formal Analysis, Methodology, Supervision, Visualization, Writing – review & editing;
Michael Gaebler: Conceptualization, Funding Acquisition, Resources, Supervision, Writing – original draft, Writing – review & editing;

Competing interests

The authors declare no competing interests.

Attributions

Figure 1:

Canon AT-1 Retro Camera (https://skfb.ly/6ZwNB) by AleixoAlonso and *EyeBall*

(https://skfb.ly/osJMS) by CrisLArt are licensed under Creative Commons Attribution

(http://creativecommons.org/licenses/by/4.0/).

References

Adam, K. C. S., Vogel, E. K., & Awh, E. (2020). Multivariate analysis reveals a generalizable

    human electrophysiological signature of working memory load. *Psychophysiology*,

    57(12). https://doi.org/10.1111/psyp.13691

Barry, S. R. (with Sacks, O. W.). (2010). *Fixing my gaze: A scientist's journey into seeing in*

    three dimensions / Susan R. Barry, foreword by Oliver Sacks. Basic Books.

Barthel, F., Morgenstern, W., Hinzer, P., Hilsmann, A., & Eisert, P. (2025). *CGS-GAN: 3D*

    Consistent Gaussian Splatting GANs for High Resolution Human Head Synthesis

    (arXiv:2505.17590). arXiv. https://doi.org/10.48550/arXiv.2505.17590

Blender Development Team. (2021). *Blender* (Version 2.93) [Computer software].

    https://www.blender.org

Bradley, M. M., & Lang, P. J. (1994). Measuring emotion: The self-assessment manikin and the

    semantic differential. *Journal of Behavior Therapy and Experimental Psychiatry*, *25*(1),

    49–59. https://doi.org/10.1016/0005-7916(94)90063-9

Brookes, J. (2019). *Unity Experiment Framework* (Version v2.3.4) [Computer software].

    https://github.com/immersivecognition/unity-experiment-framework (Original work

    published 2017)

Brookes, J., Warburton, M., Alghadier, M., Mon-Williams, M., & Mushtaq, F. (2020). Studying

    human behavior with virtual reality: The Unity Experiment Framework. *Behavior*

    Research Methods, *52*(2), 455–463. https://doi.org/10.3758/s13428-019-01242-0

Bruce, V., & Young, A. (1986). Understanding face recognition. *British Journal of Psychology*,

    77(3), 305–327. https://doi.org/10.1111/j.2044-8295.1986.tb02199.x

Brunet, N. M. (2023). Face processing and early event-related potentials: Replications and

    novel findings. *Frontiers in Human Neuroscience*, *17*, 1268972.

    https://doi.org/10.3389/fnhum.2023.1268972

Burke, D., Taubert, J., & Higman, T. (2007). Are face representations viewpoint dependent? A

stereo advantage for generalising across different views of faces. *Vision Research*,

47(16), 2164–2169. https://doi.org/10.1016/j.visres.2007.04.018

Calder, A. J., & Young, A. W. (2005). Understanding the recognition of facial identity and facial

expression. *Nature Reviews Neuroscience*, *6*(8), 641–651.

https://doi.org/10.1038/nrn1724

Calvo, M. G., Fernández-Martín, A., Gutiérrez-García, A., & Lundqvist, D. (2018). Selective eye

fixations on diagnostic face regions of dynamic emotional expressions: KDEF-dyn

database. *Scientific Reports*, *8*(1), 17039. https://doi.org/10.1038/s41598-018-35259-w

Carrasco, C. D., Bahle, B., Simmons, A. M., & Luck, S. J. (2024). Using multivariate pattern

analysis to increase effect sizes for event-related potential analyses. *Psychophysiology*,

61(7), e14570. https://doi.org/10.1111/psyp.14570

Choi, J. W., Kwon, H., Choi, J., Kaongoen, N., Hwang, C., Kim, M., Kim, B. H., & Jo, S. (2023).

Neural Applications Using Immersive Virtual Reality: A Review on EEG Studies. *IEEE*

Transactions on Neural Systems and Rehabilitation Engineering, *31*, 1645–1658.

https://doi.org/10.1109/TNSRE.2023.3254551

Chou, I. W. Y., Ban, H., & Chang, D. H. F. (2021). Modulations of depth responses in the human

brain by object context: Does biological relevance matter? *eNeuro*, *8*(4), ENEURO.0039-

21.2021. https://doi.org/10.1523/ENEURO.0039-21.2021

Cisek, P., & Green, A. M. (2024). Toward a neuroscience of natural behavior. *Current Opinion in*

Neurobiology, *86*, 102859. https://doi.org/10.1016/j.conb.2024.102859

Cumming, B. G., & Parker, A. J. (1997). Responses of primary visual cortical neurons to

binocular disparity without depth perception. *Nature*, *389*(6648), 280–283.

https://doi.org/10.1038/38487

Cutting, J. E., & Vishton, P. M. (1995). Perceiving layout and knowing distances: The

integration, relative potency, and contextual use of different information about depth. In

Perception of space and motion (pp. 69–117). Academic Press.

https://doi.org/10.1016/B978-012240530-3/50005-5

Draschkow, D. (2022). Remote virtual reality as a tool for increasing external validity. *Nature Reviews Psychology*, 1–2. https://doi.org/10.1038/s44159-022-00082-8

Duchaine, B., & Yovel, G. (2015). A Revised Neural Framework for Face Processing. *Annual Review of Vision Science*, *1*(Volume 1, 2015), 393–416. https://doi.org/10.1146/annurev-vision-082114-035518

Eimer, M. (2011). The Face-Sensitive N170 Component of the Event-Related Brain Potential. In A. J. Calder, G. Rhodes, M. H. Johnson, & J. V. Haxby (Eds.), *Oxford Handbook of Face Perception* (p. 0). Oxford University Press. https://doi.org/10.1093/oxfordhb/9780199559053.013.0017

Ekman, P., & Friesen, W. V. (1978). Facial action coding system. *Environmental Psychology & Nonverbal Behavior*. https://psycnet.apa.org/doiLanding?doi=10.1037/t27734-000.

Engbert, R., & Kliegl, R. (2003). Microsaccades uncover the orientation of covert attention. *Vision Research*, *43*(9), 1035–1045. https://doi.org/10.1016/S0042-6989(03)00084-1

Engbert, R., & Mergenthaler, K. (2006). Microsaccades are triggered by low retinal image slip. *Proceedings of the National Academy of Sciences*, *103*(18), 7192–7197. https://doi.org/10.1073/pnas.0509557103

Engbert, R., Sinn, P., Mergenthaler, K., & Trukenbrod, H. (2015). *Microsaccade Toolbox for R* (Version v0.9) [Computer software].

Feng, Y., Feng, H., Black, M. J., & Bolkart, T. (2021). Learning an animatable detailed 3D face model from in-the-wild images. *ACM Transactions on Graphics*, *40*(4), 88:1-88:13. https://doi.org/10.1145/3450626.3459936

Fischl, B., Sereno, M. I., Tootell, R. B. H., & Dale, A. M. (1999). High-resolution intersubject averaging and a coordinate system for the cortical surface. *Human Brain Mapping*, *8*(4),

272–284. https://doi.org/10.1002/(SICI)1097-0193(1999)8:4<272::AID-HBM10>3.0.CO;2-4

Freiwald, W., Duchaine, B., & Yovel, G. (2016). Face Processing Systems: From Neurons to Real-World Social Perception. *Annual Review of Neuroscience*, *39*(1), 325–346. https://doi.org/10.1146/annurev-neuro-070815-013934

Gao, C., Conte, S., Richards, J. E., Xie, W., & Hanayik, T. (2019). The neural sources of N170: Understanding timing of activation in face-selective areas. *Psychophysiology*, *56*(6), e13336. https://doi.org/10.1111/psyp.13336

Gilbert, M., Demarchi, S., & Urdapilleta, I. (2021). FACSHuman, a software program for creating experimental material by modeling 3D facial expressions. *Behavior Research Methods*, *53*(5), 2252–2272. https://doi.org/10.3758/s13428-021-01559-9

Glasser, M. F., Coalson, T. S., Robinson, E. C., Hacker, C. D., Harwell, J., Yacoub, E., Ugurbil, K., Andersson, J., Beckmann, C. F., Jenkinson, M., Smith, S. M., & Van Essen, D. C. (2016). A multi-modal parcellation of human cerebral cortex. *Nature*, *536*(7615), 171–178. https://doi.org/10.1038/nature18933

Gramfort, A., Luessi, M., Larson, E., Engemann, D. A., Strohmeier, D., Brodbeck, C., Goj, R., Jas, M., Brooks, T., Parkkonen, L., & Hämäläinen, M. S. (2013). MEG and EEG Data Analysis with MNE-Python. *Frontiers in Neuroscience*, *7*(267), 1–13. https://doi.org/10.3389/fnins.2013.00267

Greene, C. M., Flannery, O., & Soto, D. (2014). Distinct parietal sites mediate the influences of mood, arousal, and their interaction on human recognition memory. *Cognitive, Affective, & Behavioral Neuroscience*, *14*(4), 1327–1339. https://doi.org/10.3758/s13415-014-0266-y

Grill-Spector, K., Weiner, K. S., Kay, K., & Gomez, J. (2017). The Functional Neuroanatomy of Human Face Perception. *Annual Review of Vision Science*, *3*, 167–196. https://doi.org/10.1146/annurev-vision-102016-061214

Grootswagers, T., Wardle, S. G., & Carlson, T. A. (2017). Decoding Dynamic Brain Patterns

from Evoked Responses: A Tutorial on Multivariate Pattern Analysis Applied to Time

Series Neuroimaging Data. *Journal of Cognitive Neuroscience*, *29*(4), 677–697.

https://doi.org/10.1162/jocn_a_01068

Hakala, J., Kätsyri, J., & Häkkinen, J. (2015). Stereoscopy Amplifies Emotions Elicited by Facial

Expressions. *I-Perception*, *6*(6), 2041669515615071.

https://doi.org/10.1177/2041669515615071

Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D.,

Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk, M.

H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., … Oliphant, T. E.

(2020). Array programming with NumPy. *Nature*, *585*(7825), 357–362.

https://doi.org/10.1038/s41586-020-2649-2

Haufe, S., Meinecke, F., Görgen, K., Dähne, S., Haynes, J.-D., Blankertz, B., & Bießmann, F.

(2014). On the interpretation of weight vectors of linear models in multivariate

neuroimaging. *NeuroImage*, *87*, 96–110.

https://doi.org/10.1016/j.neuroimage.2013.10.067

Haxby, J. V., Hoffman, E. A., & Gobbini, M. I. (2000). The distributed human neural system for

face perception. *Trends in Cognitive Sciences*, *4*(6), 223–233.

https://doi.org/10.1016/S1364-6613(00)01482-0

Hebart, M. N., & Baker, C. I. (2018). Deconstructing multivariate decoding for the study of brain

function. *NeuroImage*, *180*, 4–18. https://doi.org/10.1016/j.neuroimage.2017.08.005

Herrando, C., & Constantinides, E. (2021). Emotional Contagion: A Brief Overview and Future

Directions. *Frontiers in Psychology*, *12*. https://doi.org/10.3389/fpsyg.2021.712606

Hofmann, S. M., Klotzsche, F., Mariola, A., Nikulin, V., Villringer, A., & Gaebler, M. (2021).

Decoding subjective emotional arousal from EEG during an immersive virtual reality

experience. *eLife*, *10*, e64812. https://doi.org/10.7554/eLife.64812

Jack, R. E., & Schyns, P. G. (2015). The Human Face as a Dynamic Tool for Social

Communication. *Current Biology: CB*, *25*(14), R621-634.

https://doi.org/10.1016/j.cub.2015.05.052

Jas, M., Engemann, D. A., Bekhti, Y., Raimondo, F., & Gramfort, A. (2017). Autoreject:

Automated artifact rejection for MEG and EEG data. *NeuroImage*, *159*, 417–429.

https://doi.org/10.1016/j.neuroimage.2017.06.030

Kamitani, Y., & Tong, F. (2005). Decoding the visual and subjective contents of the human

brain. *Nature Neuroscience*, *8*(5), 679–685. https://doi.org/10.1038/nn1444

Kanwisher, N., & Yovel, G. (2006). The fusiform face area: A cortical region specialized for the

perception of faces. *Philosophical Transactions of the Royal Society B: Biological*

Sciences, *361*(1476), 2109–2128. https://doi.org/10.1098/rstb.2006.1934

Klotzsche, F., de Mooij, J., Ohl, S., & Gaebler, M. (2025, May). *EDIA: An open-source toolbox*

for virtual reality-based eye tracking research using Unity. Annual Meeting of the Vision

Science Society, St. Pete's Beach, Florida, USA.

Klotzsche, F., Gaebler, M., Villringer, A., Sommer, W., Nikulin, V., & Ohl, S. (2023). *Visual short-*

term memory related EEG components in a virtual reality setup (p. 2023.01.23.525140).

bioRxiv. https://doi.org/10.1101/2023.01.23.525140

Kret, M. E., & Sjak-Shie, E. E. (2019). Preprocessing pupil size data: Guidelines and code.

Behavior Research Methods, *51*(3), 1336–1342. https://doi.org/10.3758/s13428-018-

1075-y

Kriegeskorte, N., & Douglas, P. K. (2019). Interpreting encoding and decoding models. *Current*

Opinion in Neurobiology, *55*, 167–179. https://doi.org/10.1016/j.conb.2019.04.002

Le Meur, O., & Baccino, T. (2013). Methods for comparing scanpaths and saliency maps:

Strengths and weaknesses. *Behavior Research Methods*, *45*(1), 251–266.

https://doi.org/10.3758/s13428-012-0226-9

Leiner, D. J. (2019). *SoSci Survey* [Computer software]. https://www.soscisurvey.de

Lettieri, G., Handjaras, G., Ricciardi, E., Leo, A., Papale, P., Betta, M., Pietrini, P., & Cecchetti,

L. (2019). Emotionotopy in the human right temporo-parietal cortex. *Nature*

Communications, *10*(1), 5568. https://doi.org/10.1038/s41467-019-13599-z

Liu, C. H., & Ward, J. (2006). The use of 3D information in face recognition. *Vision Research*,

46(6), 768–773. https://doi.org/10.1016/j.visres.2005.10.008

Liu, C. H., Ward, J., & Young, A. W. (2006). Transfer between two- and three-dimensional

representations of faces. *Visual Cognition*, *13*(1), 51–64.

https://doi.org/10.1080/13506280500143391

Liu, H., Laeng, B., & Czajkowski, N. O. (2020). Does stereopsis improve face identification? A

study using a virtual reality display with integrated eye-tracking and pupillometry. *Acta*

Psychologica, *210*, 103142. https://doi.org/10.1016/j.actpsy.2020.103142

Lützow Holm, E., Fernández Slezak, D., & Tagliazucchi, E. (2024). Contribution of low-level

image statistics to EEG decoding of semantic content in multivariate and univariate

models with feature optimization. *NeuroImage*, *293*, 120626.

https://doi.org/10.1016/j.neuroimage.2024.120626

Ma, D. S., Correll, J., & Wittenbrink, B. (2015). The Chicago face database: A free stimulus set

of faces and norming data. *Behavior Research Methods*, *47*(4), 1122–1135.

https://doi.org/10.3758/s13428-014-0532-5

Menz, M. D., & Freeman, R. D. (2003). Stereoscopic depth processing in the visual cortex: A

coarse-to-fine mechanism. *Nature Neuroscience*, *6*(1), 59–65.

https://doi.org/10.1038/nn986

Mills, K. (2016). *HCP-MMP1.0 projected on fsaverage* (p. 4139170 Bytes) [Dataset]. figshare.

https://doi.org/10.6084/M9.FIGSHARE.3498446.V2

Mostert, P., Albers, A. M., Brinkman, L., Todorova, L., Kok, P., & de Lange, F. P. (2018). Eye

Movement-Related Confounds in Neural Decoding of Visual Working Memory

Representations. *eNeuro*, *5*(4), ENEURO.0401-17.2018.

https://doi.org/10.1523/ENEURO.0401-17.2018

Nolte, D., Schmidt, V., Grasso-Cladera, A., & König, P. (2024). *Investigating saccade-onset*

locked EEG signatures of face perception during free-viewing in a naturalistic virtual

environment. https://doi.org/10.1101/2024.12.12.628113

Nolte, D., Vidal De Palol, M., Keshava, A., Madrid-Carvajal, J., Gert, A. L., von Butler, E.-M.,

Kömürlüoğlu, P., & König, P. (2025). Combining EEG and eye-tracking in virtual reality:

Obtaining fixation-onset event-related potentials and event-related spectral

perturbations. *Attention, Perception & Psychophysics*, *87*(1), 207–227.

https://doi.org/10.3758/s13414-024-02917-3

Parker, A. J. (2007). Binocular depth perception and the cerebral cortex. *Nature Reviews*

Neuroscience, *8*(5), 379–391. https://doi.org/10.1038/nrn2131

Pascual-Marqui, R. D. (2007). Discrete, 3D distributed, linear imaging methods of electric

neuronal activity. Part 1: Exact, zero error localization. *arXiv:0710.3341 [Math-Ph,*

Physics:Physics, q-Bio]. http://arxiv.org/abs/0710.3341

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M.,

Prettenhofer, P., Weiss, R., Dubourg, V., & others. (2011). Scikit-learn: Machine learning

in Python. *Journal of Machine Learning Research*, *12*(Oct), 2825–2830.

Peelen, M. V., & Downing, P. E. (2023). Testing cognitive theories with multivariate pattern

analysis of neuroimaging data. *Nature Human Behaviour*, *7*(9), 1430–1441.

https://doi.org/10.1038/s41562-023-01680-z

Ritchie, J. B., Kaplan, D. M., & Klein, C. (2019). Decoding the Brain: Neural Representation and

the Limits of Multivariate Pattern Analysis in Cognitive Neuroscience. *The British Journal*

for the Philosophy of Science, *70*(2), 581–607. https://doi.org/10.1093/bjps/axx023

Rossion, B. (2014). Understanding face perception by means of human electrophysiology.

Trends in Cognitive Sciences, *18*(6), 310–318. https://doi.org/10.1016/j.tics.2014.02.013

Rossion, B., & Caharel, S. (2011). ERP evidence for the speed of face categorization in the

human brain: Disentangling the contribution of low-level visual cues from face

perception. *Vision Research*, *51*(12), 1297–1311.

https://doi.org/10.1016/j.visres.2011.04.003

Rossion, B., & Jacques, C. (2012). The N170: Understanding the time course of face perception

in the human brain. In *The Oxford handbook of event-related potential components* (pp.

115–141). Oxford University Press.

Sagehorn, M., Johnsdorf, M., Kisker, J., Gruber, T., & Schöne, B. (2024). Electrophysiological

correlates of face and object perception: A comparative analysis of 2D laboratory and

virtual reality conditions. *Psychophysiology*, *61*(5), e14519.

https://doi.org/10.1111/psyp.14519

Sagehorn, M., Johnsdorf, M., Kisker, J., Sylvester, S., Gruber, T., & Schöne, B. (2023). Real-life

relevant face perception is not captured by the N170 but reflected in later potentials: A

comparison of 2D and virtual reality stimuli. *Frontiers in Psychology*, *14*.

https://doi.org/10.3389/fpsyg.2023.1050892

Sagehorn, M., Kisker, J., Johnsdorf, M., Gruber, T., & Schöne, B. (2024). A comparative

analysis of face and object perception in 2D laboratory and virtual reality settings:

Insights from induced oscillatory responses. *Experimental Brain Research*.

https://doi.org/10.1007/s00221-024-06935-3

Savran, A., Sankur, B., & Taha Bilge, M. (2012). Comparative evaluation of 3D vs. 2D modality

for automatic detection of facial action units. *Pattern Recognition*, *45*(2), 767–782.

https://doi.org/10.1016/j.patcog.2011.07.022

Schacht, A., & Sommer, W. (2009). Emotions in word and face processing: Early and late

cortical responses. *Brain and Cognition*, *69*(3), 538–550.

https://doi.org/10.1016/j.bandc.2008.11.005

Schindler, S., & Bublatzky, F. (2020). Attention and emotion: An integrative review of emotional

face processing as a function of attention. *Cortex*, *130*, 362–386.

https://doi.org/10.1016/j.cortex.2020.06.010

Schubring, D., Kraus, M., Stolz, C., Weiler, N., Keim, D. A., & Schupp, H. (2020). Virtual Reality

Potentiates Emotion and Task Effects of Alpha/Beta Brain Oscillations. *Brain Sciences*,

10(8), Article 8. https://doi.org/10.3390/brainsci10080537

Schupp, H. T., Flaisch, T., Stockburger, J., & Junghöfer, M. (2006). Emotion and attention:

Event-related brain potential studies. In S. Anders, G. Ende, M. Junghofer, J. Kissler, &

D. Wildgruber (Eds.), *Progress in Brain Research* (Vol. 156, pp. 31–51). Elsevier.

https://doi.org/10.1016/S0079-6123(06)56002-9

Schurgin, M. W., Nelson, J., Iida, S., Ohira, H., Chiao, J. Y., & Franconeri, S. L. (2014). Eye

movements during emotion recognition in faces. *Journal of Vision*, *14*(13), 14.

https://doi.org/10.1167/14.13.14

Seabold, S., & Perktold, J. (2010). statsmodels: Econometric and statistical modeling with

python. *9th Python in Science Conference*.

Smith, F. W., & Smith, M. L. (2019). Decoding the dynamic representation of facial expressions

of emotion in explicit and incidental tasks. *NeuroImage*, *195*, 261–271.

https://doi.org/10.1016/j.neuroimage.2019.03.065

Stein, N., Niehorster, D. C., Watson, T., Steinicke, F., Rifai, K., Wahl, S., & Lappe, M. (2021). A

Comparison of Eye Tracking Latencies Among Several Commercial Head-Mounted

Displays. *I-Perception*, *12*(1), 2041669520983338.

https://doi.org/10.1177/2041669520983338

Steyvers, M. (1999). Morphing techniques for manipulating face images. *Behavior Research*

Methods, Instruments, & Computers, *31*(2), 359–369.

https://doi.org/10.3758/BF03207733

Tarr, M. J., & Warren, W. H. (2002). Virtual reality in behavioral neuroscience and beyond.

Nature Neuroscience, *5*(11), 1089–1092. https://doi.org/10.1038/nn948

Tauscher, J.-P., Schottky, F. W., Grogorick, S., Bittner, P. M., Mustafa, M., & Magnor, M.

(2019). Immersive EEG: Evaluating Electroencephalography in Virtual Reality. *2019*

IEEE Conference on Virtual Reality and 3D User Interfaces (VR), 1794–1800.

https://doi.org/10.1109/VR.2019.8797858

Thurley, K. (2022). Naturalistic neuroscience and virtual reality. *Frontiers in Systems*

Neuroscience, *16*. https://doi.org/10.3389/fnsys.2022.896251

Vaidya, A. R., Jin, C., & Fellows, L. K. (2014). Eye spy: The predictive value of fixation patterns

in detecting subtle and extreme emotions from faces. *Cognition*, *133*(2), 443–456.

https://doi.org/10.1016/j.cognition.2014.07.004

Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D.,

Burovski, E., Peterson, P., Weckesser, W., Bright, J., Van Der Walt, S. J., Brett, M.,

Wilson, J., Millman, K. J., Mayorov, N., Nelson, A. R. J., Jones, E., Kern, R., Larson, E.,

… Vázquez-Baeza, Y. (2020). SciPy 1.0: Fundamental algorithms for scientific

computing in Python. *Nature Methods*, *17*(3), 261–272. https://doi.org/10.1038/s41592-

019-0686-2

Vishwanath, D. (2014). Toward a new theory of stereopsis. *Psychological Review*, *121*(2), 151–

178. https://doi.org/10.1037/a0035233

Vishwanath, D., & Hibbard, P. B. (2013). Seeing in 3-D With Just One Eye. *Psychological*

Science. https://doi.org/10.1177/0956797613477867

Wade-Bohleber, L. M., Thoma, R., & Gerber, A. J. (2020). Neural correlates of subjective

arousal and valence in health and panic disorder. *Psychiatry Research: Neuroimaging*,

305, 111186. https://doi.org/10.1016/j.pscychresns.2020.111186

Wang, L., Chen, W., & Li, H. (2017). Use of 3D faces facilitates facial expression recognition in

children. *Scientific Reports*, *7*(1), Article 1. https://doi.org/10.1038/srep45464

Weber, D., Hertweck, S., Alwanni, H., Fiederer, L. D. J., Wang, X., Unruh, F., Fischbach, M.,

Latoschik, M. E., & Ball, T. (2021). A Structured Approach to Test the Signal Quality of

Electroencephalography Measurements During Use of Head-Mounted Displays for

Virtual Reality Applications. *Frontiers in Neuroscience*, *15*, 733673.

https://doi.org/10.3389/fnins.2021.733673

Welchman, A. E. (2016). The Human Brain in Depth: How We See in 3D. *Annual Review of*

Vision Science, *2*(Volume 2, 2016), 345–376. https://doi.org/10.1146/annurev-vision-

111815-114605

Willis, J., & Todorov, A. (2006). First Impressions: Making Up Your Mind After a 100-Ms

Exposure to a Face. *Psychological Science*, *17*(7), 592–598.

https://doi.org/10.1111/j.1467-9280.2006.01750.x

Wilson, H., Chen ,Xi, Golbabaee ,Mohammad, Proulx ,Michael J., & and O'Neill, E. (2024).

Feasibility of decoding visual information from EEG. *Brain-Computer Interfaces*, *11*(1–2),

33–60. https://doi.org/10.1080/2326263X.2023.2287719

1269