EEG-decodability of facial expressions and their stereoscopic depth cues in immersive virtual reality

Felix Klotzsche[1,2], Ammara Nasim[1,3], Simon M. Hofmann[1,4], Arno Villringer[1], Vadim Nikulin[1], Werner Sommer[2,5], Michael Gaebler[1]

[1] Max Planck Institute for Human Cognitive and Brain Sciences, Department of Neurology, Leipzig, Germany
[2] Humboldt-Universität zu Berlin, Department of Psychology, Germany
[3] Carl von Ossietzky Universität Oldenburg, Germany
[4] Fraunhofer Institute Heinrich Hertz, Department of Artificial Intelligence, Berlin, Germany
[5] Zhejiang Normal University, Department of Psychology, Jinhua, China

Corresponding author

Felix Klotzsche
Stephanstr. 1A
04103 Leipzig
Germany
klotzsche@cbs.mpg.de

Key words

Face perception, depth perception, immersive virtual reality

Abstract

Face perception typically occurs in three-dimensional space, where stereoscopic depth cues enrich the perception of facial features. Yet, most neurophysiological research on face processing relies on two-dimensional displays, potentially overlooking the role of stereoscopic depth information. Here, we combine immersive virtual reality (VR), electroencephalography (EEG), and eye tracking to examine the neural representation of faces under controlled manipulations of stereoscopic depth. Thirty-four participants viewed computer-generated faces with neutral, happy, angry, and surprised expressions in frontal view under monoscopic and stereoscopic viewing conditions. Using time-resolved multivariate decoding, we show that EEG signals in immersive VR conditions can reliably differentiate facial expressions. Stereoscopic depth cues elicited a distinct and decodable neural signature, confirming the sensitivity of our approach to depth-related processing. Yet, expression decoding remained robust across depth conditions, indicating that under controlled frontal viewing, the neural encoding of facial expressions is invariant to binocular depth cues. Eye tracking showed that expression-related gaze patterns contained comparable information but did not account for neural representations, while depth information was absent in gaze patterns—consistent with dissociable representational processes. Our findings demonstrate the feasibility of EEG-based neural decoding in fully immersive VR as a tool for investigating face perception in naturalistic settings and provide new evidence for the stability of expression representations across depth variations in three-dimensional viewing conditions.

Introduction

Faces are among the most relevant visual input for humans. They play a crucial role in social communication, enabling us to recognize and distinguish individuals, as well as to infer detailed semantic information about them, such as their emotional states (Bruce & Young, 1986; Jack & Schyns, 2015). Humans are able to detect subtle differences between faces and facial expressions, although they are composed of relatively few key features (e.g., one mouth, one nose, two eyes) and share a similar configuration. Moreover, faces and the emotions they convey are processed and evaluated more rapidly than other objects of comparable visual complexity (Willis & Todorov, 2006). The sophisticated processing of facial stimuli is supported by a hierarchical cortical network, ranging from retinotopic areas in the early visual cortex, which process single features, to face-specific visual areas like the fusiform face area (FFA) that encode view-invariant, abstract representations of faces (Calder & Young, 2005; Duchaine & Yovel, 2015; Freiwald et al., 2016; Haxby et al., 2000).

In the real world, humans constantly process faces in complex, three-dimensional (3D) settings. However, laboratory studies of face perception usually simplify these experiences, relying on two-dimensional (2D) stimuli presented on flat screens. Such conditions omit key features of natural vision—for example, binocular depth information. Binocular disparity is a visual feature which is automatically and (seemingly) effortlessly extracted from the retinal inputs and integrated into a percept with stereoscopic depth: Each eye captures a slightly different image, which the cerebral cortex integrates—together with further visual cues such as relative size, blur, shading, perspective, texture gradients, or motion as well as with sensory signals from other modalities—to gain depth-information about the shape of an object or the configuration of a scene (Parker, 2007; Welchman, 2016). During this fusion into a stereoscopic representation, coarse percepts change and refine over time (Menz & Freeman, 2003). Among the various available depth cues, binocular information plays a special role for the subjective experience of stereoscopic depth (Barry, 2010; Vishwanath, 2014). However, binocular disparity information is neither necessary (Vishwanath & Hibbard, 2013) nor sufficient (Cumming & Parker, 1997) for a subjective impression of stereoscopic depth. The precise contribution of binocular disparity information for the brain's processing of complex stimuli like faces—and, in particular, how it interacts with the representation of other visual features of the same object—is still unclear.

As humans often encounter faces at close range—where binocular disparity provides important
cues (Cutting & Vishton, 1995)—depth information may play a key role in face processing.
Indeed, stereoscopic depth modulates the recognition and representation of faces and facial
expressions: It improves participants' ability to recognize the same person from different
viewpoint angles or distances (Burke et al., 2007; C. H. Liu & Ward, 2006; H. Liu et al., 2020).
C. H. Liu et al. (2006) observed impaired performance when recognition conditions differed from
encoding conditions in the availability of spatial depth cues (stereoscopic vs monoscopic),
suggesting that neural encoding depends on whether faces are processed with or without
stereoscopic depth information. Hakala et al. (2015) demonstrated that stereoscopically
presented facial expressions evoke stronger emotional responses than their monoscopic
counterparts, with natural depth cues amplifying negative reactions to angry faces. Children (3–
6 years old) are faster in recognizing emotional facial expressions in stereoscopic as compared
to monoscopic conditions (Wang et al., 2017). Collectively, these findings suggest that
stereoscopic depth cues can shape natural face processing, highlighting the importance of
binocular information in how humans perceive and respond to faces and their expressions.
94
Here, we used electroencephalography (EEG) in combination with immersive virtual reality (VR)
and eye tracking to investigate how the human brain processes faces and facial expressions in
the presence of stereoscopic depth cues. Due to its high temporal resolution, EEG is a powerful
tool for studying the temporal dynamics of face perception (for reviews see Brunet, 2023;
Rossion, 2014). Previous EEG research has identified several characteristic components of the
event-related potential (ERP), each emerging within a specific time window and reflecting a
distinct processing stage of cortical face processing: The earliest component associated with
face processing, is the P1 component (80–120 ms) which has been linked to low-level visual
analysis of faces (Rossion & Caharel, 2011). It is followed by the N170 (130–200 ms),
generated in the fusiform gyrus (Gao et al., 2019), which encodes structural face recognition
and differentiates facial expressions and identities (Rossion & Jacques, 2012). Around 250–300
ms after stimulus onset, the Early Posterior Negativity (EPN) indexes reflexive attentional
orienting toward emotional contents and its selection for further processing (Schindler &
Bublatzky, 2020). Finally, the Late Positive Complex (LPC; 400–600 ms) reflects higher-order
cognitive evaluation of faces and other stimuli of motivational relevance (Schacht & Sommer,
2009; Schupp et al., 2006).
111

These well-established ERP components provide informative temporal markers of the
sequential stages of face processing in the human brain. However, because they are typically
derived by averaging over predefined electrode clusters, they may overlook more subtle,
spatially distributed patterns of neural activity. Multivariate decoding—used to probe whether
specific stimulus information is present in high-dimensional neurophysiological signals (e.g.,
Kamitani & Tong, 2005; for a recent review, see Peelen & Downing, 2023)—extends this
approach by exploiting the full spatiotemporal structure of the EEG data and optimally weighting
channels on the level of the individual participant (Carrasco et al., 2024; Grootswagers et al.,
2017). By doing so, it can offer greater sensitivity, detecting stimulus-specific information
embedded in distributed activity patterns—information that might not be apparent in classical
ERP analyses.

In the following, we refer to such decodable information as *representation.* While this usage is
controversial (see Fallon et al., 2023, for an overview), it aligns with how the term is commonly
used by many neuroscientists—where *representation* is often approximated with *decodability*
and reflects mutual information between a pattern of brain activity and an experimental variable
of interest (Hebart & Baker, 2018).[1] Neuroscientists use decodability as a proxy for determining
where and *when* information about a feature is available in the brain (Grootswagers et al.,
2017). EEG-based decoding offers high temporal resolution, enabling researchers to track the
sequential stages at which such information emerges. Quantifying the contribution of individual
EEG channels to decoding performance permits a coarse spatial interpretation of the underlying
signals. Subsequent source reconstruction can map these patterns to their cortical generators,
thereby identifying the brain regions most relevant for the representation of the decoded feature.

In the present study, we applied this approach to investigate facial expression representations
while selectively manipulating the presence of stereoscopic depth cues. To achieve this, we
used immersive VR with head mounted displays (HMDs) to deliver binocular stimulation.
Immersive VR is increasingly adopted by cognitive and perceptual scientists—not only for its
ability to present stereoscopic depth (Choi et al., 2023; Draschkow, 2022; Tarr & Warren, 2002;
Thurley, 2022) but also because the computer-generated stimulation of the (almost) entire

---

[1] Successfully decoding a stimulus feature suggests that the decodable information is present in the recorded data and—given some necessary assumptions about their origin—also available in the identified physiological sources (e.g., brain regions at a given moment in time). This does not imply that the brain (e.g., other brain regions) actually makes use of this information—which would be a necessary requirement for a *representation* in a more strict interpretation (Kriegeskorte & Douglas, 2019; Ritchie et al., 2019).

visual field enables high levels of experimental control and facilitates various opportunities for
stimulus modification. Building on these developments, cognitive neuroscientists have begun
combining immersive VR with EEG to investigate neural processing of face stimuli under 3D
viewing conditions (Nolte et al., 2024; Sagehorn et al., 2023; Sagehorn, Johnsdorf, et al., 2024;
Sagehorn, Kisker, et al., 2024; Schubring et al., 2020).

However, combining HMDs with EEG recordings presents several challenges. Placing the HMD
over an EEG cap introduces additional sources of noise, potentially obscuring signals of interest
(Tauscher et al., 2019; Weber et al., 2021). Larger stimulus eccentricities due to the wider field
of view compared to conventional computer screens can affect visually evoked ERP
components (Klotzsche et al., 2023). In addition, while conventional laboratory studies often
restrict eye movements to maintain stable retinotopic stimulus presentation, VR paradigms
typically permit free exploration of the environment, which leads to eye movement-related
artifacts and confounds in the EEG data and may require different analytical approaches (Nolte
et al., 2024, 2025). Finally, little is known about how the mere addition of binocular depth alters
the neural processing of relevant stimuli. Overall, it remains unclear to what extent findings from
conventional 2D screen-setups generalize to 3D settings that include stereoscopic depth
information.

The present study had two main objectives. First, we addressed a methodological challenge:
whether time-resolved EEG decoding can recover facial expression information in an immersive
VR setup, where signal quality and noise sources differ from conventional laboratory settings.
Second, we examined whether the neural representation of—facial expressions is modulated
with the presence of stereoscopic depth cues—examining both whether depth information alters
expression-related activation patterns and whether stereoscopic depth itself is a decodable
feature in the EEG. To contextualize these findings, we performed complementary source
reconstruction and eye-tracking analyses to characterize neural and eye movement-related
origins of both facial expression and stereoscopic depth cue representations.

Figure 1: Experimental paradigm and decoding analysis. **(a)** In each trial of the emotion recognition task,

participants fixated centrally before a face stimulus was presented for 1,000 ms. Subsequently, they

selected the recognized emotional expression using the VR controller. **(b)** Face stimuli were presented

either with (right) or without (left) stereoscopic depth information. For the stereoscopic condition, a 3D

model of the face was rendered using two slightly offset virtual cameras (a "binocular VR camera"),

providing binocular depth cues. For the monoscopic condition, the same 3D model was first rendered

from a single virtual camera to produce a flat 2D texture, eliminating stereoscopic disparity. This texture

was then presented to both eyes via the binocular VR camera, removing binocular depth cues while

maintaining all other visual properties. **(c)** Overview of all stimulus combinations: three different face

identities (rows) expressing four different emotional facial expressions (columns: happy, angry, surprised,

neutral). Face identity was irrelevant for the emotion recognition task. Face models were originally

created and evaluated by Gilbert et al. (2021). **(d)** Schematic of the decoding approach: A multivariate

linear classifier (logistic regression) was trained on successive time windows of EEG data, treating each

channel as a feature. The emotional expression shown in the respective trial served as the classification

label. Using a 5-fold cross-validation, the classifier was tested repeatedly on 80% of the trials and its

predictions were validated on the remaining 20%. This procedure yielded decoding performance scores

per time window, reflecting the amount of available stimulus information in the EEG data at the

corresponding time in the epoch.

Figure 2: Time-resolved classification performance for different decoding targets and conditions. **(a)** Classification performance (mean ± 1 SEM) of the decoder distinguishing between the four facial expressions, trained separately for the mono- and stereoscopic viewing conditions, as well as on data pooled across both depth conditions. Horizontal lines at the bottom indicate clusters where decoding was significantly above chance. Shaded rectangles in the background mark relevant ERP time windows associated with face processing. **(b)** Selection of three (out of six) binary contrasts which underlie the

multiclass classification in (a). *Angry vs neutral*: Highest decoding performance. *Happy vs surprised*:
classification performance lacks an early peak and only rises later in the trial. *Angry vs surprised*: Lowest
(but still significant) decoding performance. **(c)** Average performance per time window, depth condition
(*top*; colors as in (a)), and binary contrast (*bottom*; *: selection and colors as in (b)). Thick bars: mean ± 1
SEM. **(d)** Time resolved classification performance (mean ± 1 SEM) for the task-irrelevant decoding
targets: identity of the stimulus face (*top*) and presence vs absence of stereoscopic depth information
(*bottom*). ROC-AUC: area under the receiver operating characteristic.
203

Results

EEG Decoding

Decodability of facial expressions

Information about the observed facial expression was decodable from the EEG data, indicated by a decoding performance significantly above chance-level (Figure 2). For multi-class decoding (distinguishing between the four facial expressions: neutral, angry, happy, and surprised), we observed a large interval with above-chance decoding performance extending from 94 ms after stimulus onset until the onset of the response panel (1,000 ms after stimulus onset). The highest decoding performance (ROC-AUC; average of individual maxima: M = 0.61, SD = 0.03, 95% CI [0.60, 0.62]) was observed for most participants at a median (Mdn) delay of 414 ms (SD = 315.81, 95% CI [306.25, 521.75]).

Figure 2, Supplementary Figure S3, and Supplementary Table ST1 show the decoding results for the binary decoders which were trained to distinguish between pairs of emotions. For each contrast, we found at least one significant cluster, demonstrating above chance-level decoding also for all binary classifiers. Descriptively, different emotion pairs exhibited distinct pairwise-decoding profiles, varying in average decoding performances and temporal dynamics (e.g., the contrast between angry and neutral emotions showed higher and earlier average decodability compared to the contrast between angry and surprised). To investigate the decoding performance over time, we compared the ROC-AUC scores averaged within four time windows corresponding to the P1, N170, EPN, and LPC components commonly used in EEG research on face processing. We found a significant main effect of the time window on the ROC-AUC ($F_{(3,96)} = 22.01$, $p < .001$) which was driven by a significantly lower decoding performance in

the P1-window compared to all other time windows. The remaining time windows did not differ

significantly for the multiclass decoding approach. For the binary classifiers (contrasting pairs of

facial expressions), we observed again a significant main effect of time window ($F_{(3,96)}$ =

21.13, $p < .001$), a significant main effect of contrast ($F_{(5,160)}$ = 9.43, $p < .001$), as well as a

significant interaction ($F_{(15,480)}$ = 9.02, $p < .001$). The P1-window yielded the lowest decoding

performance across all binary decoders. Only for one out of the six contrasts ("surprised-vs-

happy"), the decoding performance was significantly above chance during this time window. All

other time windows did not differ in their average ROC-AUC (across all binary contrasts) and

were not significantly above chance level in the P1 window. In the remaining time windows, all

contrasts, except for "angry-vs-surprised" in the LPC window, performed significantly above

chance level. The decoders distinguishing "angry-vs-neutral" and "angry-vs-happy" showed

significantly higher decoding performance than the other binary classifiers. This difference was

most pronounced in the N170 and the LPC time windows. Details are depicted in Figure 2 and

Supplementary Figure S4.

The role of stereoscopic depth cues

We did not observe different classification performances (decoding the observed facial

expression) for the monoscopic and the stereoscopic viewing conditions. The multiclass

decoders validated on trials with and without stereoscopic depth information differed neither in

terms of the maximal decoding performance (mono: M = 0.61, SD = 0.02, 95% CI [0.60, 0.62];

stereo: M = 0.61, SD = 0.03, 95% CI [0.60, 0.62]; $t_{(32)}$ = -0.49, $p = 0.627$) nor for the latency of

the peak decoding performance (mono: Mdn = 384.00 ms, SD = 287.71, 95% CI [285.83,

482.17]; stereo: Mdn = 524.00 ms, SD = 386.06), 95% CI [392.28, 655.72]; $t_{(32)}$ = -1.04, $p =$

0.305). This was confirmed by a cluster-corrected comparison of the decoding performance at

each time-point which did not indicate a significant difference between the two depth conditions.

In a four-by-two rmANOVA which modeled the average decoding performance as a function of

the time window (four levels: P1, N170, EPN, LPC) and the depth condition (two levels: mono-

and stereoscopic), only time window was a significant predictor ($F_{(3,96)}$ = 17.82, $p < .001$), but

neither depth condition ($F_{(1,32)}$ = 1.55, $p = 0.222$) nor its interaction with time window ($F_{(3,96)}$

= 1.00, $p = 0.395$). Also for all the binary classifiers (distinguishing pairs of emotions), we

observed no significant differences between the two depth conditions, neither for peak decoding

performance nor for its latency (Table ST1).

To scrutinize further whether any information about the presence or absence of stereoscopic

depth cues was present in the EEG data, we made the depth condition itself the decoding target

of a binary classifier (i.e., decoding whether the data came from a trial in the mono- or the

stereoscopic condition). Figure 2d shows the time-resolved decoding performance of this

decoder. Above-chance decodability was indicated by a long interval of significant decoding

performance starting 114 ms after stimulus onset (end: 714 ms) and multiple shorter intervals at

later time points in the epoch. On average, a peak decoding score of $M = 0.65$ ($SD = 0.07$, 95%

CI [0.62, 0.67]) was observed for most participants at $Mdn = 184$ ms after stimulus onset.

Descriptively, the decoding performance peaked early (peak decoding time: $Mdn = 184$ ms, SD

= 204.17, 95% CI [114.34, 253.66]) and continuously decreased toward the end of the epoch.

We observed a similar temporal profile of the decoding performance when classifying the

identity of the stimulus face (rows in Figure 1c)—another task-irrelevant stimulus feature—from

the EEG data (peak decoding score $M = 0.60$, $SD = 0.03$, 95% CI [0.59, 0.61]; peak decoding

time: $Mdn = 134$ ms, $SD = 244.62$, 95% CI [50.54, 217.46]; Figure 2d). Classifiers trained only

on trials from one of the viewing conditions (with or without stereoscopic depth information)

performed equally well when tested on trials from the same or the other ("cross-decoding")

depth condition (see Supplementary Figure S5).

Source reconstruction

Figure 3 depicts the spatial patterns (Haufe et al., 2014) underlying the decoders and a

reconstruction of the associated cortical sources. Classification of task-relevant features (facial

expression) as well as task-irrelevant features (identity, depth condition) primarily involved

occipital, parietal, and temporal sources. Early after stimulus onset (P1, N170, EPN windows),

the most informative sources for facial expression classification were located in the primary and

early visual cortex. At later stages (LPC window), sources in the parietal cortex became more

prominent contributors. Supplementary Table ST2 lists the most relevant sources for the binary

classifiers, which distinguish between pairs of facial expressions. Supplementary Figure S9

visualizes the associated cortical source reconstructions. For the contrasts with the highest

decoding performance ("angry-vs-neutral" and "angry-vs-happy"), primary and early visual

cortices remained the most informative sources, even during the LPC time window. In contrast,

the other pairwise comparisons between two emotional expressions showed more variable

results, with regions along both the ventral and dorsal processing streams playing dominant

roles.

The most informative sources for the classifier trained to distinguish trials with and without

stereoscopic depth information were located along the ventral visual processing stream and in

the MT+ complex (see Figure 3 and Supplementary Figure S8). Similarly, the decoding of face

identity relied primarily on signals originating from the ventral visual processing stream during

the N170 time window (Supplementary Figure S8). In contrast, during the two later time

windows (EPN and LPC), identity decoding shifted to rely most on information from parietal

regions (see Supplementary Table ST2 for an overview).

Figure 3: Spatial patterns and localized sources related to decoding
(a) facial expressions and (b) the availability of stereoscopic depth
information. **(a)** *Top*: Classification of the four facial expressions.
Spatial patterns of the classifier (top row) and their projection onto
the cortical surface using eLORETA (second and third row) for the
four time windows. Colors indicate the absolute, normalized weight
of each sensor or cortical parcel (warmer colors represent higher
absolute weights). In the topographies, the six most informative
channels (top 10%) are highlighted in yellow. Projections on the
cortical surface are masked to show only the top 5% most
informative parcels. Second row: Lateral view on both hemispheres. Third row: View on occipital and
parietal cortices of the right hemisphere. Colored lines on the cortex mark the outlines of relevant regions
(see (c)). *Bottom*: Time course of decoding performance for multiclass classification of the four emotional
expressions (as in Figure 2). **(b)** As in (a) [in reversed order], but for the classifier trained to distinguish
between trials with and without stereoscopic depth information. **(c)** Outlines of relevant cortical regions,
following the reduced parcellation atlas by Glasser et al. (2016) and Mills (2016). *SPC: Superior Parietal*
Cortex; MT+: MT+ Complex and Neighboring Visual Areas; VSVC: Ventral Stream Visual Cortex; EVC:
Early Visual Cortex; PVC: Primary Visual Cortex (V1).

Eye Tracking

Saccade and fixation patterns

To check if the dynamics of the EEG decoding performance can be explained by eye
movements, we analyzed the concurrently recorded eye tracking data (combined gaze between
left and right eye) for a subsample of participants (n=17), for whom eye tracking data were
available. Figure 4b shows the average fixation heatmaps on the face stimuli separately for the
different facial expressions. Supplementary Figure S6 shows the corresponding heatmaps
separately for each of the four time windows. Participants mostly kept fixation at the center of
the face. Towards later time windows (after about 200 ms), there was a notable shift of fixations
towards the lower half of the face. This observation was supported by a 4x2x4 MANOVA which
modeled the average fixation position as a function of facial expression, depth condition, and
time window. The multivariate result was significant for the predictor time window (Wilk's lambda
= 0.93, F(6, 1022) = 6.14, p < .001) but not for the other predictors or any interaction. Univariate
follow-up analyses (rmANOVA and post-hoc t-tests) demonstrated that vertical fixation locations
differed significantly between the LPC time window and all other time windows. No significant

differences were observed among the remaining time windows, and averaged horizontal fixation
positions did not differ significantly across any time window.

In a generalized linear model (GLM; Poisson, log-linear) modeling the number of saccades
(Pseudo R^2 = 0.90, Supplementary Table ST3) only time window was a significant predictor
(Wald $\chi^2(3)$ = 115.81, p < .001). Neither facial expression (Wald $\chi^2(3)$ = 2.42, p = .491) nor depth
condition (Wald $\chi^2(1)$ = 1.47, p = .225) or any interactions explained significant amounts of
variance. The average saccade amplitude did not differ significantly between facial expressions,
depth conditions, or time windows (all p-values > .150). Furthermore, the model did not explain
a substantial portion of the variance in the data (Gaussian, log-linear GLM; Pseudo R^2 = 0.03).
Figure 4c shows the distribution of saccade directions as a function of the time window and
expression. A MANOVA which modeled the average saccade direction (two-dimensional,
spherical coordinates), indicated a significant main effect of time window (Wilk's lambda = 0.96,
F(6, 968) = 3.22, p = .004) and a significant interaction between time window and emotional
expression (Wilk's lambda = 0.94, F(18, 968) = 1.65, p = .04), but no significant effects for the
other predictors.

Figure 4: Eye tracking analyses and comparison with the EEG decoding results. **(a)** *Top left*: Exemplary
gaze trace (one trial) on a stimulus face. Saccades are plotted in red, fixations in blue. The fixation cross

preceding the stimulus was displayed at (0,0). *Top right*: Vertical component of the same gaze trace over
time. *Bottom left*: Horizontal gaze component over time. *Bottom right*: Saccade rate (saccades per
second) over the time of the trial across all trials and participants. Colors like in (b) and (c). We observed
a dip in saccade rate right after stimulus onset, followed by a sharp increase peaking during the EPN time
window. **(b)** Heatmaps showing fixation distributions within the first second after stimulus onset, across all
trials and participants, separated by emotional expression. **(c)** Circular histograms of saccade directions
(polar angles relative to the preceding fixation), plotted per time window and emotional expression (colors
like in (b)). Saccade counts are normalized by the length of the time window. Most saccades occurred
during the time window of the EPN (an ERP component associated with reflexive attention to the
stimulus), predominantly in downward (especially for angry and surprised faces) or lateral directions. **(d)**
Decoding performance of classifiers trained on the gaze data (spherical coordinates) for different
decoding targets. EEG-based decoding performance is overlaid in grey for comparison (in the subset of
participants with eye tracking data). Horizontal bars at the bottom of each plot indicate time points with
decoding significantly above chance level. Red bars mark significant differences in performance between
eye tracking and EEG-based decoding (two-sided, cluster-corrected *t*-test). Note, EEG decoding results
shown here are based on the subsample with eye tracking data (n=17), resulting in lower scores
compared to Figures 1 and 2.

Decodability from gaze data

As for the EEG data, we trained another set of time-resolved, linear classifiers to test the

decodability of relevant attributes—however, now from the two-dimensional gaze data (i.e., the

orientation of the combined eyes in spherical coordinates). Using cluster-corrected permutation

testing, we demonstrated significant decoding performance for the classifier which successfully

distinguished between the four emotional expressions. This was indicated by a cluster of

significant decoding scores which started 230 ms after stimulus onset and extended to the end

of the epoch (1,000 ms). The highest decoding performance (ROC AUC; M = 0.59, SD = 0.03,

95% CI [0.57, 0.60]) was observed for most participants at Mdn = 700 ms (SD = 230.04, 95% CI

[590.65, 809.35]). Using the four time windows which we also used to bin the EEG data (P1,

N170, EPN, LPC), we found a significant effect of the time window on the decoding

performance (F(3,48) = 26.78, p < .001), with significant pairwise differences between all time

windows apart from P1 vs N170 and EPN vs LPC (in other words, no differences between the

two early and between the two late time windows). Only for the two later time windows, EPN

and LPC, the performance of the decoder was significantly above chance level.

We also found significant decoding performance for all binary classifiers (pairwise distinction of

facial expressions) supported by cluster-corrected permutation testing against chance-level.

Further, a rmANOVA comparing the average decoding performance across the binary contrasts

and the four time windows revealed significant main effects for the the decoding contrast

(F(5,80) = 3.12, p = .013) and the time window (F(3,48) = 29.70, p < .001), but no significant

interaction (F(15,240) = 1.50, p = .106). Post-hoc tests (pairwise t-tests, Bonferroni corrected)

showed significant differences in the decoding performance between all time windows, apart from P1 and N170 which did not differ significantly. Later time windows yielded higher decoding performances than early time windows. The post-hoc pairwise comparisons of the contrasts did not reveal any significant differences (after Bonferroni correction).

Stereoscopic information

As for the EEG data, the classifier performance when decoding facial expressions from eye tracking data did not differ between monoscopic and stereoscopic viewing conditions. For the decoding of the facial expressions, there were no significant differences in peak performance (mono: M = 0.60, SD = 0.03, 95% CI [0.58, 0.61]; stereo: M = 0.59, SD = 0.03, 95% CI [0.57, 0.60]; t(16) = 1.88, p = .079) or timing (mono: Mdn = 741.67 ms, SD = 268.15, 95% CI [614.20, 869.14]; stereo: Mdn = 650.00 ms, SD = 301.43, 95% CI [506.71, 793.29]; t(16) = 1.11, p = .283). This finding was indirectly supported by a non-significant cluster-based permutation test contrasting the time-resolved performances for expression decoding in the mono- and the stereoscopic condition. Similarly, no binary classifier showed significant performance differences between the two depth conditions.

In contrast to the EEG data, a separate classifier trained to explicitly differentiate between the two depth conditions (monoscopic vs stereoscopic) based on the time-resolved eye-tracking data did not perform above chance level (see Figure 4d). However, a classifier trained to differentiate between the face identities achieved above chance-level decoding, indicated by a cluster of time-points with significant decoding accuracy, beginning at 242 ms after stimulus onset and continuing until the onset of the response panel (peak decoding score: M = 0.60, SD = 0.03, 95% CI [0.58, 0.61]; peak decoding time: Mdn = 550.00 ms, SD = 231.29, 95% CI [440.05, 659.95]; Figure 4d).

The relationship between EEG and eye tracking based decoding performances

On the group level, there was no significant correlation between the performance of the decoder trained to distinguish facial expressions based on EEG data and the one based on eye tracking data. This applied to peak decoding performance (r(15) = 0.059, p = .821), latency of the peak performance (r(15) = -0.160, p = .540), and average decoding performance across the observation window (r(15) = -0.031, p = .907). Decoding performance based on EEG data surpassed decoding based on eye tracking data early in the trial, as indicated by a significant cluster between 94 and 224 ms (see Figure 3d, left). For the remaining time of the observation window, there was no significant difference between EEG and eye tracking based decoding of

facial expressions. By contrast, the decoders for facial *identity* displayed a different relationship between their performance profiles (see Figure 3d, middle): the EEG-based decoding again ramped up earlier than the eye tracking-based decoding (first significant cluster: 164–194 ms), but at later stages, eye tracking-based decoding outperformed EEG-based decoding (second significant cluster with opposite-signed cluster mass: 384–1,000 ms). In decoding the depth condition, the classifier trained on EEG data outperformed the classifier trained on eye tracking data (significant clusters: 114–224 ms and 244–474 ms), with the latter never reaching a performance level above chance.

Behavior

We compared the emotion ratings provided by the participants with the objective categorization of the facial expression (i.e., the FACS ratings provided by Gilbert et al., 2021). The results are shown in the form of confusion matrices in Supplementary Figure S1. Recognition rates differed across the emotional expressions ($F(3,96) = 6.81$, $p < .001$) but were high for all expressions (correct: M = 90.73%, SD = 16.98, 95% CI [89.06, 92.41]). The lowest recognition level was found for neutral faces (correct: M = 80.32%, SD = 25.12, 95% CI [71.75, 88.89]) which were classified second most frequently as "other" (confusion rate: M = 17.39%, SD = 23.51, 95% CI [9.37, 25.41]). We did not observe a difference in recognition rate for the mono- (M = 90.96 %, SD = 16.79, 95% CI [88.10, 93.82]) and the stereoscopic depth conditions (M = 90.51 %, SD = 17.32, 95% CI [87.55, 93.46]). Accordingly, there was neither a significant main effect of depth condition ($F(2, 64) = 1.85$, p = .165) nor a significant interaction with the emotional expression ($F(6, 192) = 1.37$, p = .230).

To control for the experienced level of intensity, at the end of the experiment, we asked participants to rate for each of the 24 stimuli (4 emotions, 3 face identities, 2 depth conditions; Figure 1c) the intensity of the displayed emotional face expression using the 9-point SAM scale for arousal (Supplementary Figure S2). We observed a significant main effect of emotion ($F(3,93) = 118.95$, p = < .001): Angry faces received the highest intensity ratings (M = 7.82, SD = 0.93, 95% CI [7.50, 8.14]), while neutral faces received the lowest (M = 2.69, SD = 1.66, 95% CI [2.11, 3.26]). Happy (M = 4.60, SD = 1.47, 95% CI [4.09, 5.11]) and surprised faces (M = 6.15, SD = 0.96, 95% CI [5.81, 6.48]) fell in between. Neither the main effect of the depth condition ($F(1,31) = 0.01$, p = .932) nor its interaction with the emotional expression was significant ($F(3,93) = 0.34$, p = .794).

452 Discussion

We investigated the neurocognitive processes underlying the recognition of facial expressions in
immersive VR and if the presence of stereoscopic depth cues changes the neural
representations of face stimuli. In each trial, we showed a computer-generated face which
displayed one out of four facial expressions. As the main measure of interest we used time-
resolved, multivariate decoding from EEG data to infer how much information about the stimulus
is present in the brain signals. Our main decoding target was the emotional expression shown
by the face—which the participants had to indicate at the end of each trial. Facial expressions
could be decoded from EEG data with robust above-chance accuracy. At the same time, the
decoding performance was not influenced by the availability of stereoscopic depth information.
We demonstrate that information about the presence of stereoscopic depth cues is present in
the EEG signals nevertheless: With a separate classifier we could successfully distinguish
mono- from stereoscopic trials. The temporal profile of this decoding differed from decoding the
expressions but resembled the temporal profile of decoding the identity of the stimulus face,
another task-irrelevant feature. We therefore conclude that in neurocognitive processing of face
stimuli, stereoscopic depth information is treated like other task-irrelevant stimulus features
and—at least as long as the behavioral task can be easily solved without integrating this
information—it does not modify the (measurable) neurophysiological representation.

Successful decoding of emotional expression

Our decoding results reveal that the EEG data recorded in our VR setup contained information
about the emotional expression of the stimulus faces. Previous studies have demonstrated that
similar linear EEG classifiers could distinguish between different facial expressions presented
as gray-scale, two-dimensional images on conventional computer screens (Smith & Smith,
2019). Our results replicate and extend these findings by showing that time-resolved
multivariate decoding yields comparable results when using naturalistic, 3D face stimuli in
immersive VR settings. Such setups are gaining interest in human perception and cognition
research for their ability to provide more naturalistic stimulation—closer to how people perceive
and experience the world—thereby potentially improving the generalizability of experimental
findings to real-world contexts (Cisek & Green, 2024). Yet, VR also introduces substantial

challenges compared to the traditional, more restrictive setups. For example, combining EEG
with a VR headset can lower the signal-to-noise ratio by introducing artifacts from mechanical
pressure on the electrodes, muscular activity caused by head movements or headset weight, or
electrical noise from the device and its cables (Tauscher et al., 2019; Weber et al., 2021).
Despite these challenges, our study shows that EEG signal quality in controlled VR settings is
sufficient to reliably discriminate between facial expressions and identities by using linear
classifiers applied to an observer's EEG data. In this context, multivariate decoding is especially
valuable, condensing high-dimensional EEG data into a one-dimensional, time-resolved, and
interpretable metric—decoding performance—via optimized, data-driven weighting of EEG
channels. Cross-validation ensures that the classification results are generalizable and not due
to overfitting. In contrast, traditional ERP analysis rely on strong a priori assumptions (e.g.,
preselected electrodes) and often require extensive post-hoc corrections for multiple
comparisons, yet rarely employ cross-validation. Prior studies have shown that multivariate
decoding offers higher sensitivity than conventional ERP analyses (Carrasco et al., 2024;
Grootswagers et al., 2017), which is particularly relevant for data prone to low signal-to-noise
ratios. Future VR studies on face processing in immersive contexts may build on our findings to
inform their methodological choices and anticipate effect sizes.
Consistent with the findings by Smith & Smith (2019), our EEG decoding results showed distinct
patterns for task-relevant and task-irrelevant features: emotional expression (task-relevant)
yielded sustained decodability after it surpassed chance level, whereas the decoding
performance for task-irrelevant features (here: face identity and availability of stereoscopic
depth cues) peaked early, followed by temporal decline (Figure 2).

The role of stereoscopic depth cues

We hypothesized that 3D viewing—by more closely approximating natural perceptual
contexts—would elicit more robust and distinct neural representations, thereby enhancing
decoding performance. Contrary to this prediction, we found no significant differences in
decoding performance between the two conditions for either a task-relevant (expression) or a
task-irrelevant (identity) decoding target. Stereoscopic information did not enhance decoding
performance, alter its temporal dynamics, or affect the spatial distribution of the classifier
weights. These findings were corroborated by cross-condition generalization tests (cross-
decoding), where classifiers trained and validated on stereoscopic trials performed equally well
when tested on monoscopic trials, and vice versa (Supplementary Figure S5). If 3D and 2D
percepts relied on fundamentally different neural activation patterns, we would expect reduced

generalization across conditions. However, our results provide no evidence for such a
difference, suggesting that the neurophysiological activation patterns underlying facial
expression categorization remain largely consistent regardless of the presence of stereoscopic
depth information.

If the subjective percepts in the two conditions are markedly different, why do the underlying
neural activation patterns associated with the decoded features show no significant differences?
Importantly, our main analyses employed activation patterns optimized for decoding specific
target variables (facial expression, face identity), not representing the brain's holistic response
to the stimuli. Within this scope, 3D and 2D conditions did not show differences. However, when
directly decoding the presence of stereoscopic depth cues, we identified significant distinctions
in the neural responses, peaking around 180 ms after stimulus onset and subsequently
declining—similar to the temporal profile for decoding face identity, another task-irrelevant
feature (Figure 2d). We thereby demonstrate that the distinction between viewing conditions
with and without stereoscopic depth cues was detectable in our neurophysiological data. This
adds to previous findings regarding binocular depth processing gained with different methods
(from single cell recordings in non-human primates to fMRI in humans; for an overview see
Welchman, 2016) and stimuli (from face pictures; Chou et al., 2021; to abstract random dot
motion; Parker, 2007). Our study addresses a relevant research gap by demonstrating that also
EEG data in a VR setup with naturalistic, computer-generated stimuli can track stereoscopic
depth processing. To our knowledge, this is the first study demonstrating that face stimuli
differing only in stereoscopic depth cues can be differentiated through EEG decoding while
investigating potential interference with the representation of other stimulus features.

Cortical sources
In an exploratory analysis, we applied source reconstruction to project the spatial patterns
associated with the decoders back onto the cortical surface. For the classification of emotional
expressions, primary and early visual cortices contributed most substantially, especially shortly
after stimulus onset (P1, N170, and EPN windows). This dominance was particularly evident in
the binary contrasts with the highest decoding performance ("angry-vs-neutral", "angry-vs-
happy"; see Supplementary Figure S9 and Supplementary Table ST2). In contrast, lower-
performing binary classifiers (e.g., "angry-vs-surprised"), relied primarily on regions in lateral
occipital and posterior inferotemporal cortex. This suggests that decoding was more reliable
when information about the contrast was also present in primary or early visual cortices. This
aligns with previous studies which found that early visual cortices, which mostly process low-

level stimulus features, support effective visual input decoding (Kamitani & Tong, 2005; Lützow

Holm et al., 2024; Wilson et al., 2024). Accordingly, the contrasts with the highest decoding

performance expressed the most salient visual differences between the involved faces. For

example, angry faces were characterized by a widely opened mouth showing both rows of

teeth, whereas neutral and happy faces had a closed mouth with no teeth visible. The decoding

of these contrasts may have relied heavily on these low-level feature representations.

Nevertheless, contrasts with more subtle low-level visual differences still yielded above chance-

level decoding, primarily drawing on brain regions higher in the visual processing hierarchy.

When two facial expressions lacked sufficient differences in their low-level visual features,

decoding appeared to rely more on signals from cortical areas known to process abstract

features of facial expressions. Overall, our findings indicate that also for naturalistic face stimuli

the decoding-based approach does not simply exploit arbitrary features, rely solely on low-level

visual features, or exclusively depend on abstract representations of the observed facial

expression.

Running the source reconstruction separately for the mono- and stereoscopic conditions yielded

only slightly different distributions across the cortical surfaces as compared to running it on the

pooled data (see Supplementary Table ST2). We attribute these variations to the fact that

splitting the data set leads to less robust source estimates and therefore a higher variance.

Overall, we did not observe a systematic difference between the distribution of sources in the

mono- as compared to the stereoscopic viewing condition, congruent with the numeric decoding

results.

The decoder trained to explicitly categorize the depth condition (i.e., separating mono- from

stereoscopic trials) mostly relied on information from areas in the ventral visual stream. Also, the

decoding of the different face identities was mostly informed by areas in the ventral visual

stream—in particular during the N170 time window where the decoding performance was

highest. This aligns with previous findings that the N170 reflects activity of the fusiform face

area (Gao et al., 2019) and neighbouring ventral areas which process information relevant for

distinguishing different faces (Eimer, 2011; Grill-Spector et al., 2017; Kanwisher & Yovel, 2006).

Our spatially resolved source reconstruction has limitations: We used a common average head

model without individual anatomical brain scans, relied on the canonical locations in the 10-20

system without participant-specific registration, and faced potential spatial distortions (i.e.,

electrode displacement) from the VR headset worn over the EEG cap. Despite these

constraints, we successfully recorded and analyzed spatially interpretable signals that
meaningfully map onto the cortical surface.

Computer-generated faces as stimuli

We used computer-generated (CG) stimuli, unlike most EEG studies on human face processing
which have typically relied on standardized photographs (e.g., from the Chicago Face
Database; Ma et al., 2015). CG stimuli can be precisely tailored to the specific requirements of
each study whereas photographs are less modifiable and challenging to alter without
introducing visible distortions. For example, to produce gradual (i.e., parametrically adjustable)
versions of facial expressions, "morphing" between versions of two existing images has been
used (Steyvers, 1999). In recent years, more complex generative algorithms have gained
momentum which allow for the creation of artificial but increasingly naturalistic face stimuli both
in 2D and 3D (e.g., Barthel et al., 2025; Feng et al., 2021). Here, we used 3D models and
predefined blend shape modifications to generate a set of static facial expressions. These
expressions had been evaluated in 2D (i.e., rendering 2D images of the generated 3D models)
by an independent sample of both experts and non-experts (Gilbert et al., 2021), ensuring
participants could clearly distinguish them—increasing the likelihood of obtaining separable
EEG signals. Our results establish that robust EEG decoding is achievable in immersive VR
when using clearly distinguishable face stimuli, serving as a foundation for future studies using
more ambiguous facial stimuli to explore how these affect both behavioral responses and EEG
decodability.

Behavioral recognition

Participants were clearly able to recognize the displayed emotional facial expressions. We
designed the stimuli by selecting facial expressions (i.e., FACS configurations) with empirically
validated high recognition rates (Gilbert et al., 2021), minimizing ambiguities in decoding arising
from subjective indecisiveness. This approach ensured that potential challenges encountered
during neural decoding could be ascribed to a lack of information in the EEG signal itself (e.g.,
low signal-to-noise ratio), rather than to the relevant information not being encoded in the first
place. While future studies using more ambiguous facial expressions may reveal additional
aspects of stereoscopic information processing, here we sought to minimize the risk of
uninterpretable null results due to non-significant decoding scores. A prior EEG decoding study
using clearly distinguishable facial expressions achieved only modest above-chance

performance (Smith & Smith, 2019), and VR-EEG setups are likely to exacerbate noise-related
reductions in effect size. We therefore prioritized maximizing decoding feasibility in VR-EEG as
a foundational step for subsequent work, with a special focus on the introduction of stereoscopic
depth cues.

Building on our results and effect sizes, future studies can now more confidently work their way
towards more ambiguous facial expressions while studying the concurrent neurophysiology. We
cannot exclude the possibility that for more ambiguous facial expressions, for which decoding is
more difficult (both for the human observer and the EEG decoder), stereoscopic depth cues
become more critical. Similarly, in computer vision-based recognition of human facial
expressions, it has been shown that, particularly for low-intensity expressions, models
incorporating 3D information outperform those using only 2D information (Savran et al., 2012).

Emotional intensity of the stimuli

Participants' subjective ratings at the end of the experiment indicated differences in emotional
intensity between the facial expressions and the different identities. Stereoscopic depth had no
influence on the intensity ratings.

While the stimulus intensity may partially explain the EEG decoding results, for example,
through arousal contagion (Herrando & Constantinides, 2021), this alone cannot fully account
for our decoding results. While emotional arousal has widespread effects in the human brain
which can be read out by similar decoding approaches (Hofmann et al., 2021), these are
typically not localized in early visual cortices—one of the most informative brain areas in the
present study. Furthermore, face identity was decodable with similar accuracy to expressions
despite substantially weaker differences between the identities in terms of emotional intensity.
Finally, stereoscopic viewing conditions were successfully differentiated based on the EEG,
despite no differences in the emotional intensity ratings between with and without stereoscopic
depth cues.

However, the above argumentation may hold less for later times in the trial (>500 ms after
stimulus onset), during which the decoding performance declined for the task-irrelevant
decoding targets (identity and depth condition) while it was constant for the decoding of the
facial expressions. Also, some of the most informative sources shifted from early visual cortex to
parietal and ventral temporal regions, which have been found to be modulated by emotional
arousal (Greene et al., 2014; Lettieri et al., 2019; Wade-Bohleber et al., 2020). This suggests

that early decoding reflects visual feature processing, while later stages may incorporate
emotional arousal effects.

Eye tracking results and their relation to the EEG results

The EEG decoding might have been influenced by eye movements (Mostert et al., 2018), as
participants could freely explore the faces (for 1,000 ms) after initial central fixation. Analyses of
fixation locations and saccade parameters revealed that the saccade rate peaked around the
EPN time window, with later fixations targeting the lower face—consistent with previous findings
(Schurgin et al., 2014). Saccade direction, especially in the later part of the trial, was modulated
by the facial expression—also consistent with previous findings (Calvo et al., 2018; Schurgin et
al., 2014; Vaidya et al., 2014). Time-resolved linear classifiers showed comparable decoding
performances from eye tracking and EEG data (Figure 4)—with similar temporal profiles—
raising the question of whether EEG decoding might, in the end, simply reflect eye movements
rather than neurophysiological representations of stimulus features (see (Mostert et al., 2018),
for a more detailed discussion of this argument and potential underlying mechanisms).
Importantly, multiple analyses indicate that eye movements do not fully account for the
observed EEG patterns. First, if the decodable activity in the EEG data was directly caused by
eye movements (e.g., due to eyeball motion or by retinal image shifts), both time series should
be perfectly time-aligned or show a slight lead for eye tracking signals. Instead, we observed a
different pattern: eye tracking decodability consistently lagged behind EEG signals by 100–200
ms (see Figure 4d). This delay cannot be attributed to temporal imprecision during data
recording. To compensate for potential lag in eye tracking data recorded with the HTC Vive Pro
Eye, we post-hoc aligned it with the EEG time series, by cross-correlating the eye tracking data
with the electrooculogram channels. We identified and corrected a similar delay as reported by
Stein et al. (2021). Stimulus information was therefore decodable from EEG *before* the
concurrent eye tracking data, making it implausible that eye movements caused the patterns we
observed in the EEG. Second, if EEG decodability were merely a byproduct of the eye
movements, decoding scores from both modalities should be correlated (e.g., participants with
highly/late decodable eye movements should exhibit high/late EEG decoding peaks). Contrary
to this assumption, we found no systematic relationship between EEG and eye tracking-based
decoding metrics on the participant level (see Supplementary Figure S7). Finally, while the
decoding performance curves for EEG and eye tracking look similar when classifying facial
expressions, the patterns differ for the task-irrelevant decoding targets (Figure 3d). Most
prominently, the depth condition—while well decodable from EEG—was entirely undecodable

from eye tracking data. These dissociations make it unlikely that EEG decoding in our data set
merely reflects eye movements. While the similarity in some dynamics suggests shared
information between the modalities, the dissociations strongly indicate that EEG decoding
provides complementary insights, capturing aspects of neurocognitive processing beyond what
eye tracking data alone can reveal—for example, the presence or absence of stereoscopic
depth information.

Conclusion
681

In sum, our results demonstrate that emotional facial expressions can be reliably decoded from
EEG in immersive VR, with no clear advantage observed under conditions involving
stereoscopic depth cues. While the presence of stereoscopic depth elicited distinct neural
signatures, it did not affect the decodability of other, orthogonal face features—whether task-
relevant or irrelevant. This suggests that, in controlled facial emotion recognition tasks using
clearly distinguishable, static stimuli, the brain treats stereoscopic depth like other independent
stimulus features—at least from the perspective of decodable EEG representations. Our
findings establish a methodological foundation for EEG-based decoding in immersive VR and
invite future research to explore how richer, more ambiguous, or dynamic face stimuli might
leverage stereoscopic depth information in behaviorally and neurophysiologically meaningful
ways.

Methods
694

Participants

We acquired data from 34 healthy, young, female adults (age: M = 26.65, SD = 4.56, 5
lefthanded). Persons wearing glasses could not participate in the study to facilitate compatibility
with the eye tracker. We ensured intact stereoscopic vision in all participants using a Titmus test
(*Fly-S Stereo Acuity Test*, Vision Assessment Corporation, Hamburg, Germany). The study was
approved by the ethics committee of the Department of Psychology at the Humboldt-Universität
zu Berlin and participants provided their written consent prior to participation. Participants were
compensated with 12€ per hour.

The final sample consisted of data from 33 participants for the EEG analyses (incomplete data
for 1 participant) and 17 participants for the eye tracking control analyses (due to technical
failure, no eye tracking data was stored for the remaining 16 participants).
706

Setup

We recorded participants' electroencephalogram (EEG) and electrooculogram (EOG) using a
LiveAmp amplifier (BrainProducts GmbH, Gilching) and 60 active electrodes according to the
10-20 system in an electrode cap (actiCap snap; BrainProducts). Four EOG electrodes were
placed below the eyes and next to the outer canthi. All electrodes were referenced to electrode
FCz (ground: FPz). EEG and EOG were sampled at a rate of 500 Hz and using a hardware-
based lowpass filter at 131 Hz (third order sinc filter, −3 dB cutoff). We ensured that at the
beginning of the experiment, the impedances of all electrodes were below 25 kΩ.
During the VR part of the study, participants were seated and wore a VR headset (HTC Vive
Pro Eye, HTC, Taiwan) with an integrated eye tracker (sampling rate: 120 Hz). We adjusted the
headset at the beginning of the experiment to match the interpupillary distance of the
participant.
The VR headset was positioned on top of the EEG cap (covered by a disposable shower cap).
The flat design of the actiCAP snap electrodes, combined with the cushioning of the HTC Vive
Pro's back section, facilitated an even weight distribution, minimizing excessive pressure on any
individual electrode. A custom facial interface cushion with recesses at designated locations
prevented pressure on the frontal EEG electrodes (Fp1/2).
724

Software

For the implementation of the experiment, we used the Unity game engine (v2020.3.3f1; Unity
Technologies) in combination with SteamVR (Valve Corporation) and ran it on a VR-ready PC
(Intel Core i9-9900K, 3.6 GHz, 32 GB RAM, NVIDIA RTX 2080Ti GPU, Windows 10). The
computer was connected to the EEG amplifier via an analog port (D-SUB 25) to enable
synchronization of the EEG data with the experimental events. We used the EDIA toolbox
(Klotzsche et al., 2025)—an extension of the Unity Experiment Framework (v2.3.4; Brookes,
2017/2019)—for structuring the experiment, recording events, and tracking the behavior (incl.
eye movements). The eye tracker was interfaced using the SRanipal SDK and EDIA to allow for
sampling the eye tracking data at 120 Hz. To synchronize the data streams (i.e., stimulus onset

events, eye tracking, EEG), we used custom C# scripts to send analog triggers (EEG) and store

associated timestamps (eye tracking and event data). We recorded EEG and EOG data using

the BrainVision Recorder software (v1.22.0101; BrainProducts). Before and after the VR-based

part of the experiment, participants filled in questionnaires implemented in SoSciSurvey (Leiner,

2019). Data analysis was performed using Python (v3.10.4), Scikit-learn (v1.5.1; Pedregosa et

al., 2011), SciPy (v1.14.0; Virtanen et al., 2020), statsmodels (v0.14.2; Seabold & Perktold,

2010), and NumPy (v1.26.4; Harris et al., 2020).

Stimuli

The stimulus set entailed computer-generated faces from three digital humans, each showing

four different facial expressions (angry, happy, neutral, surprised; see Figure 1c), yielding 12

static face stimuli in total. We generated the faces using the open-source software makehuman

and the FACSHuman plugin (Gilbert et al., 2021), based on material provided by the first author

of the plugin. Gilbert et al. (2021) provide validations of 2D, greyscale versions of these stimuli.

Two independent raters, professionally trained in the Facial Action Coding System (FACS;

Ekman & Friesen, 1978), had approved the adherence of the emotional expressions to the

FACS criteria and their recognizability was demonstrated in a sample of naïve participants in an

online experiment (Gilbert et al., 2021). For the present study, we selected the four emotional

expressions which were best recognized and distinguished from one another in this validation

experiment. We chose only female faces and we manually masked the hair and the ears of the

3D models (using the Blender software; v2.93, Blender Development Team, 2021) to decrease

task-unrelated differences between the stimuli. Each face stimulus measured approximately 24

cm in vertical height (from the crown of the head to the base of the neck), roughly matching the

dimensions of an adult human face in physical reality. We presented the faces against a grey

background and at a distance of 1.37 virtual meters from the perspective of the participant, so

that for the observer each face spanned approximately 10 degrees of visual angle (dva) along

its vertical axis. Stimuli were presented centrally in the visual field in a way that the virtual head

frontally faced the participant irrespective of the orientation of the participant's head (i.e., in *local*

space). Head movements, therefore, did not lead to displacements of the stimuli within the

visual field. For the 3D condition, we displayed the regular three-dimensional model of the face

stimuli, yielding a stereoscopic view in the VR headset. The VR software renders two slightly

different viewpoints of the scene to the displays in the headset, thereby enabling stereoscopic

depth cues. In the 2D condition, we replaced the 3D model by a two-dimensional "portrait shot"

768 taken by a single cyclopean (virtual) camera and displayed as a canvas in the Unity scene. The

769 2D image was size- and position-aligned with the (invisible) 3D head model and then rendered

770 to the displays in the headset, yielding an impression very similar to the rendering in the 3D

771 condition, just without stereoscopic depth information (Figure 1b). The percept in the 2D

772 condition was comparable to viewing a life-size portrait picture from a distance of 1.37 m.

Task

775 In the main task of the experiment, participants performed an emotion recognition task (Figure

776 1a). In each trial, after a fixation period of 500 ms, we displayed for 1,000 ms a single face

777 stimulus centrally in the visual field of the participant. After the offset of the face, the participant

778 was presented with five response buttons arranged in a cross-like fashion centrally in the visual

779 field (see Figure 1a). The buttons displayed the four facial expression categories (neutral, angry,

780 happy, surprised) as well as the option "other". Using a VR controller, participants indicated their

781 response by pointing a ray toward the corresponding virtual button. The assignment of the

782 buttons to the positions on the cross was randomized across trials. Participants could therefore

783 only decide where to press once the buttons were visible, thus avoiding preparatory activity

784 during the presentation of the face stimulus. The next trial started immediately after the

785 response or automatically 5,000 ms after stimulus offset.

786 In 50% of the trials, the face stimuli were shown with stereoscopic depth information. In the

787 remaining trials, the 2D version of the face was presented. The experimental manipulations

788 (facial expression, identity, depth condition) were fully interleaved and pseudo-randomized,

789 ensuring a uniform distribution of all experimental conditions within each block. Participants

790 completed six experimental blocks with 120 trials each, yielding 720 trials in total. After each

791 block, the experiment was paused and participants could take a short break (incl. removal of the

792 VR headset and re-calibration of the eye tracker).

793 Before the start of the first block, participants completed 24 training trials to get familiar with the

794 task and the stimuli. In these trials, each combination of face identity, facial expression, and

795 depth condition was shown once in a random sequence. Data from the training trials was not

796 analyzed.

797 After the main block of the experiment, participants performed an intensity rating of all face

798 stimuli. To this end, all 24 combinations of face identity, facial expression, and depth condition

799 were shown in a random sequence in the VR headset. This time, the face stimulus was visible

800 permanently (until the participant had responded) above a 9-point self-assessment manikin

801 (SAM) scale (Bradley & Lang, 1994) that allowed the participant to indicate the intensity (i.e., the
802 degree of emotional arousal) of the displayed facial expression (see Supplementary Figure S2).
803 Participants selected the according level with the VR controller. No EEG or eye tracking data
804 was recorded for this part.
805

EEG preprocessing

We processed the EEG data with MNE-Python (v1.2.3; Gramfort et al., 2013). First, we
identified and rejected channels which were noisy throughout the experiment based on their
power spectrum and visual inspection. Using ICA decomposition (extended Infomax), we then
removed artifacts caused by blinks and eye movements. For fitting the ICA solution, we used a
separate copy of the data which we filtered between 1 and 40 Hz (FIR filter with a hamming
window of length 1651 samples, lower/upper passband edge: 1.00/40.00 Hz, lower/upper
transition bandwidth: 1.00/10.00 Hz, lower/upper −6 dB cutoff frequency: 0.50/45.00 Hz).
From this copy, we extracted epochs of 1,300 ms in length, starting 300 ms before and ending
1,000 ms after the onset of the face stimuli. Epochs with particularly noisy EEG signals were
identified using the autoreject software (v0.4.3; Jas et al., 2017) and removed before fitting the
ICA weights. Based on their correlation with the bipolar EOG channels and visual inspection, we
identified components related to blinks and other eye movements. Using only the remaining ICA
weights (i.e., setting the weights of affected channels to zero), we cleaned a separate version of
the data. This dataset was filtered between 0.1 and 40 Hz (FIR filter with hamming window of
length 16,501 samples, lower/upper passband edge: 0.10/40.00 Hz, lower/upper transition
bandwidth: 0.10/10.00 Hz, lower/upper −6 dB cutoff frequency: 0.05/45.00 Hz) to preserve
slow ERP components. Again, we extracted epochs of 1,300 ms in length, starting 300 ms
before and ending 1,000 ms after the onset of the face stimuli. For baseline-correction, we
subtracted the mean voltage during a 200 ms baseline interval (i.e., the 200 ms before
stimulus onset) from each epoch. Subsequently, we used the autoreject package for local (i.e.,
per participant, sensor, and epoch) interpolation and trial rejection.
828

EEG decoding

We trained and cross-validated time-resolved linear classifiers on the EEG data to test the
decodability of the facial expressions from the participant's brain activity. A separate decoding
model was validated for each participant using all available EEG channels. The samples used

for training and testing the classifier were formed by averaging mini-batches of three trials from
the same class. Using averaged data from mini-batches has been found to improve the
performance of classifiers trained on EEG data due to suppression of noise (Adam et al., 2020;
Grootswagers et al., 2017). Along the time-dimension, we downsampled the signal using a
moving average of five samples (10 ms) with no overlap. For each time point, we then trained a
logistic regression model (solver: liblinear, L2-regularization: $\lambda = 1.0$) on the data from all 60
EEG sensors and assessed its decoding performance by means of a stratified 5-fold cross-
validation. In each fold, the model was trained on 80% of the mini-batches and tested on the
remaining 20% while we kept the class proportions equal between train and test sets.
Comparing the model predictions with the ground truth (FACS ratings of the facial expressions)
in the test set, we calculated the area under the receiver operating characteristic (ROC-AUC) to
assess the model's decoding performance. To obtain a robust estimate, we performed this
decoding procedure 50 times for each participant and time point—varying the random allocation
of trials into mini-batches and randomly splitting samples into train and test sets. An overall
decoding score per time point and participant was obtained by averaging the ROC-AUC scores
across all repetitions.
We conducted cluster-based permutation tests on the group-level to determine whether the
decoding performance was significantly above chance-level during the first second after
stimulus onset. To this end, we calculated a one-sided paired t-test for each time point, testing if
the actual decoding score was significantly higher than chance (ROC-AUC = 0.5). The cluster-
based permutation procedure allowed for a correction of the number of tests (i.e., the number of
time points). For a physiological interpretation of the decoding results, we calculated the
patterns of the classifier (by multiplying the covariance of the EEG data with the filter weights;
Haufe et al., 2014) for each time point.
To test the decodability of the facial expression (i.e., a four-class classification problem), we
trained the above-mentioned model by applying a *one-vs-rest* (i.e., one vs the three remaining
conditions) multi-class extension of the binary classifier. We further evaluated separate models
for each two-sided contrast (i.e., six pairwise contrasts between the four emotional expressions)
for enhanced interpretability.
To facilitate the interpretability of the decoding results across time, we calculated the mean
decoding score within four distinct time windows, based on canonical ERP components
associated with face expression processing (P1, N170, EPN, LPC).

Using repeated-measures analyses of variance (rmANOVAs) and post-hoc *t*-tests (Bonferroni

corrected), we modeled the decoding performance as a function of the *time window* (four levels)

and the binary decoding *contrast* (six levels).

To test whether the presence of stereoscopic depth cues impacts the decodability, we

performed the same decoding procedure separately with data from the mono- and stereoscopic

depth conditions. We then compared the resulting decoding performances at each time window

using two-sided, paired *t*-tests with cluster-correction. We also compared the monoscopic and

the stereoscopic depth condition in terms of the peak decoding performance (highest decoding

performance across all time points) and its latency using paired, two-sided *t*-tests. Further, we

used a rmANOVA with the factors *time window* (P1, N170, EPN, LPC) and *depth condition*

(mono- vs stereoscopic) to model the decoding scores. Finally, we used the same decoding

procedure to make the *depth condition* itself the decoding target (i.e., predicting if a sample was

measured under mono- or stereoscopic viewing conditions), as well as the *identity* of the

stimulus face (three classes; see Figure 1c)—both task-irrelevant features of the stimulus.

Source reconstruction

To achieve higher spatial resolution of key brain areas relevant for classification, we applied

source reconstruction to project the spatial patterns obtained from the decoding process onto

the cortical surface. Specifically, we used exact low-resolution tomography analysis (eLORETA;

Pascual-Marqui, 2007) to localize the sources corresponding to the extracted components. The

reconstruction utilized the standard average forward model from FreeSurfer (Fischl et al., 1999)

as provided by MNE-Python, restricting the solution to dipoles with fixed orientations

perpendicular to the cortical surface. Using eLORETA, we constructed spatial filters for each

voxel from the leadfield matrix. The sources were then computed by multiplying the demixing

matrix with the spatial patterns (Haufe et al., 2014) derived from the classifiers trained in EEG

channel space. For multiclass classifiers, this procedure was performed separately for each

underlying binary (one-vs-rest) classifier, and the normalized source time courses were

averaged (per time point) to produce a single overall source time course for the multiclass

decoder. To determine the most informative source within the canonical ERP time windows, we

calculated the average weight of each vertex over the respective time intervals, identified the

vertex with the highest average weight, and classified its corresponding brain region using the

reduced parcellation atlas (23 labels per hemisphere) provided by Glasser et al. (2016) and

Mills (2016).

Eye tracking analyses

We analyzed the eye tracking data (combined gaze data for left and right eye as provided by the eye tracking SDK) in a subsample of 17 participants (due to a technical error no eye tracking data was recorded for the remaining participants). To compensate for the internal processing time of the eye tracker—specifically, the delay between recording an eye tracking sample and the moment when the corresponding sample is provided by the eye tracking SDK (Stein et al., 2021)—and to ensure temporal alignment of the eye tracking data with the EEG data, we first performed a cross-correlation between the eye tracking data and the EOG channels of the EEG data. This yielded a temporal offset between the two signals of on average 60 ms (SD = 3.80, range: 50–67 ms); this delay was corrected by subtracting it from the timestamps in the eye tracking samples. We performed a baseline-correction procedure on a trial-by-trial basis, in which we subtracted the mean gaze position during the 200 ms time window before the onset of the stimulus face from the gaze positions in the entire trial. Furthermore, we identified blinks using the algorithm based on the dynamics of the pupil dilation values suggested by Kret & Sjak-Shie (2019), which specifically looks for rapid changes in pupil size. We then linearly interpolated the gaze values during the times of identified blinks (plus a safety margin of 100 ms on each side).

We applied the same decoding approach as we used for the EEG data: we trained and evaluated a time-resolved linear classifier with a similar architecture (L2-regularized logistic regression; λ = 1.0; repeated randomized 5-fold cross-validation) for each participant. Here, we decoded the target variables (e.g., facial expressions, depth conditions, face identities) from the time-resolved, two-dimensional gaze direction. To this end, we converted the gaze vector (i.e., viewing direction) into spherical coordinates: phi (vertical) and theta (horizontal component). In contrast to the EEG-decoding, we did not apply downsampling nor mini-batching for the decoding from eye tracking data because, in comparison to EEG, eye tracking data is substantially less prone to measurement noise and single-trial data is more reliable.

In exploratory analyses, we analyzed the gaze behavior by classifying saccades and fixations on a single trial level. Saccade detection was based on a velocity-based algorithm with noise-dependent threshold (i.e., 5 SDs velocity threshold and minimum duration of 3 samples; Engbert et al., 2015; Engbert & Kliegl, 2003; Engbert & Mergenthaler, 2006). For these analyses, we excluded saccades with amplitudes smaller than 2 degrees of visual angle. This exclusion criterion was implemented due to the limitations in precision and sampling rate of the eye

tracker within the VR headset, which make the classification and description of smaller
saccades unreliable. For fixations, we retained only those with a duration of at least 50
milliseconds. To calculate the fixation heatmaps in Figure 4, we followed the recommendation
provided by Le Meur & Baccino (2013): On the subject-level, we calculated the average
spherical coordinates for each fixation, binned the fixations into spatial bins of a width and
height of 0.1 dva, and convolved the resulting two-dimensional histogram (across all trials of the
respective condition) with a two-dimensional gaussian kernel (SD = 1 dva for both dimensions
and default parameters for the method "gaussian_kernel" from the SciPy Python module). We
calculated a 4x2x4 MANOVA which modeled the average fixation position (two-dimensional,
spherical coordinates) as a function of the face's expression (neutral, angry, happy, surprised),
depth condition (mono, stereo), and time window (P1, N170, EPN, LPC). We used the same
model to analyze the (two-dimensional) saccade directions. Further, we applied Generalized
Linear Models (GLM) to model the number of saccades (Poisson, log-linear link function) and
the saccade amplitude (Gaussian, log-linear) as a function of emotional expression, time
window, and depth condition.

Behavioral data

We compared participants' behavioral categorizations of each trial's facial expression with the
objective categorizations based on the FACS values to calculate confusion matrices
(Supplementary Figure S1). Due to the high level of agreement, we used the FACS categories
as ground truth for the further analyses. To test for differences in the recognition performance
between the mono- and the stereoscopic depth condition, we calculated a rmANOVA, modeling
the recognition scores (i.e., the values on the diagonal of the confusion matrices in
Supplementary Figure S1) as a function of the depth condition (two levels), the emotional
expression (four levels), and their interaction. Finally, we modeled the intensity ratings from the
last part of the experiment (based on the 9-point SAM scale) using a rmANOVA with the factors
emotional expression and depth condition.

Supplementary Material

Supplementary information is available in a separate file.

Further information

Data availability

The data that support the findings of this study are openly available in "Edmond – the Open Research Data Repository of the Max Planck Society" at https://doi.org/10.17617/3.CQ2VXX. The code for data analysis can be found at https://github.com/eioe/vr2f.

Acknowledgements

We thank Michael Gilbert for his support and guidance regarding the stimulus material, particularly for providing the original 3D face models from his validation study. We are also grateful to Jeroen de Mooij for his assistance and expertise in implementing the experiment in Unity. This research was supported by the cooperation between the Max Planck Society and the Fraunhofer Gesellschaft (grant: project NEUROHUM). This work was conducted at the Max Planck Dahlem Campus of Cognition (MPDCC) of the Max Planck Institute for Human Development, Berlin, Germany.

CrediT statement

Felix Klotzsche: Conceptualization, Data curation, Formal Analysis, Investigation, Methodology, Software, Visualization, Writing – original draft, Writing – review & editing;
Ammra Nasim: Conceptualization, Data curation, Investigation, Methodology, Writing – review & editing;
Simon M. Hofmann: Conceptualization, Methodology, Software, Writing – review & editing;
Arno Villringer: Funding Acquisition, Resources, Supervision;
Vadim Nikulin: Formal Analysis, Methodology, Supervision, Writing – review & editing;
Werner Sommer: Conceptualization, Formal Analysis, Methodology, Supervision, Visualization, Writing – review & editing;
Michael Gaebler: Conceptualization, Funding Acquisition, Resources, Supervision, Writing – original draft, Writing – review & editing;

Competing interests

The authors declare no competing interests.

988 **Attributions**

989 Figure 1:

990 *Canon AT-1 Retro Camera* (https://skfb.ly/6ZwNB) by AleixoAlonso and *EyeBall*

991 (https://skfb.ly/osJMS) by CrisLArt are licensed under Creative Commons Attribution

992 (http://creativecommons.org/licenses/by/4.0/).

References

Adam, K. C. S., Vogel, E. K., & Awh, E. (2020). Multivariate analysis reveals a generalizable

      human electrophysiological signature of working memory load. *Psychophysiology*,

      57(12). https://doi.org/10.1111/psyp.13691

Barry, S. R. (with Sacks, O. W.). (2010). *Fixing my gaze: A scientist's journey into seeing in*

      three dimensions / Susan R. Barry, foreword by Oliver Sacks. Basic Books.

Barthel, F., Morgenstern, W., Hinzer, P., Hilsmann, A., & Eisert, P. (2025). *CGS-GAN: 3D*

      Consistent Gaussian Splatting GANs for High Resolution Human Head Synthesis

      (arXiv:2505.17590). arXiv. https://doi.org/10.48550/arXiv.2505.17590

Blender Development Team. (2021). *Blender* (Version 2.93) [Computer software].

      https://www.blender.org

Bradley, M. M., & Lang, P. J. (1994). Measuring emotion: The self-assessment manikin and the

      semantic differential. *Journal of Behavior Therapy and Experimental Psychiatry*, *25*(1),

      49–59. https://doi.org/10.1016/0005-7916(94)90063-9

Brookes, J. (2019). *Unity Experiment Framework* (Version v2.0.1) [Computer software].

      https://github.com/immersivecognition/unity-experiment-framework (Original work

      published 2017)

Bruce, V., & Young, A. (1986). Understanding face recognition. *British Journal of Psychology*,

      77(3), 305–327. https://doi.org/10.1111/j.2044-8295.1986.tb02199.x

Brunet, N. M. (2023). Face processing and early event-related potentials: Replications and

      novel findings. *Frontiers in Human Neuroscience*, *17*, 1268972.

      https://doi.org/10.3389/fnhum.2023.1268972

Burke, D., Taubert, J., & Higman, T. (2007). Are face representations viewpoint dependent? A

      stereo advantage for generalising across different views of faces. *Vision Research*,

      47(16), 2164–2169. https://doi.org/10.1016/j.visres.2007.04.018

Calder, A. J., & Young, A. W. (2005). Understanding the recognition of facial identity and facial

expression. *Nature Reviews Neuroscience*, *6*(8), 641–651.

https://doi.org/10.1038/nrn1724

Calvo, M. G., Fernández-Martín, A., Gutiérrez-García, A., & Lundqvist, D. (2018). Selective eye

fixations on diagnostic face regions of dynamic emotional expressions: KDEF-dyn

database. *Scientific Reports*, *8*(1), 17039. https://doi.org/10.1038/s41598-018-35259-w

Carrasco, C. D., Bahle, B., Simmons, A. M., & Luck, S. J. (2024). Using multivariate pattern

analysis to increase effect sizes for event-related potential analyses. *Psychophysiology*,

61(7), e14570. https://doi.org/10.1111/psyp.14570

Choi, J. W., Kwon, H., Choi, J., Kaongoen, N., Hwang, C., Kim, M., Kim, B. H., & Jo, S. (2023).

Neural Applications Using Immersive Virtual Reality: A Review on EEG Studies. *IEEE*

Transactions on Neural Systems and Rehabilitation Engineering, *31*, 1645–1658.

https://doi.org/10.1109/TNSRE.2023.3254551

Chou, I. W. Y., Ban, H., & Chang, D. H. F. (2021). Modulations of depth responses in the human

brain by object context: Does biological relevance matter? *eNeuro*, *8*(4), ENEURO.0039-

21.2021. https://doi.org/10.1523/ENEURO.0039-21.2021

Cisek, P., & Green, A. M. (2024). Toward a neuroscience of natural behavior. *Current Opinion in*

Neurobiology, *86*, 102859. https://doi.org/10.1016/j.conb.2024.102859

Cumming, B. G., & Parker, A. J. (1997). Responses of primary visual cortical neurons to

binocular disparity without depth perception. *Nature*, *389*(6648), 280–283.

https://doi.org/10.1038/38487

Cutting, J. E., & Vishton, P. M. (1995). Perceiving layout and knowing distances: The

integration, relative potency, and contextual use of different information about depth. In

Perception of space and motion (pp. 69–117). Academic Press.

https://doi.org/10.1016/B978-012240530-3/50005-5

Draschkow, D. (2022). Remote virtual reality as a tool for increasing external validity. *Nature*

Reviews Psychology, 1–2. https://doi.org/10.1038/s44159-022-00082-8

Duchaine, B., & Yovel, G. (2015). A Revised Neural Framework for Face Processing. *Annual*

Review of Vision Science, *1*(Volume 1, 2015), 393–416. https://doi.org/10.1146/annurev-

vision-082114-035518

Eimer, M. (2011). The Face-Sensitive N170 Component of the Event-Related Brain Potential. In

A. J. Calder, G. Rhodes, M. H. Johnson, & J. V. Haxby (Eds.), *Oxford Handbook of Face*

Perception (p. 0). Oxford University Press.

https://doi.org/10.1093/oxfordhb/9780199559053.013.0017

Ekman, P., & Friesen, W. V. (1978). Facial action coding system. *Environmental Psychology &*

Nonverbal Behavior. https://psycnet.apa.org/doiLanding?doi=10.1037/t27734-000.

Engbert, R., & Kliegl, R. (2003). Microsaccades uncover the orientation of covert attention.

Vision Research, *43*(9), 1035–1045. https://doi.org/10.1016/S0042-6989(03)00084-1

Engbert, R., & Mergenthaler, K. (2006). Microsaccades are triggered by low retinal image slip.

Proceedings of the National Academy of Sciences, *103*(18), 7192–7197.

https://doi.org/10.1073/pnas.0509557103

Engbert, R., Sinn, P., Mergenthaler, K., & Trukenbrod, H. (2015). *Microsaccade Toolbox for R*

(Version v0.9) [Computer software].

Feng, Y., Feng, H., Black, M. J., & Bolkart, T. (2021). Learning an animatable detailed 3D face

model from in-the-wild images. *ACM Transactions on Graphics*, *40*(4), 88:1-88:13.

https://doi.org/10.1145/3450626.3459936

Fischl, B., Sereno, M. I., Tootell, R. B. H., & Dale, A. M. (1999). High-resolution intersubject

averaging and a coordinate system for the cortical surface. *Human Brain Mapping*, *8*(4),

272–284. https://doi.org/10.1002/(SICI)1097-0193(1999)8:4<272::AID-

HBM10>3.0.CO;2-4

Freiwald, W., Duchaine, B., & Yovel, G. (2016). Face Processing Systems: From Neurons to

Real-World Social Perception. *Annual Review of Neuroscience*, *39*(1), 325–346.

https://doi.org/10.1146/annurev-neuro-070815-013934

Gao, C., Conte, S., Richards, J. E., Xie, W., & Hanayik, T. (2019). The neural sources of N170:

Understanding timing of activation in face-selective areas. *Psychophysiology*, *56*(6),

e13336. https://doi.org/10.1111/psyp.13336

Gilbert, M., Demarchi, S., & Urdapilleta, I. (2021). FACSHuman, a software program for creating

experimental material by modeling 3D facial expressions. *Behavior Research Methods*,

53(5), 2252–2272. https://doi.org/10.3758/s13428-021-01559-9

Glasser, M. F., Coalson, T. S., Robinson, E. C., Hacker, C. D., Harwell, J., Yacoub, E., Ugurbil,

K., Andersson, J., Beckmann, C. F., Jenkinson, M., Smith, S. M., & Van Essen, D. C.

(2016). A multi-modal parcellation of human cerebral cortex. *Nature*, *536*(7615), 171–

178. https://doi.org/10.1038/nature18933

Gramfort, A., Luessi, M., Larson, E., Engemann, D. A., Strohmeier, D., Brodbeck, C., Goj, R.,

Jas, M., Brooks, T., Parkkonen, L., & Hämäläinen, M. S. (2013). MEG and EEG Data

Analysis with MNE-Python. *Frontiers in Neuroscience*, *7*(267), 1–13.

https://doi.org/10.3389/fnins.2013.00267

Greene, C. M., Flannery, O., & Soto, D. (2014). Distinct parietal sites mediate the influences of

mood, arousal, and their interaction on human recognition memory. *Cognitive, Affective,*

& Behavioral Neuroscience, *14*(4), 1327–1339. https://doi.org/10.3758/s13415-014-

0266-y

Grill-Spector, K., Weiner, K. S., Kay, K., & Gomez, J. (2017). The Functional Neuroanatomy of

Human Face Perception. *Annual Review of Vision Science*, *3*, 167–196.

https://doi.org/10.1146/annurev-vision-102016-061214

Grootswagers, T., Wardle, S. G., & Carlson, T. A. (2017). Decoding Dynamic Brain Patterns

from Evoked Responses: A Tutorial on Multivariate Pattern Analysis Applied to Time

Series Neuroimaging Data. *Journal of Cognitive Neuroscience*, *29*(4), 677–697.

https://doi.org/10.1162/jocn_a_01068

Hakala, J., Kätsyri, J., & Häkkinen, J. (2015). Stereoscopy Amplifies Emotions Elicited by Facial

Expressions. *I-Perception*, *6*(6), 2041669515615071.

https://doi.org/10.1177/2041669515615071

Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D.,

Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk, M.

H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., … Oliphant, T. E.

(2020). Array programming with NumPy. *Nature*, *585*(7825), 357–362.

https://doi.org/10.1038/s41586-020-2649-2

Haufe, S., Meinecke, F., Görgen, K., Dähne, S., Haynes, J.-D., Blankertz, B., & Bießmann, F.

(2014). On the interpretation of weight vectors of linear models in multivariate

neuroimaging. *NeuroImage*, *87*, 96–110.

https://doi.org/10.1016/j.neuroimage.2013.10.067

Haxby, J. V., Hoffman, E. A., & Gobbini, M. I. (2000). The distributed human neural system for

face perception. *Trends in Cognitive Sciences*, *4*(6), 223–233.

https://doi.org/10.1016/S1364-6613(00)01482-0

Hebart, M. N., & Baker, C. I. (2018). Deconstructing multivariate decoding for the study of brain

function. *NeuroImage*, *180*, 4–18. https://doi.org/10.1016/j.neuroimage.2017.08.005

Herrando, C., & Constantinides, E. (2021). Emotional Contagion: A Brief Overview and Future

Directions. *Frontiers in Psychology*, *12*. https://doi.org/10.3389/fpsyg.2021.712606

Hofmann, S. M., Klotzsche, F., Mariola, A., Nikulin, V., Villringer, A., & Gaebler, M. (2021).

Decoding subjective emotional arousal from EEG during an immersive virtual reality

experience. *eLife*, *10*, e64812. https://doi.org/10.7554/eLife.64812

Jack, R. E., & Schyns, P. G. (2015). The Human Face as a Dynamic Tool for Social

Communication. *Current Biology: CB*, *25*(14), R621-634.

https://doi.org/10.1016/j.cub.2015.05.052

Jas, M., Engemann, D. A., Bekhti, Y., Raimondo, F., & Gramfort, A. (2017). Autoreject:

Automated artifact rejection for MEG and EEG data. *NeuroImage*, *159*, 417–429.

https://doi.org/10.1016/j.neuroimage.2017.06.030

Kamitani, Y., & Tong, F. (2005). Decoding the visual and subjective contents of the human

brain. *Nature Neuroscience*, *8*(5), 679–685. https://doi.org/10.1038/nn1444

Kanwisher, N., & Yovel, G. (2006). The fusiform face area: A cortical region specialized for the

perception of faces. *Philosophical Transactions of the Royal Society B: Biological*

Sciences, *361*(1476), 2109–2128. https://doi.org/10.1098/rstb.2006.1934

Klotzsche, F., de Mooij, J., Ohl, S., & Gaebler, M. (2025, May). *EDIA: An open-source toolbox*

for virtual reality-based eye tracking research using Unity. Annual Meeting of the Vision

Science Society, St. Pete's Beach, Florida, USA.

Klotzsche, F., Gaebler, M., Villringer, A., Sommer, W., Nikulin, V., & Ohl, S. (2023). *Visual short-*

term memory related EEG components in a virtual reality setup (p. 2023.01.23.525140).

bioRxiv. https://doi.org/10.1101/2023.01.23.525140

Kret, M. E., & Sjak-Shie, E. E. (2019). Preprocessing pupil size data: Guidelines and code.

Behavior Research Methods, *51*(3), 1336–1342. https://doi.org/10.3758/s13428-018-

1075-y

Kriegeskorte, N., & Douglas, P. K. (2019). Interpreting encoding and decoding models. *Current*

Opinion in Neurobiology, *55*, 167–179. https://doi.org/10.1016/j.conb.2019.04.002

Le Meur, O., & Baccino, T. (2013). Methods for comparing scanpaths and saliency maps:

Strengths and weaknesses. *Behavior Research Methods*, *45*(1), 251–266.

https://doi.org/10.3758/s13428-012-0226-9

Leiner, D. J. (2019). *SoSci Survey* [Computer software]. https://www.soscisurvey.de

Lettieri, G., Handjaras, G., Ricciardi, E., Leo, A., Papale, P., Betta, M., Pietrini, P., & Cecchetti,

L. (2019). Emotionotopy in the human right temporo-parietal cortex. *Nature Communications*, *10*(1), 5568. https://doi.org/10.1038/s41467-019-13599-z

Liu, C. H., & Ward, J. (2006). The use of 3D information in face recognition. *Vision Research*, *46*(6), 768–773. https://doi.org/10.1016/j.visres.2005.10.008

Liu, C. H., Ward, J., & Young, A. W. (2006). Transfer between two- and three-dimensional representations of faces. *Visual Cognition*, *13*(1), 51–64. https://doi.org/10.1080/13506280500143391

Liu, H., Laeng, B., & Czajkowski, N. O. (2020). Does stereopsis improve face identification? A study using a virtual reality display with integrated eye-tracking and pupillometry. *Acta Psychologica*, *210*, 103142. https://doi.org/10.1016/j.actpsy.2020.103142

Lützow Holm, E., Fernández Slezak, D., & Tagliazucchi, E. (2024). Contribution of low-level image statistics to EEG decoding of semantic content in multivariate and univariate models with feature optimization. *NeuroImage*, *293*, 120626. https://doi.org/10.1016/j.neuroimage.2024.120626

Ma, D. S., Correll, J., & Wittenbrink, B. (2015). The Chicago face database: A free stimulus set of faces and norming data. *Behavior Research Methods*, *47*(4), 1122–1135. https://doi.org/10.3758/s13428-014-0532-5

Menz, M. D., & Freeman, R. D. (2003). Stereoscopic depth processing in the visual cortex: A coarse-to-fine mechanism. *Nature Neuroscience*, *6*(1), 59–65. https://doi.org/10.1038/nn986

Mills, K. (2016). *HCP-MMP1.0 projected on fsaverage* (p. 4139170 Bytes) [Dataset]. figshare. https://doi.org/10.6084/M9.FIGSHARE.3498446.V2

Mostert, P., Albers, A. M., Brinkman, L., Todorova, L., Kok, P., & de Lange, F. P. (2018). Eye Movement-Related Confounds in Neural Decoding of Visual Working Memory

Representations. *eNeuro*, *5*(4), ENEURO.0401-17.2018.

https://doi.org/10.1523/ENEURO.0401-17.2018

Nolte, D., Schmidt, V., Grasso-Cladera, A., & König, P. (2024). *Investigating saccade-onset locked EEG signatures of face perception during free-viewing in a naturalistic virtual environment*. https://doi.org/10.1101/2024.12.12.628113

Nolte, D., Vidal De Palol, M., Keshava, A., Madrid-Carvajal, J., Gert, A. L., von Butler, E.-M., Kömürlüoğlu, P., & König, P. (2025). Combining EEG and eye-tracking in virtual reality: Obtaining fixation-onset event-related potentials and event-related spectral perturbations. *Attention, Perception & Psychophysics*, *87*(1), 207–227. https://doi.org/10.3758/s13414-024-02917-3

Parker, A. J. (2007). Binocular depth perception and the cerebral cortex. *Nature Reviews Neuroscience*, *8*(5), 379–391. https://doi.org/10.1038/nrn2131

Pascual-Marqui, R. D. (2007). Discrete, 3D distributed, linear imaging methods of electric neuronal activity. Part 1: Exact, zero error localization. *arXiv:0710.3341 [Math-Ph, Physics:Physics, q-Bio]*. http://arxiv.org/abs/0710.3341

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., & others. (2011). Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, *12*(Oct), 2825–2830.

Peelen, M. V., & Downing, P. E. (2023). Testing cognitive theories with multivariate pattern analysis of neuroimaging data. *Nature Human Behaviour*, *7*(9), 1430–1441. https://doi.org/10.1038/s41562-023-01680-z

Ritchie, J. B., Kaplan, D. M., & Klein, C. (2019). Decoding the Brain: Neural Representation and the Limits of Multivariate Pattern Analysis in Cognitive Neuroscience. *The British Journal for the Philosophy of Science*, *70*(2), 581–607. https://doi.org/10.1093/bjps/axx023

Rossion, B. (2014). Understanding face perception by means of human electrophysiology.

Trends in Cognitive Sciences, *18*(6), 310–318. https://doi.org/10.1016/j.tics.2014.02.013

Rossion, B., & Caharel, S. (2011). ERP evidence for the speed of face categorization in the

human brain: Disentangling the contribution of low-level visual cues from face

perception. *Vision Research*, *51*(12), 1297–1311.

https://doi.org/10.1016/j.visres.2011.04.003

Rossion, B., & Jacques, C. (2012). The N170: Understanding the time course of face perception

in the human brain. In *The Oxford handbook of event-related potential components* (pp.

115–141). Oxford University Press.

Sagehorn, M., Johnsdorf, M., Kisker, J., Gruber, T., & Schöne, B. (2024). Electrophysiological

correlates of face and object perception: A comparative analysis of 2D laboratory and

virtual reality conditions. *Psychophysiology*, *61*(5), e14519.

https://doi.org/10.1111/psyp.14519

Sagehorn, M., Johnsdorf, M., Kisker, J., Sylvester, S., Gruber, T., & Schöne, B. (2023). Real-life

relevant face perception is not captured by the N170 but reflected in later potentials: A

comparison of 2D and virtual reality stimuli. *Frontiers in Psychology*, *14*.

https://doi.org/10.3389/fpsyg.2023.1050892

Sagehorn, M., Kisker, J., Johnsdorf, M., Gruber, T., & Schöne, B. (2024). A comparative

analysis of face and object perception in 2D laboratory and virtual reality settings:

Insights from induced oscillatory responses. *Experimental Brain Research*.

https://doi.org/10.1007/s00221-024-06935-3

Savran, A., Sankur, B., & Taha Bilge, M. (2012). Comparative evaluation of 3D vs. 2D modality

for automatic detection of facial action units. *Pattern Recognition*, *45*(2), 767–782.

https://doi.org/10.1016/j.patcog.2011.07.022

Schacht, A., & Sommer, W. (2009). Emotions in word and face processing: Early and late

cortical responses. *Brain and Cognition*, *69*(3), 538–550.

https://doi.org/10.1016/j.bandc.2008.11.005

Schindler, S., & Bublatzky, F. (2020). Attention and emotion: An integrative review of emotional

face processing as a function of attention. *Cortex, 130*, 362–386.

https://doi.org/10.1016/j.cortex.2020.06.010

Schubring, D., Kraus, M., Stolz, C., Weiler, N., Keim, D. A., & Schupp, H. (2020). Virtual Reality

Potentiates Emotion and Task Effects of Alpha/Beta Brain Oscillations. *Brain Sciences*,

10(8), Article 8. https://doi.org/10.3390/brainsci10080537

Schupp, H. T., Flaisch, T., Stockburger, J., & Junghöfer, M. (2006). Emotion and attention:

Event-related brain potential studies. In S. Anders, G. Ende, M. Junghofer, J. Kissler, &

D. Wildgruber (Eds.), *Progress in Brain Research* (Vol. 156, pp. 31–51). Elsevier.

https://doi.org/10.1016/S0079-6123(06)56002-9

Schurgin, M. W., Nelson, J., Iida, S., Ohira, H., Chiao, J. Y., & Franconeri, S. L. (2014). Eye

movements during emotion recognition in faces. *Journal of Vision*, *14*(13), 14.

https://doi.org/10.1167/14.13.14

Seabold, S., & Perktold, J. (2010). statsmodels: Econometric and statistical modeling with

python. *9th Python in Science Conference*.

Smith, F. W., & Smith, M. L. (2019). Decoding the dynamic representation of facial expressions

of emotion in explicit and incidental tasks. *NeuroImage*, *195*, 261–271.

https://doi.org/10.1016/j.neuroimage.2019.03.065

Stein, N., Niehorster, D. C., Watson, T., Steinicke, F., Rifai, K., Wahl, S., & Lappe, M. (2021). A

Comparison of Eye Tracking Latencies Among Several Commercial Head-Mounted

Displays. *I-Perception*, *12*(1), 2041669520983338.

https://doi.org/10.1177/2041669520983338

Steyvers, M. (1999). Morphing techniques for manipulating face images. *Behavior Research Methods, Instruments, & Computers*, *31*(2), 359–369. https://doi.org/10.3758/BF03207733

Tarr, M. J., & Warren, W. H. (2002). Virtual reality in behavioral neuroscience and beyond. *Nature Neuroscience*, *5*(11), 1089–1092. https://doi.org/10.1038/nn948

Tauscher, J.-P., Schottky, F. W., Grogorick, S., Bittner, P. M., Mustafa, M., & Magnor, M. (2019). Immersive EEG: Evaluating Electroencephalography in Virtual Reality. *2019 IEEE Conference on Virtual Reality and 3D User Interfaces (VR)*, 1794–1800. https://doi.org/10.1109/VR.2019.8797858

Thurley, K. (2022). Naturalistic neuroscience and virtual reality. *Frontiers in Systems Neuroscience*, *16*. https://doi.org/10.3389/fnsys.2022.896251

Vaidya, A. R., Jin, C., & Fellows, L. K. (2014). Eye spy: The predictive value of fixation patterns in detecting subtle and extreme emotions from faces. *Cognition*, *133*(2), 443–456. https://doi.org/10.1016/j.cognition.2014.07.004

Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D., Burovski, E., Peterson, P., Weckesser, W., Bright, J., Van Der Walt, S. J., Brett, M., Wilson, J., Millman, K. J., Mayorov, N., Nelson, A. R. J., Jones, E., Kern, R., Larson, E., … Vázquez-Baeza, Y. (2020). SciPy 1.0: Fundamental algorithms for scientific computing in Python. *Nature Methods*, *17*(3), 261–272. https://doi.org/10.1038/s41592-019-0686-2

Vishwanath, D. (2014). Toward a new theory of stereopsis. *Psychological Review*, *121*(2), 151–178. https://doi.org/10.1037/a0035233

Vishwanath, D., & Hibbard, P. B. (2013). Seeing in 3-D With Just One Eye. *Psychological Science*. https://doi.org/10.1177/0956797613477867

Wade-Bohleber, L. M., Thoma, R., & Gerber, A. J. (2020). Neural correlates of subjective

arousal and valence in health and panic disorder. *Psychiatry Research: Neuroimaging*,

305, 111186. https://doi.org/10.1016/j.pscychresns.2020.111186

Wang, L., Chen, W., & Li, H. (2017). Use of 3D faces facilitates facial expression recognition in

children. *Scientific Reports*, *7*(1), Article 1. https://doi.org/10.1038/srep45464

Weber, D., Hertweck, S., Alwanni, H., Fiederer, L. D. J., Wang, X., Unruh, F., Fischbach, M.,

Latoschik, M. E., & Ball, T. (2021). A Structured Approach to Test the Signal Quality of

Electroencephalography Measurements During Use of Head-Mounted Displays for

Virtual Reality Applications. *Frontiers in Neuroscience*, *15*, 733673.

https://doi.org/10.3389/fnins.2021.733673

Welchman, A. E. (2016). The Human Brain in Depth: How We See in 3D. *Annual Review of*

Vision Science, *2*(Volume 2, 2016), 345–376. https://doi.org/10.1146/annurev-vision-

111815-114605

Willis, J., & Todorov, A. (2006). First Impressions: Making Up Your Mind After a 100-Ms

Exposure to a Face. *Psychological Science*, *17*(7), 592–598.

https://doi.org/10.1111/j.1467-9280.2006.01750.x

Wilson, H., Chen ,Xi, Golbabaee ,Mohammad, Proulx ,Michael J., & and O'Neill, E. (2024).

Feasibility of decoding visual information from EEG. *Brain-Computer Interfaces*, *11*(1–2),

33–60. https://doi.org/10.1080/2326263X.2023.2287719

1285