rbio1 - training scientific reasoning LLMs with biological world models as soft verifiers

Ana-Maria Istrate* [iD], Fausto Milletari [iD], Fabrizio Castrotorres [iD],
Jakub M. Tomczak [iD], Michaela Torkar [iD], Donghui Li [iD], and Theofanis Karaletsos* [iD]

Chan Zuckerberg Initiative, Redwood City, CA

*Corresponding authors: A.I. (aistrate@chanzuckerberg.com), T.K. (tkaraletsos@chanzuckerberg.com)

Abstract

Reasoning models are typically trained against verification mechanisms in formally specified systems such as code or symbolic math. In open domains like biology, however, we lack exact rules to enable large-scale formal verification and instead often rely on lab experiments to test predictions. Such experiments are slow, costly, and cannot scale with computation. In this work, we show that world models of biology or other prior knowledge can serve as approximate oracles for *soft verification*, allowing reasoning systems to be trained without additional experimental data. We present two paradigms of training models with approximate verifiers: **RLEMF**: reinforcement learning with experimental model feedback and **RLPK**: reinforcement learning from prior knowledge. Using these paradigms, we introduce **rbio1**, a reasoning model for biology post-trained from a pretrained LLM with reinforcement learning, using learned biological models for verification during training. We demonstrate that soft verification can distill biological world models into **rbio1**, enabling it to achieve state-of-the-art performance on perturbation prediction in the PerturbQA benchmark. We further show that composing multiple AI-verifiers improves performance and that models trained with soft biological rewards transfer zero-shot to cross-domain tasks such as disease-state prediction. We present **rbio1** as a proof of concept that predictions from biological models can train powerful reasoning systems using simulations rather than experimental data, offering a new paradigm for model training.

1 Introduction

Building foundation models suitable for scientific tasks is a task of major interest and has produced numerous successful examples in recent memory [1–3]. Similarly, large language models (LLMs) have shown groundbreaking potential as parametric representations of the world's knowledge, and have been used across every sector. A key challenge is figuring out how to bridge the quantitative accuracy of models of experimental scientific data, for example in biology, with LLMs such that knowledge from these low-level representations of biological systems may be transferred into more flexible and interactive models, such as conversational LLMs, with the explicit goal of being useful for scientific exploration.

Of great promise on scientific tasks are reasoning models, which aim to extend LLMs toward systems that can perform structured, multi-step inference and use test-time compute to generalize better to a given query. Popular reasoning models like DeepSeek-R1 [4] and QWEN [5] have shown potential in multiple fields, while specialized reasoning LLMs have been explored in fields such as medicine [6, 7] and chemistry [8]. In frameworks such as reinforcement learning with human feedback (RLHF) [9, 10], and reinforcement learning with verifiable rewards (RLVR) [11], both experimental data collection with human labels and exact oracles of rewards are used to train language models to align to a reward structure and improve their reasoning capabilities. In domains that are not formally specified like biology, however, experimental data and ground-truth verifiers are scarce: while mathematics and code benefit from exact execution and have symbolically accessible oracles, experiments are costly and slow. Consider training a language model to answer biological queries like '*Will knocking down gene AARS in liver cells affect the expression of gene ATAD2B?*' In traditional RL domains, we could automatically verify thousands of such predictions, but in biology, each verification requires a costly laboratory experiment, making it impossible to generate the millions of training signals needed for effective learning. This motivates exploring alternative supervision strategies for reasoning for such domains.

*Corresponding authors: Ana-Maria Istrate, aistrate@chanzuckerberg.com; Theofanis Karaletsos, tkaraletsos@chanzuckerberg.com

To overcome these limitations and further advance the utility of reasoning models for scientific tasks in biology, we propose employing models of biological data to run virtual experiments which can be used as sources of probabilistic -or soft- verification signal. This can be seen as a form of reinforcement learning from AI feedback (RLAIF) [12] with structural adjustments to map to our scientific setting, where RLHF and RLVR are not tractable. We consider those *soft verifiers*, since they return probabilistic rewards which measure the coherence of a biology-model or of biological prior knowledge to a reasoning trace and its returned answer. Much like with RLVR, we can use this *soft verification* paradigm to generate a broad distribution of verified data limited only by how we can query the biology model at hand. We thus turn a (world) model of biology into a reasoning environment to generate rewards to train reasoning models.

Our work also connects with the concept of virtual cell models (VCMs) [13–15], which envisions building powerful predictive systems of biology that can simulate transitions such as diseased → healthy states. Advances in compute and large-scale data have enabled construction of such foundation models in specific modalities-transcriptomics [16–20], imaging [21], proteomics [1, 3], genomics [22], and multimodal models [23–28].

Our approach can be seen as using and aligning such world models of biology into a common representation using language as the bridge. This approach not only aggregates knowledge but also makes it accessible through natural language, allowing experimentalists to interact conversationally with biological models. By distilling biological knowledge into LLMs, we transform experimental insights into human-readable reasoning models. Our motivations are threefold: (i) enable training from biological simulations rather than costly experimental data, (ii) integrate diverse models of biology into a single platform, (iii) democratize access to biological knowledge through dialogue.

Contributions.   Our work contributes to the design of supervision strategies for reasoning LLMs for scientific use, using biological perturbation prediction -e.g., predicting effects of gene knockdowns on differential expression, as a case study:

(1) We propose two new processes for training models with AI-verifiers: **RLEMF**: reinforcement learning with experimental model feedback and **RLPK**: reinforcement learning from prior knowledge - that reward with predictive models, and prior knowledge, respectively.

(2) RLEMF-trained models generalize out-of-distribution (OOD) and compete with ablation-models trained on experimental data, achieving new state-of-the-art results on the PerturbQA benchmark

(3) We show that mixtures of AI-verifiers can be combined to compose stronger models while drawing from different sources of biological knowledge, even when supervision is off-task.

(4) We show that inference-time chain-of-thought prompting [29] further improves reasoning performance, allowing **rbio1** to reach state of the art on the PerturbQA benchmark without tool use or experimental data at inference, even at a fraction of training data.

(5) We show that models trained with biological soft verifiers transfer zero-shot to cross-domain biological tasks, including disease-state prediction, and that their performance gains are robust to verifier noise, confidence variation, and reward design.

(6) We show that domain-specific post-training with biological soft verifiers enables **rbio1** to outperform general-purpose reasoning and instruction-tuned LLMs with up to 40× more parameters on PerturbQA.

In summary, **rbio1** extends standard RL training for reasoning models by incorporating AI-based verification through both predictive biological models of experimental data and curated knowledge sources and provides a general framework of using model simulations to train reasoning models. Code implementing the core training methodology is available at `https://github.com/czi-ai/rbio`. This release focuses on the essential components for reproducibility and community adoption.

2   Related Work

Recent reasoning-oriented LLMs-such as OpenAI's o-series, Claude 3.7/4, Gemini 2.5, and DeepSeek-R1-exhibit strong multi-step inference and logical deduction across domains. Their development spans four paradigms: (i) inference-time scaling (e.g., chain-of-thought, self-consistency), e.g., see [30]; (ii) pure RL approaches like DeepSeek-R1-Zero, where traces emerge from accuracy- and format-based rewards; (iii) hybrid supervised finetuning plus RL, as in DeepSeek-R1; and (iv) distillation into smaller backbones such as Qwen [5] or Llama [4, 31]. Despite

FIGURE 1. **rbio1 overview.** (a) Distilling VCMs into reasoning LLMs via soft verification. (b) GRPO loop with Virtual Cell Models (VCM) rewards (shown as double helix). (c) Soft vs. hard supervision.

advances, persistent challenges remain in hallucination, logical consistency, verbosity, and interpretability-issues directly tied to the quality of the rewards.

Domain-specific reasoning has also been explored. BioReason [6] combines a genomic encoder with an LLM for disease-pathway inference with interpretable steps, while CellReasoner [7] frames cell-type annotation explicitly as a reasoning task. Both approaches, however, depend heavily on curated datasets, limiting robustness to noisy or rare populations and motivating richer, more scalable reasoning signals. Our approach differs by using machine learning models of biology directly as reward-generating verifiers. Prior methods integrated external models (e.g., embeddings) into reasoning traces but still evaluated against annotated data. We instead shape rewards themselves with model predictions, showing that biological world models can be distilled into reasoning LLMs -positioning our work within the broader space using AI-rewards.

Wu et al. [32] propose SUMMER, an inference-time pipeline combining knowledge-graph summaries, retrieval, and chain-of-thought prompting for perturbation prediction. While it outperforms prior methods on PerturbQA, gains are modest, causal directionality remains error-prone, and large models are required even for preprocessing. Unlike SUMMER, our models achieve comparable or better results without experimental data, relying solely on model predictions.

Our work also connects to concurrent research on soft- and AI- verification. In RLAIF [12] and follow-up work, other LLMs are used as reward mechanisms. Our approach RLEMF - as described in Sec 3.3 differs by not requiring an LLM or any text model as an AI-feedback model, and uses models in a different data space of experimental data linked by appropriate prompting techniques and embeddings. Our idea thus builds a bridge between models of experimental data yielding AI-feedback, and the reasoning LLMs learning from that feedback to generate more accurate textual descriptions of valid scientific knowledge. However, we share the approach the model is used to

TABLE 1. Verifiers used during RL training. EXP = experimental data; MLP = multilayer perceptron; GO = Gene Ontology.

Verifier	Type	Reward Signal	Source
EXP	Hard	Binary $r_i^{hard} \in \{0,1\}$	Experimental data
MLP	Soft	Probability $r_i^{soft} = p,\ 0 \leq p \leq 1$	Simulations
GO	Soft	ROUGE, keyword, likelihood	Knowledge base

provide a probabilistic verifiable reward. Saad-Falcon et al. [33] also use LLMs as soft verifiers for other LLMs and combine verifiers. In contrast, we generalize beyond LLMs to arbitrary biological models and combine multiple verifiers as separate reward functions. In a framework closest to our approach RLPK 3.4, Yu et al. [34] use LLMs to use the reasoning LLM itself to score answers as rewards. In RLPK we do not use answers, but structured databases of prior scientific knowledge. To our knowledge, we are the first to apply this paradigm to reasoning models for biology, shifting the training signal from experimental data to simulations and broadening the design space of verifiers for reasoning LLMs.

3 rbio1: Methods

In standard domains, during RL training, verifiers return precise signals-for example, whether code executes or a math solution is correct. In biology, some queries can be validated experimentally (hard verification), but exhaustive lab testing is infeasible due to scale. Consider a biological query related to genetic perturbation, such as: *Is a knockdown of AARS in hepg2 cells likely to result in differential expression of ATAD2B?* with a binary answer: yes/no. During training, the LLM produces completions o_i for query q. Rewards can be assigned in three ways that we introduce in the following sections and also showcase in Fig. 1. Table 1 summarizes these verifiers and reward formulations. We follow the PerturbQA benchmark protocol [32], evaluating CRISPRi single-gene perturbation prediction across four cell lines (RPE1, K562, HEPG2, JURKAT); cell lines share 40–75% of perturbed genes, ensuring out-of-distribution generalization rather than within-cell-line interpolation. A more detailed description of the biological setup is provided in **Appendix A.1**. We report F1, Balanced Accuracy, and MCC as the most biologically meaningful metrics, since identifying true positive perturbations is more critical than avoiding false positives **Appendix A.2**.

3.1 Reinforcement Learning for reasoning

Let $P(Q)$ denote a dataset used for training; q a query sampled from $P(Q)$, G a set of outputs generated during training by the reasoning LLM π_θ in response to input queries; o_i a generated sequence of tokens with tokens $o_{i,t}$ in response to q; π_{ref} a reference base model from the supervised finetuned LLM; r_ϕ a reward model emitting rewards r_i; $L_{GRPO}(\theta)$ the surrogate objective and β the coefficient for the KL penalty. Given these variables, Group Relative Policy Optimization (GRPO) [35, 36] training maximizes the following objective function, with the goal of increasing the accumulated collective rewards $\{r_{i,\geq t}\}$:

$$J_{GRPO} = \mathbb{E}_{q \sim P(Q), \{o_i\}_{i=1}^G \sim \pi_{\theta_{old}}} \left[L_{GRPO}(\theta) \right]. \tag{1}$$

We use the clipped surrogate objective:

$$L_{GRPO}(\theta) = \frac{1}{|G|} \sum_{i=1}^{G} \frac{1}{|o_i|} \sum_{t=1}^{|o_i|} \min\left(\frac{\pi_\theta(o_{i,t}|q,o_{i<t})}{\pi_{\theta_{old}}(o_{i,t}|q,o_{i<t})} \hat{A}_{i,t},\ g(\epsilon, \hat{A}_{i,t}) \right) - \beta D_{KL}[\pi_\theta || \pi_{\text{ref}}] \tag{2}$$

$$g(\epsilon, \hat{A}_{i,t}) = \text{clip}\left(\frac{\pi_\theta(o_{i,t}|q,o_{i<t})}{\pi_{\theta_{old}}(o_{i,t}|q,o_{i<t})},\ 1-\epsilon,\ 1+\epsilon \right) \hat{A}_{i,t} \tag{3}$$

$$\hat{A}_{i,t} = \frac{r_i - \text{mean}(\{r_1,...,r_G\})}{\text{std}(\{r_1,...,r_G\})} \tag{4}$$

$$D_{KL}[\pi_\theta || \pi_{\text{ref}}] = \frac{\pi_{\text{ref}}(o_{i,t}|q,o_{i<t})}{\pi_\theta(o_{i,t}|q,o_{i<t})} - \log \frac{\pi_{\text{ref}}(o_{i,t}|q,o_{i<t})}{\pi_\theta(o_{i,t}|q,o_{i<t})} - 1. \tag{5}$$

3.2 RBIO-EXP: Reinforcement Learning with Hard Verification

In this setting, verification relies on experimentally validated observations that provide binary outcomes. Let $D_{\exp}$ denote the collection of experimental results containing pairs (q, y^*), where each query q (e.g., a perturbation experiment) has a corresponding ground-truth label $y^* \in \{0, 1\}$.

We define a *verifier function*

$$V_{\exp}(q, o_i; D_{\exp}) : (q, o_i) \mapsto \{0, 1\}, \tag{6}$$

which returns 1 when the model output o_i matches the experimentally validated outcome for q, and 0 otherwise:

$$V_{\exp}(q, o_i; D_{\exp}) = \begin{cases} 1, & o_i = y^*(q) \text{ and } (q, y^*(q)) \in D_{\exp}, \\ 0, & \text{otherwise.} \end{cases} \tag{7}$$

The reward assigned to completion o_i is then defined as

$$r_i^{\text{hard}}(q, o_i; D_{\exp}) = V_{\exp}(q, o_i; D_{\exp}). \tag{8}$$

Here, $D_{\exp}$ is not itself the verifier but rather the data source queried by the deterministic verification function $V_{\exp}$. A description of the RBIO-EXP algorithm is provided in **Appendix Alg- 1**.

3.3 RBIO-RLEMF: Reinforcement Learning with Experimental Model Feedback

In many cases, exhaustive experimental datasets $D_{\exp}$ are not available for all biological queries, or are expensive or even impossible to generate. To extend reward coverage across more scientific breadth, we use predictive models of experimental data as *surrogate verifiers*, and denote the process as experimental model feedback. These models -for example, neural predictors of perturbation effects-provide *soft*, probabilistic rewards rather than binary outcomes. More generally, this approach is akin to RLAIF, with the key difference that RLEMF utilizes arbitrary other (non-LLM) models as feedback mechanisms for a query, in our example world models of biology defined on experimental data.

Let $\mathcal{M}$ denote a biological model that can be queried with a prompt q and contextual information c_j (e.g., the cell line or other covariates), producing a scalar prediction $\hat{p} = p(c_j | q; \mathcal{M})$ that reflects the likelihood of the queried biological effect being true.

We define a corresponding *verifier function*

$$V_{\text{EMF}}(q, o_i; \mathcal{M}, c_j) : (q, o_i) \mapsto [0, 1], \tag{9}$$

which emits a soft reward based on the model's predicted probability:

$$V_{\text{EMF}}(q, o_i; \mathcal{M}, c_j) = \mathcal{M}(q; c_j), \tag{10}$$

where higher values indicate stronger agreement between the model prediction and the reasoning output o_i. For instance, when $\mathcal{M}$ is a multilayer perceptron (MLP) trained on perturbation outcomes, $V_{\text{EMF}}(q, o_i; \mathcal{M}, c_j)$ corresponds to the model's predicted probability that the statement in q is true for context c_j. Within this framework one can also utilize other metrics like log-likelihoods appropriately normalized given a collection of data to be between 0 and 1 cast as rewards representing the belief of the model in the simulated data. The reinforcement learning reward is then defined as:

$$r_i^{\text{soft}}(q, o_i) = \mathcal{M}(q, c_j), \tag{11}$$

which generalizes the hard verification in Eq. 8 to a continuous reward signal in $[0, 1]$.

This approach allows reasoning models to be trained against *world models of biology* that approximate experimental verification, effectively replacing slow or expensive wet-lab experiments with computational feedback. The verifier V_{EMF} is therefore a deterministic function parameterized by the predictive model $\mathcal{M}$, not a probabilistic conditional, ensuring conceptual consistency with the formulation in Sec. 7. A description of the RBIO-RLEMF algorithm is provided in **Appendix Alg- 2**.

3.4 RBIO-RLPK: Reinforcement Learning from Prior Knowledge

In addition to experimental or model-based verification, reasoning models can also be guided by structured scientific knowledge. Here, we propose prior knowledge feedback (**RLPK**), where prior knowledge sources are

used to verify the semantic consistency of a model's output with curated facts rather than empirical measurements. Let K_S denote a structured knowledge source (e.g., the Gene Ontology) containing a set of prior facts or annotations relevant to a query q which take the shape of text or other sequences. Given an output o_i produced by the reasoning model, we define a corresponding *verifier function* $V_{\mathrm{PK}}(q, o_i; K_S) : (q, o_i) \mapsto \mathbb{R}$, which emits a scalar reward r_i^{soft} reflecting the agreement between o_i and relevant knowledge retrieved from K_S.

Knowledge retrieval. For each query q, we obtain a collection of knowledge statements $\mathcal{Q}_{\mathrm{prior}}(q) = \{ q_j^{\mathrm{prior}} \}_{j=1}^J$ by querying K_S for entries semantically related to q (e.g., gene annotations or biological process descriptions). Each q_j^{prior} has a sequence length T_j and thus consists of a list of tokens $\mathbf{y}_j = \{y_{j,1}, ... y_{j,T_j}\}$.

Scoring metrics. The verifier V_{PK} computes rewards using one or more of the following metrics:

(1) **ROUGE-based score:** We request the model to expose the relevant gene facts inside `<gene_info>` tags—which we refer to as o_i^{relevant}—and compute standard ROUGE-1/2/L F-scores between q_j^{prior} and the extracted o_i^{relevant}:

$$V_{\mathrm{PK}}^{(\mathrm{ROUGE})}(q, o_i; K_S) = \sum_{j=1}^J \sum_{X \in \{1,2,L\}} \mathrm{ROUGE-X}(q_j^{\mathrm{prior}}, o_i^{\mathrm{relevant}}),$$

where o_i^{relevant} denotes the portion of the reasoning trace encapsulated in `<gene_info>` tags.

(2) **Keyword-overlap score:**

$$V_{\mathrm{PK}}^{(\mathrm{KWS})}(q, o_i; K_S) = \sum_{j=1}^J \frac{|\, \mathrm{KW}(q_j^{\mathrm{prior}}) \cap \mathrm{KW}(o_i^{\mathrm{relevant}}) \,|}{|\, \mathrm{KW}(q_j^{\mathrm{prior}}) \,|},$$

where $\mathrm{KW}(\cdot)$ extracts normalized keyword sets from each string.

(3) **Likelihood-based score:** For likelihood-based verifiers, we encourage the model to assign higher likelihood to prior knowledge $\{q_j^{\mathrm{prior}}\}$ under our learned policy π_θ given the model's reasoning emissions. To account for variability in sequence length T_j, we average over the sequence tokens y_k in q_j^{prior} and define:

$$V_{\mathrm{PK}}^{(\mathrm{LL})}(q, o_i; K_S) = \sum_{j=1}^J \frac{1}{T_j} \sum_{k=1}^{T_j} \log p_{\pi_\theta}(y_{j,k} \mid y_{j,<k}, o_i, q), \tag{12}$$

which measures how likely each prior-knowledge sequence q_j^{prior} is under the current policy π_θ.

Reward normalization. Because raw scores vary widely across metrics, each reward is normalized via an exponential moving average (EMA) before computing GRPO advantages:

$$\tilde{r} \leftarrow (1 - \alpha)\tilde{r} + \alpha r_m, \quad \tilde{v} \leftarrow (1 - \alpha)\tilde{v} + \alpha(r_m - \tilde{r})^2, \quad \bar{r} = 0.5 + \frac{1}{2z_{\max}} \mathrm{clip}\left(\frac{r_m - \tilde{r}}{\sqrt{\tilde{v} + \varepsilon}}, -z_{\max}, z_{\max} \right),$$

where $\bar{r}$ is the normalized reward used for token-level advantages (Eq. 4).

Summary. The final reward for RBIO-RLPK is

$$r_i^{\mathrm{soft}}(q, o_i) = V_{\mathrm{PK}}(q, o_i; K_S),$$

where V_{PK} may be a weighted combination of the metrics above. This keeps consistency with earlier sections: the verifier is a deterministic mapping parameterized by the knowledge source K_S, not a probabilistic conditional (see **Appendix Alg. 3**).

3.5 Composable Verification for Model Integration

All **rbio** models use formatting (r_{format}) and mention (r_{mention}) rewards (e.g., gene mentions). When training with multiple verifiers (Sec. 4.2), each prompt q is verified by a specific function V_s. With verifier functions V_k emitting

rewards $r_{i,k}$:

$$r_i(q, o_i) = r_{\text{format}} + r_{\text{mention}} + \sum_k \delta_{ks} \lambda_k \, r_{i,k}^{hard/soft}(q, o_i), \qquad \lambda_k \geq 0. \tag{13}$$

Unless stated otherwise, $\lambda_k = 2$, giving soft-verifier rewards higher variance weighting than r_{format} and r_{mention} in GRPO updates. Full training configurations and evaluation protocols are provided in Appendix A.10, with data and code availability described in Appendix A.11.

4 Results

4.1 rbio with AI-verification generalizes OOD on perturbation tasks

FIGURE 2. **Model performance for experimental vs. simulation-based soft verification. (a)** rbio-EXP-one-cell-line: trained and tested on the same cell line (in-distribution). **(b)** rbio-EXP-leave-one-out: trained on three cell lines, tested on the held-out one (out-of-distribution). **(c)** rbio-MLP-leave-one-out: trained using MLP predictions on the held-out line (MLP fit on the others). **(d)** Aggregate metrics: computed over four cell lines (K562, RPE1, JURKAT, HEPG2), averaged across 5 runs. SEM computation described in **Appendix A.2**. **(e)** Metrics split by cell line. Baselines: *SUMMER* (experimental + domain knowledge), *GEARS* (specialized perturbation model), *Qwen2.5-3b* (base reasoning model).

As shown in Fig. 2, on PerturbQA [32] (CRISPRi knockdowns in RPE1, K562, HEPG2, JURKAT), models trained with *soft verifiers* generalize to held-out cell lines, reducing reliance on cell-line–specific experimental data. We

first evaluate a 2-layer MLP (64 hidden units) trained on three cell lines and use it to generate predictions on the fourth, which serve as rewards during RL. Gene representations include one-hot and Gene2Vec [37]. The resulting models, *rbio-MLP-leave-one-out-one-hot* and *rbio-MLP-leave-one-out-gene2vec*, perform comparably to experimental-data–trained **rbio1** models. The MLP architecture and training details are provided in **Appendix A.6**. Sec. 4.7 directly compares the MLP verifiers with the *rbio-MLP-leave-one-out-X* for X ∈ {one-hot, gene2vec} variations. While the MLP provides calibrated biological supervision, **rbio1** consistently exceeds its performance across all metrics, demonstrating that GRPO-based reinforcement learning refines and extends the verifier's signal rather than merely imitating it.

We compare to two experimental-data baselines: *rbio-EXP-one-cell-line* (train/test within a cell line; Fig. 2a) and *rbio-EXP-leave-one-out* (train on three cell lines; test on the fourth; Fig. 2b). We also benchmark against SUMMER [32]. As shown in Fig. 2d–e, the soft-verifier models closely match experimental-data models on F1 and MCC, and exceed them in Balanced Accuracy via higher TPR while maintaining similar TNR. Identifying true effects is paramount in perturbation, so higher TPR is valuable even with some F1 trade-off. All **rbio1** variants also outperform GEARS [38], a state-of-the-art model for perturbation prediction and the base Qwen2.5-3B.

In Sec. 4.6 and Appendix A.4, A.4.2, and A.4.3, we present detailed analyses of the robustness of **rbio1** models to verifier fidelity and signal miscalibration, as well as the effect of different reward components. Our results show that **rbio1** models capture genuine biological signal—remaining robust to verifier noise and miscalibration, leveraging but not depending on soft verifier confidence. Beyond perturbation OOD generalization—where shifts reflect cell-line–specific transcriptional programs—we further evaluated **rbio1** on zero-shot transcriptomic cell-state prediction: Alzheimer's disease (2 classes) and myeloid cancers (7 classes). Trained solely on perturbation reasoning with biological soft-verifier rewards, **rbio1** substantially outperforms the base Qwen model on both datasets (+94% F1, +136% Recall for Alzheimer; +36% F1, +68% Recall for Cancer), approaching the performance of SCVI [39]—a model trained on full raw-count matrices—despite using only natural-language inputs over the top-100 expressed genes and metadata. This shows that reinforcement learning with biological verifiers yields transferable representations of cellular state that generalize from causal perturbation dynamics to disease-level transcriptional inference. Full analyses appear in **Sec 4.4**.

4.2 Training rbio1 on mixtures of AI-verifiers leads to performance gains

FIGURE 3. **Model performance for compositions of verifiers** $V_i \| V_j$ corresponds to training models sequentially, first on V_i, then on V_j. $V_i \cup V_j$ corresponds to models trained on a random mixture of $\{V_i, V_j\}$; **(a, b)** *MLP* and *EXP*, trained for 1, and 2 epochs. **(c)** *EXP* and GO_{all-ll} **(d)** *MLP* and GO_{all-ll}

We find that combining verifiers improves performance over using them individually. Notably, the order in which models see the verifiers matters, reflecting differences in the knowledge provided. For a pair of verifiers V_i, V_j, we evaluate:

(1) V_i: trained only with V_i , $i \in \{1, 2\}$
(2) $V_i \| V_j$: trained sequentially, V_i, then V_j
(3) $V_i \cup V_j$: trained on a random mixture of V_i and V_j

We experiment with the following combinations of verifiers: (1) $V_1 =$ EXP (hard verifier; experimental data) and $V_2 =$ MLP (soft verifier; MLP predictions); (2) $V_1 =$ EXP and $V_2 = GO_{all-ll}$ (soft verifier; GO Ontology likelihood reward); (3) $V_1 =$ MLP and $V_2 = GO_{all-ll}$. Note that the training data for each of V_1, V_2 is independent of each other - i.e. if V_1 is a verifier of experimental data from a dataset D_1, emissions from V_2 will be on an independent dataset D_2 where $D_1 \cap D_2 = \varnothing$. In the case of the GO_{all-ll} the soft verification is the likelihood of the prior knowledge $\{q_j^{prior}\}$ we have under our learned policy π_θ as described in Eq. 12.

As shown in Fig. 3, adding verifiers consistently improves performance over using them individually. For $V_1 =$ EXP and $V_2 =$ MLP (Fig. 3a,b), all three composition strategies (Sec. 4.2) perform similarly, yet each surpasses the single verifiers, underscoring the complementary value of strong verification sources such as experimental data and models of experimental data. When combining knowledge and experimental verifiers, training order is critical. In Fig. 3c,d, models trained with GO_{all-ll} first and then MLP, EXP ($GO_{all-ll}\|MLP, GO_{all-ll}\|EXP$) outperform the reverse. GO-based supervision increases TPR (captures more positives) but lowers TNR; subsequent MLP/EXP training restores TNR, improving Balanced Accuracy and MCC. Starting from MLP or EXP and adding GO_{all-ll} later reduces performance, showing that knowledge signals can dilute experimental ones if applied too late. Thus, GO rewards are most useful early for broad guidance, while high-fidelity verifiers refine later. Cross-verifier agreement (**Appendix A.5; SI Figs. SI-3–SI-5**) shows EXP and MLP are strongly aligned ($r = 0.81$–0.85, binary 0.92–0.94). Overall, the results reveal a hierarchy: GO early aids recall, ending with a high-fidelity verifier (GO→MLP/EXP) yields robust signals, while the reverse (MLP/EXP→GO) introduces noise. Later verifiers denoise earlier rewards, indicating effects stem from signal quality rather than reward scaling. This follows a standard training principle—start broad and noisy (ontologies), then refine with higher-quality experimental supervision—and naturally generalizes to multiple verifiers $V_1, V_2, \dots, V_k$.

4.3 Rbio with chain-of-thought yields state of the art on PerturbQA

FIGURE 4. **Effect of chain-of-thought prompting.** Models using CoT achieve state-of-the-art performance on the PerturbQA benchmark.

Adding chain-of-thought (CoT) reasoning at inference improves all **rbio1** variants we tested (Table 2), surpassing SUMMER as state-of-art performance on the PerturbQA benchmark. The CoT prompt that performed the best was: *'The Biologist will evaluate each step of this problem, using logical reasoning and evidence from the prompt."* Examples of performance increase: *rbio-EXP-all-cell-lines* F1 0.75→0.79, Balanced Accuracy 0.88→0.91, TPR 0.83→0.87; *rbio-MLP-ESM* F1 0.67→0.71, Balanced Accuracy 0.85→0.89, TPR 0.81→0.87. We offer examples of answers and reasoning traces generated by the **rbio1** models on a perturbation question in Figure SI-1 in Supplementary

material. Shown in Figure 4 are **rbio1** models trained on only one-fifth of the data and tested with and without CoT. Remarkably, adding CoT at inference lets them reach state-of-the-art performance on PerturbQA - with *rbio-MLP ∪ EXP-CoT* surpassing SUMMER despite being trained on a fraction of training data - demonstrating the power of inference-time capabilities and verifier composition in reasoning models. Note that here SUMMER's higher TNR reflects a stricter precision–recall trade-off rather than overall superior performance.

4.4 Rbio generalizes zero-shot to Alzheimer's and cancer disease prediction

FIGURE 5. | **Zero-shot disease prediction performance on Alzheimer and Cancer datasets using rbio1 models trained with models of perturbation data.** Models are trained on a fraction of the available data (top-100 highly expressed genes + metadata). We compare baseline Qwen2.5-3B, SCVI, and **rbio1** variants using various verifiers: rbio-EXP, rbio-MLP, rbio-MLP∪EXP and rbio-MLP∪EXP∪GO. Chain-of-thought was solicited at inference time. Across both datasets, **rbio1** substantially improves recall and F1 over the Qwen2.5-3b baseline and approaches SCVI despite using only a data fraction, highlighting that soft-verifier RL generalizes beyond perturbation prediction to a distinct disease-classification task.

To assess whether perturbation-trained reasoning models generalize beyond their training domain, we evaluate **rbio1** on two disease-state classification tasks that are *completely zero-shot and out-of-distribution*: Alzheimer's disease (binary classification: normal vs. diseased) and myeloid cancers (multi-class classification with seven cancer types plus a normal state), constructed from public CELLxGENE single-cell datasets. Importantly, **rbio1** is trained *only* on perturbation-prediction tasks from PerturbQA using biological soft-verifier rewards and receives *no* disease-specific supervision, fine-tuning, or examples. Each cell is represented as a natural-language prompt describing its experimental metadata together with the *top 100 expressed genes*, and the model is asked to infer the disease state directly from this description.

Despite the complete domain shift—from causal perturbation reasoning to disease-state classification—**rbio1** substantially outperforms the base Qwen model, achieving a +136% increase in recall and roughly doubling F1 score on Alzheimer's disease, and improving F1 by 30–70% on myeloid cancers while maintaining high specificity. Remarkably, this fully zero-shot performance approaches that of SCVI, a specialized expression model trained directly on raw count matrices. Further details on dataset construction, prompt formulation, evaluation protocol, and qualitative examples are provided in **Appendix. A.7**.

4.5 Rbio outperforms LLMs with up to 40× more parameters on PerturbQA

Despite having only 3 billion parameters, **rbio1** models substantially outperform both reasoning-oriented and instruction-tuned LLMs that are an order of magnitude larger (Table 2). Zero-shot baselines—including DeepSeek R1 distilled models (32B–70B parameters), Qwen2.5 Instruct (3B–72B), and OpenAI o1-series models (20B–120B)—achieve F1 scores between 0.24 and 0.30 and MCC scores below 0.16. In contrast, *rbio*-EXP-CoT reaches F1 = 0.786 and MCC = 0.752, while *rbio*-MLP ∪ EXP-CoT trained on only 1/15 of the data achieves F1 = 0.716 and MCC = 0.668. This demonstrates that domain-specific post-training with soft verification enables smaller models to acquire biological reasoning capabilities that general-purpose LLMs fail to exhibit through pre-training and instruction-tuning alone.

Model	F1-score	Balanced Accuracy	TPR	TNR	MCC
Models trained on full data size					
rbio-EXP	0.750 ± 0.018	0.883 ± 0.011	0.827 ± 0.018	0.939 ± 0.003	0.709 ± 0.020
rbio-EXP-CoT	$\mathbf{0.786 \pm 0.000}$	$\mathbf{0.907 \pm 0.000}$	$\mathbf{0.872 \pm 0.000}$	0.943 ± 0.000	$\mathbf{0.752 \pm 0.000}$
rbio-MLP	0.669 ± 0.025	0.855 ± 0.017	0.807 ± 0.030	0.902 ± 0.004	0.618 ± 0.029
rbio-MLP-CoT	0.714 ± 0.000	0.889 ± 0.000	0.873 ± 0.000	0.906 ± 0.000	0.672 ± 0.000
SUMMER	0.695 ± 0.012	0.799 ± 0.006	0.626 ± 0.012	$\mathbf{0.972 \pm 0.002}$	0.657 ± 0.013
Qwen2.5-3b	0.231 ± 0.002	0.522 ± 0.001	0.529 ± 0.014	0.515 ± 0.013	0.032 ± 0.001
GEARS	0.296 ± 0.033	0.588 ± 0.012	0.178 ± 0.024	0.997 ± 0.001	0.371 ± 0.023
Models trained on 1/15 of full data size					
rbio-MLP	0.588 ± 0.030	0.792 ± 0.019	0.690 ± 0.034	0.894 ± 0.005	0.518 ± 0.035
rbio-MLP-CoT	0.642 ± 0.001	0.827 ± 0.000	0.752 ± 0.000	0.903 ± 0.000	0.582 ± 0.001
rbio-EXP	0.578 ± 0.018	0.804 ± 0.012	0.741 ± 0.025	0.866 ± 0.008	0.510 ± 0.021
rbio-EXP-CoT	0.639 ± 0.000	0.819 ± 0.000	0.731 ± 0.000	0.908 ± 0.000	0.577 ± 0.001
rbio-MLP ∪ EXP	0.648 ± 0.025	0.825 ± 0.015	0.737 ± 0.027	0.913 ± 0.005	0.589 ± 0.029
rbio-MLP ∪ EXP-CoT	$\mathbf{0.716 \pm 0.000}$	$\mathbf{0.861 \pm 0.000}$	0.792 ± 0.000	0.930 ± 0.000	$\mathbf{0.668 \pm 0.000}$
rbio-MLP ‖ EXP	0.623 ± 0.025	0.829 ± 0.016	0.771 ± 0.028	0.886 ± 0.005	0.563 ± 0.029
rbio-MLP ‖ EXP-CoT	0.696 ± 0.000	0.858 ± 0.000	$\mathbf{0.799 \pm 0.001}$	$\mathbf{0.918 \pm 0.000}$	0.646 ± 0.000
rbio-EXP ‖ MLP	0.641 ± 0.026	0.827 ± 0.017	0.748 ± 0.031	0.906 ± 0.003	0.582 ± 0.030
rbio-EXP ‖ MLP-CoT	0.703 ± 0.000	0.856 ± 0.000	0.786 ± 0.000	0.926 ± 0.000	0.653 ± 0.000
Baseline Reasoning (R)/Instruction-tuned models					
DeepSeek R1 Distil					
Qwen 32B (R)	0.241 ± 0.004	0.512 ± 0.011	0.694 ± 0.026	0.340 ± 0.032	0.024 ± 0.010
Llama 70B (R) †	0.248 ± 0.000	0.513 ± 0.000	0.790 ± 0.000	0.235 ± 0.000	0.021 ± 0.000
Qwen2.5 3B Instruct	0.240 ± 0.003	0.518 ± 0.012	0.663 ± 0.026	0.376 ± 0.030	0.028 ± 0.010
Qwen2.5 72B Instruct	0.247 ± 0.004	0.543 ± 0.009	0.517 ± 0.039	0.569 ± 0.047	0.045 ± 0.018
OpenAI OSS 20B (R) †	$\mathbf{0.295 \pm 0.013}$	$\mathbf{0.602 \pm 0.018}$	$\mathbf{0.435 \pm 0.036}$	$\mathbf{0.758 \pm 0.032}$	$\mathbf{0.151 \pm 0.016}$
OpenAI OSS 120B (R)	0.289 ± 0.019	0.602 ± 0.017	0.279 ± 0.027	0.896 ± 0.017	0.131 ± 0.019

TABLE 2. **Aggregate PerturbQA performance.** Mean ± SE over 5 completions across 4 cell lines. *rbio-EXP* corresponds to rbio-EXP-all-cell-lines. Comparison to baselines: SUMMER [32] (task SOTA), and SOTA reasoning and instruction-tuned models. Best model in each category bolded. Models with † were unable to answer all prompts. Reasoning/instruction-tuned models evaluated zero-shot.

4.6 Rbio is robust to verifier miscalibration and reward design

4.6.1 Effect of verifier signal miscalibration

FIGURE 6. | **Performance of rbio1 under progressively miscalibrated verifier signals.** The fraction of randomized MLP predictions (0.25 – 0.75) or flipped labels is shown on the x-axis, with the extreme case of completely random rewards included. **rbio1** performance (F1, MCC, Balanced Accuracy, TPR, TNR) declines smoothly as verifier noise increases but remains above the base Qwen 2.5-3B model until supervision becomes random, confirming that the model does not amplify verifier errors but instead learns robustly from partial biological signal. Numbers show percentage decrease in performance compared to the model trained on a fully-calibrated MLP.

To evaluate robustness to imperfect supervision, we simulate controlled levels of miscalibration in the MLP verifier used during reinforcement learning, ranging from partial randomization to fully random rewards (details in **Appendix A.4**).

As shown in Fig. 6, **rbio1** performance (F1, MCC, Balanced Accuracy, TPR, TNR) decreases smoothly as verifier noise increases, but remains well above the Qwen2.5-3B baseline until rewards are completely random. When signals are flipped or randomized, performance converges to—but does not fall below—the base model. This indicates that **rbio1** is able to learn from imperfect verifiers and that training is driven by biologically structured signal rather than incidental correlations.

4.6.2 Biological rewards versus generic RL shaping

To isolate the contribution of biological supervision, we ablate the reward into format, mention, and biological-answer components (full definitions in **Appendix A.4.2**).

As shown in Fig. 7, models trained with the full biological-answer reward outperform those using only generic format or mention rewards across all metrics (F1, Balanced Accuracy, TPR, TNR, MCC) and verifier types. The trend is consistent across EXP, MLP, and EXP ||MLP settings, with gains of up to +100% in F1 and MCC when including r_{verifier}. These results demonstrate that **rbio1**'s improvements are driven by the *biological signal* encoded in verifier feedback rather than generic RL regularization. Format- or mention-only rewards provide minor stylistic consistency but little biological benefit, whereas the full composition—especially the answer-level reward—contributes substantially to both recall and calibration. This supports our central claim that meaningful scientific rewards, not auxiliary shaping terms, are the dominant source of performance.

Consistency with generic RL/IT baselines. Table 2 further supports this conclusion: instruction-tuned and general RL reasoning models (e.g., DeepSeek R1, Qwen Instruct, OpenAI OSS) trained with generic format, helpfulness or self-verification signals achieve only modest performance on PerturbQA, whereas rbio1 variants—differing mainly by the presence of the biological answer reward—substantially exceed these baselines using the same 3B

backbone. Together with the ablations above, this indicates that *biological* supervision is the principal driver of improvement, not generic reinforcement or instruction tuning.

FIGURE 7. | **Ablation of reward components for rbio1 trained with experimental (EXP), model-based (MLP), and combined (EXP ||MLP) verifiers.** Across all settings, models trained with the full biological-answer reward outperform those using only generic format or mention rewards. The improvement is consistent across metrics and verifier types, indicating that the biological signal—not generic RL regularization—is the dominant contributor to performance.

4.6.3   Sensitivity to verifier confidence

FIGURE 8. | **Sensitivity of rbio1 performance to verifier fidelity.** Relationship between verifier confidence and **rbio1** test-time performance, aggregated across perturbed genes. Points denote confidence-bin centers (after min–max scaling); shaded regions show ± s.e.m. with sample counts *n*. Left: recall (TPR) vs. YES-confidence. Center: specificity (TNR) vs. NO-confidence. Right: overall correctness (accuracy) vs. confidence in the correct class. Recall increases with verifier confidence, while specificity and overall correctness remain high, indicating that **rbio1** leverages—but does not depend on—verifier certainty.

We further analyze how **rbio1** performance varies with verifier confidence by aggregating predictions across perturbed genes with different average verifier scores (details in **Appendix A.4.3**).

As shown in Fig. 8, recall increases monotonically with verifier confidence, while specificity and overall correctness remain stable even at low confidence. This indicates that **rbio1** leverages verifier certainty but does not depend on it to maintain performance. Extended experimental definitions and analyses for these studies are provided in **Appendix A.4.3**.

4.7   Reinforcement learning improves beyond supervised verifier imitation

FIGURE 9. | **Reinforcement learning improves beyond supervised verifier imitation. rbio1** models trained with an MLP verifier outperform the MLP itself across all metrics, indicating that reinforcement learning extends beyond direct imitation of the verifier.

As shown in Fig. 9, **rbio1** models trained using the MLP as a soft verifier (via reinforcement learning under the GRPO objective) outperform the MLP verifier itself across all metrics (F1, MCC, Balanced Accuracy, TPR, TNR) and for both input representations. The largest gains occur in recall (TPR), indicating that the reinforcement learning step allows the model to generalize beyond the fixed decision boundary of the MLP. While the MLP provides the biological reward signal, the reinforcement objective enables the policy to explore multiple reasoning trajectories at inference (via CoT) and to refine predictions through multi-sample consistency. This demonstrates that **rbio1** benefits not only from biological supervision but also from reinforcement optimization that integrates reasoning dynamics and soft-verifier feedback—allowing improvements that pure supervised imitation cannot achieve.

Together, these robustness analyses show that **rbio1**'s gains arise from biologically meaningful supervision and remain stable under verifier noise, confidence variation, and reward ablations (Sec. 4.6). We further analyze data and compute scaling behavior in Appendix A.8, showing predictable performance improvements with increased supervision and training compute. Additional analyses of compute efficiency and training-step scaling are provided in Appendix A.9.

5   Conclusion

We introduce **rbio1**, a suite of reasoning models trained via *soft verification*, where simulations from biological world models provide rewards for reinforcement learning. This approach rivals experimental-data–trained models, especially when combined with chain-of-thought prompting. By leveraging predictive bio-models (e.g., MLPs on gene embeddings) and knowledge sources like the GO Ontology, **rbio1** shows that simulations and prior knowledge can substitute for costly experimental supervision. Across experiments, we find that soft biological verifiers provide informative, robust training signals—enabling reinforcement learning to improve reasoning performance beyond supervised imitation while remaining resilient to verifier noise and miscalibration, outperforming general-purpose reasoning and instruction-tuned LLMs with up to 40× more parameters on PerturbQA and transferring zero-shot to cross-domain tasks such as disease-state prediction. We aim to extend **rbio1** across diverse biological models and modalities toward a universal virtual cell system integrating multiple sources as soft verifiers. Soft verification defines a general paradigm for training reasoning LLMs—scalable to domains without exact verifiers and opening new directions for verifier design, noise robustness, and evaluation beyond task accuracy.

6   Acknowledgment

We thank Wyatt Robarts and Jae Lee for legal and security counsel; CZI AI-Infra team for supporting the computing needs; Yun Liu and the CZI Creative team for assistance with figure preparation and graphic design; Maximilian Lombardo and Omar Valenzuela for assisting with open sourcing the code repository and Notebook tutorials; Amanda Mahoney for helpful guidance on communications and outreach related to this preprint.

References

[1] Josh Abramson, Jonas Adler, Jack Dunger, Richard Evans, Tim Green, Alexander Pritzel, Olaf Ronneberger, Lindsay Willmore, Andrew J Ballard, Joshua Bambrick, et al. Accurate structure prediction of biomolecular interactions with alphafold 3. *Nature*, 630(8016):493–500, 2024.

[2] Haotian Cui, Chloe Wang, Hassaan Maan, Kuan Pang, Fengning Luo, Nan Duan, and Bo Wang. scgpt: toward building a foundation model for single-cell multi-omics using generative ai. *Nature methods*, 21(8):1470–1480, 2024.

[3] Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Robert Verkuil, Ori Kabeli, Yaniv Shmueli, et al. Evolutionary-scale prediction of atomic-level protein structure with a language model. *Science*, 379(6637):1123–1130, 2023.

[4] Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.

[5] An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

[6] Adibvafa Fallahpour, Andrew Magnuson, Purav Gupta, Shihao Ma, Jack Naimer, Arnav Shah, Haonan Duan, Omar Ibrahim, Hani Goodarzi, Chris J Maddison, et al. Bioreason: Incentivizing multimodal biological reasoning within a dna-llm model. *arXiv preprint arXiv:2505.23579*, 2025.

[7] Guangshuo Cao, Yi Shen, Jianghong Wu, Haoyu Chao, Ming Chen, and Dijun Chen. Cellreasoner: A reasoning-enhanced large language model for cell type annotation. *bioRxiv*, pages 2025–05, 2025.

[8] Siddharth M Narayanan, James D Braza, Ryan-Rhys Griffiths, Albert Bou, Geemi Wellawatte, Mayk Caldas Ramos, Ludovico Mitchener, Samuel G Rodriques, and Andrew D White. Training a scientific reasoning model for chemistry. *arXiv preprint arXiv:2506.17238*, 2025.

[9] Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[10] Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. Learning to summarize with human feedback. *Advances in neural information processing systems*, 33:3008–3021, 2020.

[11] Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, Lester James V Miranda, Alisa Liu, Nouha Dziri, Shane Lyu, et al. Tulu 3: Pushing frontiers in open language model post-training. *arXiv preprint arXiv:2411.15124*, 2024.

[12] Harrison Lee, Samrat Phatale, Hassan Mansoor, Kellie Ren Lu, Thomas Mesnard, Johan Ferret, Colton Bishop, Ethan Hall, Victor Carbune, and Abhinav Rastogi. Rlaif: Scaling reinforcement learning from human feedback with ai feedback. 2023.

[13] Charlotte Bunne, Yusuf Roohani, Yanay Rosen, Ankit Gupta, Xikun Zhang, Marcel Roed, Theo Alexandrov, Mohammed AlQuraishi, Patricia Brennan, Daniel B Burkhardt, et al. How to build the virtual cell with artificial intelligence: Priorities and opportunities. *Cell*, 187(25):7045–7063, 2024.

[14] Boris M Slepchenko, James C Schaff, Ian Macara, and Leslie M Loew. Quantitative cell biology with the virtual cell. *Trends in cell biology*, 13(11):570–576, 2003.

[15] Leslie M Loew and James C Schaff. The virtual cell: a software environment for computational cell biology. *TRENDS in Biotechnology*, 19(10):401–406, 2001.

[16] Yanay Rosen, Yusuf Roohani, Ayush Agarwal, Leon Samotorčan, Tabula Sapiens Consortium, Stephen R Quake, and Jure Leskovec. Universal cell embeddings: A foundation model for cell biology. *BioRxiv*, pages 2023–11, 2023.

[17] James D Pearce, Sara E Simmonds, Gita Mahmoudabadi, Lakshmi Krishnan, Giovanni Palla, Ana-Maria Istrate, Alexander Tarashansky, Benjamin Nelson, Omar Valenzuela, Donghui Li, et al. A cross-species generative cell atlas across 1.5 billion years of evolution: The transcriptformer single-cell model. *bioRxiv*, pages 2025–04, 2025.

[18] Haiyang Bian, Yixin Chen, Xiaomin Dong, Chen Li, Minsheng Hao, Sijie Chen, Jinyi Hu, Maosong Sun, Lei Wei, and Xuegong Zhang. scmulan: a multitask generative pre-trained language model for single-cell analysis. In *International Conference on Research in Computational Molecular Biology*, pages 479–482. Springer, 2024.

[19] Nicholas Ho, Caleb N Ellington, Jinyu Hou, Sohan Addagudi, Shentong Mo, Tianhua Tao, Dian Li, Yonghao Zhuang, Hongyi Wang, Xingyi Cheng, et al. Scaling dense representations for single cell with transcriptome-scale context. *bioRxiv*, pages 2024–11, 2024.

[20] Christina V Theodoris, Ling Xiao, Anant Chopra, Mark D Chaffin, Zeina R Al Sayed, Matthew C Hill, Helene Mantineo, Elizabeth M Brydon, Zexian Zeng, X Shirley Liu, et al. Transfer learning enables predictions in network biology. *Nature*, 618(7965):616–624, 2023.

[21] Ankit Gupta, Zoe Wefers, Konstantin Kahnert, Jan N Hansen, Will Leineweber, Anthony Cesnik, Dan Lu, Ulrika Axelsson, Frederic Balll1losera Navarro, Theofanis Karaletsos, et al. Subcell: Vision foundation models for microscopy capture single-cell biology. *bioRxiv*, pages 2024–12, 2024.

[22] Eric Nguyen, Michael Poli, Matthew G Durrant, Brian Kang, Dhruva Katrekar, David B Li, Liam J Bartie, Armin W Thomas, Samuel H King, Garyk Brixi, et al. Sequence modeling and design from molecular to genome scale with evo. *Science*, 386(6723):eado9336, 2024.

[23] Syed Asad Rizvi, Daniel Levine, Aakash Patel, Shiyang Zhang, Eric Wang, Curtis Jamison Perry, Nicole Mayerli Constante, Sizhuang He, David Zhang, Cerise Tang, et al. Scaling large language models for next-generation single-cell analysis. *BioRxiv*, pages 2025–04, 2025.

[24] Bernardo P de Almeida, Guillaume Richard, Hugo Dalla-Torre, Christopher Blum, Lorenz Hexemer, Priyanka Pandey, Stefan Laurent, Chandana Rajesh, Marie Lopez, Alexandre Laterre, et al. A multimodal conversational agent for dna, rna and protein tasks. *Nature Machine Intelligence*, 7(6):928–941, 2025.

[25] Daniel Levine, Syed Asad Rizvi, Sacha Lévy, Nazreen Pallikkavaliyaveetil, David Zhang, Xingyu Chen, Sina Ghadermarzi, Ruiming Wu, Zihe Zheng, Ivan Vrkic, et al. Cell2sentence: teaching large language models the language of biology. *BioRxiv*, pages 2023–09, 2024.

[26] Moritz Schaefer, Peter Peneder, Daniel Malzl, Mihaela Peycheva, Jake Burton, Anna Hakobyan, Varun Sharma, Thomas Krausgruber, Jörg Menche, Eleni M Tomazou, et al. Multimodal learning of transcriptomes and text enables interactive single-cell rna-seq data exploration with natural-language chats. *BioRxiv*, pages 2024–10, 2024.

[27] Jeongbin Park, Sumin Kim, Jiwon Kim, Dongjoo Lee, Sungwoo Bae, Haenara Shin, Daeseung Lee, and Hongyoon Choi. Cellama: foundation model for single cell and spatial transcriptomics by cell embedding leveraging language model abilities. *Advanced Science*, page e13210, 2024.

[28] Ana-Maria Istrate, Donghui Li, and Theofanis Karaletsos. scgenept: Is language all you need for modeling single-cell perturbations? *bioRxiv*, pages 2024–10, 2024.

[29] Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35:22199–22213, 2022.

[30] Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori B Hashimoto. s1: Simple test-time scaling. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 20286–20332, 2025.

[31] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.

[32] Menghua Wu, Russell Littman, Jacob Levine, Lin Qiu, Tommaso Biancalani, David Richmond, and Jan-Christian Huetter. Contextualizing biological perturbation experiments through language. *arXiv preprint arXiv:2502.21290*, 2025.

[33] Jon Saad-Falcon, E Kelly Buchanan, Mayee F Chen, Tzu-Heng Huang, Brendan McLaughlin, Tanvir Bhathal, Shang Zhu, Ben Athiwaratkun, Frederic Sala, Scott Linderman, et al. Shrinking the generation-verification gap with weak verifiers. *arXiv preprint arXiv:2506.18203*, 2025.

[34] Tianyu Yu, Bo Ji, Shouli Wang, Shu Yao, Zefan Wang, Ganqu Cui, Lifan Yuan, Ning Ding, Yuan Yao, Zhiyuan Liu, et al. Rlpr: Extrapolating rlvr to general domains without verifiers. *arXiv preprint arXiv:2506.18254*, 2025.

[35] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, YK Li, Yang Wu, et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

[36] Youssef Mroueh. Reinforcement learning with verifiable rewards: Grpo's effective loss, dynamics, and success amplification. *arXiv preprint arXiv:2503.06639*, 2025.

[37] Jingcheng Du, Peilin Jia, Yulin Dai, Cui Tao, Zhongming Zhao, and Degui Zhi. Gene2vec: distributed representation of genes based on co-expression. *BMC genomics*, 20(Suppl 1):82, 2019.

[38] Yusuf Roohani, Kexin Huang, and Jure Leskovec. Gears: Predicting transcriptional outcomes of novel multi-gene perturbations. *BioRxiv*, pages 2022–07, 2022.

[39] Romain Lopez, Jeffrey Regier, Michael B Cole, Michael I Jordan, and Nir Yosef. Deep generative modeling for single-cell transcriptomics. *Nature methods*, 15(12):1053–1058, 2018.

A Supplementary Material

A.1 Perturbation-reasoning task setup and natural-language formulation

Overview. The PerturbQA benchmark was introduced by [32]and provides CRISPRi single-gene perturbation experiments across four human cell lines—**RPE1**, **K562**, **HEPG2**, and **JURKAT**. Each experimental record indicates whether a knock-down of gene *A* affects the expression of gene *B* in a specific cell line. We follow the processed natural-language formulation introduced in PerturbQA, using the converted perturbation records into text-based reasoning query.

   Natural-language conversion. Each example is phrased as a binary scientific question, for instance:

   "Is a knockdown of AARS in hepg2 cells likely to result in differential expression of ATAD2B? The answer is either yes or no."

This transformation allows language models to treat biological perturbation prediction as a question-answering task grounded in experimental evidence. Ground-truth labels (yes/no) are derived directly from differential-expression outcomes reported in the original CRISPRi datasets. This representation enables the model to reason jointly over biological entities, relationships, and cell-line context, bridging structured perturbation data with language-based reasoning.

   Prompting formulation. Each perturbation question is provided as the **user_prompt**, and the model responds according to a fixed **system_prompt** describing a structured reasoning dialogue:

   "A conversation between User and Biologist. The user asks a question, and the Biologist solves it. The Biologist first thinks about the reasoning process in the mind and then provides the user with the answer. The reasoning process and answer are enclosed within `` *and* `<answer>` *tags, respectively, i.e.,* `` *reasoning process here* `` `<answer>` *answer here* `</answer>`*."*

This format explicitly separates latent reasoning from the final prediction, allowing reinforcement learning to target biologically grounded reasoning steps and answer correctness.

   Task setups (as illustrated in Fig. 2). We evaluate three complementary configurations:

- **(a) rbio-EXP-one-cell-line:** Models are trained and evaluated on perturbations within a single cell line (e.g., train = test = RPE1). This setup measures within-cell-line generalization where training and test gene pairs are disjoint, isolating reasoning performance without cross-cell transfer.
- **(b) rbio-EXP-leave-one-out:** Models are trained on three of the four cell lines and tested on the held-out one (e.g., train = RPE1 + K562 + HEPG2 test = JURKAT). This configuration evaluates out-of-distribution (OOD) generalization across cellular contexts.
- **(c) rbio-MLP-leave-one-out:** In this setting, an MLP surrogate model is first trained on three cell lines using experimental data, then used to generate probabilistic predictions (soft rewards) on the training split of the held-out fourth cell line. Testing is on this split. These model-predicted probabilities serve as reward signals during reinforcement learning, effectively replacing direct experimental supervision.

Baselines. We compare against: **SUMMER** [32] (retrieval + knowledge-based reasoning), **GEARS** [38] (a specialized perturbation model), and the base **Qwen2.5-3B** reasoning model without biological supervision.

A.2   Metrics

Metrics Used We formulate the genetic perturbation prediction task as a question in natural language with a binary answer. Given a pair of genes $gene_A$ and $gene_B$, the model is asked to emit a binary answer — **yes** or **no**. We use four CRISPRi single-gene perturbation knockdown datasets on four cancer cell lines (RPE1, K562, HEPG2, JURKAT), post-processed into natural language queries by PerturbQA [32]. We compute the following metrics:

$$Recall\ (TPR) = \frac{TP}{TP + FN} \tag{14}$$

$$TNR = \frac{TN}{TN + FP} \tag{15}$$

$$Precision = \frac{TP}{TP + FP} \tag{16}$$

$$F1\ Score = \frac{2 \cdot Precision \cdot Recall}{Precision + Recall} \tag{17}$$

$$Balanced\ Accuracy = \frac{TPR + TNR}{2} \tag{18}$$

$$MCC\ (Matthews\ Correlation\ Coefficient) = \frac{TP \cdot TN - FP \cdot FN}{\sqrt{(TP + FP)(TP + FN)(TN + FP)(TN + FN)}} \tag{19}$$

Interpretation. The PerturbQA datasets are inherently class-imbalanced, with substantially fewer positive (true perturbation) cases than negatives. In this setting, identifying true positive perturbations is biologically more important than avoiding false positives, since missing true regulatory effects (false negatives) can obscure functional gene relationships. We therefore emphasize **Recall (TPR)**, **F1-score**, **Balanced Accuracy**, and **MCC** as the most informative metrics. Recall captures the model's sensitivity to true perturbations, F1 balances precision and recall under imbalance, Balanced Accuracy accounts for both sensitivity and specificity, and MCC provides a single correlation-like summary that remains meaningful even for skewed label distributions. Together, these metrics provide a robust picture of biological prediction fidelity under class imbalance.

Computation of error bars in reported metrics For each model m and metric ℓ, performance values are first aggregated within dataset (corresponding to one of the four cell lines (K562, RPE1, JURKAT, HEPG2) $d \in D$ by taking the mean:

$$\bar{v}_d = \frac{1}{n_d} \sum_{i=1}^{n_d} v_{d,i},$$

where $v_{d,i}$ are per-example scores within dataset d. We then compute the mean performance across datasets

$$\bar{v} = \frac{1}{|D|} \sum_{d \in D} \bar{v}_d,$$

and quantify variability across datasets as

$$s = \sqrt{\frac{1}{|D| - 1} \sum_{d \in D} (\bar{v}_d - \bar{v})^2}.$$

The error bars in all aggregate bar plots represent the standard error of the mean (s.e.m.) across datasets:

$$\text{SEM} = \frac{s}{\sqrt{|D|}}.$$

This approach first averages performance within each dataset, then estimates variability across datasets, ensuring that all datasets contribute equally and preventing larger datasets from dominating the uncertainty estimate.

A.3 Examples of reasoning traces

Is a knockdown of ISCA2 in rpe1 cells likely to result in differential expression of CEP295? The answer is either yes or no

system_prompt
A conversation between User and Biologist. The user asks a question, and the Biologist solves it. The biologist first thinks about the reasoning process in the mind and then provides the user with the answer. The reasoning process and answer are enclosed within   and <answer> </answer> tags, respectively, i.e., reasoning process here <answer> answer here </answer>.

system_prompt
A conversation between User and Biologist. The user asks a question, and the Biologist solves it. The biologist first thinks about the reasoning process in the mind and then provides the user with the answer. The reasoning process and answer are enclosed within   and <answer> </answer> tags, respectively, i.e., reasoning process here <answer> answer here </answer>.The Biologist will evaluate each step of this problem, using logical reasoning and evidence from the prompt.

system_prompt
You are an AI model trained as a Biologist through reinforcement learning. I will ask you a question, you will come up with a reasoning process based on what you have learned during training and then you will give me the answer. The reasoning process and answer are enclosed within   and <answer> </answer> tags, respectively, i.e., reasoning process here <answer> answer here </answer>. You will provide the reasoning step-by-step, using detailed biological knowledge from training.

Example answer

Knockdown of ISCA2 in RPE1 cells would likely lead to differential expression of CEP295. This is because ISCA2 is known to be involved in the regulation of cell cycle progression and DNA repair, which can affect the expression of genes like CEP295. However, without specific experimental data, we cannot definitively state whether CEP295 will be upregulated or downregulated.

Example answer using Chain-of-Thought

ISCA2 is a protein that is involved in the regulation of cell cycle progression. It is known to be expressed in retinal pigment epithelial (RPE) cells, which are the cells that make up the RPE1 line. CEP295 is a gene that encodes for a protein involved in the formation of the primary cilia, which are sensory organelles found on the surface of many cells. Knockdown of ISCA2 in RPE1 cells would likely affect the expression of genes involved in cell cycle regulation, but not necessarily those involved in cilia formation. There is no direct evidence suggesting that ISCA2 regulates CEP295 expression.

Example answer using self-aware Chain-of-Thought

Knockdown of ISCA2 in RPE1 cells would likely lead to differential expression of CEP295. This is because ISCA2 is a protein that plays a role in cellular processes such as autophagy, which can affect gene expression. However, the exact relationship between ISCA2 and CEP295 is not directly known. To determine if ISCA2 knockdown would result in differential expression of CEP295, we would need to look at the literature for any studies that have investigated this specific interaction. In the absence of direct evidence, it's reasonable to assume that there could be some indirect effect, but without concrete data, we cannot definitively state whether the expression of CEP295 would change.

FIGURE SI-1. | **Examples of reasoning traces for perturbation prediction, answering a question sampled randomly from the test set.** Each panel shows reasoning text generated within the `` tags (qualitative traces). Different examples correspond to distinct chain-of-thought prompting strategies (standard, explicit chain-of-thought, and self-aware chain-of-thought). Outputs are from a model trained with combinations of soft verifiers. Final answer omitted for brevity

A.4 Robustness to Verifier Fidelity and Miscalibration

A.4.1 Effect of Verifier Signal Miscalibration

Setup. To assess the robustness of **rbio1** to verifier reliability, we simulate controlled levels of miscalibration in the MLP verifier used during reinforcement learning. During training, each instance receives a scalar reward $r \in [0, 1]$ based on the verifier's predicted probability p_{yes} (and $p_{\text{no}} = 1 - p_{\text{yes}}$). If the model outputs "yes," the reward is $r = p_{\text{yes}}$; otherwise, $r = p_{\text{no}}$.

To emulate verifier noise, we perturb p_{yes} according to:

$$p'_{\text{yes}} = \begin{cases} p_{\text{yes}}, & \text{no noise} \\ (1 - \rho)\, p_{\text{yes}} + \rho\, U(0, 1), & \text{partial randomization, } \rho \in \{0.25, 0.5, 0.75\} \\ 1 - p_{\text{yes}}, & \text{flipped} \\ U(0, 1), & \text{fully random} \end{cases} \tag{20}$$

where $U(0, 1)$ denotes samples from a uniform distribution over $[0, 1)$, implemented with `np.random.rand()`. The complement is set as $p'_{\text{no}} = 1 - p'_{\text{yes}}$. This parameterization allows a smooth transition from correctly calibrated to fully corrupted verifier signals.

A.4.2 Reward Components Ablations

Setup. To isolate the effect of different reward components defined in Eq. 13, we conduct ablations across the three verifier classes—experimental (EXP), model-based (MLP), and combined (EXP ||MLP). The full reward in Eq. 13 can be re-written as:

$$r_i(q, o_i) = r_{\text{format}} + r_{\text{mention}} + r_{\text{verifier}} \tag{21}$$

which includes (i) a *format reward* enforcing structured output, (ii) a *mention reward* encouraging relevant entity inclusion—in our case, gene mentions—and (iii) a *biological-answer reward* r_{verifier} that encodes signal from verifier V_k (e.g., experimental or MLP-based). We train variants using only individual terms: r_{format}, r_{mention}, $r_{\text{format}} + r_{\text{mention}}$, and the full biological reward r_{verifier}.

A.4.3 Sensitivity to verifier confidence (per-gene analysis)

Setup. Let g index perturbed genes. From training logs, we compute the MLP verifier's mean YES-confidence per gene over all cell lines:

$$\bar{p}_{\text{yes}}(g) = \mathbb{E}_{\text{MLP emissions for } g}[p_{\text{yes}}], \qquad \bar{p}_{\text{no}}(g) = 1 - \bar{p}_{\text{yes}}(g).$$

We left-join these per-gene confidences to each test example (x, g, y) and evaluate the trained policy's binary prediction $\hat{y} \in \{0, 1\}$. For analysis we form:

$$\text{TPR input: } c^+ = \bar{p}_{\text{yes}}(g) \text{ for } y = 1, \quad \text{TNR input: } c^- = \bar{p}_{\text{no}}(g) \text{ for } y = 0, \quad c^\star = \begin{cases} \bar{p}_{\text{yes}}(g) & y = 1 \\ \bar{p}_{\text{no}}(g) & y = 0. \end{cases}$$

Each c is min–max scaled to $[0, 1]$ and partitioned into 12 equal-width bins; the plotted points correspond to bin centers, with y-values equal to binned means of (i) $\mathbb{E}[\hat{y} \mid y{=}1]$ (TPR), (ii) $\mathbb{E}[1{-}\hat{y} \mid y{=}0]$ (TNR), and (iii) $\mathbb{E}[\mathbb{I}\{\hat{y}{=}y\}]$ (overall correctness).

Intersections of Genes Perturbed Across Cell Lines

FIGURE SI-2. | **Gene overlap across TRAIN sets and TEST.** Radar plots show the percentage of shared perturbed genes between cell lines within training (left) and between training and test splits (right) for each held-out cell line. Each small radar corresponds to one reference cell line and compares its gene set to those of the remaining lines. While cell lines share 40–75% of perturbed genes in training, overlap between a test set and other training sets ranges from 50–78%. This partial but non-trivial intersection indicates that cell lines differ in transcriptional programs yet retain overlapping biological structure, making leave-one-out evaluation both challenging and biologically realistic.

Connection to cross–cell-line context. Fig. SI-2 shows that gene vocabularies are only partially shared across TRAIN splits (40–75%) and between TEST and TRAIN (50–78%), so the sensitivity curves in Fig. 8 reflect aggregation over both shared and distinct gene sets across cell lines rather than a trivially identical vocabulary.

A.5   Verifier Agreement and Composition Effects

FIGURE SI-3. | **Verifier agreement across cell lines for MLP and EXP verifiers.** Agreement measured as Pearson correlation of continuous scores (left) and majority-vote agreement (right) between verifier outputs.

FIGURE SI-4. | **Verifier agreement across cell lines for GO and EXP verifiers.** Agreement measured as Pearson correlation of continuous scores (left) and majority-vote agreement (right) between verifier outputs.

FIGURE SI-5. | **Verifier agreement across cell lines for GO and MLP verifiers.** Agreement measured as Pearson correlation of continuous scores (left) and majority-vote agreement (right) between verifier outputs.

Setup. We compare verifier outputs across the four PerturbQA cell lines (K562, RPE1, HEPG2, and Jurkat) to quantify consistency between the experimental (EXP), model-based (MLP), and ontology-derived (GO) verifiers. For each cell line, we compute (i) the *continuous agreement*, measured as the Pearson correlation r between the continuous verifier scores; and (ii) the *majority-vote agreement*, measured as binary accuracy between thresholded verifier predictions. These statistics are aggregated over all shared gene pairs within each cell line.

Results. As shown in Figs. SI-3–SI-5, EXP and MLP verifiers exhibit high agreement across all cell lines ($r \approx 0.8$, binary agreement ≈ 0.93), indicating that both encode consistent biological signal. By contrast, GO-based verifiers show weaker raw correlation with EXP or MLP ($r \approx 0.3$) but still moderate binary alignment (accuracy ≈ 0.75), reflecting that ontology-derived priors capture complementary but coarser relationships. Compositional verifiers such as GO ∥EXP and GO ∥MLP realign more closely with the higher-fidelity verifiers applied last, confirming that the order of composition influences which signal dominates.

Interpretation. High pairwise consistency among EXP and MLP verifiers supports that **rbio1** learns from largely aligned supervision sources rather than conflicting signals. The weaker continuous correlation but stable discrete alignment of GO-based rewards suggests that these verifiers contribute structured regularization rather than direct label imitation—providing a complementary prior that the reinforcement process integrates effectively across cell lines.

A.6 Reinforcement Learning vs. Supervised Verifiers

MLP Architecture and Training

MLPClassifier

Input: $\mathbb{R}^{2d}$ Gene embedding

Linear
$(2d \rightarrow 64)$ 64 units

ReLU

Linear
$(64 \rightarrow 1)$ 1 unit

Sigmoid

Output: $[0, 1]$

FIGURE SI-6. MLP Structure

TABLE 3. MLP Training Hyperparameters

Hyperparameter Name	Value
Number of Epochs	10
Batch Size	32
Learning Rate	1×10^{-3}
Random Seed	42

Setup. The MLP verifier is a simple two-layer network (Fig. SI-6) consisting of a linear projection from the concatenated gene embedding ($\mathbb{R}^{2d} \rightarrow 64$), followed by a ReLU activation, a second linear layer ($64 \rightarrow 1$), and a

sigmoid output. It produces a scalar confidence $p_{\text{yes}} \in [0, 1]$ representing the probability of a positive perturbation effect. Training hyperparameters are listed in Table 3. We evaluate two gene-encoding schemes:

- **One-hot representation:** genes are represented by binary one-hot vectors, providing no relational prior.
- **Gene2Vec embedding:** genes are embedded in a dense continuous space learned from large-scale co-expression networks, capturing semantic relationships between genes.

A.7   Out-of-Distribution and Cross-Domain Generalization

FIGURE SI-7. | **Dataset Class Distribution for Disease Prediction Task.** The Alzheimer dataset has two binary labels and the Cancer dataset has seven different types of cancer as cell states. Both datasets have been obtained from CELLXGENE

Dataset composition. We evaluate generalization beyond perturbation reasoning on two disease-state datasets: (i) **Alzheimer's disease**, a binary classification task (normal vs. diseased; Fig. SI-7, top), and (ii) **Myeloid cancers**, a multi-class task containing eight disease states (normal plus seven cancer types; Fig. SI-7, bottom). Each cell or sample is represented using the top 100 highly expressed genes and relevant experimental metadata, including tissue, assay type, developmental stage, cell type, and organism. All gene-expression data are sourced from CELLxGENE public collections.

   Prompt construction and input representation. For each single-cell observation, we generate a natural-language query that integrates biological metadata and expression context. Each prompt follows the format:

   "This is a single-cell observation obtained using [assay] from the [tissue] of a [sex] Homo sapiens. The top 100 expressed genes in this cell are: [gene$_1$, gene$_2$, ..., gene$_{100}$]. Based on these genes, identify the disease state of this single cell. Choose one: [class$_1$ | class$_2$ | ... | class$_n$]."

For example:

   "This is a single-cell observation obtained using 10x 3' v2 from the ovary of an unknown female Homo sapiens. The top 100 expressed genes in this cell are: MALAT1, TMSB4X, B2M, ACTB, RPL10, MT-ATP6, ..., LY6H. Based on these genes, identify the disease state of this single cell. Choose one: normal | lung cancer | ovarian cancer | uveal melanoma | colorectal cancer | breast cancer | liver cancer | melanoma."

This structured input provides biologically interpretable features that the language model can reason over. Metadata tokens give high-level context, while ranked genes reflect the underlying transcriptional state. Together, they form a natural-language interface between single-cell biology and language-based reasoning.

Zero-shot evaluation. All models are evaluated in a zero-shot setting—no fine-tuning or disease-specific supervision is used. **rbio1** models are trained only on perturbation-prediction tasks from PerturbQA using biological soft-verifier rewards (MLP, EXP, and GO). The disease tasks thus test transfer to an out-of-distribution setting, assessing whether models trained on causal perturbations can generalize to disease-state reasoning.

Example model response. Below is an example of an **rbio1** reasoning trace, illustrating how the model integrates gene-expression patterns and biological context to infer cell identity and disease state:

> `` The expression levels of different genes can give us an idea of the cell type. For example, genes related to ribosomal proteins are often expressed at high levels in cells that are actively dividing or have a high rate of protein synthesis. Given that there are multiple genes for ribosomal proteins (RPL10, RPL41, RPL13A, RPL13, RPL7, RPL28, RPL37A, etc.), as well as other genes involved in translation (such as EEF1A1, EEF1A2), we can infer that this cell is likely a rapidly proliferating cell. MALAT1 is known to be associated with the epithelial-mesenchymal transition and metastasis, which may suggest the presence of a tumor. B2M (beta-2 microglobulin) is a protein marker for antigen presentation and can be found on the surface of many types of immune cells and some tumor cells. Vimentin (VIM) is a marker of mesenchymal cells and can also be found in some tumors. All of these factors could indicate a potential tumor cell state. However, since the gene list does not explicitly mention any of the known markers for specific cancers, we must consider the most probable option given the data available. The presence of ribosomal proteins and genes related to translation and the possibility of a tumor cell state points towards ovarian cancer as the most plausible diagnosis. ``
>
> `<answer>` ovarian cancer `</answer>`

SCVI baseline. As a reference, we train a standard **SCVI** model directly on the same Alzheimer and Cancer datasets. Following the default training setup:

(1) SCVI is initialized using `scvi.model.SCVI` with the disease label as `labels_key="disease"`.
(2) The model is trained for 100 epochs with learning rate 1×10^{-3}.
(3) The latent representation is extracted and used to train a linear logistic regression classifier for disease-state prediction.

The model's mean performance is computed from accuracy, precision, recall, and F1 score as in the main evaluation pipeline.

TABLE 4. SCVI training and evaluation setup.

Parameter	Value / Description
Model	`scvi.model.SCVI` (default)
Training epochs	100
Learning rate	1×10^{-3}
Latent dimension	default (10)
Classifier	Logistic Regression (L_2 regularization, max_iter=200)
Evaluation metrics	Accuracy, Precision, Recall, F1 (macro)
Input data	Same Alzheimer and Cancer datasets as **rbio1** experiments

Results and interpretation. As shown in Fig. 5, **rbio1** achieves large gains over EXP and MLP verifiers across metrics (F1, precision, recall) while maintaining calibration. On the Alzheimer dataset, **rbio1** doubles the F1 score and achieves a +136% increase in recall relative to baseline verifiers. For Myeloid cancers, **rbio1** improves F1 by 30–70% while retaining high specificity. These results approach those of SCVI—a specialized expression model trained directly on raw counts—despite **rbio1** being trained exclusively on perturbation reasoning signals.

Significance. This experiment demonstrates that **rbio1** internalizes generalizable molecular reasoning patterns. Trained solely with reinforcement learning from biological verifiers, it transfers this understanding to infer disease states in unseen data distributions. This zero-shot ability highlights the potential of soft-verifier RL to unify experimental, model-based, and knowledge-based biological reasoning into a single transferable system.

A.8 Data and Compute Scaling

Setup. We systematically vary two axes of training—dataset size and compute—to examine scaling behavior and robustness of **rbio1** under different supervision regimes. Each variant uses the same Qwen2.5-3B-Instruct base model trained under the GRPO objective with identical hyperparameters. Dataset-size experiments sample 20%, 50%, and 100% of the full PerturbQA training data across verifier types (EXP, MLP, EXP ∪ MLP, and EXP ∪ MLP ∪ GO) and are run for 1, 3, or 5 epochs. Compute experiments fix the full dataset and vary the number of optimization steps (1, 3, and 5 epochs equivalent) to test performance scaling with training duration.

FIGURE SI-8. | **Effect of training data size on rbio1 accuracy and generalization, 1 epoch.**

Results — data scaling. Across all verifier configurations and metrics (F1, Balanced Accuracy, TPR, TNR, MCC), performance increases predictably with the amount of training data (Figs. SI-8–SI-10). The scaling trend is approximately log-linear, with diminishing returns at higher data fractions but consistent improvement in both sensitivity and specificity. This indicates that the GRPO-based optimization effectively captures additional signal as more examples are available.

FIGURE SI-9. | **Effect of training data size on rbio1 accuracy and generalization, 3 epochs.**

FIGURE SI-10. | **Effect of training data size on rbio1 accuracy and generalization, 5 epochs.**

A.9   Compute Efficiency

Results — compute scaling. Increasing training compute yields analogous improvements (Fig. SI-11). Metrics such as F1 and MCC rise smoothly with training steps, confirming that **rbio1** adheres to reinforcement-learning scaling laws observed in other large-model settings.

FIGURE SI-11. | **Influence of training compute at 1, 3, and 5 epochs on rbio1 performance.**

Interpretation. Together, these analyses show that **rbio1** scales predictably with both data and compute—doubling training data or epochs consistently improves recall, precision, and calibration. This behavior demonstrates that the biological reward signals provide a smooth and information-rich learning gradient, enabling steady performance growth without reward collapse. It further confirms that reinforcement learning over biological verifiers is a robust and scalable paradigm for large-model training in scientific domains.

A.10   Training and Evaluation

Models have been trained using the GRPO framework and the HuggingFace interface. We use a Qwen2.5-3B-Instruct model as a base model, accessed through HuggingFace. Most models presented on individual verifiers have been trained for up to 100k steps with `max_completion_len=256`, taking approximately 10 days to complete on 8 H100 GPUs. Models containing compositions of verifiers were trained for up to 10 epochs. Ablation and sensitivity experiments used proportionally shorter runs or reduced data fractions to ensure efficiency while preserving relative comparisons. Each experiment presents the checkpoint corresponding to its stated data fraction and number of training epochs; while absolute values may vary, the observed performance trends are consistent across configurations. All models used `batch_size=4`, `n_generation=4`, and a learning rate of 5×10^{-6}. During inference, each model was prompted for `N=5` generations with `max_new_tokens=1024`, `do_sample=True`, `temperature=0.7`, `top_p=0.9`, `top_k=50`. Metrics are reported over five different generations. Each model also includes formatting rewards, following [4].

TABLE 5. Training configuration for **rbio1** models.

Model Specification	
Model	Qwen2.5-3B-Instruct (3.09B parameters)
Training Hyperparameters	
Per-device train batch size	4
Number of rollouts	4
Max completion length	256
Length penalty	200
Learning rate	1×10^{-6}
Random seed	42

A.11 Data and Code Availability

We used the pre-processed versions, as well as the training and testing splits of the perturbation datasets on the four cell lines (K562, RPE1, HEPG2, JURKAT) from https://github.com/genentech/PerturbQA.

We have released a GitHub repository (`https://github.com/czi-ai/rbio`) that reproduces the MLP-verifier experiments and provides an end-to-end example of training an *rbio* model using the MLP signal, as well as inference scripts. This release focuses on the essential components for reproducibility and community adoption.

Model weights are also publicly available with links available on the GitHub repo page. For the disease prediction task, the datasets were obtained from CELLXGENE with the following identifiers:

Alzheimer Dataset: https://cellxgene.cziscience.com/collections/0d35c0fd-ef0b-4b70-bce6-645a4660e5fa

Cancer Dataset: https://cellxgene.cziscience.com/collections/3f7c572c-cd73-4b51-a313-207c7f20f188.

A.12   Algorithms

Algorithm 1 Rbio-RLEXP: Reinforcement Learning with Hard Verification

---

Require: Dataset of prompts/experimental outcome labels $\{X_i, Y_i\}_{i=1}^N$
Require: Model parameters θ implementing policy π_θ
Require: Hyperparameters: τ (temperature), G (generations per prompt), β (KL penalty), ϵ (clipping)
Ensure: Trained model with parameters $\tilde{\theta}$ implementing policy $\pi_{\tilde{\theta}}$

1: Initialize θ from supervised fine-tuned LLM
2: **for** each step $t = 1$ to T **do**
3:      Sample batch indices $b \subset \{1, \dots, N\}$ uniformly at random
4:      Retrieve batch $\{X_b, Y_b\}$ from dataset
5:      **for** each prompt X_b in batch **do**
6:          **for** $i = 1$ to G **do**
7:              Generate sequence $o_i \sim \pi_\theta(\cdot \mid X_b)$ using model θ and policy π_θ
8:              Extract binary answer $\hat{a}_i$ from o_i (if existing)
9:              **if** answer $\hat{a}_i$ exists **then**
10:                 Score against ground truth Y_b:
11:                 **if** $\hat{a}_i = Y_b$ **then**
12:                     $r_i^{\text{hard}} = 1$
13:                 **else**
14:                     $r_i^{\text{hard}} = 0$
15:                 **end if**
16:             **else**
17:                 $r_i^{\text{hard}} = 0$ {Penalize missing answer}
18:             **end if**
19:             Add auxiliary rewards: $r_i = r_i^{\text{hard}} + r_{\text{format}} + r_{\text{mention}}$
20:         **end for**
21:     **end for**
22:     Compute normalized advantages $\hat{A}_{i,t}$ using Eq. (4)
23:     Update θ via GRPO objective (Eq. 2) with KL divergence penalty (Eq. 5)
24: **end for**
25: **return** $\tilde{\theta}$ =0

Algorithm 2 Rbio-RLEMF: Reinforcement Learning with Experimental Model Feedback

---

Require: Dataset of prompts $\{X_i\}_{i=1}^N$ (without experimental labels)
Require: Pre-trained frozen model Φ (e.g., MLP, VCM)
Require: Model parameters θ implementing policy π_θ
Require: Reward transformation function η: maps model predictions to rewards in $[0, 1]$
Require: Hyperparameters: τ (temperature), G (generations per prompt), β (KL penalty), ϵ (clipping)
Ensure: Trained model with parameters $\tilde{\theta}$ implementing policy $\pi_{\tilde{\theta}}$

1: Initialize θ from supervised fine-tuned LLM
2: **for** each step $t = 1$ to T **do**
3:     Sample batch indices $b \subset \{1, \dots, N\}$ uniformly at random
4:     Retrieve batch $\{X_b\}$ from dataset
5:     **for** each prompt X_b in batch **do**
6:        **for** $i = 1$ to G **do**
7:           Generate sequence $o_i \sim \pi_\theta(\cdot \mid X_b)$ using model θ and policy π_θ
8:           Extract binary answer $\hat{a}_i$ from o_i (if existing)
9:           **if** answer $\hat{a}_i$ exists **then**
10:              Query frozen model: $\hat{p} = \Phi(X_b)$ {Model prediction}
11:              Transform prediction to reward: $r_i^{\text{soft}} = \eta(\hat{p}, \hat{a}_i) \in [0, 1]$
12:           **else**
13:              $r_i^{\text{soft}} = 0$ {Penalize missing answer}
14:           **end if**
15:           Add auxiliary rewards: $r_i = r_i^{\text{soft}} + r_{\text{format}} + r_{\text{mention}}$
16:        **end for**
17:     **end for**
18:     Compute normalized advantages $\hat{A}_{i,t}$ using Eq. (4)
19:     Update θ via GRPO objective (Eq. 2) with KL divergence penalty (Eq. 5)
20: **end for**
21: **return** $\tilde{\theta}$ =0

Algorithm 3 Rbio-RLPK: Reinforcement Learning from Prior Knowledge

---

Require: Dataset of prompts $\{X_i\}_{i=1}^N$ (without labels)
Require: Knowledge source KS (e.g., Gene Ontology)
Require: Model parameters θ implementing policy π_θ
Require: Knowledge scoring function ν: scores reasoning traces against prior knowledge
Require: Hyperparameters: τ (temperature), G (generations per prompt), β (KL penalty), ϵ (clipping)
Ensure: Trained model with parameters $\tilde{\theta}$ implementing policy $\pi_{\tilde{\theta}}$
 1: Initialize θ from supervised fine-tuned LLM
 2: **for** each step $t = 1$ to T **do**
 3:    Sample batch indices $b \subset \{1, \ldots, N\}$ uniformly at random
 4:    Retrieve batch $\{X_b\}$ from dataset
 5:    **for** each prompt X_b in batch **do**
 6:       Query knowledge source: $\{q_j^{\text{prior}}\} = \text{query\_KS}(X_b)$ {Retrieve relevant prior knowledge}
 7:       **for** $i = 1$ to G **do**
 8:          Generate sequence $o_i \sim \pi_\theta(\cdot \mid X_b)$ using model θ and policy π_θ
 9:          Extract gene_information o_i^{relevant} from o_i (from <gene> tags)
10:          **if** gene_information o_i^{trace} exists **then**
11:             Score gene_information against prior knowledge: $r_i^{\text{soft}} = \nu(o_i^{\text{trace}}, \{q_j^{\text{prior}}\})$
12:          **else**
13:             $r_i^{\text{soft}} = 0$ {Penalize missing gene information}
14:          **end if**
15:          Add auxiliary rewards: $r_i = r_i^{\text{soft}} + r_{\text{format}} + r_{\text{mention}}$
16:       **end for**
17:    **end for**
18:    Compute normalized advantages $\hat{A}_{i,t}$ using Eq. (4)
19:    Update θ via GRPO objective (Eq. 2) with KL divergence penalty (Eq. 5)
20: **end for**
21: **return** $\tilde{\theta}$ =0

Algorithm 4 Formatting Reward r_{format}

Require: Completion o_i
Require: Set of formatting constraints $\mathcal{F} = \{F_1, F_2, \ldots, F_k\}$
Ensure: Formatting reward $r_{\text{format}} \in [0, 1]$
 1: Initialize score vector $s = []$
 2: **for** each constraint $F_j \in \mathcal{F}$ **do**
 3:    **if** F_j is satisfied in o_i **then**
 4:       Append 1.0 to s
 5:    **else**
 6:       Append 0.0 to s
 7:    **end if**
 8: **end for**
 9: $r_{\text{format}} = \frac{1}{|\mathcal{F}|} \sum_{j=1}^{|\mathcal{F}|} s_j$
10: **return** r_{format} =0

Algorithm 5 Mention Reward r_{mention}

Require: Completion o_i
Require: Set of desired terms $\mathcal{T} = \{t_1, t_2, \ldots, t_m\}$
Ensure: Mention reward $r_{\text{mention}} \in [0, 1]$
 1: Extract reasoning trace o_i^{trace} from o_i (from `` tags)
 2: Initialize score vector $s = []$
 3: **for** each term $t_j \in \mathcal{T}$ **do**
 4:     **if** t_j appears in o_i^{trace} **then**
 5:         Append 1.0 to s
 6:     **else**
 7:         Append 0.0 to s
 8:     **end if**
 9: **end for**
10: $r_{\text{mention}} = \frac{1}{|\mathcal{T}|} \sum_{j=1}^{|\mathcal{T}|} s_j$
11: **return** $r_{\text{mention}} = 0$

1.13 Hard-Ground Truth Experiments

1.13.1 Training on Experimental Data improves performance compared to baselines

FIGURE 12. | **Comparison of rbio-EXP with Qwen baselines**. Our refers to rbio-EXP trained on one cell line at a time.

The composite radar plots 12 compare a Qwen-based language model that we further optimized with reinforcement learning (GRPO) and a hard verifier against three purely instruction-tuned baselines (Qwen2.5-3 B, Qwen2.5-7 B and Qwen3-32 B). Across four independent test cell-line datasets (K562, RPE1, HEPG2 and Jurkat) our hard-verified RL model encloses the baselines on every axis, namely, Accuracy, Precision, Recall (TPR), F1, Specificity (TNR) and AUC-ROC, indicating superior performance for all six metrics. The largest absolute gains concentrate on Recall, F1 and AUC-ROC, where the new model reaches radii of 0.7–0.9 while the baselines remain below 0.4. These improvements show that coupling reinforcement learning to the hard verifier causes the policy to capture a far larger share of true positives without materially inflating false-positive rates, thereby harmonizing sensitivity with specificity. The benefit is consistent across heterogeneous cell types and does not depend on parameter count:

the 32-billion-parameter baseline performs almost identically to its 3-billion counterpart, underscoring that task-aligned objectives, here enforced by hard verification on experimental data, outweigh scale alone. Because missed positives are costlier than occasional false alarms in downstream wet-lab validation, the balanced operating point delivered by hard-verified RL training translates directly into practical utility. Finally, the consistently high AUC-ROC (around 0.9) suggests that the learned policy generalizes its reasoning rather than memorizing characteristics of any single dataset. Taken together, these findings demonstrate that injecting experimentally grounded hard verification into the reinforcement-learning loop is a powerful mechanism for elevating reasoning-centric LLMs beyond what can be achieved with instruction tuning and parameter scaling alone.

1.13.2 Training on experimental data from multiple sources shows increased performance, showing there is beneficial cross-dataset knowledge transfer

FIGURE 13. | **Comparison of rbio-EXP trained on training splits of all cell lines vs trained on training splits of cell lines outside of the test distribution.**. Our refers to rbio-EXP trained on one cell line at a time.

Across all four evaluation datasets, the model trained jointly on the complete, heterogeneous collection ("Trained on all", blue polygons) delivers the most consistent and highest-scoring performance envelope. Accuracy, recall (TPR), specificity (TNR) and AUC-ROC cluster tightly around 0.88-0.92, while F1-scores remain around 0.80 despite the precision penalty introduced by class imbalance in these assays.

Withholding the target dataset during training ("Trained without X", orange) causes a uniform yet modest degradation. Accuracy, AUC-ROC and TNR typically fall by 2-4 percentage points, and F1-score by about 5 points. Importantly, however, this leave-one-out model still outperforms the best single-source baseline (green) by large margins ($\geq$ 15 points in accuracy and $\geq$ 0.20 in AUC-ROC on every dataset). The result demonstrates that information learned from the remaining three datasets generalizes meaningfully to the held-out system, providing clear evidence of positive transfer rather than over-fitting to individual batches or cell-line specific artifacts.

The shape of the radar plots is also instructive. Metrics that depend on negative class recognition (specificity, AUC-ROC) decline only slightly when a dataset is omitted, whereas precision and F1, which require well-calibrated decision boundaries for the minority class, drop more noticeably. This pattern implies that shared features across experiments chiefly support broad discrimination between classes; fine-grained calibration still benefits from direct exposure to the target distribution.

Taken together, these observations indicate that aggregating experimental data from disparate sources yields a richer representation space and endows the model with a transferable prior that boosts generalization to unseen datasets. Consequently, the incremental cost of acquiring and harmonizing additional training datasets is rewarded with measurable gains in robustness and predictive power, an encouraging result for scaling this approach to new cell types or assay modalities.

1.13.3 Analysis of training on in and out-of-distribution experimental data

FIGURE 14. | **Analysis on performance on rbio models trained on experimental data for in-distribution vs out of distribution datasets**. rbio-EXP-one-cell-line is trained on one the training split from one cell line at a time and tested on the test split of that cell line (in-distribution), rbio-EXP-all-cell-lines is trained on the training splits on all four cell lines and tested on separate test splits, and rbio-EXP-leave-one-out is trained on the three cell lines not in test (out-of distribution)