ARCADE: Controllable Codon Design from Foundation Models via Activation Engineering

Jiayi Li, Litian Liang, Shiyi Du,

Shijie Tang, Hong-sheng Lai, Carl Kingsford*

Ray and Stephanie Lane Computational Biology Department, School of

Computer Science, Carnegie Mellon University, Pittsburgh, PA,

15217, US

{lijiayi, litianl, shiyid, shijiet, hongshel, carlk}@cs.cmu.edu

Abstract

Codon sequence design is crucial for generating mRNA sequences with desired functional properties for tasks such as creating novel mRNA vaccines or gene editing therapies. Yet existing methods lack flexibility and controllability to adapt to various design objectives. We propose a novel framework, ARCADE, that enables flexible control over generated codon sequences. ARCADE is based on activation engineering and leverages inherent knowledge from pretrained genomic foundation models. Our approach extends activation engineering techniques beyond discrete feature manipulation to continuous biological metrics. Specifically, we define biologically meaningful semantic steering vectors in the model's activation space, which directly modulate continuous-valued properties such as the codon adaptation index, minimum free energy, and GC content without retraining. Experimental results demonstrate the superior performance and far greater flexibility of ARCADE compared to existing codon optimization approaches, underscoring its potential for advancing programmable biological sequence design.

Keywords: mRNA design; controllable sequence generation; foundation model post training; foundation model for genomics; and activation engineering

---

*Corresponding author.

1 Introduction

Codon design aims to select synonymous codons to construct mRNA sequences that encode the same protein, yet with custom functional attributes. This requires precise control over multiple properties such as codon usage bias, secondary structure stability, and desired protein expression levels. These properties are crucial for controlling mRNA translation dynamics and have direct implications in developing mRNA-based vaccines and medicines [1, 2, 3, 4].

Previous research has tackled the codon design problem on multiple fronts but has largely focused on optimizing a narrow set of properties: codon usage bias (codon adaptiveness index, CAI) and RNA structural stability (minimal free energy, MFE). A lack of explicit, flexible, and fine-grained control over diverse sequence properties is prevalent in both algorithmic approaches [5, 6] and deep learning-based methods [7, 8].

This gap is also present in the more general field of biological sequence generation. Prior works often lack explicit control mechanisms [9, 10, 11] or rely on training auxiliary prediction models for gradient-based guided generation [12, 13, 14, 15], where the performance of the predictors and the need for large-scale labeled data severely limit their utility in controlling diverse properties.

Among the techniques developed for controllable generation in language models (LMs), *activation engineering* fully utilizes the LM's inherent knowledge, modifying the LM's internal activations during inference to steer model outputs towards desired properties [16, 17]. Requiring no LM-specific designs or extensive training as earlier methods do [18, 19, 20, 21, 22], activation engineering promises to be a viable solution to controllability in codon design and biological sequence generation.

Still, there are two major hurdles in the development of controllable codon design methods. First, in natural language processing, controllable generation typically steers discrete and human-interpretable properties, such as sentiment, topic, or styles [20, 23, 21, 19, 24]. However, properties in genomics, such as biological functionality (e.g., protein expression), structural integrity, and translation rate, are often continuous and require computational models or experimental assays for quantification. This highlights a compelling need to extend controllable generation methods, in particular activation engineering, to fine-grained control over continuous properties for genomics sequence design tasks.

Second, current biological foundation models [1, 25, 26, 27, 28] largely adopt encoder-only architectures, which provide powerful pretrained contextual embeddings useful for various downstream tasks, but do not support direct generation as current decoder-only LMs do. This necessitates modifications to the biological foundation models to grant them generation-like capabilities that will facilitate the integration of controllable generation methods developed for LMs.

To bridge these gaps, we propose ARCADE (**A**ctivation enginee**R**ing for **C**ontroll**A**ble co**D**on d**E**sign), a framework that enables attribute-specific control over codon sequences through activation engineering on pretrained biological foundation models. Instead of optimizing for individual attributes, ARCADE aims to adapt to various desired biological properties such as codon adaptive index (CAI), minimized free energy (MFE), protein expression, and their combinations.

ARCADE leverages activation engineering to enable controllable codon sequence generation under synonymy constraints, which guarantee the codons translate to the same protein sequence. We prepare and inject biologically meaningful semantic steering vectors into a foundation model's latent activation space, allowing direct and flexible control over diverse continuous attributes during generation. To enable generation-like control for codon design, ARCADE augments encoder-only biological foundation models with a token classification objective, reframing codon sequence generation as a position-wise prediction problem.

ARCADE offers flexibility across multiple objectives, fine-grained, continuous control over each attribute, and requires no training or large-scale labeled data. Our implementation is available at `https://github.com/Kingsford-Group/arcade`.

Our contributions are as follows:

- We develop the first deep learning method for controllable codon sequence design, enabling flexible multi-attribute steering without model training.

- We enable generation-like control of the outputs of encoder-only biological foundation models through token classification, which leverages their reconstruction capabilities.

- We establish a generalizable activation engineering framework capable of handling continuous-valued biological properties, creating biologically meaningful steering vectors that enable explicit control over key biological attributes such as protein expression, mRNA stability, and codon usage diversity.

- We extensively validate our method on various codon design objectives and their combinations, showing that it outperforms previous methods in a wide range of settings, allowing far more flexibility to adapt to new design goals.

2   Related work

Controllable text generation   Controllable text generation enables the steering of language model outputs in terms of style, content, or factuality. CTRL [21] introduces control codes in conditional transformers. Li et al. propose prefix tuning [29], which enables lightweight adaptation by optimizing small continuous prompts. PPLM [19] offers inference-time control using external attribute classifiers. Subramani et al. [16] and

Hernandez et al. [30] develop learnable activation-based methods that modify internal representations to reflect specific knowledge or behavior.

Meanwhile, training-free activation engineering techniques have gained popularity for their efficiency and flexibility. ActAdd [17] steers generation using the activation difference between prompt pairs. CAA [31] refines this using the average of the activation differences between contrast prompt sets to control behaviors like hallucination or sentiment. Konen et al. [24] allow nuanced control of text style by averaging activations from examples with desired stylistic attributes. These approaches mark significant progress toward efficient, flexible, and precise text generation control, though none have been applied to the codon design task and biological sequence generation in general.

Genomic language models Advancements in large language models (LLMs) have spurred the development of Genomic Language Models (gLMs), which are large-scale pretrained foundation models capable of performing multiple tasks in understanding and interpreting biological sequences, particularly DNA and RNA sequences. For example, DNABERT [25], Nucleotide Transformer [26], HyenaDNA [32], and EVO [33] are all large-scale gLMs for DNA sequence modeling.

For RNA sequence modeling, gLMs like RNABERT [34] and BigRNA [35] are trained on general RNA sequences, while Li et al. [1] developed a gLM that is more suitable for mRNA and protein expression-related tasks by using the codons of RNA sequences as input. We leverage the representation power of gLMs to extract embeddings of codon sequences, which lie at the basis of ARCADE.

Codon design Early computational methods for codon design focus on matching the codon usage frequency of the target gene to that of the host organism. For instance, JCAT [5] greedily selects the most frequent synonymous codons in the identified highly expressed genes of the host. More recent algorithms address the complexity and multi-objective nature of codon design. LinearDesign [6] uses lattice parsing to navigate the massive search space for possible codon sequences and jointly optimizes the codon adaptation index (CAI) and minimum free energy (MFE), but its decoding complexity scales quadratically with input length, making it computationally expensive to design long sequences. These non-machine learning methods lack flexibility and generalizability, and can be time-consuming when exploring many variations.

Machine learning approaches learn latent features directly from sequences to guide codon design. They have also achieved linear-time inference and benefited from GPU acceleration. Fu et al. [7] used a BiLSTM-CRF network and treated codon design as a sequence annotation problem, where they mapped amino acid sequences to codon sequences based on the codon usage patterns in the host genome. CodonBERT [8], a BERT-based architecture, applies cross-attention between amino acid and codon sequences

to learn contextual codon preferences. RNADiffusion [14], a latent diffusion model that maps RNA sequences to a low-dimensional latent space, enables guided generation by leveraging gradients from reward models operating on the same latent space.

While these machine learning methods can capture generalizable latent sequence features, they lack flexibility in codon design objectives. Our work bridges this gap by exploring activation engineering to flexibly steer codon sequences, imbuing them with a broad spectrum of desired properties.

3 Method

3.1 The codon design problem

The codon design problem is defined as rewriting a given input codon sequence to promote specific biological properties while preserving the encoded protein sequence. Formally, let $\mathcal{C}^{\text{in}} = c_1^{\text{in}}, c_2^{\text{in}}, \ldots, c_n^{\text{in}}$ be an input codon sequence, where each codon c_i^{in} translates to amino acid a_i via the translation function $T(c_i^{\text{in}}) = a_i$. The objective is to construct an output sequence $\mathcal{C}^{\text{out}} = c_1^{\text{out}}, c_2^{\text{out}}, \ldots, c_n^{\text{out}}$, such that $T(c_i^{\text{out}}) = T(c_i^{\text{in}})$ for each i and $\mathcal{C}^{\text{out}}$ exhibits more favorable biological properties. This latter goal is a variable and multi-objective function that depends on the use case and users' desires, which are manifested by the user selecting a set of properties P for which they want to optimize. The varied properties in Section 4.2 provide extensive examples of these objective functions.

3.2 Activation engineering for codon design

To optimize a set of user-specified biological properties P, we apply activation engineering (Figure 1). For an input sequence x, we modify the activations of the frozen foundation model to steer its output toward a desired direction, such as increasing or decreasing the value of a specified property $p \in P$.

To steer towards properties P, a steering vector $\mathbf{v}_p^{(i)}$ is created for each layer i and each $p \in P$. A linear combination of these vectors is added to the original activations $\mathbf{a}^{(i)}(x)$ at layer i (Figure 1(c)):

$$\hat{\mathbf{a}}^{(i)}(x) = \mathbf{a}^{(i)}(x) + \sum_{p \in P} \lambda_p \mathbf{v}_p^{(i)}, \tag{1}$$

where $\hat{\mathbf{a}}^{(i)}(x)$ denotes the modified activation at layer i, $\mathbf{a}^{(i)}(x)$ denotes the original activation, and the λ_p values control the steering strengths for each goal.

To construct the steering vector $\mathbf{v}_p^{(i)}$ for a property p, we label training sequences $\mathcal{S}$ with high values of the property p by $\mathcal{S}_{p^+}$ and low values as $\mathcal{S}_{p^-}$. We denote by $\bar{\mathbf{a}}_{p^+}^{(i)}$ and $\bar{\mathbf{a}}_{p^-}^{(i)}$ the mean activation vectors at layer i for sequences with high and low values of p,

Figure 1: Overview of ARCADE. Given an input codon sequence, (a) when there is no steering, the foundation model reconstructs the sequence using a token classification head. (b, c) To guide generation toward desired properties, activation engineering is performed by injecting the learned steering vectors into the layer activations of a frozen foundation model. (d) Steering vectors are constructed from the activation differences between high- and low-value examples, mutated from a set of seed sequences, and scored with a property-specific function.

respectively. The steering vector toward a higher value of the property p is defined as

$$\mathbf{v}_p^{(i)} = \bar{\mathbf{a}}_{p^+}^{(i)} - \bar{\mathbf{a}}_{p^-}^{(i)}. \tag{2}$$

To obtain $\mathcal{S}_{p^+}$ and $\mathcal{S}_{p^-}$ samples for each property p, we propose a data-driven construction method tailored for continuous-valued biological attributes, as illustrated in Figure 1(d). Specifically, given a set of seed codon sequences, we introduce property-specific directed mutations to generate variants of high and low values of that property. The mutation method depends on the property of interest (see Appendix A.2 for details). The high- and low-value variants are treated as positive ($\mathcal{S}_{p^+}$) and negative ($\mathcal{S}_{p^-}$) examples, respectively, and the steering vector is computed as the difference in average layer-wise

activations between these two groups.

In summary, our activation engineering method enables gradient-free, property-aware control over biological sequences, fully eliciting the inherent knowledge in foundation models to fulfill fine-grained, continuous biological design objectives.

3.3 Token classification for sequence reconstruction

While activation engineering is typically applied to decoder-only models with generative capabilities, genomics foundation models are typically encoder-only models [36, 32, 25, 1]. To adapt an encoder-only model for codon sequence generation, we introduce a token classification head that reconstructs the mRNA codon sequences, effectively approximating a decoder-like function (Figure 1(a)).

Let $\mathcal{C} = c_1, c_2, \ldots, c_n$ denote a codon sequence of length n, where each c_i belongs to the vocabulary $\mathcal{V}$ of the 64 possible codons. The model encodes the input into contextual representations $\mathbf{H} = \mathbf{h}_1, \mathbf{h}_2, \ldots, \mathbf{h}_n$, where $\mathbf{h}_i \in \mathbb{R}^d$ denotes the hidden representation at position i. A token classification head maps each $\mathbf{h}_i$ to a categorical distribution over the possible codons:

$$\mathbf{z}_i = \mathrm{softmax}(W\mathbf{h}_i + b), \tag{3}$$

where $W \in \mathbb{R}^{|\mathcal{V}| \times d}$ and $b \in \mathbb{R}^{|\mathcal{V}|}$ are learnable parameters. The model is trained to minimize the cross-entropy loss between the predicted distribution and the ground-truth codon label y_i:

$$\mathcal{L}_{\mathrm{recon}} = -\sum_{i=1}^{n} \log p(y_i \mid \mathbf{h}_i). \tag{4}$$

To ensure synonymy, we apply a codon-level mask during training that restricts predictions to codons encoding the same amino acid as the original input (see Algorithm 1 in Appendix A.3). This formulation casts codon reconstruction as a constrained token-level classification task, enabling biologically valid and controllable sequence generation through subsequent activation steering.

4 Experiments

For all our experiments, we build ARCADE on the codon-level foundation model introduced by Li et al. [1], which we then fine-tuned on the codon token classification task (see Appendix A.1 for more details of the foundation model). We demonstrate that ARCADE enables effective and flexible control over a wide range of attributes for codon design.

4.1 Datasets

Training and evaluation data We extract protein-coding transcripts from the GEN-CODE Human Release 47 (GRCh38.p14) annotation [37] (abbreviated "GENCODE"). We isolate the coding regions (CDSs) from 85,099 transcripts. To conform to the input length limit of 1,024 codons of the foundation model [1], we filter out sequences longer than 3,072 base pairs. The dataset is split into training and testing sets at a 9:1 ratio, while ensuring all transcript variants of the same gene are assigned to the same split to prevent information leakage between transcripts of the same gene. The training set is used both to fine-tune the token classification head and to compute activation statistics for steering vector construction. The test set contains 8,508 sequences and is held out for evaluation.

mRFP evaluation dataset For evaluation on experimentally measured monomeric Red Fluorescent Protein (mRFP) expression, we use the data from Nieuwkoop et al. [38], which contains 1,459 variants of the mRFP gene annotated with their measured expression levels. This benchmark enables us to assess the effectiveness of steering methods on a real-world, functionally grounded biological property.

4.2 Diverse codon properties

To evaluate whether ARCADE generalizes across diverse biological and functional properties of codon sequences, we applied it to generate sequences that optimize a wide range of metrics. Details of the metric calculations are provided in Appendix A.8.

Codon usage metrics The *Codon Adaptation Index (CAI)* is widely used to evaluate how closely a codon sequence aligns with the preferred codon usage in a given organism [39]. CAI values range from 0 to 1 (unitless), with higher values implying greater compatibility with the host's translational machinery. Optimizing CAI has been shown to enhance the efficiency in protein translation [40, 41].

Structure-related metrics *Minimum Free Energy (MFE)* [42], measured in kcal/mol, reflects the thermodynamic stability of mRNA folding. We report *Negated Minimum Free Energy (NMFE)* in the results, the additive inverse of MFE. Thus, higher NMFE values correspond to more stable mRNA structures. *GC content* measures the fraction of guanine and cytosine nucleotides in the sequence (range 0-1). Higher GC content is typically correlated with increased structural stability [43].

Immunity-related metrics CpG and UpA dinucleotide densities are known to affect the innate immune response. The *CpG density* and *UpA density* metrics are computed as

the number of `CG` or `UA` dinucleotides per 100 base pairs(bp) of sequence [44]. Modulating these densities can attenuate viral replication and enhance vaccine safety [45].

Functional outputs The expression level of mRFP (metric $mRFP$) serves as a proxy for evaluating the functional impact of codon optimization strategies. Increasing the expression of a gene (such as mRFP) is a typical goal for improving the efficacy of gene therapies [46, 38]. The distribution of mRFP expression values in the training data is presented in Appendix Figure 5.

4.3   Steering single properties

For each codon property, we apply ARCADE to steer toward either higher ("Positive") or lower ("Negative") values. Positive steering results in consistently elevated values, while negative steering leads to decreased values relative to the wild-type ("WT") sequence (see mean values in Table 1 and distributions in Figure 4, Appendix A.4). This demonstrates the controllability of ARCADE and its broad applicability across multiple aspects of codon design objectives.

Table 1: Effective control of the metrics in Section 4.2 with ARCADE. "WT" denotes the unmodified wild-type input sequences. mRFP expression is evaluated on the dataset from Nieuwkoop et al. [38], and all other metrics are averages over GENCODE test set (see Section 4.1). ($\lambda = 1$.)

	Translation (CAI)	Stability (NMFE)	GC content	CpG density	UpA density	mRFP expression
Positive	0.964	350.42	0.671	8.168	7.024	11.110
WT	0.778	331.09	0.522	3.376	3.159	10.162
Negative	0.568	305.22	0.325	1.330	1.915	8.129

We examine the effect of steering strength λ on CAI and NMFE. Increasing λ consistently alters the generated sequences in the intended direction (Figure 2). For CAI, values of λ below approximately 0.25 have a negligible effect, followed by a rapid increase as λ rises from 0.25 to 2, and saturates around $\lambda = 4$. NMFE shows a similar monotonic trend, with saturation also occurring at a threshold around $\lambda = 4$. This indicates that λ serves as an effective tuning knob for balancing native sequence properties and desired objectives. For both metrics, we observe that the range $\lambda \in [0.5, 4]$ is the most appropriate regime: strong enough to meaningfully influence sequence generation yet without exceeding the model's representation capacity. This provides some practical guidance on how to choose λ (see more discussion in Section 4.5).

4.4   Steering pairs of properties

Flexible steering of pairs of desired properties is important for practical applications where codon sequences must satisfy multiple biological constraints, such as increasing

Figure 2: Effect of steering strength λ on sequence-level properties. **Left:** CAI improves rapidly for $\lambda \in [0.5, 4]$ and plateaus for $\lambda > 4$. **Right:** NMFE increases with larger λ and also saturates around $\lambda = 4$. The exact values for each point are provided in the Tables 7 and 8 in Appendix A.5.

expression while maintaining structural stability. We demonstrate ARCADE's effectiveness in simultaneously steering towards the property pairs CAI + NMFE, CAI + GC content, and mRFP + NMFE.

Table 2: Joint steering across multiple objective pairs. Each row block corresponds to a pair of target properties. "WT" denotes the unmodified wild-type input sequences. "Single" steers toward a single objective ($\lambda = 1$). "Joint Steering" jointly steers the two directions, both using $\lambda_p = 1$ (Eq. 1).

Objective Pair	Metric	WT	Single	Joint Steering
CAI + NMFE	CAI	0.778	0.964	0.978
	NMFE	331.09	350.42	424.05
CAI + GC	CAI	0.778	0.964	0.978
	GC	0.522	0.671	0.672
mRFP + NMFE	mRFP	10.162	11.110	11.144
	NMFE	195.97	223.37	225.93

As shown in Table 2, joint steering improves both target metrics relative to the wild-type (WT) baseline. For example, in CAI + NMFE, CAI increases from 0.778 to 0.978, while NMFE improves from 331.09 to 424.05. Similar trends hold for joint steering of CAI + GC content, and mRFP expression + NMFE, where both a structural and a functional property are jointly improved over the WT baseline, and matching or exceeding results by single-property steering. These results demonstrate that ARCADE can support robust, multi-objective control across translational and structural features and even real-valued functional outputs.

To better understand the effectiveness of multi-objective steering, we analyze the geometry of steering directions in the metrics space. Figure 3 visualizes the average steering effect induced by ARCADE for CAI, NMFE, and their combination with varied steering strength.

Figure 3: Visualization of steering directions in the metrics space. The vectors represent average value shifts steered by ARCADE for CAI, NMFE, and their combination (CAI+NMFE). This structure suggests the existence of a controllable region in the model's latent space (top right), where multi-objective trade-offs can be navigated via vector-based interpolation.

Although CAI and NMFE are generally considered to be in trade-off, ARCADE is able to improve both CAI and NMFE at the same time by steering solely for CAI or NMFE (see also Section 4.5). This suggests that, within the model's representation space, there exists a region where the two objectives can be jointly optimized without strong conflict. ARCADE also exposes a locally controllable subspace within the model's internal representation, allowing navigation of the trade-offs between objectives. Within this subspace, the steering strength λ acts as a continuous control parameter, enabling flexible balancing between objectives without model retraining or architectural modification. Instead of collapsing toward one objective, the model responds to joint steering by exploring a shared region of the representation space where both objectives can improve.

4.5 Comparison with other methods

Other methods are typically limited to optimizing a narrow selection of metrics. JCAT [5] only optimizes for CAI. CodonBERT [8] and BiLSTM-CRF [7] only target CAI and MFE, yet they do not allow control of the trade-off between the two metrics.

Though ARCADE is designed for flexible control, it is competitive with these baseline methods on the metrics for which they aim to optimize (Tables 3 and 4). For each objective (CAI, NMFE), we select the best-performing single-property models via a grid search on the training data over steering strengths $\lambda \in \{0.5, 1, 2, 4, 10\}$, denoted as CAI_{single} and $NMFE_{single}$. The joint steering model (CAI+NMFE) applies both directions

simultaneously with $\lambda = 1$ and achieves competitive or superior results on both metrics compared to the other methods.

Table 3: Comparison of ARCADE with CodonBERT and JCAT on CAI and NMFE metrics. Within ARCADE, CAI_{single} and $NMFE_{single}$ denote the best-performing single-property models (see Table 9 in Appendix A.6), and "CAI+NMFE" applies both steering directions simultaneously. "unit NMFE" is NMFE normalized by sequence length. The best results among the last three columns are in bold.

| | WT | ARCADE | | | CodonBERT | JCAT |
		CAI_{single}	$NMFE_{single}$	CAI+NMFE		
CAI	0.773	0.978	0.849	0.978	0.967	1.0
NMFE	331.09	401.27	439.55	424.05	400.71	369.18
unit NMFE	0.324	0.384	0.435	0.413	0.399	0.363

Table 4: Comparison of ARCADE with BiLSTM-CRF on a subset of sequences with coding sequence length < 1500, to match the input length constraints of the BiLSTM-CRF model. The best results of the last two columns are marked in bold.

| | WT | ARCADE | | | BiLSTM-CRF |
		CAI_{single}	$NMFE_{single}$	CAI+NMFE	
CAI	0.778	0.981	0.851	0.979	0.750
NMFE	220.26	341.68	377.87	362.20	245.56
unit NMFE	0.322	0.381	0.436	0.411	0.362

We also compared ARCADE with LinearDesign [6], a recent non-machine learning method for jointly optimizing CAI and MFE. For fairness, we adopt their combination mode (with internal parameter $\lambda = 4$, distinct from our method). Due to the high computational cost of LinearDesign, we evaluate the methods in Table 5 on a randomly selected subset of 100 coding sequences from the full test set (size 8, 508). We also run the second-best method, CodonBERT, from Tables 3 and 4 on this data set.

Table 5: Comparison with LinearDesign. For mRFP expression, ARCADE applies steering vectors that improve mRFP expression. For CAI and NMFE, ARCADE adopts joint steering combining CAI and NMFE vectors (both with $\lambda = 1$).

	ARCADE	CodonBERT	LinearDesign
mRFP expression	11.186	9.916	9.570
CAI	0.977	0.964	0.944
NMFE	416.30	395.46	568.172

As shown in Table 5, all methods achieve comparable CAI values, while LinearDesign produces the most stable sequences in terms of NMFE. However, for mRFP expression,

ARCADE significantly outperforms both LinearDesign and CodonBERT. This result underscores the flexibility of ARCADE in steering properties beyond CAI and MFE, including experimentally measured functional outcomes.

Even for 100 sequences, LinearDesign requires over 8 hours using two Intel(R) Xeon(R) CPU E5-2690v2 3.00GHz (20 cores), highlighting its limitations for large-scale codon design tasks. In contrast, ARCADE enjoys superior scalability, optimizing these 100 sequences in 16 seconds, including model loading time, using a single NVIDIA A100 GPU with 40GB of memory.

4.6   Ablation studies

To verify that the observed effects are attributable to meaningful steering directions rather than mere perturbation, we compare steering on CAI and NMFE with random steering perturbations and also with steering strength $\lambda = 0$. As shown in Table 1, positive steering raises CAI by 24.7%, increases GC content by 28.5%, and improves NMFE by 5.8% relative to the wild-type baseline, and negative steering reduces CAI by 26.5%, decreases GC content by 37.7%, and lowers NMFE by 7.8%.

In contrast, applying a random steering vector, which is constructed to have the same shape and magnitude as the learned steering vector but filled with random values, or setting the steering strength to zero, results in values nearly identical to those of the wild-type sequence, within 0.01% change relative to the value of wild-type (Table 6). These results confirm that the observed effects do not arise from arbitrary perturbations or noise, corroborating that our steering directions are both informative and closely linked to the biological properties of interest.

Table 6: Ablation study. "Random" applies random steering vectors with the same ℓ_2 norm as the original vectors. "$\lambda = 0$" applies no steering at all.

	CAI	NMFE	GC content
WT	0.778	331.09	0.522
Random	0.778	331.12	0.522
$\lambda = 0$	0.778	331.12	0.522

5   Discussion

In this paper, we introduce ARCADE, a flexible and generalizable framework for controllable codon sequence generation. Unlike prior codon design methods, which focus on optimizing a fixed, narrow set of metrics, typically CAI and MFE, ARCADE enables fine-grained, multi-objective control over diverse biological properties, including codon usage, secondary structure stability, nucleotide composition, immune-related motifs, and

even experimentally measured expression levels. This process only depends on steering vectors extracted from pretrained foundation models. Other methods that optimize CAI and MFE do not incidentally optimize other metrics such as mRFP expression.

One key insight is that the latent space of pretrained codon language models captures biologically meaningful directions. ARCADE exploits this structure to enable flexible control, supporting both single- and multi-objective generation. Even for properties often considered in trade-off (e.g., CAI vs. MFE), ARCADE identifies directions that jointly improve both metrics towards a Pareto-like trade-off space, offering a new perspective on optimization in genomics design tasks.

Despite its flexibility, ARCADE has some constraints. Its effectiveness depends on the inductive biases of the underlying foundation model and the natural sequences from which the steering vectors were constructed. As a result, steering is confined to biologically plausible regions of the sequence space, which may be good for some applications and limiting for others. We have not evaluated the performance of the model on more than two objectives simultaneously, and it is likely that as the number of objectives increases, the approach may degrade. Moreover, ARCADE applies only global, whole-sequence control and does not provide sequence-specific or position-aware editing.

Future work could address these gaps by integrating local feedback mechanisms or gradient-based refinement to support instance-level control. We also plan to extend this approach to other molecular metrics, such as DNA regulatory elements, and to explore nonlinear or learned steering vectors that adapt to different sequence contexts. Finally, integrating ARCADE into iterative design loops with experimental validation would further validate its utility for synthetic biology.

Acknowledgment

This work was supported in part by the US National Science Foundation [III-2232121] and the US National Institutes of Health [R01HG012470]. Conflict of Interest: C.K. is a co-founder of Ellumigen, Inc.

References

[1] Sizhen Li, Saeed Moayedpour, Ruijiang Li, Michael Bailey, Saleh Riahi, Lorenzo Kogler-Anele, Milad Miladi, Jacob Miner, Fabien Pertuy, Dinghai Zheng, et al. CodonBERT large language model for mRNA vaccines. *Genome Research*, 34(7):1027–1035, 2024.

[2] L Frelin, G Ahlen, M Alheim, O Weiland, C Barnfield, P Liljeström, and M Sällberg. Codon optimization and mrna amplification effectively enhances the immunogenicity of the hepatitis c virus nonstructural 3/4a gene. *Gene therapy*, 11(6):522–533, 2004.

[3] Zijun Wang, Fabian Schmidt, Yiska Weisblum, Frauke Muecksch, Christopher O Barnes, Shlomo Finkin, Dennis Schaefer-Babajew, Melissa Cipolla, Christian Gaebler, Jenna A Lieberman, et al. mrna vaccine-elicited antibodies to sars-cov-2 and circulating variants. *Nature*, 592(7855):616–622, 2021.

[4] Lei Miao, Yu Zhang, and Leaf Huang. mrna vaccine for cancer immunotherapy. *Molecular cancer*, 20(1):41, 2021.

[5] Andreas Grote, Karsten Hiller, Maurice Scheer, Richard Münch, Bernd Nörtemann, Dietmar C Hempel, and Dieter Jahn. Jcat: a novel tool to adapt codon usage of a target gene to its potential expression host. *Nucleic acids research*, 33(suppl_2):W526–W531, 2005.

[6] He Zhang, Liang Zhang, Ang Lin, Congcong Xu, Ziyu Li, Kaibo Liu, Boxiang Liu, Xiaopin Ma, Fanfan Zhao, Huiling Jiang, et al. Algorithm for optimized mrna design improves stability and immunogenicity. *Nature*, 621(7978):396–403, 2023.

[7] Hongguang Fu, Yanbing Liang, Xiuqin Zhong, ZhiLing Pan, Lei Huang, HaiLin Zhang, Yang Xu, Wei Zhou, and Zhong Liu. Codon optimization with deep learning to enhance protein expression. *Scientific reports*, 10(1):17617, 2020.

[8] Zilin Ren, Lili Jiang, Yaxin Di, Dufei Zhang, Jianli Gong, Jianting Gong, Qiwei Jiang, Zhiguo Fu, Pingping Sun, Bo Zhou, et al. Codonbert: a bert-based architecture tailored for codon optimization using the cross-attention mechanism. *Bioinformatics*, 40(7):btae330, 2024.

[9] Nathan Killoran, Leo J Lee, Andrew Delong, David Duvenaud, and Brendan J Frey. Generating and designing dna with deep generative models. *arXiv preprint arXiv:1712.06148*, 2017.

[10] Donatas Repecka, Vykintas Jauniskis, Laurynas Karpus, Elzbieta Rembeza, Irmantas Rokaitis, Jan Zrimec, Simona Poviloniene, Audrius Laurynenas, Sandra Viknander, Wissam Abuajwa, et al. Expanding functional protein sequence spaces using generative adversarial networks. *Nature Machine Intelligence*, 3(4):324–333, 2021.

[11] Ali Madani, Bryan McCann, Nikhil Naik, Nitish Shirish Keskar, Namrata Anand, Raphael R Eguchi, Po-Ssu Huang, and Richard Socher. Progen: Language modeling for protein generation. *arXiv preprint arXiv:2004.03497*, 2020.

[12] Simon Senan, Aniketh Janardhan Reddy, Zach Nussbaum, Aaron Wenteler, Matei Bejan, Michael I Love, Wouter Meuleman, and Luca Pinello. Dna-diffusion: Leveraging generative models for controlling chromatin accessibility and gene expression via synthetic regulatory elements. In *ICLR 2024 Workshop on Machine Learning for Genomics Explorations*, 2024.

[13] Lin Zongying, Li Hao, Lv Liuzhenghao, Lin Bin, Zhang Junwu, Chen Calvin Yu-Chian, Yuan Li, and Tian Yonghong. Taxdiff: taxonomic-guided diffusion model for protein sequence generation. *arXiv preprint arXiv:2402.17156*, 2024.

[14] Kaixuan Huang, Yukang Yang, Kaidi Fu, Yanyi Chu, Le Cong, and Mengdi Wang. Latent diffusion models for controllable rna sequence generation. *arXiv preprint arXiv:2409.09828*, 2024.

[15] Sophia Tang, Yinuo Zhang, Alexander Tong, and Pranam Chatterjee. Gumbel-softmax flow matching with straight-through guidance for controllable biological sequence generation. *arXiv preprint arXiv:2503.17361*, 2025.

[16] Matthew E. Peters Nishant Subramani, Nivedita Suresh. Extracting latent steering vectors from pretrained language models. *arXiv preprint arXiv:2205.05124*, 2022.

[17] Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering. *arXiv preprint arXiv:2308.10248*, 2023.

[18] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[19] Sumanth Dathathri, Andrea Madotto, Janice Lan, Jane Hung, Eric Frank, Piero Molino, Jason Yosinski, and Rosanne Liu. Plug and play language models: A simple approach to controlled text generation. *arXiv preprint arXiv:1912.02164*, 2019.

[20] Zhiting Hu, Zichao Yang, Xiaodan Liang, Ruslan Salakhutdinov, and Eric P Xing. Toward controlled generation of text. In *International conference on machine learning*, pages 1587–1596. PMLR, 2017.

[21] Nitish Shirish Keskar, Bryan McCann, Lav R. Varshney, Caiming Xiong, and Richard Socher. Ctrl: A conditional transformer language model for controllable generation. *arXiv preprint arXiv:1909.05858*, 2019.

[22] Abhishek Panigrahi, Nikunj Saunshi, Haoyu Zhao, and Sanjeev Arora. Task-specific skill localization in fine-tuned language models. In *International Conference on Machine Learning*, pages 27011–27033. PMLR, 2023.

[23] Xun Liang, Hanyu Wang, Yezhaohui Wang, Shichao Song, Jiawei Yang, Simin Niu, Jie Hu, Dan Liu, Shunyu Yao, Feiyu Xiong, et al. Controllable text generation for large language models: A survey. *arXiv preprint arXiv:2408.12599*, 2024.

[24] Kai Konen, Sophie Jentzsch, Diaoulé Diallo, Peer Schütt, Oliver Bensch, Roxanne El Baff, Dominik Opitz, and Tobias Hecking. Style vectors for steering generative large language model. *arXiv preprint arXiv:2402.01618*, 2024.

[25] Yanrong Ji, Zhihan Zhou, Han Liu, and Ramana V Davuluri. DNABERT: pre-trained bidirectional encoder representations from transformers model for DNA-language in genome. *Bioinformatics*, 37(15):2112–2120, 2021.

[26] Hugo Dalla-Torre, Liam Gonzalez, Javier Mendoza-Revilla, Nicolas Lopez Carranza, Adam Henryk Grzywaczewski, Francesco Oteri, Christian Dallago, Evan Trop, Bernardo P de Almeida, Hassan Sirelkhatim, et al. The nucleotide transformer: Building and evaluating robust foundation models for human genomics. *BioRxiv*, pages 2023–01, 2023.

[27] Chloe Hsu, Robert Verkuil, Jason Liu, Zeming Lin, Brian Hie, Tom Sercu, Adam Lerer, and Alexander Rives. Learning inverse folding from millions of predicted structures. *ICML*, 2022.

[28] Zeming Lin, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, Allan dos Santos Costa, Maryam Fazel-Zarandi, Tom Sercu, Sal Candido, et al. Language models of protein sequences at the scale of evolution enable accurate structure prediction. *bioRxiv*, 2022.

[29] Percy Liang Xiang Lisa Li. Prefix-tuning: Optimizing continuous prompts for generation. *arXiv preprint arXiv:2101.00190*, 2021.

[30] Jacob Andreas Evan Hernandez, Belinda Z. Li. Inspecting and editing knowledge representations in language models. *arXiv preprint arXiv:2304.00740*, 2023.

[31] Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Turner. Steering llama 2 via contrastive activation addition. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15504–15522, Bangkok, Thailand, 2024. Association for Computational Linguistics.

[32] Eric Nguyen, Michael Poli, Marjan Faizi, Armin Thomas, Michael Wornow, Callum Birch-Sykes, Stefano Massaroli, Aman Patel, Clayton Rabideau, Yoshua Bengio, et al. HyenaDNA: Long-range genomic sequence modeling at single nucleotide resolution. *Advances in Neural Information Processing Systems*, 36, 2024.

[33] Eric Nguyen, Michael Poli, Matthew G Durrant, Armin W Thomas, Brian Kang, Jeremy Sullivan, Madelena Y Ng, Ashley Lewis, Aman Patel, Aaron Lou, et al. Sequence modeling and design from molecular to genome scale with Evo. *BioRxiv*, pages 2024–02, 2024.

[34] Manato Akiyama and Yasubumi Sakakibara. Informative RNA base embedding for RNA structural alignment and clustering by deep representation learning. *NAR Genomics and Bioinformatics*, 4(1):lqac012, 2022.

[35] Albi Celaj, Alice Jiexin Gao, Tammy TY Lau, Erle M Holgersen, Alston Lo, Varun Lodaya, Christopher B Cole, Robert E Denroche, Carl Spickett, Omar Wagih, et al. An RNA foundation model enables discovery of disease mechanisms and candidate therapeutics. *bioRxiv*, pages 2023–09, 2023.

[36] Gonzalo Benegas, Chengzhong Ye, Carlos Albors, Jianan Canal Li, and Yun S Song. Genomic language models: opportunities and challenges. *Trends in Genetics*, 2025.

[37] Adam Frankish, Mark Diekhans, Anne-Maud Ferreira, Rory Johnson, Irwin Jungreis, Jane Loveland, Jonathan M Mudge, Cristina Sisu, James Wright, Joel Armstrong, et al. Gencode reference annotation for the human and mouse genomes. *Nucleic acids research*, 47(D1):D766–D773, 2019.

[38] Thijs Nieuwkoop, Barbara R Terlouw, Katherine G Stevens, Richard A Scheltema, Dick De Ridder, John Van der Oost, and Nico J Claassens. Revealing determinants of translation efficiency via whole-gene codon randomization and machine learning. *Nucleic acids research*, 51(5):2363–2376, 2023.

[39] Paul M Sharp and Wen-Hsiung Li. The codon adaptation index-a measure of directional synonymous codon usage bias, and its potential applications. *Nucleic acids research*, 15(3):1281–1295, 1987.

[40] Zhiyong Zhou, Paul Schnake, Lihua Xiao, and Altaf A Lal. Enhanced expression of a recombinant malaria candidate vaccine in escherichia coli by codon optimization. *Protein expression and purification*, 34(1):87–94, 2004.

[41] Adnan B Al-Hawash, Xiaoyu Zhang, and Fuying Ma. Strategies of codon optimization for high-level heterologous protein expression in microbial expression systems. *Gene Reports*, 9:46–53, 2017.

[42] Robert M Dirks, Justin S Bois, Joseph M Schaeffer, Erik Winfree, and Niles A Pierce. Thermodynamic analysis of interacting nucleic acid strands. *SIAM review*, 49(1):65–88, 2007.

[43] Jing Zhang, CC Jay Kuo, and Liang Chen. Gc content around splice sites affects splicing through pre-mrna secondary structures. *BMC genomics*, 12:1–11, 2011.

[44] Daniel Beck, Millissia Ben Maamar, and Michael K Skinner. Genome-wide cpg density and dna methylation analysis method (medip, rrbs, and wgbs) comparisons. *Epigenetics*, 17(5):518–530, 2022.

[45] Colin P Sharp, Beth H Thompson, Tessa J Nash, Ola Diebold, Rute M Pinto, Luke Thorley, Yao-Tang Lin, Samantha Sives, Helen Wise, Sara Clohisey Hendry, et al. Cpg dinucleotide enrichment in the influenza a virus genome as a live attenuated vaccine development strategy. *PLoS Pathogens*, 19(5):e1011357, 2023.

[46] Aikaterini Alexaki, Gaya K Hettiarachchi, John C Athey, Upendra K Katneni, Vijaya Simhadri, Nobuko Hamasaki-Katagiri, Puja Nanavaty, Brian Lin, Kazuyo Takeda, Darón Freedberg, et al. Effects of codon optimization on coagulation factor ix translation and structure: Implications for protein and gene therapies. *Scientific reports*, 9(1):15449, 2019.

[47] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pages 4171–4186, 2019.

[48] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. Lora: Low-rank adaptation of large language models. *ICLR*, 1(2):3, 2022.

[49] Krishnamurthy Subramanian, Bryan Payne, Felix Feyertag, and David Alvarez-Ponce. The codon statistics database: A database of codon usage bias. *Molecular Biology and Evolution*, 39(8):msac157, 2022.

[50] Ronny Lorenz, Stephan H Bernhart, Christian Höner Zu Siederdissen, Hakim Tafer, Christoph Flamm, Peter F Stadler, and Ivo L Hofacker. ViennaRNA Package 2.0. *Algorithms for Molecular Biology*, 6(1):26, 2011.

A Appendix

A.1 Foundation model backbone

We build ARCADE upon the codon-level foundation model introduced by Li et al. [1], a BERT [47] encoder pretrained on over 10 million mRNA codon sequences spanning a broad range of species, including mammals, bacteria, and human viruses. We use its publicly released checkpoint and tokenizer (`https://github.com/Sanofi-Public/CodonBERT`). The authors imposed a custom artifact license and software license, which grants permission free of charge, for academic research purposes only and for non-commercial uses only, to any person from academic research or non-profit organizations to copy, use, or modify the software, models, software, datasets and/or algorithms, and associated documentation files. We fully adhere to these two licenses.

The model uses a 12-layer transformer encoder with 12 self-attention heads per layer and a hidden size of 768. Input sequences are tokenized at the codon level using a 64-token vocabulary representing the standard genetic codons. The model is pretrained using a masked codon modeling objective to capture contextual patterns of codon usage across diverse organisms.

We fine-tune the model using Low-Rank Adaptation (LoRA) [48] on the codon token classification task to enable sequence reconstruction. The model parameters are then frozen and used as the fixed backbone for all activation steering experiments. We use learning rate 5×10^{-5}, lora rank 32, lora scaling alpha 32, dropout 0.1. The accuracy of the fine-tuned model on the token classification test set is as high as 99.9%.

A.2 Deriving $\mathcal{S}_{p+}$ and $\mathcal{S}_{p-}$ samples via sequence mutations

To construct steering vectors for each metric, we adopt a metric-specific strategy. We randomly sample a subset of 77 coding sequences from the training set and apply controlled mutations to generate sequence variants.

For CAI, we create $\mathcal{S}_{p+}$ by mutating codons with high usage frequencies, and $\mathcal{S}_{p-}$ by replacing codons with less frequently used synonyms. A similar strategy is applied for GC content, CpG density, and UpA density.

For NMFE, which is a structural property that is not directly interpretable in terms of codon substitutions, we use LinearDesign [6] to generate high-stability sequences for $\mathcal{S}p^+$ (high NMFE), while $\mathcal{S}p^-$ (low NMFE) is generated via random synonymous perturbations.

For the mRFP dataset, which contains mutated coding sequences of the mRFP gene along with experimentally measured expression values, we directly use the top and bottom 3% of sequences ranked by expression as the $\mathcal{S}_{p+}$ (high-expression) and $\mathcal{S}_{p-}$ (low-expression) sets, respectively.

A.3 Synonymous codon mask

To ensure that only synonymous codon variations are considered during reconstruction, we define a mask M of shape $(B, \text{seqlen}, 4)$ on output logits of token classification head. The mask is constructed as Algorithm 1.

Algorithm 1 Generating synonymous codon mask

Require: Input codon sequence: input_codons $\in \mathbb{R}^{(B,\text{seqlen},4)}$
Require: Synonymous codon mapping: synonymous_codons_dict
Require: Nucleotide index mapping: nucleotide_index $= \{A : 0, T : 1, C : 2, G : 3\}$
Ensure: Output mask: $M \in \mathbb{R}^{(B,\text{seqlen},4)}$
 1: Initialize mask $M \leftarrow \mathbf{0}$
 2: **for** each batch index b **do**
 3:     **for** each nucleotide position p in $[1, \text{seqlen}/3]$ **do**
 4:         codon_start $\leftarrow p \times 3$
 5:         codon $\leftarrow$ input_codons$[b, \text{codon\_start} : \text{codon\_start} + 3]$
 6:         aa $\leftarrow$ codon_to_amino_acid(codon)
 7:         synonymous_codons $\leftarrow$ synonymous_codons_dict[aa]
 8:         **for** each synonymous codon syn_codon **do**
 9:             **for** each nucleotide position p' in $[0, 1, 2]$ **do**
10:                 nucleotide $\leftarrow$ syn_codon$[p']$
11:                 $M[b, \text{codon\_start} + p', \text{nucleotide\_index[nucleotide]}] \leftarrow 1$
12:             **end for**
13:         **end for**
14:     **end for**
15: **end for**
16: **return** M

A.4 Performance across single-property steering tasks

To complement the mean values reported in Table 1, Figure 4 presents the full distribution of property values under each steering direction: *Positive*, *Negative*, and *WT* (wild-type baseline). By showing the distributional effects across all sequences, this figure highlights ARCADE's ability to steer individual sequences, not just shift the mean.

A.5 Effect of steering strength λ

Tabel 7 and Table 8 show the exact values in Figure 2.

Table 7: Performance of CAI only steering with different steering strength λ.

Metric	WT	λ=0	λ=0.25	λ=0.5	λ=0.75	λ=1	λ=2	λ=3	λ=4	λ=5	λ=10	λ=20	CodonBERT
NMFE	331.09	331.12	331.29	365.49	408.50	417.69	415.59	405.43	401.27	399.46	396.58	394.47	400.71
CAI	0.777	0.778	0.7790	0.8544	0.9358	0.9638	0.9765	0.9765	0.9777	0.9776	0.9760	0.974	0.9669

Figure 4: Distribution of property values across the test set. Boxplots for each steering direction (Positive, Negative) and the wild-type (WT) baseline are presented. Variability in the distributions reflects differences in sequence length across the dataset.

Table 8: Performance of NMFE only steering with different steering strength λ.

	WT	λ=0	λ=0.5	λ=1	λ=1.5	λ=2	λ=4	λ=10	λ=20	CodonBERT
NMFE	331.09	331.12	331.42	350.42	390.18	422.16	438.94	439.55	440.19	400.71
CAI	0.777	0.778	0.779	0.794	0.812	0.833	0.860	0.849	0.849	0.967

A.6 Steering strength in comparison

In Table 9, we present the steering strengths used for the ARCADE models in Tables 3 and 4.

Table 9: Steering strength λ used in Tables 3 and 4.

	$\text{CAI}_{\text{single}}$	$\text{NMFE}_{\text{single}}$	CAI+NMFE
λ	4	10	(1,1)

A.7 Details in Figure 3

We report the steering strengths represented by the dots in Figure 3.

For the red dots (CAI steering), from bottom-left to top-right, the steering strengths λ are $0.5, 0.75, 1, 2$, respectively.

For the red dots (NMFE steering), from bottom-left to top-right, the steering strengths λ are $1, 1, 5, 2, 10$, respectively.

The combination of the λs for the yellow dots, as well as their performance in terms of CAI and NMFE, is presented in Table 10.

Table 10: The performance of joint steering in Figure 3.

$(\lambda_{\text{CAI}}, \lambda_{\text{MFE}})$	(1,4)	(1,2)	(1,1)	(4,1)	(10,1)
MFE	433.03	426.45	424.05	405.11	397.80
CAI	0.923	0.964	0.978	0.981	0.977

A.8 Calculation of metrics

Codon Adaptation Index (CAI) The *CAI* quantifies synonymous codon usage bias across species [39]. It is commonly used as a proxy for translational efficiency. Given an mRNA coding sequence r of length $|r|$ nucleotides, the number of codons is $n = |r|/3$. Let $\text{codon}(r, i)$ denoe the i-th codon in the sequence, for $0 \le i < n$. Each codon c is assigned a relative adaptiveness weight $w(c) \in [0, 1]$, which reflects its frequency relative to the most used synonymous codon for the same amino acid, based on a reference table (e.g., from the Codon Statistics Database [49]).

Then, the CAI of a sequence r is defined as the geometric mean of the adaptiveness values over all codons:

$$\text{CAI}(r) = \left(\prod_{i=0}^{n-1} w\big(\text{codon}(r, i)\big) \right)^{1/n} \tag{5}$$

which ranges from 0 to 1, with higher values indicating better alignment with the host's codon usage preferences [39].

Minimum Free Energy (MFE) The *MFE* of an RNA sequence reflects its predicted thermodynamic stability. A lower MFE indicates a more stable RNA secondary structure. In our work, we compute MFE for each mRNA r using the `RNAfold` algorithm from the ViennaRNA package (v2.7.0) with default settings [50]. Results are reported in kcal/mol.

To facilitate interpretation, we use the *Negated minimum free energy (NMFE)* as defined in Section 4.2, such that higher NMFE values correspond to greater structural stability.

GC content The *GC content* of an mRNA sequence r is defined as the percentage of guanine (`G`) and cytosine (`C`) nucleotides it contains. Let $\#X(r)$ denote the count of nucleotide X in r.

$$\text{GC}(r) \; = \; \frac{\#\text{G}(r) \; + \; \#\text{C}(r)}{|r|} \times 100\% \tag{6}$$

CpG density and UpA density The CpG density is defined as the number of CG dinucleotides per 100 base pairs(bp) [44]. It is calculated as follows:

$$\text{CpG density} = \frac{\text{num\_CG\_dinucleotides}}{\text{length\_of\_sequence}} \cdot 100 \tag{7}$$

The UpA density is calculated analogously.

mRFP expression prediction Since mRFP expression is an experimentally measured value without a known analytical formula, we train a predictive model by fine-tuning the pretrained model from Li et al. [1]. We follow the default hyperparameters and training settings described in their paper. The distribution of mRFP expression values in the training set is shown in Figure 5.

B Safety

B.1 Broader impacts

Our method, ARCADE, introduces controllable codon design by enabling fine-grained manipulation of biological properties such as expression level and structural stability. This can support applications in synthetic biology, gene therapy, and mRNA vaccine development, offering potential societal benefits by accelerating therapeutic design and improving biological sequence performance.

Figure 5: Distribution of mRFP expression

However, the same controllability could raise risks if used to design sequences with unintended or malicious properties, such as avoiding immunogenicity detection or bypassing biosafety checks. Furthermore, because our approach builds on pretrained models, its behavior is ultimately constrained by the biases and limitations of the underlying training data, which may lead to unreliable results in poorly represented sequence regimes.

While this work remains foundational and is not intended for direct deployment, future applications should consider integrating biosafety filters, rigorous interpretability tools, and transparent sequence audit trails to ensure responsible use.

B.2 Responsible code release

We plan to release the source code for ARCADE under a research-only open-source license (CC BY 4.0) to encourage reproducibility and further academic research. We will include documentation specifying that the code is intended solely for non-commercial, academic use.

To prevent unintended use, we claim that the code is not intended for clinical or therapeutic deployment. Additionally, users are encouraged to conduct proper validation before applying the code to any real-world biological or medical contexts.