Title

Cenote-Taker 3 for Fast and Accurate Virus Discovery and Annotation of the Virome

Authors

Michael J. Tisza[1,2†], Joseph F. Petrosino[1,2], Sara J. Javornik Cregeen[1,2†]

Affiliations

[1]   The Alkek Center for Metagenomics and Microbiome Research, Department of Molecular Virology and Microbiology, Baylor College of Medicine, Houston, TX, 77030, USA

[2]   Department of Molecular Virology and Microbiology, Baylor College of Medicine, Houston, TX, 77030, USA

† Corresponding authors, email at SaraJoan.JavornikCregeen@bcm.edu, Michael.Tisza@bcm.edu

Abstract

Viruses are abundant across all Earth's environments and infect all classes of cellular life. Despite this, viruses are something of a black box for genomics scientists. Their genetic diversity is greater than all other lifeforms combined, their genomes are often overlooked in sequencing datasets, and no function can be inferred for most of their genes. For these reasons, scientists need robust, performant, well-documented, extensible tools that can conduct sensitive and specific analyses of sequencing data to discover virus genomes - even those with high divergence from known references - and annotate their genes. Here, we present Cenote-Taker 3. This command line interface tool processes genome assemblies and/or metagenomic assemblies with modules for virus discovery, prophage extraction, and annotation of genes and other genetic features. Benchmarks show that Cenote-Taker 3 outperforms most tools for virus gene annotation in both speed (wall time) and accuracy. For virus discovery benchmarks, Cenote-Taker 3 performs well compared to geNomad, and these tools produce complementary results. Cenote-Taker 3 is freely available on Bioconda, and its open-source code is maintained on GitHub (https://github.com/mtisza1/Cenote-Taker3)

Main Text

Introduction

Cataloging the virome from assembled sequencing data remains a primary challenge in the field of virus genomics. Essential subtasks within this challenge include identifying virus genomes, taxonomically classifying them, functionally annotating their genes, and extracting prophages (via phage/bacteria border prediction) when appropriate[1]. Until bioinformatics tools can sufficiently conduct these tasks, downstream analyses such as association of viruses with specific host phenotypes (e.g. health vs. disease), deep understanding of virus evolution, and microbial ecology of viruses and their hosts all remain underwhelming and subject to errors and biases in catalog composition and annotation.

Cenote-Taker 3 takes on these challenges to advance viral genomics by discovering and annotating virus genomes from sequence assemblies. This tool scales from a single genome to terabase-size datasets. The complete Cenote-Taker 3 workflow is summarized as follows: 1) predict and translate open reading frames from input contigs, 2) detect presence/absence of viral hallmark genes in each contig to detect putative virus contigs, 3) explore these contigs for terminal repeats or circularity, wrapping and rotating potentially circular contigs, 4) annotate genes by function, 5) extract prophages in contigs with high bacterial gene content, and 6) assign hierarchical taxonomy labels to each virus sequence (Fig. 1). Output files include gene- and contig-level summary tables, .fasta files for nucleotide and protein sequences, and interactive genome maps for each predicted virus.

Benchmarking of bioinformatics software, while essential, can be difficult to interpret due to choices made and the priorities set by the individuals conducting the benchmarking tests. One approach in virus prediction benchmarks is to synthesize ever smaller snippets of nucleotide sequences of known viruses[2]. While this may have some use, we argue that, for the purposes of cataloging the virome, these tests are of minimal utility, as they do not measure the ability of software to identify previously undiscovered, highly divergent virus genomes. Furthermore, contigs representing complete or mostly complete virus genomes are substantially more valuable to catalogs than incomplete genome fragments. Finally, metagenomic assembly algorithms utilizing short reads (produced by the standard technologies for over a decade) produce a plurality of short contigs representing small genome fragments. However, long read technologies, such as those employed by PacBio and Oxford Nanopore Technologies (and under development by other companies), produce reads from metagenomic libraries of sufficient quantity, quality, and length to allow assembly of complete cellular (e.g. bacterial), plasmid, and virus genomes. And these technologies are increasingly applied to metagenomes[3].

Therefore, the benchmarks herein focus on single-contig MAGs (metagenome-assembled genomes) representing complete or high-quality genomes from a diversity of ecosystems. The virus genomes in these benchmarks overwhelmingly have no or little nucleotide similarity to genome records in the large public RefSeq or GenBank repositories. In fact, many genomes in

these benchmarks have little protein similarity (based on translated open reading frames) to these public records.

All things considered, Cenote-Taker 3 is a high-performing tool that allows researchers to discover and annotate the virome in complex sequence datasets.

Results

Figure 1

Cenote-Taker 3 Schematic. A visual description of how input contigs are systematically processed by Cenote-Taker 3 to identify virus genomes, produce gene annotations, prune prophages, and assign taxonomy. Output files include genome maps (.gbf), tabular virus- and gene-level summaries, and sequences (.fasta).

Improvements Over Cenote-Taker 2

Cenote-Taker 3, while sharing the same goals as its predecessor[4], completely eclipses its utility and performance. The codebase has been completely rewritten, additional utilities were added, it is much more efficient (5-fold decrease in wall time for the same dataset (Fig. S1B)), the database is greatly expanded and more consistently annotated (Fig. S1A). Also, it is now available via the Bioconda package manager[2].

Figure S1

Updates from Cenote-Taker 2. (A) The hallmark gene Hidden Markov Model database from Cenote-Taker 2 was expanded for Cenote-Taker 3 by adding 7,726 new records. (B) Comparing time to process 100 UHGV genomes between Cenote-Taker 2, Cenote-Taker 3, and Pharokka. The phanotate open reading frame predictor was used as it is the only setting that is comparable to Cenote-Taker 3.

Functional Gene Annotation

Cenote-Taker 3 exists in a rich ecosystem of bioinformatics tools that are purported to or can be used to annotate genes and other features on virus genomes. Not all software packages are tested here. While Cenote-Taker 3 has the capability (via the scope of its databases) to annotate (and discover) eukaryotic viruses, most other tools focus on annotation of phage genomes, which, via their ubiquity and immense diversity, provide ample test sets.

The UHGV (United Human Gut Virome) catalog has compiled hundreds of thousands of virus MAGs of varying levels of completeness, and UHGV primarily consists of dsDNA and ssDNA phages from human guts. Here we have taken random subsets of 100 and 1,000 high-quality virus MAGs. Compared to state-of-the art tools geNomad[5], MetaCerberus[6], Pharokka[7], and phold (https://github.com/gbouras13/phold), Cenote-Taker 3 annotates a significantly higher proportion of genes than all tools except phold (Fig. 2A). It has a shorter wall time than all tools except geNomad (Fig. 2B). Note that phold is the only software requiring GPU capabilities for gene annotation from this set. Wall time rankings remain consistent when the dataset is scaled to 1,000 virus MAGs (Fig. S2).

Simply measuring the proportion of genes annotated does not account for the possibility of false positives. Considering the test data are mostly divergent genomes that are difficult to assess for ground truth, we reasoned that some features should be nearly universal in some virus categories. For example, head-tail phages (viruses in the class *Caudoviricetes*) should have one and only one copy of a major capsid protein (MCP) gene, a large terminase subunit (TerL) gene, and a portal gene. Software packages can be benchmarked on their ability to annotate a single copy for each of these conserved genes. Therefore, suitable datasets of putatively complete *Caudoviricetes* genomes were needed to assess specific marker gene annotation.

A recent study used long read plus short read data to assemble and polish contigs from the viromes of human gut (stool) and seawater virus-like particle preps [8]. These assemblies contained many complete head-tail phages, and we used these genomes to assess annotation accuracy of major capsid (MCP), large terminase (TerL), and portal genes. In both the gut dataset (Fig 2C-E) and the seawater dataset (Fig2F-H), Cenote-Taker 3 annotates the most head-tail phage genomes with correct number of these three genes . Figure 3 C and F demonstrate that all tools are susceptible to missing these genes (false negatives) as well as multiple copies of the target genes (false positives). Cenote-Taker 3 annotated the expected number of MCP/TerL/Portal genes in 22/27 head-tail phages in the gut dataset (Fig. 2D) and 174/242 in the seawater dataset (Fig. 2G), outpacing other tools. The combination of speed, annotation rate, and accuracy demonstrate that Cenote-Taker 3 is a strong choice for gene annotation tasks for virus MAGs.

Figure 2

Virus gene annotation benchmarks. (A) UHGV 100 virus Metagenome-Assembled Genomes (MAGs) annotated with five different software packages. The y-axis reports annotated (non-hypothetical) genes as a percentage of total genes. (B) Wall time for UHGV 100 virus MAGs annotation. (C) 27 circular gut (stool)-derived head-tail phage MAGs annotated by five software packages. Per-genome number of annotated major capsid protein (MCP), large terminase

subunit (TerL), and portal genes. (D) Out of 27 circular gut (stool)-derived head-tail phage MAGs, number of genomes with single copy MCP/TerL/portal genes. (E) 27 circular gut (stool) head-tail phage MAGs, reporting annotated (non-hypothetical) genes as a percentage of total genes. (F) Like (C) but with 242 seawater-derived head-tail phage MAGs. (G) Like (D) but with 242 seawater-derived head-tail phage MAGs. (H) Like (E) but with 242 seawater-derived head-tail phage MAGs.

Figure S2

Wall Time for Annotating 1,000 UHGV Genomes

RNA viruses, such as those that might be sequenced in metatranscriptomics studies, have more diverse genome end types and may consist of multiple segments. Therefore, determining completeness of previously undiscovered viruses is more difficult. Nevertheless, other, potentially more biased, methods exist to detect complete virus MAGs. Here, assemblies from an RNA sequencing data set from a large seawater virus-like particle preparation were filtered using CheckV to retain putatively complete and high-quality virus genomes. These genomes were annotated by the same five software packages, and Cenote-Taker 3 had the highest proportion of annotated genes and had the highest number of contigs with an annotated RNA-dependent RNA polymerase gene and capsid/coat genes (Fig. S3). It should be noted that Pharokka and phold are designed for DNA phages, and their decreased performance should be understood as a design choice.

Annotation of RNA virus genomes. (A) 1,133 putatively complete RNA virus MAGs annotated by five software packages. Per-genome number of annotated capsid/coat protein (Cap) and RNA-Dependent RNA Polymerase (RDRP). (B) 1,133 putatively complete RNA virus MAGs annotation rate. The y-axis reports annotated (non-hypothetical) genes as a percentage of total genes. (C) Out of 1,133 putatively complete RNA virus MAGs, number of genomes with Cap and RDRP annotated, respectively.

Virus Discovery

To assess virus discovery capabilities, we compared Cenote-Taker 3 with geNomad on circular contigs from two distinct environmental datasets: hot springs[9] and anaerobic digester metagenomes[10]. GeNomad was chosen as it has become the predominant virus discovery software in recent years and is well-maintained. It uses a combination of marker gene annotation and *k*mer-based neural network classification to predict which contigs are viruses. Cenote-Taker 3 uses a solely marker gene-based approach to virus discovery.

Long read datasets were assembled with myloasm v0.1.0 (https://github.com/bluenote-1577/myloasm) and filtered for circularity. Circular contigs should represent either complete bacterial chromosomes (which may contain prophages), plasmids, or virus genomes. These were run through Cenote-Taker 3 and geNomad using virus discovery/detection settings recommended in each software's documentation.

Overall, the two methods largely agree on the hot springs data (Fig. 3A). However, there is some disagreement. Again, ground truth is difficult if not impossible to know when working with this data type. To analyze Cenote-Taker 3-specific and geNomad-specific contigs, phold was used to annotate genes since this method's structure-based approach is somewhat orthogonal to other methods. We find that both discovery methods missed contigs with complete arrays of major capsid protein, large terminase subunit, and portal genes (Fig. 3B-C). Inspection of phold-based genome maps is interesting if not conclusive (Fig. 3D,E). Many Cenote-Taker 3-specific contigs encode high numbers of phage tail-related genes, for example, which may represent phage-derived tailocin elements.

Results were more divergent in the anaerobic digester dataset (Fig. 4A), wherein geNomad called 143 unique contigs while Cenote-Taker 3 called 37 unique contigs viral. We find that Cenote-Taker 3 has a greater number of unique contigs that encode major capsid protein, large terminase, and/or portal genes, per phold annotation (Fig. 4B,D). GeNomad, on the other hand, has many unique contigs from the anaerobic digester dataset that have few of these marker genes (despite geNomad taxonomic labels of *Caudoviricetes* for nearly all contigs), and, interestingly, most are about 25 kilobases in length (Fig. 4C,E). The geNomad output files show that the large majority of the unique contigs encoded no hallmark genes (109/143) and the software used predictions from its neural network on these MAGs (Fig. S4). Shared gene content (not shown) suggests these contigs may represent a coherent class of elements. It's hard to say whether these elements are truly viruses, but it would also be difficult to ascribe any other category to them.

When these results are taken together, potential users of these software packages face a difficult choice. Using Cenote-Taker 3, putative virus MAGs may be easier to verify since presence of virus hallmark genes can be checked with orthogonal methods. With geNomad, the virus MAGs primarily predicted by the neural network are harder to verify but may contain genomes from entirely undescribed types of viruses.

Figure 3

Virus Discovery Comparison for Hot Springs Data. (A) Comparison of viruses identified/discovered between geNomad and Cenote-Taker 3 in a dataset of circular MAGs from a hot spring long read metagenome assembly. (B) For viruses in this dataset only identified by Cenote-Taker 3, count of MCP/TerL/Portal genes annotated per contig by phold. (C) Like (B) but for viruses in this dataset only identified by geNomad. (D) For viruses in this dataset only identified by Cenote-Taker 3, genome maps of phold annotations, highlighting MCP/TerL/Portal genes. Only contigs with under 200 genes shown for readability. (E) Like (D) but for viruses in this dataset only identified by geNomad.

Figure 4

Virus Discovery Comparison for Anaerobic Digester Data. (A) Comparison of viruses identified/discovered between geNomad and Cenote-Taker 3 in a dataset of circular MAGs from anaerobic digester long read metagenome assembly. (B) For viruses in this dataset only identified by Cenote-Taker 3, count of MCP/TerL/Portal genes annotated per contig by phold. (C) Like (B) but for viruses in this dataset only identified by geNomad. (D) For viruses in this dataset only identified by Cenote-Taker 3, genome maps of phold annotations, highlighting MCP/TerL/Portal genes. Only contigs with under 200 genes shown for readability. (E) Like (D) but for viruses in this dataset only identified by geNomad.

Figure S4

Hot Springs virus MAGs

Anaerobic Digester virus MAGs

Virus MAG Hallmark Comparison for Shared and Unique Detections. (A) Comparison of hallmark genes for viruses identified/discovered between geNomad and Cenote-Taker 3 in a dataset of circular MAGs from hot spring long read metagenome assembly. Cenote-Taker 3 hallmark gene counts. (B) Like (A), but geNomad hallmark gene counts. (C) Like (A) but for circular MAGs from anaerobic digester long read metagenome assembly. Cenote-Taker 3 hallmark gene counts. (D) Like (C) but geNomad hallmark gene counts.

Other Features: Taxonomy, Prophage Extraction

Cenote-Taker 3 also assigns hierarchical taxonomy of virus contigs based on identity and agreement of its "hallmark" genes to GenBank virus records. A comparison of the aforementioned UHGV dataset of 100 high-quality MAGs shows very similar output to geNomad (Fig. S5).

Prophage extraction from bacterial chromosomes is performed by finding regions with virus "hallmark" genes and scoring surrounding genes for virus vs bacterial features and clipping the prophage where high bacterial gene content begins. This feature is not benchmarked here and is the focus of future research.

Figure S5

Taxonomic Labelling of UHGV virus MAGs. 100 high-quality virus MAGs from the UHGV dataset were run through Cenote-Taker 3 and geNomad and the hierarchical taxonomy labels were compared. Genomes were faceted by realm assigned by Cenote-Taker 3.

Discussion

Cenote-Taker 3 is an ideal piece of software for annotation and cataloging of the virome, particularly if the focus is on high-quality genomes. It readily scales from single virus genomes to thousands of metagenomes. It can be used as an end-to-end program to identify virus MAGs, annotated their genes, excise prophage sequences from bacterial genomes, and taxonomically label virus sequences. Alternatively, it can also be used to simply annotate genes and report taxonomy of pre-discovered virus MAGs.

Cenote-Taker 3 reliably reports on the function of important genes and identifies viruses in complex datasets. Some existing software outperforms Cenote-Taker 3 in some ways, but this tool stands out for its combination of performance and accuracy. For example, the

benchmarking performed showed that Cenote-Taker 3 annotated essential genes (MCP, TerL, portal for head-tail phages; RDRP and Cap for RNA viruses) more accurately than other tools and finished annotation tasks more quickly than most tools (Fig. 2, Fig. S2-3). Virus discovery tests showed that Cenote-Taker 3 identifies some highly convincing virus MAGs that are missed by the field standard geNomad (Fig. 3-4).

Comparative tests for annotation and discovery of viruses, such as those performed in this study, also present discrete and useful opportunities for all software packages compared to improve. For example, when other software identifies a major capsid protein gene that Cenote-Taker 3 does not, this signal can be validated (e.g. using structural prediction) and the Cenote-Taker 3 database can be improved accordingly.

As long-read sequencing technologies continue to mature and become more affordable, tools like Cenote-Taker 3 will become increasingly valuable for producing high-quality complete viral genome annotations from metagenomic data. Future developments will focus on expanding reference databases to improve annotation of currently unknown genes, particularly those from under-sampled environments and viral lineages.

By offering simplified installation through Bioconda along with high performance on standard consumer hardware and high-performance compute systems, Cenote-Taker 3 contributes to democratizing viral genomics research, enabling labs with limited computational resources to conduct sophisticated analyses.

Methods

Cenote-Taker 3 Code Details

Cenote-Taker 3 is a command-line interface tool coded using Python and Bash. It imports and/or calls several bioinformatics packages. To read and write sequencing records, Biopython[11] and Seqkit[12] are used. To predict open-reading frames, pyrodigal-gv[13] is used by default, and pyrodigal and phanotate[14] are also available per command-line argument. Gene functional annotation is performed using pyhmmer[14] and mmseqs2[15]. Hhsuite[16] and its databases can also be used. trnascan-se[17] is used to predict tRNA elements. Bedtools[18] is used to deal with genomic ranges and coordinates. Minimap2[19] and samtools[20] are used for optional read alignment and quantification steps.

All code is publicly available and maintained on GitHub (https://github.com/mtisza1/Cenote-Taker3).

Basic installation instructions using the mamba/conda package manager:

mamba create -n ct3_env bioconda::cenote-taker3

Bioconda package page can be accessed [here](). Quay container image, generated automatically by Bioconda, can be accessed [here]().

Cenote-Taker 3 Database Details

for the HMM databases, used for virus "hallmark" (virion, rdrp, and dnarep) gene detection as well as for some additional gene annotation tasks, the Cenote-Taker 2 database was expanded with gene models from PHROGs[21], efams[22], sequences from the Buck et al. survey[23], and manually curated models. All model names were manually checked and updated as necessary to ensure similar models returned the same annotation.

For the taxonomy database, NCBI's NR Clustered cd90 amino acid sequence [database]() was downloaded on December 12, 2023, and filtered for records belonging the "Viruses" taxon. Then, these records were queried against the Cenote-Taker 3 hallmark databases (virion, rdrp, and dnarep) (DB v3.1.1), and hits were returned by standard Cenote-Taker 3 cut-offs. Hierarchical taxonomy labels were retrieved from Genbank for these selected records using taxonkit[24]. Only records which contained class, family, and genus labels were kept for the final taxonomy database. Mmseqs2 was used to create a taxDB with these records.

Database files can be accessed on [Zenodo]() (DOI 10.5281/zenodo.8429308)

Annotation Benchmarks

All benchmarks were performed using a 2023 MacBook Pro laptop computer with 16 GB of memory and an Apple M2 Pro chip running MacOS.

The UHGV, Gut Circular, and Seawater Circular, Seawater virus-like particle RNA virus MAG sequences are available at [Zenodo](). Seawater virus-like particle RNA sequencing reads and assemblies are available on NCBI under bioproject PRJNA605028.

The following software package versions and databases were used: geNomad v1.11.1 (DB v1.9), Metacerberus v1.4.0 (DB v1.4), Pharokka v1.7.3 (DB v1.4.0), phold v0.2.0 (DB v2), Cenote-Taker 3 v3.4.1 (DB v3.11).

All annotation software tested used pyrodigal-gv to conduct open reading frame prediction, making annotation rates as comparable as possible. The most appropriate setting for annotation were used based on software documentation. Example commands are as follows:

genomad annotate --splits 4 seqs.fna gnmd_test1_out genomad_dbs/

metacerberus.py --prodigalgv seqs.fna --hmm "ALL" --dir_out metc_test1_out

pharokka.py -m -s -g prodigal-gv --meta_hmm -d pharokka_db -i seqs.fna -o phar_test1_out

phold run -i seqs.fna -o phold_test1_out

cenotetaker3 -c seqs.fna -r ct3_test1_out -p F -am T

All scripts to reproduce analyses of annotation outputs are available on GitHub (https://github.com/mtisza1/ct3_benchmarks), and data are available on Zenodo.

Discovery Benchmarks

Circular MAG assemblies from hot spring reads (DRR290133) and anaerobic digester sample reads (ERR10905741) are available on Zenodo. Reads were downloaded from SRA and assembled with myloasm v0.1.0 with default settings. Circularity of contigs is reported in myloasm output sequence headers.

GeNomad end-to-end pipeline was run on these data with default settings plus the "--enable-score-calibration" flag. Cenote-Taker 3 was run with the flags "-p T --lin_minimum_hallmark_genes 2 --circ_minimum_hallmark_genes 2" as recommended on the GitHub README for whole genome shotgun metagenome data.

Tool-specific contigs were annotated with phold v0.2.0 using default settings and visualized with Rstats package gggenomes[25].

Author Contributions Statement

Conceptualization: M.J.T., S.J.C., J.F.P.
Methodology: M.J.T.
Investigation: M.J.T.
Visualization: M.J.T.
Funding acquisition: S.J.C., J.F.P.
Project administration: S.J.C.
Supervision: J.F.P., S.J.C.
Writing—original draft: M.J.T., S.J.C.
Writing—review and editing: M.J.T., S.J.C., J.F.P.

Acknowledgements

We are grateful all insights and suggestions from early users of this software, especially Drs. Chris Buck and Arvind Varsani.

Competing Interests Statement

The authors declare no competing interests.

References

Camargo, A. P. *et al.* IMG/VR v4: an expanded database of uncultivated virus genomes within a framework of extensive functional, taxonomic, and ecological metadata. *Nucleic Acids Res* **51**, D733-D743, doi:10.1093/nar/gkac1037 (2023).

Ho, S. F. S., Wheeler, N. E., Millard, A. D. & van Schaik, W. Gauge your phage: benchmarking of bacteriophage identification tools in metagenomic sequencing data. *Microbiome* **11**, 84, doi:10.1186/s40168-023-01533-x (2023).

Agustinho, D. P. *et al.* Unveiling microbial diversity: harnessing long-read sequencing technology. *Nat Methods* **21**, 954-966, doi:10.1038/s41592-024-02262-1 (2024).

Tisza, M. J., Belford, A. K., Dominguez-Huerta, G., Bolduc, B. & Buck, C. B. Cenote-Taker 2 democratizes virus discovery and sequence annotation. *Virus Evol* **7**, veaa100, doi:10.1093/ve/veaa100 (2021).

Camargo, A. P. *et al.* Identification of mobile genetic elements with geNomad. *Nat Biotechnol* **42**, 1303-1312, doi:10.1038/s41587-023-01953-y (2024).

Figueroa Iii, J. L., Dhungel, E., Bellanger, M., Brouwer, C. R. & White Iii, R. A. MetaCerberus: distributed highly parallelized HMM-based processing for robust functional annotation across the tree of life. *Bioinformatics* **40**, doi:10.1093/bioinformatics/btae119 (2024).

Bouras, G. *et al.* Pharokka: a fast scalable bacteriophage annotation tool. *Bioinformatics* **39**, doi:10.1093/bioinformatics/btac776 (2023).

Cook, R. *et al.* The long and short of it: benchmarking viromics using Illumina, Nanopore and PacBio sequencing technologies. *Microb Genom* **10**, doi:10.1099/mgen.0.001198 (2024).

Kato, S., Masuda, S., Shibata, A., Shirasu, K. & Ohkuma, M. Insights into ecological roles of uncultivated bacteria in Katase hot spring sediment from long-read metagenomics. *Front Microbiol* **13**, 1045931, doi:10.3389/fmicb.2022.1045931 (2022).

Benoit, G. *et al.* High-quality metagenome assembly from long accurate reads with metaMDBG. *Nat Biotechnol* **42**, 1378-1383, doi:10.1038/s41587-023-01983-6 (2024).

Cock, P. J. *et al.* Biopython: freely available Python tools for computational molecular biology and bioinformatics. *Bioinformatics* **25**, 1422-1423, doi:10.1093/bioinformatics/btp163 (2009).

Shen, W., Le, S., Li, Y. & Hu, F. SeqKit: A Cross-Platform and Ultrafast Toolkit for FASTA/Q File Manipulation. *PLoS One* **11**, e0163962, doi:10.1371/journal.pone.0163962 (2016).

Larralde, M. Pyrodigal: Python bindings and interface to Prodigal, an efficient method for gene prediction in prokaryotes. *Journal of Open Source Software*, doi:10.21105/joss.04296 (2022).

McNair, K., Zhou, C., Dinsdale, E. A., Souza, B. & Edwards, R. A. PHANOTATE: a novel approach to gene identification in phage genomes. *Bioinformatics* **35**, 4537-4542, doi:10.1093/bioinformatics/btz265 (2019).

Steinegger, M. & Soding, J. MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. *Nat Biotechnol* **35**, 1026-1028, doi:10.1038/nbt.3988 (2017).

Steinegger, M. *et al.* HH-suite3 for fast remote homology detection and deep protein annotation. *BMC Bioinformatics* **20**, 473, doi:10.1186/s12859-019-3019-7 (2019).

Chan, P. P., Lin, B. Y., Mak, A. J. & Lowe, T. M. tRNAscan-SE 2.0: improved detection and functional classification of transfer RNA genes. *Nucleic Acids Res* **49**, 9077-9096, doi:10.1093/nar/gkab688 (2021).

Quinlan, A. R. & Hall, I. M. BEDTools: a flexible suite of utilities for comparing genomic features. *Bioinformatics* **26**, 841-842, doi:10.1093/bioinformatics/btq033 (2010).

Li, H. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics* **34**, 3094-3100, doi:10.1093/bioinformatics/bty191 (2018).

Danecek, P. *et al.* Twelve years of SAMtools and BCFtools. *Gigascience* **10**, doi:10.1093/gigascience/giab008 (2021).

Terzian, P. *et al.* PHROG: families of prokaryotic virus proteins clustered using remote homology. *NAR Genom Bioinform* **3**, lqab067, doi:10.1093/nargab/lqab067 (2021).

Zayed, A. A. *et al.* efam: an expanded, metaproteome-supported HMM profile database of viral protein families. *Bioinformatics* **37**, 4202-4208, doi:10.1093/bioinformatics/btab451 (2021).

Buck, C. B. *et al.* Widespread Horizontal Gene Transfer Among Animal Viruses. *bioRxiv*, doi:10.1101/2024.03.25.586562 (2024).

Shen, W. & Ren, H. TaxonKit: A practical and efficient NCBI taxonomy toolkit. *J Genet Genomics* **48**, 844-850, doi:10.1016/j.jgg.2021.03.006 (2021).

Hackl, T., Duponchel, S., Barenhoff, K., Weinmann, A. & Fischer, M. G. Virophages and retrotransposons colonize the genomes of a heterotrophic flagellate. *Elife* **10**, doi:10.7554/eLife.72674 (2021).