Title

Cenote-Taker 3 for Fast and Accurate Virus Discovery and Annotation of the Virome

Authors

Michael J. Tisza[1,2†], Arvind Varsani[3,4], Joseph F. Petrosino[1,2], Sara J. Javornik Cregeen[1,2†]

Affiliations

[1]   The Alkek Center for Metagenomics and Microbiome Research, Department of Molecular Virology and Microbiology, Baylor College of Medicine, Houston, TX, 77030, USA

[2]   Department of Molecular Virology and Microbiology, Baylor College of Medicine, Houston, TX, 77030, USA

[3]   The Biodesign Center for Fundamental and Applied Microbiomics, Center for Evolution and Medicine, School of Life Sciences, Arizona State University, Tempe, AZ, 85287-5001, USA

[4]   Structural Biology Research Unit, Department of Integrative, Biomedical Sciences, University of Cape Town, Observatory, Cape Town, 7925, South Africa

† Corresponding authors, email at SaraJoan.JavornikCregeen@bcm.edu, Michael.Tisza@bcm.edu

Abstract

Viruses are abundant across all Earth's environments and infect all classes of cellular life. Despite this, viruses are something of a black box for genomics scientists. Their genetic diversity is greater than all other lifeforms combined, their genomes are often overlooked in sequencing datasets, they encode polyproteins, and no function can be inferred for a large majority of their encoded proteins. For these reasons, scientists need robust, performant, well-documented, extensible tools that can be deployed to conduct sensitive and specific analyses of sequencing data to discover virus genomes - even those with high divergence from known references - and annotate their genes. Here, we present Cenote-Taker 3. This command line interface tool processes genome assemblies and/or metagenomic assemblies with modules for virus discovery, prophage extraction, and annotation of genes and other genetic features. Benchmarks show that Cenote-Taker 3 outperforms most tools for virus gene annotation in both speed (wall time) and accuracy. For virus discovery benchmarks, Cenote-Taker 3 performs well compared to geNomad, and these tools produce complementary results. Cenote-Taker 3 is

31 freely available on Bioconda, and its open-source code is maintained on GitHub
32 (https://github.com/mtisza1/Cenote-Taker3).

Main Text

Introduction

Cataloging the virome from *de novo* assembled sequencing data remains a primary challenge in
the field of virus metagenomics. Essential subtasks within this challenge include identifying
virus genomes over viral-like genetic elements in host genomes, taxonomically classifying them,
functionally annotating their genes, and extracting prophages (integrated virus genomes in
prokaryotic host genomes) and proviruses (viruses in eukaryotic chromosomes) via
virus/cellular genome boundary[1]. Until bioinformatics tools can sufficiently conduct these tasks,
downstream analyses such as association of viruses with specific host phenotypes (e.g. health
vs. disease), deep understanding of virus evolution through comparative genomics, and
microbial ecology of viruses and their hosts all remain underwhelming and subject to errors and
biases in catalog composition and annotation.
45
Virus discovery from metagenomic assemblies is commonly performed with tools such as
VirSorter2[2], VIBRANT[3], and geNomad[4], which use combinations of hallmark-gene detection and
(in some cases) machine-learning classifiers to distinguish viral from cellular or plasmid
sequences. For functional annotation and genome interpretation, many workflows rely on ORF
calling with prodigal[5], prodigal-gv (https://github.com/apcamargo/prodigal-gv), or PHANOTATE[6]
and phage-focused functional annotators such as Pharokka[7] (PHROGs-based), broader
annotation frameworks such as MetaCerberus[8], and complementary approaches such as phold[9]
that leverage structure-informed protein annotation. Downstream quality control utilities like
CheckV[1] are used for completeness/contamination estimates, and specialty tools like
CRESSENT[10] can perform value-added analyses on certain taxa (e.g. CRESS-DNA viruses).
Despite having various software packages for a complete viromics "workflow", major gaps
remain in the discovery and characterization genetic entities that are extremely divergent from
well-characterized records.
59
Cenote-Taker 3 takes on these challenges to advance viral genomics for discovery and
annotation of virus genomes from *de novo* assembled sequences (contigs). This tool scales
from a single genome to terabase-size datasets. The complete Cenote-Taker 3 workflow can be
summarized as follows: 1) predict and translate open reading frames from input contigs, 2)
detect presence/absence of viral hallmark genes in each contig to detect putative virus contigs,
3) explore these contigs for terminal repeats or circularity, wrapping and rotating potentially
circular contigs, 4) annotate genes by function, 5) extract prophages in contigs with high
bacterial gene content, and 6) assign hierarchical taxonomy labels to each virus sequence (Fig.
1). Output files include gene- and contig-level summary tables, FASTA format files for
nucleotide and protein sequences, and GenBank flat files as interactive genome maps for each
predicted virus. In this manuscript, we benchmark Cenote-Taker 3 against several of the most

prominent virus metagenomics tools to determine its utility in gene annotation, virus discovery,
and scalability.
73
Benchmarking of bioinformatics software, while essential, can be difficult to interpret due to
choices made and the priorities set by the individuals conducting the benchmarking tests. One
approach in virus prediction benchmarks is to synthesize ever smaller snippets of nucleotide
sequences of known viruses and then determine if these snippets can be recalled by virus
prediction software[11]. While this may have some use, we argue that, for the purposes of
cataloging the virome, these tests are of minimal utility, as they do not measure the ability of
software to identify previously undiscovered, highly divergent virus genomes. Furthermore,
contigs representing complete or mostly complete virus genomes with identifiable coding
regions / functional domains are substantially more valuable and informative to catalogs than
incomplete genome fragments.
84
In the future, we envision biome-specific catalogs of complete, well-characterized virus
genomes that can be used in quantitative read-mapping analyses, comparative genomics and
other biotechnology applications. To achieve this, we consider what different technologies can
offer. Metagenomic assembly algorithms utilizing short reads (produced by the standard
technologies for over a decade) produce a plurality of short contigs usually representing small
genome fragments. However, long read technologies, such as those employed by PacBio and
Oxford Nanopore Technologies (and under development by other companies), produce reads
from metagenomic libraries of sufficient quantity, quality, and length to allow assembly of
complete cellular (e.g. bacterial), plasmid, and virus genomes. And these technologies are
increasingly applied to metagenomes[12].
95
96   Therefore, because of their utility and increasing obtainability, the benchmarks herein focus on
97   single-contig MAGs (metagenome-assembled genomes) representing complete or high-quality
98   genomes from a diversity of ecosystems. The virus genomes in these benchmarks encoding
99   genes that primarily have no or little amino acid similarity to protein records in the large public
100   RefSeq Virus repository[13].
101
102   All things considered, Cenote-Taker 3 is a high-performing tool that allows researchers to
103   discover and annotate the virome in complex sequence datasets.

Results

Figure 1

Cenote-Taker 3 Schematic*. A visual description of how input contigs are systematically processed by Cenote-Taker 3 to identify virus genomes, produce gene annotations, prune prophages, and assign taxonomy. Output files include genome maps (.gbf), tabular virus- and gene-level summaries, and sequences (.fasta).*

Improvements Over Cenote-Taker 2

Cenote-Taker 3, while sharing the same goals as its predecessor[14], completely eclipses its utility and performance. The codebase has been completely rewritten, additional utilities were added, it is much more efficient (5-fold decrease in wall time for the same dataset; Fig. S1B), the database is greatly expanded and more consistently annotated (Fig. S1A). Also, it is now available via the Bioconda package manager[11].

117   Figure S1

118
***Updates from Cenote-Taker 2**. (A) The hallmark gene Hidden Markov Model database from*
Cenote-Taker 2 was expanded for Cenote-Taker 3 by adding 7,726 new models. (B) Comparing
time to process 100 UHGV genomes between Cenote-Taker 2, Cenote-Taker 3, and Pharokka.
The phanotate open reading frame predictor was used as it is the only setting that is
comparable to Cenote-Taker 3.

Functional Gene Annotation

Cenote-Taker 3 exists in a rich ecosystem of bioinformatics tools that are purported to or can be
used to annotate genes and other features on virus genomes. Not all software packages are
tested here. While Cenote-Taker 3 has the capability (because of the scope of its curated
databases) to annotate (and discover) viruses-infecting all domains of life, most other tools
focus on annotation of bacteriophage genomes, which, via their ubiquity and immense diversity,
provide ample test sets.

131
The UHGV catalog[15] has compiled hundreds of thousands of virus MAGs of varying levels of
completeness, and UHGV primarily consists of dsDNA and ssDNA phages from human guts.
Here we have taken random subsets of 100 and 1,000 high-quality virus MAGs (Table 1) and
compared to state-of-the art tools geNomad[4] (mmseqs-based), MetaCerberus[8] (hmmer-based),
Pharokka[7] (hmmer-based), and phold[9] (foldseek-based[16]), and Cenote-Taker 3 (hmmer- and
mmseqs-based). Here, Cenote-Taker 3 annotates a significantly higher proportion of genes than
all tools except phold (Fig. 2A). It has a shorter wall time than all tools except geNomad (Fig.
2B). Note that phold is the only software requiring GPU capabilities for gene annotation from
this set. Wall time rankings remain consistent when the dataset is scaled to 1,000 virus MAGs
(Fig. S2E).

142
Simply measuring the proportion of genes annotated does not account for the possibility of false
positives or improper labeling. Considering the test data are mostly divergent genomes (Fig.
S2A-C) that are difficult to assess for ground truth, we reasoned that some features should be
nearly universal in some virus categories. For example, head-tail phages (viruses in the class
Caudoviricetes) should have one and only one copy of a major capsid protein (MCP) gene, a
large terminase subunit (TerL) gene, and a portal protein gene. Software packages can be

benchmarked on their ability to annotate a single copy for each of these conserved genes.
Therefore, suitable datasets of putatively complete *Caudoviricetes* genomes were needed to
assess specific marker gene annotation.
152
A recent study used long read data plus short read data to assemble and polish contigs from the
viromes of human gut (stool) and seawater virus-like particle preps [17] (Table 1). These
assemblies contained many complete head-tail phages, and we used these genomes to assess
annotation accuracy of major capsid (MCP), large terminase (TerL), and portal genes. In both
the gut dataset (Fig 2C-E) and the seawater dataset (Fig2F-H), Cenote-Taker 3 annotates the
most head-tail phage genomes with correct number of these three genes . Figure 3 C and F
demonstrate that all tools are susceptible to missing these genes (false negatives) as well as
predicting multiple copies of the target genes (false positives). Cenote-Taker 3 annotated the
expected number of MCP/TerL/Portal protein genes in 22/27 head-tail phages (81.4% perfect
rate) in the gut dataset surpassing geNomad (22.2%), MetaCerberus (40.7%), Pharokka
(70.3%), and phold (74.1%) (Fig. 2D). And Cenote-Taker 3 correctly classified 174/242 (73.5%
perfect rate) in the seawater dataset, outpacing geNomad (18.5%), MetaCerberus (25.2%),
Pharokka (33.5%), and phold (25.6%) (Fig. 2G). Additional statistics are available in
Supplementary Tables S1-6. The combination of speed, annotation rate, and accuracy
demonstrate that Cenote-Taker 3 is a strong choice for gene annotation tasks for virus MAGs.

Figure 2

_Virus gene annotation benchmarks__. (A) UHGV 100 virus Metagenome-Assembled Genomes (MAGs) annotated with five different software packages. The y-axis reports annotated (non-hypothetical) genes as a percentage of total genes. (B) Wall time for UHGV 100 virus MAGs annotation. (C) 27 circular gut (stool)-derived head-tail phage MAGs annotated by five software packages. Per-genome number of annotated major capsid protein (MCP), large terminase subunit (TerL), and portal protein genes. (D) Out of 27 circular gut (stool)-derived head-tail phage MAGs, number of genomes with single copy MCP/TerL/portal genes. (E) 27 circular gut (stool) head-tail phage MAGs, reporting annotated (non-hypothetical) genes as a percentage of total genes. (F) Like (C) but with 242 seawater-derived head-tail phage MAGs. (G) Like (D) but with 242 seawater-derived head-tail phage MAGs. (H) Like (E) but with 242 seawater-derived head-tail phage MAGs._

Additional Annotation Analyses. *Translated amino acid sequences were compared to RefSeq*
Virus amino acid sequences using mmseqs (e-value cutoff 0.01) for (A) Gut DTR Genomes, (B)
Seawater DTR Genomes, and (C) Seawater RNA Genomes. (D) RefSeq Virus genomes
(n=18,969 contigs) annotated with four different software packages. The y-axis reports
annotated (non-hypothetical) genes as a percentage of total genes. (E) Wall Time for
Annotating 1,000 UHGV Genomes.

RNA viruses, such as those that might be sequenced in metatranscriptomics studies, have more
diverse genome end types and may consist of multiple segments. Therefore, determining
completeness of previously undiscovered viruses is more difficult. Nevertheless, other,
potentially more biased, methods exist to detect complete virus MAGs. Here, MAGs from an
RNA sequencing dataset from a large seawater virus-like particle preparation (Table 1) were
filtered using CheckV to retain putatively complete and high-quality virus genomes (Fig. S2C).
These genomes were annotated by the same five software packages, and Cenote-Taker 3 had
the highest proportion of annotated genes and had the highest number of contigs with an
annotated RNA-dependent RNA polymerase (RdRP) gene and Capsid/Coat gene (Fig. S3). It

199   should be noted that Pharokka and phold are designed for DNA phages, and their decreased
200   performance should be understood as a design choice.

201   Figure S3

202
Annotation of RNA virus genomes. *(A) 1,133 putatively complete RNA virus MAGs annotated*
by five software packages. Per-genome number of annotated capsid/coat protein (Cap) and
RNA-Dependent RNA Polymerase (RdRP). (B) 1,133 putatively complete RNA virus MAGs
annotation rate. The y-axis reports annotated (non-hypothetical) genes as a percentage of total
genes. (C) Out of 1,133 putatively complete RNA virus MAGs, number of genomes with Cap
and RdRP annotated, respectively.
209
210   To compare annotation performance on a well-characterized and diverse dataset, each software
211   package was run on complete RefSeq Virus genomes (n=18,969) (Table 1). In this test, Cenote-
212   Taker 3 annotated the highest proportion of genes on average, followed closely by
213   MetaCerberus (Fig. S2D).
214

Next, we wanted to resolve why Cenote-Taker 3 outperformed other software packages in these
virus annotation benchmarks despite using similar methods (hmmer and mmseqs) as most
other approaches. Cenote-Taker 3, Pharokka, MetaCerberus, and Cenote-Taker 2 have
associated HMM databases containing models for virus gene families, and these databases
could be compared. Consensus amino acid sequences of all models were extracted and aligned
using mmseqs2[18] (e-value threshold 0.01). Across all comparisons, Cenote-Taker 3's database
contained thousands of models with no similarity to models in other databases (Fig. 3A-D).
Importantly, when we looked at the top 10 functional labels in Cenote-Taker 3-specific models
(i.e. no mmseqs alignments to models in other tools), we see that models for Major Capsid
Protein, Portal protein, Large Terminase, RNA-Dependent RNA Polymerase, and other key
hallmark genes are the most abundant. Therefore, it's almost certain that the gene annotation
improvements are primarily a function of more and better gene family models utilized by
Cenote-Taker 3.
228

Comparison of Gene Family HMMs. *Consensus sequences from all individual HMMs were*
extracted from Cenote-Taker 3, Pharokka, MetaCerberus, geNomad and Cenote-Taker 2 and
compared with mmseqs2. (A) Left: histogram of amino acid identity of consensus sequences of
Cenote-Taker 3 DB to Pharokka DB. Right: top 10 functional categories of Cenote-Taker 3

models with no detected similar to Pharokka models. (B) Like A but with MetaCerberus and
Cenote-Taker 3. (C) Like A but with geNomad and Cenote-Takaer 3. (D) Like A but with
Cenote-Taker 2 and Cenote-Taker 3.
238
239 Table 1: Annotation Datasets

Dataset	Description	Genomes
UHGV 100	Unified Human Gastrointestinal Virome, high-quality MAGs	100
UHGV 1000	UHGV MAGs for runtime testing	1,000
RefSeq Virus	NCBI RefSeq Virus reference genomes	18,969
Gut DTR	Complete (circular) gut virome head-tail phages	27
Seawater DTR	Complete (circular) seawater virome head-tail phages	242
Seawater RNA Virome	Complete RNA virus genomes from seawater (PRJNA605028)	1,133
Random GenBank Viruses	Random GenBank virus genomes for taxonomy accuracy	3,696

Virus Discovery

To assess virus discovery capabilities, we compared Cenote-Taker 3 with geNomad on circular
contigs from two distinct environmental datasets: hot springs[19] and anaerobic digester
metagenomes[20] (Table 2). GeNomad was chosen since it has become a dominant virus
discovery software in recent years and is well-maintained. It uses a combination of marker gene
annotation and *k*mer-based neural network classification to predict which contigs are viruses.
Cenote-Taker 3 uses a solely marker gene-based approach to virus discovery.
248
249 Long read datasets were assembled with myloasm v0.1.0[21] and filtered for circularity. Circular
250 contigs should represent either complete bacterial chromosomes (which may contain
251 prophages), plasmids, or circular DNA virus genomes. These were run through Cenote-Taker 3
252 and geNomad using virus discovery/detection settings recommended in each software's
253 documentation.
254
Overall, the two methods largely agree on the hot springs data (Fig. 4A). However, there is
some disagreement. Again, ground truth is difficult if not impossible to know when working with
this data type. To analyze Cenote-Taker 3-specific and geNomad-specific contigs, phold was
used to annotate genes since this method's structure-based approach is somewhat orthogonal
to other methods. We find that both discovery methods missed contigs with complete arrays of
major capsid protein, large terminase subunit, and portal genes (Fig. 4B-C). Inspection of phold-
based genome maps is interesting if not conclusive (Fig. 4D,E). Many Cenote-Taker 3-specific

contigs encode high numbers of phage tail-related genes, for example, which may represent
phage-derived tailocin elements.
264
Results were more divergent in the anaerobic digester dataset (Fig. 5A), wherein geNomad
called 143 unique contigs while Cenote-Taker 3 called 37 unique contigs viral. We find that
Cenote-Taker 3 has a greater number of unique contigs that encode major capsid protein, large
terminase, and/or portal protein genes, per phold annotation (Fig. 5B,D). GeNomad, on the
other hand, has many unique contigs from the anaerobic digester dataset that have few of these
marker genes (despite geNomad taxonomic labels of *Caudoviricetes* for nearly all contigs), and,
interestingly, most are about 25 kilobases in length (Fig. 5C,E). The geNomad output files show
that the large majority of the unique contigs encoded no hallmark genes (109/143) and the
software used predictions from its neural network on these MAGs (Fig. S4). Shared gene
content (not shown) suggests these contigs may represent a coherent class of elements. It's
hard to say whether these elements are truly viruses, but it would also be difficult to ascribe any
other category to them.
277
While we do not claim that Cenote-Taker 3 is the best approach to use when searching
metagenomic data for highly fragmented and incomplete virus genomes, it is nevertheless
informative to see how it performs in virus discovery tasks on short-read metagenomics
assemblies. Six datasets from gut (stool) DNA – three from bulk WGS and three from virus-like
particle preps – were assembled (Table 2). Then, Cenote-Taker 3 and geNomad were run in
discovery mode, using a two marker/hallmark gene minimum to avoid false positives. While no
ground truth data is available to validate these benchmarks, the union between these tools is
greater than the differences (Fig. S5), suggesting that either software might be used for this
task. Further, using different parameters and thresholds will affect the results.
287
288 When these results are taken together, potential users of these software packages face a
289 difficult choice. Using Cenote-Taker 3, putative virus MAGs may be easier to verify since
290 presence of virus hallmark genes can be checked with orthogonal methods. With geNomad, the
291 virus MAGs primarily predicted by the neural network are harder to verify but may contain
292 genomes from entirely undescribed types of viruses.

Figure 4

Virus Discovery Comparison for Hot Springs Data. *(A) Comparison of viruses*
identified/discovered between geNomad and Cenote-Taker 3 in a dataset of circular MAGs from
a hot spring long read metagenome assembly. (B) For viruses in this dataset only identified by
Cenote-Taker 3, count of MCP/TerL/Portal protein genes annotated per contig by phold. (C)
Like (B) but for viruses in this dataset only identified by geNomad. (D) For viruses in this dataset
only identified by Cenote-Taker 3, genome maps of phold annotations, highlighting
MCP/TerL/Portal protein genes. Only contigs with under 200 genes shown for readability. (E)
Like (D) but for viruses in this dataset only identified by geNomad.

Figure 5

304
Virus Discovery Comparison for Anaerobic Digester Data. *(A) Comparison of viruses*
identified/discovered between geNomad and Cenote-Taker 3 in a dataset of circular MAGs from
anaerobic digester long read metagenome assembly. (B) For viruses in this dataset only
identified by Cenote-Taker 3, count of MCP/TerL/Portal protein genes annotated per contig by
phold. (C) Like (B) but for viruses in this dataset only identified by geNomad. (D) For viruses in
this dataset only identified by Cenote-Taker 3, genome maps of phold annotations, highlighting
MCP/TerL/Portal protein genes. Only contigs with under 200 genes shown for readability. (E)
Like (D) but for viruses in this dataset only identified by geNomad.
313

314   Figure S4

Hot Springs virus MAGs

Anaerobic Digester virus MAGs

315
Virus MAG Hallmark Comparison for Shared and Unique Detections. *(A) Comparison of*
hallmark genes for viruses identified/discovered between geNomad and Cenote-Taker 3 in a
dataset of circular MAGs from hot spring long read metagenome assembly. Cenote-Taker 3
hallmark gene counts. (B) Like (A), but geNomad hallmark gene counts. (C) Like (A) but for
circular MAGs from anaerobic digester long read metagenome assembly. Cenote-Taker 3
hallmark gene counts. (D) Like (C) but geNomad hallmark gene counts.
322

324 Figure S5

326
327 **Virus Discovery on Short-Read Assemblies.** *(A) Three bulk WGS sequencing runs for stool*
328 *samples were downloaded from SRA and assembled. Cenote-Taker 3 and geNomad were run*
329 *with comparable settings, and specific contigs that are predicted to be viruses are compared.*
330 *(B) Like A but with Virus-like Particle preps from stool samples.*
331

332
333
334 Table 2: Discovery Datasets

Dataset	Description	Size	Sequences
DRR290133	Long-read assembly, circular contigs	0.168 Gb	301
ERR10905741	Long-read assembly, circular contigs	0.175 Gb	390
ERR8081307	Short-read VLP assembly	0.014 Gb	5,666
ERR8081362	Short-read VLP assembly	0.007 Gb	2,699
ERR8081370	Short-read VLP assembly	0.006 Gb	3,673
ERR13455686	Short-read bulk WGS assembly	0.018 GB	4,909
SRR36807671	Short-read bulk WGS assembly	0.032 Gb	16,397
SRR36931851	Short-read bulk WGS assembly	0.18 Gb	67,543

335 Computational Performance and Resource Scaling

In an era where large metagenomic studies often produce tens to hundreds of gigabases (Gb)
of metagenomic contigs, it is important to understand how your software of choice scales.
Sampling a large pool of metagenomic contigs at 3% (0.15 Gb), 10% (0.49 Gb), 30% (1.50 Gb),
and 100% (5.18 Gb) (Table 3), we compared the wall time and random-access memory usage
of Cenote-Taker 3 and geNomad on compute nodes with 1 to 32 CPUs (central processing
units).
342

This benchmark demonstrates that both Cenote-Taker 3 and geNomad can handle very large
individual datasets with these resources. Cenote-Taker 3 was faster (higher throughput) when
using 1 or 2 CPUs, there were data-dependent results for 4 or 8 CPUs, and geNomad had
superior throughput with 16 or 32 CPUs (Fig. S6A-B). In all cases, however, geNomad was
most memory-efficient, likely due to Cenote-Taker 3 using pyhmmer for heavy computation
whereas geNomad does not (Fig. S6C).
Cenote-Taker 3's parallel scaling efficiency falls off above 4 CPUs and falls more steeply than
geNomad (Fig. S6D). Therefore, we can recommend that users wishing to run Cenote-Taker 3
on many datasets deploy compute nodes with 4 CPUs for optimal efficiency.
352

354
Performance Scaling for Virus Discovery. *Three large metagenomic read sets (SRA:*
DRR582205, ERR9769281,ERR10905741) were assembled and these assemblies were

combined to make an extremely large "stress test" for Cenote-Taker 3 and geNomad. The 100%
dataset is 5.18 Gb of contigs; the 30% subset is 1.50 Gb; the 10% subset is 0.49 Gb; the 3%
subset is 0.15 Gb. These different subsets were fed to Cenote-Taker 3 and geNomad with
different resource allowances. (A) Runtime by CPU count and dataset size. (B) Throughput
(Gb/hour) with different resource allowances. (C) Memory efficiency (Gb per Gigabyte of max
RAM) with different resource allowances. (D) Parallel scaling efficiency.
363
364 Table 3: Resource Scaling Datasets

Dataset	Subset	Size	Sequences
Large Metagenome (DRR582205 + ERR9769281 + ERR10905741)	100%	5.18 Gb	177,667
Large Metagenome (DRR582205 + ERR9769281 + ERR10905741)	30%	1.50 Gb	53,667
Large Metagenome (DRR582205 + ERR9769281 + ERR10905741)	10%	0.49 Gb	17,876
Large Metagenome (DRR582205 + ERR9769281 + ERR10905741)	3%	0.15 Gb	5,417

Other Features: Taxonomy, Prophage Extraction

Cenote-Taker 3 also assigns hierarchical taxonomy of virus contigs based on identity of its
"hallmark" genes to GenBank virus records. A comparison of the aforementioned UHGV dataset
of 100 high-quality MAGs shows very similar output to geNomad (Fig. S7A). Next, thousands of
random GenBank genomes with NCBI taxonomy labels were downloaded, and Cenote-Taker 3
was used to annotate these to determine taxonomical concordance. For genomes where
Cenote-Taker 3 detects a marker gene, we see >89% agreement with GenBank down to the
family level (Fig. S7B). Cenote-Taker 3 will only classify genomes for which a hallmark gene is
detected. When considering all contigs from this set, the accuracy drops to 73% at the family
level (Fig. S7C), mostly due to the many reverse-transcribing viruses in GenBank, which
Cenote-Taker 3 DB does not contain hallmark genes for, and small segments of segmented
viruses.
378
Prophage extraction from bacterial chromosomes is performed by finding regions with virus
"hallmark" genes and scoring surrounding genes for virus vs bacterial features and clipping the
prophage where high bacterial gene content begins. Cenote-Taker 3 was compared to
geNomad, VirSorter 2, and VIBRANT in a study by Wirbel, Hickey et al.[22] for prophage
boundary prediction accuracy. This study used soft clipping information to find prophage
excision/integration points in bacterial MAGs and compared these coordinates to the boundaries
predicted by the software. Overall, geNomad had the lowest error, and Cenote-Taker 3 had
middle of the road performance. Cenote-Taker 3 boundary error was on par with geNomad after
CheckV post-processing, suggesting a practical approach for Cenote-Taker 3-based pipelines.

389
390   **Taxonomic Benchmarking**. *(A) 100 high-quality virus MAGs from the UHGV dataset were run*

397
398

Discussion

Cenote-Taker 3 is an ideal piece of software for annotation and cataloging of the virome,
particularly if the focus is on high-quality genomes. It readily scales from single virus genomes
to thousands of metagenomes. It can be used as an end-to-end program to identify virus MAGs,
annotate their genes, excise prophage sequences from bacterial genomes, and taxonomically
label virus sequences. Alternatively, it can also be used to simply annotate genes and report
taxonomy of pre-discovered virus MAGs.
406
Cenote-Taker 3 reliably reports on the function of important genes and identifies viruses in
complex datasets. Some existing software outperforms Cenote-Taker 3 in some ways, but this
tool stands out for its combination of performance and accuracy. For example, the
benchmarking performed showed that Cenote-Taker 3 annotated essential genes (MCP, TerL,
portal protein for head-tail phages; RdRP and Capsid/Coat for RNA viruses) more accurately
than other tools and finished annotation tasks more quickly than most tools (Fig. 2, Fig. S2-3).
Virus discovery tests showed that Cenote-Taker 3 identifies some highly convincing virus MAGs
that are missed by the field standard geNomad (Fig. 4-5). Therefore, we believe it's justified to
say that Cenote-Taker 3 occupies an impactful niche in viromics workflows, excelling at 1)
functional annotation of previously uncharacterized virus genomes and 2) virome catalog
building with a focus on complete/near complete MAGs. Cenote-Taker 3 will be essential for
virome cataloging projects alongside other software, such as geNomad, used in this
manuscript's benchmarking.
420
421   Comparative tests for annotation and discovery of viruses, such as those performed in this
422   study, also present discrete and useful opportunities for all software packages compared to
423   improve. For example, when other software identifies a major capsid protein gene that Cenote-
424   Taker 3 does not, this signal can be validated (e.g. using structural prediction) and the Cenote-
425   Taker 3 database can be improved accordingly.
426
427   As long-read sequencing technologies continue to mature and become more affordable, tools
428   like Cenote-Taker 3 will become increasingly valuable for producing high-quality complete viral
429   genome annotations from metagenomic data. Future developments will focus on expanding
430   reference databases to improve annotation of currently unknown genes, particularly those from
431   under-sampled environments and viral lineages.
432

433 By offering simplified installation through Bioconda along with high performance on standard
434 consumer hardware and high-performance compute systems, Cenote-Taker 3 contributes to
435 democratizing viral genomics research, enabling labs with limited computational resources to
436 conduct sophisticated analyses.

437 Methods

438 Cenote-Taker 3 Code Details

Cenote-Taker 3 is a command-line interface tool coded using Python and Bash. It imports
and/or calls several bioinformatics packages. To read and write sequencing records,
Biopython[23] and Seqkit[24] are used. To predict open-reading frames, pyrodigal-gv[5] is used by
default, and pyrodigal and phanotate[6] are also available per command-line argument. Gene
functional annotation is performed using pyhmmer[6] and mmseqs2[18]. Hhsuite[25] and its
databases can also be used. trnascan-se[26] is used to predict tRNA elements. Bedtools[27] is used
to deal with genomic ranges and coordinates. Minimap2[28] and samtools[29] are used for optional
read alignment and quantification steps.
447
448 All code is publicly available and maintained on GitHub (https://github.com/mtisza1/Cenote-
449 Taker3). The repo is also automatically backed up in Zenodo located at
450 DOI:10.5281/zenodo.17290322.
451
452 Basic installation instructions using the mamba/conda package manager:
453
454 **mamba create -n ct3_env bioconda::cenote-taker3**
455
456 Bioconda package page can be accessed here. Quay container image, generated automatically
457 by Bioconda, can be accessed here.

458 Cenote-Taker 3 Database Details

for the HMM databases, used for virus "hallmark" (virion, rdrp, and dnarep) gene detection as
well as for some additional gene annotation tasks, the Cenote-Taker 2 database was expanded
with gene models from PHROGs[30], efams[31], sequences from the Buck et al. survey[32], and
manually curated models. All model names were manually checked and updated as necessary
to ensure similar models returned the same annotation. Notably, Cenote-Taker 3 hallmark
databases do not contain gene models for reverse transcribing viruses (class Revtraviricetes).
This is a design choice made to avoid overloading of results with endogenous retroviruses of
eukaryotic genomes.
467
For the taxonomy database, NCBI's NR Clustered cd90 amino acid sequence database was
downloaded on December 12, 2023, and filtered for records belonging the "Viruses" taxon.
Then, these records were queried against the Cenote-Taker 3 hallmark databases (virion, rdrp,

and dnarep) (DB v3.1.1), and hits were returned by standard Cenote-Taker 3 cut-offs.
Hierarchical taxonomy labels were retrieved from GenBank for these selected records using
taxonkit[33]. Only records which contained class, family, and genus labels were kept for the final
taxonomy database. Mmseqs2 was used to create a taxDB with these records.
475
476 Database files can be accessed on Zenodo (DOI 10.5281/zenodo.8429308)

Annotation Benchmarks

478 Annotation benchmarks were performed using a 2023 MacBook Pro laptop computer with 16
479 GB of memory and an Apple M2 Pro chip running MacOS. Resource scaling benchmarks were
480 performed on compute nodes with Intel "Emerald Rapids" with 32 central processing units and
481 large onboard cache with 1 TB memory each.
482
483 The UHGV, Gut Circular, and Seawater Circular, Seawater virus-like particle RNA virus MAG,
484 GenBank, RefSeq, short-read assemblies, and large metagenome sequences are available at
485 Zenodo. Seawater virus-like particle RNA sequencing reads and assemblies are available on
486 NCBI under bioproject PRJNA605028.
487
488 The following software package versions and databases were used: geNomad v1.11.1 (DB
489 v1.9), MetaCerberus v1.4.0 (DB v1.4), Pharokka v1.7.3 (DB v1.4.0), phold v0.2.0 (DB v2),
490 Cenote-Taker 3 v3.4.1 (DB v3.11).
491
All annotation software tested used pyrodigal-gv to conduct open reading frame prediction,
making annotation rates as comparable as possible. The most appropriate setting for annotation
were used based on software documentation. These are the threshold used by each tool,
pharokka hmmer e-value $\leq 1e^{-5}$, MetaCerberus hmmer e-value $\leq 1e^{-9}$, Cenote-Taker 3 hmmer
e-value $1e^{-7}$ and mmseqs search e-value $\leq 1e^{-3}$, genomad mmseqs search $\leq 1e^{-3}$, phold
foldseek e-value $1e^{-3}$. Example commands are as follows:
498
499 **genomad annotate --splits 4 seqs.fna gnmd_test1_out genomad_dbs/**
500
501 **metacerberus.py --prodigalgv seqs.fna --hmm "ALL" --dir_out metc_test1_out**
502
503 **pharokka.py -m -s -g prodigal-gv --meta_hmm -d pharokka_db -i seqs.fna -o**
504 **phar_test1_out**
505
506 **phold run -i seqs.fna -o phold_test1_out**
507
508 **cenotetaker3 -c seqs.fna -r ct3_test1_out -p F -am T**
509
510 All scripts to reproduce analyses of annotation outputs are available on GitHub
511 (https://github.com/mtisza1/ct3_benchmarks), and data are available on Zenodo.

Discovery Benchmarks

Circular MAG assemblies from hot spring reads (DRR290133) and anaerobic digester sample reads (ERR10905741) are available on [Zenodo](#). Reads were downloaded from SRA and assembled with myloasm v0.1.0 with default settings. Circularity of contigs is reported in myloasm output sequence headers.

GeNomad end-to-end pipeline was run on these data with default settings plus the "--enable-score-calibration" flag. Cenote-Taker 3 was run with the flags "-p T --lin_minimum_hallmark_genes 2 --circ_minimum_hallmark_genes 2" as recommended on the GitHub README for whole genome shotgun metagenome data.

Tool-specific contigs were annotated with phold v0.2.0 using default settings and visualized with Rstats package gggenomes[34].

Author Contributions Statement

Conceptualization: M.J.T., S.J.C., J.F.P.
Methodology: M.J.T., A.V.
Investigation: M.J.T., A.V.
Visualization: M.J.T.
Funding acquisition: S.J.C., J.F.P.
Project administration: S.J.C.
Supervision: J.F.P., S.J.C.
Writing—original draft: M.J.T., S.J.C.
Writing—review and editing: M.J.T., S.J.C., J.F.P., A.V.

Acknowledgements

We are grateful all insights and suggestions from early users of this software, especially Dr. Chris Buck.

Competing Interests Statement

The authors declare no competing interests.

References

Camargo, A. P. *et al.* IMG/VR v4: an expanded database of uncultivated virus genomes within a framework of extensive functional, taxonomic, and ecological metadata. *Nucleic Acids Res* **51**, D733-D743, doi:10.1093/nar/gkac1037 (2023).

Guo, J. *et al.* VirSorter2: a multi-classifier, expert-guided approach to detect diverse DNA and RNA viruses. *Microbiome* **9**, 37, doi:10.1186/s40168-020-00990-y (2021).

Kieft, K., Zhou, Z. & Anantharaman, K. VIBRANT: automated recovery, annotation and curation of microbial viruses, and evaluation of viral community function from genomic sequences. *Microbiome* **8**, 90, doi:10.1186/s40168-020-00867-0 (2020).

Camargo, A. P. *et al.* Identification of mobile genetic elements with geNomad. *Nat Biotechnol* **42**, 1303-1312, doi:10.1038/s41587-023-01953-y (2024).

Larralde, M. Pyrodigal: Python bindings and interface to Prodigal, an efficient method for gene prediction in prokaryotes. *Journal of Open Source Software*, doi:10.21105/joss.04296 (2022).

McNair, K., Zhou, C., Dinsdale, E. A., Souza, B. & Edwards, R. A. PHANOTATE: a novel approach to gene identification in phage genomes. *Bioinformatics* **35**, 4537-4542, doi:10.1093/bioinformatics/btz265 (2019).

Bouras, G. *et al.* Pharokka: a fast scalable bacteriophage annotation tool. *Bioinformatics* **39**, doi:10.1093/bioinformatics/btac776 (2023).

Figueroa Iii, J. L., Dhungel, E., Bellanger, M., Brouwer, C. R. & White Iii, R. A. MetaCerberus: distributed highly parallelized HMM-based processing for robust functional annotation across the tree of life. *Bioinformatics* **40**, doi:10.1093/bioinformatics/btae119 (2024).

Bouras, G. *et al.* Protein structure-informed bacteriophage genome annotation with Phold. *Nucleic Acids Res* **54**, doi:10.1093/nar/gkaf1448 (2026).

Pavan, R. R., Sullivan, M. B. & Tisza, M. J. CRESSENT: a bioinformatics toolkit to explore and improve ssDNA virus annotation. *Microb Genom* **12**, doi:10.1099/mgen.0.001632 (2026).

Ho, S. F. S., Wheeler, N. E., Millard, A. D. & van Schaik, W. Gauge your phage: benchmarking of bacteriophage identification tools in metagenomic sequencing data. *Microbiome* **11**, 84, doi:10.1186/s40168-023-01533-x (2023).

Agustinho, D. P. *et al.* Unveiling microbial diversity: harnessing long-read sequencing technology. *Nat Methods* **21**, 954-966, doi:10.1038/s41592-024-02262-1 (2024).

Goldfarb, T. *et al.* NCBI RefSeq: reference sequence standards through 25 years of curation and annotation. *Nucleic Acids Res* **53**, D243-D257, doi:10.1093/nar/gkae1038 (2025).

Tisza, M. J., Belford, A. K., Dominguez-Huerta, G., Bolduc, B. & Buck, C. B. Cenote-Taker 2 democratizes virus discovery and sequence annotation. *Virus Evol* **7**, veaa100, doi:10.1093/ve/veaa100 (2021).

Camargo, A. P. *et al.* A genomic atlas of the human gut virome elucidates genetic factors shaping host interactions. *bioRxiv*, doi:10.1101/2025.11.01.686033 (2025).

van Kempen, M. *et al.* Fast and accurate protein structure search with Foldseek. *Nat Biotechnol* **42**, 243-246, doi:10.1038/s41587-023-01773-0 (2024).

Cook, R. *et al.* The long and short of it: benchmarking viromics using Illumina, Nanopore and PacBio sequencing technologies. *Microb Genom* **10**, doi:10.1099/mgen.0.001198 (2024).

18   Steinegger, M. & Soding, J. MMseqs2 enables sensitive protein sequence searching for
the analysis of massive data sets. *Nat Biotechnol* **35**, 1026-1028, doi:10.1038/nbt.3988
(2017).
19   Kato, S., Masuda, S., Shibata, A., Shirasu, K. & Ohkuma, M. Insights into ecological
roles of uncultivated bacteria in Katase hot spring sediment from long-read
metagenomics. *Front Microbiol* **13**, 1045931, doi:10.3389/fmicb.2022.1045931 (2022).
20   Benoit, G. *et al.* High-quality metagenome assembly from long accurate reads with
metaMDBG. *Nat Biotechnol* **42**, 1378-1383, doi:10.1038/s41587-023-01983-6 (2024).
21   Shaw, J., Marin, M. G. & Li, H. High-resolution metagenome assembly for modern long
reads with myloasm. *bioRxiv*, doi:10.1101/2025.09.05.674543 (2025).
22   Wirbel, J. *et al.* Long-read metagenomics reveals phage dynamics in the human gut
microbiome. *Nature* **649**, 982-990, doi:10.1038/s41586-025-09786-2 (2026).
23   Cock, P. J. *et al.* Biopython: freely available Python tools for computational molecular
biology and bioinformatics. *Bioinformatics* **25**, 1422-1423,
doi:10.1093/bioinformatics/btp163 (2009).
24   Shen, W., Le, S., Li, Y. & Hu, F. SeqKit: A Cross-Platform and Ultrafast Toolkit for
FASTA/Q File Manipulation. *PLoS One* **11**, e0163962,
doi:10.1371/journal.pone.0163962 (2016).
25   Steinegger, M. *et al.* HH-suite3 for fast remote homology detection and deep protein
annotation. *BMC Bioinformatics* **20**, 473, doi:10.1186/s12859-019-3019-7 (2019).
26   Chan, P. P., Lin, B. Y., Mak, A. J. & Lowe, T. M. tRNAscan-SE 2.0: improved detection
and functional classification of transfer RNA genes. *Nucleic Acids Res* **49**, 9077-9096,
doi:10.1093/nar/gkab688 (2021).
27   Quinlan, A. R. & Hall, I. M. BEDTools: a flexible suite of utilities for comparing genomic
features. *Bioinformatics* **26**, 841-842, doi:10.1093/bioinformatics/btq033 (2010).
28   Li, H. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics* **34**, 3094-
3100, doi:10.1093/bioinformatics/bty191 (2018).
29   Danecek, P. *et al.* Twelve years of SAMtools and BCFtools. *Gigascience* **10**,
doi:10.1093/gigascience/giab008 (2021).
30   Terzian, P. *et al.* PHROG: families of prokaryotic virus proteins clustered using remote
homology. *NAR Genom Bioinform* **3**, lqab067, doi:10.1093/nargab/lqab067 (2021).
31   Zayed, A. A. *et al.* efam: an expanded, metaproteome-supported HMM profile database
of viral protein families. *Bioinformatics* **37**, 4202-4208,
doi:10.1093/bioinformatics/btab451 (2021).
32   Buck, C. B. *et al.* Widespread Horizontal Gene Transfer Among Animal Viruses. *bioRxiv*,
doi:10.1101/2024.03.25.586562 (2024).
33   Shen, W. & Ren, H. TaxonKit: A practical and efficient NCBI taxonomy toolkit. *J Genet
Genomics* **48**, 844-850, doi:10.1016/j.jgg.2021.03.006 (2021).
34   Hackl, T., Duponchel, S., Barenhoff, K., Weinmann, A. & Fischer, M. G. Virophages and
retrotransposons colonize the genomes of a heterotrophic flagellate. *Elife* **10**,
doi:10.7554/eLife.72674 (2021).
630