CASTLE: a training-free foundation-model pipeline for cross-species behavioral classification

Yu-Shun Liu[1,2,3], Han-Yuan Yeh[1,2], Yu-Ting Hu[1,4], Bing-Shiuan Wu[1,2,5], Yi-Fang Chen[1,4.], Jia-Bin Yang[6], Sureka Jasmin[7], Ching-Lung Hsu[2,4,8], Suewei Lin[1,2], Chun-Hao Chen[6] and Yu-Wei Wu[1,2,4,5,*]

[1] Institute of Molecular Biology, Academia Sinica, Taipei, Taiwan.
[2] Neuroscience Program in Academia Sinica, NPAS, Academia Sinica, Taipei, Taiwan
[3] Department of Computer Science, National Yang Ming Chiao Tung University, Hsinchu, Taiwan
[4] Genome and Systems Biology Degree Program, College of Life Science, National Taiwan University, Taipei, Taiwan
[5] Department of Life Science, National Taiwan University, Taipei, Taiwan
[6] Institute of Molecular and Cellular Biology, College of Life Science, National Taiwan University, Taipei, Taiwan
[7] Taiwan International Graduate Program in Interdisciplinary Neuroscience, National Taiwan University and Academia Sinica, Taipei, Taiwan
[8] Institute of Biomedical Sciences, Academia Sinica, Taipei, Taiwan

Figures: 8

Supplementary Figure: 6

Key words: Computational ethology, Visual foundation models, Unsupervised behavioral pattern discovery, Cross-species analysis, Zero-shot

Running title: CASTLE: training-free pipeline for behavioral classes discovery

*Correspondence should be addressed to:

Dr. Yu-Wei Wu

Institute of Molecular Biology, Academia Sinica, Taipei 115, Taiwan;

wuyuwei@as.edu.tw +886-2-2789-9334 (Tel)

Summary

Accurately quantifying animal behavior at scale and without manual labels is a long-standing bottleneck for neuroscience and ethology. We present CASTLE (Combined Approach for Segmentation and Tracking with Latent Extraction), an end-to-end training-free, label-free pipeline that combines state-of-the-art segmentation, object tracking, and foundation model-based feature extraction to generate detailed, orientation-invariant descriptors of movement. Hierarchical clustering of these descriptors through an interactive GUI yields distinct behavioral classes without predefined categories, revealing previously unrecognized behavioral motifs. *CASTLE*'s versatility is demonstrated across model organisms, including skilled reaching and open-field exploration in mice, spontaneous locomotion and grooming in fruit flies, and foraging in *C. elegans*, consistently exceeding 90% agreement with expert human labels and even identifying disease-relevant phenotypes in a Parkinsonian mouse model. Notably, *CASTLE*'s automatically tracked movements match conventional pose-tracking methods in neural decoding accuracy, confirming that its label-free approach does not compromise neurophysiological insights. A user-friendly graphical interface further makes this advanced analysis accessible to non-computational researchers, establishing *CASTLE* as a broadly applicable, scalable framework for cross-species behavioral phenotyping.

Introduction (653)

Quantifying behavior with the same rigor that we quantify neural activity is now a central mandate in systems neuroscience[1-3], psychiatry[4], and drug discovery[5], because behavior provides the ultimate read-out of neural computations[6] and gene–environment interactions[7]. Nevertheless, the field still relies heavily on labor-intensive scoring or task-specific pose-tracking[5,8-10], creating a significant bottleneck between data collection and biological insight. Contemporary behavioral quantification faces the challenge of mapping video pixels to features that are actually relevant for specific research questions. Ideally, feature extraction should maximize relevant behavioral information while minimizing irrelevant details.

Data-driven approaches have emerged to address these challenges. Berman *et al.* pioneered a data-driven framework[8] emphasizing unsupervised methods, particularly advantageous for identifying novel behaviors elicited by experimental manipulations[9,11,12]. Such unsupervised techniques circumvent limitations inherent in supervised approaches, which rely on predefined categories and manual labeling[13]. Meanwhile, advances in deep learning-based pose estimation have greatly reduced keypoint annotation requirements via transfer learning. Tools like *DeepLabCut*[14] and *Lightning Pose*[15] leverage ImageNet-trained backbones to extract spatial features, spurring numerous supervised and unsupervised methods for behavior analysis[9,12,16-24]. However, standard keypoint-based methods reduce animals to sparse skeletons, fundamentally constraining our ability to discover unexpected behavioral patterns that don't fit predetermined landmark configurations.

To preserve richer behavioral dynamics, alternative approaches have been developed. Region-based detectors (*e.g.*, R-CNN architectures[5,25]) and object detectors like *YOLO*[26] maintain spatial contexts, while spatiotemporal techniques such as "pattern images[27] and optical flow analysis[28] capture pixel-level motion dynamics. Visual Foundation Models (VFMs)[29,30] have recently revolutionized behavioral analysis, offering powerful zero-shot capabilities for spatial feature extraction without additional training. Models like *Selfee*[31], *Animal-JEPA*[32], and *VideoPrism*[33] leverage self-supervised learning on image data,

capturing detailed visual features useful across diverse behavioral tasks. *MouseGPT*[34]

further integrates large language models, demonstrating the robust potential of VFMs for

direct behavioral description.

Despite these advances, a key conceptual challenge remains: most existing

approaches—including those leveraging VFMs—still require task-specific fine-tuning or

retraining to achieve optimal performance, demanding substantial computational

resources and annotated datasets that many laboratories cannot readily provide.

Moreover, the rich visual features extracted by powerful VFMs inevitably include many

task-irrelevant components, introducing noise for specific behavioral analyses.

Developing a training-free method to focus pre-trained features on behaviorally relevant

information is therefore a critical and largely unexplored opportunity to democratize

advanced behavioral analysis. No current framework fully addresses this gap: in particular,

no existing approach combines segmentation, tracking, and latent feature clustering in

one generalizable pipeline without retraining.

To tackle these challenges, we introduce *CASTLE* (*C*ombined *A*pproach for

*S*egmentation and *T*racking with *L*atent *Ex*traction), a pipeline designed to fully leverage

VFMs by using different foundation models for complementary roles and by employing a

"deep" use of visual latent features to refine behavior classification. *CASTLE* integrates

zero-shot segmentation (*Segment Anything Model*[35]), robust tracking (*DeAOT*[36]), and

dense visual feature extraction (*DINOv2*[37]). By segmenting each ROI and then encoding

video frames with a foundation model, *CASTLE* produces focused latent features that

filter out background noise and are invariant to orientation or viewpoint. Crucially, this

pipeline is training-free and requires no task-specific network retraining or fine-tuning. The

resulting latent features are clustered hierarchically using a multi-stage nonlinear

dimensionality reduction and clustering approach, enabling fine-grained identification of

behavioral classes without any predefined labels. We validate *CASTLE* across four

distinct contexts—skilled reach-and-grasp and open-field assays in mice, spontaneous

locomotion and grooming in *Drosophila*, and search behaviors in *C. elegans*. Without a

single behavior-specific label or network retraining, *CASTLE* recovers expert-level

annotations (>90 % agreement with human validation), uncovers previously unnoticed

sub-actions, and detects disease-relevant phenotypes in a Parkinsonian mouse model.
CASTLE eliminates the reliance on manual labeling and task-specific training. This
foundation-model pipeline thus establishes a scalable framework for high-resolution,
cross-species behavioral phenotyping that breaks the field's dependence on manual
labelling while having a visualized curation for the clustering process guided by
meaningful visual ROIs. This novel approach continues the progression from supervised
learning through transfer learning to VFMs, significantly enhancing behavioral
classification capabilities and reliability for neuroscientific research.

Results

***CASTLE* accurately extracts and identifies discrete behavioral classes from video**
data.

We developed the *CASTLE* pipeline to facilitate precise behavioral classification directly
from raw video data (**Fig. 1**). The flowchart of the *CASTLE* pipeline is provided in **Fig. 1a**
with detailed mathematic descriptions in **Fig. S1a**. Initially, *CASTLE* uses a user-define
and semi-automatic segmentation approach where users define regions-of-interest (ROIs)
using *SAM*[35] (**Fig. 1b; Fig. S1b,c**), typically corresponding to key anatomical landmarks,
such as paws and nose in mice (**Fig. 1c; Fig. S1b**). These ROIs are tracked frame-by-
frame using the *DeAOT* video object segmentation model[36], yielding robust spatial
tracking that captures movement trajectories and changes in ROI area over time.

To ensure comprehensive visual semantic capture, *CASTLE* employs *DINOv2*, a state-
of-the-art visual foundation model[37], encoding each video frame into rich 768-dimensional
visual latent features (**Fig. 1c**). For visualization and enhancing interpretability, the visual
latent features undergo dimensionality reduction via Principal Component Analysis (PCA)
reveals a stable representation of body parts of the mouse over different image frames
(**Fig. 1c**, *right panel*; **Fig. S1d**). These latent representations are combined with ROI-
specific spatial data, resulting in "focused visual latent features" that accurately represent
the visual dynamics associated with each anatomical feature of interest (**Fig. 1d**). The
temporal dynamics of "focused visual latent features" were visualized by PCA colormap
(**Fig. 1d**). Notably, only the left paw (*ROI1*) showed drastic change over time, indicating

the variation in the posture of the left paw but not the right paw (ROI2) and the nose

(ROI3). Without focused latent extraction, the first 3 PC features do not reflect clear

changes in all body parts (**Fig. S1d**), suggesting the importance of the application of

"Focusing".

Finally, *CASTLE* performs latent feature exploration by temporally concatenating the

extracted ROI-specific latent signals, which are embedded into a lower-dimensional

space using Uniform Manifold Approximation and Projection (*UMAP*)[38]. Clusters formed

through Density-Based Spatial Clustering of Applications with Noise (*DBSCAN*)[39] define

initial behavioral classes (**Fig. 1a and 1e**). Further hierarchical dimensionality reduction

groups these initial classes along the temporal axis, revealing consistent, repetitive

behavioral patterns termed behavioral classes (**Fig. 1e**). This comprehensive and efficient

pipeline (**Fig. 1a**) thus enables unbiased, high-throughput behavioral quantification from

unannotated video data.

Intuitive Graphical User Interface (GUI) for behavioral analysis using *CASTLE*

The *CASTLE* pipeline is integrated into a user-friendly graphical user interface (GUI),

making behavioral analysis streamlined and intuitive. The interface simplifies complex

analytical procedures into clearly defined steps. Initially, users employ the segmentation

and tracking module (**Fig. 2a and 2d**) to interactively define and adjust ROIs across video

frames. In this module, user input establishes initial tracking conditions, while automated

position predictions facilitate iterative adjustments, ensuring robust and accurate ROI

tracking.

In the subsequent latent feature extraction step (**Fig. 2b and 2e**), visual data from the

video is combined seamlessly with ROI information to generate ROI-specific latent

features. These visual latent features effectively capture essential dynamics critical for

distinguishing behaviors, forming a powerful intermediate representation for detailed

analysis. Lastly, the latent exploration module (**Fig. 2c and 2f**) offers extensive tools for

visualizing and analyzing latent features. Users can load videos along with extracted

latent data, set appropriate temporal resolutions, and conduct initial dimensionality

reduction using *UMAP* (**Fig. S2**). Additionally, the interface supports recursive refinement through hierarchical dimensionality reductions within selected clusters. *DBSCAN* clustering clearly differentiates behavioral classes, and interactive verification tools allow users to precisely localize and validate behavioral classes temporally. Collectively, the intuitive GUI implementation of *CASTLE* significantly reduces the complexity associated with advanced behavioral analyses, enabling sophisticated latent-space exploration accessible even to researchers without extensive computational expertise.

Comparison of *CASTLE* and *DeepLabCut* in paw tracking

We aimed to evaluate whether *CASTLE* could achieve tracking performance comparable to established marker-based methods, such as *DeepLabCut* (*DLC*), while providing additional advantages in efficiency and robustness. Comparative analyses between *CASTLE* and *DLC* for paw tracking during mouse reaching tasks revealed similar tracking accuracy. Visual inspection demonstrated comparable trajectories generated by *CASTLE* and those labeled by *DLC*, particularly during significant movements exceeding defined displacement thresholds (**Fig. 3a**). However, trajectories from *DLC* consistently exhibited greater pre-movement displacement and higher noise levels, especially evident during stationary/resting phases across multiple trials (**Fig. 3b**). Such jitter in *DLC*-generated trajectories likely arises from minor variations inherent in manually labeled ground truth data used to train the *DLC* model. Quantitative assessments further supported *CASTLE*'s advantage in noise reduction, showing significantly lower standard deviation values of paw speed during resting states compared to *DLC* (Wilcoxon signed-rank test, p < 0.0001; **Fig. 3c-d**). This reduced jitter underscores *CASTLE*'s robustness and highlights its efficiency, as it eliminates the need for extensive manual labeling or prolonged neural network training periods required by *DLC*.

We further validated tracking performance by employing neural decoding as a benchmark. Accurate paw position tracking is crucial for interpreting the neural correlates of behavior, making neural decoding performance a suitable and biologically relevant measure for assessing tracking accuracy (see *Method details*). Neural decoding analyses using simultaneously recorded neural spiking activity from sensorimotor cortices indicated

comparable decoding accuracy for paw positions (R^2) between *CASTLE* and *DLC* (n =

10 independently trained models, *CASTLE*: R^2 = 0.8554 ± 0.0135, *DLC*: R^2 = 0.8524 ±

0.0086, student t-test, p = 0.5791 **Fig. 3e-f**). Importantly, models trained using *CASTLE*-

derived trajectories demonstrated significantly lower mean squared error (MSE) during

training and validation (**Fig. 3g**). In addition, similar tracking performance of *CASTLE*

compared with *DLC* is also archivable in open filed tests (**Fig. S3**). Collectively, these

findings underscore *CASTLE's* practical utility, efficiency, and robustness, making it

particularly suited for high-throughput and reliable behavioral studies.

Hierarchical extraction and validation of behavioral classes in a mouse reach-and-

grasp task using *CASTLE*

Given *CASTLE*'s advantages in efficiently capturing subtle behavioral dynamics without

extensive manual labeling, we explored its capacity to identify detailed behavioral classes

within complex reach-and-grasp tasks. These tasks present substantial analytical

challenges due to the intricate and subtle variations in paw postures and movements[40],

which standard key-point labeling methods often fail to capture adequately. Specifically,

typical key-point labeling methods, such as *DLC*, require detailed and extensive labeling

of anatomical landmarks (e.g., finger joints or ankle positions) to accurately represent

nuanced paw postures during grasping[12,14]. Such detailed labeling is not only highly time-

consuming but also demands high-quality video data, significantly increasing costs and

reducing practical usability. *CASTLE* leverages the visual foundation model *DINOv2* to

directly encode comprehensive visual information from video frames, overcoming these

limitations.

Initially, we manually defined five behavioral clusters: "on perch," "lifting," "grabbing," "at

mouth," and "on stage" (**Fig. 4a, c**). *CASTLE* generated high-dimensional focused visual

latent features from selected ROIs, encoding semantic visual information from front and

side views (768 dimensions each, totaling 1536 dimensions; **Fig. 4a**). Movement

kinematic features (position, speed, area) were extracted during segmentation and

tracking but did not notably enhance classification quality (**Fig. S4a**). Ablation studies

confirmed the necessity of both "focused ROI extraction" and "visual latent features" for effective classification (**Fig. S4b,c**).

To systematically explore behavioral clusters, we applied a hierarchical clustering strategy in *CASTLE*'s Latent Explorer (**Fig. 4b**). Iterative dimensionality reduction via *UMAP* first captured broad behavioral distinctions, subsequently refining local latent structures to isolate subtle differences (see **Fig. S2a-d** for *UMAP* parameters consideration), similar to the delineation of skilled forelimb movements described previously[12,14,40] (**Fig. 4b**).

We validated *CASTLE*-derived classifications against expert annotations, achieving a weighted average F1 score of 0.9015. Confusion matrix analysis showed discrepancies primarily involving transitions between "lifting," "grabbing," and "at mouth" behaviors, likely due to expert labeling variability and subtle behavioral transitions (**Fig. 4c-d**). To objectively assess these classifications, we employed neural decoding, as neural signals inherently reflect specific motor behaviors. Neural decoding models (a two-layer GRU[41] with fully connected layers) trained on neural spiking activity across 36 trials demonstrated that *CASTLE*-derived behavior classifications significantly enhanced decoding accuracy for "grabbing" and "at mouth" compared to expert annotations ("grabbing", manual label: f1 score = 0.8459 ± 0.0143 , *CASTLE*: $R^2 = 0.9193 \pm 0.0085$, Wilcoxon rank-sum test, $p < 0.001$; "At mouth ", manual label: $R^2 = 0.8770 \pm 0.0082$, *CASTLE*: $R^2 = 0.9162 \pm 0.0080$, Wilcoxon rank-sum test, $p < 0.001$), aligning closely with underlying neural representations (**Fig. 4e**). Notably, *CASTLE* identified two subtle behavioral variations overlooked by expert annotations: "food approaching mouth" (transitional lift between "grabbing" and "at mouth") and "food releasing at mouth" (occurring post "at mouth"). Visual embeddings distinctly separated these behaviors, demonstrating *CASTLE*'s potential in uncovering novel behavioral classes and providing deeper insights into skilled motor sequences (**Fig. 4f-g**).

Comprehensive behavioral class identification in mouse open field tests (OFTs) using CASTLE

Considering the limitations of traditional OFT in automatically distinguishing detailed behavioral patterns, we leveraged the *CASTLE* framework to enhance behavioral classification. Traditional OFT typically rely on basic metrics such as locomotion, exploratory activity, and spatial preferences, lacking the ability to automatically classify more complex behaviors like grooming and rearing [42,43]. In contrast, *CASTLE* significantly advances behavioral analysis by automating the precise identification of subtle behaviors such as grooming, supported rearing, and unsupported rearing without extensive manual annotation, thus improving sensitivity, accuracy, and efficiency.

We applied the *CASTLE* pipeline to analyze a 30-minute video recording of a mouse in an OFT environment at 30 Hz (**Fig. 5a**), aiming for automated classification of detailed behaviors. To ensure precise behavioral representation, we removed irrelevant positional and directional features by cropping and aligning ROIs, a critical "focusing" step in *CASTLE* (**Fig. 5a**). ROIs for the body and tail-base were identified via VOS, from which angular metrics (angle, angular velocity) and focused visual latent features were extracted (**Fig.5b**). Directly using kinematic features, including speed, angular velocity, and area of ROI, for hierarchical latent exploration did not achieve clear behavioral classes (**Fig. S4d**). Hierarchical latent exploration using sequential *UMAP* dimensionality reduction enabled effective classification of subtle behaviors from focused visual latent features (768 x 5 dimensions; **Fig.5c**). Initially, grooming behavior was distinctly separated using *UMAP* (time window = 5 frames, 167 ms). A subsequent two-layer *UMAP* approach identified nuanced differences between supported and unsupported rearing behaviors. Due to the high visual similarity between walking and immobility states, which could not be distinguished based on visual features alone, we applied a kinematic threshold of 4 mm/s (**Fig.5c**)[44].

CASTLE successfully classified five distinct behavioral classes: grooming, supported rearing, unsupported rearing, walking, and immobility (**Fig.5d**). Comparative analyses across control and mouse models of Parkinson's disease (PD) — mild (acute MPTP-induced PD model) and severe (6-OHDA-induced hemi-PD model) — revealed distinct behavioral phenotypes (**Fig.5e**). Specifically, mild PD mice exhibited increased overall walking time but reduced occurrences of supported and unsupported rearing. Severe PD mice demonstrated increased immobility, reduced grooming, decreased rearing, and

280 significantly slower walking speeds **(Fig.5f)**. These findings highlight *CASTLE's* robust
281 ability to accurately characterize detailed behavioral phenotypes in both healthy and
282 disease states, underscoring its value in high-throughput behavioral neuroscience
283 research.

Neutralizing location and orientation effects for improved classification

In developing CASTLE, we observed that appropriately focusing on ROIs is crucial to
extract meaningful latent features for behavior classification. This observation implies that
although VFMs capture abundant image information, much of it may be irrelevant or even
detrimental for behavioral analysis. One particularly problematic factor is the animal's
orientation to the camera. Orientation changes can produce large shifts in the latent
feature space that are unrelated to behavior *per se*. Orientation-sensitive features can
sometimes be mitigated by physically aligning subjects in preprocessing (*e.g.*, always
orienting the head in the same direction in each frame; **Fig. 5a**), but such alignment is
often non-trivial for freely moving animals, especially for creatures like *C. elegans*, or
when video quality is limited. We therefore explored strategies to neutralize orientation in
the latent features themselves.
As a first step, we quantified how rotations of the input frames affect the latent
representation. We took example video frames and rotated them by various angles, then
examined the *DINOv2* latent features (**Fig. 6a,b**). Qualitative inspection indicated that
certain latent dimensions were highly sensitive to rotation, while others were relatively
invariant (**Fig. 6a**). Comparing to classification with focused latent extraction and
alignment (**Fig. 6c,d**), directly extract the latent features from original image frames
revealed a strong clustering by absolute orientation and position rather than by behavior,
which degraded the quality of behavioral clustering (**Fig. 6e,f**). Removing only positional
information by introducing "focused" latent feature extraction partially reduced orientation-
related variability, offering moderate improvements in behavioral clustering (**Fig. 6g-h**).
We then implemented a more comprehensive rotation-averaging approach: for each
video frame, we generated 24 rotated copies (every 15°) and averaged the latent
embeddings across all these rotations. This approach dramatically reduced orientation-
specific variance in the latent space and yielded much cleaner behavioral clusters

(**Fig. 6i,j**). Using the orientation-neutralized latent features, *CASTLE* achieved high classification accuracy for all behaviors (average F1 scores >0.9), with misclassifications largely limited to frames at the boundaries between behaviors (**Fig. 6j,k**). Analyses of transition probabilities and confusion (**Fig. 6l,m**) further confirmed that orientation-neutralization greatly improved the consistency and reliability of clustering—errors were minor and predominantly occurred at true behavior transition points. In summary, our results demonstrate that a rotation-based preprocessing strategy can robustly neutralize orientation effects in VFM-based latent features, thereby enhancing automated behavioral classification, especially for organisms or setups where consistent orientation alignment is infeasible.

Unsupervised behavioral classification of flies using *CASTLE*

Flies are widely used model organisms in behavioral neuroscience due to their well-defined behavioral repertoire, genetic tractability, and suitability for high-throughput screening[8,45,46]. Conventional behavioral studies in flies have relied heavily on manual annotation or supervised machine learning approaches, which require substantial training and user intervention[46]. Pose estimation methods like *DLC*, *LEAP,* and *SLEAP* have been developed to track fly movements precisely but require high-resolution video and extensive manual annotation for key-point labeling, making these methods resource-intensive and time-consuming[12]. To address these limitations, we extended the applicability of the *CASTLE* pipeline to automatically analyze and classify the complex behaviors of flies.

Using *CASTLE*, we analyzed behavior of flies in open-field test by sequentially performing background subtraction, segmentation, tracking, and orientation neutralization **(Fig. 7a)**. Short 10-frame snippets of the flies' focused latent features were embedded into a low-dimensional feature space via *UMAP* for unsupervised class discovery. A density-based clustering in this *UMAP* space yielded distinct behavioral clusters with minimal user input – no manual labeling or predefined behaviors were required. By eliminating a priori definitions of behaviors, *CASTLE*'s unsupervised approach mitigates human bias in behavioral identification. Notably, whereas earlier unsupervised frameworks mapped hundreds of micro-behavioral "syllables" in flies[8], our single-stage *UMAP* embedding

strategy distilled the repertoire into a concise set of interpretable classes. In total, seven predominant behavioral classes emerged from the *CASTLE* analysis (**Fig. 7b**). Each of these classes corresponded to a distinct cluster in the *UMAP* behavior-space **(Fig. 7c)** and was verified by manual inspection of video segments.

The clusters were further characterized by their quantitative feature profiles, including centroid position, translational speed, ROI area, angular velocity, and latent pose features. Characteristic kinematics were evident for several behaviors: for example, head grooming and wing grooming bouts showed pronounced changes in ROI area (due to limb or wing extension) and high angular velocity (calculated from the longest axis, which is significantly affected by wing movements). In contrast, front leg grooming lacked a unique signature in simple kinematic features and was distinguishable only in the high-dimensional visual latent space – reflecting the subtle, localized motion of the forelegs that *CASTLE*'s learned features could detect. Locomotor behaviors (walking and sideways walking) were associated with sustained movement and higher speed, whereas grooming and wing-extension behaviors occurred during brief pauses with little translational movement. We visualized the spatiotemporal distribution of these behaviors to confirm *CASTLE*'s classifications. The fly's trajectory was color-coded by behavior classes (**Fig. 7d**), revealing that locomotion classes (walking modes) covered large areas of the arena, while grooming actions and wing extensions appeared as stationary or confined events (often occurring when the fly paused, frequently near the arena edges). Representative snapshots of the animal during each behavior are shown in **Fig. 7e**, highlighting distinctive postures — for instance, the extension of a single wing during wing grooming, or the forelegs touching the head during head grooming. Finally, we generated cluster-wise density maps of the flies' behavioral classes (**Fig. 7f**). These maps indicate generalized and fly-specific differences in behavioral repertoires. In summary, *CASTLE* discovers meaningful structure in spontaneous fly behavior that aligns with known ethological motifs, without the extensive manual annotation required by supervised tracking tools like *SLEAP*[47] or the complexity of earlier unsupervised mapping techniques[8]. This illustrates the power of combining video-based deep learning features with *UMAP-DBSCAN* clustering to catalog animal behavior in an objective, data-driven manner.

Unsupervised behavioral classification of *C. elegans* using *CASTLE*

Nematodes like *C. elegans* are staples of behavioral genetics, yet most locomotor analyses rely on curated ethograms, specialized single-worm (*WormTracker 2.0*[48]) or multi-worm trackers (*Multi-Worm Tracker* (*MWT*)[49], *WormLab*, and *Tierpsy Tracker*[50]), or interactive classifiers that demand human supervision or require motorized stages and running in containerized environments. Against this backdrop, we apply *CASTLE* to freely-moving *C. elegans* and revealed that this unsupervised pipeline can robustly distinguish both spontaneous locomotor patterns and optogenetically-evoked responses. After background subtraction, segmentation, tracking and orientation neutralization (24 rotations per mask; **Fig.8a**), five-frame snippets of the worm's ROI were embedded via *UMAP* (**Fig.8b,c**). Density-based clustering revealed 5 discrete states: "Coiling" (tight, high-curvature curls), "Looping" (Ω-turns) (large body bends linked to reversals), "Local search" (area-restricted exploration with frequent reorientations), and extended search subdivided into "Forward (Global search)" and "Backward" movements (**Fig. 8c-e**). Direction was determined by comparing consecutive displacement vectors (**Fig. 8d**). Color-coded trajectory plots show that local search traces are clustered, global searches traverse the plate, reversals punctuate long runs, and coiling forms isolated dots (**Fig. 8f**). To test if optogenetic neural modulation affects locomotion behaviors, we stimulate an escape circuit with brief orange-light pulses (see Methods). Worms expressing a light-gated channel significantly shifted from sustained forward roaming into more looping and local search (N = 6, Looping: pre: $1.86 \pm 0.81\%$, post: $10.82 \pm 3.12\%$; Local search: pre: $13.4 \pm 4.20\%$, post: $39.48 \pm 5.39\%$; Global search, pre: $72.47 \pm 7.77\%$, post: $31.40 \pm 5.43\%$, all values expressed as mean ± SEM; Aligned Rank Transform (ART) ANOVA: stimulation × behavior interaction, $p < 0.001$; *post-hoc* Tukey-adjusted comparisons for Pre vs Post stimulation: looping $p < 0.005$, local search $p < 0.001$, global search $p < 0.001$, **Fig. 8g**). These shifts recapitulate the "pirouette" sequence documented in classical foraging studies and align with the forward–reverse–turn hierarchy mapped by neural circuit analyses[51-53]. Finally, skeleton-based body curvature patterns confirm that *CASTLE*'s unsupervised class labels correspond to biomechanically distinct locomotor modes (**Fig. 8h**).

Notably, all six worms expressed these behaviors with pronounced individual differences (**Fig. S6a**). Most worms spent most of their time roaming (global search forward) or

performing local searches in control condition, while looping and coiling were observable

after optogenetic stimulation. Some worms never coiled in the 20-min recording (**Fig.**

S6b-e); one produced multiple coils, especially immediate after optogenetically evoked

escape responses. Despite this variability, the underlying repertoire was consistent

across individuals. *CASTLE* unsupervised classifier provides a label-free alternative to

specialized single worm trackers. It yields posture-aware classifications with the

interpretability of curated ethograms and delivers a unified framework for high-throughput

phenotyping across species.

Discussion

CASTLE combines zero-shot segmentation (*SAM*[35]), robust mask tracking (*DeAOT*[36]) and foundation-model vision (*DINOv2*[37]) to create posture-specific, orientation-neutral latent spaces that are hierarchically clustered into a multiscale ethogram. By removing the need for labor-intensive annotation and task-specific retraining—common bottlenecks for current methods—*CASTLE* enables rapid, label-free behavioral analysis while preserving shape, context, and motion information left out in skeletonized representations.

Supervised pose estimators, such as *DLC*[14] and *Lightning Pose*[15] have transformed laboratory workflows by leveraging *ImageNet* pretraining, yet both require substantial labeled data and fine-tuning for each new species, assay, or camera geometry, and ultimately reduce behavior to sparse keypoints. In our reach-and-grasp study, *CASTLE* reproduced *DLC*-derived trajectories comparable neural-decoding accuracy and substantially less jitter during quiescent periods—achieved without intensive behavior-specific label or network training. While *Lightning Pose*[15] introduces semi-supervised losses and ensembling, it still depends on an initial keypoint model and yields a reduced coordinate representation; *CASTLE* bypasses this stage entirely, producing dense, semantic descriptors that capture subtle paw rotations or digit spreads invisible in limited keypoint space.

Relation to existing behavioral-classification toolkits

SLEAP[47] and *AlphaTracker*[17] extend supervised pose estimation to multi-animal settings, but their strength—identity-aware tracking for multiple animals—comes with increased annotation burden and identity-swap risk. The present work validates *CASTLE* on single-animal datasets (flies and worms analyzed one per video). Because *CASTLE* is built on category-agnostic segmentation and per-ROI embeddings rather than a fixed skeleton, the architecture is intrinsically compatible with multi-animal scenes once distinct masks are available; benchmarking this extension against SLEAP[47]/*AlphaTracker*[17] is a clear next step. Label-free discovery tools such as *B-SOiD*[9] and *MoSeq*[54] pioneered unsupervised behavioral parsing from keypoint dynamics or depth silhouettes, but they inherit constraints from upstream skeletonization and typically produce a flat set of

micro-syllables. *CASTLE* achieves similarly unbiased discovery without a prerequisite keypoint model and uses a hierarchical *UMAP→DBSCAN* loop to reveal both micro- and macro-motifs in one workflow. By decoupling from keypoint dependencies, it demonstrates unique advantages in scenarios where keypoints are prone to occlusion (e.g., finger occlusions during reach-grasp behaviors) or difficult to define (*e.g., C. elegans*), ensuring truly data-driven behavioral classification. Methods that embrace holistic vision via task-specific training—*Selfee*[31] and *LabGym*[27]—require fresh GPU training or curated clips for every new domain. In contrast, *CASTLE* reuses a pre-trained VFM whose priors generalized from mice to flies to worms without any optimization, matching expert labels in mice (weighted F1 ≈ 0.90), and uncovering seven spontaneous fly behaviors and five worm locomotor modes—all without retraining or manual labels.

Limitations of *CASTLE*

CASTLE shares limitations typical of unsupervised, vision-based systems. First, despite zero-shot segmentation, users still seed masks and occasionally correct drift—usually a handful of frames per hour of video. Second, orientation neutralization improves clustering but increases inference time. Third, the latent space inherits biases of *DINOv2*; under-represented fine movements (e.g., whisker or wing micro-tremors) may be harder to resolve. Fourth, temporal context is incorporated by concatenating frame embeddings; behaviors that hinge on long-range sequence order may benefit from video-native foundation models. Finally, our current validation focuses on single-animal recordings; multi-animal tracking will require reliable multi-mask segmentation and identity maintenance.

Future directions for *CASTLE*

Several extensions are natural. (1) Video-native or multimodal VFMs could encode motion directly and support joint embeddings with audio or neural signals, tightening the link between latent clusters and underlying computations. (2) Language grounding— attaching concise natural-language descriptors[34] to clusters—could close the loop between automated discovery and human-readable ethograms. (3) Closed-loop control: integrating CASTLE's low-latency labels with experimental hardware would enable

state-contingent stimulation within tens of milliseconds. (4) Social behavior: extending

segmentation/tracking to multiple interacting animals will allow benchmarking against

SLEAP[47] and *AlphaTracker*[17] in identity-aware settings.

Conclusion

In summary, *CASTLE* occupies a distinctive middle-ground niche: as label-free and

discovery-oriented as *B-SOiD*[9] or *MoSeq*[54], yet as spatially precise as *DLC*[14], as video-

aware as VFMs, and potentially scalable to social settings once multi-mask tracking is

enabled. By exchanging bespoke training for foundation-model vision and layering a

multiscale clustering engine on top, *CASTLE* delivers a turnkey, versatile, cross-species

solution that recovers expert-level annotations, uncovers hidden motifs and scales from

limb dynamics to whole-body behavior. As foundation models advance, CASTLE should

remain an adaptable platform for high-throughput, objective behavioral phenotyping in

neuroscience and computational ethology.

Acknowledgments

The authors thank Dr. Kuo-Hua Huang, Dr. Yu Tsao, Dr. Jun Ding, and members of Wu laboratory for helpful discussions. This study was funded by grants from the Academia Sinica I-AI-A Grant AS-IAIA-114-L01 (Y.-W.W. and C.-L.H.); the Ministry of Science and Technology and National Science and Technology Council, Taiwan, NSTC 114-2321-B-001-005 (Y.-W.W.), NSTC 113-2321-B-001-012 (Y.-W.W.), NSTC 112-2321-B-001-007 (Y.-W.W.), MOST 111-2321-B-001-011 (Y.-W.W.), MOST 110-2321-B-001-012 (Y.-W.W.); Institute of Molecular Biology, Academia Sinica SPP (2024) and SPP (2025),.

Author contributions

Y.-S.L. and Y.-W.W. designed the analysis pipelines and the experiments. Y.-S.L. established the analysis pipeline and the GUI. Y.-S.L. performed the data analysis for behavioral classifications and neural decoding. Y.-S.L., H.-Y.Y, Y.-T.H, and B.-S.W.,. performed OFT of mice. Y.-S.L., Y.-W.W. and Y.-F.C performed reach-and-grasp test of mice. J.S. and S.L. performed OFT of flies. J.-B.Y. and C.-H.C. performed OFT of *C. elegans*. Y.-W.W. and Y.-S.L. made the figures and wrote the manuscript with contribution of all coauthors. Y.-W.W. conceived the study and supervised the research.

Declaration of interests

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Figures and legends

Figure 1. Overview of the *CASTLE* pipeline for deriving behavioral classes from video data.

a. *CASTLE* flowchart. **b**. Segmentation & Tracking: The process begins by extracting a selected
frame (*V(i)*) of the video with *SAM*, allowing researchers to define specific Regions-of-Interest
(ROIs). A video object segmentation model, *DeAOT*, then tracks these ROIs across subsequent
frames, providing detailed information on their position and area over time. **c**. Latent feature
Extraction: A visual foundation model, *DINOv2*, is employed to encode each video frame into
high-dimensional features, capturing comprehensive visual information for the entire image.
These features are then integrated with the ROI data from **b** to produce a focused visual latent
representation ($L_{ROI}(t)$), highlighting key aspects of the tracked objects. **d.** Combined Approach:
The focused visual latent features derived from ROIs are projected onto principal component
analysis (PCA) masks, generating dimension-reduced, ROI-specific latent signals for detailed
behavioral analysis. **e.** Latent Exploration: The focused latent representations are analyzed by
comparing similarities between pairs of frames using embedding and clustering techniques.
Similar frames are grouped into clusters, which are then classified into distinct behavioral classes.
Hierarchical clustering is subsequently applied to these classes along the timeline, resulting in
the identification of behavioral classes**.**

Figure 2. Implementation of the *CASTLE* pipeline within a graphical user interface (GUI) for behavior analysis.

a-c. Workflow overview in the GUI, showing the three main stages of the *CASTLE* pipeline: **a.** Segmentation & Tracking: Users select a reference frame and define regions-of-interest (ROIs) via interactive prompts. The GUI facilitates the definition of tracking time windows and subsequent refinement of ROI tracking across video frames. **b.** Latent Extraction: This stage integrates video data with tracked ROI information to generate ROI-specific visual latent features, capturing crucial visual aspects necessary for behavioral analysis. **c.** Latent Explorer: Users load the combined latent and video data, select suitable temporal bins, and perform dimensionality reduction (*UMAP*), optionally with hierarchical refinement. Behavioral classification is executed through clustering (*DBSCAN*), enabling temporal verification of classes and identification of behavioral classes. **d-f.** GUI Screenshots: **d.** Segmentation & Tracking GUI: Interface for defining, tracking, and refining ROIs. **e.** Latent Extraction GUI: Visualization of how video frames and ROI data combine to form latent representations. **f.** Latent Explorer GUI: Displays results of dimensionality reduction, cluster analyses, and timelines of behavioral classifications.

Figure 3. Comparative performance analysis between *CASTLE* and *DeepLabCut* (*DLC*) in tracking accuracy and neural decoding.

a. Visualization of left paw trajectories from resting state to food grasping. Trajectories generated by *CASTLE* (purple lines), defined by connecting centroids of segmented ROI regions, are compared with DLC-derived trajectories (green-blue lines) using wrist-labeled tracking. **b.** Three-dimensional representation of ROI centroid trajectories across 10 independent trials. Darker segments denote trajectories before reach onset, highlighting greater displacement and higher noise levels in DLC-derived trajectories compared to *CASTLE*. **c-d.** Quantitative comparison of movement jitter measured as standard deviation (STD) of paw speed during resting states. *CASTLE* shows significantly lower jitter than DLC across 44 trials, as confirmed by statistical analysis (Wilcoxon signed-rank test, $p < 0.001$). **e-g.** Neural decoding accuracy using simultaneously recorded neural spike data. A recurrent neural network (comprising two-layer GRUs and fully connected layers) trained with *CASTLE*-derived trajectories achieved comparable decoding performance for paw position (**f**) and lower mean squared error (MSE) loss during validation (**g**), indicating equivalent or superior performance relative to DLC-based keypoint tracking.

Figure 4. Extraction and hierarchical exploration of behavioral classes in a mouse reach-and-grasp task

a. Following the tracking of ROI trajectories, *CASTLE* employs *DINOv2* to extract focused visual latent representations from selected ROIs. These latent features represent semantic visual information within high-dimensional (768D per view) spaces, derived from both front and side views, totaling 1536 dimensions. Kinematic data including position, speed, and area are integrated alongside the visual latent features. Five clusters identified by *CASTLE* correspond directly to manually annotated behavioral phases during mouse reaching: "on perch," "lifting," "grabbing," "at mouth," and "on stage." **b.** Hierarchical clustering process in Latent Explorer, demonstrating iterative dimension reduction to simplify and visualize complex latent structures. In

the initial stages, global structures were identified by employing parameters focusing on broad
differences (high neighbor count and moderate dimensionality). Subsequent stages progressively
refined local structures by adjusting *UMAP* parameters, effectively isolating distinct behaviors.
The hierarchical strategy enabled identification of subtle behavioral distinctions not initially
anticipated by researchers. **c-d.** Reliability assessment of *CASTLE*-derived behavioral
classifications compared to expert annotations, yielding an average F1 score of 0.90. Confusion
matrix analysis indicated key discrepancies in classifications involving transitions among "Lift,"
"Grab," and "At mouth" behaviors. **e.** Neural activity recorded simultaneously was used to
evaluate the classification performance of *CASTLE* versus expert annotations. A recurrent neural
network (two-layer GRU with fully connected layers) was trained to predict behaviors from neural
data across 36 trials. Over 10 independent training runs, there were no significant performance
differences for the 'on perch", "on stage", and "lifting" classes. However, performance on the
"grabbing" and "at mouth" classes differed significantly, suggesting that the features defining
these classes may be captured differently by the two labeling methods (n = 10, Wilcoxon rank-
sum test $p_{\text{on perch}} = 0.880$, $p_{\text{on stage}} = 0.226$, $p_{\text{lifting}} = 0.0963$, $p_{\text{grabbing}} = 0.000157$, $p_{\text{at mouth}} =$
0.000157). **f-g.** CASTLE identified two distinct "Lift" behaviors overlooked by initial expert
annotations: a transitional lift between "grabbing" and "at mouth," and a lift post "at mouth."
Embedding visualizations illustrate how *CASTLE* clusters separate these subtle behaviors,
extending researchers' behavioral definitions beyond pre-established expectations, highlighting
CASTLE's utility in exploring and defining novel behavioral classes.

Figure 5. Behavioral classification using *CASTLE* in an OFT

a. Workflow illustrating the preprocessing steps for behavioral analysis using *CASTLE*. Initially, regions-of-interest (ROIs) were identified using Video Object Segmentation (VOS). ROIs were cropped and aligned to remove spatial and directional bias, after which focused visual latent features were extracted using DINOv2, excluding irrelevant positional and directional information. **b.** Representative kinematic (position, speed, area, angular velocity) and visual latent (four-dimensional subset) data traces derived from the mouse body and tail-base ROIs. Behavioral classes (grooming, supported rearing, unsupported rearing, walking, and immobile) were identified through latent exploration. **c.** Hierarchical latent exploration pipeline. An initial *UMAP* stage isolates grooming behavior. Subsequently, a two-layer *UMAP* strategy delineates supported and unsupported rearing. Walking and immobile states are further distinguished using a kinematic speed threshold (4 mm/s). **d.** Representative video frames illustrating classified behaviors. **e-f.** Behavioral trajectories and analyses of control, mild Parkinson's disease (PD), and severe PD mice. Walking speeds are visualized by color gradients, with darker colors indicating higher speeds. Severe PD mice exhibited significantly increased immobility.

Figure 6. Effective extraction of focused latent features with orientation effect neutralization

a. Analysis of orientation sensitivity within focused visual latent features derived from *DINOv2*. The analysis demonstrates rotation-induced variations in latent values across dimensions by rotating a single mouse locomotion frame through 360 degrees. Results highlight dimensions with high orientation sensitivity (dimension 701) and those with minimal orientation dependence (dimension 155). **b.** Visualization of angular variations in focused visual latent features through RGB representation of the first three principal components (PC1-3) across different orientations,

demonstrating the comprehensive influence of orientation effects across entire latent dimensions. **c-d.** Implementation of the baseline approach combining Focus and Alignment preprocessing to eliminate positional and orientation information. This method categorizes mouse behaviors into four distinct classes: grooming, supported rearing, unsupported rearing, and combined walking and immobile states. **e-f.** Latent exploration results from raw OFT video frames without preprocessing, demonstrating significant position-dependent clustering that obscures meaningful behavioral distinctions and limits effective behavioral classification. **g-h.** Latent exploration results following Focus preprocessing alone, which removes positional information but retains orientation dependencies. This approach shows improved clustering compared to raw data but still exhibits orientation-related artifacts that limit behavioral discrimination. **i-j.** Latent exploration results following Orientation Neutralization preprocessing, where averaged latent features from multiple rotated frames effectively eliminate orientation dependencies while preserving behavioral distinctions for accurate classification. **k.** Performance comparison through weighted F1 scores between the baseline Focus and Alignment approach versus the Focus and Orientation Neutralization method, demonstrating equivalent classification accuracy without requiring reliable body orientation alignment. **l.** Temporal tolerance analysis examining F1 score performance across varying time bin tolerance levels. The improved accuracy with increased temporal tolerance validates that misclassifications are primarily transition-related differences. **m.** Confusion matrix visualization under ±2 time bin (±330 milliseconds) tolerance conditions, illustrating classification performance and error patterns between the alignment-based reference standard and Orientation Neutralization predictions.

Figure 7. Application of *CASTLE* for unsupervised behavioral classification in flies

a. Workflow for analyzing fly behavior from open-field test. The data include videos from 3 flies (3 minutes each at 60 Hz). Steps include background removal, ROI segmentation and tracking, and orientation neutralization prior to feature extraction. **b-c.** Behavioral classes identified by *CASTLE*. A single-stage *UMAP* dimensionality reduction was applied to the focused visual latent features. Behaviors were clustered based on manual inspection and verification, using an optimal temporal binning (bin size = 10 frames, 6 Hz resolution) for analysis. **d.** Fly trajectories color-coded by their assigned behavioral clusters, demonstrating clear spatial segregation of different behaviors. **e.** Representative video frames and the standard deviation of pixel changes within a 15-frame interval highlighting diverse behaviors classified by *CASTLE*, such as grooming (front leg, back leg, head, and wing), walking, sideways movement, and wing extension. **f.** Density heatmaps showing the temporal density distribution of behaviors for three individual flies, revealing both common behavioral patterns and subject-specific differences in behavioral repertoires.

Figure 8. Application of *CASTLE* for unsupervised behavioral classification in *C. elegans*

a. Workflow for analyzing six 20-minute *C. elegans* open-field videos (7.5 fps). The pipeline includes ROI segmentation and tracking, background removal to eliminate locomotion trails, and orientation neutralization to remove directional bias prior to focused visual latent feature extraction. **b.** Integrated visualization displaying traditional kinematic information (xy coordinates, speed, ROI areas, Angular speed), focused visual latent features, and behavioral classes identified by *CASTLE*. The correlation between kinematic parameters and dynamics of focused visual latent representations are illustrated how focused visual latent features effectively capture behavioral distinctions that translate into discrete behavioral classifications. **c.** Latent exploration employing a three-stage hierarchical clustering approach. Stage 1: Initial *UMAP* dimensionality reduction (n_neighbors=30, n_components=2, bin size=5) successfully isolated the "coiling" behavioral cluster (red). Stage 2: Two-layer *UMAP* architecture (Layer 1: n_neighbors=300, min_dist=0, n_components=5; Layer 2: n_neighbors=100, min_dist=0, n_components=2) identified and separated the "looping" behavioral cluster (pink). Stage 3: Applying identical parameters to the remaining data distinguished the "local search" cluster. **d**. Since global search forward and

backward movements exhibit similar morphological characteristics preventing visual distinction, directional classification utilizes positional trajectory analysis incorporating historical location, immediate past position, and current position to determine movement directionality. Algorithm for computing directional dot products to distinguish forward from backward locomotion, with displacement threshold D set at 2.5 mm. **e.** Representative video frames illustrating diverse behaviors classified by *CASTLE*, including global search, local search, backward movement, coiling and looping behaviors. **f.** *C. elegans* trajectories color-coded by their assigned behavioral cluster, demonstrating clear spatial segregation and characteristic movement patterns for different behavioral categories. The inset shows a trajectory segment that includes backward movement. **g**. Quantitative comparison of behavioral state proportions before and after optogenetic stimulation (N=6, error bars indicate SEM). Statistical analysis was performed using Aligned Rank Transform (ART) ANOVA for repeated measures, revealing a significant stimulation × behavior interaction ($p < 0.001$). Post-hoc comparisons with Tukey adjustment demonstrated significant pre-post stimulation differences for looping ($p < 0.01$), local search ($p < 0.001$), and global search ($p < 0.001$) behaviors. **h.** Validation of *CASTLE*-identified behavioral classes through comparison with *C. elegans* body curvature dynamics. Curvature analysis confirms that *CASTLE* behavioral classifications correspond to distinct biomechanical signatures, providing independent verification of the *CASTLE* behavioral categorization through established postural analysis methods.

References

Krakauer, J. W., Ghazanfar, A. A., Gomez-Marin, A., MacIver, M. A. & Poeppel, D. Neuroscience needs behavior: correcting a reductionist bias. Neuron 93, 480–490 (2017).

Guo, J.-Z. et al. Cortex commands the performance of skilled movement. Elife 4, e10774 (2015).

Brown, A. E. & De Bivort, B. Ethology as a physical science. Nature Physics 14, 653–657 (2018).

Han, Y. et al. Multi-animal 3D social pose estimation, identification and behaviour embedding with a few-shot learning framework. Nature Machine Intelligence 6, 48–61 (2024).

Marks, M. et al. Deep-learning-based identification, tracking, pose estimation and behaviour classification of interacting primates and mice in complex environments. Nature machine intelligence 4, 331–340 (2022).

Berman, G. J., Bialek, W. & Shaevitz, J. W. Predictability and hierarchy in Drosophila behavior. Proceedings of the National Academy of Sciences 113, 11943–11948 (2016).

Mathis, M. W. & Mathis, A. Deep learning tools for the measurement of animal behavior in neuroscience. Current opinion in neurobiology 60, 1–11 (2020).

Berman, G. J., Choi, D. M., Bialek, W. & Shaevitz, J. W. Mapping the stereotyped behaviour of freely moving fruit flies. Journal of The Royal Society Interface 11, 20140672 (2014).

Hsu, A. I. & Yttri, E. A. B-SOiD, an open-source unsupervised algorithm for identification and fast prediction of behaviors. Nature communications 12, 5188 (2021).

Goodwin, N. L. et al. Simple Behavioral Analysis (SimBA) as a platform for explainable machine learning in behavioral neuroscience. Nature Neuroscience, 1–14 (2024).

Wiltschko, A. B. et al. Mapping sub-second structure in mouse behavior. Neuron 88, 1121–1135 (2015).

Pereira, T. D. et al. Fast animal pose estimation using deep neural networks. Nature methods 16, 117–125 (2019).

Todd, J. G., Kain, J. S. & de Bivort, B. L. Systematic exploration of unsupervised methods for mapping behavior. Physical biology 14, 015002 (2017).

Mathis, A. et al. DeepLabCut: markerless pose estimation of user-defined body parts with deep learning. Nature neuroscience 21, 1281–1289 (2018).

Biderman, D. et al. Lightning Pose: improved animal pose estimation via semi-supervised learning, Bayesian ensembling and cloud-native open-source tools. Nature Methods, 1–13 (2024).

Luxem, K. et al. Identifying behavioral structure from deep variational embeddings of animal motion. Communications Biology 5, 1267 (2022).

Chen, Z. et al. AlphaTracker: a multi-animal tracking and behavioral analysis tool. Frontiers in Behavioral Neuroscience 17, 1111908 (2023).

Weinreb, C. et al. Keypoint-MoSeq: parsing behavior by linking point tracking to pose dynamics. Nature Methods 21, 1329–1339 (2024).

Huang, K. et al. A hierarchical 3D-motion learning framework for animal spontaneous behavior mapping. Nature communications 12, 2784 (2021).

Segalin, C. et al. The Mouse Action Recognition System (MARS) software pipeline for automated analysis of social behaviors in mice. Elife 10, e63720 (2021).

Bohnslav, J. P. et al. DeepEthogram, a machine learning pipeline for supervised behavior classification from raw pixels. elife 10, e63377 (2021).

Graving, J. M. et al. DeepPoseKit, a software toolkit for fast and robust animal pose estimation using deep learning. Elife 8, e47994 (2019).

740 23 Günel, S. et al. DeepFly3D, a deep learning-based approach for 3D limb and appendage
741   tracking in tethered, adult Drosophila. Elife 8, e48571 (2019).
742 24 Lauer, J. et al. Multi-animal pose estimation, identification and tracking with DeepLabCut.
743   Nature Methods 19, 496–504 (2022).
744 25 Bates, K., Le, K. N. & Lu, H. Deep learning for robust and flexible tracking in behavioral
745   studies for C. elegans. PLOS Computational Biology 18, e1009942 (2022).
746 26 Sun, G. et al. DeepBhvTracking: a novel behavior tracking method for laboratory animals
747   based on deep learning. Frontiers in behavioral neuroscience 15, 750894 (2021).
748 27 Hu, Y. et al. LabGym: Quantification of user-defined animal behaviors using learning-
749   based holistic assessment. Cell Reports Methods 3 (2023).
750 28 Harris, C., Finn, K. R., Kieseler, M.-L., Maechler, M. R. & Tse, P. U. DeepAction: a
751   MATLAB toolbox for automated classification of animal behavior in video. Scientific
752   Reports 13, 2688 (2023).
753 29 Awais, M. et al. Foundational models defining a new era in vision: A survey and outlook.
754   arXiv 2023. arXiv preprint arXiv:2307.13721 (2023).
755 30 Wang, E. Y. et al. Foundation model of neural activity predicts response to new stimulus
756   types. Nature 640, 470–477 (2025).
757 31 Jia, Y. et al. Selfee, self-supervised features extraction of animal behaviors. Elife 11,
758   e76218 (2022).
759 32 Zheng, C. et al. in 2024 IEEE International Conference on Big Data (BigData). 1909–
760   1918 (IEEE).
761 33 Sun, J. J. et al. Video Foundation Models for Animal Behavior Analysis. bioRxiv,
762   2024.2007. 2030.605655 (2024).
763 34 Xu, T. et al. MouseGPT: A Large-scale Vision-Language Model for Mouse Behavior
764   Analysis. arXiv preprint arXiv:2503.10212 (2025).
765 35 Kirillov, A. et al. in Proceedings of the IEEE/CVF International Conference on Computer
766   Vision. 4015–4026.
767 36 Yang, Z. & Yang, Y. Decoupling features in hierarchical propagation for video object
768   segmentation. Advances in Neural Information Processing Systems 35, 36324–36336
769   (2022).
770 37 Oquab, M. et al. Dinov2: Learning robust visual features without supervision. arXiv preprint
771   arXiv:2304.07193 (2023).
772 38 McInnes, L., Healy, J. & Melville, J. Umap: Uniform manifold approximation and projection
773   for dimension reduction. arXiv preprint arXiv:1802.03426 (2018).
774 39 Ester, M., Kriegel, H.-P., Sander, J. & Xu, X. in kdd. 226–231.
775 40 Guo, J. Z. et al. Cortex commands the performance of skilled movement. Elife 4, e10774
776   (2015). https://doi.org/10.7554/eLife.10774
777 41 Chung, J., Gulcehre, C., Cho, K. & Bengio, Y. Empirical Evaluation of Gated Recurrent
778   Neural Networks on Sequence Modeling. arXiv:1412.3555 (2014).
779   <https://ui.adsabs.harvard.edu/abs/2014arXiv1412.3555C>.
780 42 Seibenhener, M. L. & Wooten, M. C. Use of the Open Field Maze to measure locomotor
781   and anxiety-like behavior in mice. J Vis Exp, e52434 (2015). https://doi.org/10.3791/52434
782 43 Walsh, R. N. & Cummins, R. A. The Open-Field Test: a critical review. Psychol Bull 83,
783   482–504 (1976).
784 44 Sanders, T. H. & Jaeger, D. Optogenetic stimulation of cortico-subthalamic projections is
785   sufficient to ameliorate bradykinesia in 6-ohda lesioned mice. Neurobiology of disease 95,
786   225–237 (2016).
787 45 Dankert, H., Wang, L., Hoopfer, E. D., Anderson, D. J. & Perona, P. Automated monitoring
788   and analysis of social behavior in Drosophila. Nature methods 6, 297–303 (2009).

46   Kabra, M., Robie, A. A., Rivera-Alba, M., Branson, S. & Branson, K. JAABA: interactive
machine learning for automatic annotation of animal behavior. Nature methods 10, 64–67
(2013).
47   Pereira, T. D. et al. SLEAP: A deep learning system for multi-animal pose tracking. Nature
methods 19, 486–495 (2022).
48   Vedantham, K. et al. Track-A-Worm 2.0: A Software Suite for Quantifying Properties of C.
elegans Locomotion, Bending, Sleep, and Action Potentials. bioRxiv (2024).
https://doi.org/10.1101/2024.09.12.612524
49   Swierczek, N. A., Giles, A. C., Rankin, C. H. & Kerr, R. A. High-throughput behavioral
analysis in C. elegans. Nat Methods 8, 592–598 (2011).
https://doi.org/10.1038/nmeth.1625
50   Javer, A. et al. An open-source platform for analyzing and sharing worm-behavior data.
Nat Methods 15, 645–646 (2018). https://doi.org/10.1038/s41592-018-0112-1
51   Kato, S. et al. Global brain dynamics embed the motor command sequence of
Caenorhabditis elegans. Cell 163, 656–669 (2015).
https://doi.org/10.1016/j.cell.2015.09.034
52   Flavell, S. W., Raizen, D. M. & You, Y. J. Behavioral States. Genetics 216, 315–332 (2020).
https://doi.org/10.1534/genetics.120.303539
53   Huo, J. et al. Hierarchical behavior control by a single class of interneurons. Proc Natl
Acad Sci U S A 121, e2410789121 (2024). https://doi.org/10.1073/pnas.2410789121
54   Markowitz, J. E. et al. The striatum organizes 3D behavior via moment-to-moment action
selection. Cell 174, 44–58. e17 (2018).
811