Adjudicating competing theories of semantic representation with 7T-fMRI and

multivariate decoding

Saskia L. Frisby[1], Christopher R. Cox[2], Ajay D. Halai[1], Matthew A. Lambon Ralph[1], & Timothy

T. Rogers[3]

[1] MRC Cognition and Brain Sciences Unit, University of Cambridge, Cambridge, UK

[2] Department of Psychology, Louisiana State University, Baton Rouge, USA

[3] Department of Psychology, University of Wisconsin–Madison, Madison, USA

Abstract: Theories of semantic representation in the brain are numerous and contradictory

and are supported by an equally contradictory literature of multivariate neuroimaging

studies. Equipped with two pioneering tools – (1) a 7T-fMRI acquisition sequence capable of

capturing signal in crucial ventral temporal regions, and (2) four innovative decoding

methods that are designed to probe specific hypotheses about the nature of the semantic

code – we resolve this confusion. Evidence best supports the hypothesis that the ventral

anterior temporal lobe represents complex, multidimensional semantic information via an

interdependent, dynamic code similar to that observed in neural networks. Similar

representations – highly variable across individuals – were discovered in posterior temporal

and occipitotemporal cortex. In summary, this work adjudicates competing theories of

semantic cognition, thereby reconciling the discrepancy in results between multivariate

imaging and other sources of evidence – neuropsychology, noninvasive brain stimulation,

intracranial electrophysiology, and neural network modelling.

Keywords: semantic representation, 7T-fMRI, decoding, multivariate pattern analysis

1. Introduction

Semantic cognition is our ability to store general knowledge and to use this knowledge to interpret the meaning of language, objects, and events. Influential theories of how the brain might encode semantic information are numerous and contradictory[1–9] and are supported by an equally contradictory literature of multivariate neuroimaging studies[10–18]. This confusion arises for at least two reasons – (1) magnetic field inhomogeneity[19–26] that compromises signal quality in crucial ventral temporal regions and (2) analytic assumptions, embedded in multivariate methods, that restrict the kinds of hypotheses that each method can test[27]. This study surmounted these obstacles by (1) utilising a novel 7 Tesla functional magnetic resonance imaging (7T-fMRI) acquisition protocol capable of recovering signal in regions prone to imaging artefacts[26] and (2) employing four innovative decoding methods[11,28–31] that are designed to directly adjudicate different hypotheses about the nature of the semantic code. Previous theoretical work described what semantic representations might possibly be like[27] – here, for the first time, we resolve those outstanding questions empirically.

Despite their many differences, multiple theories of semantic cognition agree that the ventral anterior temporal lobes (vATLs) are important (cf.[7,8]). This claim is supported by multiple sources of evidence – in semantic dementia, atrophy of the vATL causes multimodal semantic impairment but spares other cognitive abilities[32–35] and a similar, though milder and transient, effect is observed following transcranial magnetic stimulation (TMS) to the vATL[23,36–39]. However, theorists disagree on the vATL's precise role. Damasio and colleagues[3] propose that modality-specific semantic information (an object's visual appearance, name, associated motor action, etc.) is encoded in separate modality-specific regions; convergence zones – one for each concept – trigger and synchronise activity within these areas during representation. The convergence zones are organised, by category, into convergence regions, with a convergence region for unique entities (such as individuals) in the temporal pole and a convergence region for animals just behind[4]. By contrast, Binder and colleagues[2] propose that the vATL functions, not simply as a pointer towards modality-specific cortex, but as one of multiple semantic "hubs" that computes complex semantic representations from independent features (e.g. *has eyes*, *has gills*) represented elsewhere[1,2,40]. More similar concepts share more features, accounting for graded semantic

similarity (e.g. a robin and a wren are more similar to each other than to an ostrich). A third

theory, the hub-and-spoke model[6,9,41], is motivated by the finding that neuro-computational

models with a single hub can represent transmodal semantic structure (whereas other

architectures fail[9,42,43]) and proposes that the vATL is the brain's *only* semantic hub. Like the

deep layers of a computational model, activity within the vATL does not correspond to

interpretable features – rather, after initial dynamic and nonlinear change, activity patterns

adopt steady states that are gradedly more similar for more similar concepts.[44]

Notwithstanding its theoretical importance, neuroimaging studies of semantic tasks

rarely highlight the vATL. One possible reason is the proximity of the vATL to the air-filled

sinuses – this causes magnetic field inhomogeneity, and consequently signal dropout and

distortions. Univariate fMRI studies that use distortion correction, such as spin-echo or

multi-echo acquisition, do detect semantic effects in the vATL[19–26]. A second possible reason

concerns analysis. Multivariate methods – which analyse patterns of activity over multiple

neural units (voxels, sensors, or electrodes) to characterise what information those patterns

represent – each encapsulate hypotheses that constrain the kind of neural code that they

can detect and these assumptions can lead to drastically different results[27]. For example,

when decoding semantic information from voltages recorded from electrocorticography

(ECoG) surface grid electrodes, representational similarity analysis[45] revealed a simple

binary animacy (living/non-living) distinction in the ATL[46] whereas methods based on

regularised regression revealed a complex, multidimensional semantic structure[28].

Each contemporary theory of semantic cognition also implicates regions outside the

vATL. Several theories agree that modality-specific regions are important because they

encode modality-specific semantic information about a concept[2,3,6–8]. For example,

neuroimaging studies highlight the inferior parietal cortex when processing tools[47]; lesions

to inferior parietal regions can cause category-specific semantic impairments for tools[48]; and

similar but transient impairments can be achieved with TMS[39]. Additionally, neuroimaging

studies report activity in posterior medial temporal cortex when processing tools and in

posterior lateral temporal cortex when processing animals[7,49]. However, theorists interpret

this evidence differently – some assert that this indicates representation of interpretable

features belonging to animals and tools; others note that the same results emerge in

computational models with uninterpretable activations due to differential connectivity

patterns of posterior temporal subregions[50]. Theories that propose the existence of multiple

hubs assign a central role to the angular gyrus, which is highlighted by imaging studies of

semantic tasks[1,51] and which, when damaged, produces a pattern of impairment that

appears to be mostly semantic[52] (cf.[53,54]). Finally, some theories even propose that semantic

information is radically dispersed across most or all of the cortex[5,14,15]. Each of these

opposing theories is supported to some extent by multivariate neuroimaging studies[10,12−

15,28,44]. Although regions outside the ventral anterior temporal and orbitofrontal cortices are

not affected by magnetic field inhomogeneity, methodological choices (which incorporate

theoretical assumptions) may contribute to this variability.

In summary, contemporary theories of semantic cognition make contradictory

claims. These claims concern not only *where* semantic information is represented, but also

how it is represented – for example, Binder and colleauges[2] argue that semantic

representations are constructed through linear combination of interpretable features,

whereas the hub-and-spoke model[6,9,41] proposes that semantic features are uninterpretable

and interdependent. Most multivariate neuroimaging studies test the predictions of a single

theory; this work is distinctive because we directly tested the predictions of competing

theories against one another. Utilising a clear theoretical framework[27], we tested whether

semantic representations are:

1. *Category* representations (one discrete, independent unit per concept), *feature-*

based representations (multiple independently-interpretable features), or *vector-*

space representations (patterns across units that are not independently

interpretable)

2. *Homogeneous* (units all adopt the same activation state – i.e., all increase in activity

or all decrease – when representing the same concept) or *heterogeneous* (units

adopt different activation states for the same concept)

3. *Consistent* (units encode semantic information in the same way across individuals) or

inconsistent (units exhibit different semantic codes across individuals)

4. *Contiguous* (units are spatially adjacent) or *dispersed* (units are spatially distributed

across the cortex) – representations can be contiguous or dispersed within or across

individuals

We also assessed the compatibility of our results with the hub-and-spoke model's claim that

representations in the vATL are *dynamic*, meaning that the information carried by a

particular neural unit changes over time – for example, a unit may signify animacy with

increased activity at one timepoint and with decreased activity at the next[44].

We overcame two obstacles that have hindered previous attempts to characterise

semantic representations. First, to address magnetic field inhomogeneity affecting ventral

temporal regions, we employed a novel multi-echo, multiband acquisition sequence

optimised for recovering signal in the vATL without sacrificing signal quality elsewhere[26].

Second, we leverage the inseparability of multivariate analysis and theory to our advantage

– we employ multivariate methods that make opposing theoretical assumptions and then

contrast the results obtained with each method. First, we decoded animacy using binary

logistic regression classifiers. These were used in combination with LASSO (L1)

regularisation[55], which assumes that the neural code is sparse (only a few of the features

under consideration encode the target structure), and with sparse-overlapping-sets LASSO

(SOSLASSO) regularisation[11,30,31], which additionally assumes that important features are

loosely spatially clustered within and across participants. Second, we used Representational

Similarity Learning (RSL)[28,29] to decode graded, multidimensional semantic similarity

structure. In RSL, a similarity structure is modelled (for example, using feature norms[27,56]),

then decomposed into multiple independent dimensions. Linear regression models then

learn to predict the coordinates of each stimulus on each dimension; significant correlations

between true and predicted coordinates indicate that the modelled similarity structure is a

good representation of the brain's. With RSL we used LASSO regularisation and group-

ordered-weighted LASSO (grOWL) regularisation[28,29], which assumes that the neural code is

sparse, that important features are correlated in their activity, and that features are likely to

encode multiple target dimensions at once (an interdependent, vector-space

representation).

We applied regularised logistic regression and RSL within a vATL region of interest

(ROI) and at the whole-brain level with the aim of adjudicating contemporary theories about

the nature of semantic representation.

2. Results

2.1. Characterising semantic representations in the ventral anterior temporal lobe

(vATL)

27 healthy participants completed the study successfully. None were excluded because of

excessive head motion, as defined by two metrics – framewise displacement[57] and DVARS

(which indexes the rate of change of BOLD signal across the entire brain between each pair

of successive frames of data)[58]. The participants named 100 line drawings of animals and

inanimate objects that were used previously for decoding [28,44] and that were matched for

age of acquisition, concreteness, word frequency and familiarity. The participants named

the stimuli with high accuracy (mean = 96.85%, standard deviation 2.71%). Three

participants had at least one run with accuracy less than two standard deviations below the

group mean. However, since none of these participants had accuracy less than 88% on any

run, we decided to include them.

Multiple theories propose that the vATL plays an important role in semantic

cognition[2,3,6,9,41], although its precise role is debated – a convergence region[3] or a hub,

combining independent[2,7,8] or interdependent features[6,9,41]. Therefore, we aimed first to

decode semantic information from the vATL and next to characterise the nature of semantic

representations there. We constructed bilateral ventral temporal ROIs based on ECoG

electrode coverage in a previous decoding study[59]. We also created "half-ROIs" by bisecting

the ROIs between their anteriormost and posteriormost points. This was primarily to

facilitate tests for dynamic coding, which was previously observed more distinctly in

anterior than posterior temporal regions in ECoG data[44], but for completeness we ran all

decoding analyses on all ROIs and half-ROIs. The ROIs were backprojected into each

participant's native space and were masked with a participant-specific grey matter mask.

All models were trained on contrast beta values (one per stimulus, averaged over

repeated presentations of the same stimulus) within each ROI and were assessed using ten-

fold cross-validation.

2.1.1.　Is semantic structure present in the vATL?

2.1.1.1.　Animacy

First, we attempted to decode animacy from the vATL using logistic regression. Figure 1A

shows the results. All classifiers trained on all ROIs performed better than chance.

Classification accuracy was very high (hold-out accuracy $\cong$ 0.95) for decoders trained on the

whole ROI or on the posterior half. This result confirmed that animacy was represented

within our ROI.

196   2.1.1.2.   Multidimensional semantic structure

Second, we attempted to decode multidimensional semantic structure from the vATL using

RSL. We modelled a target semantic similarity structure using feature norms[56] and used

singular value decomposition to decompose the structure into three dimensions that

explained 89.5% of the variance. Figure 2 shows the coordinates of all 100 stimuli on each

dimension. We then trained RSL models to predict the coordinates of each stimulus on all

dimensions.

Figure 1B shows the mean hold-out correlation between predicted and true

coordinates on each target semantic dimension. All models showed very good decoding of

dimension 1 of the target semantic space in all ROIs. In the right hemisphere, all models

produced significant correlations on at least one other dimension that, though small, were

statistically significant as assessed via permutation testing (see Methods; dimension 3 for

LASSO, and both dimension 2 and dimension 3 for grOWL). In the left hemisphere,

dimensions 2 and 3 were not reliably decoded in any ROI. These results confirmed the

presence of multidimensional semantic structure in the right ROI.

213   2.1.1.3.   Graded semantic structure

As shown in Figure 2, animate stimuli usually take low values on dimension 1 and inanimate

stimuli usually take high values. Therefore, a model that predicted the same low value for all

animate stimuli and the same high value for all inanimate stimuli could generate predicted

coordinates that correlate reliably with the target coordinates, yet the model would not be

detecting graded similarity structure. However, significant correlations *within* animate and

inanimate domains (i.e. when the model is evaluated only on the animate or only on the

inanimate stimuli) arise only if semantic structure is truly graded.[28]

Figure 3 shows correlations calculated for animate and inanimate stimuli separately.

For animate stimuli, results depended on the regularisation penalty - whereas models with

LASSO exhibited reliable decoding of only one dimension, models with grOWL discovered

within-domain structure for dimensions 1 and 2. For inanimate stimuli, although correlation

coefficients were generally smaller, multiple dimensions were decoded. Whereas these

patterns were somewhat variable for models regularised with LASSO, models with grOWL

systematically showed significant decoding of dimensions 1 and 3 in both hemispheres.

These results confirmed that graded semantic structure was represented within our ROI.

When the two domains were considered separately, multidimensional semantic

structure was observed in the left temporal lobe for both, despite the fact that correlations

on only one dimension were observed there when all stimuli were considered together

(Figure 1). Note that dimension 2 distinguishes the animate stimuli, but not the inanimate

stimuli, and the reverse is true for dimension 3 (Figure 2); significant correlations within-

domain usually emerged on dimension 2 for animate stimuli and on dimension 3 for

inanimate stimuli.

2.1.2.　　　　What are semantic representations in the vATL like?

2.1.2.1.　　Categories, features, or vector-spaces?

Damasio and colleagues[3] propose that the vATL contains category-specific convergence

regions for animals and unique entities. This theory would predict successful decoding of

animacy from our ROI – it would be active for animate stimuli and not for inanimate stimuli.

However, because convergence zones simply point to representations elsewhere – they do

not themselves express semantic information – the vATL would not be predicted to express

multiple semantic dimensions. Figures 1 and 3 show that our results are at odds with this

prediction.

Of the theories that do predict multidimensional information representation in the

vATL, some propose that its role is to combine independently-interpretable features[2] while

others propose that it encodes a vector-space with interdependent, uninterpretable

dimensions[6,9,41]. These possibilities can be adjudicated by comparing RSL results with

different regularisation penalties. grOWL assumes that features are likely to encode multiple

target dimensions at once whereas LASSO does not make that assumption. Therefore,

better performance with grOWL than LASSO supports the notion of interdependent, vector-space representation.

Figure 1B shows that RSL models with grOWL regularisation produced significant correlations on all three dimensions, whereas models with LASSO regularisation produced significant correlations on only two. Figure 3 shows that, for animate stimuli, models with LASSO exhibited reliable decoding of only one dimension; models with grOWL could decode dimensions 1 and 2. Within the inanimate domain, models with grOWL systematically showed significant decoding of dimensions 1 and 3 whereas LASSO exhibited less consistent results. Although grOWL produced larger correlations than LASSO (permutation $p < 0.05$) in only a few cases, the reverse was never true. These results suggest that the semantic code within the vATL is an uninterpretable, vector-space code.

2.1.2.2.　Contiguous or dispersed?

SOSLASSO assumes that features are loosely spatially clustered within and across participants, but LASSO does not make that assumption. Figure 1A shows that, in all ROIs apart from the right anterior half-ROI, SOSLASSO produced significantly higher classification accuracy than LASSO (permutation $p < 0.05$), suggesting that semantic representations within the vATL are loosely contiguous within and across individuals.

2.1.2.3.　Static or dynamic?

The hub-and-spoke model[6,9,41] claims that activity patterns within the vATL undergo dynamic and nonlinear change during stimulus processing – for example, a voxel may signify animacy with increased activity at one timepoint and with decreased activity at the next. A previous ECoG study, focused on decoding animacy, observed these patterns more distinctly in very anterior than in more posterior temporal regions[44]. The temporal resolution of fMRI is far lower than that of ECoG and the resulting spatial blurring may therefore obscure a temporally intricate semantic code. We would therefore expect poorer decoding performance in the anterior than the posterior half of the ROI. Figure 2A shows that classification accuracy in the anterior half-ROI was significantly worse than accuracy in the

posterior half-ROI (permutation p < 0.05). This fMRI result does not *establish* that the

semantic code is dynamic, but the results are *compatible* with this claim.

Similarly, Figure 1B shows worse decoding in the anterior half-ROI than the posterior

half (r ≅ 0.4 vs. r ≅ 0.8). However, dynamic representation of multidimensional semantics

has not yet been demonstrated with time-resolved imaging methods. We therefore chose

not to formally test the differences between half-ROIs or to interpret differences as

evidence for dynamic coding of multidimensional semantic structure.

Figure 1: Decoding in regions of interest. Surface plots (right) indicate which bar
corresponds to which ROI or half-ROI. (A) Mean and 95% confidence interval of the hold-out
accuracy for regularised logistic regression classifiers trained on contrast beta values to
discriminate animate from inanimate stimuli. Classifiers are trained using LASSO
regularisation on the left ROI and half-ROIs (upper left, shades of blue), using LASSO
regularisation on the right ROI and half-ROIs (upper right, shades of green), using SOSLASSO

regularisation on the left ROI and half-ROIs (lower left, shades of pink), or using SOSLASSO
regularisation on the right ROI and half-ROIs (lower right, shades of purple). Stars (*)
indicate a significant difference between classifier accuracy and chance (as determined by
permutation test, probabilities adjusted to control the false-discovery rate at α = 0.05).
Daggers (†) indicate a significant difference between classifier accuracy using that
regularisation penalty and accuracy in the same ROI using the other regularisation penalty
(probabilities adjusted to control the false-discovery rate at α = 0.05). (B) Mean and 95%
confidence interval of the hold-out correlation for RSL models trained on contrast beta
values to predict the coordinates of held-out stimuli on three target semantic dimensions
(dimension 1, D1; dimension 2, D2; and dimension 3, D3). Models are trained using LASSO
regularisation on the left ROI and half-ROIs (upper left, shades of blue), using LASSO
regularisation on the right ROI and half-ROIs (upper right, shades of green), using grOWL
regularisation on the left ROI and half-ROIs (lower left, shades of red), or using grOWL
regularisation on the right ROI and half-ROIs (lower right, shades of yellow). Stars (*)
indicate a significant correlation between predicted and target coordinates (as determined
by permutation test, probabilities adjusted to control the false-discovery rate at α = 0.05).
Daggers (†) indicate a significant difference between correlation on that dimension using
that regularisation penalty and correlation on the same dimension in the same ROI using the
other regularisation penalty (probabilities adjusted to control the false-discovery rate at α =
0.05).
321

322
323 Figure 2: Coordinates of all stimuli on each target semantic dimension. Colours indicate
324 category membership – land mammals (red), birds (orange), invertebrates (brown), other
325 animals (magenta), instruments (green), clothes (light blue), vehicles (dark blue), and other
326 inanimate objects (grey). Reprinted with permission from Cox and colleagues[28].
327
328

Figure 3: Hold-out correlations within-domain in regions of interest. Mean and 95% confidence interval of the hold-out correlation for RSL models trained on contrast beta values to predict the coordinates of held-out stimuli on three target semantic dimensions (dimension 1, D1; dimension 2, D2; and dimension 3, D3). Surface plots (right) indicate which bar corresponds to which ROI or half-ROI. Models are trained using LASSO regularisation on the left ROI and half-ROIs (upper left, shades of blue), using LASSO

regularisation on the right ROI and half-ROIs (upper right, shades of green), using grOWL
regularisation on the left ROI and half-ROIs (upper left, shades of red), or using grOWL
regularisation on the right ROI and half-ROIs (upper right, shades of yellow). Stars (*)
indicate a significant correlation between predicted and target coordinates (as determined
by permutation test, probabilities adjusted to control the false-discovery rate at α = 0.05).
Daggers (†) indicate a significant difference between correlation on that dimension using
that regularisation penalty and correlation on the same dimension in the same ROI using the
other regularisation penalty (probabilities adjusted to control the false-discovery rate at α =
0.05). (A) Hold-out correlations for animate stimuli only; (B) Hold-out correlations for
inanimate stimuli only.

2.2. Characterising semantic representations at the whole-brain level

All contemporary theories of sematic cognition implicate some regions outside the

vATL – modality-specific regions[2,3,6–8], posterior temporal cortex[7,49,50], the inferior parietal

lobe including the angular gyrus[1,2], or even the whole cortex[5,14,15]. Therefore, we next aimed

to investigate where else in the brain semantic information could be detected and to

characterise the semantic representations there. For these analyses, all models were trained

on contrast beta values (one per stimulus, averaged over repeated presentations of the

same stimulus) from the whole brain. Models were assessed using ten-fold cross-validation.

2.2.1. Is semantic structure present at the whole-brain level?

2.2.1.1. Animacy

Figure 4A shows the results from decoding animacy with logistic regression with LASSO or

SOSLASSO regularisation. As in the ROI analysis, classification accuracy was very high (hold-

out accuracy ≅ 0.95). This result confirmed the presence of information about animacy.

To assess which regions drove this result we visualised classifier coefficients on the

cortical surface (see Methods) and compared these to univariate results (animate >

inanimate and inanimate > animate; Figure 5A). Both univariate and multivariate analyses

highlighted posterior temporal and occipitotemporal regions – the univariate map included

some parietal regions that were absent from the multivariate maps and the multivariate

maps encompassed the ventral posterior temporal lobe more comprehensively than the

univariate map did.

2.2.1.2. Graded, multidimensional semantic structure

As shown in Figure 4B, decoding of dimension 1 was very successful (r ≅ 0.8). However, evidence for *multidimensional* structure depended on the regularisation penalty - models with grOWL produced significant correlations on dimensions 2 and 3 whereas models with LASSO did not. The results from RSL with grOWL provided evidence for multidimensional semantic structure at the whole-brain level.

Figure 6 shows the hold-out correlations calculated for animate and inanimate stimuli separately. Although only RSL with grOWL revealed multidimensional structure when all stimuli were considered together, both RSL with LASSO and RSL with grOWL produced significant correlations on two dimensions within-domain. For animate stimuli, these were dimensions 1 and 2 (which separates out the animate stimuli) and, for inanimate stimuli, the dimensions were dimension 1 and 3 (which separates out the inanimate stimuli). These findings confirmed the presence of graded structure at the whole-brain level.

Figure 7 shows the coefficients from RSL models. As in the classification analyses, posterior temporal and occipitotemporal regions were selected. Other regions that have been proposed to represent semantic information, such as the angular gyrus[1,2], were absent from these maps. The vATL was also absent[6,9,41], despite the fact that our ROI analysis detected semantic structure there.

2.2.2. What are semantic representations outside the vATL like?

2.2.2.1. Categories, features, or vector-spaces?

Figure 4B shows that only RSL with grOWL was successful at decoding more than one dimension when all stimuli were considered together; Figure 6 shows that RSL with LASSO could successfully decode two dimensions within-domain, but was outperformed by RSL with grOWL when decoding dimension 2 for animate stimuli and dimension 3 for inanimate stimuli (permutation p < 0.05). Figure 7 shows that, when visualising coefficients on the cortical surface, models with grOWL yielded significant results for all three dimensions. However, for models with LASSO, coefficients for dimensions 2 and 3 did not survive

permutation thresholding. This clear advantage of grOWL over LASSO indicates that the representations in posterior temporal cortex are likely to be interdependent, vector-space representations[15].

2.2.2.2. Homogeneous or heterogeneous?

The coefficient maps for the classification analysis (Figures 6B and 6C) feature lateral occipitotemporal regions in which coefficients are consistently negative across participants (meaning that, in most participants, a positive beta value is associated with an increased probability that the stimulus is animate) and medial occipitotemporal regions in which coefficients are consistently positive. The same pattern is seen in Figure 7B in the coefficients for dimension 1 in the RSL analysis with grOWL (this correspondence would be expected because dimension 1 distinguishes animate from inanimate stimuli; Figure 2). This demonstrates that these representations are heterogeneous – some units increase in activity when representing a concept; others decrease.

2.2.2.3. Consistent or inconsistent?

The coefficient maps for the classification analysis (Figures 6B and 6C) and for dimension 1 in the RSL analysis with grOWL regularisation (Figure 7B) feature regions in which coefficients are inconsistent in direction across participants. In the coefficient maps for dimensions 2 and 3, the regions of inconsistent coefficient directions were even larger.

2.2.2.4. Contiguous or dispersed?

In contrast to the ROI analysis, there was no difference in classification accuracy between SOSLASSO and LASSO (Figure 4A) and the same regions were highlighted with both methods (Figures 6B and 6C). This does not constitute evidence for contiguity within and across participants, although note also that classification performance may have been at ceiling and that this may account for the similarity between methods.

Figure 4: Decoding results at the whole-brain level. (A) Mean and 95% confidence interval of the hold-out accuracy for regularised logistic regression classifiers trained on contrast beta values to discriminate animate from inanimate stimuli. Classifiers are trained using LASSO regularisation (top, teal) or using SOSLASSO regularisation (bottom, magenta). Stars (*) indicate a significant difference between classifier accuracy and chance (as determined by permutation test, probabilities adjusted to control the false-discovery rate at α = 0.05). (B) Mean and 95% confidence interval of the hold-out correlation for RSL models trained on contrast beta values to predict the coordinates of held-out stimuli on three target semantic dimensions (dimension 1, D1; dimension 2, D2; and dimension 3, D3). Models are trained using LASSO regularisation (top, teal) or using grOWL regularisation (bottom, orange). Stars (*) indicate a significant correlation between predicted and target coordinates (as determined by permutation test, probabilities adjusted to control the false-discovery rate at α = 0.05). Daggers (†) indicate a significant difference between correlation on that dimension using that regularisation penalty and correlation on the same dimension using the other regularisation penalty (probabilities adjusted to control the false-discovery rate at α = 0.05).

Figure 5: Coefficients for classification analyses. (A) Univariate effects (A > I, red; I > A, blue)
are shown projected to the cortical surface and are cluster-corrected at p < 0.05 based on
an uncorrected voxel threshold of p < 0.001. (B) Coefficients for logistic regression classifiers
trained with LASSO regularisation on contrast beta values to discriminate animate from
inanimate stimuli are shown projected to the cortical surface and thresholded via
permutation testing to control the false discovery rate at α = 0.05 (see Methods). Warm
colours indicate that coefficients are mostly negative across participants (since animals were
coded as 0 and inanimate objects as 1, a negative coefficient indicates that a positive beta
value is associated with increased probability that the stimulus is animate); cool colours
indicate that coefficients are mostly positive across participants (a positive beta value is
associated with increased probability that the stimulus is inanimate); green shades indicate
that the region was selected in multiple participants but that the sign of the coefficient was
not consistent across participants. (C) Coefficients for logistic regression classifiers trained
with SOSLASSO regularisation on contrast beta values to discriminate animate from
inanimate stimuli are shown projected to the cortical surface and thresholded via
permutation testing to control the false discovery rate at α = 0.05 (see Methods). The colour
scaling is the same as in (A).

Figure 6: Hold-out correlations within-domain at the whole-brain level. Mean and 95% confidence interval of the hold-out correlation for RSL models trained on contrast beta values to predict the coordinates of held-out stimuli on three target semantic dimensions (dimension 1, D1; dimension 2, D2; and dimension 3, D3). Models are trained using LASSO regularisation (top, teal) or using grOWL regularisation (bottom, orange). Stars (*) indicate a significant correlation between predicted and target coordinates (as determined by permutation test, probabilities adjusted to control the false-discovery rate at α = 0.05). Daggers (†) indicate a significant difference between correlation on that dimension using that regularisation penalty and correlation on the same dimension using the other regularisation penalty (probabilities adjusted to control the false-discovery rate at α = 0.05). (A) Hold-out correlations for animate stimuli only; (B) Hold-out correlations for inanimate stimuli only.

Figure 7: Coefficients for RSL analyses. (A) Coefficients for RSL models trained with LASSO regularisation on contrast beta values to predict the coordinates of held-out stimuli on three target semantic dimensions are shown projected to the cortical surface and thresholded via permutation testing to control the false discovery rate at α = 0.05 (see Methods). Warm colours indicate that coefficients are mostly negative across participants; cool colours indicate that coefficients are mostly positive across participants; green shades indicate that the region was selected in multiple participants but that the sign of the coefficient wasnot consistent across participants. (B) Coefficients for RSL models trained with grOWL regularisation on contrast beta values to predict the coordinates of held-out stimuli on three target semantic dimensions are shown projected to the cortical surface and thresholded via permutation testing to control the false discovery rate at α = 0.05 (see Methods). The colour scaling is the same as in (A).

3. Discussion

Equipped with a novel 7T-fMRI acquisition protocol capable of recording signal in ventral temporal regions[26] and four innovative decoding methods[11,28–31], this study detected, characterised, and thereby adjudicated theories about the brain's semantic representations. We revealed graded, multidimensional semantic structure in the vATL, represented by an interdependent, contiguous, dynamic[44] code. We also discovered interdependent, heterogeneous, inconsistent[27] representations in posterior temporal and occipitotemporal cortex.

Multiple theories of semantic cognition implicate the vATL, but those theories differ in the neural code that they propose to exist in the vATL. Damasio and colleagues[3] hold that the vATL contains convergence zones that simply coordinate representations elsewhere – the vATL does not itself express semantic information. Conversely, we could decode multiple semantic dimensions from vATL activity. Other theories argue that the vATL functions as a hub that assembles and encodes complex semantic representations. The finding that RSL with grOWL, which assumes that features are interdependent, outperformed LASSO indicates that the vATL represents semantic information as an uninterpretable vector-space code, aligning with predictions of the hub-and-spoke model[6,9,41] rather than theories positing independent representational elements[1,2,40]. Also in accordance with predictions of the hub-and-spoke model, poorer decoding performance was observed in the anterior than the posterior half of our vATL ROI, suggesting the existence of a dynamic code that is most clearly observed with time-resolved imaging methods.

Our ROI results converge with results from neuropsychology[32–35], TMS[23,36–39], intracranial electrophysiology[28,44,59–64], and computational modelling[9,42,43], yet diverge from other multivariate studies using fMRI, which rarely highlight the vATL[10–18]. Two factors are likely to account for this difference. The first is signal inhomogeneity caused by the proximity of the vATL to the air-filled sinuses. Employing a novel multi-echo, multiband 7T-fMRI acquisition sequence[26], in contrast to the standard acquisition used by others, we were able to decode both animacy and graded, multidimensional semantic similarity structure even from the most anterior region of the vATL. Collecting data with a standard sequence (to enable a direct comparison) was beyond the scope of this study; previous work has

directly tested the link between acquisition sequence and correlation-based decoding

accuracy[26] and others should extend this test to decoding methods that depend on machine

learning (including logistic regression and RSL). The second factor is choice of method. This

study illustrated clear differences between decoding methods – SOSLASSO produced higher

classification accuracy than LASSO and grOWL decoded multiple semantic dimensions more

reliably than LASSO. The regularisation penalties that we used make assumptions (sparsity

and/or anatomical clustering and/or interdependence) that are explicitly based on theories

about how neural systems represent information[11,28]. However, note that, in comparison to

common approaches such as encoding[5,13,14] and RSA[16–18], the assumptions they make are

few and gentle. Our results suggest that adopting mild, neurally-inspired assumptions may

produce better coherence between fMRI results and results from other methods. However,

as argued previously[27], the most appropriate method for future studies is the one that aligns

with those individual researchers' explicit hypotheses. In summary, aided by two technical

advances, we have been able to reconcile the discrepancy between multivariate imaging

and other work.

Our whole-brain analysis discovered graded, multidimensional semantic similarity

structure in posterior temporal and occipitotemporal cortex. These regions have been

implicated by multiple theories – some propose that they encode visual properties including

colour, form, and motion[7,8] that may be particularly relevant for representing tools[49]; others

even propose that they encode mental states[5]. Our results enable us to distinguish

competing theories in two ways. First, as in the ROI analysis, we can adjudicate theories

based on the *nature* of the code that they propose. Detecting codes of varying natures is an

advantage of our multivariate approach[27] – note that the regions of inconsistent code

direction (green in Figures 5B and 5C) were missing from the univariate analysis (Figure 5A).

The interdependent, heterogeneous, inconsistent representations that we discovered

match the *kind* of code predicted by the hub-and-spoke model[6,9,41] (see also[15]). Note,

however, that the hub-and-spoke model does not predict what informational content we

should expect in the spokes (a set of regions which may include the posterior temporal and

occipitotemporal cortex). Preliminary evidence from computational modelling suggests that

spoke regions do come to represent overall semantic similarity structure (rather than

similarity structure within a particular modality) during semantic tasks[42,50], but it may only

be the spoke that is processing the current sensory input that does so[65]. The results of this

study are consistent with these exploratory findings – we presented visual stimuli and found

similarity structure in visual association cortex.

A second method of distinguishing between theories is considering which regions

were *not* selected in our analysis. The angular gyrus, which has been proposed as an

additional semantic hub[1,2], was absent, which means that our results do not readily support

a multi-hub perspective. The differences between this study and previous work[1,66,67],

however, remain to be explored in detail. One possible explanation is that the angular gyrus

is not a semantic store, but instead buffers multimodal and/or temporally-extended

information, including semantic information, during cognition[54,68]. Alternatively or

additionally, the angular gyrus may contribute to semantic control, possibly by representing

a semantic space that is "warped" to emphasise task-relevant dimensions[69]. To test this,

future studies should employ paradigms that make greater control requirements than our

naming paradigm does.

The vATL was also absent from our whole-brain results, despite the fact that our ROI

analysis detected semantic structure there. This discrepancy may arise because the

permutation distribution used for statistical thresholding of these maps is nonuniform –

voxels in the vATL are selected far more frequently than voxels elsewhere (Supplementary

Figures S1 and S2). This methodological quandary remains unresolved, but preliminary

simulation results suggest that overselection occurs when the correlated noise structure

present in fMRI breaks down under conditions of magnetic inhomogeneity, increasing the

dimensionality of the data and, consequently, the probability that data will correlate with a

permuted target (Frisby, unpublished analyses). Future work should both probe this

problem further and evaluate alternative methods of statistical significance testing for

decoding.

5. Conclusion

Previous theoretical work described the kinds of semantic representations that might

possibly exist[27]. This study represents the first endeavour to adjudicate those possibilities

empirically. We revealed graded, multidimensional semantic structure in the vATL,

represented by an interdependent, contiguous, dynamic[44] code. We also discovered

interdependent, heterogeneous, inconsistent[27] representations in posterior temporal and

occipitotemporal cortex. These results align better with the hub-and-spoke model of

semantic cognition than with competing theories. Our comparative multivariate approach is

an effective method that has the potential to reveal how the brain represents, not only

semantic knowledge, but any kind of information.

6. Online methods

6.1. Participants

32 participants were recruited to the study. Of these, five were unable to complete the

study either for medical reasons (for example, an incidental finding) or because of technical

problems during data acquisition which meant that the scanner needed to be rebooted. This

left 27 participants (age range 19-50, mean age 27.96 years, 17 female, 10 male) who were

all native speakers of British English, were right-handed, had normal or corrected-to-normal

vision, and had no neurological or sensory disorders. All participants gave written informed

consent and the research was approved by a local National Health Service (NHS) ethics

committee.

6.2. Stimuli and task

Stimuli were the same 100 line drawings used in previous ECoG work[28,44,59] – 50 animals and

50 inanimate items including vehicles, clothes, musical instruments and a range of other

objects[70] (https://github.com/slfrisby/7TConvergent/tree/main/stimuli/). There were no

significant differences between the categories with respect to age of acquisition, visual

complexity, familiarity, word frequency, name agreement, and non-semantic visual

structure[44,71]. PsychoPy 2022.2.5[72] was used to display stimuli and to record speech. Stimuli

for both tasks were rear-projected onto a screen in the MRI scanner, and observers viewed

stimuli through a mirror mounted to the head coil directly above the eyes.

The study had a fast event-related design with 4 runs per participant, collected in a

single session. Each run began 16 s after the start of the MR sequence and consisted of 100

trials (each stimulus appeared once per run). Each trial consisted of a stimulus presented for

4 s followed by a fixation cross presented for 4 s. 4 sequences of animate and inanimate

stimuli were created and counterbalanced across participants. The order of trials was

optimised for the contrast between animate and inanimate stimuli using optseq2

(https://surfer.nmr.mgh.harvard.edu/fswiki/optseq2). For each run and each participant, a

random order of animate stimuli and a random order of inanimate stimuli were created; the

stimuli were then interspersed according to the sequence generated with optseq2.

Participants were instructed to name each picture out loud as quickly and accurately

as possible while keeping head motion to a minimum. To ensure that participants

understood the instructions, they practised the task before entering the scanner while the

experimenter provided feedback about their head motion. Practice continued until the

experimenter was satisfied that head motion was minimised.

Overt speech was recorded for each trial and responses were scored for accuracy

with the study's aim of decoding semantic similarity structure in mind. If the participant did

not respond within the 4 seconds during which the stimulus was on-screen, the trial was

marked as incorrect. If the participant responded incorrectly but named an object that the

rater judged to be visually and semantically similar to the stimulus and at a similar level of

specificity (e.g. "wasp" for bee), the trial was marked as correct; if the object that they

named was semantically dissimilar or was named at a less specific level (e.g. "insect" for

bee), the trial was marked as incorrect. It was important that neural responses did not

reflect a "blend" of the semantics of multiple stimuli so, if the participant gave two

synonyms (e.g. "gun, pistol") the trial was marked as correct; if they named two different

objects ("kettle, iron") the trial was marked as incorrect even if one of the names was

correct. Trials containing fillers such as "um" and "err" in addition to a correct response

were marked as correct because the participants were neurologically healthy and there was

no reason to believe that these utterances reflected anything other than normal speech

processes. The mean and standard deviation of the accuracy scores were calculated.

6.3. Image acquisition

All images were acquired on a whole-body 7T Siemens MAGNETOM Terra MRI scanner

(Siemens Healthcare, Erlangen, Germany) with an 8Tx32Rx head coil (Nova Medical, USA).

An MP2RAGE anatomical scan was acquired with the following parameters: 224 sagittal

slices (interleaved acquisition), FOV 240 x 225.12 x 240 mm, voxel size 0.75 x 0.75 x 0.75

mm, TR 4300 ms, inversion times 840 and 2370 ms, TE 1.99 ms, flip angles 5° and 6°,

GRAPPA acceleration factor 3. Next, manual B_0-shimming was performed over the volume

to be used for echo-planar imaging (EPI). The aim was to reduce the water linewidth,

defined as full width of the spectrum at half height, to below 40 Hz. However, for some

participants the adjustments proved time-consuming and so adjustment time was capped at

30 minutes from the start of scanning after which the best shim parameters were adopted.

The actual average water linewidth was 38.80 Hz (standard deviation = 5.93 Hz).

All four functional runs of EPI used the multi-echo multiband sequence optimised by

Frisby and colleagues[26] with the following parameters: 48 axial slices (interleaved

acquisition), FOV 210 x 210 x 210 mm to cover the whole brain in most participants (visual

inspection ensured that the vATL was included in the FOV for all participants and the FOV

was tilted up at the nose to avoid ghosting of the eyes into the vATL), TR = 1510 ms, 3

echoes, TE_1 = 11.80 ms, TE_2 = 27.05 ms, TE_3 = 42.30 ms, multiband factor 2, GRAPPA

acceleration factor 3, phase partial Fourier 7/8, voxel size 2.5 mm isotropic (no gap), flip

angle 63°, and A-P phase encoding direction. Immediately *before* each run, 5 additional

volumes were acquired with the phase encoding direction changed to P-A. These volumes

were to be used for distortion correction during preprocessing.

6.4. Data analysis

All analysis code is available at: https://github.com/slfrisby/7TConvergent/.

6.4.1.   Preprocessing

For ease of data sharing we converted all DICOMs to BIDS format[73] using *heudiconv*

(v1.1.1)[74].

Standard reproducible preprocessing pipelines designed for 3T-fMRI, such as

fMRIprep[75–77], perform poorly on 7T-fMRI EPI data; therefore, the analysis pipeline was split

into stages using different software packages. The MP2RAGE T1w (combined) image first

had its background noise removed using O'Brien regularisation[78] and was then submitted to

CAT12 for segmentation[79] (in SPM12; https://www.fil.ion.ucl.ac.uk/spm/). The bias-

corrected and global-intensity-corrected T1w (combined) image produced was provided to

as input to *fMRIPrep* 21.0.1. The T1w (combined) image was corrected for intensity non-

uniformity with *N4BiasFieldCorrection*[80] and skull-stripped with a Nipype implementation of

the *antsBrainExtraction.sh* workflow (ANTs). Brain tissue segmentation of cerebrospinal

fluid (CSF), white matter (WM), and grey matter (GM) was performed on the brain-extracted

T1w (combined) image using *fast* (FSL 6.0.5.1)[81]. Volume-based spatial normalisation to

standard space (MNI152NLin2009cAsym) was performed through nonlinear registration

with *antsRegistration.sh* (ANTs 2.3.3, https://github.com/ANTsX/ANTs)[82,83].

Functional preprocessing was performed using in-house code, composed of

functions from AFNI (v.18.3.03; https://afni.nimh.nih.gov/)[84,85], FSL (v.5.0.10;

https://fsl.fmrib.ox.ac.uk/fsl/fslwiki)[86–89], tedana (v.24.0.0;

https://tedana.readthedocs.io/en/stable/index.html)[90–93], and ANTS (v. 2.2.0;

https://github.com/ANTsX/ANTs)[82,83]. EPIs were slice-time corrected to the middle slice

using *3dTshift* (AFNI). Next, EPIs from the first echo were motion corrected with *3dvolreg*

and *3dAllineate* using the first volume of the first run acquired as a reference. The same

transforms were applied to the EPIs from the second and third echoes. EPIs were then skull-

stripped using *BET* (FSL)[88] to create a participant-specific brain mask. *tedana* was used to

combine data from all echoes optimally based on T2* weighting[94] and to denoise the data

using ICA. *tedana* conducts denoising by decomposing data using PCA and ICA, classifying

components according to whether the signal scales linearly with TE (as BOLD signal does),

and reconstructing the data using only BOLD-like components. The brain mask created with

BET was used as the mask for this stage.

Next, unwarping was conducted using *topup* and *applytopup* (FSL)[95]. Field

displacement maps were calculated using 10 volumes (5 with A-P phase encoding direction,

extracted from the start of each functional run, and 5 with P-A phase encoding direction,

collected separately before each run) and the resulting correction was applied to all images.

Finally, the mean EPI for each run was coregistered to the skull-stripped native

structural image using a rigid-body registration in *AntsRegistrationSyN.sh* (ANTS). This

produced transforms from native EPI space to native T1 space. For all decoding analyses,

images remained in native space and were not smoothed. However, the transforms from

native EPI to native T1 (for the first run) and the transforms from native T1 to standard

space (MNI152NLin2009cAsym), calculated with *antsApplyTransforms* (ANTS), were used to

calculate the MNI-space coordinates that each voxel *would* have *were* images to be

transformed into MNI space. (These coordinates were used for visualisation and were

provided to classifiers trained with SOSLASSO regularisation, which take anatomical

information as input.) The transform from native EPI to native T1 space was also used to transform the participant's grey-matter mask into native EPI space. For the univariate analysis, images were transformed into standard space (MNI152NLin2009cAsym) with *antsApplyTransforms* (ANTS) and smoothed with a 6 mm FWHM Gaussian filter in SPM12 (https://www.fil.ion.ucl.ac.uk/spm/).

6.4.2. 1st-level (within-participant) GLM

Data were processed using the general linear model (GLM) approach implemented in SPM12 in MATLAB r2023b. For decoding, each stimulus was modelled as an individual boxcar function, 1.5 seconds in length because the stimulus in our stimulus set with the longest mean naming time had a mean naming time of 1323 ms[70] (periods between stimuli were modelled implicitly). These boxcar functions were subsequently convolved with SPM's difference of gammas haemodynamic response function. The six motion parameters extracted during preprocessing were used as regressors of no interest. Data from all four runs were concatenated, so an additional constant was included for each run. The micro-time resolution was set as the number of slices (n = 48), the micro-time onset was set as the reference slice for slice-time correction (n = 24), and the high-pass filter cutoff was 128 seconds. Each participant's grey matter mask in native EPI space was used as a mask for the analysis. The parameter estimation method was restricted maximum likelihood estimation (ReML) and serial correlations were accounted for using an autoregressive AR(1) model during estimation. This produced one beta image per stimulus in native space. For univariate analysis, the same model was run on the normalised, smoothed data with identical parameters except that a grey matter mask in standard space (MNI152NLin2009cAsym) was used and that stimuli named incorrectly were modelled as additional regressors of no interest. The univariate contrasts of interest were greater activation for animate stimuli named correctly than inanimate stimuli named correctly (A > I) and greater activation for inanimate stimuli named correctly than animate stimuli named correctly (I > A). This produced contrast images in MNI space.

6.4.3. Univariate analysis – 2nd-level (across-participant) GLM

Group-level t-tests of each contrast of interest (A > I, I > A) were conducted in SPM12. The

group t-maps were assessed for significance by using a voxel-height threshold of p < 0.001

to define clusters and then a cluster-defining family-wise-error-corrected threshold of p <

0.05 for statistical inference. Group-level results were then projected to the pial surface

(fsaverage template[96,97]) using *volume-to-surface-mapping* with trilinear interpolation in

Connectome Workbench 1.5.0 and the thresholded maps were plotted on the pial surface

using *plot_surf_stat_map* in *nilearn* implemented in Python 3.9.

6.4.4.   Multivariate decoding

To prepare data for decoding, beta images from all 4 presentations of each stimulus

were averaged across runs. If a participant had named a stimulus incorrectly on one to three

occasions, the beta image(s) corresponding to the incorrect trial(s) were not included in the

averaging. If the participant named the stimulus incorrectly on all four trials, the values for

each voxel were interpolated with the median value for that voxel over all other stimuli.

We constructed our vATL ROI based on electrode coverage in a previous study[59] (all

electrode coordinates are available at https://github.com/slfrisby/7TConvergent/).

Electrode coordinates in the temporal lobe were converted to a single NIFTI volume at

native resolution (2.5 mm isotropic) in MNI space using SPM12 and smoothed at 10mm

FWHM. In order to exclude regions that lay outside the temporal lobe, a mask was created

by taking the Harvard-Oxford cortical and subcortical atlases, removing the temporal lobe

from the atlas, and adding the cerebellum from the AAL 2 atlas[98] (since the Harvard-Oxford

atlas does not include a cerebellum). Only voxels that lay outside this atlas mask were

included in the ROI. After masking the ROI was smoothed again at 4mm FWHM because, on

inspection, this created a smooth shape with space around the temporal lobes – since the

ROIs were to be backprojected into native space, it was important to ensure that individual

participants' temporal lobes would be fully encompassed. Since electrode coverage was far

more extensive in the left than the right hemisphere, a mirror-image of the left ROI was

used as the right ROI. To create half-ROIs to enable tests for dynamism, we bisected the

ROIs between their anteriormost and posteriormost points (y = -20). The final ROIs in

standard space (MNI152NLin2009cAsym) are shown projected to the surface in Figures 1

and 3 and are available at https://github.com/slfrisby/7TConvergent/tree/main/ROI/.

The ROIs were backprojected into each participant's native space using the

transforms from native EPI to native T1 and the transforms from native T1 to standard space

generated with *antsRegistration.sh*. For the ROI decoding analysis, only beta values from

voxels that overlapped with both the ROI and the participant's native-space grey matter

mask were provided as input to decoding models. (For the whole-brain analysis, only voxels

within the participant's native-space grey matter mask were provided as input).

We tested for semantic structure using two decoding methods.

6.4.4.1.   Regularised logistic regression

We used regularised logistic regression to decode animacy. Regularised logistic regression

classifiers avoid overfitting by finding a set of coefficients β (one per feature, in this case per

voxel) that minimise both prediction error and a regularisation penalty:

$$\min_{\beta}((1 - \lambda)f(\beta) + \lambda h(\beta))$$

where $f(\beta)$ is the prediction error, $h(\beta)$ is the regularisation penalty, and λ is a learnt

hyperparameter that controls how the optimisation should weigh the regularisation penalty

versus the prediction error.

One set of classifiers was trained using LASSO (L1) regularisation[55], for which the

regularisation penalty is:

$$h(\beta) = \sum_{j=1}^{m} |\beta_j|$$

The LASSO penalty increases as the sum of the absolute values of the coefficients increases

and is therefore at its lowest when most coefficients are zero and the voxels that receive

the few nonzero coefficients are uncorrelated in their activity. Classifiers with LASSO

therefore encapsulate the assumption that the neural code is sparse (only a few voxels

encode the target structure) and uncorrelated.

Classifiers with LASSO were fitted using *glmnet* in MATLAB r2023b[99], using $3 - 0.2$ as

the range of possible lambda values. Each classifier took, as input, beta values from multiple

voxels from a single participant.

A second set of classifiers was trained using SOSLASSO regularisation[11,30,31]. Before

model training, voxels are assigned to "sets" – ROI-like spheres defined in MNI space. In this

study, the sets were 9 mm in radius and overlapped by 9mm with adjacent spheres. All

decoding analyses were conducted in native space, but each voxel was assigned to sets

based on the location that it *would* have *were* the images to be transformed into MNI space

(see Preprocessing). The sets are defined in a common space, so voxels from multiple

participants are assigned to the same anatomical set.

Classifiers are then fit to beta values from multiple voxels from *all* participants. The

SOSLASSO regularisation penalty is calculated for each set individually and summed over all

sets S:

830
$$h(S, \beta) = \sum_{S} \left((1 - \alpha) \sum_{j=1}^{m} |\beta_j| + \alpha \sqrt{\sum_{j=1}^{m} \beta^2} \right)$$

where α is a learnt hyperparameter that scales the two components of the SOSLASSO

penalty – the LASSO penalty $\sum_{j=1}^{m} |\beta_j|$, which increases as the sum of the coefficients

increases, and the grouping penalty $\sqrt{\sum_{j=1}^{m} \beta^2}$, which also increases as the sum of the

coefficients increases but increases more steeply when those voxels are in different sets

than when they are in the same set. This means that classifiers with SOSLASSO assume that

the code is sparse, but also found in similar locations within and across participants.

Classifiers with SOSLASSO were fitted using the WISC MVPA toolbox in MATLAB

r2018b (https://github.com/crcox/WISC_MVPA/) with hyperband budget set to 25 (all other

parameters were set as defaults, including $3 - 0.2$ as the range of possible lambda values).

6.4.4.2.   Representational similarity learning

Next, we used RSL to decode graded, multidimensional similarity structure. We first

constructed a representational similarity matrix (RSM) S that expressed the semantic

similarity between each possible pair of stimuli (operationalised using feature verification

norms[56]. We then applied singular value decomposition to extract three components

accounting for 89.5% of the variance in the whole RSM (81.1%, 4.4%, and 4.0%,

respectively)[28]. Figure 2 shows the coordinates of all 100 stimuli on each dimension. Where

n is the number of stimuli and r is the number of dimensions, SVD yields three products:

1. An $n \times r$ matrix ($\boldsymbol{U}$) of components, also known as singular vectors.

2. The transpose of $\boldsymbol{U}$ ($\boldsymbol{U^T}$).

3. An $r \times r$ matrix ($\boldsymbol{D}$) of singular values.

To summarise:

856
$$S \cong UDU^T$$

857   We weighted the components $\boldsymbol{U}$ by the square root of the singular values $\sqrt{\boldsymbol{D}}$ to create an

858    $n \times r$ matrix $\boldsymbol{C}$ – three target dimensions for decoding.

859
$$C = U\sqrt{D}$$

860   Next, RSL models were trained to predict the coordinates of each stimulus on each

861   dimension. Each voxel receives three coefficients – one per dimension – and so the set of

862   coefficients to be learnt is an $m \times r$ matrix $\boldsymbol{\beta}$. Where $\boldsymbol{X}$ is the matrix of data (of size n

863   stimuli x m voxels) and α is a learnt hyperparameter, RSL aims to find the set of coefficients

864   that minimises:

866
$$\min_{\beta}((1 - \lambda)\|C - X\beta\|_F + \lambda H(\boldsymbol{\beta}))$$

One set of models used LASSO regularisation and were trained using *glmnet* in

MATLAB r2023b, using $6 - 0$ as the range of possible lambda values. Each model took, as

input, beta values from multiple voxels from a single participant.

A second set of models used grOWL regularisation. grOWL works by creating a

vector w of non-negative, non-increasing values (i.e. each successive value of w is smaller

than or equal to the previous value). w is of length m (the number of voxels) and a

correspondence is learnt between elements of w and rows of $\boldsymbol{\beta}$ such that the row of $\boldsymbol{\beta}$

containing the largest coefficients (defined by the Euclidean norm or 2-norm of those

coefficients) receives the largest value in w, the row containing the next largest coefficients

receives the next largest value, and so on. Note that, because successive elements of w can

be equal, rows of $\boldsymbol{\beta}$ containing very similar coefficients can receive the same value in w.

The total grOWL regularisation penalty is calculated by taking the Euclidean norm

(also known as the 2-norm) of each row of $\boldsymbol{\beta}$, multiplying that with its corresponding value

in w, and summing the results. Where $\boldsymbol{\beta}_{[i].}$ is the row of $\boldsymbol{\beta}$ with the i-th largest 2-norm and

w_i is the value in w corresponding to $\boldsymbol{\beta}_{[i].}$:

$$H(\beta) = \sum_{i=1}^{m} w_i \left\| \boldsymbol{\beta}_{[i]\cdot} \right\|_2$$

$\left\| \boldsymbol{\beta}_{[i]\cdot} \right\|_2$ increases as each coefficient increases. However, unlike LASSO which prefers voxels

to be uncorrelated in their activity, grOWL assigns similar values in w to correlated voxels,

meaning that those correlated voxels either all receive nonzero coefficients or all receive

coefficients of zero. Consequently, grOWL assumes that the neural code is sparse but

correlated – in other words, while LASSO assumes that only a few voxels will be important,

grOWL assumes that only a few *groups of correlated voxels* will be important. Note also that

$\left\| \boldsymbol{\beta}_{[i]\cdot} \right\|_2$ is smaller when coefficients in a row of $\boldsymbol{\beta}$ are similar in size than when one is large

and others are small or zero. grOWL therefore makes the *spanning assumption* – that

important voxels should predict multiple target dimensions at once, and therefore that the

target dimensions are represented interdependently.

893   grOWL models were trained using the WISC MVPA toolbox in MATLAB r2018a with

894 hyperband budget set to 25 (all other parameters were set as defaults, including 6 − 0 as the

895 range of possible lambda values). Each model took, as input, beta values from multiple

896 voxels from a single participant.

898    6.4.4.3.    Cross-validation and model assessment

Classifier or model accuracy was assessed via ten-fold nested cross-validation. In each outer

loop, ten out of 100 stimuli (five animate, five inanimate) were defined as the outer-loop

hold-out set. A second ten stimuli (five animate, five inanimate) were defined as the inner-

loop hold-out set. The remaining 80 stimuli were used as training data to search for the best

hyperparameter(s) - λ, plus α for SOSLASSO and w for grOWL. Hyperparameter

performance was assessed on the inner-loop hold-out set. The folds were then reassigned

so that ten stimuli previously used for training became the inner-loop hold-out set. Once all

combinations of inner-loop hold-out set and training data had been explored, the best-

performing hyperparameter value(s) were used to train a final model that was assessed on

the outer-loop hold-out set. The procedure was then repeated with the nine other possible

hold-out sets. In the first instance, stimuli were assigned randomly to the ten hold-out folds,

but this order was then fixed so that models fitted with every kind of regularisation were

assessed using the same fold configuration.

The mean classification accuracy (for regularised logistic regression classifiers) or

correlation between true and predicted coordinates (for RSL models) was calculated over all

hold-out folds. Statistical significance was assessed via permutation testing. This was done

for two reasons. First, since we used a fast event-related design, the haemodynamic

response overlapped between trials. This means that, if temporally adjacent stimuli were

divided between training and test sets, the stimulus in the training set may contain

information about the stimulus in the test set and so may produce classification hold-out

accuracies above 0.5 or hold-out correlations above 0. Second, cross-validated correlation

(as was calculated for RSL models) is known to produce predicted coordinates that

sometimes correlate *negatively* with the target coordinates in a hold-out set – the mean

correlation under the null hypothesis may be below zero[28,100]; therefore, the magnitude of

the real correlation can be understood only with reference to the permutation distribution.

In permutation testing, the stimulus labels were permuted before model training (as for

hold-out folds, the permutation orders were generated at random but then fixed so that the

permutations for each model were comparable). The procedure was repeated 100 times to

produce 100 simulated accuracy or correlation values for each participant. A group-level

empirical null distribution was simulated by randomly sampling one of the 100 values from

each participant and computing a group average 10,000 times[101]. One-tailed p-values were

calculated (where m is the number of values in the permutation distribution and b is the

number of values in the permutation distribution larger than the true value[28,102]):

$$p = \frac{b + 1}{m + 1}$$

To test whether one model or ROI produced a higher accuracy or correlation than another, a

group-level permutation distribution of differences was created using the differences

between the values in both permutation distributions and using the group-level simulation

procedure described above. A p-value was then calculated for the true difference.

Statistical significance for all tests was defined after adjusting p-values to control the

false discovery rate at α = 0.05[103].

Ten-fold nested cross-validation does not provide a clear picture of which voxels are

informative – each of the ten final models selects its own set of coefficients[11]. Therefore, to

visualise coefficients, one model was trained for each participant using an inner loop of ten

stimuli to identify the best hyperparameter(s) but no outer loop (i.e. all 90 stimuli that were

not in the current inner loop hold-out set were used for hyperparameter exploration;

therefore, all 100 stimuli were used for training). 100 permutation models were also trained

for each participant. Coefficients were converted to one NIFTI volume per participant at

native resolution (2.5 mm isotropic) in MNI space using SPM12. Coefficients both for models

trained on real data and for models trained on permuted data were projected to the pial

surface (fsaverage template[96,97]) using *-volume-to-surface-mapping* with trilinear

interpolation and smoothed on the surface at 6 mm FWHM using *–metric-smoothing* in

Connectome Workbench 1.5.0. Two metrics were calculated – (1) the proportion of

participants in which each vertex was selected and (2) the proportion of negative

coefficients that each vertex received (since animals were coded as 0 and inanimate objects

as 1, a negative coefficient indicates that a positive beta value is associated with increased

probability that the stimulus is animate). The map of the proportion of negative coefficients

was thresholded using the map of coefficient selection - vertices were included in the map

only if they were selected significantly more frequently in the real distribution than they

were in the permutation distribution, as assessed via binomial tests with p-values adjusted

to control the false discovery rate at $\alpha = 0.05$[103]. Finally, the thresholded map was plotted

on the pial surface using *plot_surf_stat_map* in *nilearn* implemented in Python 3.9.

Data and code availability: Data will be made publicly available upon peer review and

acceptance. Code is publicly available at: https://github.com/slfrisby/7TConvergent/.

Author contributions: Saskia L. Frisby – Conceptualisation, Methodology, Investigation,

Formal Analysis, Visualisation, Writing – Original Draft, Writing – Review and Editing,

Funding Acquisition; Christopher R. Cox – Conceptualisation, Methodology, Software,

Writing – Review and Editing; Ajay D. Halai – Conceptualisation, Writing – Review and

Editing, Supervision, Funding Acquisition; Matthew A. Lambon Ralph – Conceptualisation,

Writing – Review and Editing, Supervision, Funding Acquisition; Timothy T. Rogers –

Conceptualisation, Writing – Review and Editing, Supervision, Funding Acquisition.

Funding: This work was supported by an EPS study visit grant (G118497) to S.L.F., by an MRC

Career Development Award (MR/V031481/1) to A.D.H., by an MRC programme grant

(MR/R023883/1) and intramural funding (MC_UU_00005/18) to M.A.L.R., and by an NSF

grant (NCS-FO 219903 DRL) to T.T.R.

Competing interests: The authors declare no conflicts of interest.

Acknowledgements: We would like to thank the participants and the Wolfson Brain Imaging

Centre radiographers.

References

1. Binder, J. R., Desai, R. H., Graves, W. W. & Conant, L. L. Where is the semantic system? A critical review and meta-analysis of 120 functional neuroimaging studies. *Cereb. Cortex N. Y. N 1991* **19**, 2767–2796 (2009).
2. Binder, J. R. & Desai, R. H. The neurobiology of semantic memory. *Trends Cogn. Sci.* **15**, 527–536 (2011).
3. Damasio, A. R. The brain binds entities and events by multiregional activation from convergence zones. *Neural Comput.* **1**, 123–132 (1989).
4. Damasio, H., Tranel, D., Grabowski, T., Adolphs, R. & Damasio, A. Neural systems behind word and concept retrieval. *Cognition* **92**, 179–229 (2004).
5. Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E. & Gallant, J. L. Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature* **532**, 453–458 (2016).
6. Lambon Ralph, M. A., Jefferies, E., Patterson, K. & Rogers, T. T. The neural and computational bases of semantic cognition. *Nat. Rev. Neurosci.* **18**, 42–55 (2017).
7. Martin, A. The representation of object concepts in the brain. *Annu. Rev. Psychol.* **58**, 25–45 (2007).
8. Martin, A. GRAPES — Grounding representations in action, perception, and emotion systems: How object properties and categories are represented in the human brain. *Psychon. Bull. Rev.* **23**, 979–990 (2016).
9. Rogers, T. T. *et al.* Structure and deterioration of semantic memory: a neuropsychological and computational investigation. *Psychol. Rev.* **111**, 205–235 (2004).
10. Anderson, A. J. *et al.* Multiple Regions of a Cortical Network Commonly Encode the Meaning of Words in Multiple Grammatical Positions of Read Sentences. *Cereb. Cortex* **29**, 2396–2411 (2019).
11. Cox, C. R. & Rogers, T. T. Finding distributed needles in neural haystacks. *J. Neurosci.* **41**, 1019–1032 (2021).
12. Dehghani, M. *et al.* Decoding the neural representation of story meanings across languages. *Hum. Brain Mapp.* **38**, 6096–6106 (2017).
13. Fernandino, L. *et al.* Concept representation reflects multimodal abstraction: A framework for embodied semantics. *Cereb. Cortex* **26**, 2018–2034 (2016).

14. Popham, S. F. *et al.* Visual and linguistic semantic representations are aligned at the border of human visual cortex. *Nat. Neurosci.* **24**, 1628–1636 (2021).

15. Pereira, F. *et al.* Toward a universal decoder of linguistic meaning from brain activation. *Nat. Commun.* **9**, 1–13 (2018).

16. Devereux, B. J., Clarke, A. & Tyler, L. K. Integrated deep visual and semantic attractor neural networks predict fMRI pattern-information along the ventral object processing pathway. *Sci. Rep.* **8**, 10636 (2018).

17. Devereux, B. J., Clarke, A., Marouchos, A. & Tyler, L. K. Representational similarity analysis reveals commonalities and differences in the semantic processing of words and objects. *J. Neurosci.* **33**, 18906–18916 (2013).

18. Connolly, A. C. *et al.* The representation of biological classes in the human brain. *J. Neurosci.* **32**, 2608–2618 (2012).

19. Devlin, J. T. *et al.* Susceptibility-induced loss of signal: Comparing PET and fMRI on a semantic task. *NeuroImage* **11**, 589–600 (2000).

20. Halai, A. D., Welbourne, S. R., Embleton, K. & Parkes, L. M. A comparison of dual gradient-echo and spin-echo fMRI of the inferior temporal lobe. *Hum. Brain Mapp.* **35**, 4118–4128 (2014).

21. Halai, A. D., Parkes, L. M. & Welbourne, S. R. Dual-echo fMRI can detect activations in inferior temporal lobe during intelligible speech comprehension. *NeuroImage* **122**, 214–221 (2015).

22. Halai, A. D., Henson, R. N., Finoia, P. & Correia, M. M. Comparing the effect of multi gradient echo and multi band fMRI during a semantic task. 2024.03.20.585909 Preprint at https://doi.org/10.1101/2024.03.20.585909 (2024).

23. Binney, R. J., Embleton, K. V., Jefferies, E., Parker, G. J. M. & Lambon Ralph, M. A. The ventral and inferolateral aspects of the anterior temporal lobe are crucial in semantic memory: Evidence from a novel direct comparison of distortion-corrected fMRI, rTMS, and semantic dementia. *Cereb. Cortex* **20**, 2728–2738 (2010).

24. Embleton, K. V., Haroon, H. A., Morris, D. M., Lambon Ralph, M. A. L. & Parker, G. J. M. Distortion correction for diffusion-weighted MRI tractography and fMRI in the temporal lobes. *Hum. Brain Mapp.* **31**, 1570–1587 (2010).

25. Visser, M., Jefferies, E. & Lambon Ralph, M. A. Semantic processing in the anterior temporal lobes: a meta-analysis of the functional neuroimaging literature. *J. Cogn. Neurosci.* **22**, 1083–1094 (2010).

26. Frisby, S. L. *et al.* Optimising 7T-fMRI for imaging regions of magnetic susceptibility. 2025.03.17.643748 Preprint at https://doi.org/10.1101/2025.03.17.643748 (2025).

27. Frisby, S. L., Halai, A. D., Cox, C. R., Lambon Ralph, M. A. & Rogers, T. T. Decoding semantic representations in mind and brain. *Trends Cogn. Sci.* **27**, 258–281 (2023).

28. Cox, C. R. *et al.* Representational similarity learning reveals a graded multidimensional semantic space in the human anterior temporal cortex. *Imaging Neurosci.* **2**, 1–22 (2024).

29. Oswal, U., Cox, C. R., Lambon Ralph, M. A., Rogers, T. T. & Nowak, R. D. Representational Similarity Learning with Application to Brain Networks. in *Proceedings of The 33rd International Conference on Machine Learning* 1041–1049 (PMLR, 2016).

30. Rao, N., Nowak, R. D., Cox, C. & Rogers, T. Classification with the sparse group lasso. *IEEE Trans. Signal Process.* **64**, 448–463 (2016).

31. Rao, N., Cox, C., Nowak, R. D. & Rogers, T. T. Sparse overlapping sets lasso for multitask learning and its application to fMRI analysis. in *Advances in Neural Information Processing Systems* vol. 26 (2013).

32. Bozeat, S., Lambon Ralph, M. A., Patterson, K., Garrard, P. & Hodges, J. R. Non-verbal semantic impairment in semantic dementia. *Neuropsychologia* **38**, 1207–1215 (2000).

33. Hodges, J. R. & Patterson, K. Semantic dementia: a unique clinicopathological syndrome. *Lancet Neurol.* **6**, 1004–1014 (2007).

34. Snowden, J., Goulding, P. J. & Neary, D. Semantic dementia: A form of circumscribed cerebral atrophy. *Behav. Neurol.* **2**, 124043 (1989).

35. Warrington, E. K. The selective impairment of semantic memory. *Q. J. Exp. Psychol.* **27**, 635–657
(1975).
36. Lambon Ralph, M. A., Pobric, G. & Jefferies, E. Conceptual knowledge is underpinned by the
temporal pole bilaterally: Convergent evidence from rTMS. *Cereb. Cortex* **19**, 832–838 (2009).
37. Pobric, G., Jefferies, E. & Lambon Ralph, M. A. Anterior temporal lobes mediate semantic
representation: Mimicking semantic dementia by using rTMS in normal participants. *Proc. Natl.*
Acad. Sci. **104**, 20137–20141 (2007).
38. Pobric, G., Jefferies, E. & Lambon Ralph, M. A. Amodal semantic representations depend on
both anterior temporal lobes: Evidence from repetitive transcranial magnetic stimulation.
Neuropsychologia **48**, 1336–1342 (2010).
39. Pobric, G., Jefferies, E. & Lambon Ralph, M. A. Category-specific versus category-general
semantic impairment induced by transcranial magnetic stimulation. *Curr. Biol.* **20**, 964–968
(2010).
40. Binder, J. R. *et al.* Toward a brain-based componential semantic representation. *Cogn.*
Neuropsychol. **33**, 130–174 (2016).
41. Patterson, K., Nestor, P. J. & Rogers, T. T. Where do you know what you know? The
representation of semantic knowledge in the human brain. *Nat. Rev. Neurosci.* **8**, 976–987
(2007).
42. Jackson, R. L., Rogers, T. T. & Lambon Ralph, M. A. Reverse-engineering the cortical architecture
for controlled semantic cognition. *Nat. Hum. Behav.* **5**, 774–786 (2021).
43. Rogers, T. T. & McClelland, J. L. *Semantic Cognition: A Parallel Distributed Processing Approach*.
(MIT Press, Cambridge, Mass., 2004).
44. Rogers, T. T. *et al.* Evidence for a deep, distributed and dynamic code for animacy in human
ventral anterior temporal cortex. *eLife* **10**, e66276 (2021).
45. Kriegeskorte, N., Mur, M. & Bandettini, P. Representational similarity analysis – connecting the
branches of systems neuroscience. *Front. Syst. Neurosci.* **2**, (2008).
46. Chen, Y. *et al.* The 'when' and 'where' of semantic coding in the anterior temporal lobe:
Temporal representational similarity analysis of electrocorticogram data. *Cortex* **79**, 1–13
(2016).
47. Mahon, B. Z., Schwarzbach, J. & Caramazza, A. The representation of tools in left parietal cortex
is independent of visual experience. *Psychol. Sci.* **21**, 764–771 (2010).
48. Tranel, D., Damasio, H. & Damasio, A. R. A neural basis for the retrieval of conceptual
knowledge. *Neuropsychologia* **35**, 1319–1327 (1997).
49. Chao, L. L., Haxby, J. V. & Martin, A. Attribute-based neural substrates in temporal cortex for
perceiving and knowing about objects. *Nat. Neurosci.* **2**, 913–919 (1999).
50. Chen, L., Lambon Ralph, M. A. & Rogers, T. T. A unified model of human semantic knowledge
and its disorders. *Nat. Hum. Behav.* **1**, 0039 (2017).
51. Price, A. R., Bonner, M. F., Peelle, J. E. & Grossman, M. Converging evidence for the
neuroanatomic basis of combinatorial semantics in the angular gyrus. *J. Neurosci.* **35**, 3276–
3284 (2015).
52. Geschwind, N. Language and the brain. *Sci. Am.* **226**, 76–83 (1972).
53. Seghier, M. L., Fagan, E. & Price, C. J. Functional subdivisions in the left angular gyrus where the
semantic system meets and diverges from the default network. *J. Neurosci.* **30**, 16809–16817
(2010).
54. Humphreys, G. F., Lambon Ralph, M. A. & Simons, J. S. A unifying account of angular gyrus
contributions to episodic and semantic cognition. *Trends Neurosci.* **44**, 452–463 (2021).
55. Tibshirani, R. Regression shrinkage and selection via the lasso. *J. R. Stat. Soc. Ser. B Methodol.*
58, 267–288 (1996).
56. Dilkina, K. & Lambon Ralph, M. A. Conceptual structure within and between modalities. *Front.*
Hum. Neurosci. **6**, (2012).

57.   Power, J. D., Barnes, K. A., Snyder, A. Z., Schlaggar, B. L. & Petersen, S. E. Spurious but systematic
correlations in functional connectivity MRI networks arise from subject motion. *NeuroImage* **59**,
2142–2154 (2012).
58.   Afyouni, S. & Nichols, T. E. Insight and inference for DVARS. *NeuroImage* **172**, 291–312 (2018).
59.   Frisby, S. L. *et al.* All spectral frequencies of neural activity reveal semantic representation in the
human anterior ventral temporal cortex. 2025.04.17.649404 Preprint at
https://doi.org/10.1101/2025.04.17.649404 (2025).
60.   Clarke, A. Dynamic activity patterns in the anterior temporal lobe represents object semantics.
Cogn. Neurosci. **11**, 111–121 (2020).
61.   Rupp, K. *et al.* Semantic attributes are encoded in human electrocorticographic signals during
visual object recognition. *NeuroImage* **148**, 318–329 (2017).
62.   Wang, W., Degenhart, A. D., Sudre, G. P., Pomerleau, D. A. & Tyler-Kabara, E. C. Decoding
semantic information from human electrocorticographic (ECoG) signals. *Annu. Int. Conf. IEEE*
Eng. Med. Biol. Soc. IEEE Eng. Med. Biol. Soc. Annu. Int. Conf. **2011**, 6294–6298 (2011).
63.   Sato, N. *et al.* Frequency-dependent cortical interactions during semantic processing: an
electrocorticogram cross-spectrum analysis using a semantic space model. *Cereb. Cortex* **31**,
4329–4339 (2021).
64.   Matoba, K. *et al.* Basal temporal language area revisited in Japanese language with a language
function density map. *Cereb. Cortex* **34**, bhae218 (2024).
65.   Cox, C. R. Testing neurocognitive predictions of the hub-and-spoke model of semantic memory
with network representational similarity analysis. (University of Wisconsin-Madison, 2016).
66.   Handjaras, G. *et al.* Modality-independent encoding of individual concepts in the left parietal
cortex. *Neuropsychologia* **105**, 39–49 (2017).
67.   Fernandino, L., Tong, J.-Q., Conant, L. L., Humphries, C. J. & Binder, J. R. Decoding the
information structure underlying the neural representation of concepts. *Proc. Natl. Acad. Sci.*
119, e2108091119 (2022).
68.   Humphreys, G. F. & Tibon, R. Dual-axes of functional organisation across lateral parietal cortex:
the angular gyrus forms part of a multi-modal buffering system. *Brain Struct. Funct.* **228**, 341–
352 (2023).
69.   Giallanza, T., Campbell, D., Cohen, J. D. & Rogers, T. T. An integrated model of semantics and
control. *Psychol. Rev.* (2024) doi:10.1037/rev0000485.
70.   Morrison, C. M., Chappell, T. D. & Ellis, A. W. Age of acquisition norms for a large set of object
names and their relation to adult estimates and other variables. *Q. J. Exp. Psychol. Sect. A* **50**,
528–559 (1997).
71.   Barry, C., Morrison, C. M. & Ellis, A. W. Naming the Snodgrass and Vanderwart pictures: Effects
of age of acquisition, frequency, and name agreement. *Q. J. Exp. Psychol. Sect. A* **50**, 560–585
(1997).
72.   Peirce, J. *et al.* PsychoPy2: Experiments in behavior made easy. *Behav. Res. Methods* **51**, 195–
203 (2019).
73.   Gorgolewski, K. J. *et al.* The brain imaging data structure, a format for organizing and describing
outputs of neuroimaging experiments. *Sci. Data* **3**, 160044 (2016).
74.   Halchenko, Y. O. *et al.* HeuDiConv — flexible DICOM conversion into structured directory
layouts. *J. Open Source Softw.* **9**, 5839 (2024).
75.   Esteban, O. *et al.* fMRIPrep: a robust preprocessing pipeline for functional MRI. *Nat. Methods*
16, 111–116 (2019).
76.   Gorgolewski, K. J. *et al.* Nipype: A flexible, lightweight and extensible neuroimaging data
processing framework in python. *Front. Neuroinformatics* **5**, (2011).
77.   Markiewicz, C. J. *et al.* fMRIPrep: a robust preprocessing pipeline for functional MRI. Zenodo
https://doi.org/10.5281/zenodo.12774221 (2024).
78.   O'Brien, K. R. *et al.* Robust T1-weighted structural brain imaging and morphometry at 7T using
MP2RAGE. *PLOS ONE* **9**, e99676 (2014).

79. Gaser, C. *et al.* CAT – A computational anatomy toolbox for the analysis of structural MRI data.
2022.06.11.495736 Preprint at https://doi.org/10.1101/2022.06.11.495736 (2023).
80. Tustison, N. J. *et al.* N4ITK: improved N3 bias correction. *IEEE Trans. Med. Imaging* **29**, 1310–
1320 (2010).
81. Zhang, Y., Brady, M. & Smith, S. Segmentation of brain MR images through a hidden Markov
random field model and the expectation-maximization algorithm. *IEEE Trans. Med. Imaging* **20**,
45–57 (2001).
82. Avants, B. B., Tustison, N. & Johnson, H. Advanced Normalization Tools (ANTS). (2009).
83. Avants, B. B. *et al.* A reproducible evaluation of ANTs similarity metric performance in brain
image registration. *NeuroImage* **54**, 2033–2044 (2011).
84. Cox, R. W. AFNI: software for analysis and visualization of functional magnetic resonance
neuroimages. *Comput. Biomed. Res.* **29**, 162–173 (1996).
85. Cox, R. W. & Hyde, J. S. Software tools for analysis and visualization of fMRI data. *NMR Biomed.*
10, 171–178 (1997).
86. Andersson, J. L. R., Skare, S. & Ashburner, J. How to correct susceptibility distortions in spin-echo
echo-planar images: application to diffusion tensor imaging. *NeuroImage* **20**, 870–888 (2003).
87. Jenkinson, M., Beckmann, C. F., Behrens, T. E. J., Woolrich, M. W. & Smith, S. M. FSL.
NeuroImage **62**, 782–790 (2012).
88. Smith, S. M. Fast robust automated brain extraction. *Hum. Brain Mapp.* **17**, 143–155 (2002).
89. Smith, S. M. *et al.* Advances in functional and structural MR image analysis and implementation
as FSL. *NeuroImage* **23**, S208–S219 (2004).
90. The tedana Community *et al.* ME-ICA/tedana: 23.0.1. Zenodo
https://doi.org/10.5281/zenodo.7926293 (2023).
91. DuPre, E. *et al.* TE-dependent analysis of multi-echo fMRI with tedana. *J. Open Source Softw.* **6**,
3669 (2021).
92. Kundu, P., Inati, S. J., Evans, J. W., Luh, W.-M. & Bandettini, P. A. Differentiating BOLD and non-
BOLD signals in fMRI time series using multi-echo EPI. *NeuroImage* **60**, 1759–1770 (2011).
93. Kundu, P. *et al.* Integrated strategy for improving functional connectivity mapping using
multiecho fMRI. *Proc. Natl. Acad. Sci.* **110**, 16187–16192 (2013).
94. Posse, S. Multi-echo acquisition. *NeuroImage* **62**, 665–671 (2012).
95. Andersson, J. L. R., Skare, S. & Ashburner, J. How to correct susceptibility distortions in spin-echo
echo-planar images: application to diffusion tensor imaging. *NeuroImage* **20**, 870–888 (2003).
96. Dale, A. M., Fischl, B. & Sereno, M. I. Cortical Surface-Based Analysis: I. Segmentation and
Surface Reconstruction. *NeuroImage* **9**, 179–194 (1999).
97. Fischl, B., Sereno, M. I. & Dale, A. M. Cortical surface-based analysis: II. Inflation, flattening, and
a surface-based coordinate system. *NeuroImage* **9**, 195–207 (1999).
98. Tzourio-Mazoyer, N. *et al.* Automated anatomical labeling of activations in SPM using a
macroscopic anatomical parcellation of the MNI MRI single-subject brain. *NeuroImage* **15**, 273–
289 (2002).
99. Friedman, J., Hastie, T. & Tibshirani, R. Regularization paths for generalized linear models via
coordinate descent. *J. Stat. Softw.* **33**, (2010).
100.   Zhou, Y., Vales, M. I., Wang, A. & Zhang, Z. Systematic bias of correlation coefficient may
explain negative accuracy of genomic prediction. *Brief. Bioinform.* **18**, 744–753 (2017).
101.   Stelzer, J., Chen, Y. & Turner, R. Statistical inference and multiple testing correction in
classification-based multi-voxel pattern analysis (MVPA): Random permutations and cluster size
control. *NeuroImage* **65**, 69–82 (2013).
102.   Phipson, B. & Smyth, G. K. Permutation p-values should never be zero: calculating exact p-
values when permutations are randomly drawn. *Stat. Appl. Genet. Mol. Biol.* **9**, (2010).
103.   Benjamini, Y. & Hochberg, Y. Controlling the false discovery rate: A practical and powerful
approach to multiple testing. *J. R. Stat. Soc. Ser. B Stat. Methodol.* **57**, 289–300 (1995).
1218