SAGA (Simplified Association Genome-wide Analyses): a user-friendly Pipeline to Democratize Genome-Wide Association Studies

Basilio Cieza[1], Neetesh Pandey[1], Vivek Ruhela[1], Sarwan Ali[1], Giuseppe Tosto*[1,2,3]

1. Taub Institute for Research on Alzheimer's Disease and the Aging Brain, Vagelos College of Physicians and Surgeons, Columbia University. 630 West 168th Street, New York, NY 10032, USA.
2. The Gertrude H. Sergievsky Center, Vagelos College of Physicians and Surgeons, Columbia University. 630 West 168th Street, New York, NY 10032, USA.
3. Department of Neurology, Vagelos College of Physicians and Surgeons, Columbia University, and the New York Presbyterian Hospital. 710 West 168th Street, New York, NY 10032, USA.

*Corresponding author:

Giuseppe Tosto, M.D., Ph.D.

G.H.Sergievsky Center, The Taub Institute for Research on Alzheimer's Disease and the Aging Brain

Department of Neurology, Columbia University Irving Medical Center

630W 168th street, room PH19-314

New York City, New York, 10032

Tel. 212-305-9274

gt2260@cumc.columbia.edu

Abstract

Genome-wide association studies (GWAS) have enabled clinicians and researchers to identify genetic variants linked to complex traits and diseases(1–3). However, GWAS still face several challenges, particularly regarding accessibility and reproducibility (4–6). Conducting these analyses often requires substantial bioinformatics expertise for data preprocessing, software installation, and scripting(7–10). We then developed SAGA ("*Simplified Association Genome-wide Analyses'*), a BASH-based, open-source, fully automated pipeline that integrates three widely adopted tools—PLINK(11), GMMAT(12), and SAIGE(13)—for accessible, robust, and reproducible GWAS. After installation, users simply need to provide genotype and phenotype files in standard formats. The pipeline automates preprocessing, association testing, and visualization, outputting summary statistics, Manhattan plots, and quantile-quantile plots. SAGA enables robust GWAS for users without scripting experience, expanding access to complex genetic analyses.

Keywords: GWAS, SAIGE, GMMAT, PLINK, pipeline, bash, summary statistics, user-friendly, Manhattan plot, quantile-quantile plot.

1. Introduction

Genome-wide association studies (GWAS) have transformed discovery of gene-variant associations for complex traits and diseases in human populations (14–16). Yet, the broader deployment of GWAS is limited by technical barriers: multi-step software installations, data formatting, and intricate analytic workflows (17–19). SAGA ("*Simplified Association Genome-wide Analyses*") addresses this gap for non-bioinformaticians with a modular, bash-based pipeline that integrates three popular platforms: **PLINK** for standard linear/logistic regression (11), **GMMAT** for generalized mixed model association testing, suited for related or family-based samples (12), and **SAIGE** for large, imbalanced case-control studies and rare variant analysis (13). SAGA offers an automated, reproducible solution for GWAS analysis on mainstream genomic data, providing ready-to-use outputs for downstream exploration and publication.

2. Methods

Tool Selection and Rationale

We implemented PLINK, GMMAT, and SAIGE for their complementary strengths (11–13) (**Table 1**).

Pipeline Workflow

The user simply has to shape input genetic files in traditional PLINK's binary format (*.bed/.bim/.fam*) along with a structured phenotype file containing family and individual IDs ("*FID*" and "*IID*", respectively), outcome measures (binary or quantitative), and optional covariates. All input files undergo automated validation to ensure completeness and correct formatting (**Supplementary Figure 1** for more details). In the preprocessing stage, SAGA performs quality control (QC) to filter variants and samples based on missingness, Hardy–Weinberg equilibrium, and minor allele frequency (MAF) thresholds as best practice guides suggest (20–22) (**Supplementary Table 1** and **2**). Population structure is assessed via principal component analysis (PCA), generating the top ten principal components for covariate adjustment (23,24) using PLINK. To account for relatedness in GMMAT, SAGA generates a dense genetic relationship matrix (GRM) using GEMMA (25); on the contrary, SAIGE builds internally a sparse GRM which will be used in subsequential steps. Each preprocessing step is standardized and error-checked to minimize user intervention. Association analysis is conducted using one of three backends, selected automatically according to user-defined parameters or data characteristics: PLINK for fast linear or logistic regression on no related populations, GMMAT for generalized linear mixed models in related populations, and SAIGE (which uses a saddlepoint approximation "SPA") for mixed model designed to handle large-scale datasets (e.g. biobanks) featuring highly unbalanced case-control ratios and analyses of rare variants. Finally, post-analysis procedures standardize summary statistics across backends and produce publication-ready Manhattan and quantile-quantile (QQ) plots in both high-resolution *.png* and *.pdf* formats using

automated R scripts (26). This fully integrated workflow ensures consistent, reproducible results from raw genotype data to final visualization.

Technical Implementation

SAGA is implemented entirely in BASH and requires only a UNIX/Linux environment for execution. The pipeline depends on PLINK for genotype processing, R 4.2.2 for running GMMAT and generating plots, and Singularity container of SAIGE (version 1.3.0) for scalable mixed-model association testing. Installation is straightforward via a single command:

git clone https://github.com/bciezah1/SAGA.git

Upon completion of the analysis, SAGA generates all results in an organized output/ directory. This includes standardized summary statistics ("*summary_stats.txt*") and high-quality plots (Manhattan, QQ, and SNP density plots).

Automated Preprocessing Details

Once installed, the package can be launched via a single command.

For example, employing PLINK with a binary phenotype and three covariates:

> **./run_pipeline_plink.sh **
>
> *{user's path}/***toy_data/geno **
>
> *{user's path}/***toy_data/pheno_binary.txt **
>
> **COV1, COV2, COV3, PC1, PC2, PC3 **
>
> **PHENO **
>
> **binary **
>
> **OutputFolderLabel**

In this example, the second argument specifies the location of the genotype data in PLINK format, followed by the phenotype file location, a comma-separated list of covariates ("*COV1, COV2, COV3*") and principal components to include ("*PC1, PC2, PC3*"), the target phenotype name ("*PHENO*"), the phenotype type ("*quantitative*" or "*binary*"), and the label of the folder where the results will be located ("*OutputFolderLabel*"). Upon completion, SAGA generates standardized summary statistics ("*summary_stats.txt*") and high-quality Manhattan and QQ plots ("*manhattan.png" and "qqplot.png*" (**Supplementary Table 2** for additional details).

3. Benchmarking

Simulated Data

We benchmarked the performance and usability of SAGA, using in-house simulated datasets that varied in complexity in a controlled manner. Specifically, we simulated datasets with three different sample sizes (N=1,000, 5,000, and 10,000 individuals), with 100 000 single nucleotide polymorphisms (SNPs; **Figure 1**, **Supplementary Table 3**). Phenotypes and covariates were simulated to mimic binary traits with typical covariate structures encountered in common GWAS studies. Each dataset was analyzed separately using the three GWAS analysis backends integrated within SAGA.

Real Data

We further evaluated the performance and applicability of SAGA using real data from the Alzheimer's Disease Sequencing Project (ADSP) (27). Specifically, we analyzed seven independent cohorts — ADC, PeADI, NOMAS, PRADI, PR1066, TARCC, and WHICAP — each representing diverse populations and study designs.

For each cohort, genotype and phenotype data were processed independently through the full SAGA workflow, including sample and variant QC, SNP pruning, covariate adjustment, and genome-wide association testing. The primary phenotype, Alzheimer's disease (AD), was modeled as a binary trait, with age, sex, and the top five ancestry-derived PCs included as covariates.

Each cohort was analyzed individually using SAGA (PLINK, GMMAT, and SAIGE. In addition, all cohorts were combined into a single multi-sample to perform a joint genome-wide association analysis, enabling us to test SAGA under large sample sizes (in addition to increased statistical power and cross-cohort consistency assessment). Results for the ADSP multi-sample using SAIGE are presented in **Figure 2** and **3** (**Supplementary Figure 3** and **4** for PLINK and GMMAT results, respectively), while results from individual cohort are provided in **Supplementary Figures 4-10**.

4. Discussion and conclusions

SAGA provides GWAS workflow for users without scripting or programming expertise by offering an intuitive and automated framework. One of its major advantages is ease of access, as users do not need to edit code and only require minimal familiarity with command-line operations (customized coding is of course optional to the user's end). The pipeline covers all critical steps of genome-wide association studies, from quality control through association analysis to the generation of publication-ready plots, thereby significantly reducing the technical burden on researchers. By employing consistent, standardized processing methods compliant with leading best practices (20–22), SAGA ensures reproducible results across multiple runs. Importantly, it

includes rigorous quality control measures that account for population structure and relatedness among samples, facilitating robust association testing.

Our benchmarking results highlight the strengths of SAGA in terms of runtime efficiency, error control, reproducibility, and usability. Moreover, SAGA substantially simplifies GWAS implementation, enabling researchers - even those with limited computational experience - to perform large-scale analyses quickly and reliably as we showed in our analysis of ADSP data. Importantly, the framework demonstrated the ability to scale with increasing dataset sizes and variant complexity while preserving automated and reproducible workflows across multiple statistical models and software implementations. These findings underscore the utility of SAGA for a wide range of GWAS applications and emphasize its potential to broaden access to advanced genetic association analyses for researchers without extensive computational expertise.

SAGA has some limitations. It assumes that users provide valid and properly formatted phenotype files, as it does not incorporate functionality to check or compose phenotypic data. Additionally, SAGA currently lacks native support for meta-analysis or the merging of multiple cohorts, which are important considerations for large-scale genetic studies. While the pipeline can handle moderately large datasets, analyzing very large datasets—such as those exceeding 50,000 individuals—may still require high-performance computing clusters or cloud resources due to memory and processing demands. SAGA has been tested and optimized for Linux-based systems and has not yet been validated on Windows or macOS environments. Moreover, the SAIGE component is executed through a Singularity image, which requires a compatible cluster or server environment and is not intended for use on local workstations or laptops.

We have plans to include the addition of modules for gene-based rare variant analyses, which would extend the pipeline's scope to capture a broader spectrum of genetic variation. The developers also intend to implement advanced post-GWAS annotation functionalities, including compatibility with tools for pathway analyses, which can facilitate the biological interpretation of significant loci. Another anticipated feature is support for polygenic risk scores, enabling the translation of GWAS findings into quantitative measures of genetic risk for complex diseases. These enhancements aim to further empower researchers with limited computational backgrounds to perform comprehensive and insightful genetic association studies.

Table 1. Software included in SAGA and their features.

Tool	Key Strengths	Ideal For	Model Type	Handles Relatedness	Handles Case-Control Imbalance
PLINK	Fast, user-friendly	Unrelated individuals	Linear/logistic regression	NO	NO
GMMAT	Mixed models, kinship-aware	Family/related samples	Linear/logistic mixed model	YES	NO
SAIGE	Scalability, rare variants	Biobank, unbalanced traits	Saddlepoint Approximation (SPA)	YES	YES

Figure 1. Benchmark for three different samples sizes and 100,000 SNPs using PLINK, GMMAT, and SAIGE (green, red and blue color, respectively).

Figure 2. Manhattan plot, QQ, and SNP density plot for <u>common variant</u> analysis using SAIGE.

Figure 3. Manhattan plot, QQ, and SNP density plot for <u>rare variant</u> analysis using SAIGE.

DATA AND SOFTWARE AVAILABILITY

All code, documentation, and test data are available at:

https://github.com/bciezah1/SAGA.git

AUTHOR CONTRIBUTIONS

BC, GT: Conceptualization, manuscript writing

BC: software development

BC, NP, VR, SA, GT: documentation, testing

ETHICAL STATEMENT

No human or animal subjects were involved in this work. All testing datasets were simulated and fully anonymized.

ACKNOWLEDGEMENTS

We thank the GiusTo Lab at Columbia University for cohort data access and deployment support. This work is supported by NIA/NIH award U01AG081817, RF1AG082009 and U19AG074865.

REFERENCES

1. Uffelmann E, Huang QQ, Munung NS, de Vries J, Okada Y, Martin AR, et al. Genome-wide association studies. Vol. 1, Nature Reviews Methods Primers. Springer Nature; 2021.

2. Abdellaoui A, Yengo L, Verweij KJH, Visscher PM. 15 years of GWAS discovery: Realizing the promise. Vol. 110, American Journal of Human Genetics. Cell Press; 2023. p. 179–94.

3. Manolio TA. Bringing genome-wide association findings into clinical use. Vol. 14, Nature Reviews Genetics. 2013. p. 549–58.

4. Marigorta UM, Rodríguez JA, Gibson G, Navarro A. Replicability and Prediction: Lessons and Challenges from GWAS. Vol. 34, Trends in Genetics. Elsevier Ltd; 2018. p. 504–17.

5. Trent Editor R. Clinical Bioinformatics Second Edition Methods in Molecular Biology 1168 [Internet]. Available from: http://www.springer.com/series/7651

6. McCarthy MI, Abecasis GR, Cardon LR, Goldstein DB, Little J, Ioannidis JPA, et al. Genome-wide association studies for complex traits: Consensus, uncertainty and challenges. Vol. 9, Nature Reviews Genetics. 2008. p. 356–69.

7. Schönherr S, Schachtl-Riess JF, Di Maio S, Filosi M, Mark M, Lamina C, et al. Performing highly parallelized and reproducible GWAS analysis on biobank-scale data. NAR Genom Bioinform. 2024 Mar 1;6(1).

8. Song Z, Gurinovich A, Federico A, Monti S, Sebastiani P. nf-gwas-pipeline: A Nextflow Genome-Wide Association Study Pipeline. J Open Source Softw. 2021 Mar 2;6(59):2957.

9. Childs LH, Lisec J, Walther D. Matapax: An online high-throughput genome-wide association study pipeline. Plant Physiol. 2012;158(4):1534–41.

10. Muñiz-Fernandez F, Carreño-Torres A, Morcillo-Suarez C, Navarro A. Genome-wide association studies pipeline (GWASpi): A desktop application for genome-wide SNP analysis and management. Bioinformatics. 2011 Jul;27(13):1871–2.

11. Purcell S, Neale B, Todd-Brown K, Thomas L, Ferreira MAR, Bender D, et al. PLINK: A tool set for whole-genome association and population-based linkage analyses. Am J Hum Genet. 2007;81(3):559–75.

12. Chen H, Wang C, Conomos MP, Stilp AM, Li Z, Sofer T, et al. Control for Population Structure and Relatedness for Binary Traits in Genetic Association Studies via Logistic Mixed Models. Am J Hum Genet. 2016 Apr 7;98(4):653–66.

13. Zhou W, Nielsen JB, Fritsche LG, Dey R, Gabrielsen ME, Wolford BN, et al. Efficiently controlling for case-control imbalance and sample relatedness in large-scale genetic association studies. Nat Genet. 2018 Sep 1;50(9):1335–41.

14. Khan O, Ullah N. Unlocking Rare Diseases Genetics: Insights from Genome-Wide Association Studies and Single Nucleotide Polymorphisms. Vol. 7, International Journal of Int. J. Mol. Microbiol. Alam. 2024.

15. Kingsmore SF, Lindquist IE, Mudge J, Gessler DD, Beavis WD. Genome-wide association studies: Progress and potential for drug discovery and development. Vol. 7, Nature Reviews Drug Discovery. 2008. p. 221–30.

16. Khoury MJ, Bertram L, Boffetta P, Butterworth AS, Chanock SJ, Dolan SM, et al. Genome-wide association studies, field synopses, and the development of the knowledge base on genetic variation and human diseases. Vol. 170, American Journal of Epidemiology. 2009. p. 269–79.

17. Moore JH, Asselbergs FW, Williams SM. Bioinformatics challenges for genome-wide association studies. Vol. 26, Bioinformatics. 2010. p. 445–55.

18. Akdeniz BC, Frei O, Hagen E, Filiz TT, Karthikeyan S, Pasman J, et al. COSGAP: COntainerized Statistical Genetics Analysis Pipelines. Bioinformatics Advances. 2024;4(1).

19. Lück S, Scholz U, Douchkov D. Introducing GWAStic: a user-friendly, cross-platform solution for genome-wide association studies and genomic prediction. Bioinformatics Advances. 2024;4(1).

20. Casaburi G, McCullough R, D'Argenio V. Establishing Best Practices for Clinical GWAS: Tackling Imputation and Data Quality Challenges. Vol. 26, International Journal of Molecular Sciences. Multidisciplinary Digital Publishing Institute (MDPI); 2025.

21. Pavan S, Delvento C, Ricciardi L, Lotti C, Ciani E, D'Agostino N. Recommendations for Choosing the Genotyping Method and Best Practices for Quality Control in Crop Genome-Wide Association Studies. Vol. 11, Frontiers in Genetics. Frontiers Media S.A.; 2020.

22. Marees AT, de Kluiver H, Stringer S, Vorspan F, Curis E, Marie-Claire C, et al. A tutorial on conducting genome-wide association studies: Quality control and statistical analysis. Int J Methods Psychiatr Res. 2018 Jun 1;27(2).

23. Patterson N, Price AL, Reich D. Population structure and eigenanalysis. PLoS Genet. 2006 Dec;2(12):2074–93.

24. Yu K, Wang Z, Li Q, Wacholder S, Hunter DJ, Hoover RN, et al. Population substructure and control selection in genome-wide association studies. PLoS One. 2008 Jul 2;3(7).

25. Zhou X, Stephens M. Genome-wide efficient mixed-model analysis for association studies. Nat Genet. 2012 Jul;44(7):821–4.

26. Yin L, Zhang H, Tang Z, Xu J, Yin D, Zhang Z, et al. rMVP: A Memory-efficient, Visualization-enhanced, and Parallel-accelerated Tool for Genome-wide Association Study. Genomics Proteomics Bioinformatics. 2021 Aug 1;19(4):619–28.

27. Carter L, Leung YY, Lee W, Kuzma AB, Gangadharan P, Nicaretta HI, et al. ADSP Whole Genome Sequencing (WGS) Release 5 data update from Genome Center for Alzheimer's Disease. Alzheimer's & Dementia [Internet]. 2024 Dec 3;20(S1). Available from: https://alz-journals.onlinelibrary.wiley.com/doi/10.1002/alz.087495