Unraveling operational drivers of nitrous oxide emissions in biological wastewater

treatment systems through machine learning analysis of multi-decadal datasets

Gnanaraj Augustine, Kartik Chandran[*]

[*]*Department of Environmental Engineering, Columbia University, New York, 10027, USA*

ABSTRACT: This study focused on the development of machine-learning- (ML-) based strategies for

mitigating nitrous oxide (N_2O) emissions from various wastewater treatment systems in the United

States measured using a benchmark USEPA-endorsed protocol. Results revealed that in general, poor

process performance correlated with higher N_2O emissions. Specifically, local variables including zone-

specific dissolved oxygen, ammonia, and nitrite concentrations and global variables including effluent

nitrite and nitrate concentrations contributed positively towards N_2O emissions from both aerobic and

anoxic zones of the process bioreactors. The optimal operational conditions identified for minimizing

N_2O emissions included, operation of aerobic and anoxic zones at DO > 4 mg O_2/L and < 1 mg O_2/L,

respectively, coupled with appropriate solids retention times (SRTs) that maximize process performance.

Accordingly, our results strongly underscore the utility of ML models in combination with bioprocess

fundamentals for predicting and mitigating N_2O emissions, while concomitantly optimizing wastewater

treatment operations.

KEYWORDS: *nitrous oxide, activated sludge, greenhouse gas, machine learning*

Introduction

Nitrous oxide (N_2O) is a potent greenhouse gas (GHG) and ozone depleting substance [1,2]. Wastewater

treatment plants (WWTPs) have been increasingly recognized as substantial anthropogenic sources

of N_2O emissions[3–7]. On one hand, increasingly stringent effluent nitrogen limits from wastewater

treatment plants have spurred a global effort to develop and implement engineered biological nutrient

removal (BNR) processes to improve water quality[4]. On the other hand, suboptimal operating

conditions and process configurations associated with BNR operations can exacerbate N_2O

production[8].

Biological pathways and drivers for chemolithoautotrophic and chemoorganoheterotrophic

N_2O production during BNR operations. During nitrification, ammonia-oxidizing bacteria (AOB)

and nitrite-oxidizing bacteria (NOB) sequentially oxidize ammonia (NH_3) to nitrite (NO_2^-) and nitrate

(NO_3^-), respectively, using oxygen as the preferred terminal electron acceptor[9]. During denitrification,

NO_3^- is reduced to dinitrogen (N_2) gas, coupled with the utilization of organic or inorganic electron

donors[9]. In nitrifying WWTPs, AOB produce nitric oxide (NO) and N_2O via nitrifier denitrification

under limiting dissolved oxygen (DO) and non-limiting NO_2^- concentrations [6,10–15]. Also, under non-

limiting DO and NH_3 concentrations, AOB produce N_2O during the oxidation of hydroxylamine

(NH_2OH) [10,16]. N_2O can also be produced through chemical oxidation of NH_2OH abiotically [10,16].

During typical engineered denitrification, chemoorganoheterotrophic bacteria produce N_2O under

operating conditions that favor inhibition of nitrous oxide reductase (Nos) [16], for instance, associated

with inhibition by oxygen and NO_2^- [12,17,18]. Despite the contribution of both nitrification and

denitrification in N_2O production, it has now been established that both *production* and *emission* of

N_2O from aerated zones are higher than from non-aerated zones at WWTPs [4].

The characterization and minimization of N_2O emissions from WWTPs has assumed widespread and

critical importance as wastewater utilities aim to minimize the overall carbon footprint of treatment

operations, while adhering to increasingly stringent discharge regulations[19]. Previous N_2O

footprinting studies performed at full-scale BNR and non-BNR WWTPs around the United States

reported N_2O emission fractions (EFs) in the range 0.01-1.8% relative to the influent TKN load[4].

Other full-scale studies have reported widely varying EFs in the range 0.001-25.4% of the influent

load[4,20].

N_2O production is directly correlated with nitrogen conversion dynamics in WWTPs further

indicating the potential of N_2O emissions as BNR performance indicators [4–6,20]. Various operational

and environmental factors such as solids retention time (SRT), specific AOB activity, temperature,

and influent loading patterns contribute to both N_2O emissions and overall process performance in

BNR systems [4–7,20]. BNR operations at sub-optimal conditions, such as excessively high or low DO

concentrations combined with inadequate SRT, can lead to transient or permanent NH_3 or NO_2^-

accumulation. Such accumulation is symptomatic of inadequate nitrification and denitrification

performance and can be correlated, in turn, to NO and N_2O production and emission[5–10]. Mechanistic

models have been used to predict and reduce N_2O emissions in the BNR systems from WWTPs,

ranging from models based on the activated sludge framework [21] to models based on gene- and

protein-expression[15,22–25]. Other data-driven models have also been proposed, which when trained

on robust and representative datasets, offer a balance between the mathematical and metabolic

intricacies relating to N_2O production and their practical end-application for process control[4,26].

Data-driven models such as unsupervised Principal Component Analysis (PCA) and supervised

machine learning (ML) models have shown greater insights into improving process performance and

identifying factors contributing to N_2O emissions[27–39]. Supervised ML models have demonstrated the

potential for predicting N_2O emissions from full-scale BNR operations, and studies have shown the

usage of ML models focused on predicting effluent water quality[32–36] or separate N_2O emissions.[40–

43], with limited dataset and using different models and hyperparameter optimization (HPO)[43].

In this study, we subjected both historical and currently obtained datasets to unsupervised PCA and

supervised ML modeling approaches to uncover the complex interplay between operational strategies,

N_2O emissions and effluent water quality and to develop actionable insights into WWTP operating

strategies that minimize both *gaseous* and *aqueous* nitrogenous discharges. Through this research,

we offer new insights into concurrently maximizing BNR process efficiency and achieving

decarbonization of BNR operations, thereby promoting a more sustainable wastewater sector.

Results

Updated N_2O emissions from advanced mainstream and sidestream activated sludge processes

We first present the results obtained from recently conducted (2023-2024) N_2O measurement

campaigns at five different next-generation mainstream and sidestream wastewater treatment

processes in the Northeastern and Mid-Atlantic regions of the United States (**Table 1**). For the

mainstream processes tested, the average emission factor (EF), representing the fraction of the

influent nitrogen load emitted as N_2O, was statistically lower than the IPCC EF ($1.6\pm1.2\%$) ($p=0.03$,

$\alpha=0.05$)[3]. Within the mainstream processes evaluated, the EF for the four-pass step-feed BNR process

tested ($0.20\pm0.03\%$) was statistically higher ($p=0.01$, $\alpha=0.05$) than for the processes based on

ammonia-based aeration control (ABAC) ($0.004\pm0.00\%$), partial denitratation-anammox (PdNA)

($0.006\pm0.00\%$), and fermentate-fed partial denitratation ($0.003\pm0.00\%$). In contrast, the *sidestream*

process exhibited EFs in the range 6.3 -14 %, which were statistically higher ($p<0.05$) than both the

mainstream and IPCC EFs. Compared to our previous study EF**(Table 1),** our current study EF from

next-generation mainstream systems shows lower EF and better N-removal (**Figure S1**), showcasing

our recent development in improved process operation and reduced N_2O emissions.

However, some process-specific nuances could also be inferred based on the current datasets. For

the mainstream PdNA process, operating temperature did not statistically impact either the BNR

performance (% TN removal, which averaged 72 ± 9 % across temperatures) or the N_2O EF (**Table**

1). In contrast, the emissions from the step-feed BNR process were higher during the lower

temperature monitoring campaign (**Table 1**). On the other hand, ABAC-based process represents

distinct operating characteristics with uncoupled organic carbon, nitrification, and post-

denitrification, and displayed a low EF. A specific N-removal efficiency for the ABAC process could

not be correlated with the measured N_2O emissions, which were restricted to the aerated zones in the

process (**Table 1**). Therefore, N_2O emissions are subjective to their process operations within the

designed process configuration, and are not truly influenced by operating temperatures.

The SHARON process tested treats post-anaerobic digestion centrate and operates via a combination

of nitritation (oxidation of influent NH_3 to NO_2^-) followed by glycerol-mediated denitritation

(reduction of NO_2^- to N_2). The SHARON process displayed low ammonia conversion ($46\pm15\%$ and

$54\pm11\%$) and low nitrogen removal ($36\pm17\%$ and $38\pm16\%$)(**Table 1**). These observed process

performance measures corresponded with a higher N_2O EF (6.3-14%), relative to the other processes

tested. Conceptually, sidestream treatment processes, including those operating in partial nitritation

mode can display EFs as low as 0.5%[4,44], suggesting considerable room for reduction in emissions

with concomitant performance improvements in the system tested herein.

Such findings reinforce the previously demonstrated parallels between process performance and N_2O

emissions from WWTPs[7,44–46]. Nevertheless, a robust approach capable of unraveling the complex

interplay between process configurations, operating conditions, process performance and

corresponding emissions is needed to explore the development of process optimization and

decarbonization strategies, and is described next.

Unraveling the Interdependencies of N_2O Flux and Process Parameters Using a Multi-Decadal

Wastewater Treatment Operations Dataset

Advanced unsupervised and supervised machine learning models were employed using our present

and past wastewater process operational data spanning more than a decade of process monitoring

(**Table 1**), with the goal of improving both *aqueous* and *gaseous* nitrogen discharges.

First, using unsupervised principal component analysis (PCA), we revealed the interdependencies

between nitrification and denitrification process variables (nitrogen species, organic compounds,

suspended solids), operating conditions (SRT, influent flow rate) and measured N_2O fluxes. In the

presented PCA biplots, (**Figures 1A and 1B)** the length of the arrow represents the magnitude of the

variable contribution. Positively correlated variables are clustered on the same side of the axis of a

reference variable (for instance, N_2O fluxes), while the negatively and uncorrelated variables are

positioned opposite and perpendicular, respectively. We further classified the different influential

factors into two categories. Specifically, zone-specific variables including NH_3, DO, NO_2^- and SRT

were classified as *local variables*, since they reflect spatially discrete sampling locations within the

WWTP process bioreactors. Influent and effluent water quality parameters, influent flowrate, and

temperature were considered as *global variables*.

PCA-based interpretation of aerated zone emissions. Based on aerated zone data from current and

previous sampling campaigns, PC1 and PC2 captured 35.7% and 19.1% of the variance, respectively

(**Figure.1A**). Among the local variables, NH_3, DO, NO_2^- and among the global variables, influent

TKN, effluent NO_2^-, effluent TSS, effluent ffCOD, and effluent tCOD were strongly and positively

correlated with N_2O fluxes (**Figures 1, and S2A**). One fundamental interpretation of such

correlations between the local variables and observed N_2O emissions from the aerated zones points

to the role of nitrifier nitrification and nitrifier denitrification pathways. During nitrifier-nitrification,

non-limiting DO and NH_3 concentrations in aerated zones can lead to incomplete NH_2OH oxidation

by AOB, which results in NO and N_2O production therein [4,10,16]. During nitrifier-denitrification, AOB

produce N_2O primarily under conditions that result in non-limiting NO_2^- concentrations, potentially

exacerbated by limiting DO and non-limiting NH_3 concentrations [4,10]. Of the global variables, high

influent TKN and effluent NO_2^- concentrations could indirectly correspond with higher N_2O fluxes

depending on SRT and the corresponding extant local variables (**Figure 1A**). The observed positive

correlation of measured N_2O fluxes with different effluent TSS and organic carbon (ffCOD and

tCOD) concentrations for a given degree of nitrification cannot be interpreted in isolation and likely

needs to be considered using more complex models (such as the ML models considered below).

Negative correlations of SRT, zone-specific NO_3^-, and influent tCOD concentrations with measured

N_2O fluxes were also observed (**Figures 1A, and S2A**), suggesting overall that conditions that

promote full nitrification (higher zone-specific NO_3^- concentrations) at WWTPs (higher SRTs)

correspond to lower N_2O fluxes (in keeping with previous results) [47]. In general, the link between

lower N_2O emissions and lower influent tCOD concentrations is indirect and points to increased

oxygen availability for complete nitrification compared to organic carbon oxidation[9].

Of the remaining global variables, effluent NO_2^- concentrations correlated positively with aerobic

N_2O fluxes, and likely represent the link inadequate nitrogen removal and higher N_2O emissions[4]

(**Figures.1A and S2A**). The global variables captured by both PC1 and PC2 included temperature,

influent flow rate, influent TIN, influent NH_3, effluent VSS, effluent NH_3, and did not statistically

correlate with aerobic-zone N_2O fluxes (**Figures 1A, and S2A**).

PCA-based interpretation of anoxic-zone emissions. For data obtained from all the previously and

currently sampled anoxic zones, PC1 and PC2 captured 32.4% and 15.3% of the variance,

respectively. Local variables including zone-specific DO and NO_2^- concentrations were positively

correlated with measured N_2O fluxes (**Figures 1B, and S2B**). Notably, zone-specific DO and NO_2^-

concentrations clustered closely together, emphasizing their potential significant interactive impacts

on N_2O production again linked with poor process operation and incomplete denitrification, as also

shown previously [4].

Global variables such as effluent NO_3^-, effluent NO_2^-, influent TKN, influent NH_3, and influent TIN

concentrations, exhibited a positive correlation with N_2O fluxes (**Figures 1B, and S2B**). In contrast,

zone-specific NO_3^- concentrations and influent flow rate were negatively correlated with N_2O fluxes

(**Figure 1B**). Effluent TKN and effluent NH_3 concentrations were not statistically correlated with

N_2O fluxes (**Figures 1B, and S2B**).

Hyperparameter Optimization of ML models for predicting N_2O flux under different

wastewater treatment parameters

We further developed ML models with combinations of different process variables and parameters

from our past and present data to predict and mitigate N_2O emissions from WWTP operations. The

ML models were trained to predict N_2O flux (g-N/min-m^2), N_2O emission rate (g-N/d), and N_2O

concentration (ppm) using three machine learning algorithms namely Random forest (RF), Gradient

Boosting (GBM), and XG Boost. Each model was optimized under different hyperparameter tuning

to identify the optimum parameter for achieving the best prediction performance (**Table S1**). Among

these, XG boost consistently demonstrated superior performance, achieving an R^2 of 0.99 for N_2O

flux prediction in both aerobic and anoxic conditions. The Root Mean Square Error (RMSE) for XG

Boost was significantly lower compared to RF and GB, with values of 0.053 and 0.022 for aerobic

and anoxic conditions (Table S2). Furthermore, N_2O emission rates and concentrations also showed

higher prediction accuracy with XG Boost compared to RF and GB models (**Table S2**).

Machine Learning Insights into the direct impact of wastewater effluent quality on N_2O flux

From the trained ML models, permutation importance values were extracted for both aerobic and

anoxic zone conditions (**Figure 2A-C**). The most important variables influencing aerated-zone N_2O

emission fluxes included influent flow rate, local NH_3, DO, and NO_2^- concentrations, SRT, and

Effluent NO_2^- concentrations (**Figure 2B**). For non-aerated zones, the most important variables

influencing N_2O emission fluxes were temperature, zone-specific DO, and NO_2^- concentrations, SRT,

and Influent NH_3, Effluent NO_3^-, Effluent TIN and Effluent sCOD concentrations **(Figure 2C)**. These

variables identified by the ML models as being influential on N_2O emissions aligned with the PCA

analysis and underscored the now well-established link between process performance and emissions

[4]. Our results also aligned with findings from a similar ML study using AdaBoost, which pointed to

temperature, DO, NH_3, NO_2^-, and NO_3^- as being influential factors for aerobic zone N_2O emissions,

without corresponding insights into anoxic-zone emissions [27]. Our study highlights the critical need

to consider quantifying and predicting N_2O emissions from anoxic zones, as their contribution to N_2O

production and emissions are inevitably under poor operating conditions[4,5].

We further integrated SHAP analysis to uncover the magnitude and directionality influence

of the variables towards predicted N_2O flux, bridging the gap between model predictions and

actionable process insights. *SHAP analysis for aerobic* N_2O flux indicates that influent flow rate is

the most significant variable compared to others (**Figure 3A**). An increase in influent flow rate

positively influences higher N_2O flux, as it is on the positive side of the SHAP values. NH_3 and DO

demonstrate considerable influence as elevated NH_3 SHAP value and its concentrations explain

increased N_2O flux, while higher DO levels can result in both higher and lower N_2O flux conditions,

depending on the condition. The results show that operations under non-limiting NH_3 concentrations

can lead to N_2O production, regardless of whether DO levels are high or low. Therefore, optimizing

DO levels *in conjunction with* appropriate NH_3 concentrations is essential for effective nitrification.

Our results also suggest potential interactive effects of operating SRT with DO and NH_3

concentrations (**Figure 3A**), which has a firm biochemical basis. For instance, operation at elevated

SRT can lead to reduced N_2O fluxes, when coupled with optimization of DO concentrations to

achieve a given NH_3 conversion. Based on our data, NO_2^- concentrations had a lower impact on N_2O

fluxes compared to that of NH_3, DO, and SRT. Again, the production of NO_2^- can only be controlled

by concurrently optimizing DO and SRT along with NH_3 concentration.

Based on *SHAP analysis for anoxic* zones, the N_2O fluxes therein were highly influenced by

DO concentrations (**Figure 3B**), which could be linked to DO-mediated inhibition of N_2O reduction

to N_2[4,5,18]. A biphasic response of N_2O fluxes to SRT values was observed once again pointing to

possible interactions with extant DO and NO_2^- concentrations. NO_3^- on the other hand, influenced

anoxic-zone N_2O to a lower extent. Higher NO_3^- feature value representing higher SHAP value

(**Figure 3B**) does not directly imply its involvement in producing N_2O. The global variables, effluent

NO_2^- and NO_3^- have higher feature values in the positive side of the SHAP (Figure 3B), reflecting

that higher effluent NO_2^- and NO_3^- correlate with increased N_2O flux as it represents an ineffective

denitrification process.

Optimization of process performance from the ML predictive outcome

i. Aerobic zone optimization

The process optimization approach entailed identifying operating ranges for SRT, which is the

principal process parameter coupled with process performance responses that concurrently minimize

off-gas N_2O fluxes, via PDP analysis. **Figure 4A** suggests that NH_3 concentrations < 3 mg L^{-1} at a

SRT < 10 days show less N_2O flux. To study the relationship between DO and NH_3, **Figure 4B**

suggests that operating conditions that achieve NH_3 concentrations < 3 mg L^{-1}, with DO < 3 mg L^{-1},

are effective in minimizing N_2O production. In contrast, operating conditions that foster concomitant

non-limiting DO and NH_3 concentrations, correspond to high N_2O fluxes **(Figure 4B).** Such

predictions are in excellent alignment with fundamental and mechanistic understanding of drivers for

N_2O emissions under aerobic conditions at WWTPs, via a combination of oxidative and reductive

pathways primarily in AOB[4–10,44–48].

ii.   Anoxic zone optimization

Similarly, conditions that minimize N_2O fluxes from anoxic zones included operation at DO

concentrations < 1 mg/L, however, coupled with a total process SRT < 20 days (**Figure 4C**). On the

other hand, N_2O flux increases when operated at DO concentration > 1 mg/L, under SRT < 20

days(**Figure 4C**). **Figure 4D** shows that when operated at DO concentrations > 1 mg/L, results in

NO_2^- accumulation in the anoxic zone, which subsequently increases N_2O flux. Higher DO and NO_2^-

concentrations promote high N_2O flux even under increased SRT. Also, we acknowledge that

operation at such high SRT values may be an option for some but not all WWTPs. Therefore,

understanding *process control vs process operation* in a dynamic environment is essential to mitigate

N_2O fluxes and improve reactor performance.

Discussion

Poor process operation leads to high N_2O emissions irrespective of process configuration and temperature variations.

Based on a combination of current measurements and extensive historic datasets, we determined that

less than optimal process operations can manifest themselves in combinations of both local and global

variables that in turn are correlated with higher N_2O production and emission across aerobic and

anoxic zones. Among the identified variables, SRT and DO emerged as the critical control factors

governing emissions. The key local and global variables identified from the unsupervised PCA

followed by supervised ML permutation feature importance and SHAP align well with the established

understanding of the nitrification and denitrification processes[4–7,29–31], thus providing consistent

insights into the contribution and significance linking to the process operation, N_2O emission, and

effluent water quality. The PDP analysis conducted for aerobic zones illustrates the relationship of

NH_3 concentration with key process control variables, DO and SRT, identifying the optimal operating

conditions for effective nitrification and reduced N_2O flux (**Figure 4A, B**). Similarly, in anoxic zones,

the PDP analysis highlights the interactions among DO, SRT, and NO_2^- pinpointing optimal

conditions to achieve effective denitrification and reduced N_2O emissions (**Figure 4C, D**). Thus, the

findings from ML-based analysis reveal the interplay between the operational variables and their

dynamic environment, that contribute to N_2O fluxes. Using interpretation tools, like PDP, coupled

with biochemical understanding, can provide real-time insights to optimize wastewater treatment

processes to minimize both *aqueous* and *gaseous* nitrogenous discharges.

Integration of real-time process control based on ML framework

This study demonstrates the immense potential of data-driven models for process control and

optimization. Upon further integrating such models into Supervisory Control And Data Acquisition

(SCADA) systems, they continuously process data generated from real-time or non-real-time

measurements, facilitating the development of digital twin architectures based on model-based

systems engineering (MBSE)[49]. Data-driven models can provide early fault detection, and advanced

process control capabilities, which mechanistic models typically cannot deliver using real-time data[49].

Indeed, previous studies have successfully applied data-driven approaches in real-time reactor

operations, enhancing reactor performance and effluent water quality [50–53]. The emphasis on data-

driven modeling for GHG emissions, particularly N_2O emissions, continues to expand, driven by

ongoing efforts to understand their process dynamics better and improve forecasting accuracy[27,40–43].

Our current work demonstrates the capabilities of ML models and their useful insights into the

dynamic interplay and link between process operations, N_2O emissions and effluent water quality.

The advanced interpretation tools, PDP, within the supervised ML models allows for better process

control setpoints and leverages the scope for digital and hybrid twin systems for optimized prediction

and management of WWTP operations.

Materials and Methods

Field Data Collection using an USEPA Approved Protocol to Measure N_2O Emissions from BNR Processes

The currently reported overall N_2O measurement campaign was performed at three different BNR

wastewater treatment plants around the US. **Table S3.** provides an overview of the sampling

techniques performed across both mainstream and sidestream WWTPs. The gaseous N_2O emission

concentrations from the BNR processes were quantified using an USEPA endorsed protocol[54]. The

Surface Emission Isolated Flux Chamber (SEIFC), the only floating body approved by the

Environmental Protection Agency (EPA) ($\Delta P=0$), has a circular cross-sectional area of 0.13 m^2 and

is used to measure gaseous nitrogen fluxes from activated sludge tanks[54,55]. The SEIFC consists of a

floating enclosed space through which exhaust gas were collected in real time fashion. The SEIFC

was employed to obtain headspace N_2O concentration(ppm) and fluxes at distinct locations (aerated

and nonaerated) in a treatment process. At each location, online measurements of gaseous N_2O

concentration and gas flow were conducted over a 24-hour period to address the diurnal variability

of gas emissions. The gaseous N_2O concentration was measured via infrared gas filter correlation

(Teledyne API, San Diego, California) at a frequency of 1/min. For emission measurements from the

closed-surface, sidestream SHARON process, the N_2O analyzer was directly connected to the off-gas

stacks. Mainstream N_2O measurements were conducted at both aerobic and anoxic zones in the target

WWTPs. Measurement campaigns in both mainstream and sidestream processes were conducted

over multiple days to determine the spatial and temporal variability. The use of GC-TCD in past

studies to measure the off-gas flow has provided valuable data at different WWTPs around US[4,55].

We used an anemometer (Hotwire thermo anemometer) to measure the air flow from the off-gas of

the flux chamber, which helps to identify the N_2O flux from the aerated and non-aerated zones without

requiring heavy-weight GC and other supplies. In other studies, a major drawback when monitoring

flux from the aerated and anoxic zone is to rely on the blower diffuser data and bulk airflow measured

in a vent from a closed tank[56]. In an aerobic zone, inconsistent blower supply due to aging

infrastructure and lack of continuous blower data limits flux measurements from the tank,

representing substantial spatial variable emissions. Anoxic zones do not have blower data, limiting

the ability to monitor and measure N_2O flux contribution from their AST systems.

Figure. S7 and supplementary section 7 explains the drawbacks of using blower data to measure

aerobic zone emissions and neglecting the anoxic zone, which can significantly eliminate the

consideration of N_2O contribution from the anoxic zone. We have also calculated the off-gas

estimations comparing blower and air flow data. **Figure. S8** represents the difference between air

flow and blower off-gas flow rates for every aerobic zone during our campaign in step-feed BNR

process. The results show that consideration of blower data can overestimate emission rates from

WWTPs. In addition to our comparative study on blower vs air flow data, we also identified the

optimum sweep air introduction to the flux chamber in the anoxic zone to quantify fluxes. **Figure.**

S9 discusses the introduction of sweep air into the flux chamber in an anoxic zone, where the optimum

sweep air introduction are determined based on the off-gas saturation flow rate and gaseous N_2O

dilution.

Concomitantly, during each monitoring campaign, wastewater nitrogen species

concentrations, including influent and effluent bioreactor samples were obtained using an

autosampler every 1 hour to measure NH_3, NO_2^-, and NO_3^- concentrations using Lachat Quickchem

Flow injection analysis system [57]. Activated sludge mixed-liquor temperature, pH, DO are acquired

from the SCADA system and soluble chemical oxygen (sCOD) and total chemical oxygen demand

(tCOD) were measured with Hach TNTplus kits and a Hach DR2800 spectrophotometer (HACH

Loveland, CO). Mixed-liquor suspended solids (MLSS) and volatile suspended solids (VSS)

concentrations were analyzed using Standard Methods 2504D and 2540E [57].

Bioreactor profile samples were collected from nitrifying and denitrifying tanks once a day to

measure NH_3, NO_2^-, and NO_3^- concentrations using Hach TNTplus kits and a Hach DR2800

spectrophotometer (HACH Loveland, CO). DO concentrations, temperature (°C), and pH were

measured using HACH handheld sensors (HACH Loveland, CO). Process air flow rate (standard

cubic feet per minute, SCFM), SRT, the surface area of the tanks (m^2) and influent flow rates (million

gallons per day, MGD) were obtained from the plant operation records.

The N_2O fluxes were calculated from both aerated and non-aerated zone using Eq.1 and the

emissions were calculated using Eq.2.

$$N_2O_{Flux}\left(\frac{g-N}{min-m^2}\right) = \left(\frac{(V_{air}*A_t*1000*60)+Q_{N2O\_inst}}{A_{SEIFC}(m^2)}\right) * C_{N_2O}\left(\frac{g-N}{L}\right) \qquad \textbf{Eq.1}$$

$$N_2O_{ER}\left(\frac{g-N}{d}\right) = N_2O_{Flux}\left(\frac{g-N}{min-m^2}\right) * A_{tank}(m^2) * 1440 \qquad \textbf{Eq.2}$$

$$EF\% = \frac{N_2O_{ER}\left(g-\frac{N}{d}\right)}{Influent\ TKN\ Load\left(g-\frac{N}{d}\right)} * 100 \qquad \textbf{Eq.3}$$

Where N_2O_{flux} is the measure of N_2O flux(g-N/min.m^2) from the activated sludge tank, V_{air} is

the air velocity (m.s^{-1}) measured in the anemometer from the SEIFC parallel to the N_2O concentration

measurements, A_t is the Area of the tube(m^2), Q_{N2O_inst} is the off-gas flow recorded on the N_2O

analyzer (L.min^{-1}) from the SEIFC, A_{SEIFC} is the area of the flux chamber (m^2) and C_{N2O} is the average

concentration of the gaseous N_2O concentration (g-N.L^{-1}). N_2O_{ER} is the N_2O emission rate (g-N/d)

from the overall tank, and A_{tank} is the area of the activated sludge tank (m^2). To determine the Emission

Factor (EF), the Q_{N2O} (N_2O emission rate (g-N/d)) was normalized to the influent Total Kjeldahl

Nitrogen (TKN) (g-N/d) load using Eq.3.

Data Preprocessing for Calculating EF and Implementing unsupervised PCA analysis

The measured data were grouped into zone-specific aerobic and anoxic zone measurements, which were then used to calculate N_2O emission rates and EF across the system **(Figure 2A)**. The dataset throughout this study are expressed to two significant figures. Furthermore, past and present datasets were processed to identify missing and non-numeric values before initiating the analysis in machine learning algorithms. The missing values were filled with "*missForest,*" a package in the R studio that successfully handles the missing values for different variables, even under non-linear relations[58].

To perform the unsupervised PCA analysis, processed datasets are arranged according to aerobic and anoxic zone conditions. We used "*prcomp*" package with "*factoextra*" visualization packages in R studio to advance the PCA visualization. For Pearson correlation, "*corrplot*" and "*ggcorrplot*" packages were used to develop the correlation heatmap.

Supervised Machine Learning Approach to Predict N_2O Fluxes from Different Operating Conditions

To develop the supervised ML models, the datasets were log-transformed and min-max normalized [0,1]. **Figure S10** provides the graphical representation of the preprocessed dataset in a boxplot for both aerobic and anoxic datasets. The pre-processed dataset were randomly split into 75% for training and 25% for testing. The dataset split for the training data were divided into k-fold cross-validation (cv) splits to optimize the model hyperparameters effectively. Outlier detection was performed to understand the data sets variability for all the independent variables associated with N_2O fluxes.

Supervised ML comprising an ensemble based on decision trees were employed. They are Random Forest, Gradient Boosting, and Xtreme Gradient Boost. The model hyperparameter tuning of the selected models was optimized using a grid search algorithm. The grid search explores a pre-define space of parameters to find the set of values that maximizes the model mean performance on the k-

fold CV subsets. The hyperparameters and optimized hyperparameter values for each model are

provided in **Supplementary Section 4.** All the model evaluations are implemented in R-studio.

Model evaluation and comparison

The model accuracy with N_2O flux estimates was evaluated in both statistical metrics and dynamic

process evaluations. **Table S2** shows regression-based metrics, including the coefficients of

determination (R^2), which are used to estimate the proportion of the variance the model explains.

Mean Square Error (MSE) and Root Mean Square Error (RMSE) were also employed to understand

the magnitude of errors that occur across different ranges of N_2O flux prediction for both aerobic and

anoxic prediction. This provides detailed residual analysis to provide deeper insight into the model

performance and detect potential areas of improvement.

Tools utilized for N_2O flux prediction from machine learning models

We employed SHAP and PDP analyses to interpret the ML model predictions and to investigate the

directionality and relative influence of process variables on the predicted N_2O flux. For this purpose,

we used the *iml* package to perform model-agnostic interpretation, *pdp* to generate partial dependence

plots, *ggbeeswarm* to create beeswarm plots for visualizing SHAP values, and *shapviz* for efficient

and scalable SHAP-based visualizations. The *viridis* package was used to apply perceptually uniform,

colorblind-friendly palettes, and *plotly* was utilized to develop interactive visualizations of SHAP and

PDP outputs.

References

1. Ravishankara, A. R., Daniel, J. S. & Portmann, R. W. Nitrous Oxide (N$_2$0): The Dominant Ozone-Depleting Substance Emitted in the 21st Century. *Science* **326**, 123–125 (2009).

2. Stocker, T. *Climate Change 2013: The Physical Science Basis: Working Group I Contribution to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change*. (Cambridge University Press, 2014).

3. 2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories — IPCC. https://www.ipcc.ch/report/2019-refinement-to-the-2006-ipcc-guidelines-for-national-greenhouse-gas-inventories/.

4. Ahn, J. H. *et al.* N2O emissions from activated sludge processes, 2008-2009: Results of a national monitoring survey in the united states. *Environmental Science and Technology* **44**, 4505–4511 (2010).

5. Rassamee, V., Sattayatewa, C., Pagilla, K. & Chandran, K. Effect of oxic and anoxic conditions on nitrous oxide emissions from nitrification and denitrification processes. *Biotechnology and Bioengineering* **108**, 2036–2045 (2011).

6. Yu, R., Kampschreur, M. J., Loosdrecht, M. C. M. van & Chandran, K. Mechanisms and Specific Directionality of Autotrophic Nitrous Oxide and Nitric Oxide Generation during Transient Anoxia. *Environ. Sci. Technol.* **44**, 1313–1319 (2010).

7. Brotto, A. C. *et al.* Characterization and mitigation of nitrous oxide (N2O) emissions from partial and full-nitrification BNR processes based on post-anoxic aeration control. *Biotechnology and Bioengineering* **112**, 2241–2247 (2015).

8. Kampschreur, M. J., Temmink, H., Kleerebezem, R., Jetten, M. S. M. & van Loosdrecht, M. C. M. Nitrous oxide emission during wastewater treatment. *Water Research* **43**, 4093–4103 (2009).

9. Grady, C. P. L. *Biological Wastewater Treatment*. (New York : Marcel Dekker, 1999).

10. Chandran, K., Stein, L. Y., Klotz, M. G. & Van Loosdrecht, M. C. M. Nitrous oxide production

by lithotrophic ammonia-oxidizing bacteria and implications for engineered nitrogen-removal

systems. *Biochemical Society Transactions* **39**, 1832–1837 (2011).

11. Zumft, W. G. Cell biology and molecular basis of denitrification. *Microbiol Mol Biol Rev* **61**,

533–616 (1997).

12. Kester, R. A., De Boer, W. & Laanbroek, H. J. Production of NO and N(inf2)O by Pure Cultures

of Nitrifying and Denitrifying Bacteria during Changes in Aeration. *Appl Environ Microbiol* **63**,

3872–3877 (1997).

13. Ritchie, G. A. & Nicholas, D. J. Identification of the sources of nitrous oxide produced by

oxidative and reductive processes in Nitrosomonas europaea. *Biochem J* **126**, 1181–1191

(1972).

14. Stüven, R., Vollmer, M. & Bock, E. The impact of organic matter on nitric oxide formation by

Nitrosomonas europaea. *Arch. Microbiol.* **158**, 439–443 (1992).

15. Yu, R., Perez-Garcia, O., Lu, H. & Chandran, K. *Nitrosomonas europaea* adaptation to anoxic-

oxic cycling: Insights from transcription analysis, proteomics and metabolic network modeling.

Science of The Total Environment **615**, 1566–1573 (2018).

16. Schreiber, F., Wunderlin, P., Udert, K. M. & Wells, G. F. Nitric oxide and nitrous oxide turnover

in natural and engineered microbial communities: biological pathways, chemical reactions, and

novel technologies. *Front Microbiol* **3**, 372 (2012).

17. Wunderlin, P., Mohn, J., Joss, A., Emmenegger, L. & Siegrist, H. Mechanisms of N2O

production in biological wastewater treatment under nitrifying and denitrifying conditions.

Water Research **46**, 1027–1037 (2012).

18. Lu, H. & Chandran, K. Factors promoting emissions of nitrous oxide and nitric oxide from

denitrifying sequencing batch reactors operated with methanol and ethanol as electron donors.

Biotechnology and Bioengineering **106**, 390–398 (2010).

19. US EPA, O. Effluent Guidelines. https://www.epa.gov/eg (2014).

20. Daelman, M. R. J., van Voorthuizen, E. M., van Dongen, U. G. J. M., Volcke, E. I. P. & van

Loosdrecht, M. C. M. Seasonal and diurnal variability of N2O emissions from a full-scale

municipal wastewater treatment plant. *Science of the Total Environment* **536**, 1–11 (2015).

21. Gernaey, K. V., van Loosdrecht, M. C. M., Henze, M., Lind, M. & Jørgensen, S. B. Activated

sludge wastewater treatment plant modelling and simulation: state of the art. *Environmental*

Modelling & Software **19**, 763–783 (2004).

22. Perez-Garcia, O., Mankelow, C., Chandran, K., Villas-Boas, S. G. & Singhal, N. Modulation of

Nitrous Oxide (N2O) Accumulation by Primary Metabolites in Denitrifying Cultures Adapting

to Changes in Environmental C and N. *Environ. Sci. Technol.* **51**, 13678–13688 (2017).

23. Frontiers | Metabolic Network Modeling of Microbial Interactions in Natural and Engineered

Environmental Systems.

https://www.frontiersin.org/journals/microbiology/articles/10.3389/fmicb.2016.00673/full.

24. Perez-Garcia, O., Chandran, K., Villas-Boas, S. G. & Singhal, N. Assessment of nitric oxide

(NO) redox reactions contribution to nitrous oxide (N2O) formation during nitrification using a

multispecies metabolic network model. *Biotechnology and Bioengineering* **113**, 1124–1136

(2016).

25. Perez-Garcia, O., Villas-Boas, S. G., Swift, S., Chandran, K. & Singhal, N. Clarifying the

regulation of NO/N2O production in *Nitrosomonas europaea* during anoxic–oxic transition via

flux balance analysis of a metabolic network model. *Water Research* **60**, 267–277 (2014).

26. Behera, C. R., Srinivasan, B., Chandran, K. & Venkatasubramanian, V. Model based predictive

control for energy efficient biological nitrification process with minimal nitrous oxide

production. *Chemical Engineering Journal* **268**, 300–310 (2015).

27. Khalil, M., AlSayed, A., Liu, Y. & Vanrolleghem, P. A. Machine learning for modeling N2O

emissions from wastewater treatment plants: Aligning model performance, complexity, and

interpretability. *Water Research* **245**, 120667 (2023).

28. Bellandi, G., Weijers, S., Gori, R. & Nopens, I. Towards an online mitigation strategy for N2O

emissions through principal components analysis and clustering techniques. *J Environ Manage*

261, 110219 (2020).

29. Villez, K. *et al.* Combining multiway principal component analysis (MPCA) and clustering for

efficient data mining of historical data sets of SBR processes. *Water Sci Technol* **57**, 1659–1666

(2008).

30. Sobczyk, M., Pajdak-Stós, A., Fiałkowska, E., Sobczyk, Ł. & Fyda, J. Multivariate analysis of

activated sludge community in full-scale wastewater treatment plants. *Environ Sci Pollut Res*

28, 3579–3589 (2021).

31. Cui, F. *et al.* Application of principal component analysis (PCA) to the assessment of parameter

correlations in the partial-nitrification process using aerobic granular sludge. *Journal of*

Environmental Management **288**, 112408 (2021).

32. Çimen Mesutoğlu, Ö. & Gök, O. Prediction of COD in industrial wastewater treatment plant

using an artificial neural network. *Sci Rep* **14**, 13750 (2024).

33. Liu, T., Zhang, H., Wu, J., Liu, W. & Fang, Y. Wastewater treatment process enhancement based

on multi-objective optimization and interpretable machine learning. *Journal of Environmental*

Management **364**, 121430 (2024).

34. Mathur, R. *et al.* Modeling of two-stage anaerobic onsite wastewater sanitation system to

predict effluent soluble chemical oxygen demand through machine learning. *Sci Rep* **14**, 1835

(2024).

35. Zhang, Y. *et al.* Machine learning modeling for the prediction of phosphorus and nitrogen

removal efficiency and screening of crucial microorganisms in wastewater treatment plants.

Science of The Total Environment **907**, 167730 (2024).

36. Sheik, A. G. *et al.* Prediction of wastewater quality parameters using adaptive and machine

learning models: A South African case study. *Journal of Water Process Engineering* **67**, 106185

(2024).

37. Szeląg, B., Zaborowska, E. & Mąkinia, J. An algorithm for selecting a machine learning method

for predicting nitrous oxide emissions in municipal wastewater treatment plants. *Journal of*

Water Process Engineering **54**, 103939 (2023).

38. Yaqub, M., Asif, H., Kim, S. & Lee, W. Modeling of a full-scale sewage treatment plant to

predict the nutrient removal efficiency using a long short-term memory (LSTM) neural

network. *Journal of Water Process Engineering* **37**, 101388 (2020).

39. Hu, J., Yin, R., Wang, J. & Ren, H. Data driven multiple objective optimization of AAO process

towards wastewater effluent biological toxicity reduction. *npj Clean Water* **7**, 1–11 (2024).

40. Seshan, S., Poinapen, J., Zandvoort, M. H., van Lier, J. B. & Kapelan, Z. Forecasting nitrous

oxide emissions from a full-scale wastewater treatment plant using LSTM-based deep learning

models. *Water Research* **268**, 122754 (2025).

41. Xu, X. *et al.* Prediction of nitrous oxide emission of a municipal wastewater treatment plant

using LSTM-based deep learning models. *Environ Sci Pollut Res* **31**, 2167–2186 (2024).

42. Li, K. *et al.* An Integrated First Principal and Deep Learning Approach for Modeling Nitrous

Oxide Emissions from Wastewater Treatment Plants. *Environmental Science and Technology*

56, 2816–2826 (2022).

43. Khalil, M., AlSayed, A., Liu, Y. & Vanrolleghem, P. A. An integrated feature selection and

hyperparameter optimization algorithm for balanced machine learning models predicting N2O

emissions from wastewater treatment plants. *Journal of Water Process Engineering* **63**, 105512 (2024).

44. Ahn, J. H., Kwan, T. & Chandran, K. Comparison of Partial and Full Nitrification Processes Applied for Treating High-Strength Nitrogen Wastewaters: Microbial Ecology through Nitrous Oxide Production. *Environ. Sci. Technol.* **45**, 2734–2740 (2011).

45. Kim, Y. M., Park, H. & Chandran, K. Nitrification inhibition by hexavalent chromium Cr(VI)-- Microbial ecology, gene expression and off-gas emissions. *Water Res* **92**, 254–261 (2016).

46. Brotto, A. C., Annavajhala, M. K. & Chandran, K. Metatranscriptomic Investigation of Adaptation in NO and N2O Production From a Lab-Scale Nitrification Process Upon Repeated Exposure to Anoxic–Aerobic Cycling. *Front Microbiol* **9**, 3012 (2018).

47. Li, B. & Wu, G. Effects of Sludge Retention Times on Nutrient Removal and Nitrous Oxide Emission in Biological Nutrient Removal Processes. *Int J Environ Res Public Health* **11**, 3553–3569 (2014).

48. Brotto, A. C. *et al.* Factors controlling nitrous oxide emissions from a full-scale activated sludge system in the tropics. *Environ Sci Pollut Res* **22**, 11840–11849 (2015).

49. Wang, A.-J. *et al.* Digital Twins for Wastewater Treatment: A Technical Review. *Engineering* **36**, 21–35 (2024).

50. Zhou, J. *et al.* Sub-period division strategies combined with multiway principle component analysis for fault diagnosis on sequence batch reactor of wastewater treatment process in paper mill. *Process Safety and Environmental Protection* **146**, 9–19 (2021).

51. AL-Kordy, S. U. & Khudair, D. B. H. Effluent quality assessment of sewage treatment plant using principal component analysis and cluster analysis. *Journal of Engineering* **27**, 79–95 (2021).

52. Liu, H., Yang, J., Zhang, Y. & Yang, C. Monitoring of wastewater treatment processes using

dynamic concurrent kernel partial least squares. *Process Safety and Environmental Protection*

147, 274–282 (2021).

53. Yang, C., Zhang, Y., Huang, M. & Liu, H. Adaptive dynamic prediction of effluent quality in

wastewater treatment processes using partial least squares embedded with relevance vector

machine. *Journal of Cleaner Production* **314**, 128076 (2021).

54. Chandran, K., Pagilla, K. & Katehis, D. Field Protocol With Quality Assurance Plan -

Characterization of Nitrogen Greenhouse Gas Emissions From Wastewater Treatment Bnr

Operations. 1–47 (2009).

55. Chandran, K. *Protocol for the Measurement of Nitrous Oxide Fluxes from Biological*

Wastewater Treatment Plants. *Methods in Enzymology* vol. 486 (Elsevier Inc., 2011).

56. Gruber, W. *et al.* Estimation of countrywide N2O emissions from wastewater treatment in

Switzerland using long-term monitoring data. *Water Research X* **13**, (2021).

57. Andrew D. Eaton, American Water Works Association, Water Environment Federation.

Standard Methods for the Examination of Water and Wastewater. (APHA-AWWA-WEF,

Washington, D.C., 2005).

58. Stekhoven, D. J. & Bühlmann, P. MissForest—non-parametric missing value imputation for

mixed-type data. *Bioinformatics* **28**, 112–118 (2012).

Tables and Figures

Table 1. Summary of N$_2$O emission fraction at a mainstream and sidestream process configuration in a Full-Scale BNR WWTPs

Plant configuration		Temp (ºC)	Q (MGD)	Influent TKN load (g-N/day)	Removed TN load (g-N/day)	% Nitrogen removed	% influent TKN emitted as N$_2$O (EF)	Reference
Step feed BNR		18±3	21	1.6E+06	1.0E+06	62±21	0.20±0.03	This study
		23±3	23	1.6E+06	8.5E+05	56±16	0.03±0.006	
PdNA		18±1.7	15	1.8E+06	1.2E+06	68±7	0.006±0.00	
		25±2.8	12	2.1E+06	1.7E+06	77±8	0.005±0.00	
ABAC		26±2.2	23	1.4E+06	NA	NA	0.004±0.00	
Fermentate-fed partial denitratation		25±0.7	2.0	4.7E+01	3.3E+01	71±20	0.003±0.00	
SHARON	Train 1	30±0.56	1.0	2.5E+06	9.5E+05	36±17	6.3±1.8	
	Train 2		0.79	2.0E+06	7.0E+05	38±16	14±2.0	
Separate-stage BNR		15±0.48	23	1.8E+06	3.6E+05	20±1	0.03±0.00	Ahn.et al[4]
		23±0.28	27	2.3E+06	4.3E+05	19±4	0.01±0.00	
Four-stage Bardenpho		14±0.26	7.8	8.6E+05	1.7E+05	20±1	0.16±0.10	
		23±0.20	8.1	7.4E+05	7.6E+04	10±4	0.60±0.29	
Step-feed BNR 1		19±0.22	29	3.1E+06	1.4E+06	45±8	1.6±0.83	
		25±0.28	30	2.9E+06	9.4E+05	32±10	0.62±0.27	
Step-feed non-BNR		17±0.12	71	8.6E+06	4.4E+06	51	0.18±0.18	
		26±0.81	93	8.9E+06	4.2E+06	47	1.8±0.79	
Separate centrate		30±2.3	2.0	8.8E+06	5.5E+06	63	0.24±0.02	
		34±0.32	1.6	8.5E+06	4.2E+06	49	0.54±0.16	
Plug-flow 1		11±0.20	18	1.8E+06	1.0E+06	56	0.40±0.14	
		23±0.46	15	1.8E+06	7.3E+05	41	0.41±0.14	
Plug-flow 2		11±0.41	8.7	6.3E+05	4.0E+05	63	0.62±0.15	
		22±0.58	6.6	6.6E+05	4.0E+05	61	0.09±0.03	
MLE 1		26±1.8	4.0	6.8E+05	1.9E+05	28	0.07±0.04	
MLE 2		26±0.17	4.1	6.9E+05	1.5E+05	22	0.06±0.02	
Step-feed BNR 2		29±0.18	14	2.2E+06	2.9E+05	13	1.5±0.02	
Oxidation ditch		19±0.58	3.4	3.9E+05	4.3E+04	11±1	0.03±0.01	
Step-feed BNR 3		24±0.78	57	7.8E+06	8.6E+05	11±2	0.05±0.03	

Legend of Figures

Figure 1. PCA analysis on N$_2$O flux and wastewater quality parameters. A,B, N$_2$O flux (g-N d^{-1}-m^2) and their multivariate relationship between local and global variables in aerobic **(A)** and anoxic **(B)** zones.

Figure 2. Data collection and processing in ML with permutation importance score from the XG Boost algorithm. A, pipeline representing quantifying real-time N$_2$O emission data, N-profile and plant operational data, integrated into ML models provides mitigation strategies to reduce N$_2$O emissions along with clean water and better sanitation system. **B,C,** permutation importance and their contributing towards predicted N$_2$O flux in aerobic **(B)** and anoxic **(C)** zone

Figure 3. The Beeswarm SHAP analysis of predicted N$_2$O flux with wastewater parameters. A,B, Magnitudina and directionality insights from ML interpretable SHAP across both local and global variables in aerobic **(A)** and anoxic **(B)** zones predicted N$_2$O flux

Figure 4. 2D PDP on predicted N$_2$O flux with selective key features. Predicted N$_2$O flux and its dynamic relationship towards key process variables in PDP, across aerobic **(A,B)** and anoxic **(C,D)** zones. **(A)** predicted N$_2$O flux with NH$_3$ and SRT, **(B)** predicted N$_2$O flux with NH$_3$ and DO, **(C)** predicted N$_2$O flux with DO and SRT, **(D)** predicted N$_2$O flux with DO and NO$_2^-$

Figure 1. PCA analysis on N₂O flux and wastewater quality parameters. A,B, N_2O flux (g-N d^{-1}-m^2) and their multivariate relationship between local and global variables in aerobic **(A)** and anoxic **(B)** zones.

Figure 2. Data collection and processing in ML with permutation importance score from the XG Boost algorithm. A, pipeline representing quantifying real-time N_2O emission data, N-profile and plant operational data, integrated into ML models provides mitigation strategies to reduce N_2O emissions along with clean water and better sanitation system. **B,C,** permutation importance and their contributing towards N_2O flux in aerobic **(B)** and anoxic **(C)** zone

Figure 3. The Beeswarm SHAP analysis of predicted N₂O flux with wastewater parameters.
A,B, Magnitudinal and directionality insights from ML interpretable SHAP across both local and global variables in aerobic **(A)** and anoxic **(B)** zones predicted N₂O flux .

Figure 4. 2D PDP on predicted N₂O flux with selective key features. Predicted N₂O flux and its dynamic relationship towards key process variables in PDP, across aerobic **(A,B)** and anoxic **(C,D)** zones. **(A)** predicted N₂O flux with NH₃ and SRT, **(B)** predicted N₂O flux with NH₃ and DO, **(C)** predicted N₂O flux with DO and SRT, **(D)** predicted N₂O flux with DO and NO₂⁻