Dorsomedial Prefrontal Cortex links abstract planning to motor execution

Ricardo J. Alejandro[*], Iris Ikink, Emmanouela Foinikianaki, Clay B. Holroyd

Department of Experimental Psychology, Ghent University, Ghent, Belgium

*Corresponding author: rjalejandrob@gmail.com

ABSTRACT

Mental planning is essential for producing action sequences. Despite the contribution of planning to many everyday activities, the neurocognitive processes that map a selected plan into a concrete course of action are unclear. We asked whether planning and execution are linked by abstract task relationships that are divorced from the specifics of action implementation. Human participants underwent functional MRI while performing a task that required encoding and maintaining abstract representations in order to plan and later apply those representations to execute action sequences. Our analyses revealed that dorsomedial prefrontal cortex encoded representations during the planning period that shifted progressively from information based on perceptual input to information associated with the abstract task context. These abstract representations were then used to translate between the action plan and its execution irrespective of the perceptual and motor details, indicating that DMPFC builds and sustains an abstract representational bridge that links planning to action.

INTRODUCTION

Mental planning is a powerful neurocognitive mechanism that enables flexible production of action sequences. For instance, imagine a driver encountering a traffic sign that indicates that a roundabout is close ahead, requiring them to examine the sign quickly to determine and plan the appropriate exit (Figure 1A, left). This complex planning process entails retrieving task-relevant information from memory, associating these concepts within the current task context, simulating possible behaviors, and predicting and evaluating their outcomes in terms of the task goals and subgoals, all of which often happen without the benefit of external guidance or cues (for example, because the traffic sign has already been passed). Moreover, once a plan is selected (such as taking the fifth exit; Figure 1A, left), this information needs to be maintained until the actual roundabout is reached and the planned sequence of actions executed. The implementation of the plan requires mapping it into a concrete course of action, all the while monitoring action execution for any deviations from the intended goals and unforeseen environmental constraints (such as encountering a roundabout with an unusual shape; Figure 1A, right). Planning is thus essential for many everyday behaviors (Rowe et al., 2001). Yet despite their importance, the cognitive and neural operations that link and translate planning to execution are largely unknown.

Several neuroimaging studies have examined neural activity occurring during a delay or planning period between an instruction cue and its designated response (J. D. Cohen et al., 1997; Curtis & D'Esposito, 2003; Fuster & Alexander, 1971; Kubota & Niki, 1971). However, these experimental paradigms have mostly related the planning phase to a prospective motor action such as a button press, hand movement, or eye saccade. Consequently, many of these studies reported a mixture of signals related to cognitive control, action and motor preparation that are related but not specific to planning, across a distributed network of brain regions including dorsolateral-, ventrolateral-, and dorsomedial prefrontal cortex (DLPFC, VLPFC, DMPFC, respectively), anterior cingulate cortex (ACC), posterior parietal cortex (PPC), basal ganglia, cerebellum, insular cortex, and motor and pre-motor regions (Balaguer et al., 2016; Crescentini et al., 2012; Elsinger et al., 2006; Gallivan et al., 2011; Hanakawa et al., 2008, 2008; Henderson et al., 2022; Hoshi & Tanji, 2004; Ito, 2008; Koechlin et al., 2000; Lazeron et al., 2000; Liang et al., 2022; Momennejad & Haynes, 2012, 2013; Rousseau et al., 2021; Ruge et al., 2010; Tanaka et al., 2021; Tosoni et al., 2014; Van Den Heuvel et al., 2003; Wagner et al., 2006; Yewbrey et al., 2023). Conversely, the execution period in these studies often reveals a combination of brain areas involved in motor and cognitive control, including DLPFC, DMPFC, PPC, cerebellum, and basal ganglia (Brandi et al., 2014; Crescentini et al., 2012; Hanakawa et al., 2008; Papitto et al., 2024; Turella et al., 2020; Unterrainer & Owen, 2006).

The wide variety of brain regions highlights the fact that multiple cognitive processes related to perception, cognitive control, memory, and motor control work in parallel both when planning and when implementing planned behaviors as specific actions (Elsinger et al., 2006). This ubiquity of signals complicates identifying the specific contribution of each region to each of these processes (Rowe et al., 2001). Moreover, considering the reciprocal relationship between planning and execution, it has been noted that these are not truly separate processes (Cisek & Kalaska, 2010;

Coles et al., 1985; Hommel et al., 2001). Rather, it has been proposed that planning evokes a latent,

coarse representation of the action plan that is maintained in an active state until the actions are

completed, in order to monitor the execution of the plan and intervene as needed (Konidaris et al.,

2018). On this view, this representation would intermediate between developing a plan and

implementing it, utilizing a language that is common to both task phases and supersedes their

differences. Such a high-level, abstract representation would provide the flexibility needed to map

internal models to concrete courses of action while adapting the execution of the plan to external

perturbations and behavioral errors.

Extending this proposal, we suggest that this superordinate process, which encodes task-relevant

information at an abstract level as a bridge between plans and actions, does so specifically by

harnessing learned representations that generalize over extensive repertoires of tasks and task

requirements (i.e., goals and constraints). Notably, the behaviors that compose a task can be

organized into hierarchical structures that facilitate goal-directed behavior (Botvinick, 2008; Colin et

al., 2025; Correa et al., 2023; Tomov et al., 2020; Wientjes & Holroyd, 2024), such that higher-order

task goals and concepts modulate subordinate subgoals and explicit actions (G. A. Miller et al., 1960).

Such hierarchical representations allow for existing knowledge and task properties to be generalized

to new tasks (or new instances of known tasks) (Hall-McMaster et al., 2025; Lee et al., 2022, 2024;

Sheahan et al., 2021; Skorstad et al., 1988; Theves et al., 2021). For instance, when learning to play

the piano, a skilled guitarist does not relearn all of musical theory from scratch, but instead utilizes

task-related abstractions such as notes and musical chords to integrate the commonalities across

instruments (Collins & Frank, 2013; Garvert et al., 2017; Huang & Luo, 2024; Reverberi et al., 2012;

Theves, 2025; Xia & Collins, 2021). These higher-order representations enable mappings between

action sequences across different domains of feature perception and motor execution (Figure 1A).

Consistent with this possibility, neuroimaging evidence has revealed that hierarchically-organized

plans are represented in the brain at different levels of abstraction in orbitofrontal cortex (OFC), ACC,

DLPFC, DMPFC, and hippocampus (HPC) (Balaguer et al., 2016; Brunec & Momennejad, 2022;

Grossman et al., 2025; Liang et al., 2022). However, whether these areas link plans to action

execution utilizing such a hierarchical encoding scheme is not clear.

Here, we identify brain areas that encode hierarchical representations for abstract planning and action

execution. While undergoing functional magnetic resonance imaging (fMRI), participants were

required to encode and maintain abstract representations of an upcoming action sequence and later

apply those representations to execute said sequences. Crucially, this abstract context was

independent of the visual stimuli and the motor actions used in the task. Following a pre-registered

protocol, we trained a classifier on the multivariate fMRI activity during the planning period to

discriminate different plans for sequence implementation and then tested the classifier on the activity

during the execution period. A searchlight application of this approach identified brain areas sensitive

to the high-level task context that generalized over the low-level implementational details of the task.

Additionally, to identify brain areas supporting abstract vs. perceptual aspects of planning, we

assessed the representational similarity of brain activations with respect to two possible

representational formats: abstract representations that relate different stimuli according to the task

context, and perceptual representations that relate stimuli according to their shared visual features.

These analyses converged in identifying a cluster of activity overlapping DMPFC and dorsal ACC

(hereafter, simply DMPFC), which suggests that this brain region maintains abstract, higher-order task

representations during planning that are then used to implement the plans during their execution. In

contrast, low-level visual representations related to stimulus identity were identified in visual cortex, as

expected. Lastly, an exploratory analysis revealed that as the planning interval progressed, the

representation during the planning period shifted from a perceptually-based format to a more abstract

format.

RESULTS

Experimental task

Fifty participants took part in the experiment, which consisted of a main task (Figure 1B) and two

functional localizer tasks (Figure 1C), while they underwent fMRI scanning. Participants were trained

online beforehand during a separate session (see Methods) on task rules that required mapping

colored geometric shapes into specific codes (sequence combinations of the characters "#" and "&").

On each trial of the fMRI main task (Figure 1B), the participants were shown a set of two colored

geometric shapes (red and blue squares and triangles, and green and yellow diamonds and circles;

Figure 1D) during a stimulus phase (blue highlight in Figure 1B), followed by a planning phase

(orange highlight in Figure 1B) that required the participants to internally translate the observed

sequence of colored shape stimuli into the corresponding sequential code (Figure 1E). After the

planning phase, participants were shown an input field, images of two buttons labelled with the

characters "#" and "&" (the relative positions of which varied at random from trial to trial), and the

instruction "enter code" (execution phase, green highlight in Figure 1B). They were then required to

type the corresponding (planned) 4-character code sequence as instructed on that trial (Figure 1B, D).

Figure 1. Study conceptualization and experimental paradigm(s). A. Illustration of the abstract link between planning and execution. A driver needs to go to City E; therefore when encountering the traffic sign, they determine that the fifth exit needs to be taken. This information must be maintained until the plan is executed because the sign has been passed and will no longer be available as a cue. Once the roundabout is reached, its physical layout might be as expected (execution, top) or not (execution, bottom), hence the plan must be encoded in a flexible format that is independent of the

specific details of its execution. **B.** Main task paradigm. On each trial an abstract set of visual symbols

("stimuli", blue shading) instructed participants to map the stimuli to the corresponding codes

(predefined sequences of the characters "#" and "&") during a planning phase ("planning", orange

shading) and subsequently type the corresponding sequence into a password prompt ("execution",

green shading). **C.** Following the main task, participants completed two functional localizer tasks

(shape and code localizer). Top: functional "shape" localizer. Participants were presented with colored

geometric shapes (stimuli, blue shade; same combinations as in the main task), which were instructed

to be remembered during a subsequent planning phase (planning, orange shade), after which another

set of colored geometric shapes were presented that either were or were not the same as the initial

set during the trial, together with the question "same?" (execution, green shade). Participants were

required to respond by selecting "yes" to indicate that the second set was exactly the same across all

stimulus dimensions (i.e., same shapes, same colors, and same positions) as the initial set, or "no" to

indicate that they were not the same in one or more of the stimulus dimensions. This localizer was

designed to capture perceptual processing elements related to the main task (see Methods). Bottom:

functional "code" localizer. Participants were shown an abstract code (stimuli, blue shade; same

combinations of "&" and "#" as in the main task) that they were required to remember during a

planning phase (planning, orange shade), after which they were prompted with a screen to execute

the abstract code (execution, green shade). This localizer was designed to capture abstract

processing elements related to the main task (see Methods). **D.** Visual stimuli and their corresponding

abstract codes. Each geometric shape was represented by a 2-character code that was mapped to its

shape (first character) and color (second character) following specific constraints. Squares and

diamonds corresponded to "#", and triangles and circles corresponded to "&". Squares and triangles

could be blue ("#") or red ("&"), and circles and diamonds could be green ("#") or yellow ("&"). **E.** On

each trial, participants were required to execute 2-stimulus sequences of 4 button presses. To

increase the amount of observations per condition, the majority of codes presented during the tasks

(~82% during the main task, ~88% during the localizer tasks) were c1: "#&&#" and c2: "&##&"

(standard trials, see Methods), which included two 2 shape-pairs per code (c1 represented by c1s1:

"red square + blue triangle" or c1s2: "yellow diamond + green circle", c2 represented by c2s1: "blue

triangle + red square" or c2s2: "green circle + yellow diamond". Our analyses focused on these

"standard" trials only. During the tasks, standard trials were intermixed with catch trials that were

constructed from all of the remaining valid combinations of stimuli, comprising ~18% of the main task

trials and ~12% of the localizer tasks trials (see Methods and Table S1).

Behavioral results

RT signature of chunking and benefit of planning

Because each trial required executing a four-step sequence of button presses according to each

shape's two-button sequence, we predicted that participants would encode this information

hierarchically by consolidating the four-step code into two independent two-step subsequence codes

(or "chunks"). To test this prediction, reaction times (RTs) to the four individual actions were compared

both within-subsequence, where we predicted that the first action within each subsequence would be
slower than the second (RT1 > RT2, and RT3 > RT4), and between-subsequences, where we
predicted that the transition between subsequences would result in the third action to be slower than
the second action (RT3 > RT2) (Eckstein & Collins, 2021; Rosenbaum et al., 1983; Verwey, 1996).
Additionally, evidence of planning can be seen in shorter RTs after longer planning periods (Afshar et
al., 2011; Rosenbaum, 1980). We therefore predicted that the first step of the entire sequence (RT1)
would be faster with increasing time for planning (namely, for planning periods of 4.5 s, 6 s, and 7.5 s;
see Figure 1B and Method details).

We fitted RT data with a linear mixed-effects model (LMM) that included sequence step (1, 2, 3, 4),
and planning duration (short, medium, long, given by the jittered duration of the planning phase; see
Method details) as fixed effects, as well as their interactions, and random intercepts per participant.
The linear mixed-effects model revealed significant main effects of sequence step ($F_{(3, 32907)}$ =
1418.81, $p < 0.0001$) and planning duration ($F_{(2, 32908)}$ = 1.47, $p < 0.0001$), and a significant
interaction between sequence step and planning duration ($F_{(6, 32907)}$ = 6.51, $p < 0.0001$).
Subsequent post-hoc pairwise comparisons (using Tukey's HSD) estimated the direction of the main
effects and their interaction. As shown in Figure 2A, RT1 was significantly higher than RT2 ($p <$
0.0001), and RT3 was significantly higher than RT4 ($p < 0.0001$). However, the difference between
RT2 and RT3 was not statistically significant ($p = 0.258$). We supposed that the lack of the expected
effect of hierarchical chunking (i.e., a slow-down when transitioning subsequences) could have
resulted from the participants' repeated exposure to the task both during their online behavioral
training (see Methods) and during the fMRI session itself, thereby attenuating the effect. In fact, an
analysis of the RT data from the online behavioral training revealed the predicted signature of
hierarchical chunking (RT2 < RT3; $p < 0.0001$) (Figure S1), in addition to replicating the significant
effects observed in the main fMRI task (RT1 > RT2, $p < 0.0001$); and RT3 > RT4, $p < 0.0001$).

232
Figure 2. Behavioral Results. A. Reaction time (RT) per sequence step and post-hoc pairwise
comparisons following the main effect of sequence step on RT. Bold black line represents the average
RT across participants, gray lines represent individual participants. Asterisks denote statistical
significance at $p < 0.0001$; n.s.: non-significant. **B.** Task accuracy per block; there were no significant
differences across blocks ($\chi^2(3) = 3.99$, $p = 0.262$). Error bars denote the standard error of the mean
(SEM) across participants.

Further, the main effect of plan duration was driven by significant differences between long and
medium (7.5 vs 6 s., p = 0.0008), long and short (7.5 vs 4.5 s., p < 0.0001), and medium and short (5
vs 4.5 s., p < 0.0001) planning durations, suggesting that the speed of sequence execution was
influenced by the length of preparation time. Regarding the interaction between sequence step and
planning duration, the main effect of planning duration on RT was only significant for RT1 when
contrasted against all planning durations (long vs medium, p < 0.0001; long vs short, p < 0.0001;
medium vs short, p < 0.0001). All pairwise differences for RT2, RT3, and RT4 were not statistically
significant (Figure S2). This result confirmed that participants used the planning period to prepare
their responses, beginning sequence execution more quickly when provided with longer periods to
plan their response.

Average accuracy across participants (Figure 2B) was high (M = 0.94; SD = 0.08), with no significant
differences across blocks (as revealed by a Kruskal-Wallis test: $\chi^2(3)$ = 3.99, p = 0.262), as was
expected due to their extensive training (see Methods).

Neuroimaging results

DMPFC, DLPFC, and basal ganglia encode abstract information during planning that is used
during execution

We sought to identify brain areas that mediated between superordinate, abstract sequential codes
during planning and execution. To this end, following our pre-registered analysis plan we applied
Multi-Voxel Pattern Analysis (MVPA; Haynes & Rees, 2006; Norman et al., 2006) to conduct a
searchlight cross-decoding analysis on the multivariate fMRI data (see Figure S3 for results in pre-
determined ROIs). The searchlight technique systematically inspects a spherical subset (i.e., a
"searchlight") of data from the entire brain volume that is iteratively centered on every voxel in the
volume. The voxel values within each searchlight are used by a classifier to discriminate between the
conditions of interest, assigning the classification accuracy score to the voxel at the center of the
searchlight. This process is repeated for every voxel location within the volume, resulting in a
decoding accuracy map of the entire brain (Kriegeskorte et al., 2006). During decoding, part of the
data serves to train the classifier, and the rest is used for testing, which gives an estimate of the
predictability of new data points based on the training set. Here, we operationalized "abstraction" as
the generalization performance of a multivariate decoder on conditions not used for training (Bernardi
et al., 2020). We trained the classifier to discriminate between abstract representations during the
planning phase and tested it during the execution phase to predict the activity of the same
representations. We hypothesized that if this abstract context connects both task phases (planning
and execution), then the (abstract) information shared across phases would enable prediction of one
phase from the other, regardless of the low-level (non-abstract) components of the action plan (i.e.,
the visual stimuli and motor responses).

Specifically, we trained a support vector machine (SVM) on the brain activity patterns (i.e., the beta
value estimates, see Methods) during the planning phase of one of the stimulus subsets of each code

(e.g., planning c1s1 and c2s1; Figure 3A), and used it to classify activity patterns during execution of
the left-out stimuli of each code (e.g., executing c1s2 and c2s2; Figure 3A). Importantly, the task
design and analysis controlled for stimulus confounds by 1) showing only a blank screen during the
planning period, and 2) training the classifier on activity patterns of one set of visual stimuli (e.g., red
square and blue triangle) and testing the classifier on the activity patterns of different visual stimuli
that mapped to the same code (e.g., yellow diamond and green circle; Figure 3A). Note that this task
design ensured that training and testing occurred on different trials. The task design further controlled
for motor-related confounds by providing participants with the button-to-screen mappings (i.e.,
whether the left or the right button corresponded to the "#" and "&" symbols) only during the execution
phase of the trial, which varied randomly from trial-to-trial. Furthermore, in addition to controlling for
visual and motor confounds, training on data from one set of stimuli and testing on data from another
set of stimuli limits the influence of the hemodynamic response lag (Huettel, 2012; Kruggel & Von
Cramon, 1999) by dissociating temporally adjacent events across different training and testing sets.
All together, this procedure trained and tested the data for different visual stimuli (belonging to the
same abstract context), different trial phases (associated with planning versus execution), different
trials (because the stimulus for training occurred on a different trial than the stimulus for testing), and
different functional runs (via leave-one-run-out cross-validation).

This searchlight cross-decoding analysis yielded no significant clusters after family-wise error (FWE)
rate multiple comparison correction (p_{FWE} = 0.05). However, an exploratory analysis using a less
restrictive, uncorrected threshold of (p_{unc} < 0.001) identified three clusters of activity in which the
representations formed during planning could be decoded at an above chance level based on the
representations applied during execution (Figure 3B). One cluster encompassed DMPFC (including
part of DACC, Figure 3B, left; peak at x = 10; y = 46; z = 40), another cluster was located in DLPFC
(Figure 3B, middle; peak at x = -48; y = 30; z = 30) and the third cluster centered on a region of the
basal ganglia (BG) including the putamen and pallidum (Figure 3B, right; peak at x = -26; y = -14; z = -
4).

303
Figure 3. MVPA procedures and results. A. Pre-registered searchlight cross-decoding analysis. We
trained a SVM on the brain activity patterns during the planning phase of one of the stimulus subsets
of each code (e.g., planning of c1s1 and c2s1, orange highlights), and tested this classifier on brain
activity patterns during execution of the left-out stimulus subsets of each code (e.g., execution of c1s2
and c2s2, green highlights; note that the position of the buttons for "&" and "#" were pseudo-
randomized across trials). Training and testing took place on data from different visual stimuli (which
mapped to the same abstract context), on different trial phases (planning versus execution), on
different trials (stimuli for training appeared on different trials than stimuli for testing), and on different
functional runs (via leave-one-run-out cross-validation). **B.** Searchlight cross-decoding results. Three
clusters were identified where execution activity was decoded from planning activity at above-chance
level ($p_{unc} < 0.001$): DMPFC (including DACC; peak at x = 10; y = 46; z = 40), DLPFC (peak at x = -
48; y = 30; z = 30), and BG (putamen and pallidum, peak at x = -26; y = -14; z = -4). **C.** Control
searchlight cross-decoding analysis. An SVM was trained on the brain activity patterns during the
planning phase of the visual sets of each code (e.g., planning of c1s1 and c1s2, orange highlights),
and tested on brain activity patterns during execution of the visual sets of the other code (e.g.,
execution of c2s1 and c2s2, green highlights). Training and testing took place on data from different

codes (which shared high visual similarities), on different trial phases (planning versus execution), on

different trials (stimuli for training appeared on different trials than stimuli for testing), and on different

functional runs (via leave-one-run-out cross-validation). **D.** Control searchlight cross-decoding results.

One cluster was identified where execution was decoded from planning at above-chance level (p_{unc} <

0.001): VC (peak at x = 4; y = -76; z = 10). **E.** Pre-registered searchlight representational similarity

analysis (RSA). On brain activations only from the planning phase, we contrasted each participant's

"brain-RDM" (all task conditions correlated against each other: c1s1 VS c1s2 VS c2s1 VS c2s2)

against two candidate "hypothesis-RDMs": an abstract RDM was designed to capture abstract

representations (representational distances depended on whether stimuli belong to within- or between

code contexts), and a perceptual RDM which was designed to depict low-level visually-driven

representations (distances depended on how visually similar the stimuli are). **F.** Searchlight RSA

results. Top: One cluster was identified with significant similarity (p_{FWE} = 0.014) between the brain

RDM and the abstract RDM, located in DMPFC (including DACC, peak at x = 3; y = 38; z = 44).

Bottom: One cluster was identified with significant similarity (p_{FWE} < 0.001) between the brain RDM

and the perceptual RDM, located in VC (peak at x = -18; y = -91; z = 1). **G.** Overlay of the significant

clusters found by the two multivariate approaches. The same DMPFC region was found significantly

active by cross-decoding planning versus execution (neural data from different trial phases) and by

comparing the representational similarity during planning (neural data only from the planning phase)

against hypothesis-RDMs. SVM: support vector machine; DACC: dorsal anterior cingulate cortex;

DMPFC: dorsomedial prefrontal cortex; DLPFC: dorsolateral prefrontal cortex; BG: basal ganglia; VC:

visual cortex.

Abstract decoding differs from perceptual decoding

To verify that these findings did not simply result from the visual similarities across different stimuli or

codes, we conducted a control analysis (not pre-registered) by training an SVM classifier on the

planning-related activations of the stimuli that mapped to the same abstract code (e.g., planning c1s1

and c1s2; Figure 3C) and tested it on the execution-related brain activity of the stimuli that mapped to

the other code (e.g., executing c2s1 and c2s2; Figure 3C). Because each pair of stimuli denoted both

codes, and thus shared a high degree of visual similarity, we hypothesized that application of the

searchlight SVM cross-decoder would predominantly reveal activity clusters near visual areas. As

expected, this analysis identified one significant cluster located in visual cortex (VC; Figure 3D, peak

at x = 4; y = -76; z = 10).

DMPFC represents abstract information during planning

Via the previous multivariate decoding analysis we tested whether abstract representations of plans

formed during plan preparation could be subsequently decoded from the same brain areas during the

execution of those plans. Next, we investigated the abstract representational profile expressed during

planning that links plans to actions, independently of the actual execution of those plans. An

abstracted plan could be expressed either as a representation that generalizes across different stimuli

(such that different explicit action sequences are represented by the same pattern of activations), or
as individual representations that map to each action sequence. Additionally, if the planning
information is based on the perceptual features (instead of on the abstract links) of the task elements,
then the task concepts should relate to each other by their visual similarities. Here we focused on the
abstraction that subserves generalization. We hypothesized that if the planning information is indeed
represented in an abstract format, then the task concepts should generalize across their higher-level
relationships.

To test these predictions, we performed a pre-registered searchlight representational similarity
analysis (RSA) on brain activations recorded during the planning phase (see Methods). We
constructed two hypothesis-driven RDMs that contrasted all the task conditions (standard trials)
against each other (c1s1 VS c1s2 VS c2s1 VS c2s2): an Abstract RDM that tested for high-level,
abstract relationships between plans (where the distances depended on whether the stimuli mapped
to the same or different code contexts), and a Perceptual RDM that tested for low-level, visually-
driven relationships between plans (where the distances depended on the visual similarity of the
stimuli) (Figure 3E). We expected this hypothesis-driven RSA-searchlight to identify clusters that
overlapped with the areas identified from the decoding-searchlight analysis.

The searchlight-RSA analysis yielded a single significant (p_{FWE} = 0.014) cluster representing abstract
planning information in DMPFC (including parts of DACC, Figure 3F, top; peak at x = 3; y = 38; z =
44). This cluster highly overlapped the DMPFC cluster identified by the decoding analysis (Figure 3G).
Likewise, the analysis yielded a single significant (p_{FWE} < 0.001) cluster representing perceptual
information in VC (Figure 3F, bottom; peak at x = -18; y = -91; z = 1), which also overlapped with the
VC cluster identified by the decoding analysis.

Shifts of representational formats during planning
Next, we investigated the temporal evolution of the abstract representations during the planning
period. Toward this end, we employed two functional localizer tasks that were performed after the
main fMRI task during the same functional imaging session (see Methods). The "shape" localizer
(Figure 1C, top; Figure 4A, top) captured variance in the main task explained by visual processing
and visual memory (such as mentally recalling the visual shapes during the planning phase). By
contrast, the "code" localizer (Figure 1C, bottom; Figure 4A, bottom) captured variance in the main
task explained by abstract processing alone (i.e., the abstract codes independent of the properties of
their stimulus representations). We expected stronger perceptual contributions to neural activity at the
beginning of the planning phase (due to visual reactivation of stimuli), resulting in greater
correspondence with the shape localizer. By contrast, we expected stronger abstract contributions to
neural activity at the end of the planning phase (following the translation of the instructive cues into
their respective abstract codes), resulting in greater correspondence with the code localizer (Figure
4B).

To do so, we inspected the differential contribution of the perceptual vs abstract representations at
different points in time (beginning and middle) during the planning phase in the clusters obtained
during the cross-decoding analysis (DMPFC, DLPFC, and BG; see above). As pre-registered, semi-
partial correlations were estimated between the patterns of activity during planning in the main task,
and the patterns of activity during each of the localizer tasks (Figure 4A, B), for each of these clusters.
A two-way repeated measures ANOVA with factors time (beginning, middle) and localizer (shape,
code) was then performed on the semi-partial correlation estimates, separately for each cluster. This
analysis returned a significant interaction between time point and localizer in DMPFC ($F(1,1) = 5.98$, p
= 0.015). Pairwise post-hoc comparisons showed that the interaction was driven by a significant
difference between the middle and beginning time points (p = 0.028) for the code localizer in DMPFC
but not for the shape localizer (Figure 4C). All of the other effects across all three clusters were not
statistically significant (Figure 4C).

407
Figure 4. Functional localizer tasks and results. A. Illustration of the semi-partial correlation
analysis between the planning phase of the main fMRI task and the planning phase of each of the
functional localizer tasks. We correlated the patterns of activity at the beginning and middle time
points during the main task with the activity patterns during the planning phase of the shape localizer
(blue frame, intended to capture the variance driven by visual processing and visual memory alone)
and the code localizer (green frame, intended to capture the variance driven by abstract processing
alone). **B.** Predicted planning representational dynamics during the main task. We hypothesized that
the beginning planning phase would be more correlated with the shape localizer, while the middle
planning phase would be more correlated with the code localizer (see main text). **C.** Semi-partial
correlations of cluster activity with functional localizers. The x-axis indicates the representational

format (shape/perceptual vs code/abstract) during the planning period. The y-axis indicates the

difference between semi-partial correlations at the middle and the beginning of the planning phase,

with positive or negative numbers signaling an increase or decrease in the respective representational

format (shape/perceptual vs code/abstract), respectively, from the beginning to the middle of the

planning phase. Activity in the DMPFC cluster (multivariate cross-decoding analysis, see Results) was

significantly more correlated with the code localizer (green square) at the middle of the planning

phase, indicating an enhanced abstract representational format late in the planning period, in contrast

to the correlation with the shape localizer, which did not change during the planning phase. Activity in

the other brain areas (DMPFC and BG) did not change significantly during planning for either of the

representational formats. Asterisk denotes statistical significance at $p < 0.05$.

DISCUSSION

Mental planning has been conceptualized as an iterative process of response selection and outcome

prediction for goal-directed search, which is used to prepare or simulate upcoming sequential

behaviors before their actual execution (Dehaene & Changeux, 1997). This process is understood to

utilize internal representations (or models) derived from prior task experience and environmental

constraints (Tolman, 1948). However, the variety of potential behaviors available for simulation often

renders this process computationally intractable (Daw & Dayan, 2014; Mattar & Lengyel, 2022). One

strategy to make the process more efficient is to generalize over related sequences of actions in order

to plan at a more abstract, hierarchically higher level, thereby simplifying the problem domain (Ho et

al., 2022; Ying et al., 2025) while supporting the actual implementation of the plans. To investigate this

possibility, we recorded brain activity of participants as they performed a hierarchical planning task

expressly designed to test these predictions. On each trial, participants were required to map visual

stimuli to abstract codes, maintain that abstract information throughout a delay period, and then

implement the corresponding sequence of responses in an execution period. Behavioral analyses

revealed that participants effectively used the planning period to prepare their upcoming responses by

encoding the task rules hierarchically (Figure S1), though this latter effect was attenuated with

repeated exposure to the task (Figure 2A).

Neuroimaging analyses revealed that the hypothesized abstract context was encoded by DMPFC

(together with sections of dorsal ACC), DLPFC, and BG (including the putamen and pallidum) (Figure

3B). Specifically, an MVPA classifier was trained to discriminate between fMRI data related to different

abstract codes that mapped to the same stimuli during the planning phase. That classifier was then

tested on fMRI data collected during the execution phase (Figure 3A). This analysis revealed that

these areas instantiated the same patterns of activity when planning and executing the behavioral

sequences. These correspondences allowed for the identity of each hierarchical sequence to be

predicted from the neural activity patterns occurring during its execution, based on the patterns of

activity that occurred when planning an equivalent action sequence from a different, symbolic code.

Hence these representations aligned according to their higher-order contexts (as specified by the

higher-order relationships between the different stimuli) rather than to the stimulus and action

specifics of task execution. Importantly, these results were not due to the visual similarity of stimuli corresponding to the abstract codes, as confirmed by a control analysis that trained the classifier to discriminate between different stimuli that mapped to the same abstract code (Figure 3C), which revealed activity in VC (Figure 3D). These abstract representations were also unrelated to the implementational details of plan execution, because the current experimental design prevented participants from determining the specifics of sequence execution (i.e., code-to-button mappings) until the execution phase (see Methods). Furthermore, DMPFC in particular encoded planning information in an abstract format, as revealed by searchlight-RSA based on an RDM that grouped the planning phase data according to their high-order similarity (Figure 3F, top), whereas a searchlight-RSA based on an RDM that grouped the planning phase data according to the stimuli's visual similarity revealed activity in VC, as expected (Figure 3F, bottom). Finally, a follow-up analysis employing functional localizers revealed that the abstract representations in DMPFC increased in strength as the delay period progressed, as would be expected of a region involved in planning the response in a higher-order space (Figure 4C).

Despite the involvement of all of these neural systems in planning, our results point to a crucial distinction between the functions of DMPFC vs. BG and DLPFC. In particular, DMPFC was the only brain region that was sensitive both to the correspondence between planning and execution and to abstract processing (Figure 3G). This property suggests that DMPFC encodes an abstract representation of a forthcoming behavioral sequence that is maintained until used, namely, during the execution of the sequence. By contrast, DLPFC and BG were identified by the searchlight cross-decoding analysis but not by the searchlight-RSA, which suggests that although these areas worked in tandem with the DMPFC to plan and produce the behavioral sequences, that information was not encoded in the same abstract format as in DMPFC. Figure 5 presents a schematic that illustrates this apparent relationship: for DMPFC alone the RSA revealed generalized patterns of activity that related the sequences within a common abstract code (Figure 5, left), but for DLPFC and BG, the sequences were encoded in specialized formats whereby the distances within the plans were about as equal as the distances across the plans (Figure 5, right). This distinction suggests complementary functions: whereas DLPFC and BG are concerned with the implementational details of the plans via specialized representations, only DMPFC generalizes across plans by providing an abstract context that facilitates task maintenance during planning (Figure 4C) and execution (Figure 3G). In other words, DMPFC is responsible for maintaining representations of sequences of actions in an abstract format while planning and until execution, such that both the perceptual task features and explicit implementational actions are irrelevant for its encoding. By contrast, DLPFC and BG work in conjunction to select and direct the execution of actions according to specific plan-related policies.

Figure 5. Schematic interpretation of multivariate fMRI findings: Hypothesized representational space. The functional localizer and RSA findings highlight features in DMPFC (left panel) that differ from those in DLPFC or BG (right panel). Although all three regions encoded plans that could be decoded during their execution, only DMPFC maintained the planning information in an abstract representational format that increased in strength as the planning phase progressed. Separability between conditions despite the absence of abstract encoding might be a consequence of the representational format itself. Stimuli could be represented by their abstract relationships (as was the case for DMPFC, left panel), in which case the equivalent conditions were closer together in the state space. By contrast, all of the conditions might have distinct representations that nevertheless allow for a hyperplane (red dotted lines) to define a boundary that separates the conditions following their abstract relationships but not necessarily according to an abstract code (as was the case for DLPFC and BG, right panel).

These results are supported by previous work that has highlighted DMPFC as a center for abstract, hierarchically-organized behavior and planning (Alejandro & Holroyd, 2024b; Alexander & Brown, 2015; Duverne & Koechlin, 2017; Foinikianaki et al., 2025; Holroyd & Verguts, 2021; Holroyd & Yeung, 2012; Umemoto et al., 2017; Zarr & Brown, 2016). For example, one fMRI experiment found that during a variable planning interval DMPFC was involved in sustaining and "energizing" task-relevant processes (Vallesi et al., 2009). In an fMRI study where participants planned their navigation in a virtual subway network, DMPFC activity was observed to encode the task context (i.e., current subway line), and was correlated with the cost of representing a hierarchical plan (i.e., the number of subway lines to take as opposed to the number of stations to visit) (Balaguer et al., 2016). Similarly, when navigating a virtual city, information about upcoming paths was represented across a gradient of activity in anterior prefrontal cortex (APFC, including parts of DMPFC), with more anterior regions encoding places to be visited more distantly in the future (Brunec & Momennejad, 2022). Dorsal ACC activity was also observed to encode hierarchical representations in a sequential task that emulated making different beverages (coffee vs. tea), as these representations were predicted by the activation states of a recurrent neural network (RNN) model of the task (Holroyd et al., 2018). More recently, a reanalysis of these data incorporating goal states into the RNN model demonstrated that more rostral

regions of DMPFC (rostral ACC) encoded the goal-related representations in the task (Colin et al.,
2025). Further, our results align with a model-based hierarchical reinforcement learning (MB-HRL)
framework that proposes that dorsal ACC is responsible for selecting and maintaining high-level task
options (goals), where DLPFC follows by exerting top-down control over BG to facilitate the execution
of the specific actions that implement the selected option (Holroyd & Verguts, 2021). Beyond
maintaining such currently executed behaviors, we found that DMPFC prospectively maintains an
abstract representation of the task context during planning and uses that representation to guide the
execution of upcoming behavior.

Note that although the RSA and decoding analysis provide converging evidence on the role of
DMPFC in planning, the decoding results (but not the RSA results) were determined using an
uncorrected threshold and therefore should be considered as exploratory. Nevertheless, the DLPFC
and BG observations are consistent with a wide neuroimaging literature on this system. The prefrontal
cortex (PFC) and BG are well-known to support model-based learning and planning (Fermin et al.,
2016; E. K. Miller & Buschman, 2008), with the PFC constructing internal models of entire behaviors,
simulating them, and directing their execution (Simon & Daw, 2011; Tricomi et al., 2009), and the BG
learning action values specific to task states (Kawagoe et al., 1998; Samejima et al., 2005). Further,
the activity patterns observed in DLPFC are consistent with previous arguments that this region
implements rule-based response selection (Bunge et al., 2002; Cole et al., 2010; Sakai &
Passingham, 2006; Schumacher & D'Esposito, 2002). In particular, DLPFC activity has been
implicated when planning information is actively monitored (Vallesi et al., 2009) and processed
(Crescentini et al., 2012) (as opposed to simply maintained) during a planning delay, and when
rehearsing and preparing planned responses and updating evolving task goal states (Fincham et al.,
2002), for instance by selecting items and actions from working memory (Sakai & Passingham, 2003).
Likewise, the BG, which are highly interconnected with the frontal cortex (Frank et al., 2001), have
been associated with rehearsal and implementation of appropriate motor and behavioral plans
(Baladron & Hamker, 2024; Graybiel, 2000; Groenewegen, 2003; Scholz et al., 2000). The DLPFC
might therefore encode a set of task rules or instruction mappings (Mian et al., 2014) that are
comparable during both planning and execution and are learned via BG associations (Redgrave et al.,
2010). This interpretation is consistent with the role of BG in learning stimulus-association and
response selection (M. X. Cohen & Frank, 2009) and of DLPFC in manipulating task information
compliant with task rules (Abe et al., 2007; Postle et al., 1999), namely by translating shapes to codes
during planning (first selecting actions internally) and from codes to button presses during execution
(then executing the actions externally). In so doing, DLPFC prepares the upcoming sequence of
actions (Pochon, 2001; Vallesi et al., 2009) by relating this information between planning and
execution (Sakai et al., 2002; Vaidya & Badre, 2022).

Planning and action operate along a continuum whereby planning allows for behaviors to be internally
prepared and rehearsed, and action entails the rehearsed sequences of behavior to be implemented.
These operations that translate planning to action require a common representation that spans the
transition from intention to execution. Crucially, real-world environments provide constraints that are

sometimes revealed only during the execution of a behavior, and thus are difficult to plan for in advance. Hence, when driving on a roundabout, we might miss our turn if the roundabout has an unfamiliar layout despite having read the sign and planned our exit well in advance (Figure 1A). Such abstract representations encode fundamental, high-level relational information that can be used to plan behavioral sequences and then adaptively translate the plans into specific details of implementation. Our results indicate that DMPFC plays a unique role in this hierarchical planning-to-action mechanism.

EXPERIMENTAL MODEL AND STUDY PARTICIPANT DETAILS

Participants

Fifty-three participants (38 females, mean age = 24.5, range = 18.8 – 37.5) took part in an online behavioral training session. Before the subsequent fMRI scanning session, the data of two participants were removed due to failure to complete the training (online training timed out), and the data of one other participant were removed due to MRI-incompatibility. Our sample for analysis therefore included 50 participants (35 females, mean age = 24.4, range = 18.8 – 37.5) who took part in both the online behavioral training and in the fMRI experiment. All participants were screened for MRI-compatibility and normal or corrected-to-normal visual acuity, were compensated for their participation, and provided informed consent before each experimental session (online and fMRI). The Ethics Committee of Ghent University Hospital reviewed and approved this study. This study was conducted in accord with the Declaration of Helsinki.

Procedure

We conducted a two-part experiment. In the first part, participants underwent behavioral training online, which was intended for participants to learn the task stimuli and rules. For the second part, participants underwent fMRI scanning while performing a slightly modified version of the task (see Method Details) plus two additional functional localizer tasks inside an fMRI scanner. The two portions of the experiment were completed by the same set of participants.

Behavioral training (online)

The online session comprised three increasingly difficult task training phases with two parts each: guided training (instructions + 10 practice trials) followed by task practice that required an accuracy criterion to be met (10 consecutive correct trials; same for all training stages) in order to proceed to the next training stage. The duration of the online training task depended on instruction reading time and task performance. However, the online training timed out after 120 minutes.

fMRI scanning session

Within 24 hours after successfully completing the online session, participants came to the fMRI scanner for an imaging session that included a main task and two functional localizer tasks. Due to scanner malfunctions, 3 of the participants were rescheduled for a later date.

Prior to entering the scanner, participants practiced the task (a shortened version of the online
training) for about 10 minutes on a laptop. Inside the scanner they performed the main task, which
was similar to the task they learned in the preceding session (see Method Details) for four blocks of
about 10 minutes each. After the four main task blocks, they performed two functional localizer tasks
for about 10 minutes each. In total, the scanning session took around 65 minutes.

METHOD DETAILS

Experimental design, sample size, and statistical analyses were preregistered (Alejandro & Holroyd,
2024a) and are described below. Deviations from the preregistration are noted as such.

Behavioral tasks

Online training task

Participants were instructed to decipher codes (combinations of characters "#" and "&") from abstract
stimuli (colored geometric shapes), and that they would use the index and middle fingers of their right
hand to press the "J" and "K" keys to select items (the characters "#" and "&") on the left and the right
side of their screen, respectively. In general, the training started with an elementary task version of 1
stimulus with 1-character code (representing its shape), progressed to 1 stimulus with a 2-character
code (representing shape + color), and finished with 2 stimuli with a 2-character code each
(representing shape + color for each).

On the first training stage (training shape), participants were shown a single, randomly selected white
shape (square, circle, diamond, or triangle) on a black background, and were instructed to select "#" if
the shape was a square or a diamond, or "&" if the shape was a triangle or a circle. A trial ended when
the correct response was chosen. They performed 10 practice trials irrespective of their accuracy.
Then, in order to advance to the next training stage, they were required to correctly complete two 10-
trial sequences of consecutive trials (thus meeting an accuracy criterion).

For the second training stage, a delay screen was introduced after stimulus presentation, during
which the participants were required to plan the code that they would enter in the subsequent
execution phase. As with the first training stage, they performed 10 practice trials, which they
repeated until reaching the accuracy criterion.

For the next (third) training stage (training shape + color), the participants were presented with the
same shapes as before (square, diamond, circle, triangle) but now displayed in specific colors
(squares and triangles were either blue or red, circles and diamonds were either green or yellow;
Figure 1C), selected at random. Consequently, the codes to be input had two dimensions (i.e.,
character shape and character color). Initially, the participants were presented with each colored
shape and were asked to input the 2-character code, and afterwards a planning phase was
introduced (similar to stage 1). Finally, a time limit was introduced for the execution phase. The
participants proceeded to the next stage once they have reached the accuracy criterion.

In the final (fourth) training stage (training shape + color with 2 stimuli), the stimuli at each trial
consisted of 2 shapes (a shape pair) presented together. Participants were required to input two 2-

character codes one after the other (equivalent to one 4-character code). Similar as the proceeding
training stages, participants were trained in blocks without a planning phase, with a planning phase,
and with a time limit for execution. They proceeded to the next stage once they had reached accuracy
criterion.

After participants completed the training stages, they performed the "main training task" by performing
4 blocks of the task with two shape pairs (describing two 2-character codes). This stage was
conducted without an accuracy criterion. Accuracy across blocks for the main training task was high
(M = 0.93, SD = 0.007, range = 0.92 – 0.94) and comparable to the main fMRI task (M = 0.94, SD =
0.007, range = 0.93 – 0.95).

fMRI tasks

Each imaging session consisted of a main task and two functional localizer tasks.

For the main task, participants were placed inside the scanner and performed 4 blocks of around 10
minutes each of a task similar to the main training task. Each trial started with a fixation cross,
followed by the presentation of the trial stimuli (colored geometric shapes). The durations of both the
fixation cross and the stimuli were jittered by 2.0 ± 0.5 s. After stimulus presentation, a black screen
was presented for 6.0 ± 1.5 s. (jittered), signaling the planning phase. During this period participants
were required to map the stimuli (colored geometric shapes) presented on that trial to their
corresponding codes (that were learned during the practice session). Finally, the execution phase was
signaled by the presentation on screen of an input field, the instruction "enter code", and two buttons
labelled with the characters "#" and "&" (the relative positions of these buttons varied at random from
trial to trial). The execution phase lasted 3.0 ± 0.5 s. (jittered), and participants were required to enter
the codes corresponding to the trial stimuli by pressing two spatially equivalent buttons (i.e., right
button to select right item on the screen) on an MRI-compatible button box using the right-hand index
and middle fingers. A feedback screen was presented only for incorrect trials with a fixed duration of
0.5 s.

The duration of each of the phases (fixation cross, stimuli presentation, planning, and execution) were
assigned pseudo-randomly on each trial, such that all the trials in the experiment lasted for 13 s, and
all possible durations were presented in equal proportion (e.g., the planning phase lasted an equal
number of times for 4.5, 6.0, or 7.5 s).

The fMRI task differed from the (online) main training task (see above) according to the relative
proportions of the presented stimuli. To increase the number of observations per condition, we
restricted the number of codes to be analyzed to only two (c1: "#&&#", c2: "&##&"), each of which was
represented by two 2 shape-pairs -- i.e., c1 represented by c1s1 ("red square + blue triangle") and
c1s2 ("yellow diamond + green circle"), and c2 represented by c2s1 ("blue triangle + red square") and
c2s2 ("green circle + yellow diamond") (Figure 1E). Each main task run contained 44 trials, about 82%
of which consisted of the trials of interest or "standard trials" (c1 or c2; Figure 1E), and the remaining
18% were "catch trials" (Table S1) that were randomly selected from the allowed feature combinations
(i.e.., shapes in s1 combined only with shapes and colors within s1, and shapes in s2 combined only

with shapes and colors within s2; Figure 1D). Standard and catch trials were presented intermixed
during each task run.

After completing the main task, participants performed two functional localizer tasks ("shape" and
"code" localizers) that lasted approximately 10 minutes each. The shape localizer task included 68
task trials, including 15 trials per standard-trial shape-pair (or 30 trials per each of the two standard-
trial codes), and 8 (~12%) catch trials. During each trial of the shape localizer task, participants first
saw a fixation cross, followed by the presentation of a shape-pair (according to the same stimuli and
constraints as in the main task). The durations of both the fixation cross and the stimulus
presentations were jittered by 2.00 ± 0.50 s. Next, a black screen appeared for 3.00 ± 0.50 s (jittered
across trials). During this planning phase participants were required to maintain the stimulus
information in working memory. Then, a shape-pair with the same stimulus properties and constraints
as in the main task (including both standard and catch trials) was presented for a duration of $1.75 \pm$
0.50 s. During this execution phase, participants were required to indicate whether the stimuli were
identical to those presented at the start of the trial by pressing one of two buttons on a response box
corresponding to the answers "yes" and "no". The correspondence between the button location (left or
right) and the response options ("yes" and "no") was cued on the screen and was pseudo-randomized
across trials such that each button corresponded to "yes" and "no" an equal proportion of times. The
duration of each of the phases (fixation cross, stimulus presentation, planning, and execution) were
assigned pseudo-randomly on each trial, such that all the trials in the shape localizer task lasted for
8.75 s, and all possible durations were presented in equal proportion (e.g., the planning phase lasted
an equal number of times for 2.50, 3.00, or 3.50 s).

The code localizer task included 68 task trials (30 trials per each of the two standard-trial codes) and
8 (~12%) catch trials. During each trial, participants were presented with a fixation cross (2.00 ± 0.50
s) and then an abstract code consisting of the same combinations of the symbols "&" and "#" as they
appeared in the main task (2.00 ± 0.50 s), the duration of which was jittered across trials. Then a
black screen was displayed for 3.00 ± 0.50 s jittered across trials, during which the participants were
required to remember the observed code. Finally, a screen that was identical to the execution phase
of the main task appeared for 2.25 ± 0.50 s, during which participants were required to execute a
response (see above and Figure 1). The duration of each of the phases (fixation cross, stimulus
presentation, planning, and execution) were assigned pseudo-randomly for each trial such that all the
trials in the code localizer task lasted for 9.25 s, with all possible durations presented in equal
proportions (e.g., the planning phase lasted an equal number of times for 2.50, 3.00, or 3.50 s).

For both the main task and the functional localizer tasks, the standard and catch trials were presented
intermixed. The standard trial codes were constructed such that 1) each character appeared an equal
number of times in each code, 2) the codes were composed of more than one symbol (excluding, for
example, the stimulus "####"), and 3) the dimensions were orthogonal across codes (e.g., red in
code 1 is blue in code 2). During the scanning session all of the participants performed the main task
first, followed by the two localizer tasks; the order of the two localizer tasks was counterbalanced
across participants.

Participants pressed the left and right buttons of the MRI-compatible button box to select the code
characters ("#" and "&") that were presented on the left and the right side of the screen. Importantly,
the location of the characters on the screen was assigned pseudorandomly across trials and
participants, such that either code character appeared at the same (left or right) screen location for no
more than 2 consecutive trials.

MRI Data Collection

MRI data were collected in a Siemens MAGNETOM PrismaFit 3T MRI scanner using a 64-channel
head coil. For each participant we collected a high-resolution T1-weighted anatomical scan using an
MPRAGE sequence (176 slices; voxel size = 1 mm isotropic; TR = 2250 ms; TE = 4.18 ms; FoV =
256 mm), and whole-brain, T2*-weighted multi-band echo-planar imaging (EPI) functional scans (54
slices per volume; TR = 1780 ms; TE = 27 ms; voxel size = 2.5 mm isotropic; FoV = 210 mm;
interleaved slice acquisition).

QUANTIFICATION AND STATISTICAL ANALYSIS

R (version 4.4.0) running under RStudio (version 2024.09.1+394) was used for all behavioral
analyses. Neuroimaging analyses were conducted using SPM12 software (Statistical Parametric
Mapping; Wellcome Department of Imaging Neuroscience, London, UK) running on Matlab (version
R2023a) with customized scripts and in tandem with purpose-specific toolboxes: The Decoding
Toolbox (version 3.99F; Hebart et al., 2015) for decoding analysis, and the rsatoollbox (Nili et al.,
2014) for representational similarity analysis (RSA).

Behavioral data analysis

Behavioral analyses were conducted in the R environment for statistical computing and visualization
(version 4.4.0). Per participant, we estimated mean reaction times (RTs) per sequence step, and
accuracies with the Rmisc package (Hope, 2012). We performed a Kruskal-Wallis test to assess
overall differences in accuracy across blocks.

RTs were analyzed fitting a linear mixed-effects model (LMM) using the lme4 package (Bates et al.,
2015). The model included step (1, 2, 3, 4) and planning duration (short, medium, long) as fixed
effects, as well as their interaction. To account for individual differences, we included random
intercepts for subjects. We assessed the significance of the fixed effects using Type III ANOVA with
Satterthwaite's degrees of freedom approximation. For significant main effects or interactions, we
conducted post-hoc pairwise comparisons of estimated marginal means with Tukey's Honestly
Significant Difference (HSD) correction implemented in the emmeans R package (Lenth et al., 2017).

MRI data preprocessing

Before preprocessing, raw (DICOM) MRI data were converted into BIDS-format (K. J. Gorgolewski et
al., 2017) using BIDScoin 3.0.8 (Zwiers et al., 2022). Results included in this manuscript come from
preprocessing performed using fMRIPrep 23.2.3 (Esteban et al., 2019; Markiewicz et al., 2024;
RRID:SCR_016216) Nipype 1.8.6 (Esteban et al., 2022; Gorgolewski et al., 2011;

RRID:SCR_002502). Many internal operations of fMRIPrep use Nilearn 0.10.2 (Abraham et al., 2014;

RRID:SCR_001362), mostly within the functional processing workflow. As recommended by the

fMRIPrep developers, we report below the automatically generated outputs from preprocessing both

the anatomical and the functional MRI data.

Anatomical data preprocessing

A total of 1 T1-weighted (T1w) images were found within the input BIDS dataset. The T1w image was

corrected for intensity non-uniformity (INU) with N4BiasFieldCorrection (Tustison et al., 2010),

distributed with ANTs 2.5.0 (Avants et al., 2008, RRID:SCR_004757), and used as T1w-reference

throughout the workflow. The T1w-reference was then skull-stripped with a Nipype implementation of

the antsBrainExtraction.sh workflow (from ANTs), using OASIS30ANTs as target template. Brain

tissue segmentation of cerebrospinal fluid (CSF), white-matter (WM) and gray-matter (GM) was

performed on the brain-extracted T1w using fast (FSL (version unknown), RRID:SCR_002823, Zhang

et al., 2001). Brain surfaces were reconstructed using recon-all (FreeSurfer 7.3.2,

RRID:SCR_001847, Dale et al., 1999), and the brain mask estimated previously was refined with a

custom variation of the method to reconcile ANTs-derived and FreeSurfer-derived segmentations of

the cortical gray-matter of Mindboggle (RRID:SCR_002438, Klein et al., 2017). Volume-based spatial

normalization to one standard space (MNI152NLin2009cAsym) was performed through nonlinear

registration with antsRegistration (ANTs 2.5.0), using brain-extracted versions of both T1w reference

and the T1w template. The following template was selected for spatial normalization and accessed

with TemplateFlow (23.1.0, Ciric et al., 2022): ICBM 152 Nonlinear Asymmetrical template version

2009c [Fonov et al. (2009), RRID:SCR_008796; TemplateFlow ID: MNI152NLin2009cAsym].

Functional data preprocessing

For each of the 6 BOLD runs found per subject (across all tasks and sessions), the following

preprocessing was performed. First, a reference volume was generated, using a custom methodology

of fMRIPrep, for use in head motion correction. Head-motion parameters with respect to the BOLD

reference (transformation matrices, and six corresponding rotation and translation parameters) are

estimated before any spatiotemporal filtering using mcflirt (FSL, Jenkinson et al., 2002). The

estimated fieldmap was then aligned with rigid-registration to the target EPI (echo-planar imaging)

reference run. The field coefficients were mapped on to the reference EPI using the transform. The

BOLD reference was then co-registered to the T1w reference using bbregister (FreeSurfer) which

implements boundary-based registration (Greve & Fischl, 2009). Co-registration was configured with

six degrees of freedom. Several confounding time-series were calculated based on the preprocessed

BOLD: framewise displacement (FD), DVARS and three region-wise global signals. FD was computed

using two formulations following Power (absolute sum of relative motions, Power et al., 2014) and

Jenkinson (relative root mean square displacement between affines, Jenkinson et al. (2002)). FD and

DVARS are calculated for each functional run, both using their implementations in Nipype (following

the definitions by Power et al., 2014). The three global signals are extracted within the CSF, the WM,

and the whole-brain masks. Additionally, a set of physiological regressors were extracted to allow for

component-based noise correction (CompCor, Behzadi et al., 2007). Principal components are

estimated after high-pass filtering the preprocessed BOLD time-series (using a discrete cosine filter

with 128s cut-off) for the two CompCor variants: temporal (tCompCor) and anatomical (aCompCor).

tCompCor components are then calculated from the top 2% variable voxels within the brain mask. For

aCompCor, three probabilistic masks (CSF, WM and combined CSF+WM) are generated in

anatomical space. The implementation differs from that of Behzadi et al. in that instead of eroding the

masks by 2 pixels on BOLD space, a mask of pixels that likely contain a volume fraction of GM is

subtracted from the aCompCor masks. This mask is obtained by dilating a GM mask extracted from

the FreeSurfer's aseg segmentation, and it ensures components are not extracted from voxels

containing a minimal fraction of GM. Finally, these masks are resampled into BOLD space and

binarized by thresholding at 0.99 (as in the original implementation). Components are also calculated

separately within the WM and CSF masks. For each CompCor decomposition, the k components with

the largest singular values are retained, such that the retained components' time series are sufficient

to explain 50 percent of variance across the nuisance mask (CSF, WM, combined, or temporal). The

remaining components are dropped from consideration. The head-motion estimates calculated in the

correction step were also placed within the corresponding confounds file. The confound time series

derived from head motion estimates and global signals were expanded with the inclusion of temporal

derivatives and quadratic terms for each (Satterthwaite et al., 2013). Frames that exceeded a

threshold of 0.5 mm FD or 1.5 standardized DVARS were annotated as motion outliers. Additional

nuisance timeseries are calculated by means of principal components analysis of the signal found

within a thin band (crown) of voxels around the edge of the brain, as proposed by (Patriat et al.,

2017). All resamplings can be performed with a single interpolation step by composing all the

pertinent transformations (i.e. head-motion transform matrices, susceptibility distortion correction

when available, and co-registrations to anatomical and output spaces). Gridded (volumetric)

resamplings were performed using nitransforms, configured with cubic B-spline interpolation.

fMRI data analysis

To estimate voxel activity patterns via MVPA (Kriegeskorte & Douglas, 2019; Norman et al., 2006), we

used multivariate decoding (Norman et al., 2006), and Representational Similarity Analysis

(Kriegeskorte et al., 2008). We first ran a voxel-wise general linear model (GLM) on unsmoothed,

unnormalized individual data. This GLM included regressors of interest for planning and execution

phases, modelled as boxcars. Error and late trials were modelled as regressors that comprised the

duration of the entire trial. Confound regressors (estimated during preprocessing) included six head

motion parameters, framewise displacement, and global signal (within cerebrospinal fluid, white

matter, and brain mask). All regressors were convolved with a canonical hemodynamic response

function plus time and dispersion derivatives as implemented in SPM12. The resulting beta maps

were used to perform our searchlight MVPA analyses. Additionally, region-of-interest analyses were

performed for multivariate decoding-, representational similarity-, and semi-partial correlation

analyses (Figure S3). As preregistered, we used a p-value of 0.05 to establish statistical significance,

and to control for multiple comparisons where applicable we used a familywise error (FWE) cluster

correction of $p = 0.05$ and a primary voxel-wise threshold of $p < 0.001$.

Multi-Voxel Pattern Analysis (MVPA): searchlight cross-decoding of action execution from action planning

To answer our primary question of whether the brain maintains an abstract, higher-order context during planning and uses this representation when executing the plan, we conducted a one-vs-one multi-class cross-validated (leave-one-run-out) searchlight cross-classification of the executed action sequences, with classification accuracy minus chance values per voxel (accuracy maps) as the output. Beta maps from the planning phase of one shape-pair from each condition (e.g., c1s1 and c2s1) were used for training, and beta maps from the execution phase of the left-out conditions (e.g., c1s2 and c2s2) were used for testing (Figure 3A). This procedure was repeated by switching the conditions (i.e., training on the planning phases of c1s2 and c2s2, and testing on the execution phase of c1s1 and c2s1, respectively; Figure 3A). This procedure for training and testing was carried out on data taken from different trials, different trial phases (planning vs execution), and different functional runs, per subject. The output of this analysis consisted of an accuracy map per subject (from planning to execution), indicating the degree to which the abstract codes generalized across task phases regardless of their low-level stimulus features and motor demands.

The analysis was run using a linear support vector machine (SVM) implemented by LIBSVM (Chang & Lin, 2011) within The Decoding Toolbox (Hebart et al., 2015) software package. Decoding was performed in native space by scanning a spherical searchlight (6 mm of radius) across the condition beta values for the entire brain to obtain an accuracy map (cross-decoding accuracy score assigned to each searchlight-centered voxel) per subject. We normalized each subject's z-scored accuracy map into MNI space and applied spatial smoothing using a 3 mm FWHM gaussian kernel. Statistical significance was assessed at the group level by performing a one-sample t-test against the null hypothesis (chance performance level of 0.25) across participants. The recommended primary threshold of $p < 0.001$ was applied on the resulting statistical map (Woo et al., 2014) at the voxel level and a cluster size threshold of 20 voxels was applied to identify significant clusters. To correct for multiple comparisons, we applied a familywise error (FWE) cluster correction of $p = 0.05$.

Representational Similarity Analysis (RSA): searchlight RSA of planned sequences and hypothesis RDMs

To investigate the format in which information is represented while planning the execution of a sequence, a cross-validated (leave-one-run-out) searchlight representational similarity analysis (RSA) of planned sequences was applied to the data of the planning phase of the experiment. For the data of each participant, a 6 mm radius sphere was slid across the brain image in native space, obtaining for each voxel a vector of neural activations per condition (c1s1, c1s2, c2s1, c2s2). Then, on each voxel we built a 4x4 brain-RDM by estimating the cross-validated Pearson (1 - Pearson) pair-wise correlation across all conditions (c1s1 VS c1s2 VS c2s1 VS c2s2). On each fold of the cross-validation process the dissimilarity estimates were averaged across runs of the training set, and this averaged value was contrasted against the left-out set. The dissimilarity values were averaged across cross-validation folds to obtain the RDM estimate per voxel. We contrasted this "brain-RDM" against two candidate "hypothesis-RDMs" (Figure 3E): an *abstract* RDM that encoded whether the stimuli

mapped to within- or between code contexts, and a *perceptual* RDM that encoded the visual similarity
of the stimuli. To contrast the brain-RDM against each of the hypothesis-RDMs, from each voxel's
RDM we extracted the elements above the matrix diagonal, producing a 6-element vector that was
compared using Spearman's rank correlation to an equivalent 6-element vector extracted from each
hypothesis-RDM. At the group level, for each hypothesis-RDM we performed a one-sample t-test. On
the resulting statistical map, the recommended primary threshold of $p < 0.001$ (Woo et al., 2014) at
the voxel level and a cluster size threshold of 20 voxels to identify clusters with activity patterns
significantly correlated with each hypothesis-RDM. To correct for multiple comparisons, we applied a
familywise error (FWE) cluster correction of $p = 0.05$.

Semi-partial correlation: main task and functional localizers

To inspect how perceptual and abstract representational formats evolved across the planning phase,
we analyzed the brain activity patterns at the beginning and middle time points of the planning phase
focused on the clusters obtained from the cross-decoding analysis (see Results and Figure 3) as
regions of interest (ROIs), as well as additional pre-registered ROIs (see Figure S3). Following a
template tracking procedure (González-García et al., 2021; Palenciano et al., 2023; Wimber et al.,
2015), we estimated semi-partial correlations between the patterns of activity (beta maps) of the main
task in each condition during the planning period, and the patterns of activity of each of the functional
localizers during the planning period (Figure 4A). We used semi-partial correlations to assess the
individual/unique contribution of each representational format (e.g., abstract) with respect to the main
task while partializing out the contribution of the other representational format (e.g., perceptual).

We hypothesized that during the planning phase of the main task, participants initially recalled the
geometric shapes and progressively mapped the presented shapes to their specific codes,
establishing the correct code sequence for that trial. Accordingly, we designed two functional localizer
tasks to capture each of these processes: a *shape* functional localizer (Figure 1C, top) that was
sensitive to the visual properties of the stimuli, and a *code* functional localizer (Figure 1C, bottom) that
required implementing the abstract codes as action sequences.

We predicted that the planning-related activity in the regions of interest would be more correlated with
the shape localizer than with the code localizer at the beginning of the planning phase, whereas the
opposite (higher correlation with the code localizer) would be true during the middle of the planning
phase. To test these predictions we first estimated the semi-partial correlation between each localizer
and the main task while controlling for the influence of the other localizer on the main task, that is, we
correlated the activity patterns of one localizer (e.g., code) with the residuals obtained from regressing
the activity patterns of the other localizer (e.g., shape) onto the activity patterns of the main task. We
then repeated this procedure at each time point (beginning, middle) for each ROI (DMPFC, DLPFC,
and BG clusters). Then, for each ROI, the semi-partial correlation estimates were analyzed via a two-
way repeated measures ANOVA with factors time point (beginning, middle) and localizer (shape,
code). Post-hoc pairwise comparisons of main effects and interactions were further analyzed using
Tukey's Honestly Significant Difference (HSD) tests.

ACKNOWLEDGMENTS

This project was supported by funding from the European Research Council (ERC) under the EU's
Horizon 2020 Research and Innovation Programme (grant agreement no. 787307).

REFERENCES

Abe, M., Hanakawa, T., Takayama, Y., Kuroki, C., Ogawa, S., & Fukuyama, H.
(2007). Functional coupling of human prefrontal and premotor areas during
cognitive manipulation. *The Journal of Neuroscience: The Official Journal of
the Society for Neuroscience*, *27*(13), 3429–3438.
https://doi.org/10.1523/JNEUROSCI.4273-06.2007

Abraham, A., Pedregosa, F., Eickenberg, M., Gervais, P., Mueller, A., Kossaifi, J.,
Gramfort, A., Thirion, B., & Varoquaux, G. (2014). Machine learning for
neuroimaging with scikit-learn. *Frontiers in Neuroinformatics*, *8*.
https://doi.org/10.3389/fninf.2014.00014

Afshar, A., Santhanam, G., Yu, B. M., Ryu, S. I., Sahani, M., & Shenoy, K. V. (2011).
Single-Trial Neural Correlates of Arm Movement Preparation. *Neuron*, *71*(3),
555–564. https://doi.org/10.1016/j.neuron.2011.05.047

Alejandro, R. J., & Holroyd, C. (2024a). *Abstract representations of sequence
planning, execution, and learning*. OSF Registries.
https://doi.org/10.17605/OSF.IO/E58KT

Alejandro, R. J., & Holroyd, C. B. (2024b). Hierarchical control over foraging
behavior by anterior cingulate cortex. *Neuroscience & Biobehavioral Reviews*,
160, 105623. https://doi.org/10.1016/j.neubiorev.2024.105623

Alexander, W. H., & Brown, J. W. (2015). Hierarchical Error Representation: A
Computational Model of Anterior Cingulate and Dorsolateral Prefrontal Cortex.
Neural Computation, *27*(11), 2354–2410.
https://doi.org/10.1162/NECO_a_00779

Avants, B., Epstein, C., Grossman, M., & Gee, J. (2008). Symmetric diffeomorphic
image registration with cross-correlation: Evaluating automated labeling of
elderly and neurodegenerative brain. *Medical Image Analysis*, *12*(1), 26–41.
https://doi.org/10.1016/j.media.2007.06.004

Baladron, J., & Hamker, F. H. (2024). Re-Thinking the Organization of Cortico-Basal

Ganglia-Thalamo-Cortical Loops. *Cognitive Computation*, *16*(5), 2405–2410.

https://doi.org/10.1007/s12559-023-10140-9

Balaguer, J., Spiers, H., Hassabis, D., & Summerfield, C. (2016). Neural

Mechanisms of Hierarchical Planning in a Virtual Subway Network. *Neuron*,

90(4), 893–903. https://doi.org/10.1016/j.neuron.2016.03.037

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects

Models Using **lme4**. *Journal of Statistical Software*, *67*(1).

https://doi.org/10.18637/jss.v067.i01

Behzadi, Y., Restom, K., Liau, J., & Liu, T. T. (2007). A component based noise

correction method (CompCor) for BOLD and perfusion based fMRI.

NeuroImage, *37*(1), 90–101.

https://doi.org/10.1016/j.neuroimage.2007.04.042

Bernardi, S., Benna, M. K., Rigotti, M., Munuera, J., Fusi, S., & Salzman, C. D.

(2020). The Geometry of Abstraction in the Hippocampus and Prefrontal

Cortex. *Cell*, *183*(4), 954-967.e21. https://doi.org/10.1016/j.cell.2020.09.031

Botvinick, M. M. (2008). Hierarchical models of behavior and prefrontal function.

Trends in Cognitive Sciences, *12*(5), 201–208.

https://doi.org/10.1016/j.tics.2008.02.009

Brandi, M.-L., Wohlschläger, A., Sorg, C., & Hermsdörfer, J. (2014). The Neural

Correlates of Planning and Executing Actual Tool Use. *The Journal of*

Neuroscience, *34*(39), 13183–13194.

https://doi.org/10.1523/JNEUROSCI.0597-14.2014

Brunec, I. K., & Momennejad, I. (2022). Predictive Representations in Hippocampal

and Prefrontal Hierarchies. *The Journal of Neuroscience*, *42*(2), 299–312.

https://doi.org/10.1523/JNEUROSCI.1327-21.2021

Bunge, S. A., Hazeltine, E., Scanlon, M. D., Rosen, A. C., & Gabrieli, J. D. E. (2002).

Dissociable Contributions of Prefrontal and Parietal Cortices to Response

Selection. *NeuroImage*, *17*(3), 1562–1571.

https://doi.org/10.1006/nimg.2002.1252

Chang, C.-C., & Lin, C.-J. (2011). LIBSVM: A library for support vector machines.

ACM Transactions on Intelligent Systems and Technology, *2*(3), 1–27.

https://doi.org/10.1145/1961189.1961199

Ciric, R., Thompson, W. H., Lorenz, R., Goncalves, M., MacNicol, E. E., Markiewicz,
C. J., Halchenko, Y. O., Ghosh, S. S., Gorgolewski, K. J., Poldrack, R. A., &
Esteban, O. (2022). TemplateFlow: FAIR-sharing of multi-scale, multi-species
brain models. *Nature Methods*, *19*(12), 1568–1571.
https://doi.org/10.1038/s41592-022-01681-2

Cisek, P., & Kalaska, J. F. (2010). Neural Mechanisms for Interacting with a World
Full of Action Choices. *Annual Review of Neuroscience*, *33*(1), 269–298.
https://doi.org/10.1146/annurev.neuro.051508.135409

Cohen, J. D., Perlstein, W. M., Braver, T. S., Nystrom, L. E., Noll, D. C., Jonides, J.,
& Smith, E. E. (1997). Temporal dynamics of brain activation during a working
memory task. *Nature*, *386*(6625), 604–608. https://doi.org/10.1038/386604a0

Cohen, M. X., & Frank, M. J. (2009). Neurocomputational models of basal ganglia
function in learning, memory and choice. *Behavioural Brain Research*, *199*(1),
141–156. https://doi.org/10.1016/j.bbr.2008.09.029

Cole, M. W., Bagic, A., Kass, R., & Schneider, W. (2010). Prefrontal Dynamics
Underlying Rapid Instructed Task Learning Reverse with Practice. *The*
Journal of Neuroscience, *30*(42), 14245–14254.
https://doi.org/10.1523/jneurosci.1662-10.2010

Coles, M. G. H., Gratton, G., Bashore, T. R., Eriksen, C. W., & Donchin, E. (1985). A
psychophysiological investigation of the continuous flow model of human
information processing. *Journal of Experimental Psychology: Human*
Perception and Performance, *11*(5), 529–553. https://doi.org/10.1037/0096-
1523.11.5.529

Colin, T. R., Ikink, I., & Holroyd, C. B. (2025). Distributed Representations for
Cognitive Control in Frontal Medial Cortex. *Journal of Cognitive*
Neuroscience, *37*(5), 941–969. https://doi.org/10.1162/jocn_a_02285

Collins, A. G. E., & Frank, M. J. (2013). Cognitive control over learning: Creating,
clustering, and generalizing task-set structure. *Psychological Review*, *120*(1),
190–229. https://doi.org/10.1037/a0030852

Correa, C. G., Ho, M. K., Callaway, F., Daw, N. D., & Griffiths, T. L. (2023). Humans
decompose tasks by trading off utility and computational cost. *PLOS*
Computational Biology, *19*(6), e1011087.
https://doi.org/10.1371/journal.pcbi.1011087

Crescentini, C., Seyed-Allaei, S., Vallesi, A., & Shallice, T. (2012). Two networks

involved in producing and realizing plans. *Neuropsychologia*, *50*(7), 1521–

1535. https://doi.org/10.1016/j.neuropsychologia.2012.03.005

Curtis, C. E., & D'Esposito, M. (2003). Persistent activity in the prefrontal cortex

during working memory. *Trends in Cognitive Sciences*, *7*(9), 415–423.

https://doi.org/10.1016/S1364-6613(03)00197-9

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical Surface-Based Analysis.

NeuroImage, *9*(2), 179–194. https://doi.org/10.1006/nimg.1998.0395

Daw, N. D., & Dayan, P. (2014). The algorithmic anatomy of model-based evaluation.

Philosophical Transactions of the Royal Society B: Biological Sciences,

369(1655), 20130478. https://doi.org/10.1098/rstb.2013.0478

Dehaene, S., & Changeux, J.-P. (1997). A hierarchical neuronal network for planning

behavior. *Proceedings of the National Academy of Sciences*, *94*(24), 13293–

13298. https://doi.org/10.1073/pnas.94.24.13293

Duverne, S., & Koechlin, E. (2017). Hierarchical Control of Behaviour in Human

Prefrontal Cortex. In T. Egner (Ed.), *The Wiley Handbook of Cognitive Control*

(1st ed., pp. 207–220). Wiley. https://doi.org/10.1002/9781118920497.ch12

Eckstein, M. K., & Collins, A. G. (2021). How the Mind Creates Structure:

Hierarchical Learning of Action Sequences. *Proceedings of the Annual*

Meeting of the Cognitive Science Society. Annual Meeting of the Cognitive

Science Society. https://escholarship.org/uc/item/4v65s77x

Elsinger, C. L., Harrington, D. L., & Rao, S. M. (2006). From preparation to online

control: Reappraisal of neural circuitry mediating internally generated and

externally guided actions. *NeuroImage*, *31*(3), 1177–1187.

https://doi.org/10.1016/j.neuroimage.2006.01.041

Esteban, O., Markiewicz, C. J., Blair, R. W., Moodie, C. A., Isik, A. I., Erramuzpe, A.,

Kent, J. D., Goncalves, M., DuPre, E., Snyder, M., Oya, H., Ghosh, S. S.,

Wright, J., Durnez, J., Poldrack, R. A., & Gorgolewski, K. J. (2019). fMRIPrep:

A robust preprocessing pipeline for functional MRI. *Nature Methods*, *16*(1),

111–116. https://doi.org/10.1038/s41592-018-0235-4

Esteban, O., Markiewicz, C. J., Burns, C., Goncalves, M., Jarecka, D., Ziegler, E.,

Berleant, S., Ellis, D. G., Pinsard, B., Madison, C., Waskom, M., Notter, M. P.,

Clark, D., Manhães-Savio, A., Clark, D., Jordan, K., Dayan, M., Halchenko, Y.

O., Loney, F., … Ghosh, S. (2022). *Nipype 1.8.3* (Version 1.8.3) [Computer
software]. Zenodo. https://doi.org/10.5281/ZENODO.596855

Fermin, A. S. R., Yoshida, T., Yoshimoto, J., Ito, M., Tanaka, S. C., & Doya, K. (2016).
Model-based action planning involves cortico-cerebellar and basal ganglia
networks. *Scientific Reports*, *6*(1), 31378. https://doi.org/10.1038/srep31378

Fincham, J. M., Carter, C. S., Van Veen, V., Stenger, V. A., & Anderson, J. R. (2002).
Neural mechanisms of planning: A computational analysis using event-related
fMRI. *Proceedings of the National Academy of Sciences*, *99*(5), 3346–3351.
https://doi.org/10.1073/pnas.052703399

Foinikianaki, E., Ikink, I., Colin, T. R., Alejandro, R. J., & Holroyd, C. B. (2025). ACC
representations of reward-driven motivation over hierarchically-organized
behavior. *NeuroImage*, *317*, 121380.
https://doi.org/10.1016/j.neuroimage.2025.121380

Fonov, V., Evans, A., McKinstry, R., Almli, C., & Collins, D. (2009). Unbiased
nonlinear average age-appropriate brain templates from birth to adulthood.
NeuroImage, *47*, S102. https://doi.org/10.1016/S1053-8119(09)70884-5

Frank, M. J., Loughry, B., & O'Reilly, R. C. (2001). Interactions between frontal cortex
and basal ganglia in working memory: A computational model. *Cognitive,
Affective, & Behavioral Neuroscience*, *1*(2), 137–160.
https://doi.org/10.3758/CABN.1.2.137

Fuster, J. M., & Alexander, G. E. (1971). Neuron Activity Related to Short-Term
Memory. *Science*, *173*(3997), 652–654.
https://doi.org/10.1126/science.173.3997.652

Gallivan, J. P., McLean, D. A., Valyear, K. F., Pettypiece, C. E., & Culham, J. C.
(2011). Decoding Action Intentions from Preparatory Brain Activity in Human
Parieto-Frontal Networks. *Journal of Neuroscience*, *31*(26), 9599–9610.
https://doi.org/10.1523/JNEUROSCI.0080-11.2011

Garvert, M. M., Dolan, R. J., & Behrens, T. E. (2017). A map of abstract relational
knowledge in the human hippocampal–entorhinal cortex. *eLife*, *6*, e17086.
https://doi.org/10.7554/eLife.17086

González-García, C., Formica, S., Wisniewski, D., & Brass, M. (2021). Frontoparietal
action-oriented codes support novel instruction implementation. *NeuroImage*,
226, 117608. https://doi.org/10.1016/j.neuroimage.2020.117608

Gorgolewski, K., Burns, C. D., Madison, C., Clark, D., Halchenko, Y. O., Waskom, M. L., & Ghosh, S. S. (2011). Nipype: A Flexible, Lightweight and Extensible Neuroimaging Data Processing Framework in Python. *Frontiers in Neuroinformatics*, *5*. https://doi.org/10.3389/fninf.2011.00013

Gorgolewski, K. J., Alfaro-Almagro, F., Auer, T., Bellec, P., Capotă, M., Chakravarty, M. M., Churchill, N. W., Cohen, A. L., Craddock, R. C., Devenyi, G. A., Eklund, A., Esteban, O., Flandin, G., Ghosh, S. S., Guntupalli, J. S., Jenkinson, M., Keshavan, A., Kiar, G., Liem, F., … Poldrack, R. A. (2017). BIDS apps: Improving ease of use, accessibility, and reproducibility of neuroimaging data analysis methods. *PLOS Computational Biology*, *13*(3), e1005209. https://doi.org/10.1371/journal.pcbi.1005209

Graybiel, A. M. (2000). The basal ganglia. *Current Biology*, *10*(14), R509–R511. https://doi.org/10.1016/S0960-9822(00)00593-5

Greve, D. N., & Fischl, B. (2009). Accurate and robust brain image alignment using boundary-based registration. *NeuroImage*, *48*(1), 63–72. https://doi.org/10.1016/j.neuroimage.2009.06.060

Groenewegen, H. J. (2003). The Basal Ganglia and Motor Control. *Neural Plasticity*, *10*(1–2), 107–120. https://doi.org/10.1155/NP.2003.107

Grossman, C. D., Man, V., & O'Doherty, J. P. (2025). *The representation and valuation of subgoals in the human brain during model-based hierarchical behavior*. https://doi.org/10.1101/2025.03.24.645084

Hall-McMaster, S., Tomov, M. S., Gershman, S. J., & Schuck, N. W. (2025). Neural evidence that humans reuse strategies to solve new tasks. *PLOS Biology*, *23*(6), e3003174. https://doi.org/10.1371/journal.pbio.3003174

Hanakawa, T., Dimyan, M. A., & Hallett, M. (2008). Motor Planning, Imagery, and Execution in the Distributed Motor Network: A Time-Course Study with Functional MRI. *Cerebral Cortex*, *18*(12), 2775–2788. https://doi.org/10.1093/cercor/bhn036

Haynes, J.-D., & Rees, G. (2006). Decoding mental states from brain activity in humans. *Nature Reviews Neuroscience*, *7*(7), 523–534. https://doi.org/10.1038/nrn1931

Hebart, M. N., Görgen, K., & Haynes, J.-D. (2015). The Decoding Toolbox (TDT): A versatile software package for multivariate analyses of functional imaging

data. *Frontiers in Neuroinformatics*, *8*.

https://doi.org/10.3389/fninf.2014.00088

Henderson, M. M., Rademaker, R. L., & Serences, J. T. (2022). Flexible utilization of

spatial- and motor-based codes for the storage of visuo-spatial information.

eLife, *11*, e75688. https://doi.org/10.7554/eLife.75688

Ho, M. K., Abel, D., Correa, C. G., Littman, M. L., Cohen, J. D., & Griffiths, T. L.

(2022). People construct simplified mental representations to plan. *Nature*,

606(7912), 129–136. https://doi.org/10.1038/s41586-022-04743-9

Holroyd, C. B., Ribas-Fernandes, J. J. F., Shahnazian, D., Silvetti, M., & Verguts, T.

(2018). Human midcingulate cortex encodes distributed representations of

task progress. *Proceedings of the National Academy of Sciences*, *115*(25),

6398–6403. https://doi.org/10.1073/pnas.1803650115

Holroyd, C. B., & Verguts, T. (2021). The Best Laid Plans: Computational Principles

of Anterior Cingulate Cortex. *Trends in Cognitive Sciences*, *25*(4), 316–329.

https://doi.org/10.1016/j.tics.2021.01.008

Holroyd, C. B., & Yeung, N. (2012). Motivation of extended behaviors by anterior

cingulate cortex. *Trends in Cognitive Sciences*, *16*(2), 122–128.

https://doi.org/10.1016/j.tics.2011.12.008

Hommel, B., Müsseler, J., Aschersleben, G., & Prinz, W. (2001). The Theory of Event

Coding (TEC): A framework for perception and action planning. *Behavioral*

and Brain Sciences, *24*(5), 849–878.

https://doi.org/10.1017/S0140525X01000103

Hope, R. M. (2012). *Rmisc: Ryan Miscellaneous* (Version R package version 1.5.1)

[Computer software]. https://cran.r-project.org/web/packages/Rmisc

Hoshi, E., & Tanji, J. (2004). Area-Selective Neuronal Activity in the Dorsolateral

Prefrontal Cortex for Information Retrieval and Action Planning. *Journal of*

Neurophysiology, *91*(6), 2707–2722. https://doi.org/10.1152/jn.00904.2003

Huang, Q., & Luo, H. (2024). Shared structure facilitates working memory of multiple

sequences. *eLife*, *12*, RP93158. https://doi.org/10.7554/eLife.93158.3

Huettel, S. A. (2012). Event-related fMRI in cognition. *NeuroImage*, *62*(2), 1152–

1156. https://doi.org/10.1016/j.neuroimage.2011.08.113

Ito, M. (2008). Control of mental activities by internal models in the cerebellum.

Nature Reviews Neuroscience, *9*(4), 304–313.

https://doi.org/10.1038/nrn2332

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved Optimization
for the Robust and Accurate Linear Registration and Motion Correction of
Brain Images. *NeuroImage*, *17*(2), 825–841.
https://doi.org/10.1006/nimg.2002.1132

Kawagoe, R., Takikawa, Y., & Hikosaka, O. (1998). Expectation of reward modulates
cognitive signals in the basal ganglia. *Nature Neuroscience, 1*(5), 411–416.
https://doi.org/10.1038/1625

Klein, A., Ghosh, S. S., Bao, F. S., Giard, J., Häme, Y., Stavsky, E., Lee, N., Rossa,
B., Reuter, M., Chaibub Neto, E., & Keshavan, A. (2017). Mindboggling
morphometry of human brains. *PLOS Computational Biology*, *13*(2),
e1005350. https://doi.org/10.1371/journal.pcbi.1005350

Koechlin, E., Corrado, G., Pietrini, P., & Grafman, J. (2000). Dissociating the role of
the medial and lateral anterior prefrontal cortex in human planning.
Proceedings of the National Academy of Sciences, *97*(13), 7651–7656.
https://doi.org/10.1073/pnas.130177397

Konidaris, G., Kaelbling, L. P., & Lozano-Perez, T. (2018). From Skills to Symbols:
Learning Symbolic Representations for Abstract High-Level Planning. *Journal*
of Artificial Intelligence Research, *61*, 215–289.
https://doi.org/10.1613/jair.5575

Kriegeskorte, N., & Douglas, P. K. (2019). Interpreting encoding and decoding
models. *Current Opinion in Neurobiology*, *55*, 167–179.
https://doi.org/10.1016/j.conb.2019.04.002

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional
brain mapping. *Proceedings of the National Academy of Sciences*, *103*(10),
3863–3868. https://doi.org/10.1073/pnas.0600244103

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational similarity
analysis – connecting the branches of systems neuroscience. *Frontiers in*
Systems Neuroscience. https://doi.org/10.3389/neuro.06.004.2008

Kruggel, F., & Von Cramon, D. Y. (1999). Temporal properties of the hemodynamic
response in functional MRI. *Human Brain Mapping*, *8*(4), 259–271.
https://doi.org/10.1002/(SICI)1097-0193(1999)8:4<259::AID-HBM9>3.0.CO;2-
K

Kubota, K., & Niki, H. (1971). Prefrontal cortical unit activity and delayed alternation performance in monkeys. *Journal of Neurophysiology*, *34*(3), 337–347. https://doi.org/10.1152/jn.1971.34.3.337

Lazeron, R. H. C., Rombouts, S. A. R. B., Machielsen, W. C. M., Scheltens, P., Witter, M. P., Uylings, H. B. M., & Barkhof, F. (2000). Visualizing Brain Activation during Planning: The Tower of London Test Adapted for Functional MR Imaging. *American Journal of Neuroradiology*, *21*(8), 1407.

Lee, W.-T., Hazeltine, E., & Jiang, J. (2022). Interference and integration in hierarchical task learning. *Journal of Experimental Psychology: General*, *151*(12), 3028–3044. https://doi.org/10.1037/xge0001246

Lee, W.-T., Hazeltine, E., & Jiang, J. (2024). *Decoding task representations that support generalization in hierarchical task*. https://doi.org/10.1101/2024.12.02.626403

Lenth, R. V., Banfai, B., Bolker, B., Buerkner, P., Giné-Vázquez, I., Herve, M., Jung, M., Love, J., Miguez, F., Piaskowski, J., Riebl, H., & Singmann, H. (2017). *emmeans: Estimated Marginal Means, aka Least-Squares Means* (p. 1.10.7) [Computer software]. https://CRAN.R-project.org/package=emmeans

Liang, Q., Li, J., Zheng, S., Liao, J., & Huang, R. (2022). Dynamic Causal Modelling of Hierarchical Planning. *NeuroImage*, *258*, 119384. https://doi.org/10.1016/j.neuroimage.2022.119384

Markiewicz, C. J., Esteban, O., Goncalves, M., Provins, C., Salo, T., Kent, J. D., DuPre, E., Ciric, R., Pinsard, B., Blair, R. W., Poldrack, R. A., & Gorgolewski, K. J. (2024). *fMRIPrep* (Version 24.1.1) [Computer software]. Zenodo. https://doi.org/10.5281/ZENODO.852659

Mattar, M. G., & Lengyel, M. (2022). Planning in the brain. *Neuron*, *110*(6), 914–934. https://doi.org/10.1016/j.neuron.2021.12.018

Mian, M. K., Sheth, S. A., Patel, S. R., Spiliopoulos, K., Eskandar, E. N., & Williams, Z. M. (2014). Encoding of rules by neurons in the human dorsolateral prefrontal cortex. *Cerebral Cortex*, *24*(3), 807–816. https://doi.org/10.1093/cercor/bhs361

Miller, E. K., & Buschman, T. J. (2008). Rules through recursion: How interactions between the frontal cortex and basal ganglia may build abstract, complex rules from concrete, simple ones. *Neuroscience of Rule-Guided Behavior*, 419–440.

Miller, G. A., Galanter, E., & Pribram, K. H. (1960). *Plans and the structure of*
behavior. Henry Holt and Co. https://doi.org/10.1037/10039-000

Momennejad, I., & Haynes, J.-D. (2012). Human anterior prefrontal cortex encodes
the 'what' and 'when' of future intentions. *NeuroImage*, *61*(1), 139–148.
https://doi.org/10.1016/j.neuroimage.2012.02.079

Momennejad, I., & Haynes, J.-D. (2013). Encoding of Prospective Tasks in the
Human Prefrontal Cortex under Varying Task Loads. *The Journal of*
Neuroscience, *33*(44), 17342–17349.
https://doi.org/10.1523/JNEUROSCI.0492-13.2013

Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., & Kriegeskorte, N.
(2014). A Toolbox for Representational Similarity Analysis. *PLoS*
Computational Biology, *10*(4), e1003553.
https://doi.org/10.1371/journal.pcbi.1003553

Norman, K. A., Polyn, S. M., Detre, G. J., & Haxby, J. V. (2006). Beyond mind-
reading: Multi-voxel pattern analysis of fMRI data. *Trends in Cognitive*
Sciences, *10*(9), 424–430. https://doi.org/10.1016/j.tics.2006.07.005

Palenciano, A. F., Senoussi, M., Formica, S., & González-García, C. (2023).
Canonical template tracking: Measuring the activation state of specific neural
representations. *Frontiers in Neuroimaging*, *1*, 974927.
https://doi.org/10.3389/fnimg.2022.974927

Papitto, G., Friederici, A. D., & Zaccarella, E. (2024). Distinct neural mechanisms for
action access and execution in the human brain: Insights from an fMRI study.
Cerebral Cortex, *34*(4), bhae163. https://doi.org/10.1093/cercor/bhae163

Patriat, R., Reynolds, R. C., & Birn, R. M. (2017). An improved model of motion-
related signal changes in fMRI. *NeuroImage*, *144*, 74–82.
https://doi.org/10.1016/j.neuroimage.2016.08.051

Pochon, J.-B. (2001). The Role of Dorsolateral Prefrontal Cortex in the Preparation
of Forthcoming Actions: An fMRI Study. *Cerebral Cortex*, *11*(3), 260–266.
https://doi.org/10.1093/cercor/11.3.260

Postle, B. R., Berger, J. S., & D'Esposito, M. (1999). Functional neuroanatomical
double dissociation of mnemonic and executive control processes contributing
to working memory performance. *Proceedings of the National Academy of*
Sciences, *96*(22), 12959–12964. https://doi.org/10.1073/pnas.96.22.12959

Power, J. D., Mitra, A., Laumann, T. O., Snyder, A. Z., Schlaggar, B. L., & Petersen,
S. E. (2014). Methods to detect, characterize, and remove motion artifact in
resting state fMRI. *NeuroImage*, *84*, 320–341.
https://doi.org/10.1016/j.neuroimage.2013.08.048

Redgrave, P., Rodriguez, M., Smith, Y., Rodriguez-Oroz, M. C., Lehericy, S.,
Bergman, H., Agid, Y., DeLong, M. R., & Obeso, J. A. (2010). Goal-directed
and habitual control in the basal ganglia: Implications for Parkinson's disease.
Nature Reviews Neuroscience, *11*(11), 760–772.
https://doi.org/10.1038/nrn2915

Reverberi, C., Görgen, K., & Haynes, J.-D. (2012). Compositionality of Rule
Representations in Human Prefrontal Cortex. *Cerebral Cortex*, *22*(6), 1237–
1246. https://doi.org/10.1093/cercor/bhr200

Rosenbaum, D. A. (1980). Human movement initiation: Specification of arm,
direction, and extent. *Journal of Experimental Psychology: General*, *109*(4),
444–474. https://doi.org/10.1037/0096-3445.109.4.444

Rosenbaum, D. A., Kenny, S. B., & Derr, M. A. (1983). Hierarchical control of rapid
movement sequences. *Journal of Experimental Psychology: Human*
Perception and Performance, *9*(1), 86–102. https://doi.org/10.1037/0096-
1523.9.1.86

Rousseau, C., Barbiero, M., Pozzo, T., Papaxanthis, C., & White, O. (2021). Actual
and Imagined Movements Reveal a Dual Role of the Insular Cortex for Motor
Control. *Cerebral Cortex*, *31*(5), 2586–2594.
https://doi.org/10.1093/cercor/bhaa376

Rowe, J. B., Owen, A. M., Johnsrude, I. S., & Passingham, R. E. (2001). Imaging the
mental components of a planning task. *Neuropsychologia*, *39*(3), 315–327.
https://doi.org/10.1016/S0028-3932(00)00109-3

Ruge, H., Müller, S. C., & Braver, T. S. (2010). Anticipating the consequences of
action: An fMRI study of intention-based task preparation: Anticipating the
consequences of action. *Psychophysiology*, no-no.
https://doi.org/10.1111/j.1469-8986.2010.01027.x

Sakai, K., & Passingham, R. E. (2003). Prefrontal interactions reflect future task
operations. *Nature Neuroscience*, *6*(1), 75–81. https://doi.org/10.1038/nn987

Sakai, K., & Passingham, R. E. (2006). Prefrontal Set Activity Predicts Rule-Specific
Neural Processing during Subsequent Cognitive Performance. *The Journal of*

Neuroscience, *26*(4), 1211–1218. https://doi.org/10.1523/jneurosci.3887-05.2006

Sakai, K., Rowe, J. B., & Passingham, R. E. (2002). Active maintenance in prefrontal area 46 creates distractor-resistant memory. *Nature Neuroscience*, *5*(5), 479–484. https://doi.org/10.1038/nn846

Samejima, K., Ueda, Y., Doya, K., & Kimura, M. (2005). Representation of Action-Specific Reward Values in the Striatum. *Science*, *310*(5752), 1337–1340. https://doi.org/10.1126/science.1115270

Satterthwaite, T. D., Elliott, M. A., Gerraty, R. T., Ruparel, K., Loughead, J., Calkins, M. E., Eickhoff, S. B., Hakonarson, H., Gur, R. C., Gur, R. E., & Wolf, D. H. (2013). An improved framework for confound regression and filtering for control of motion artifact in the preprocessing of resting-state functional connectivity data. *NeuroImage*, *64*, 240–256. https://doi.org/10.1016/j.neuroimage.2012.08.052

Scholz, V. H., Flaherty, A. W., Kraft, E., Keltner, J. R., Kwong, K. K., Chen, Y. I., Rosen, B. R., & Jenkins, B. G. (2000). Laterality, somatotopy and reproducibility of the basal ganglia and motor cortex during motor tasks11Published on the World Wide Web on 28 August 2000. *Brain Research*, *879*(1–2), 204–215. https://doi.org/10.1016/S0006-8993(00)02749-9

Schumacher, E. H., & D'Esposito, M. (2002). Neural implementation of response selection in humans as revealed by localized effects of stimulus–response compatibility on brain activation. *Human Brain Mapping*, *17*(3), 193–201. https://doi.org/10.1002/hbm.10063

Sheahan, H., Luyckx, F., Nelli, S., Teupe, C., & Summerfield, C. (2021). Neural state space alignment for magnitude generalization in humans and recurrent networks. *Neuron*, *109*(7), 1214-1226.e8. https://doi.org/10.1016/j.neuron.2021.02.004

Simon, D. A., & Daw, N. D. (2011). Neural Correlates of Forward Planning in a Spatial Decision Task in Humans. *The Journal of Neuroscience*, *31*(14), 5526–5539. https://doi.org/10.1523/JNEUROSCI.4647-10.2011

Skorstad, J., Genter, D., & Medin, D. (1988). Abstraction Processes during Concept Learning: A Structural view. *Proceedings of the Annual Meeting of the*

Cognitive Science Society, *10*.

https://escholarship.org/uc/item/9mg8p8hp#author

Tanaka, M., Kunimatsu, J., Suzuki, T. W., Kameda, M., Ohmae, S., Uematsu, A., &

Takeya, R. (2021). Roles of the Cerebellum in Motor Preparation and

Prediction of Timing. *Neuroscience*, *462*, 220–234.

https://doi.org/10.1016/j.neuroscience.2020.04.039

Theves, S. (2025). Thinking as Analogy-Making: Toward a Neural Process Account

of General Intelligence. *The Journal of Neuroscience*, *45*(18), e1555242025.

https://doi.org/10.1523/JNEUROSCI.1555-24.2025

Theves, S., Neville, D. A., Fernández, G., & Doeller, C. F. (2021). Learning and

Representation of Hierarchical Concepts in Hippocampus and Prefrontal

Cortex. *The Journal of Neuroscience*, *41*(36), 7675–7686.

https://doi.org/10.1523/JNEUROSCI.0657-21.2021

Tolman, E. C. (1948). Cognitive maps in rats and men. *Psychological Review*, *55*(4),

189–208. https://doi.org/10.1037/h0061626

Tomov, M. S., Yagati, S., Kumar, A., Yang, W., & Gershman, S. J. (2020). Discovery

of hierarchical representations for efficient planning. *PLOS Computational*

Biology, *16*(4), e1007594. https://doi.org/10.1371/journal.pcbi.1007594

Tosoni, A., Corbetta, M., Calluso, C., Committeri, G., Pezzulo, G., Romani, G. L., &

Galati, G. (2014). Decision and action planning signals in human posterior

parietal cortex during delayed perceptual choices. *European Journal of*

Neuroscience, *39*(8), 1370–1383. https://doi.org/10.1111/ejn.12511

Tricomi, E., Balleine, B. W., & O'Doherty, J. P. (2009). A specific role for posterior

dorsolateral striatum in human habit learning. *European Journal of*

Neuroscience, *29*(11), 2225–2232. https://doi.org/10.1111/j.1460-

9568.2009.06796.x

Turella, L., Rumiati, R., & Lingnau, A. (2020). Hierarchical Action Encoding Within the

Human Brain. *Cerebral Cortex*, *30*(5), 2924–2938.

https://doi.org/10.1093/cercor/bhz284

Tustison, N. J., Avants, B. B., Cook, P. A., Yuanjie Zheng, Egan, A., Yushkevich, P.

A., & Gee, J. C. (2010). N4ITK: Improved N3 Bias Correction. *IEEE*

Transactions on Medical Imaging, *29*(6), 1310–1320.

https://doi.org/10.1109/TMI.2010.2046908

1331 Umemoto, A., HajiHosseini, A., Yates, M. E., & Holroyd, C. B. (2017). Reward-based

1332   contextual learning supported by anterior cingulate cortex. *Cognitive,*

1333   *Affective, & Behavioral Neuroscience*, *17*(3), 642–651.

1334   https://doi.org/10.3758/s13415-017-0502-3

1335 Unterrainer, J. M., & Owen, A. M. (2006). Planning and problem solving: From

1336   neuropsychology to functional neuroimaging. *Journal of Physiology-Paris*,

1337   *99*(4–6), 308–317. https://doi.org/10.1016/j.jphysparis.2006.03.014

1338 Vaidya, A. R., & Badre, D. (2022). Abstract task representations for inference and

1339   control. *Trends in Cognitive Sciences*, S1364661322000675.

1340   https://doi.org/10.1016/j.tics.2022.03.009

1341 Vallesi, A., McIntosh, A. R., Shallice, T., & Stuss, D. T. (2009). When Time Shapes

1342   Behavior: fMRI Evidence of Brain Correlates of Temporal Monitoring. *Journal*

1343   *of Cognitive Neuroscience*, *21*(6), 1116–1126.

1344   https://doi.org/10.1162/jocn.2009.21098

1345 Van Den Heuvel, O. A., Groenewegen, H. J., Barkhof, F., Lazeron, R. H. C., Van

1346   Dyck, R., & Veltman, D. J. (2003). Frontostriatal system in planning

1347   complexity: A parametric functional magnetic resonance version of tower of

1348   london task. *NeuroImage*, *18*(2), 367–374. https://doi.org/10.1016/S1053-

1349   8119(02)00010-1

1350 Verwey, W. B. (1996). Buffer loading and chunking in sequential keypressing. *Journal*

1351   *of Experimental Psychology: Human Perception and Performance*, *22*(3),

1352   544–562. https://doi.org/10.1037/0096-1523.22.3.544

1353 Wagner, G., Koch, K., Reichenbach, J. R., Sauer, H., & Schlösser, R. G. M. (2006).

1354   The special involvement of the rostrolateral prefrontal cortex in planning

1355   abilities: An event-related fMRI study with the Tower of London paradigm.

1356   *Neuropsychologia*, *44*(12), 2337–2347.

1357   https://doi.org/10.1016/j.neuropsychologia.2006.05.014

1358 Wientjes, S., & Holroyd, C. B. (2024). The successor representation subserves

1359   hierarchical abstraction for goal-directed behavior. *PLOS Computational*

1360   *Biology*, *20*(2), e1011312. https://doi.org/10.1371/journal.pcbi.1011312

1361 Wimber, M., Alink, A., Charest, I., Kriegeskorte, N., & Anderson, M. C. (2015).

1362   Retrieval induces adaptive forgetting of competing memories via cortical

1363   pattern suppression. *Nature Neuroscience*, *18*(4), 582–589.

1364   https://doi.org/10.1038/nn.3973

Woo, C.-W., Krishnan, A., & Wager, T. D. (2014). Cluster-extent based thresholding
in fMRI analyses: Pitfalls and recommendations. *NeuroImage*, *91*, 412–419.
https://doi.org/10.1016/j.neuroimage.2013.12.058

Xia, L., & Collins, A. G. E. (2021). Temporal and state abstractions for efficient
learning, transfer, and composition in humans. *Psychological Review*, *128*(4),
643–666. https://doi.org/10.1037/rev0000295

Yewbrey, R., Mantziara, M., & Kornysheva, K. (2023). Cortical Patterns Shift from
Sequence Feature Separation during Planning to Integration during Motor
Execution. *The Journal of Neuroscience*, *43*(10), 1742–1756.
https://doi.org/10.1523/JNEUROSCI.1628-22.2023

Ying, L., Collins, K. M., Sharma, P., Colas, C., Zhao, K. I., Weller, A., Tavares, Z.,
Isola, P., Gershman, S. J., Andreas, J. D., Griffiths, T. L., Chollet, F., Allen, K.
R., & Tenenbaum, J. B. (2025). *Assessing Adaptive World Models in*
Machines with Novel Games (Version 2). arXiv.
https://doi.org/10.48550/ARXIV.2507.12821

Zarr, N., & Brown, J. W. (2016). Hierarchical error representation in medial prefrontal
cortex. *NeuroImage*, *124*, 238–247.
https://doi.org/10.1016/j.neuroimage.2015.08.063

Zhang, Y., Brady, M., & Smith, S. (2001). Segmentation of brain MR images through
a hidden Markov random field model and the expectation-maximization
algorithm. *IEEE Transactions on Medical Imaging*, *20*(1), 45–57.
https://doi.org/10.1109/42.906424

Zwiers, M. P., Moia, S., & Oostenveld, R. (2022). BIDScoin: A User-Friendly
Application to Convert Source Data to Brain Imaging Data Structure. *Frontiers*
in Neuroinformatics, *15*, 770608. https://doi.org/10.3389/fninf.2021.770608

1390

1391

1392

1393

SUPPLEMENTAL INFORMATION

1395   **Table S1. Stimuli for task "catch" trials**

Stimuli	Code shape | color | shape | color	Stimuli	Code shape | color | shape | color
	####		&###
	###&		&#&#
	###&		&#&&
	##&#		&&##
	#&##		&&#&
	#&#&		&&&#
	#&&&		&&&&

1396
1397
1398
1399

1400

1401 **Table S2. Reaction time analysis – main fMRI task**

1402 Results of the Reaction Time (RT) analysis of the behavioral data during the fMRI task. Factors were

1403 sequence step (1, 2, 3, 4), planning duration (short, medium, long), and their interaction.

	Sum Sq	Mean Sq	NumDF	DenDF	F value	Pr(>F)
step	1418.81	472.94	3	32907	24256.561	< 2.2e-16
plan duration	1.47	0.73	2	32908	37.644	< 2.2e-16
step:plan duration	6.51	1.09	6	32907	55.691	< 2.2e-16

1404

1405 **Table S3. Post-hoc pairwise differences – main fMRI task**

1406 Subsequent post-hoc (Tukey HSD) tests performed to identify the direction of significant effects and

1407 interactions from the RT analysis of the behavioral data during the fMRI task.

contrast	estimate	SE	df	t.ratio	p.value
Main effect: sequence step					
step1 - step2	0.45770	0.00218	32907	210.402	**<.0001**
step1 - step3	0.46169	0.00218	32907	212.236	**<.0001**
step1 - step4	0.51072	0.00218	32907	234.778	**<.0001**
step2 - step3	0.00399	0.00218	32907	1.833	0.2576
step2 - step4	0.05302	0.00218	32907	24.375	**<.0001**
step3 - step4	0.04904	0.00218	32907	22.542	**<.0001**
Main effect: plan duration					
long - med	-0.00685	0.00189	32907	-3.625	**0.0008**
long - short	-0.01629	0.00189	32908	-8.633	**<.0001**
med - short	-0.00944	0.00189	32908	-5.034	**<.0001**
Interaction: sequence step X plan duration					
step = 1:					
long - med	-0.031884	0.00378	32907	-8.434	**<.0001**
long - short	-0.075597	0.00377	32907	-20.032	**<.0001**
med - short	-0.043713	0.00375	32907	-11.658	**<.0001**
step = 2:					
long - med	0.003342	0.00378	32907	0.884	0.6504
long - short	0.007083	0.00377	32907	1.877	0.1454
med - short	0.003741	0.00375	32907	0.998	0.5783
step = 3:					
long - med	0.001336	0.00378	32907	0.353	0.9334
long - short	0.002837	0.00377	32907	0.752	0.7325
med - short	0.001501	0.00375	32907	0.400	0.9155
step = 4:					
long - med	-0.000210	0.00378	32907	-0.056	0.9983
long - short	0.000508	0.00377	32907	0.135	0.9901
med - short	0.000718	0.00375	32907	0.191	0.9800

1408 **Figure S1. Reaction time (RT) results – behavioral training.**

1409
1410 Horizontal lines represent post-hoc pairwise comparisons following the main effect of sequence step

1411 on RT. Bold black line represents the average RT across participants, gray lines represent individual

1412 participants. Asterisks denote statistical significance at p < 0.0001.

1413

1414 **Figure S2. Post-hoc pairwise difference for the main effect of plan duration – main fMRI task.**

1415

1416

 Table S4. Activation value maps for the Multivariate Pattern Analyses.

1418 Activation values for key brain regions (clusters) identified during multivariate analyses: searchlight

1419 cross-decoding from planning to execution, and searchlight RSA comparing all 4 conditions during the

1420 planning phase.

Region	voxels	Peak t	MNI coords (peak)			Cluster p
			x	y	z	
Searchlight-cross-decoding planning -> execution (abstract)						
Lenticular nucleus, Pallidum, left Lenticular nucleus, Putamen, left	29	5.49	-26	-14	-4	0.071 (uncorr.)
Superior frontal gyrus, medial, right Medial frontal gyrus, right	26	4.22	10	46	40	0.098 (uncorr.)
Middle frontal gyrus, left	24	3.94	-48	30	30	0.098
Inferior frontal gyrus, triangular part, left		3.60	-42	36	24	(uncorr.)
Searchlight-cross-decoding planning -> execution (perceptual)						
Calcarine fissure and surrounding cortex, right	107	4.80	4	-76	10	0.046
Calcarine fissure and surrounding cortex, left		4.04	-10	-76	10	(uncorr.)
Searchlight-RSA, planning (abstract)						
Superior frontal gyrus, medial, right	46	4.27	3	38	44	
Medial frontal gyrus, right		3.91	6	47	44	0.014
Superior frontal gyrus, medial, left Medial frontal gyrus, left		4.23	-3	50	44	(FWE)
Searchlight-RSA, planning (perceptual)						
Middle occipital gyrus, left Superior occipital gyrus, left	120	6.12	-18	-91	1	
Inferior occipital gyrus, left Calcarine fissure and surrounding cortex, left Lingual gyrus, left Fusiform gyrus, left		4.66	-12	-97	11	0.000 (FWE)

1421 **Figure S3. ROI analyses.**

1422
A. ROI selection. As pre-registered, we ran follow-up analyses in specific regions of interest (ROI) for
two reasons: 1) our main hypothesis specified that a higher-order context will be represented in
planning-related regions, and 2) previous literature has shown that decoding analyses tend to be
relatively stringent, especially with regards to information in prefrontal cortex (Bhandari et al., 2018).
We selected planning-related ROIs located in: (rostral) anterior cingulate cortex (ACC), ventrolateral
prefrontal cortex (VLPFC), dorsolateral prefrontal cortex (DLPFC), posterior parietal cortex (PPC),
hippocampus (HPC), and early visual cortex (EVC) as control region. First, a binary mask of each
anatomical region was defined, extracted, and combined using the WFU pickatlas software (version
3.0.5; Maldjian et al., 2003). Second, from the metanalytical tool Neurosynth
(https://neurosynth.org/analyses/), we extracted the resulting (FDR-corrected) masks from the search
terms "working memory", "episodic memory", "planning", "execution", "decision", and "visual." These
metaanalytically-defined masks were binarized and combined into one single aggregate mask. Finally,
each anatomically-defined ROI mask was intersected with the aggregate mask, resulting in 6 ROIs.
Each ROI mask was registered back to each subject's native space via estimation of inverse
deformation fields. **B. ROI-decoding results.** Decoding was significantly above chance for VLPFC. **C.**
Semi-partial correlation results. Abstract representations increased significantly from the beginning
to the middle of planning in DLPFC, HPC, PPC, and VLPFC. Perceptual representations increased
significantly from the beginning to the middle of planning in DLPFC and PPC. The dynamics between
abstract and perceptual representations were significantly different only for VLPFC. ROI-RSA results
were not significant in any of the ROIs.

1443

1444

SUPPLEMENTARY REFERENCES

Bhandari, A., Gagne, C., & Badre, D. (2018). Just above Chance: Is It Harder to Decode Information from Prefrontal Cortex Hemodynamic Activity Patterns? *Journal of Cognitive Neuroscience*, *30*(10), 1473–1498. https://doi.org/10.1162/jocn_a_01291

Maldjian, J. A., Laurienti, P. J., Kraft, R. A., & Burdette, J. H. (2003). An automated method for neuroanatomic and cytoarchitectonic atlas-based interrogation of fMRI data sets. *NeuroImage*, *19*(3), 1233–1239. https://doi.org/10.1016/S1053-8119(03)00169-1