Mirror manifolds: partially overlapping neural subspaces for speaking and listening

Ana G. Chavez[1], Melissa Franch[1], Elizabeth A. Mickiewicz[1], Will Baltazar[1], James L. Belanger[1], Davin Devara[1], Maya Etta[1], Thomas Hamre[1], Taha Ismail[1], Brad Joiner[1], Yoon Kim[1], Abhinav Kona[1], Kasra Mansourian[1], Amy Nangia[1], Molly Pluenneke[1], Sarah Soubra[1], Thara Venkateswaran[1], Karthik Venkudusamy[1], Assia Chericoni[1], Katherine E. Kabotyanski[1], Kalman A. Katlowitz[1], Raissa K. Mathura[1], Danika L. Paulo[1], Xinyuan Yan[1], Hanlin Zhu[1], Eleonora Bartoli[1], Nicole R. Provenza[1,2], Andrew Watrous[1], Krešimir Josíc[3], Sameer A. Sheth[1,2], and Benjamin Y. Hayden[1,2]

[1] Neurosurgery, Baylor College of Medicine
[2] Neuroengineering Initiative, Rice University
[3] Departments of Mathematics, Biology and Biochemistry, University of Houston

Correspondence: Benjamin.Hayden@bcm.edu

Funding statement

This research was supported by the McNair Foundation and by NIH R01 MH129439, U01 NS121472, NINDS Research Education Grant Programs for Residents and Fellows in Neurology, Neurosurgery, Neuropathology, and Neuroradiology (UE5), the SNS Allan Friedman RUNN Research Grant, the NLM Training Program in Biomedical Informatics & Data Science for Predoctoral & Postdoctoral Fellows, T15LM007093-33

Competing interests

S.A.S has consulting agreements with Boston Scientific, Zimmer Biomet, Koh Young, and Neuropace. SAS is Co-founder of Motif Neurotech

Acknowledgements

We thank Joshua Adkinson, Justin Fine, Victoria Gates, Suzanne Kemmer, George Kokalas, and Steven Piantadosi for invaluable assistance.

ABSTRACT

Participants in conversations need to associate words with their speakers but also retain those words' general meanings. For example, someone talking about their hand is not referring to the other speaker's hand, but the word "*hand*" still carries speaker-general information (e.g., having five fingers). These two requirements impose a cross-speaker generalization / differentiation dilemma that is not well addressed by existing theories. We hypothesized that the brain resolves the dilemma by use of a vectorial semantic code that blends collinear and orthogonal coding subspaces. To test this hypothesis, we examined semantic encoding in populations of hippocampal single neurons recorded during conversations between epilepsy patients and healthy partners in the epilepsy monitoring unit (EMU). We found clear semantic encoding for both spoken and heard words, with strongest encoding just around the time of utterance for production, and just after it for reception. Crucially, hippocampal neurons' codes for word meaning were poised between orthogonalized and collinearized. Moreover, different semantic categories were orthogonalized to different degrees; body parts and names were most differentiated between speakers; function words and verbs were least differentiated. Finally, the hippocampus used the same coding principle to separate different partners in three-person conversations, with greater orthogonalization between self and other than between two others. Together, these results suggest a new solution to the problem of binding word meanings with speaker identity.

INTRODUCTION

When we converse, we take turns between listening and speaking. That back-and-forth raises an important mirroring problem for neural representations of meaning. When we say or hear a word, we must understand its general meaning, regardless of its speaker; at the same time, we must be able to associate the meaning to the speaker who said it. That in turn influences how we interpret the word. Someone saying "*my sister*" is typically referring to a different person than the conversation partner's sister. However, sisters have some features in common, and speakers need access to general cross-personal representations. Likewise, "*moon*" might mean something different if we are talking to an astronaut or a poet. The need for flexibility raises a generalization / differentiation dilemma for semantic representations. That dilemma is not readily accounted for in standard neural theories of representation, which emphasize the cross-modal aspect of meaning while ignoring the modality-specific aspect. Moreover, the degree of generalization / differentiation may vary by word; a "*leg*" is usually unique to one person; a "*cloud*" is not. The problem of cross-speaker generalization is addressed by mirror neuron theory, which proposes specialized neurons that have identical responses during production and reception of meaning (Arbib, 2005; Corballis, 2010; Rizzolati and Arbib, 1998; Rizzolatti and Craighero, 2004). Aside from its known empirical limitations (Hickok, 2010 and 2014; Heyes and Catmur, 2022), mirror neuron theory resolves only one horn of this generalization / differentiation dilemma.

Recent advances in the topology of multi-neuronal representation offer a potential solution to this dilemma (Barak et al., 2013; Bernardi et al., 2020). Specially constructed neural codes that blend features of collinear codes (which allow for generalization) and orthogonal codes (which allow for differentiation) can have the virtues of both. These semi-orthogonal codes, in other words, resolve the generalization / differentiation dilemma because they allow for simultaneous cross-conditional generalization and differentiation. Populations of neurons with these properties have been found in in complex decision-making tasks (Bernardi et al., 2020), in memory-based decision tasks (Libby and Buschman, 2021; Tian et al., 2024; Tang et al., 2020), and in value-coding regions during choice (Fine et al., 2023; Johnston et al., 2024; Yoo and Hayden, 2020). Here we propose the same principles apply to representations of semantic meaning across speakers during conversations. Because our proposal involves a solution to the mirroring problem using a high dimensional space along which neuronal activity is found (a

manifold, Perich et al., 2025), we call it the *mirror manifold hypothesis*. Critically, while the

mirror neuron hypothesis only solves the generalization problem, the mirror manifold

hypothesis, which leverages the expressive power of neural populations, can also solve the

differentiation problem.

The mirror manifold hypothesis relies on the principle that semantic encoding is

vectorized. We have previously shown that, during passive speech listening, hippocampal

neurons encode word meanings in distributed patterns of activation, which we have argued is a

vectorial coding (Franch et al., 2025; Katlowitz et al., 2025). Indeed, we found that responses of

neural populations to semantically similar words are, themselves, similar, suggesting that

populations of hippocampal neurons instantiate a semantic embedding space. These patterns are

reminiscent of the manner that word meanings are encoded in Large Language Models (LLMs,

e.g., Devlin et al., 2019; Mikolov et al., 2013). Previous theoretical work highlights the benefits

of vectorial representations for cognitive processes like similarity judgment, analogy, and

hierarchical reasoning (Piantadosi et al., 2024). Here we propose another benefit to vectorial

representations of meaning, namely, that they endow populations with the ability to solve the

generalization / differentiation dilemma imposed by conversational speech.

We were particularly interested in the hippocampus due to its demonstrated role in

conceptual representations, as well as generalization and relational reasoning (Bakermans et al,

2025; Bakker et al., 2008; Bernardi et al. 2020; Courellis et al., 2024; Leutgeb et al., 2005).

These are complemented by its established role in language, including both semantics and

grammar (Binder et al., 2009; Brown-Schmidt et al., 2001; Dijksterhuis et al., 2024; Duff and

Brown-Schmidt, 2012; Franch et al., 2025; Katlowitz et al., 2025; Piai et al., 2016; Van de Ven

et al., 2020), and its clear role in identity assignment (Danjo et al., 2018; Montagrin et al., 2018;

Rey et al., 2020; Tavares et al., 2015). We analyzed speech data collected during unconstrained

conversations between patients in the epilepsy monitoring unit (EMU) and members of their

family or our research team. We transcribed conversations and computed their semantic

embeddings using BERT with speaker tokenization. We aligned each word to firing rates of

neurons in the hippocampus and used neural responses to estimate semantic tuning. We found

clear encoding of lexical semantics for both production and reception, with strongest encoding

around the time of utterance for production, and immediately after it for reception. Critically,

tuning functions differed systematically for speaking and listening. Specifically, they reflected

the specific blend of orthogonal and collinear codes that would allow for an efficient solution to

the generalization / differentiation problem. Moreover, the degree of orthogonalization varied

consistently with semantic category: categories with the greatest generalization included function

words and personal pronouns; categories with greatest differentiation included body parts and

proper nouns. Finally, the hippocampus used the same coding principle to separate different

partners in three-person conversations, with greater rotation between self and other than between

two others.

RESULTS

Ten native English-speaking patients undergoing neural monitoring for epilepsy participated in unstructured conversations in the epilepsy monitoring unit (EMU) at Baylor St. Luke's Hospital. All patients had multiple Behnke-Fried electrodes placed in the hippocampus for surgical monitoring (**Figure 1A**). Word counts across all conversations spanned from 720 to 8260 total words (mean: 2042 words). Conversations involved either two (n=3/10) or three-plus (7/10) total participants. Aside from the patient, the other participants were either laboratory members or family members. Conversations were recorded with a directed microphone (Blue Yeti) pointed at the patient and a lavalier microphone (WAYVOSE) on the lapel of the speech partner. All conversation audio streams were recorded directly into the Blackrock recording system, resulting in temporal alignment between speech and neural activity.

To identify speech content, we used a combination of automated transcription and diarization with manual correction (**Figure 1B**). Specifically, we began with speech audio files and passed them to two distinct software systems, a lexical decoder/encoder (such as WhisperX), which identified the words that were spoken and their precise onset and offset times, and, in parallel, a diarizer (Pyannote), which identified who was speaking. However, we found that the quality of transcription and diarization were not accurate enough for neural analysis. Thus, specially trained lab members used Praat, a linguistic annotation software for speech analysis (Boersma and Weenink, 2001) to carefully correct both transcription and diarization outputs. That process took roughly one hour per minute of conversation. Finally, all files were manually re-checked and further fixed by first author AGC.

Conversations in the EMU were typical of those observed in other contexts. For example, conversations consisted of short speech turns consisting of a small number of words (median: 3 words; mean: 9 words for spoken, median: 3 words; mean: 10 words for heard. **Figure 1C and D**). Speakers spoke at a rate of 207-261 words/minute. Word lengths ranged from less than 100 ms to almost a full second (**Figure 1E**). Each participants' speech corpus consisted of an average of 1120 words (**Figure 1F**) and included 325 unique words per patient. Partners' speech turns consisted of an average of 3178 words (**Figure 1F**), including 644 unique words shared across speakers. Across all

ten conversations, 3013 words were used by both the participant and at least one partner;

178 of these were unique. The most common shared words in participant/partners'

conversations were "I", "like", "you", "the", and "yeah".

We collected responses of units in hippocampus (HPC, n=442 units, **Figure 1G**

and H) from 10 patients (range:19-77 neurons per patient). Neurons showed a clear

phasic response to the onset of individual speech turns (two clear examples shown in

Figure 1I). However, the majority of word-evoked responses had more complex

responses. To understand these responses, we took a word-based regression approach

(Franch et al., 2025). Specifically, we used a ridge-regularized Poisson regression to

predict word-evoked spike trains from static word embeddings (Word2Vec), including

both word duration and semantic–duration interaction terms as predictors (**Methods)**.

Because our primary interest was in the timing of word-evoked responses, we used a

static embedder to avoid contextual bleeding across words and to isolate word-by-word

encoding dynamics. Encoding performance was quantified as the difference in log-

likelihood between the full model and a control model in which the semantic embedding

predictors were shuffled. This analysis revealed distinct temporal dynamics for speaking

and listening (**Figure 1J**). Unsurprisingly, responses for spoken words peaked around the

time of utterance (red line) while responses for heard word peaked a few hundred ms

later (blue line). Guided by these dynamics, we selected a fixed 500 ms window

beginning 150 ms before word onset for spoken words and a 500 ms window beginning

200 ms after word onset for heard words. We chose the speaking-related window with the

goals of capturing both preparatory and execution-related activity, and because it had a

high decoding response. Subsequent analyses confirmed that all results presented are

robust to the selection of analysis window. Indeed, other windows tested with a start of

+/- 250 ms of the ones we chose produced qualitatively identical results (data not shown).

Once we selected our time windows, we tested the performance on each layer of a

contextual embedding model, BERT (Devlin et al., 2019). We chose BERT because it

generates context-dependent word embeddings and can incorporate speaker-aware tokens

directly into the tokenization process (Gu et al., 2020). We found stronger encoding with

higher layers in BERT (**Figure 1K**). Notably, encoding was significantly higher (p<.001,

Figure 1L) for heard than spoken words.

Figure 1. Encoding of semantics of conversational spoken and heard words in the hippocampus. A. Recording locations of hippocampal neurons across ten patients. **B.** Schematic of the speech processing pipeline, from raw audio to millisecond-resolved, speaker-labeled transcripts. In this and future panels, red: speaking; blue: listening. **C.** Conversational statistics: distribution of

words spoken per turn. **D.** Words heard by the patient per turn from other
speakers. **E.** Average word lengths across patients. **F.** Proportion of words
produced by each speaker. **G.** Example hippocampal neuron responses from
patient YFF showing continuous spiking activity aligned to spoken words. **H.**
Same but with heard words and corresponding spectrograms. **I.** Peristimulus
time histograms (PSTHs) illustrating turn-aligned responses in two neurons from
patients YFC (top) and YFK (bottom). **J.** Temporal dynamics of significant
difference in log likelihood between the real and shuffled model (**Methods)**
across word-aligned shifts: semantic encoding information began to peak ~150
ms before word onset for spoken words (red star) and ~200 ms after word onset
for heard words (blue star) according to smoothed data points. **K.** Semantic
encoding strength as a function of BERT embedding layer for spoken (red) and
heard (blue) words. **L.** Overall encoding strength of the full model for spoken
versus heard words.
204
205
On the relationship between neural encoding of heard and spoken language

Responses of three example neurons to three example words that were spoken and

heard multiple times are shown in **Figures 2A, B, and C**. While responses to these words

were different for speaking and listening, they reflect just a subset of the diversity of

neural responses observed. The average word-evoked firing rate of all neurons for all

patients together was nearly identical (t=0.268, p=0.7885). Nonetheless, population-level

analyses showed that neural activity patterns reliably encoded speaker identity. Both

logistic regression and random forest decoders classified speaker identity with an average

accuracy of 82% across patients (p < 0.05, above the 50% chance level). Importantly, this

effect was evident not only in the aggregate but also within individual patients (p<0.001

for each of our ten individual patients).

We considered three possible relationships between neuron population responses

to the same word for speaking and listening. First, responses to the same word spoken

and heard may have no systematic relationship (example neuron, **Figure 2D**). If that

pattern were consistent across the population of neurons, then we would expect semantic

tuning functions (that is, regression weight vectors) to be uncorrelated. Second, responses

could be partially overlapping (example neuron, **Figure 2E**). If that pattern were

consistent across the population of neurons, we would expect semantic tuning functions

to be partly correlated. Finally, if representations are fully overlapping (cartoon data,

Figure 2F), the correlation coefficient of tuning functions will be maximal (in the

absence of noise, it would approach 1, although due to noise, it would be lower).

Cartoons illustrating the effects of these single neuron solutions on subspace

representations are shown in **Figures 2G, H, and I**. These three patterns of encoding

correspond to cross-speaker differentiation, differentiation/generalization, and

generalization, respectively.

To determine which of these situations our data reflect, we computed the

correlation between tuning functions of individual neurons. Here, tuning functions refer

to the beta coefficients estimated for each neuron by our ridge regression models fit to

spoken versus heard words (**Methods**). Our data are consistent with the intermediate,

semi-orthogonalization solution (**Figures 2J and K**). Specifically, the degree of

orthogonalization between speaking and listening subspaces (purple violins) is greater

than zero in all ten of our patients individually ($p<0.05$ in all cases; one example patient

shown in **Figure 2J**), as well as in the group as a whole ($p<0.0001$, **Figure 2K**). The fact

that the measured correlation is greater than zero is, itself, notable since in high

dimensional spaces two random vectors are overwhelmingly likely to be orthogonal due

to cancellation across dimensions. Instead, this finding indicates that semantic

representations are at least partially shared between speaking and listening, offering a

solution to the generalization problem.

Equally important, we find that the degree of orthogonalization is less than fully

collinear. An observed correlation less than 1.0 is mathematically guaranteed, but not

scientifically interpretable, because any noise from any source will reduce measured

correlations below 1.0. Instead, the critical question is whether the correlation is less than

expected by chance given the noise properties of the dataset. We can estimate this using

half-split within-condition noise estimates of collinearity. Using these half-split estimates

is a powerful control, because it controls against any noise-related process that could

cause a spurious positive finding. For example, it may be that fits to the data are not

perfect, or that embeddings are suboptimal, or that we chose time windows that are

perfectly tailored to our fitting. By comparing real data to half-split within condition data,

we control for all of these confounders simultaneously.

We obtained those estimates with both listening (blue violins) and speaking (red

violins) data (note that using half-splits reduces our dataset size, thereby reducing

correlations, making our analysis even more conservative). We find, both in the

population and consistently across participants, lower half-split correlations with

speaking than with listening. This fact is consistent with our result, shown above, that

overall fits are better for listening than speaking data (**Figure 1L**). For this reason, we

take the most conservative approach and focus on the comparison between speaking and

speaking/listening cross-condition. We find, for our example patient as well as in the

population, that cross-condition correlations are lower than the half-split speaking-only

condition (above the null: $p=0.0002$, below the ceiling $p=0.001$). We find this same effect

in 9/10 of our patients (above the null: $p<0.0001$, below the ceiling $p<0.0001$) with the

remaining patient showing the same trend (patient YEY, $p=0.1124$). Together, these

results indicate that semantic vectors are poised between orthogonality and collinearity,

consistent with the mirror manifold (i.e., semi-orthogonalization) hypothesis for semantic

representations in the hippocampus.

Figure 2. Semi-orthogonality between spoken and heard word representations in the hippocampus. A–C. Example PSTHs and rasters from three hippocampal neurons (patient YFF) during both speaking and listening to the words ***"like", "to",*** and ***"I"***. These illustrate diverse response patterns across conditions. **D-F** Examples of neuron-

level firing rate correlations between spoken and heard words with conceptual
schematics: orthogonal/uncorrelated **D.**, semi-orthogonal/partially correlated **E.**, and
collinear/perfectly correlated **F. G-I** Competing hypotheses for how hippocampal
populations encode word meaning across speaking and listening: separate subspaces
or populations with no overlap **G.**, a mirror manifold with mixed selectivity across
neurons **H.**, and mirror neurons that are identical across conditions **I. J.** Example within-
patient correlations between semantic encoding weights for spoken and heard words:
values are significantly above chance but remain below the within-condition half-split
noise ceilings. **K.** Group-level results across ten patients show consistent above-chance
but sub-ceiling correlations, supporting a **mirror manifold** mechanism: spoken and
heard words are encoded in overlapping but not identical neural subspaces.

Categorical specificity of semantic subspace semi-orthogonalization

     If two people are talking about a tree, it is very likely to be the same tree. However, if one

person mentions their eyes, they are almost certainly talking about something different from the

other's eyes. Different semantic categories, in other words, may have different degrees of cross-

speaker generalization and differentiation. We next asked how subspace orthogonalization

interacts with semantic categories. We computed categories using a standard approach (Franch et

al., 2025; Huth et al., 2016; Jamali et al., 2024; Katlowitz et al., 2025, see **Methods** for details).

First, we computed a semantic embedding on all words spoken in all conversations using a non-

contextual embedder (Word2Vec, Mikolov et al., 2013). Word embeddings (300-dimensional)

were then reduced to two dimensions with UMAP (McInnes et al., 2018), and the resulting space

was clustered using HDBSCAN to identify semantic categories in an unsupervised manner. The

clustering algorithm yielded 11 semantic categories (**Figure 3A, Methods**). Not surprisingly,

function words were the most common (58.6% overall), followed by personal pronouns (13.1%

overall). The least used categories were proper nouns, social, and health/medicine (1.3%, 1.6%,

and 1.9% of words, **Figure 3B**).

     To assess how neural representations of meaning generalize across categories and

between speaking and listening, we fit our Poisson ridge regression model (see above and

Methods) separately within each semantic category, and separately for spoken and heard words.

We then measured cosine distance between the resulting tuning vectors. Data from one patient

are shown in **Figure 3C**. For this patient, the degree of orthogonality between tuning vectors for

self and other varied systematically by semantic category (ANOVA: f-statistic = 3.34;

p=0.0002). Function words (example: "*to*") had the most collinear representations between

speaking and listening, followed by action words ("*helping*") and then, surprisingly, personal
pronouns ("*mine*"). Conversely, abstract concepts ("*future*"), social words ("*grandparents*"), and
name/places ("*California")* were represented least similarly between speaking and listening
conditions.

This pattern was common across the population. Indeed, of the 10 patients we tested, all
but one showed a significant difference across categories (ANOVA, f-statistic =15.64; p<0.0001,
Figure 3D). Data for the group are shown in **Figure 3E**. Overall, function words were the most
similar across participants, followed by personal pronouns and actions. Conversely, body part
and clothing terms ("*sweater*") were the most differentiated, followed by objects and
names/places.

To confirm these findings using a complementary method, we asked whether this
categorical structure could be decoded across conditions (speaking vs listening). Specifically, we
trained a multinomial logistic regression classifier to distinguish 11 semantic categories from
neural responses to spoken words and tested its performance on responses to heard words. To
characterize how similar the underlying representational geometries were, we computed the
shared subspace fraction between classifier weight matrices. Across patients, this fraction
averaged to 0.46 (0.317-0.652). On this scale, where 0 indicates no overlap and 1 indicates
complete overlap, a value of 0.46 reveals that about half of the discriminative structure for
semantic categories is shared across conditions. In other words, the geometry is similar enough
to support generalization of category membership, but distinct enough to maintain speaker-
specific separation.

Figure 3. Differential encoding of semantic categories during speaking and listening. A. Clustering map of all words produced across the ten patient conversations, revealing broad semantic categories (e.g., body parts, social relationships, function words). **B.** Distribution of words across categories, separated by condition: words produced by the patient (red) versus words spoken by others and

therefore heard (blue). Function words were the most common in both conditions. **C.**
Example from one patient showing cosine distances between encoding weight vectors
for each semantic category, separately for speaking and listening, demonstrating
systematic differences across categories. **D.** Patient-level significance summaries: one-
way ANOVA tests revealed reliable differences between spoken and heard encoding
weights across semantic categories. **E.** Group-averaged cosine distances across
patients, highlighting that categories differed in their degree of self–other separation:
function words (e.g., *"the," "and"*) were encoded most similarly across speaking and
listening, whereas self-referential categories such as body-related words showed the
greatest divergence.
348

How the hippocampus differentiates conversation partners

Just as we must distinguish our own words from those of our partners, if we have

multiple conversational partners, we must keep them separate from each other. We next asked

whether subspace rotation is used for this purpose. In seven of our ten conversations, there were

at least three participants. **Figure 4A** shows the number of words spoken by each participant. By

convention, we defined the participant as "*speaker 1*" (average of 1120 words), the partner with

the most words as "*speaker 2*" (average of 1775 words), and the participant with the next most

words as "*speaker 3*" (average of 802 words). We did not analyze data from additional speakers

beyond those three; in all cases the number of words was too small to meaningfully analyze.

The key finding is that the brain uses subspace orthogonalization to separate semantics of

partners 2 and 3 (**Figure 4B and C**). Specifically, the subspace correlation between semantics

for partner 2 and 3 is greater than zero, indicating that there is some overlap in representations

crucial for generalization (for example patient YEY, p=0.0002; for the population: p<0.0001).

Moreover, the degree of overlap is less than 1.0, and, more importantly, is less than the amount

one would observe with noise (for example patient YEY: p=0.001; for the population:

p<0.0001). As above, we estimated the noise ceiling using a within condition half-split approach

(**Methods**).

We next used the same semantic clustering (**Figure 3A**) to assess semantic category-

specific orthogonalization across speech partners. As with self-other contrast, we found a

consistent pattern. In both our example participant (**Figure 4D**) and in six of seven participants

individually, (**Figure 4E**), we found a significant effect of semantic category on subspace angle

(ANOVA f-stat: 2.93, p = 0.0018). These patterns were also observed when combining across all

patients (**Figure 4F,** ANOVA: f-stat: 6.46, p<0.0001). As with the self-other distinction (see

above), function words, action words, and pronouns had the most collinearized representations

across contexts. In contrast to the self-other distinction, names/titles, objects, and body/clothes

were the most distinct for the self-other distinction but were middle positions for the partner 2 vs

partner 3 distinction. And, whereas descriptors ("*difficult*"), social ("*grandparents*"), and

numerical (*"thousand"*) terms were in the middle for self-other, they were maximally

differentiated for partner 2 and partner 3.

Together these results indicate that the brain uses subspace rotation as a general principle

for separating identity. The presence of three subspaces (for self and the two partners) raises the

question of how all three are related. All three subspaces may have some degree of orthogonality

relative to each other (**Figure 4G**). More generally, we can imagine four possible configurations

of three subspaces (**Figure 4H**). They can all be (i) identical, (ii) two matched and one separated,

(iii) all three separated, but organized in a line, or (iv) all three separated, forming the points of a

triangle. We find the fourth possible configuration, all three separated and forming the points of

a triangle (and therefore, consistent with **Figure 4G**). That is, the separating hyperplane that

distinguishes self from other is not unique but generalizes to also separate between different

others. Thus, we observe not only reliable separation of self from each other speaker, but also

measurable separation among the other speakers themselves. Separation is strongest between self

and other speakers, although the degree varies depending on which pair is compared. In contrast,

separation between different "other" speakers is present but weaker and demonstrated by the

higher correlations (**Figure 4I**). Specifically, correlations for self/other (1/2 and 1/3) are

significantly lower than correlations for other/other (2/3, $p<0.01$, t-test across subjects). This

same pattern is observed in 6/7 participants individually ($p<0.05$ in those cases). In other words,

the hippocampus uses the same subspace rotation principle to separate different conversation

partners, but with less rotation for the two partners than for the self vs. other.

Figure 4. Semantic encoding principles extend beyond self vs. other into
differentiation of multiple speakers. A. Pie chart of the number of words spoken by
unique speakers in each patient's conversation. Seven patients are highlighted who had

more than one other speaker present. **B.** Example patient correlations between semantic encoding weights for words heard from two different speakers. Correlations were significantly above chance but remained below the within-condition half-split noise ceilings. **C.** Group-level results across these seven patients show that the mirror manifold mechanism generalizes to distinguishing between multiple external speakers. **D.** Example from one patient showing cosine distances between encoding weight vectors for each semantic category when listening to two unique speakers. **E.** Patient-level significance summaries: one-way ANOVA tests revealed reliable differences in encoding weights between words spoken by different external speakers. **F.** Group-averaged cosine distances across patients, highlighting that semantic categories varied in their degree of separation: function words were encoded most similarly across speakers, whereas numerical or time-related words were encoded most differently. **G.** Conceptual schematic extending the mirror manifold hypothesis to multiple speakers. **H.** Competing theoretical models for how semantic encoding might scale across speakers: (i) all speakers share the same manifold, (ii) only self versus other are distinct, (iii) external speakers are differentiated but anchored to a common manifold, or (iv) each speaker is encoded on a unique manifold. **I.** Correlation data from all seven patients support the final model: hippocampal neurons encode meaning in a speaker-dependent manner, such that semantic representations are yoked to speaker identity, and each speaker occupies a distinct manifold.

DISCUSSION

Conversation imposes a difficult generalization/differentiation dilemma for any neural representation of meaning. If one speaker mentions "*my bicycle*", the other speaker should know it's not their own bicycle but can nonetheless leverage their general knowledge of bicycles to make inferences about its features. Our data support the hypothesis that this dilemma can be resolved via rotation of neural population coding subspaces for semantics. Subspace rotation has been proposed as a solution to other generalization/differentiation problems (Bernardi et al., 2020; Chericoni et al., 2025; Elsayed et al., 2016; Johnston et al., 2024; Kaufman et al., 2014; Libby and Buschman, 2021; Tang et al., 2020; Tian et al., 2024; Xie et al., 2022;). Thus, here we propose that it extends to vectorial representations of word meanings in the hippocampus. We use the term "*mirror manifold*" to describe our hypothesis. Like mirror neurons, our proposed mirror manifold can solve the cross-personal generalization problem, but, unlike mirror neurons, can also simultaneously solve the differentiation problem.

Our results may be surprising as we find clear semantic encoding localized to the hippocampus, which is not a classical language structure (Fedorenko et al., 2024). However, our results are aligned with a good deal of research highlighting the role of the hippocampus in representing word meanings (Binder et al., 2009; Brown-Schmidt et al., 2021; Duff and Brown-Schmidt 2012; Franch et al., 2025; Piai et al., 2016; van de Ven et al., 2020) and grammatical processing (Dijksterhuis et al., 2024). Complementary studies of lesions to the hippocampus show clear semantic deficits (Manns et al., 2003; Moscovitch et al., 2005; Keane et al., 2019; Duff et al., 2020). This possibility is consistent with the robust evidence that the hippocampus plays an important role in memory-related processes, which may be foundational for semantics. Moreover, the hippocampus is associated with simultaneous generalization and differentiation (Bernardi et al., 2020), as well as both pattern completion and separation processes, which are conceptually related (Leutgeb et al., 2005; Bakker et al., 2008). Finally, there is evidence that supports a potential role for the hippocampus in social cognition, including identity assignment (Danjo et al., 2018; Tavares et al., 2015; Montagrin et al., 2018; Rey et al., 2020).

Taken together, these properties suggest that the hippocampus is well positioned to address a central question in language research: how production and comprehension, long treated as distinct processes, may nonetheless be linked. Early models drew a sharp boundary between speaking and listening, mapping production to Broca's area and comprehension to Wernicke's

area. More recent functional–anatomical accounts move beyond these two regions as sole language centers but still emphasize that production and comprehension are carried out in partially separable hubs or dual processing streams (e.g., Hickok & Poeppel, 2007; Ben-Shalom & Poeppel, 2008; Castellucci et al., 2022). While such dichotomous frameworks offer a solution to the problem of differentiation, they leave unresolved the complementary need for cross-speaker generalization. Complementary perspectives highlight overlapping neural mechanisms, suggesting that speaking and listening may draw on shared representational systems (Pickering & Garrod, 2013; Tremblay & Dick, 2016; Silbert et al., 2014). Our results support the idea that production and comprehension rely in part on overlapping representations.

Our study complements other recent studies on the neuroscience of conversational language. Zada et al. (2024) showed that contextual embeddings from LLMs approximate a context-sensitive representational space that both speakers map onto during face-to-face conversation. Encoding models revealed that these embeddings predict neural activity before word onset in speakers and after word onset in listeners, creating a temporal flow that mirrors conversational dynamics. Goldstein et al. (2025) extended this approach in a larger dataset of spontaneous conversations using a unified acoustic-to-speech-to-language model (Whisper), showing that the same cortical hierarchy supports both production and comprehension with similar temporal dynamics. In contrast, Cai et al. (2025) used embedding-based encoding models of intracranial LFPs and found that natural conversation recruits a distributed set of channels across cortical and limbic regions. A greater proportion of temporal cortex channels were significantly explained during comprehension, more precentral channels during production, and only ~18% of channels were jointly predictive across both conditions. Finally, using a delayed sentence repetition task, Xu et al., (2024) find evidence for *bridge* and *mirror* neurons in the precentral gyrus. Bridge neurons exhibited sustained firing rate between the same speech elements during listening and speaking. Their mirror neurons implement mirroring functions for specific speech sounds, although they do not participate in speaker differentiation. Our results confirm the idea of cross-speaker mirroring and extend them by (1) showing that cross-speaker mirroring can be identified in natural, free-flowing speech; (2) mirroring is not limited to phonemics, but also works for semantics, and (3) semantic mirroring, at least, can be found outside the classic language network. And, of course, (4) we find simultaneous mirroring and differentiation in the same populations of neurons.

Our subspace alignment proposal relies on the principle that semantic encoding in the

hippocampus is vectorial. We and others have proposed that meanings of words in naturalistic

contexts are distributed across a large number of neurons and expressed in patterns of neural

activity (Franch et al., 2025; Jamali et al., 2024; Katlowitz et al., 2025). Our results here suggest

that this vectorial representation includes factors that are outside the domain of semantics; here,

the identity of the speaker. In this sense, it resembles semantic representations in BERT, which

can incorporate identity with special identity tokens (Gu et al., 2020). In short, rather than

separate channels for identity and meaning, the same neurons are used, and identity and meaning

are multiplexed in those neurons (Rigotti et al., 2013). This view is in line with modern

neuroscience theories, which de-emphasize the expression of function in specialized categories

of individual neurons, in favor of distributed, population coding methods (Rigotti et al., 2013;

Saxena and Cunningham, 2019; Churchland et al., 2012; Ebitz and Hayden, 2021).

The semantic clustering we observe indicates that subspace rotation is not a one-size-fits-

all process (**Figure 3**). While our results do not provide insight into why certain categories have

more or less alignment, we can speculate. For example, function words (*the*, for, *and*) and

pronouns are the most consistent across both self-other (**Figure 3E**) and partner2-partner3

(**Figure 4F**). These words have both very general meanings that do not vary much by person

and, moreover, tend to have very weak semantics on their own (Katlowitz et al., 2025). Verbs are

the next most consistent (*helping*, *brushed*, *smiled*). Conversely, body parts (*face*, *eyes*, *arm*)

tend to be highly specific to individuals; the speakers' hand is almost certain to be different - and

have different conversational relevance - than the partner's hand. That may also explain why

objects (*drink*, *laundry*, *mattress*) are highly differentiated - speakers may tend to discuss objects

relative to themselves.

More speculatively, our results suggest a circuit-level approach to questions of mind-

reading and mental state inference (Mukamel et al., 2010; Koster-Hale and Saxe, 2013; Jamali et

al., 2021). As with cross-speaker language, these processes require simultaneously recognizing

the similarities between self and other while maintaining their separation (Uddin, 2011; Jamali et

al., 2021; Heatherton et al., 2016). For example, empathy requires acknowledging another

person's experience while also recognizing that it is not one's own (Decety and Jackson, 2004;

Singer et al., 2004; Lamm et al., 2007). This raises what has been termed a superposition

problem (Garagnani, 2024). Our findings suggest a complementary solution: representing

person-specific variables in partially overlapping but distinct subspaces. In this framework,

neural populations can project information into a shared representational space to capture

commonalities, while also aligning along separating axes that preserve individual distinctions.

That we observe such a mechanism in the context of language conversations suggests it may

provide a foundation for broader cognitive functions, including emotion, theory of mind, or

decision making in social contexts.

<div align="center">**METHODS**</div>

Human intracranial neurophysiology

All experiments were performed in the Epilepsy Monitoring Unit (EMU) at Baylor St. Luke's Hospital using standardized approaches (Xiao et al., 2024). Experimental data were recorded from ten adult patients (seven male, three female, age ranges: 22-54) undergoing intracranial monitoring for epilepsy. The hippocampus was not a seizure focus area of any patients included in the study. Single neuron data were recorded from stereotactic (sEEG) probes, specifically Ad-Tech Medical probes in a Behnke-Fried configuration. Each patient had an average of three probes terminating in the left and right hippocampus. Electrode locations were verified by co-registered pre-operative MRI and post-operative CT scans. Each probe includes eight microwires, each with eight contacts, specifically designed for recording single-neuron activity. Single neuron data were recorded using a 512-channel *Blackrock Microsystems Neuroport* system sampled at 30 kHz. To identify single neuron action potentials, the raw traces were spike sorted using the *Wave_clus* sorting algorithm (Chaure et al., 2018) and then manually evaluated and modified to improve sorting. Noise was removed and each signal was classified as multi or single unit using several criteria: consistent spike waveforms, waveform shape (slope, amplitude, trough-to-peak), and exponentially decaying ISI histogram with refractory period (1 ms) violations below 5%. The analyses here used all single and multiunit activity.

Electrode visualization

Electrodes were localized using the software pipeline intracranial Electrode Visualization (iELVis; Groppe et al., 2017) and plotted across patients on an average brain using Reproducible Analysis & Visualization of iEEG (RAVE; Magnotti et al., 2020). For each patient, DICOM images of the preoperative T1 anatomical MRI and the postoperative Stealth CT scans were acquired and converted to NIfTI format (Li et al., 2016). The CT was aligned to MRI space using FSL (Jenkinson et al., 2002; Jenkinson & Smith, 2001). The resulting coregistered CT was loaded into BioImage Suite (version 3.5β1; Joshi et al., 2011) and the electrode contacts were manually localized. Electrodes coordinates were converted to patient native space using iELVis MATLAB functions (Yang et al., 2012) and plotted on the Freesurfer (version 7.4.1) reconstructed brain surface (Dale et al., 1999). Microelectrode coordinates are taken from the first (deepest) macro contact on the Ad-Tech Behnke Fried depth electrodes. RAVE (Magnotti et al., 2020) was used to transform each patient's brain and electrode coordinates into MNI152 average space. The average coordinates were plotted together on a glass brain with the hippocampus segmentation and colored by patient.

Conversations

Patients with epilepsy and healthy language function engaged in unprompted conversations with researchers, family members, friends, and/or members of the clinical staff. Conversation lengths ranged from 14.7-70.1 minutes, with an average length of 20.2 minutes. Topics of conversation varied across patients. Audio was primarily recorded using two room microphones that were directed toward the location of the patient (Blue Yeti) or personal lapel microphones (WAYVOSE). The audio was synchronized to the neural recording system via analog input going directly into the Blackrock Neural Signal Processor at 30 kHz.

Audio Transcription

After experiments, the audio.wav file was automatically transcribed using WhisperX, a
state-of-the-art and commercially available AI model trained to transcribe speech (Bain et al.,
2023). Speaker diarization was achieved using an open-source toolkit written in Python named
Pyannote (Bredin et al., 2021). The transcribed words, corresponding timestamps, and speaker
labels output from these models was converted to a TextGrid and then loaded into Praat, a
software for speech analysis. The original .wav file was also loaded into Praat. Trained lab
members manually inspected the spectrograms, timestamps, and speaker labels, correcting each
word to ensure that onset and offset times were precise and assigned to the correct speaker (this
process took about 1 hour per minute of speech). The TextGrid output of corrected words and
timestamps from Praat was converted to a .xls and loaded in Python for further analysis.

Contextual and non-contextual embeddings
Contextual embeddings: To obtain contextual embeddings for each word, we used the
bert-base-cased model (BERT; Devlin et al., 2019) accessed via the Hugging Face Transformers
library (Wolf et al., 2020). This model consists of one embedding layer and 12 transformer
blocks, each producing a 768-dimensional vector for every token. The conversational transcripts
were vectorized into a single sequence of words in their natural temporal order and each word
was prepended with a speaker-specific token, allowing the model to differentiate between
speakers. This modification was inspired by prior speaker-aware adaptations of BERT for
dialogue modeling (Gu et al., 2021). To handle BERT's 512-token input limit, we used a sliding
window of 512 tokens with a stride of 256, and averaged embeddings for words that fell in
overlapping window segments. This model also allows for extraction of embeddings from each
layer (0-12). Embeddings from each of these layers were used as predictors for neural activity
(**Figure 1K**), however all other results are from output or final layer.

Non-contextual (static) embeddings: We also extracted static word embeddings using
the pre-trained fastText Word2Vec model in MATLAB, specifically the wiki-news-300d-1M
vectors (Bojanowski et al., 2017; Grave et al., 2018). This model provides fixed 300-dimensional
vectors for over one million words and phrases, trained on Wikipedia and news text to capture
broad semantic relationships. Unlike contextual embeddings, which vary depending on sentence
position or surrounding words, these static embeddings assign the same representation to each
word regardless of context. For our dataset, we mapped every word in the transcripts to its
corresponding fastText vector. Words without valid embeddings (e.g., uncommon surnames or
rare tokens not present in the model's vocabulary) were excluded from further analyses.

Semantic clustering
To identify natural semantic categories in our word data (**Figure 3A–E**), we clustered all
unique words into groups based on distributional similarity in embedding space. We first
extracted 300-dimensional static embeddings for each unique word across all conversations
using the pre-trained fastText wiki-news-300d-1M model. To reduce noise and focus on
semantically informative tokens, we excluded function words, except personal pronouns and
their contractions, using the stopword list from the Natural Language Toolkit (NLTK; Bird et al.,
2009), and treated them as a separate cluster. Dimensionality reduction was then performed with
Uniform Manifold Approximation and Projection (UMAP; McInnes et al., 2018) using the
parameters *n_neighbors = 15*, *min_dist = 0.2*, *n_components = 10*, and *metric = cosine*. UMAP
produces a lower-dimensional representation in which words with similar meanings are located

nearby. We next applied Hierarchical Density-Based Spatial Clustering of Applications with
Noise (HDBSCAN; Campello et al., 2013; McInnes & Healy, 2017) to these reduced
embeddings. HDBSCAN requires two key parameters: *minimum cluster size* (the smallest
grouping to be considered a valid cluster) and *minimum samples* (the number of points required
to define a dense region), which together determine the stability and granularity of the resulting
clusters. In our analysis, we set *minimum cluster size = 40* and *minimum samples = 8*. Words
assigned to the noise cluster were reassigned to the nearest cluster by majority vote of their
neighbors. For visualization, we projected the raw embeddings into two dimensions using t-
distributed Stochastic Neighbor Embedding (t-SNE; van der Maaten & Hinton, 2008) and
colored words by their assigned cluster IDs.
622
Turn-aligned PSTHs and rasters
For each neuron, we extracted spike trains aligned to conversational turn onsets defined
as the moment when either the patient (self) began speaking or when any other participant in the
room initiated speech (listening for self). Each turn onset was treated as time zero, and spikes
were segmented into fixed analysis windows spanning a defined pre- and post-onset interval.
Within each window, spikes were binned at a fixed bin width (20 ms). Spike counts in each bin
were divided by the bin duration (in seconds) to yield firing rates in Hz and averaged across
trials to obtain the mean peri-event time course of firing rate (PSTH). Variability across trials
was quantified as the standard error of the mean (SEM). For raster visualization, individual
spikes from each trial were plotted as vertical ticks at their millisecond timestamps relative to
turn onset, forming rasters at the baseline of the axis. To highlight temporal structure, the binary
spike trains were also smoothed with a Gaussian kernel ($\sigma \approx 10$ ms) and scaled to approximate
firing rate. These smoothed traces were plotted directly above the raster ticks, providing a
continuous PSTH trace superimposed on the underlying spike times.
637
Regressing spike counts on word embeddings
Word embeddings, such as those derived from Word2Vec or similar models, are typically
high-dimensional and can exhibit substantial collinearity among dimensions - that is, many of the
embedding features are correlated with one another. We first used Principal Component Analysis
(PCA, scikitlearn) on the full word embeddings to obtain uncorrelated features that still capture
the dominant structure in the embedding space with reduced dimensionality. For each word, we
used the first 100 principal components (PC) from Word2Vec or BERT embeddings because
they explained at least 60% of the variance of the original embedding vectors. We modeled the
spike count responses of individual neurons using a Poisson Generalized Linear Model (GLM)
with a log-link function and ridge (L2) regularization (we confirmed that spike counts for each
word follow a Poisson distribution). The model aimed to predict the number of spikes a neuron
fired in response to each word (summed spikes across word duration), using the top 100 principal
components (PCs) of the word embedding vector, the duration of the word, and the interaction
between each PC and the word's duration as predictors (z-scored prior to model fitting). This
resulted in a 201-dimensional feature vector for each word: 100 PC values, 1 duration value, and
100 PC×duration interaction terms.
The Poisson GLM assumes that the spike count y_i for word i is drawn from a Poisson
distribution with mean λ_i where:

$$y_i \sim \text{Poisson}(\lambda_i)$$
$$\log(\lambda_i) = \beta_0 + x_i^T \beta$$

Where $\lambda_{i,n}$, the expected spike count for word (*i*) and neuron n (*n*), is modeled by the linear
regression coefficients (β), one for each of the 201 predictors, 100 PCs from embeddings, word
duration, and duration PC interactions, (x_i^T), plus the y-intercept (β_0). For each neuron, we used
a 5-iteration nested training loop, where in each iteration, the data was split into training and
held-out test sets (80/20 split). Within the training set, 5-fold cross-validation was used to select
the optimal regularization strength (alpha) from a log-spaced range based on optimizing the
cross-validated log-likelihood. The selected model was then evaluated on the held-out test set
using several performance metrics, including log-likelihood, and adjusted R^2. To determine
whether the observed performance exceeded chance, we fit matched null models in which
embeddings were randomly shuffled across words 100 times, computing LLH from every
shuffled model. To determine if the actual model showed significant improvement from the
shuffled model, we performed a permutation test comparing the actual model LLH to the
shuffled model LLH distribution. We then took the difference between the actual and shuffled
model (median) LLH (LLH diff; ΔLLH). A neuron's response was successfully predicted by the
model if its ΔLLH was both positive and significant and if McFadden's pseudo-R^2 value was
positive ($P < 0.05$). Shuffled model R^2 values were significantly less than those from actual
models ($p < 0.05$, Wilcoxon signed-rank test). A predictor was considered significant if its
corresponding coefficient had a p-value less than 0.05 in the fitted Poisson model. For
population-level encoding analyses, however, we included all neurons and all model coefficients,
irrespective of their individual significance.
678
Hyperparameter Selection:
To choose the regularization strength α, we used a two-stage grid search:
1. **Coarse Search** over: $\alpha \in \{10^{-5}, 10^{-4}, ... 10^3\}$
2. **Fine Search** around the best coarse value, spanning two orders of magnitude.
For each value of *α*, we performed 5-fold cross-validation. For each fold, the model was trained
on the other four folds and evaluated on the held-out fold by computing the Poisson log-likelihood:
685
Window selection for speech comprehension and production
To identify the analysis windows for subsequent encoding models, we systematically
quantified model performance across a range of candidate window starts and lengths. Candidate
windows were defined from −1 s to +1 s relative to word onset, sampled in 10-ms increments,
with window lengths ranging from 80 ms to 500 ms. For each [window start × window length]
combination, and separately for spoken and heard words, we fit Poisson regression models using
Word2Vec embeddings as predictors. Performance was evaluated using ΔLLH, defined as the
log-likelihood difference between the full model and a semantic-shuffled model in which only
the semantic embedding PCs were permuted (with duration interactions recomputed). Model
performance increased monotonically with longer window lengths, with the strongest
improvements at 500 ms. Based on this, and to capture preparatory activity prior to speech and
integrative activity during comprehension, we selected window starts that were shifted back from
the global maximum. For speaking, the window began 150 ms before word onset; for listening,
the window began 200 ms after word onset. For visualization, ΔLLH values were smoothed
across window positions using a Savitzky–Golay filter (Savitzky & Golay, 1964). For each
neuron and word, firing rate was computed as the total spike count within the selected window,
divided by the window duration, and expressed in spikes/s. Unless otherwise noted, all analyses

reported in the manuscript used these fixed windows (**Figures 1I and 2A–C** show PSTHs
computed using identical windows for speaking and listening).
705

Reliability and cross-condition comparisons of semantic encoding
To evaluate how neural populations encode semantic information (using BERT
embeddings) across speaking and listening, we compared the structure of regression weights
obtained under each condition. We fit separate Poisson ridge regression models for spoken and
heard words (see above), yielding condition-specific vectors of beta coefficients that define each
neuron's semantic tuning curve. However, to dismiss possible explanations of these results
coming from an imbalance in the number of words within each condition we made sure to
downsample the larger class if the imbalance exceeded 1.5 times the smaller class as
implemented in the imbalanced-learn Python package (Lemaitre et al., 2017). These results did
not vary significantly from refitting the same models on perfectly balanced data. In our
framework, the regression weights learned by the model can be interpreted as the tuning curves.
When considered jointly across neurons, these tuning vectors span a neural subspace that
captures the population-level encoding of semantics under a given condition (speaking or
listening). The alignment of these two subspaces was quantified as the correlation between their
coefficient vectors (r_cross) (Johnston et al., 2024). To assess whether these correlations
exceeded chance levels, we constructed a null distribution by permuting the predictor variables:
one condition was modeled on the true data, while the other was modeled on data with semantic
predictors randomly shuffled. This procedure was repeated 500 times to estimate the distribution
of correlations expected under the null hypothesis of no shared structure. As an upper bound, or
noise ceiling, we quantified within-condition reliability by randomly splitting the data in half and
re-fitting the model separately to each split. Correlations between the resulting beta vectors
provided half-split reliability estimates for spoken (r_self) and heard (r_other) words. Together,
these three metrics allowed us to determine whether cross-condition similarity reflected true
shared semantic encoding rather than noise, and to interpret it relative to the maximum reliability
attainable in each condition.
731

Semantic cosine distance
We quantified the separation between semantic encoding during speaking and listening
using the cosine distance between regression weight vectors. For two beta coefficient vectors w_1
and w_2 cosine distance is defined as:
$$\text{Cosine distance } (w_1, w_2) = 1 - \frac{w_1 * w_2}{\|w_1\|\|w_2\|}$$
To compute category-specific distances, the regression model described above was fit separately
for each semantic category under speaking and listening conditions. This procedure was repeated
across all categories, with class counts balanced up to an imbalance ratio of 1.5 to avoid
excessive trial loss. To establish a noise ceiling for these distances, we computed half-split
reliability estimates within the most populated category (function words). Data from this
category were randomly split in half, models were refit, and cosine distances were computed
between the two halves. This was repeated with bootstrapping, and all observed category
distances were normalized by the mean half-split distance for function words. Finally,
differences in normalized cosine distances across semantic categories were evaluated using a
one-way ANOVA.
747

748 **Decoding Analyses**

Decoding Speaker Identity

To assess whether hippocampal activity carried sufficient information to distinguish speaker identity, we trained classifiers on neural firing rate data. Two decoding approaches were used: multinomial logistic regression with an elastic net penalty and random forest classifiers. Hyperparameters for both models were optimized using randomized search with cross-validation. Input features were word-by-neuron firing rate matrices constructed from the speaking and listening windows defined above. To probe the robustness of the population code, we also evaluated decoding performance while subsampling random fractions of the available neurons within each patient. Classification tasks included self versus other (patient's own speech vs. all other speakers' speech) and pairwise other–other comparisons (distinguishing between two external speakers). To mitigate class imbalance, we down sampled the majority class so that each class had an equal number of words. Decoding performance was evaluated using accuracy. To confirm that results reflected above chance decodability, we additionally computed null distributions via permutation tests in which class labels were randomly shuffled. Across patients, logistic regression and random forest yielded comparable accuracy, differing by less than ~2% within individuals.

Subspace Correlation of Semantic Decoder Weights

To assess how spoken and heard semantics relate at the population level, we trained a linear decoder to classify words into ten semantic categories (plus function words). We used a multinomial logistic regression model, with hyperparameters tuned by grid search, applied to firing rate matrices (words × neurons) constructed separately for speaking and listening conditions. The target label in each case was the semantic category of the word. To compare the representational geometry between conditions, we quantified the similarity of the semantic subspaces defined by the decoder weights (Johnston et al., 2024). For each condition, the regression weight matrix W was normalized on a per-neuron basis so that each neuron's weight vector had unit length:

$$\hat{w}_i = \frac{w_i}{\|w_i\|_2}, i = 1, \dots, N$$

where w_i is the row vector of weights for neuron i. These normalized weight vectors were then averaged across neurons to yield a population-level summary vector:

$$\bar{w} = \frac{1}{N} \sum_{i=1}^{N} \hat{w}_i$$

Finally, the subspace correlation between speaking and listening was computed as the cosine similarity between the two summary vectors:

$$\rho = \frac{\bar{w}_{self} * \bar{w}_{other}}{\|\bar{w}_{self}\|_2 \|\bar{w}_{other}\|_2}$$

787   This measure captures the degree of alignment between semantic subspaces: values near 1
788   indicate strongly overlapping subspaces, values near 0 indicate orthogonality, and negative
789   values reflect opposing alignment. Across the ten patients, subspace correlations ranged between
790   0 and 1, with a mean of ~0.46, consistent with a semi-orthogonal relationship between spoken
791   and heard semantic subspaces.

References

Aliko, S., Franch, M., Kewenig, V., Wang, B., Cooper, G., Glotfelty, A., ... & Skipper, J. I. (2023). The entire brain, more or less, is at work:'language regions' are artefacts of averaging. bioRxiv, 2023-09.

Arbib, M. A. (2005). From monkey-like action recognition to human language: An evolutionary framework for neurolinguistics. *Behavioral and brain sciences*, *28*(2), 105-124.

Bakermans, J. J., Warren, J., Whittington, J. C., & Behrens, T. E. (2025). Constructing future behavior in the hippocampal formation through composition and replay. Nature neuroscience, 1-12.

Bakker, A., Kirwan, C. B., Miller, M., & Stark, C. E. (2008). Pattern separation in the human hippocampal CA3 and dentate gyrus. *science*, *319*(5870), 1640-1642.

Bain, M., Huh, J., Han, T., & Zisserman, A. (2023). Whisperx: Time-accurate speech transcription of long-form audio. *arXiv preprint arXiv:2303.00747*.

Barak, O., Rigotti, M., & Fusi, S. (2013). The sparseness of mixed selectivity neurons controls the generalization–discrimination trade-off. Journal of Neuroscience, 33(9), 3844-3856.

Ben Shalom, D., & Poeppel, D. (2008). Functional anatomic models of language: assembling the pieces. The Neuroscientist, 14(1), 119-127.

Bernardi, S., Benna, M. K., Rigotti, M., Munuera, J., Fusi, S., & Salzman, C. D. (2020). The geometry of abstraction in the hippocampus and prefrontal cortex. Cell, 183(4), 954-967.

Binder, J. R., Desai, R. H., Graves, W. W., & Conant, L. L. (2009). Where is the semantic system? A critical review and meta-analysis of 120 functional neuroimaging studies. Cerebral cortex, 19(12), 2767-2796.

Bird, S., Klein, E., & Loper, E. (2009). *Natural language processing with Python: analyzing text with the natural language toolkit*. " O'Reilly Media, Inc.".

Boersma, P., & Weenink, D. (2001). PRAAT (Version 4.0)[computer software]. Amsterdam: University of Amsterdam.

Bredin, H., & Laurent, A. (2021). End-to-end speaker segmentation for overlap-awareresegmentation. arXiv preprint arXiv:2104.04045.

Brown-Schmidt, S., Cho, S. J., Nozari, N., Klooster, N., & Duff, M. (2021). The limited role of hippocampal declarative memory in transient semantic activation during online language processing. Neuropsychologia, 152, 107730.

Cai, J., Hadjinicolaou, A. E., Paulk, A. C., Soper, D. J., Xia, T., Wang, A. F., ... & Cash, S. S. (2025). Natural language processing models reveal neural dynamics of human conversation. Nature Communications, 16(1), 3376.

Campello, R. J., Moulavi, D., & Sander, J. (2013, April). Density-based clustering based on hierarchical density estimates. In *Pacific-Asia conference on knowledge discovery and data mining* (pp. 160-172). Berlin, Heidelberg: Springer Berlin Heidelberg.

Castellucci, G. A., Kovach, C. K., Howard III, M. A., Greenlee, J. D., & Long, M. A. (2022). A speech planning network for interactive language use. Nature, 602(7895), 117-122.

Chaure, F. J., Rey, H. G., & Quian Quiroga, R. (2018). A novel and fully automatic spike-sortingimplementation with variable number of features. Journal of neurophysiology, 120(4), 1859-1871.

Chen, D., Peterson, J. C., & Griffiths, T. L. (2017). Evaluating vector-space models of analogy. *arXiv preprint arXiv:1705.04416*.

Chericoni, A., Fine, J. M., Chavez, A. G., Franch, M. C., Mickiewicz, E. A., Mathura, R. K.,...& Hayden, B. Y. (2025). Independent Continuous Tracking of Multiple Agents in the Human Hippocampus. bioRxiv, 2025-03.

Corballis, M. C. (2010). Mirror neurons and the evolution of language. Brain and language, 112(1), 25-35.

Courellis, H. S., Minxha, J., Cardenas, A. R., Kimmel, D. L., Reed, C. M., Valiante, T. A., ... & Rutishauser, U. (2024). Abstract representations emerge in human hippocampal neurons during inference. Nature, 632(8026), 841-849.

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical surface-based analysis: I. Segmentation and surface reconstruction. *Neuroimage*, *9*(2), 179-194.

Danjo, T., Toyoizumi, T., & Fujisawa, S. (2018). Spatial representations of self and other in the hippocampus. Science, 359(6372), 213-218.

Decety, J., & Jackson, P. L. (2004). The functional architecture of human empathy. *Behavioral and cognitive neuroscience reviews*, *3*(2), 71-100.

Devlin, J., Chang, M. W., Lee, K., & Toutanova, K. (2019, June). Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)* (pp. 4171-4186).

Dijksterhuis, D. E., Self, M. W., Possel, J. K., Peters, J. C., van Straaten, E. C. W., Idema, S.,… & Roelfsema, P. R. (2024). Pronouns reactivate conceptual representations in human hippocampal neurons. Science, 385(6716), 1478-1484.

Duff, M. C., & Brown-Schmidt, S. (2012). The hippocampus and the flexible use and processing of language. *Frontiers in human neuroscience*, *6*, 69.

Duff, M. C., Covington, N. V., Hilverman, C., & Cohen, N. J. (2020). Semantic memory and the hippocampus: Revisiting, reaffirming, and extending the reach of their critical relationship. *Frontiers in human neuroscience*, *13*, 471.

Ebitz, R. B., & Hayden, B. Y. (2021). The population doctrine in cognitive neuroscience. Neuron, 109(19), 3055-3068.

Ebitz, R. B., Sleezer, B. J., Jedema, H. P., Bradberry, C. W., & Hayden, B. Y. (2019). Tonic exploration governs both flexibility and lapses. PLoS computational biology, 15(11), e1007475.

Eisenreich, B. R., Hayden, B. Y., & Zimmermann, J. (2019). Macaques are risk-averse in a freely moving foraging task. Scientific reports, 9(1), 15091.

Elsayed, G. F., Lara, A. H., Kaufman, M. T., Churchland, M. M., & Cunningham, J. P. (2016). Reorganization between preparatory and movement population responses in motor cortex. Nature Communications, 7(1), 13239.

Fedorenko, E., Ivanova, A. A., & Regev, T. I. (2024). The language network as a natural kind within the broader landscape of the human brain. Nature Reviews Neuroscience, 25(5), 289-312.

Fine, J. M., Maisson, D. J. N., Yoo, S. B. M., Cash-Padgett, T. V., Wang, M. Z., Zimmermann, J., & Hayden, B. Y. (2023). Abstract value encoding in neural populations but not single neurons. *Journal of Neuroscience*, *43*(25), 4650-4663.

Fine, J. M., Chericoni, A., Delgado, G., Franch, M. C., Mickiewicz, E. A., Chavez, A. G., ... & Hayden, B. Y. (2025). Complementary roles for hippocampus and anterior cingulate in composing continuous choice. bioRxiv, 2025-03.

Franch, M., Mickiewicz, E. A., Belanger, J. L., Chericoni, A., Chavez, A. G., Katlowitz, K. A., Sheth, S. A. & Hayden, B. Y. (2025). A vectorial code for semantics in human hippocampus. bioRxiv, 2025-02.

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: high dimensionality for higher cognition. *Current opinion in neurobiology*, *37*, 66-74.

Garagnani, M. (2024). On the ability of standard and brain-constrained deep neural networks to support cognitive superposition: a position paper. Cognitive Neurodynamics, 18(6), 3383-3400.

Goldstein, A., Wang, H., Niekerken, L., Schain, M., Zada, Z., Aubrey, B., ... & Hasson, U. (2025). A unified acoustic-to-speech-to-language embedding space captures the neural basis of natural language processing in everyday conversations. Nature human behaviour, 1-15.

Groppe, D. M., Bickel, S., Dykstra, A. R., Wang, X., Mégevand, P., Mercier, M. R., ... & Honey, C. J. (2017). iELVis: An open source MATLAB toolbox for localizing and visualizing human intracranial electrode data. Journal of neuroscience methods, 281, 40-48.

Gu, J. C., Li, T., Liu, Q., Ling, Z. H., Su, Z., Wei, S., & Zhu, X. (2020, October). Speaker-aware BERT for multi-turn response selection in retrieval-based chatbots. In Proceedings of the 29th ACM International Conference on Information & Knowledge Management (pp. 2041-2044).

Hayden, B. Y. (2019). Why has evolution not selected for perfect self-control?. Philosophical Transactions of the Royal Society B, 374(1766), 20180139.

Heyes, C., & Catmur, C. (2022). What happened to mirror neurons?. Perspectives on Psychological Science, 17(1), 153-168.

Hickok, G. (2010). The role of mirror neurons in speech perception and action word semantics. Language and cognitive processes, 25(6), 749-776.

Hickok, G. (2014). *The myth of mirror neurons: The real neuroscience of communication and cognition*. WW Norton & Company.

Hickok, G., & Poeppel, D. (2007). The cortical organization of speech processing. Nature reviews neuroscience, 8(5), 393-402.

Huth, A. G., De Heer, W. A., Griffiths, T. L., Theunissen, F. E., & Gallant, J. L. (2016). Natural speech reveals the semantic maps that tile human cerebral cortex. Nature, 532(7600), 453-458.

Jamali, M., Grannan, B., Cai, J., Khanna, A. R., Muñoz, W., Caprara, I., ... & Williams, Z. M. (2024). Semantic encoding during language comprehension at single-cell resolution. Nature, 631(8021), 610-616.

Jamali, M., Grannan, B. L., Fedorenko, E., Saxe, R., Báez-Mendoza, R., & Williams, Z. M. (2021). Single-neuronal predictions of others' beliefs in humans. Nature, 591(7851), 610-614.

Jenkinson, M., Bannister, P., Brady, M., & Smith, S. (2002). Improved optimization for the robust and accurate linear registration and motion correction of brain images. Neuroimage, 17(2), 825-841.

Jenkinson, M., & Smith, S. (2001). A global optimisation method for robust affine registration of brain images. Medical image analysis, 5(2), 143-156.

Johnston, W. J., Fine, J. M., Yoo, S. B. M., Ebitz, R. B., & Hayden, B. Y. (2024). Semi-orthogonal subspaces for value mediate a binding and generalization trade-off. Nature Neuroscience, 27(11), 2218-2230.

Joshi, A., Scheinost, D., Okuda, H., Belhachemi, D., Murphy, I., Staib, L. H., & Papademetris,X. (2011). Unified framework for development, deployment and robust testing of neuroimaging algorithms. *Neuroinformatics*, *9*(1), 69-84.

Katlowitz, K. A., Belanger, J. L., Ismail, T., Chavez, A. G., Chericoni, A., Franch, M., ... & Sheth, S. A., Hayden, B. Y. (2025). Attention is all you need (in the brain): semantic contextualization in human hippocampus. *bioRxiv*, 2025-06.

Katlowitz, K. A., Shah, S., Franch, M. C., Adkinson, J., Belanger, J. L., Mathura, R. K., ... & Sheth, S. A. (2025). Learning and language in the unconscious human hippocampus. bioRxiv, 2025-04.

Kaufman, M. T., Churchland, M. M., Ryu, S. I., & Shenoy, K. V. (2014). Cortical activity in the null space: permitting preparation without movement. Nature Neuroscience, 17(3), 440-448.

Keane, M. M., Bousquet, K., Wank, A., & Verfaellie, M. (2020). Relational processing in the semantic domain is impaired in medial temporal lobe amnesia. J Neuropsychol 14 (3): 416–430.

Koster-Hale, J., & Saxe, R. (2013). Theory of mind: a neural prediction problem. Neuron, 79(5), 836-848.

Lamm, C., Batson, C. D., & Decety, J. (2007). The neural substrate of human empathy: effects of perspective-taking and cognitive appraisal. Journal of cognitive neuroscience, 19(1), 42-58.

Lemaitre, G., Nogueira, F., & Aridas, C. K. (2017). Imbalanced-learn: A python toolbox totackle the curse of imbalanced datasets in machine learning. *Journal of machine learning research*, *18*(17), 1-5.

Leutgeb, S., Leutgeb, J. K., Barnes, C. A., Moser, E. I., McNaughton, B. L., & Moser, M. B. (2005). Independent codes for spatial and episodic memory in hippocampal neuronal ensembles. *Science*, *309*(5734), 619-623.

Li, X., Morgan, P. S., Ashburner, J., Smith, J., & Rorden, C. (2016). The first step for neuroimaging data analysis: DICOM to NIfTI conversion. Journal of neuroscience methods, 264, 47-56.

Libby, A., & Buschman, T. J. (2021). Rotational dynamics reduce interference between sensory and memory representations. Nature neuroscience, 24(5), 715-726.

Magnotti, J. F., Wang, Z., & Beauchamp, M. S. (2020). RAVE: Comprehensive open-sourcesoftware for reproducible analysis and visualization of intracranial EEG data. NeuroImage, 223, 117341.

Manns, J. R., Hopkins, R. O., & Squire, L. R. (2003). Semantic memory and the human hippocampus. *Neuron*, *38*(1), 127-133.

McInnes, L., Healy, J., & Melville, J. (2018). Umap: Uniform manifold approximation and projection for dimension reduction. arXiv preprint arXiv:1802.03426.

McInnes, L., Healy, J., & Astels, S. (2017). hdbscan: Hierarchical density based clustering. J. Open Source Softw., 2(11), 205.

Mikolov, T., Chen, K., Corrado, G., & Dean, J. (2013). Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*.

Montagrin, A., Saiote, C., & Schiller, D. (2018). The social hippocampus. Hippocampus, 28(9), 672-679

Moscovitch, M., Rosenbaum, R. S., Gilboa, A., Addis, D. R., Westmacott, R., Grady, C., ... & Nadel, L. (2005). Functional neuroanatomy of remote episodic, semantic and spatial memory: a unified account based on multiple trace theory. Journal of anatomy, 207(1), 35-66.

Mukamel, R., Ekstrom, A. D., Kaplan, J., Iacoboni, M., & Fried, I. (2010). Single-neuron responses in humans during execution and observation of actions. Current biology, 20(8), 750-756.

Myers, J., Xiao, J., Mathura, R. K., Shofty, B., Gates, V., Adkinson, J., ... & Sheth, S. A. (2025). Intracranial directed connectivity links subregions of the prefrontal cortex to major depression. Nature communications, 16(1), 6309.

Piai, V., Anderson, K. L., Lin, J. J., Dewar, C., Parvizi, J., Dronkers, N. F., & Knight, R. T.(2016). Direct brain recordings reveal hippocampal rhythm underpinnings of language processing. Proceedings of the National Academy of Sciences, 113(40), 11366-11371.

Piantadosi, S. T., Muller, D. C., Rule, J. S., Kaushik, K., Gorenstein, M., Leib, E. R., & Sanford, E. (2024). Why concepts are (probably) vectors. *Trends in Cognitive Sciences*, *28*(9), 844-856.

Pickering, M. J., & Garrod, S. (2013). An integrated theory of language production and comprehension. Behavioral and brain sciences, 36(4), 329-347.

Pearson, J. M., Hayden, B. Y., & Platt, M. L. (2010). Explicit information reduces discounting
behavior in monkeys. Frontiers in psychology, 1, 237.

Perich, M. G., Narain, D., & Gallego, J. A. (2025). A neural manifold view of the brain. *Nature*
Neuroscience, 1-16.

Provenza, N. R., Reddy, S., Allam, A. K., Rajesh, S. V., Diab, N., Reyes, G., ... & Sheth, S. A.
(2024). Disruption of neural periodicity predicts clinical response after deep brain
stimulation for obsessive-compulsive disorder. Nature Medicine, 30(10), 3004-3014.

Provenza, N., Reddy, S., Rajesh, S., Allam, A., Diab, N., Reyes, G., ... & Sheth, S. A. (2024).
Neuromodulatory Disruption of Pathological Circadian Neural Rhythms Predicts Clinical
Response in OCD. Biological Psychiatry, 95(10), S23.

Provenza, N. R., Rajesh, S. V., Reyes, G., Katlowitz, K. A., Pugalenthi, L. S., Bechtold, R. A., ...
& Sheth, S. A. (2025). High beta power in the ventrolateral prefrontal cortex indexes
human approach behavior: a case study. Journal of Neuroscience, 45(37).

Rey, H. G., Gori, B., Chaure, F. J., Collavini, S., Blenkmann, A. O., Seoane, P., ... & Quiroga, R.
Q. (2020). Single neuron coding of identity in the human hippocampal formation.
Current Biology, *30*(6), 1152-1159.

Rizzolatti, G., & Arbib, M. A. (1998). Language within our grasp. *Trends in neurosciences*,
21(5), 188-194.

Rizzolatti, G., & Craighero, L. (2004). The mirror-neuron system. Annu. Rev. Neurosci., 27(1),
169-192.

Savitzky, A., & Golay, M. J. (1964). Smoothing and differentiation of data by simplified least
squares procedures. Analytical chemistry, 36(8), 1627-1639.

Silbert, L. J., Honey, C. J., Simony, E., Poeppel, D., & Hasson, U. (2014). Coupled neural
systems underlie the production and comprehension of naturalistic narrative speech.
Proceedings of the National Academy of Sciences, 111(43), E4687-E4696.

Singer, T., Seymour, B., O'doherty, J., Kaube, H., Dolan, R. J., & Frith, C. D. (2004). Empathy
for pain involves the affective but not sensory components of pain. Science, 303(5661),
1157-1162.

Tang, C., Herikstad, R., Parthasarathy, A., Libedinsky, C., & Yen, S. C. (2020). Minimally
dependent activity subspaces for working memory and motor preparation in the lateral
prefrontal cortex. Elife, 9, e58154.

Tavares, R. M., Mendelsohn, A., Grossman, Y., Williams, C. H., Shapiro, M., Trope, Y., &
Schiller, D. (2015). A map for social navigation in the human brain. Neuron, 87(1), 231-
243.

Tian, Z., Chen, J., Zhang, C., Min, B., Xu, B., & Wang, L. (2024). Mental programming of
spatial sequences in working memory in the macaque frontal cortex. Science, 385(6716),
eadp6091.

Tremblay, P., & Dick, A. S. (2016). Broca and Wernicke are dead, or moving past the classicn
model of language neurobiology. Brain and language, 162, 60-71.

Tversky, A. (1977). Features of similarity. *Psychological review, 84*(4), 327.

van der Maaten, L., & Hinton, G. (2008). User's Guide for t-SNE Software. *Structure*.

van de Ven, V., Waldorp, L., & Christoffels, I. (2020). Hippocampus plays a role in speech
feedback processing. NeuroImage, 223, 117319.

Wang, M. Z., & Hayden, B. Y. (2021). Latent learning, cognitive maps, and curiosity. Current
Opinion in Behavioral Sciences, 38, 1-7.

Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., ... & Rush, A. M. (2019).
Huggingface's transformers: State-of-the-art natural language processing. arXiv preprint
arXiv:1910.03771.

Xiao, J., Adkinson, J. A., Allawala, A. B., Banks, G., Bartoli, E., Fan, X., ... & Hayden, B. Y.
(2024). Insula uses overlapping codes for emotion in self and others. *bioRxiv*

Xie, Y., Hu, P., Li, J., Chen, J., Song, W., Wang, X. J., ... & Wang, L. (2022). Geometry of
sequence working memory in macaque prefrontal cortex. Science, 375(6581), 632-639.

Xu, D., Chung, J. E., Silva, A. B., Metzger, S. L., Greicius, Q. R., Zhang, Y., ... & Chang, E. F.
(2024). Human precentral gyrus neurons link speech sequences from listening to
speaking. bioRxiv, 2024-12.

Yacoub, E., Grier, M. D., Auerbach, E. J., Lagore, R. L., Harel, N., Adriany, G., ... &
Zimmermann, J. (2020). Ultra-high field (10.5 T) resting state fMRI in the macaque.
Neuroimage, 223, 117349.

Yang, A. I., Wang, X., Doyle, W. K., Halgren, E., Carlson, C., Belcher, T. L., ... & Thesen,
T.(2012). Localization of dense intracranial electrode arrays using magnetic resonance
imaging. *Neuroimage*, *63*(1), 157-165.

Yoo, S. B. M., & Hayden, B. Y. (2020). The transition from evaluation to selection involves
neural subspace reorganization in core reward regions. Neuron, 105(4), 712-724.

Zada, Z., Goldstein, A., Michelmann, S., Simony, E., Price, A., Hasenfratz, L., ... & Hasson, U.
(2024). A shared model-based linguistic space for transmitting our thoughts from brain to
brain in natural conversations. *Neuron*, *112*(18), 3211-3222.