Analysing a Reported Experiment That May Demonstrate the Interplay of Fluid Velocity and Pore Pressure in Bone Adaptation

Himanshu Shekhar[1], Jitendra Prasad[1]

[1] Biomechanical Creativity & Innovation Lab

Department of Mechanical Engineering, IIT Ropar

Himanshu Shekhar

Department of Mechanical Engineering,

Indian Institute of Technology Ropar,

Rupnagar, Punjab, India, 140001

Email: himanshu.19mez0001@iitrpr.ac.in

Jitendra Prasad*

Department of Mechanical Engineering,

Indian Institute of Technology Ropar,

Rupnagar, Punjab, India, 140001

Email- jprasad@iitrpr.ac.in

*Corresponding author

Abstract

Existing models suggest that osteogenesis occurs in regions of the elevated stimuli, such as peak strain, high fluid velocity, and pore pressure. However, an in vivo study shows that cantilever loading-induced osteogenesis is prominent only at the anterio-lateral side of the mid-diaphyseal section of a mouse tibia, despite an equal magnitude of strain, fluid velocity, and pore pressure at the medial-posterior surface, located just opposite to it. This indicates that the magnitude of individual stimuli alone is not sufficient, as these stimuli appear to interact to induce new bone formation. The present work aims to investigate this interplay by analysing the above-mentioned in vivo study, and developing an improved mathematical model to predict new bone formation.

A poroelastic model was developed using finite element analysis. The tensile side of the bone section was found to have predominantly negative pore-pressure, which stretches the cell processes radially. In contrast, the compressive side predominantly exhibits positive pore pressure, which compresses the osteocyte processes radially. According to the literature, fluid flow applies drag forces on the tethering fibres of osteocytes, resulting in radial stretching of the cell processes, similar to the effect of negative pressure. Accordingly, the net radial displacement due to the combined effect of fluid flow and pore pressure is expected to be greater at the anterio-lateral site compared with the medio-posterior site. We hypothesize that this mechanism leads to new bone formation at the anterio-lateral side only.

To test this hypothesis, a Fourier series was used to approximate pore pressure as well as fluid velocity. In line with the literature, effective negative pressure due to fluid flow was assumed to be proportional to the fluid velocity. The strains induced by these stimuli were analytically computed assuming viscoelastic behaviour. The viscoelastic dissipation energy density due to the combined effect was then computed. The mineral apposition rate (MAR) was assumed to be proportional to the square root of the dissipation energy density above a reference value, consistent with the literature.

The present work provides evidence that fluid velocity and pore pressure are not only critical stimuli for new bone formation but that their interaction governs the process. This insight advances existing knowledge and may help in designing interventions for treating bone loss.

Keywords: Cortical bone, new bone formation, mathematical model, finite element analysis, dissipation energy density, load-induced fluid flow, pore pressure, mouse tibia, viscoelasticity, poroelasticity.

1. Introduction

Nature is renowned for producing structurally optimized structures, and bone is one such example. It continuously adapts and optimizes its microstructure in response to its mechanical loading environment [1]. The optimization is achieved by the coordinated activities of bone-forming cells (osteoblasts) and bone-resorbing cells (osteoclasts) [2]. Another prominent bone cell type, the osteocytes [3] [2] (former osteoblasts), are believed to direct the activities of these two cell types through their intricate lacuno-canalicular network (LCN) embedded in the bone matrix [4]. However, how osteocytes sense mechanical loading/unloading and direct the working cells is still poorly understood.

Over the past few decades, dedicated efforts have been made to decipher the mechanism of bone adaptation. Notably, the pioneering work of Piekarski and Munro [5] contributed substantially to our understanding of load-induced fluid flow within the lacuno-canalicular system (LCS). Further evidence of load-induced fluid flow was provided by Knoth et al.[6] [7], who used a tracer to confirm its existence within the LCS. After this work, it became well established that load-induced fluid flow is the primary transport mechanism [8], facilitating the movement of biomolecules necessary to maintain bone health.

Estimating fluid velocity induced by mechanical loading remains challenging due to the complexity of the LCS. Very few studies have measured real-time solute transport within the LCS to estimate fluid velocity [9]. To overcome such difficulties, finite element analysis was employed [10] [11] [12]. Subsequently, numerous mathematical models were developed, and fluid flow within the LCS was recognized as a prime stimulus correlating with new bone formation [13] [14] and disuse-induced bone loss [15]. While loading-induced fluid flow is well appreciated in the literature, the role of load-induced pore pressure within the LCS in promoting osteogenesis has been largely overlooked.

When bone is mechanically strained, a pressure gradient develops within the LCS that drives fluid flow. However, pore pressure itself cannot be ignored, as it can also radially stretch or compress the osteocyte processes depending on the loading environment. In vitro studies further confirm the potential role of pore pressure in osteogenesis [16] [17]. Recently, Singh et al. [18] proposed a robust formulation correlating the mineral apposition rate (MAR), a measure of new bone formation, with the dissipation energy density due to load-induced fluid flow and pore pressure. Researchers have modeled cortical bone as a poroelastic material [10] and applied Biot's theory [19] to estimate pore pressure and fluid velocity, considering periosteal and endocortical surfaces as impermeable and permeable, respectively.

It is noteworthy that new bone formation has been detected in regions of elevated fluid velocity [18] and pore pressure. However, in cantilever loading experiments on mouse tibiae, new bone formation occurred at the anterio-lateral site [20] but not at the medio-posterior site, despite both sites exhibiting equal magnitudes of peak normal strain (1280 με), fluid velocity, and pore pressure (Fig. 1). This raises a critical question: Why does this happen?' Why is the tensile side (anterio-lateral) more prone to bone formation compared to the compressive side (medio-posterior)?

To address this, we first developed a poroelastic model of the mouse tibia, adapting the cantilever loading protocol from Srinivasan et al. [20]. Interestingly, while fluid velocity was similar at both sites, the sign of pore pressure was opposite. Tensile strain at the anterio-lateral surface induced negative pore pressure (Fig. 1(e)), promoting radial stretching of the osteocyte cell wall (Fig. 1(g)), similar to the effect of fluid flow [21]. In contrast, compressive strain at the medio-posterior site induced positive pore pressure, which acted opposite to the fluid flow on the cell processes (Fig. 1(f)). Thus, the net algebraic effect at the tensile site was significant and promoted osteogenesis. This observation motivates the present work. We hypothesized that the combined effect of fluid flow and pore pressure is greater at the tensile site, thereby driving new bone formation.

To test this hypothesis, we present a robust methodology to capture the role of dissipation energy at the osteocytes due to the combined effects of load-induced fluid flow and pore pressure. The developed mathematical model was validated using existing cantilever loading-induced new bone formation data in the literature [20]. The accuracy of the model was assessed using statistical tests, viz., Student's t-test and Watson U^2 test. The t-test compared the in-vivo bone formation rate per unit bone surface (BFR/BS) with values computed by the model, while the Watson U^2 test compared the in-vivo site-specific distribution of new bone formation with that predicted by the model.

The paper is structured as follows: Section 2 outlines the methodology, Section 3 presents the results, Section 4 discusses the findings, and Section 5 provides the conclusions.

Fig. 1: (a) Mouse tibia subjected to cantilever loading of 0.5 N (loading protocol adapted from Srinivasan et al. [22]); (b) corresponding induced normal strain ($\mu\varepsilon$) at the mid diaphysis; (c) induced new bone formation at the anterio-lateral site; (d) induced fluid velocity (mm/s), where fluid flow tends to expand the cell processes; (e) developed pore pressure (MPa), with positive pressure at the medio-posterior site compressing the cell processes and negative pressure at the anterio-lateral site expanding them; (f) magnified view of osteocyte connectivity at the medio-

posterior site, black arrow indicates fluid flow action, red arrow indicates pore pressure action; (g) magnified view of osteocyte connectivity at the anterio-lateral site.

2. Methodology

2.1. Experimental Data

The in vivo data for the cantilever loading protocol, including the corresponding BFR/BS values and site-specific new bone formation distributions, were adapted from the study by Srinivasan et al. [20]. Three loading regimes were considered, as detailed below.

2.1.1 Low Magnitude

The low-magnitude loading protocol was conducted on 10-week-old C57BL/6J female mice (n = 6). A trapezoidal waveform with a strain rate of 0.01/s and a peak load of 0.25 N was applied for 5 consecutive days (100 cycles per day). This loading induced a peak normal strain of 650 $\mu\varepsilon$ at the mid-diaphysis of the mouse tibia. The corresponding BFR/BS value was 0.011 ± 0.013 $\mu m^3/\mu m^2/day$.

2.1.2 Low Magnitude with Rest-Insertion

The low-magnitude loading protocol with 10 s rest insertion was also conducted on 10-week-old C57BL/6J female mice (n = 6). A trapezoidal waveform with a strain rate of 0.01/s and a peak load of 0.25 N was applied for 5 consecutive days (10 cycles per day), with a 10 s rest period between successive loading cycles. This induced a peak normal strain of 650 $\mu\varepsilon$ at the mid-diaphysis. The corresponding BFR/BS value was 0.095 ± 0.071$\mu m^3/\mu m^2/day$.

2.1.3 High Magnitude

The high-magnitude loading protocol was performed on 10-week-old C57BL/6J female mice (n = 6). A trapezoidal waveform with a strain rate of 0.02/s and a peak load of 0.5 N was applied for 5 consecutive days (100 cycles per day). This loading induced a peak normal strain of 1300 $\mu\varepsilon$ at the mid-diaphysis. The corresponding BFR/BS value was 0.2238 ± 0.1221$\mu m^3/\mu m^2/day$.

2.2 Loading and Boundary Conditions

The analysis was focused on the mid-diaphysis of the mouse tibia; performing a poroelastic analysis of the entire tibia would be computationally expensive. The bone was idealized as a prismatic bar, 3 mm in length, with a cross-section similar to that of the mid-diaphysis of a C57BL6J mouse tibia studied by Srinivasan et al. [20]. In the literature, the periosteal surface is generally considered impermeable, while the endocortical surface is permeable [18], respectively. Accordingly, these conditions were implemented zero-flow and zero-pressure boundary conditions, respectively.

Three different trapezoidal loading waveforms, low magnitude (Fig.2(d)), low magnitude with rest insertion (Fig. 2 (e)), and high magnitude (Fig. 2(f)), were adapted from Srinivasan et al. [22] and applied in the finite element analysis to compute the strain, fluid velocity, and pore pressure (see Section 2.3).

Fig. 2: (a) Tibia and fibula of a mouse, with the cross-section of interest highlighted; (b) cross-section of interest as studied by Srinivasan et al. [22]; (c) prismatic bar of 3mm length created for poroelastic analysis, with a cross-section similar to that used in the experiment. One end of the prismatic bar was fixed, while the other end was loaded in all three directions (x, y and z) to induce strains similar to those reported by Srinivasan et al.[22]. The loading waveforms were also adapted from the same study: (d) low magnitude; (e) low magnitude with 10 s rest between cycles; (f) high magnitude.

2.3   Finite Element Analysis

Cortical bone consists of a solid matrix and pores through which biofluid passes to maintain homeostasis. These porosities exist at different length scales, such as vascular, lacuna-canalicular, and collagen-fiber levels. Dynamic load-induced fluid flow and pore pressure developed within the lacuna-canalicular porosities are primarily considered stimuli that promote osteogenesis. Therefore, only LCN porosity was considered in the present poroelastic analysis, and the corresponding permeability value was adapted from earlier studies on mouse tibia (Table 1) [23] [24]. The behavior of such a poroelastic material under loading was analyzed using Biot's theory of poroelasticity, and the finite element analysis was conducted in ABAQUS [25]. The poroelastic material properties were taken from earlier mouse tibia studies [15] [26] and are listed in Table 1.

The prismatic bar, 3 mm in length, was meshed with 15,120 linear hexahedral elements after convergence analysis. ABAQUS provides the element type C3D8RP (continuous 3-dimensional 8-noded reduced integration pore pressure) for analyzing poroelastic behavior under loading. These elements have four degrees of freedom per node: three displacement components (u_x, u_y, u_z) in the x, y, and z directions, respectively, and pore pressure as the fourth. Darcy law, which relates fluid velocity to the pressure gradient, was used to compute fluid velocity at the integration points. Further details of the constitutive relation can be found in the earlier study [15].

One end of the meshed prismatic bar was fixed, and the other end was loaded in all three directions to induce strains similar to those in the experimental study. The obtained strain patterns and corresponding peak strain values were verified and found to agree closely with the experimental values. Load-induced strain (EE33), fluid velocity, and pore pressure are shown in Fig. 3.

Table 1: Poroelastic material properties used in the simulations (adapted from Kumar et al. [26][15], except permeability value from Zhou et al.[24] [27])

Properties	Magnitude	Unit
Young's modulus of bone	12	GPa
Fluid bulk modulus	2.3	GPa
Solid bulk modulus	17	GPa
Porosity	0.05	
Poisson's ratio	0.3	
Intrinsic permeability (k)	3.79×10^{-21}	m^2

Fig. 3: Contour plots from finite element analysis under three loading protocols: (a) low-magnitude loading showing strain (με), fluid velocity (mm/s), pore pressure (MPa), and pressure-velocity vs. time at node 9524 (tensile side of the cross-section); (b) low-magnitude loading with 10 s rest between cycles showing strain (με), fluid velocity (mm/s), pore pressure (MPa), and pressure-velocity vs. time at node 9524; (c) high-magnitude loading showing strain (με), fluid velocity (mm/s), pore pressure (MPa), and pressure-velocity vs. time at node 9524.

2.4   Derivation of Load-induced Dissipation Energy Density

We computed the load-induced fluid velocity and pore pressure with respect to the applied loading protocol at the osteocyte level. These load-induced stimuli act directly on osteocytes and their cell processes. Fluid flow induces radial stretching, tending to expand the cell processes [28]. In contrast, the effect of pore pressure is sign-dependent: negative pressure (observed on the tensile strain side at the lateral surface of the mid-diaphysis) stretches the cell processes, similar to fluid flow; whereas positive pore pressure compresses the cell processes, opposing the action of fluid flow.

The effect of fluid flow can be described using viscous damping, where the damping force (F) is directly proportional to the velocity.

$$F = \alpha v \tag{1}$$

where α is a proportionality constant. The net radial stretch at a point can therefore be expressed as: $\sigma(t) = -p\,(t) + \alpha v(t)$.

Fig. 4: (a) Idealized lacuna-canalicular system, with the arrow indicating load-induced fluid flow in the pericellular space; (b) osteocytes and their processes modeled as a viscoelastic material under the influence of the net stretching effect, where E and η represent the elastic and viscous terms, respectively; (c) left-hand side view of the cross section of a canaliculus, where the black filled circle represents the cell process and the radially outward lines depict the tethering fibers.

Osteocytes and their processes can be modeled as viscoelastic materials under the influence of these stimuli, which leads to viscoelastic dissipation. The corresponding dissipation energy density has been adopted as a stimulus for new bone formation.

We idealized viscoelastic dissipation through the Kelvin-Voigt model (Fig. 4(b)), which represents the material response as a spring and a damper connected in parallel:

$$\sigma(t) = E\varepsilon(t) + \eta\dot{\varepsilon}(t) \tag{2}$$

where E is the elastic modulus, η is the viscosity, ε(t) is strain, and $\dot{\varepsilon}$(t) is strain rate. Here, σ(t) is a time-dependent function, which can be expressed as a Fourier series:

$$E\varepsilon(t) + \eta\dot{\varepsilon}(t) = \sigma(t) = \frac{A_0}{2} + \sum_{m=1}^{\infty} A_m \cos\left(\frac{2\pi m}{T}t\right) + \sum_{n=1}^{\infty} B_n \sin\left(\frac{2\pi n}{T}t\right) \tag{3}$$

where, A_0, A_m, and B_n are constants, and m and n are harmonic numbers.

The viscoelastic dissipation energy density per unit cycle of loading is:

$$\varphi = \int_0^T \sigma(t)\frac{d\varepsilon(t)}{dt}\,dt \tag{4}$$

Since $\sigma(t)$ is known (as a function of pore pressure and fluid velocity), $\varepsilon(t)$ can be calculated from Eq. (2), with boundary condition $\varepsilon(t=0) = 0$:

$$\varepsilon(t) = \frac{A_0}{2E} + \sum_{m=1}^{\infty} \varepsilon_{m_o} \cos\left(\frac{2\pi m}{T}t - \psi_m\right) + \sum_{n=1}^{\infty} \varepsilon_{n_o} \sin\left(\frac{2\pi n}{T}t - \theta_n\right) \tag{5}$$

and

$$\frac{d\varepsilon(t)}{dt} = \sum_{m=1}^{\infty} -\frac{2\pi m}{T}\varepsilon_{m_o} \sin\left(\frac{2\pi m}{T}t - \psi_m\right) + \sum_{n=1}^{\infty} \frac{2\pi n}{T}\varepsilon_{n_o} \cos\left(\frac{2\pi n}{T}t - \theta_n\right) \tag{6}$$

Using Eq. (4), dissipation energy density per cycle can be written as:

$$\varphi = \sum_{m=1}^{\infty} \pi\eta\left(\frac{2\pi m}{T}\right)\frac{A_m^{\,2}}{E^2 + \eta^2\left(\frac{2\pi m}{T}\right)^2} + \sum_{n=1}^{\infty} \pi\eta\left(\frac{2\pi n}{T}\right)\frac{B_n^{\,2}}{E^2 + \eta^2\left(\frac{2\pi n}{T}\right)^2} \tag{7}$$

where, A_m and B_n are:

$$A_m = \frac{2}{T}\int_0^T \sigma(t)\cos\left(\frac{2\pi m}{T}t\right)dt \tag{8}$$

$$B_n = \frac{2}{T}\int_0^T \sigma(t)\sin\left(\frac{2\pi n}{T}t\right)dt \tag{9}$$

Since $\sigma(t) = -p(t) + \alpha v(t)$, the Fourier expansions yield (with $T = T_0$):

$$\sigma(t) = \sum_{m=1}^{\infty} (\alpha A_{vm} - A_{pm}) \cos\left(\frac{2\pi m t}{T_0}\right) + \sum_{n=1}^{\infty} (\alpha B_{vn} - B_{pn}) \sin\left(\frac{2\pi n t}{T_0}\right)$$

Hence, dissipation energy density becomes:

$$\varphi = \sum_{m=1}^{\infty} \pi\eta\left(\frac{2\pi m}{T_0}\right) \frac{(\alpha A_{vm} - A_{pm})^2}{E^2 + \left(\frac{2\pi m}{T_0}\eta\right)^2} + \sum_{n=1}^{\infty} \pi\eta\left(\frac{2\pi n}{T_0}\right) \frac{(\alpha B_{vn} - B_{pn})^2}{E^2 + \left(\frac{2\pi n}{T_0}\eta\right)^2} \tag{10}$$

This can be decomposed as:

$$\varphi = \underbrace{\varphi_p}_{pore\ pressure\ dissipation} + \overbrace{\alpha^2 \varphi_v}^{fluid\ velocity\ dissipation} - \underbrace{2\alpha\varphi_{pv}}_{combined\ effect} \tag{11}$$

where,

$$\varphi_p = \sum_{m=1}^{\infty} \pi\eta\left(\frac{2\pi m}{T_0}\right) \frac{A_{pm}^2}{E^2 + \eta^2\left(\frac{2\pi m}{T_0}\right)^2} + \sum_{n=1}^{\infty} \pi\eta\left(\frac{2\pi n}{T_0}\right) \frac{B_{pn}^2}{E^2 + \eta^2\left(\frac{2\pi n}{T_0}\right)^2} \tag{12}$$

$$\varphi_v = \sum_{m=1}^{\infty} \pi\eta\left(\frac{2\pi m}{T_0}\right) \frac{A_{vm}^2}{E^2 + \eta^2\left(\frac{2\pi m}{T_0}\right)^2} + \sum_{n=1}^{\infty} \pi\eta\left(\frac{2\pi n}{T_0}\right) \frac{B_{vn}^2}{E^2 + \eta^2\left(\frac{2\pi n}{T_0}\right)^2} \tag{13}$$

$$\varphi_{pv} = \sum_{m=1}^{\infty} \pi\eta\left(\frac{2\pi m}{T_0}\right) \frac{A_{vm} A_{pm}}{E^2 + \eta^2\left(\frac{2\pi m}{T_0}\right)^2} + \sum_{n=1}^{\infty} \pi\eta\left(\frac{2\pi n}{T_0}\right) \frac{B_{vn} B_{pn}}{E^2 + \eta^2\left(\frac{2\pi n}{T_0}\right)^2} \tag{14}$$

with Fourier coefficients:

$$A_{pm} = \frac{2}{T_0} \int_0^{T_0} p(t) \cos\left(\frac{2\pi m t}{T_0}\right) dt$$

$$B_{pn} = \frac{2}{T_0} \int_0^{T_0} p(t) \sin\left(\frac{2\pi n t}{T_0}\right) dt$$

$$A_{vm} = \frac{2}{T_0} \int_0^{T_0} v(t) \cos\left(\frac{2\pi m t}{T_0}\right) dt$$

$$A_{vn} = \frac{2}{T_0} \int_0^{T_0} v(t) \sin\left(\frac{2\pi n t}{T_0}\right) dt$$

2.5 Zone of Influence

Each osteocyte contributes to osteogenesis; however, its influence decreases as the distance from the osteocyte increases, and is greater when the target location is nearby. This non-local behavior of osteocytes has been modeled in the literature using different approaches. Prasad and Goyal [29] employed a diffusion-based model, while Singh et al. [18], Kumar et al.[26], and Shekhar et al. [15] used the zone of influence (ZOI) concept. In the present study, the ZOI approach was adopted to average the stimulus (dissipation energy density) from each osteocyte, as illustrated in Fig. 5(a). A weightage average scheme was applied such that nodes farther from the target node contributed less, while closer nodes contributed more. The exponential weighting function $w = e^{-5(|x|/r)}$ was adopted from earlier studies [26], where r is the radius of the ZOI and $|x|$ is the distance between the target node and a node within the ZOI. The value of r was taken as 170 μm, corresponding to the mean cortical thickness at the mid-diaphysis of the mouse tibia (average of maximum and minimum cortical thickness).

2.6 Computation of Mineral Apposition Rate

The site-specific new bone formation is commonly quantified using the parameter mineral apposition rate (MAR). Previous studies correlated MAR with different stimuli such as load-induced dissipation energy density, strain rate, and strain energy density. However, no robust or universally accepted relationship has been established. Recently, Singh et al. [18] proposed a formulation suggesting that MAR is directly proportional to the square root of the dissipation energy density minus a threshold value, with osteogenesis is triggered only when the stimulus exceeds this threshold. Notably, this concept holds not only for new bone formation, but also for disuse-induced bone loss [23].

Fig. 5: (a) Averaging of the stimulus using the zone of influence (ZOI). Gray nodes represent the overall bone cross-section, the red node indicates the target node where the stimulus is computed, and blue nodes denote the contributing nodes influencing the target node. (b) Computation of experimental MAR at each i^{th} node of interest using an in-house code (yellow indicates new bone formation).

This relation can be written as:

$$MAR = A\left(\sqrt{\varphi} - \sqrt{\varphi_{thres}}\right) \tag{12}$$

where *A* is the remodeling rate. Hence, using Eqs. (10) and (11), *MAR* can be expressed as:

$$MAR_{model} = A\left(\sqrt{\varphi_p + \alpha^2\varphi_v - 2\alpha\varphi_{pv}} - \sqrt{\varphi_{thres}}\right) \tag{13}$$

Here, *A*, α, and φ_{thres} are constants to be determined. *MAR* (mm^3/mm^2/day) is defined as the total new bone volume formed per unit bone surface per unit time i.e., the new bone thickness added at each point on the cross-section.

For computational convenience, the periosteal surface was divided into 360 segments, and the corresponding MAR value was computed at each i^{th} point (the common point between two segments), as shown in Fig. 5(b):

$$MAR^i_{model} = A\left(\sqrt{\varphi_p^i + \alpha^2\varphi_v^i - 2\alpha\varphi_{pv}^i} - \sqrt{\varphi_{thres}}\right) \tag{14}$$

where, φ_p^i, φ_v^i, and φ_{pv}^i are known from Eqs. (10) and (11). The constants *A*, α, and φ_{thres} were determined by comparing with experimental new bone formation data reported in the

literature [20]. The experimental MAR (MAR_{exp}^i) was computed at 360 points (Fig. 5(b)) using an in-house MATLAB code. The constants were obtained by minimizing the squared error:

$$\min f(A, \alpha, \varphi_{thres}) = \sum_{i=1}^{360} \left(MAR_{exp}^i - MAR_{model}^i\right)^2 \tag{15}$$

The minimization problem was solved using the Levenberg-Marquardt algorithm in MATLAB, which fits Eq. (13) to the experimental MAR (MAR_{exp}^i) of the high-magnitude loading protocol and computes the optimal values of A, α, and φ_{thres}. The obtained optimal values were:

$A = 6.09 \times 10^{-5} \text{mm}^2/\sqrt{N}$ /day

$\alpha = 107230$

$\varphi_{thres} = 1.6 \text{ mm}^3/\text{mm}^2/\text{day}$

These constants were subsequently used to predict MAR for the other two loading protocols, i.e., low magnitude and low magnitude with rest insertion. Model predictions were evaluated using two statistical tests: Student's t-test and Watson's U^2 test. The Student's t-test compared the model bone formation rate (BFR/BS) with the experimental BFR value, while the Watson's U^2 test compared the site-specific new bone distribution.

2.7 Statistical Analysis

The new bone formation area per unit time was calculated by integrating MAR over the periosteal circumference. The bone formation rate per unit bone surface (BFR/BS) was then obtained by dividing the new bone formation area per unit time by the total perimeter of the periosteal surface of the mouse tibia.

A one-sample, two-tailed Student's t-test was used to compare the experimental BFR/BS values reported in the literature with those predicted by the model. In addition, a circular goodness-of-fit test, viz., Watson's U^2 test [30] was employed to compare the experimental site-specific distribution of new bone formation with that predicted by the model.

3. Results

3.1 High Magnitude

The constants obtained by minimizing the squared error were first applied to predict new bone formation under the high-magnitude protocol. The BFR/BS values were compared using a bar chart (Fig. 6(d)), and the model-predicted BFR/BS ($0.2354\ \mu m^3/\mu m^2/day$) was not significantly different from the experimental BFR/BS value ($0.2238 \pm 0.1221\ \mu m^3/\mu m^2/day$, $p =0.87$, Student's t-test). The experimental site-specific new bone formation (Fig. 6 (c)) was also compared with the model-predicted distribution, and no significant difference was observed ($p = 0.70$, Watson U^2 test).

3.2 Low Magnitude

The same constants were used to predict osteogenesis under the low-magnitude loading protocol. A comparison of experimental and model-predicted BFR/BS values is shown in Fig. 6(d). Statistical analysis indicates no significant difference between the experimental BFR/BS (0.011 ± 0.013 $\mu m^3/\mu m^2/day$) and the model-predicted BFR/BS (0.014 $\mu m^3/\mu m^2/day$, p=0.82, Student's t-test). The site-specific bone distribution of new bone formation (Fig. 6(a)) was also compared using the Watson U^2 test and was found not to differ significantly (p=0.78).

3.3 Low Magnitude with Rest Insertion

Introducing a 10-second rest between loading cycles significantly enhanced new bone formation compared to the continuous low-magnitude loading protocol (Fig. 6(d)). The periosteal new bone formation induced by the rest-insertion protocol was evaluated using both Student's t-test and the Watson U^2 test. The Student's t-test compared the experimental BFR/BS with the model-predicted BFR/BS, and the bar chart comparison showed that the model value (0.0621 $\mu m^3/\mu m^2/day$) was not significantly different from the experimental value (0.095 ± 0.071 $\mu m^3/\mu m^2/day$, p=0.86). Similarly, the site-specific new bone formation (Fig. 6(b)) was not significantly different (p=0.89, Watson U^2 test).

Fig. 6: Comparison of experimental new bone formation with model predictions: (a) site-specific new bone formation under the low-magnitude loading protocol (yellow indicates new bone formation); (b) site-specific new bone formation under the low-magnitude loading protocol with rest insertion; (c) site-specific new bone formation under the high-magnitude loading protocol; (d) comparison of experimental BFR/BS values with model-predicted values.

4. Discussion

The study presents a robust methodology highlighting the role of load-induced pore pressure developed within the lacunar-canalicular network (LCN) in bone mechanotransduction. A mathematical model was developed to explain why cantilever-induced new bone formation occurs predominantly at the anterior-lateral side, despite the medial-posterior side of the mid-diaphysis experiencing the same magnitudes of peak strain, fluid velocity, and pore pressure. By integrating both load-induced fluid flow in the LCS and load-induced pore pressure, the model provides deeper insight into the mechanotransduction process of bone.

The developed model successfully predicted cantilever loading-induced osteogenesis under low-magnitude, low-magnitude with rest insertion, and high-magnitude protocols with spatial accuracy. It captured not only the site-specific distribution of new bone formation but also the bone formation rate per unit bone surface (BFR/BS) across all loading protocols.

Importantly, the mathematical framework is generalizable and can be applied to predict osteogenesis under any loading protocol, regardless of waveform. Because the present methodology employs Fourier series, dissipation energy density can be computed for arbitrary loading waveforms. This makes the model uniquely suited for comparing osteogenesis across different loading waveforms and for guiding the design of exercise regimens for bone regeneration.

Earlier literature proposed strain-based mathematical models to predict osteogenesis, correlating peak strain with periosteal new bone formation only [29] [31]. However, predicting osteogenesis on both periosteal and endosteal surfaces remained a challenge. In vitro studies revealed that osteocytes respond only at very high strain levels (~30000 µε), while physiological loading typically induces tissue strains of ~2000µε [32], which is not sufficient to trigger osteocytic release biochemical signals for osteogenesis. This limitation shifted attention towards load-induced fluid flow within the LCS. Munro and Knoth provided experimental evidence for fluid flow, while Weinbaum and colleagues established the mathematical foundation. [33] [21].

Further research into the osteocyte microenvironment introduced the concept of strain amplification [34], describing how tissue-level strain amplifies into cellular-level strain. When bone is mechanically loaded, a pressure gradient develops within the porosities of the LCN, driving fluid flow within the LCS. Osteocyte processes are anchored to the bone matrix via tethering fibers (Fig. 4 (c)). As fluid passes through pericellular spaces, the cell process deforms radially, leading to dissipation of energy, which has been assumed to stimulate osteocyte activation. This paradigm has motivated mathematical models linking loading-induced stimuli to new bone formation.

Biot's theory of poroelasticity has been widely applied to model cortical bone, typically assuming periosteal and endocortical surfaces to be impermeable and permeable, respectively. This permeability of the endocortical surface results in higher fluid velocity, while the periosteal surface, being impermeable, shows negligible fluid velocity. Thus, fluid flow alone cannot account for new bone formation observed simultaneously at both surfaces, promoting further investigation into the LCS.

Over the past five decades, the role of load-induced fluid flow in bone mechanotransduction has been well recognized [5] [6] [35] [36] [37] [38], whereas the role of load-induced pore pressure has been largely overlooked. Singh et al. revisited the mechanical environment of the LCS and showed that pore pressure, in addition to fluid flow, plays a critical role in mechanotransduction. Their mathematical model correctly predicted bone formation at both surfaces simultaneously [18]. Interestingly, new bone formation was found to localize at sites of elevated stimulus. However, Srinivasan et al.[20] reported a puzzling observation: in cantilever-loaded mouse tibia, new bone formation occurred predominantly at the anterior-lateral side of the mid-diaphysis, even though the opposing medial-posterior surface experienced equal peak strain, fluid velocity, and pore pressure. This highlighted the need to examine the osteocyte microenvironment more closely.

While Singh et al.[18] considered pore pressure and fluid velocity separately – attributing fluid flow to endocortical bone formation and pore pressure to periosteal bone formation – the present study demonstrates that a complete picture emerges only when their combined effect is taken into account. Specifically, dissipation energy density arises from the interaction of these two stimuli at the osteocyte level. In this work, osteocytes and their processes were modeled as a viscoelastic material, and a methodology was proposed to compute the dissipation energy density, combining load-induced fluid velocity and pore pressure within the LCS. The developed mathematical model successfully predicted in vivo data reported in the literature (Fig. 7), including site-specific distributions under multiple loading protocols.

Fig. 7: Variation of fluid velocity and pore pressure with respect to time at node 9524 (tensile side of the bone cross-section). The time-dependent pore-pressure and fluid velocity were approximated using a Fourier series for the respective loading protocols: (a) low magnitude, (b) low magnitude with rest insertion, and (c) high magnitude.

A particularly important phenomenon captured by the model is the effect of rest insertion. Experimental data have shown that a 10-second rest between loading cycles significantly enhances new bone formation (Fig. 6(b)). The underlying mechanism can be explained by analysing fluid velocity and pore pressure dynamics (Fig. 7). At the onset of loading, pores are

relatively empty, and the pressure gradient drives fluid flow. Under continuous loading, however, fluid becomes trapped, and velocity reaches a steady state (Fig. 7(a)). In contrast, when rest intervals are introduced, fluid has sufficient time to escape and re-enter the pores, resulting in higher fluid velocities and greater pore pressure fluctuations in subsequent cycles (Fig. 7(b)). This dynamics enhances dissipation energy and, consequently, osteogenesis.

Summary of the present work:

- Load-induced fluid flow and pore pressure within the lacunar-canalicular system (LCS) are essential mechanotransductive stimuli; however, it is their combined interaction that governs new bone formation.
- The interaction of these stimuli successfully predicted the site of new bone formation and explained why the tensile side of the bone cross-section is more susceptible to osteogenesis.
- The model accurately reproduced experimental observations across three groups of mice and three different loading protocols, highlighting its robustness.
- A key contribution of this work is the development of a Fourier series-based methodology to compute dissipation energy density. This generalizable approach enables computation of stimuli under any arbitrary loading waveform and offers potential for systematically comparing osteogenic responses across diverse loading regimes.

The present model was developed with certain simplifications, which are listed below:

- The model does not incorporate the complete cellular environment, such as the attachment of tethering fibres to the bone matrix or the role of integrins.
- Bone was idealized as a linear, isotropic poroelastic material, whereas cortical bone in reality exhibits anisotropy.
- Only lacunar-canalicular (LCN) porosity was considered for fluid flow analysis. Since cortical bone contains porosities at multiple length scales (e.g., LCN and vascular porosities), incorporating vascular porosity alongside LCN may further strengthen the model.

5. Conclusions

The present work highlights the critical role of load-induced pore pressure, in combination with the fluid flow within the LCS, in promoting osteogenesis. A mathematical model was developed that correctly predicts the site of cantilever loading-induced new bone formation and proposes the underlying mechanism. The model was validated against different loading protocols reported in the literature, and its efficacy was tested using two statistical analyses, namely Student's t-test and Watson's U^2 test.

Unlike previous mathematical models, which are dependent on loading waveform, the present work proposes a methodology to compute the stimulus for new bone formation irrespective of the loading waveform. This gives the model unique potential to compare osteogenesis across diverse loading conditions reported in the literature. The comparisons may provide deeper insight into designing exercise regimens for patients suffering from bone loss.

6. References

[1] J. G. Skedros and R. A. Brand, "Biographical sketch: Georg hermann von Meyer (1815-1892)," *Clin. Orthop. Relat. Res.*, vol. 469, no. 11, pp. 3072–3076, 2011, doi: 10.1007/s11999-011-2040-6.

[2] M. B. Schaffler, W. Y. Cheung, R. Majeska, and O. Kennedy, "Osteocytes: Master orchestrators of bone," *Calcif. Tissue Int.*, vol. 94, no. 1, pp. 5–24, 2014, doi: 10.1007/s00223-013-9790-y.

[3] L. F. Bonewald, "The amazing osteocyte," *J. Bone Miner. Res.*, vol. 26, no. 2, pp. 229–238, Feb. 2011, doi: 10.1002/JBMR.320.

[4] A. Santos, A. D. Bakker, and J. Klein-Nulend, "The role of osteocytes in bone mechanotransduction," *Osteoporos. Int.*, vol. 20, no. 6, pp. 1027–1031, 2009, doi: 10.1007/s00198-009-0858-5.

[5] K. PIEKARSKI and M. MUNRO, "Transport mechanism operating between blood supply and osteocytes in long bones," *Nature*, vol. 269, no. 5623, pp. 80–82, 1977, doi: 10.1038/269080a0.

[6] M. L. Knothe Tate and U. Knothe, "An ex vivo model to study transport processes and fluid flow in loaded bone," *J. Biomech.*, vol. 33, no. 2, pp. 247–254, Feb. 2000, doi: 10.1016/S0021-9290(99)00143-8.

[7] M. L. Knothe Tate, P. Niederer, and U. Knothe, "In Vivo Tracer Transport Through the Lacunocanalicular System of Rat Bone in an Environment Devoid of Mechanical Loading," *Bone*, vol. 22, no. 2, pp. 107–117, Feb. 1998, doi: 10.1016/S8756-3282(97)00234-2.

[8] S. P. Fritton and S. Weinbaum, "Fluid and Solute Transport in Bone: Flow-Induced Mechanotransduction," *Annu. Rev. Fluid Mech.*, vol. 41, pp. 347–374, Jan. 2009, doi: 10.1146/ANNUREV.FLUID.010908.165136.

[9] C. Price, X. Zhou, W. Li, and L. Wang, "Real-time measurement of solute transport within the lacunar-canalicular system of mechanically loaded bone: Direct evidence for load-induced fluid flow," *J. Bone Miner. Res.*, vol. 26, no. 2, pp. 277–285, 2011, doi: 10.1002/jbmr.211.

[10] R. Steck, P. Niederer, and M. L. Knothe Tate, "A finite element analysis for the prediction of load-induced fluid flow and mechanochemical transduction in bone," *J. Theor. Biol.*, vol. 220, no. 2, pp. 249–259, 2003, doi: 10.1006/jtbi.2003.3163.

[11] L. Fan, S. Pei, X. Lucas Lu, and L. Wang, "A multiscale 3D finite element analysis of fluid/solute transport in mechanically loaded bone," *Bone Res.*, vol. 4, no. August, 2016, doi: 10.1038/boneres.2016.32.

[12] Q. A. Meslier and S. J. Shefelbine, "Using Finite Element Modeling in Bone Mechanoadaptation," pp. 105–116, 2023, doi: 10.1007/s11914-023-00776-9.

[13] A. F. Pereira, B. Javaheri, A. A. Pitsillides, and S. J. Shefelbine, "Predicting cortical bone adaptation to axial loading in the mouse tibia," *J. R. Soc. Interface*, vol. 12, no. 110, 2015, doi: 10.1098/rsif.2015.0590.

[14] N. Chennimalai Kumar, J. A. Dantzig, I. M. Jasiuk, A. G. Robling, and C. H. Turner, "Numerical Modeling of Long Bone Adaptation due to Mechanical Loading: Correlation with Experiments," *Ann. Biomed. Eng. 2009 383*, vol. 38, no. 3, pp. 594–604, Dec. 2009, doi: 10.1007/S10439-009-9861-4.

[15] H. Shekhar, S. Singh, and J. Prasad, "Predicting cortical bone resorption in the mouse tibia under disuse conditions caused by transient muscle paralysis," *Sci. Rep.*, vol. 15, no. 1, pp. 1–16, 2025, doi: 10.1038/s41598-025-03588-2.

[16] J. D. Gardinier, S. Majumdar, R. L. Duncan, and L. Wang, "Cyclic hydraulic pressure and fluid flow differentially modulate cytoskeleton re-organization in MC3T3 osteoblasts," *Cell. Mol. Bioeng.*, vol. 2, no. 1, pp. 133–143, 2009, doi: 10.1007/s12195-008-0038-2.

[17] C. Liu, Y. Zhao, W. Y. Cheung, R. Gandhi, L. Wang, and L. You, "Effects of cyclic hydraulic pressure on osteocytes," *Bone*, vol. 46, no. 5, pp. 1449–1456, 2010, doi: 10.1016/j.bone.2010.02.006.

[18] S. Singh, S. J. Singh, and J. Prasad, "Derivation, validation, and prediction of loading-induced mineral apposition rates at endocortical and periosteal bone surfaces based on fluid velocity and pore pressure," *Bone Reports*, vol. 19, no. November, p. 101729, 2023, doi: 10.1016/j.bonr.2023.101729.

[19] M. A. Biot, "General theory of three-dimensional consolidation," *J. Appl. Phys.*, vol. 12, no. 2, pp. 155–164, Feb. 1941, doi: 10.1063/1.1712886.

[20] S. Srinivasan, D. A. Weimer, S. C. Agans, S. D. Bain, and T. S. Gross, "Low-magnitude mechanical loading becomes osteogenic when rest is inserted between each load cycle," *J. Bone Miner. Res.*, vol. 17, no. 9, pp. 1613–1620, Sep. 2002, doi: 10.1359/jbmr.2002.17.9.1613.

[21] Y. Wang, L. M. McNamara, M. B. Schaffler, and S. Weinbaum, "A model for the role of integrins in flow induced mechanotransduction in osteocytes," *Proc. Natl. Acad. Sci. U. S. A.*, vol. 104, no. 40, pp. 15941–15946, Oct. 2007, doi: 10.1073/PNAS.0707246104.

[22] S. Srinivasan, D. A. Weimer, S. C. Agans, S. D. Bain, and T. S. Gross, "Low-magnitude mechanical loading becomes osteogenic when rest is inserted between each load cycle," *J. Bone Miner. Res.*, vol. 17, no. 9, pp. 1613–1620, 2002, doi: 10.1359/jbmr.2002.17.9.1613.

[23] H. Shekhar, S. Singh, and J. Prasad, "Predicting Cortical Bone Resorption in Disuse Condition Caused by Transient Muscle Paralysis," *bioRxiv*, p. 2023.11.21.568078, Jan. 2023, doi: 10.1101/2023.11.21.568078.

[24] X. Zhou, J. E. Novotny, and L. Wang, "Modeling fluorescence recovery after photobleaching in loaded bone: Potential applications in measuring fluid and solute transport in the osteocytic lacunar-canalicular system," *Ann. Biomed. Eng.*, vol. 36, no. 12, pp. 1961–1977, 2008, doi: 10.1007/s10439-008-9566-0.

[25] V. Abaqus, "6.14. Abaqus Analysis User's Guide," *Provid. RI, USA Dassault Syst. Simulia Corp*, 2014.

[26] N. C. Kumar, I. Jasiuk, and J. Dantzig, "Dissipation energy as a stimulus for cortical bone adaptation," *J. Mech. Mater. Struct.*, vol. 6, no. 1–4, pp. 303–319, Jun. 2011, doi:

10.2140/jomms.2011.6.303.

[27] J. D. Gardinier, C. W. Townend, K. P. Jen, Q. Wu, R. L. Duncan, and L. Wang, "In situ permeability measurement of the mammalian lacunar-canalicular system," *Bone*, vol. 46, no. 4, pp. 1075–1081, 2010, doi: 10.1016/j.bone.2010.01.371.

[28] L. You, S. C. Cowin, M. B. Schaffler, and S. Weinbaum, "A model for strain amplification in the actin cytoskeleton of osteocytes due to fluid drag on pericellular matrix," *J. Biomech.*, vol. 34, no. 11, pp. 1375–1386, 2001, doi: 10.1016/S0021-9290(01)00107-5.

[29] J. Prasad and A. Goyal, "An Invertible Mathematical Model of Cortical Bone's Adaptation to Mechanical Loading," *Sci. Rep.*, vol. 9, no. 1, pp. 1–14, Dec. 2019, doi: 10.1038/s41598-019-42378-5.

[30] G. S. WATSON, "Goodness-of-fit tests on a circle," *Biometrika*, vol. 48, no. 1–2, pp. 109–114, 1961, doi: 10.1093/biomet/48.1-2.109.

[31] A. K. Tiwari and J. Prasad, "Computer modelling of bone's adaptation: the role of normal strain, shear strain and fluid flow," *Biomech. Model. Mechanobiol.*, vol. 16, no. 2, pp. 395–410, 2017, doi: 10.1007/s10237-016-0824-z.

[32] S. P. Fritton, K. J. McLeod, and C. T. Rubin, "Quantifying the strain history of bone: Spatial uniformity and self-similarity of low-magnitude strains," *J. Biomech.*, vol. 33, no. 3, pp. 317–325, 2000, doi: 10.1016/S0021-9290(99)00210-9.

[33] S. Weinbaum, S. C. Cowin, and Y. Zeng, "A model for the excitation of osteocytes by mechanical loading-induced bone fluid shear stresses," *J. Biomech.*, vol. 27, no. 3, pp. 339–360, 1994, doi: 10.1016/0021-9290(94)90010-8.

[34] Y. Han, S. C. Cowin, M. B. Schaffler, and S. Weinbaum, "Mechanotransduction and strain amplification in osteocyte cell processes," *Proc. Natl. Acad. Sci. U. S. A.*, vol. 101, no. 47, pp. 16689–16694, 2004, doi: 10.1073/pnas.0407429101.

[35] M. L. Knothe Tate, R. Steck, M. R. Forwood, and P. Niederer, "In vivo demonstration of load-induced fluid flow in the rat tibia and its potential implications for processes associated with functional adaptation," *J. Exp. Biol.*, vol. 203, no. 18, pp. 2737–2745, Sep. 2000, doi: 10.1242/JEB.203.18.2737.

[36] S. Gururaja, H. J. Kim, C. C. Swan, R. A. Brand, and R. S. Lakes, "Modeling deformation-induced fluid flow in cortical bone's canalicular-lacunar system," *Ann. Biomed. Eng.*, vol. 33, no. 1, pp. 7–25, 2005, doi: 10.1007/s10439-005-8959-6.

[37] N. K. Wittig *et al.*, "Canalicular junctions in the osteocyte lacuno-canalicular network of cortical bone," *ACS Nano*, vol. 13, no. 6, pp. 6421–6430, Jun. 2019, doi: 10.1021/ACSNANO.8B08478/ASSET/IMAGES/MEDIUM/NN-2018-08478N_M001.GIF.

[38] A. F. Van Tol *et al.*, "The mechanoresponse of bone is closely related to the osteocyte lacunocanalicular network architecture," *Proc. Natl. Acad. Sci. U. S. A.*, vol. 117, no. 51, pp. 32251–32259, 2020, doi: 10.1073/pnas.2011504117.