RESEARCH ARTICLE:

Examination of Balancing in a Real-World Inverted Pendulum

Laura Alvarez-Hidalgo[1*], & Ian S. Howard[1*]
[1] School of Computing, Engineering and Mathematics, University of Plymouth, Plymouth,
Devon, United Kingdom.

*Correspondence should be addressed to: ISH: ian.howard@plymouth.ac.uk
Telephone: +44 1752 586324

Keywords: Human Balance, Inverted Pendulum, Predictive Control, Learning Transfer,
Real-World Dynamics, Sensorimotor Control.

Number of pages: 17
Number of figures: 7
Number of tables: 2
Number of words for Abstract: 281
Number of words for Introduction: 531
Number of words for Discussion: 1033

Statement of Financial Interests or Conflicts of Interest
The authors declare that they have no financial, personal, or professional interests that
could be construed to have influenced the paper.

Acknowledgements
Financial support for this project for LAH was provided by the Engineering and Physical
Sciences Research Council (EPSRC) and the University of Plymouth. Financial support
for ISH was provided by the University of Plymouth. During the preparation of this work,
LAH and ISH utilized ChatGPT-5 for proofreading.

Abstract (281)
Motor adaptation is typically studied using simplified virtual tasks. Here, we investigated
how humans learn to stabilize a physically unstable, underactuated system, and how
participants cope with changes in the system's dynamics. Twelve right-handed adults
balanced a real inverted pendulum by moving a cart along a linear rail. Study 1
characterized the passive mechanical properties of three pendulums (short, medium, and
long) using free-oscillatory decay and fall to ±30° trials, after their release from the upright
position. Longer rods exhibited slower decay and lower natural frequencies, as well as a
longer duration before falling, indicating greater passive stability. Study 2 assessed
human motor control of the pendulum to maintain balance. Human participants trained
with the medium pendulum (30 trials) and were then tested with all three pendulums (20
trials each). During training, balance performance improved significantly, with time to

failure increasing over trials. During testing, performance scaled with pendulum length,
and longer rods were easier to balance. Similar peak cart velocities were observed across
conditions, suggesting equivalent actuation effort. Additionally, as expected, pendulum
angular velocities decreased with rod length, reflecting underlying inertial differences.
Pendulum passive dynamics closely matched behavioral performance, supporting a
strong link between intrinsic system properties and balancing outcomes. These findings
show that motor learning in physically unstable environments is not only shaped by
feedback and effort, but also by the alignment of human control strategies and abilities
with the natural dynamics of the plant. We note that in this study, we used a modified
pendulum rig previously employed to examine control engineering approaches to
modelling balance, thereby generating a dataset that can later be used to compare human
performance with real-time computer control implementations of the same tasks.

Introduction (531)
Humans continually adjust their movements to meet changing environmental and task
demands. This adaptive capability, also known as motor adaptation, relies on the nervous
system updating internal models of the body and environment through sensory feedback
and error-based learning (Shadmehr et al., 2010; Wolpert et al., 2011; Howard et al.,
2013, 2017). These internal models support predictive control, enabling behavior to
remain effective despite noise, delays, and perturbations.

Much of what is known about motor adaptation derives from tightly controlled laboratory
tasks using artificial perturbations, such as visuomotor rotations or curl field force
perturbations applied to the hand (Howard et al., 2009, 2012; Franklin and Wolpert, 2011;
Krakauer and Mazzoni, 2011; Taylor and Ivry, 2012). While these paradigms afford clear
experimental leverage on learning mechanisms, they often minimize or eliminate key
properties of everyday interactions, such as the combined effects of mass, inertia, contact
forces, and intrinsic instability, by, for example, mapping hand motion to a screen cursor
or employing isometric contractions. Consequently, important questions remain about
how humans adapt when confronted with the physical dynamics of real objects that differ
in their intrinsic properties.

Balancing tasks offer an ecologically meaningful window onto such control problems.
They are inherently unstable and demand the integration of feedback and predictive
control to maintain equilibrium. The inverted pendulum is a system that captures core
challenges of real-world control: underactuation, sensorimotor delays, and high sensitivity
to small disturbances (Scott, 2004; Gawthrop and Wang, 2006; Liu and Todorov, 2007).
Comparable dynamics arise in human posture, manual object manipulation, and everyday
load handling (e.g., carrying a tray or a cup of tea), where success hinges on anticipating
and counteracting the evolving effects of the object's dynamics.

Many previous studies have examined balance control using simplified or virtual
implementations, such as tracking a simulated pendulum or stabilizing one via a robotic
interface that abstracts away some mechanical complexities (Burdet et al., 2001; Mehta
and Schaal, 2002; Milner and Franklin, 2005; Howard et al., 2009). These approaches
help isolate specific mechanisms but often rely on artificially simulated sources of
feedback and omit important aspects of the task.

The present study uses an authentic, physically real inverted pendulum task that preserves natural sensory cues. These include full-field visual information about the pendulum and require direct interaction with forces arising from the system's dynamics. Participants stabilized a real-world inverted pendulum by manually controlling a rolling cart in an underactuated setting, in which the rod is controlled only indirectly via base motion. Crucially, we varied pendulum length (short, medium, and long), thereby altering time constants and stability characteristics. This design allows us to quantify how human participants balance during different dynamic conditions.

We base the design of the experiments on a previous pendulum rig (Alvarez Hidalgo and Howard, 2022, 2024), developed to investigate control engineering approaches to balance, which can operate more effectively than human performance. However, in the future, we envisage that the same setup will be used to test more biologically realistic computational models that incorporate sensory and motor delays, as well as sensor and actuation noise, so that the actual human performance and behavior identified in this study can be compared with the results of simulations and examined further.

Methods

Participants

Twelve right-handed adults (eight female, four male) participated in the study. Participants were randomly assigned to one of two groups (Group A or Group B) to counterbalance the order of experimental conditions. Group A included three females (mean age: 22.16 ± 1.22 years) and three males (27.59 ± 0.86 years), while Group B comprised five females (23.56 ± 2.11 years) and one male (28.99 ± 0.00 years). This between-subjects counterbalancing strategy ensured that any order-related effects were evenly distributed across conditions.

All participants were naïve to the purpose of the study and provided written informed consent prior to participation. Handedness was confirmed using the Edinburgh Handedness Inventory (Oldfield, 1971), verifying that all participants were right-handed. The study received ethical approval from the Faculty Research Ethics and Integrity Committee at the University of Plymouth and was conducted in accordance with institutional guidelines.

Apparatus

The experimental task was implemented using a custom-built inverted pendulum apparatus mounted on a standard-height desk (Figure 1), very similar to that described in prior work (Alvarez Hidalgo and Howard, 2022, 2024). The system consisted of a rigid horizontal frame supporting a rolling cart that moved along the X-axis. A detachable vertical rod was affixed to the cart via a pivot joint, forming an underactuated inverted pendulum.

Figure 1. Schematic and photographic views of the inverted pendulum apparatus. **A)** Front view of the setup, showing the rolling cart and vertical rod assembly. **B)** Rear view, highlighting the handle used for manual control. **C)** Photograph of the complete rig mounted on a standard-height desk. **D)** The three interchangeable pendulum rods (short, medium, and long).

Motion data were recorded using two rotary encoders (2400 pulses per revolution, using all waveform edges). One encoder was mounted at the end of the rail and measured the

horizontal displacement of the cart. The second encoder was located at the rod-cart pivot
and tracked its angular displacement relative to the vertical. To systematically vary the
pendulum dynamics, three rods of different lengths were used: a short brass rod (305 mm,
90 g), a medium stainless-steel rod (635 mm, 143 g), and a long stainless-steel rod
(1030 mm, 216 g). All rods shared the same 8 mm diameter and mounting interface to
ensure consistent mechanical coupling with the cart.

Table 1. Mechanical properties of the three inverted pendulum rods.

		Short Pendulum	Medium Pendulum	Long Pendulum
Length (L)	[m]	0.305	0.635	1.030
Mass (m)	[Kg]	0.090	0.143	0.216
Length to CoG	[m]	0.153	0.318	0.515
Weight (W)	[N]	0.883	1.403	2.119
Estimated Mol (I)	[Kg·m^2]	0.003	0.019	0.076

Participants controlled the cart's position via a rear-mounted handle attached to the cart.
The entire rig was securely clamped to the desk to maintain mechanical stability. An
Arduino Mega 2560 microcontroller provided real-time data logging of pendulum angle
and cart position, at a rate of approximately 10 Hz, with each measurement recorded with
an associated precise timestamp. Interpolation was then carried out to provide
measurement samples at precisely 100 Hz. The pendulum apparatus was ergonomically
configured to ensure consistent access and comfort across participants.

Experimental Setup
Two complementary studies used the same inverted-pendulum apparatus (Figure 1).
Auditory tones cued the start and stop of a trial. Study 1 quantified passive mechanical
dynamics without human control input. Study 2 examined human balance control while
participants attempted to stabilize the inherently unstable inverted pendulum.
Uncontrolled and controlled trial termination thresholds were identical across studies. In
both cases trials terminated when the pendulum exceeded ±30°.

Study 1: Passive System Identification
To better understand the dynamical properties of the inverted pendulum system, we
conducted a set of trials without human control. These characterization trials were
designed to capture the passive dynamics of the system and to quantify how each
pendulum length affected stability and oscillatory decay behavior. For each pendulum
length, we recorded data using two passive protocols.

The first protocol examined uncontrolled full decay, and a single trial for each pendulum
length was recorded. In this protocol, the rod was released from the upright position and

allowed to oscillate until motion ceased, yielding a continuous decay trajectory. We note
here that the upright position corresponded to 180° and decayed towards 0°.

The second protocol used an uncontrolled 30° fall. In this case, the rod was manually
raised to its upright position (here defined at 0°) and released to fall freely. The trial ended
when the pendulum angle reached ±30°. This limit was also used in Study 2. To get a
good estimate of the effect of the pendulum dynamics, 20 trials were collected per length.

We note that there was always variability in setting up the experiment (angle and velocity),
as this was a noisy process, and there were also random disturbances of the rod from the
environment (such as from air currents).

Study 2: Human Study of Balance
Prior to the start of the human experiments, participants were instructed to move the cart
left and right while holding the handle of the experimental rig. They were also told to focus
their gaze exclusively on the top of the rod throughout the trials. Additionally, they were
instructed to begin moving upon hearing a "beep", and to stop moving upon hearing a
second "beep."

During each trial, participants held the handle attached to the cart. Once a participant was
set up and ready, the researcher slowly raised the pendulum rod towards 180° from its
initial resting position. When the rod's encoder detected that the angular velocity had
dropped below 5 deg·s^{-1} and the position was at 180°, a 3 second auditory tone (400 Hz)
was played. Then, the encoder count was reset to zero, defining the upright position of
the pendulum as 0°, which was the reference point for the experiment.

Participants then attempted to balance the inverted pendulum. Each trial ended either
when the rod angle exceeded ±30°, or when the participant successfully maintained
balance for 10 seconds. At the conclusion of each trial, another 3 second auditory tone
was played to signal to both the participant and the researcher that the trial had ended.

Participants did not receive any formal feedback on their performance, aside from being
able to observe how long they had balanced the pendulum. No scheduled breaks were
provided during the experiment, apart from the brief pauses between trials. Participants
also rested briefly during changes in pendulum length.

Each participant completed one training phase followed by three testing phases, one for
each rod length (Figure 2). During the training phase, participants always used the
medium-length inverted pendulum and completed a total of 30 trials.

After training, participants proceeded to the testing phase, beginning with 20 trials using
the same medium-length rod. They then completed 20 trials with each of the remaining
two rod lengths: the short and the long sized inverted pendulum. The order in which
participants performed the short and long rod testing phases was counterbalanced across
participants to control for potential order effects.

Each testing phase consisted of 20 consecutive trials using a single rod length. In total,
each participant completed 90 trials: 30 during the training phase and 60 during the testing

phases (20 per rod length). The entire experiment took approximately 60 minutes to
complete per participant.

Figure 2. Experimental design and trial structure across conditions. Each row shows the
sequence of phases for each group. All participants trained with the medium rod (30 trials;
green), then completed testing phases (20 trials each) with the short (blue), medium
(green), and long (red) rods.

Measurements
The rotary encoders provided continuous, time-indexed measurements of the cart motion
and the pendulum angle. Cart position x(t) was obtained from an encoder coupled via a
timing pulley and expressed as an angular-equivalent displacement (°) for consistency
with downstream velocity measures. Pendulum angle θ(t) was recorded at the pivot
encoder and zeroed at the upright position, such that θ = 0º denotes the unstable
equilibrium.

Rod-Specific Mechanical Parameters
To characterize the pendulums, the following mechanical properties were measured or
calculated:

Length (L): Distance from pivot to tip in meters.

Mass (m): Measured using a balance in Kg.

Centre of Gravity (CoG): The point where the rod's weight effectively acts. This was
assumed to be at half the length of the rod.

$$CoG = \frac{L}{2} \tag{1}$$

214 Moment of Inertia (I): A measure of the rod's resistance to angular acceleration about its
215 end point, in kg·m^2.

$$I = \frac{1}{3} m \cdot L^2 \tag{2}$$

217   Weight (W): The gravitational force acting on a body's mass, in Newtons.

$$W = m \cdot g \qquad (3)$$

219   These parameters can be used to derive linearized dynamics about the upright
220   equilibrium point. The small-angle natural frequency of the inverted pendulum model is:

$$f_n\,(t) = \frac{1}{2\pi}\sqrt{\frac{mgl}{CoG + ml^2}} \qquad (4)$$

222   which we used to characterize the pendulum dynamics in the passive trials (Study 1).

Angle-based kinematics
224   To characterize the angle-based kinematics of our system, the angle and angular velocity
225   for the cart position and pendulum angle were calculated. Angular velocity at the cart
226   encoder ($\dot{\theta}_{Cart}$) and angular pendulum velocity ($\dot{\theta}_{Pend}$) were obtained by numerically
227   differentiating the encoder-measured pendulum angle after converting counts to angle
228   and correcting for wraparound.

$$\dot{\theta}_{Cart}\,(t) = \frac{d\theta_{Cart}(t)}{dt} \qquad (4)$$

$$\dot{\theta}_{Pend}\,(t) = \frac{d\theta_{Pend}(t)}{dt} \qquad (5)$$

Outcome measures aligned to Results
232   Time to failure was defined as the duration from the start of the trial to termination. Trials
233   ended either when the absolute value of the pendulum angle exceeded 30°, or when the
234   participant successfully maintained balance for a maximum of 10 seconds. This measure
235   reflects the participant's ability to stabilize the system over time.

$$t_{30} = t_{end} - t_{start} \qquad (6)$$

Peak angular velocity refers to the maximum absolute speed at the respective encoder
attained during each trial. The peak angular velocity from the cart position encoder was
related to the maximum instantaneous control effort. For group summaries in the Results
section, we focused on the last 10% of trials within each phase/condition to evaluate final
performance and compute mean values for each participant.

Natural frequency f_n is the intrinsic (undamped) oscillation rate of the linearized pendulum
about the inverted equilibrium.

Results
This section covers the dynamic properties of the pendulum system and the behavioral
outcomes across both passive and active balancing conditions. We first describe the
findings from Study 1, which quantified passive decay and fall dynamics in the absence
of human control. We then present the main behavioral results from Study 2, including

changes in time to failure across training and testing phases, as well as peak velocity
metrics for both the cart and pendulum. Where appropriate, statistical comparisons are
based on repeated-measures ANOVAs with post hoc corrections, and all reported effects
are accompanied by descriptive statistics and standard error estimates.

Study 1: Passive System Identification
Free Decay
Total decay time from vertical release increased monotonically with rod length. The short
rod reached near-zero motion after 100.09 s, while the medium rod decayed after
240.08 s, and the long rod took approximately 300.10 s to settle. These durations reflect
the increasing moment of inertia and the smaller relative effect of the restoring torque
associated with longer pendulums, which prolong the time required for energy dissipation
in the absence of external control.

The oscillation frequency exhibited the inverse pattern, indicating that longer pendulums
exhibit slower passive dynamics: the long pendulum oscillated at 0.59 Hz (period =
1.71 s), the medium at 0.74 Hz (period = 1.35 s), and the short at 1.05 Hz (period = 0.95 s).
Figure 3 shows single-trial decay durations and representative angular trajectories for
each condition.

Figure 3. Passive free-decay dynamics for the three rod lengths. **A)** Overall decay time
per rod length. **B)** Angular pendulum trajectories as a function of time for the unassisted
free-decay experiments.

Fall to ±30 degrees
Fall time from upright to reach the ±30° threshold increased consistently with rod length,
again in line with the slowing down of passive dynamics as pendulum length increased.

To evaluate the effect of pendulum length on passive fall behavior, a one-way repeated-
measures ANOVA was conducted on the time to failure across three conditions: short,
medium, and long pendulums. Each trial was terminated when the pendulum reached an
angular displacement of ±30°, marking the loss of balance under passive dynamics.

A one-way repeated-measures ANOVA on passive time to failure showed a main effect
of condition, $F(2, 57) = 5.78$, $p = 0.005$, $\omega^2 = 0.137$. Pairwise post-hoc comparisons with
Bonferroni correction showed that the short pendulum yielded significantly shorter times
to failure compared to both medium ($p_{bonf} = 0.046$) and long ($p_{bonf} = 0.006$). No significant
difference was observed between the medium and long conditions ($p_{bonf} = 1.000$).
Descriptive statistics are reported in Table 2.

Table 2. Descriptive statistics for time to failure during passive falls to ±30°.

Condition	Mean Time to Failure (s)	SD	SE	Coefficient of variation
Short	1.128	0.245	0.055	0.218
Medium	1.368	0.284	0.063	0.207
Long	1.440	0.370	0.083	0.257

Time to failure did not vary significantly across trials within any of the three pendulum
lengths. A repeated-measures analysis including both trial number and condition revealed
no significant Condition × Trial interaction ($F(2, 57) = 0.015$, $p = 0.985$), indicating that
performance remained stable across repetitions. This confirms that the observed
differences between conditions were not driven by trial order or sequential variability. The
distribution of trial-wise values is visualized in Figure 4. As expected, these findings
clearly show that longer pendulums exhibit greater passive stability, taking longer to reach
the ±30° threshold.

Figure 4. Time to failure for passive falls of absolute angle to 30° across pendulum
conditions. Individual trial data are shown for short, medium, and long pendulums,
displayed with horizontal jitter for clarity. Black squares indicate the group means, and
error bars denote the standard error of the mean (±SE).

Study 2: Human Study of Balance

Time To Failure

As shown in Figure 5A, participants significantly improved their ability to maintain balance
during the training phase with the medium length pendulum. Their average time to failure
increased from 1.4 seconds at the beginning phase to 3.46 seconds at the end phase,
based on the first and last 10% of training trials. This improvement was confirmed by a
repeated-measures ANOVA, which revealed a significant main effect, $F(1, 1) = 15.518$, p
< 0.001, $\omega^2 = 0.146$, indicating robust improvement. No significant interaction between
phase and participant was found ($p = 0.573$), suggesting that the improvement trend was
consistent across individuals. In contrast, during the testing phase, as observed in Figure
5B-D, performance did not follow the same trend seen during initial training and plateaued
out.

Figure 5. Time to failure across human participants and across trials. **A)** Trial times during
the medium size pendulum training phase. **B)** Time to failure during the testing short
pendulum condition. **C)** Time to failure during the testing medium pendulum condition. **D)**
Time to failure during the testing long pendulum condition.

As shown in Figure 6A, participants' time to failure during the final 10% of testing trials
increased significantly with pendulum length. The mean time to failure was 1.35 seconds
for the short pendulum, 1.70 seconds for the medium pendulum, and 4.95 seconds for
the long pendulum. A one-way ANOVA confirmed a significant effect of condition on time
to failure ($F(2,66) = 23.69$, $p < 0.001$, $\omega^2 = 0.378$). Post-hoc comparisons revealed that
participants balanced the long pendulum significantly longer than both the medium ($p <$
0.001) and short ($p < 0.001$) pendulums.

Group order (Group A vs. Group B) did not significantly affect performance (F(1,66) =
2.56, p = 0.114). However, descriptive trends suggested that Group B exhibited longer
time to failure, particularly in the long pendulum condition (Group A: Mean = 4.00, Group
B: Mean = 5.90), though this difference was not statistically significant (p = 0.197). See
Figure 6B for further details.

Figure 6. Time to failure across human participants during the last 10% of trials. **A)** Time
to failure across each pendulum length condition. **B)** Between-subject comparison of
mean time to failure for each pendulum length condition.

Peak Velocity
To better understand how participants adapted their control strategies across pendulum
conditions, we examined peak encoder angular velocity for both the cart and pendulum
during the final 10% of trials, when behavior had stabilized.

As seen in Figure 7A, peak cart velocity remained consistent across all three rod lengths.
Regardless of whether participants were balancing the short, medium, or long pendulum,
the maximum speed they applied to the cart converged on a similar value. Statistically,
there was no main effect of condition, F(2,22) = 0.063, p = 0.939. The group means were
tightly clustered, 61,209 ± 5,056 deg·s^{-1} for short, 64,038 ± 6,323 deg·s^{-1} for medium,
and 59,830 ± 11,197 deg·s^{-1} for long. These findings suggest that, once stable control
was achieved, participants adopted similar range of actuation effort, independent of the
pendulum's length.

However, despite similar control inputs, the rod's responses diverged across conditions.
Peak pendulum angular velocity varied systematically with rod length (see Figure 7B). A
repeated-measures ANOVA revealed a main effect of condition, F(2,22) = 5.486, p =
0.012, with effect size ω² = 0.21. Pendulum angular velocities were highest for the short

condition (1,599 ± 14 deg·s^{-1}), slightly lower for medium (1,561 ± 7 deg·s^{-1}), and lowest
for long (1,123 ± 190 deg·s^{-1}). Although pairwise comparisons did not reach significance
after Holm correction (p_s= 0.091 - 0.132), the observed trend remained robust and aligned
with mechanical expectations: longer pendulums, owing to their greater inertia, exhibited
slower responses to equivalent control inputs.

Figure 7. Peak angular velocities for the different pendulum length condition and
experimental phase. **A)** Per trial-pair peak cart encoder angular velocities. The colored
line represents the group mean, with the shaded band showing ±1 standard error (SE).
The x-axis indicates the trial-pair index. Velocities are computed as absolute peak values
(|deg·s^{-1}|). **B)** Per trial-pair peak pendulum encoder angular velocities. As in panel A,
colored lines show the group mean, and shaded bands denote ±SE across participants.

To explore this further, we compared performance across phases within the medium
condition, where both training and testing were available (Figure 7C-D). Cart encoder
angular velocities were again similar across phases, $F_{(1,11)}$ = 1.488, p = 0.248 (72,582
± 3,638 vs. 64,038 ± 6,323 deg·s^{-1}), but pendulum encoder angular velocities increased
slightly at testing $F_{(1,11)}$ = 4.843, p = 0.050 (1,411 ± 67 vs. 1,561 ± 7 deg·s^{-1}).

Discussion (1033/1500)
Understanding how humans behave in real physical environments is a central question
in motor control research. While most previous studies have used simplified, virtual tasks,

our study explores control in a physically unstable, real-world system. This is the manual
balancing of inverted pendulums of three different lengths, with difficulty decreasing as
length increases. We first investigate the passive dynamics of the pendulums and then
assess the ability of human participants to balance them.

Comparative results: passive mechanics vs human control
Across both experiments, as expected, a consistent relationship emerged between the
passive mechanical properties of the pendulum system and human performance during
active balancing.

The passive characterization revealed that pendulum length substantially modulated the
plant's intrinsic dynamics. As it is already well known, longer rods exhibited greater decay
durations and lower dominant frequencies, whereas shorter rods decayed more rapidly
and oscillated at higher frequencies. In the fall to either ±30° trials, the time to failure
followed the same ordering, confirming that longer rods are inherently more stable under
passive conditions. These differences affect controllability, with longer rods providing
greater temporal margins for correction, while shorter rods demand faster and more
precise intervention to maintain stability.

We note that static friction at the pivot must be overcome to initiate motion and is less
consequential in longer pendulums, where larger restoring torques are available;
therefore, stiction becomes proportionally more significant in shorter pendulums. This
stiction factor would assist balancing of shorter pendulums, although this was not a
significant factor in our experiments. An energy-based perspective helps explain the
decay results: for the same angular range, longer pendulums store and exchange more
energy, so even with comparable dissipation mechanisms, the longer rods take more time
to settle. Conversely, shorter pendulums decay more quickly because the energy per
cycle is smaller.

Human behavior during active balancing mirrored these mechanical constraints.
Participants first trained on the medium pendulum, where performance improved over
trials, as evidenced by an increase in time to failure. This indicates practice improved the
control strategy for the medium rod. When subsequently tested on all three rods,
performance did not improve further in any condition, but rather performance outcomes
aligned with predictions based on the passive analysis: time to failure was highest for the
long rod, intermediate for the trained medium rod, and lowest for the short rod. Thus, the
intrinsic temporal dynamics of the plant imposed fundamental limits on controllability,
even after initial practice had been experienced.

We found that the performance effect across pendulum lengths was not attributable to
differences in movement speed. By the end of testing, peak cart encoder angular
velocities had converged to comparable values across all three conditions, indicating that
participants applied comparable maximum levels of actuation effort regardless of
pendulum length. However, the response of the plant diverged: peak pendulum angular
velocities were significantly higher in the short rod condition and lower in the long rod
condition. This dissociation reveals that while participants behaved similarly across
conditions, the mechanical consequences of those actions were governed by rod length.

Comparisons between training and testing on the medium rod further support the
interpretation that practice resulted in refinement of coordination, rather than changes in
movement speed. Peak cart velocities did not increase between training and testing
phases.

These findings yield two key takeaway messages. First, with practice, individuals do not
primarily learn to move faster, but rather to move more effectively, refining the timing,
coordination, and structure of their control strategies to better suit the dynamics of the
system. Second, as is well known, longer pendulums are easier to balance than shorter
ones because their slower dynamics provide a larger temporal margin for error detection
and correction, making the task inherently more forgiving and controllable.

Relation to previous work on physical pendulums
There have been numerous studies examining balancing of physical inverted pendulums
(Loram and Lakie, 2002; Lakie et al., 2003; Cabrera and Milton, 2004). They have long
been a model for studying human balance control, especially in tasks such as stick-
balancing and cart-pendulum balancing, which closely mirror real-world balance
(Yoshikawa et al., 2016).

A central theme in this literature is that there is time delayed feedback, which complicates
balance control and strongly affects how human participants can perform balancing tasks.
This leads to reaction time delays, which are crucial for balancing performance, and
longer pendulums tend to result in longer times to failure (Kovacs and Insperger, 2022).
Additionally, previous research has highlighted the role of both active feedback and
intrinsic passive stiffness in balance maintenance, which aligns with our observation of
the interplay between active and passive dynamics in balancing (Loram and Lakie, 2002;
Lakie et al., 2003).

Intermittent feedback control, which alternates between active corrections and passive
stabilization, has been proposed to enhance stability, particularly in more complex
systems, supporting the conclusion that longer pendulums require more sophisticated
feedback strategies (Yoshikawa et al., 2016). Studies have shown that intermittent
corrections are crucial for maintaining stability, with one example being the instability of
the upright fixed point in time-delayed systems (Milton et al., 2009). Additionally, skilled
stick balancing has been shown to follow a Lévy flight pattern, characterized by bursts of
corrective movement and periods of inactivity (Cabrera and Milton, 2004).

Interestingly, consistent manual adjustments across pendulum configurations suggest
fixed temporal constraints for balance control, a pattern we observed in the increased
complexity of balancing longer pendulums (Loram and Lakie, 2002). Our findings support
this concept, showing that longer pendulums lead to more variation in time to failure.
Reaction time delays are known to influence balancing performance, as reflected in our
study, where longer pendulums corresponded with longer times to failure.

Future work
The preliminary results from the current experiments could provide quantitative data for
future research to extend the analysis through computational modelling of real-time

control that integrates human biological constraints. Building on our previous dual linear-quadratic regulator (LQR) framework for this apparatus (Alvarez Hidalgo and Howard, 2022, 2024), forthcoming models will incorporate sensory delays, signal-dependent noise, static friction, and actuation limits, all of which are factors known to influence motor planning and feedback regulation in unstable tasks. Such models may account for key empirical findings observed here, including the near invariance of peak cart velocities across conditions.

Disclosures

The authors declare that they have no financial, personal, or professional conflicts of interest that may have influenced the content of this paper.

Author Contributions

LAH and ISH conceived the study. LAH implemented the study, conducted data collection, and performed data analysis. The initial draft of the manuscript was written by LAH. All authors, LAH and ISH, reviewed and edited the manuscript.

References

Alvarez Hidalgo L, Howard IS (2022) Gain scheduling for state space control of a dual-mode inverted pendulum. In: 2022 International Conference on System Science and Engineering (ICSSE), pp 039–046. IEEE.

Alvarez Hidalgo L, Howard IS (2024) Dual Mode Control of an Inverted Pendulum: Design, Analysis and Experimental Evaluation. Adv Sci Technol Eng Syst J 8:120–143.

Burdet E, Osu R, Franklin DW, Milner TE, Kawato M (2001) The central nervous system stabilizes unstable dynamics by learning optimal impedance. Nature 414:446–449.

Cabrera JL, Milton JG (2004) Human stick balancing: Tuning Lèvy flights to improve balance control. Chaos Interdiscip J Nonlinear Sci 14:691–698.

Franklin DW, Wolpert DM (2011) Computational mechanisms of sensorimotor control. Neuron 72:425–442.

Gawthrop PJ, Wang L (2006) Intermittent predictive control of an inverted pendulum. Control Eng Pract 14:1347–1356.

Howard I, Ford C, Cangelosi A, Franklin D (2017) Active lead-in variability affects motor memory formation and slows motor learning. Sci Rep 7:7806.

Howard I, Ingram J, Wolpert D (2009) A modular planar robotic manipulandum with end-point torque control. J Neurosci Methods 181:199–211.

Howard IS, Ingram JN, Franklin DW, Wolpert DM (2012) Gone in 0.6 Seconds: The Encoding of Motor Memories Depends on Recent Sensorimotor States. J Neurosci 32:12756–12768.

485   Howard IS, Wolpert DM, Franklin DW (2013) The effect of contextual cues on the
486   encoding of motor memories. J Neurophysiol 109:2632–2644.

487   Kovacs BA, Insperger T (2022) Virtual stick balancing: skill development in Newtonian
488   and Aristotelian dynamics. J R Soc Interface 19:20210854.

489   Krakauer JW, Mazzoni P (2011) Human sensorimotor learning: Adaptation, skill, and
490   beyond. Curr Opin Neurobiol 21:636–644.

491   Lakie M, Caplan N, Loram ID (2003) Human balancing of an inverted pendulum with a
492   compliant linkage: neural control by anticipatory intermittent bias. J Physiol
493   551:357–370.

494   Liu D, Todorov E (2007) Evidence for the Flexible Sensorimotor Strategies Predicted by
495   Optimal Feedback Control. J Neurosci 27:9354–9368.

496   Loram ID, Lakie M (2002) Human balancing of an inverted pendulum: position control by
497   small, ballistic-like, throw and catch movements. J Physiol 540:1111–1124.

498   Mehta B, Schaal S (2002) Forward models in visuomotor control. J Neurophysiol 88:942–
499   953.

500   Milner TE, Franklin DW (2005) Impedance control and internal model use during the initial
501   stage of adaptation to novel dynamics in humans. J Physiol 567:651–664.

502   Milton J, Cabrera JL, Ohira T, Tajima S, Tonosaki Y, Eurich CW, Campbell SA (2009)
503   The time-delayed inverted pendulum: Implications for human balance control.
504   Chaos Interdiscip J Nonlinear Sci 19:026110.

505   Oldfield RC (1971) The assessment and analysis of handedness: The Edinburgh
506   inventory. Neuropsychologia 9:97–113.

507   Scott SH (2004) Optimal feedback control and the neural basis of volitional motor control.
508   Nat Rev Neurosci 5:532–546.

509   Shadmehr R, Smith MA, Krakauer JW (2010) Error correction, sensory prediction, and
510   adaptation in motor control. Annu Rev Neurosci 33:89–108.

511   Taylor JA, Ivry RB (2012) The role of strategies in motor learning. Ann N Y Acad Sci
512   1251:1–12.

513   Wolpert DM, Diedrichsen J, Flanagan JR (2011) Principles of sensorimotor learning. Nat
514   Rev Neurosci 12:739–751.

515   Yoshikawa N, Suzuki Y, Kiyono K, Nomura T (2016) Intermittent Feedback-Control
516   Strategy for Stabilizing Inverted Pendulum on Manually Controlled Cart as Analogy
517   to Human Stick Balancing. Front Comput Neurosci 10.