Robust metabolomics data normalization across scales and experimental designs

Matthijs Vynck[1], Pablo Vangeenderhuysen[1], Ellen De Paepe[1], Tim Nawrot[2], Vera Plekhova[1], Lynn

Vanhaecke[1,3]*

[1] Laboratory of Integrative Metabolomics (LIMET), Department of Translational Physiology,

Infectiology and Public Health, Faculty of Veterinary Medicine, Salisburylaan 133, 9820

Merelbeke, Belgium

[2] Environmental and Molecular Epidemiology, Centre of Environmental Sciences, Hasselt

University, Martelarenlaan 42, 3000 Hasselt, Belgium

[3] School of Biological Sciences, Queens' University Belfast, 19 Chlorine Gardens, Belfast BT9

5DL, Northern Ireland

* To whom correspondence should be addressed: lynn.vanhaecke@ugent.be

Word count:

Main text: 5725 (without figure captions)

Abstract: 183

Figure count: 6

This manuscript is accompanied by supporting information.

Key words: metabolomics, lipidomics, data normalization, quality control samples, batch effects,

signal drift, outlier robust

Abstract

Metabolomics studies employing liquid chromatography-mass spectrometry are affected by signal drift and batch effects, introducing technical variance that impedes biological knowledge discovery. Quality control (QC) sample-based normalization strategies are widely implemented but remain vulnerable to outliers, thereby reducing normalization performance. We introduce rLOESS, rGAM and tGAM, three robust normalization methods that improve resistance to outliers by downweighting or accommodating them. Leveraging additive models, the rGAM and tGAM methods allow flexible non-linear modeling, differential sample weighting, and data-driven QC representativeness evaluation. Implementations of these methods are gathered in the Metanorm R package, integrating robust normalization with visualization for performance verification, while supporting efficient parallel processing. In *in silico* and/or experimental datasets, the robust methods, relative to several popular existing strategies, improved replicate concordance, and reduced drift and batch effects. The robust methods, with improved recovery of the underlying signal demonstrated in simulation, produced distinct differential abundance results, highlighting the impact of normalization on downstream statistical inference. Overall, tGAM-based normalization suggested the best performance across scenarios and is proposed as default choice. Metanorm is versatile, supporting normalization in metabolomics studies across scales and experimental setups.

Introduction

Liquid chromatography coupled to mass spectrometry (LC-MS) is a widely established analytical technique in metabolomics including lipidomics, and has supported significant discoveries across the life sciences and beyond[1-5]. As the technique has matured, its application has expanded to encompass increasingly larger biological sample series, nowadays frequently spanning hundreds if not thousands of samples[6,7].

Analyzing such extensive sample series presents important analytical challenges. Indeed, extended analytical runs often require, e.g., intermediate instrument maintenance or consumable replacements. In addition, longer sample collection and analysis timeframes, often spanning weeks or months, introduce variability arising from factors such as multiple operators, shifts in sample handling, and environmental changes. Collectively, these factors exacerbate batch effects (e.g., column changes), and signal attenuation or enhancement, often referred to as drift, from both chromatographic and mass spectrometric origin, such as column degradation or fouling, as well as gradual changes in, e.g., ionization efficiency or mass calibration[8,9]. Consequently, these issues become more pronounced as sample series sizes increase.

Addressing this variability has become a critical concern in the metabolomics community, underscored by the establishment of the Metabolomics Quality Assurance and Quality Control Consortium (mQACC) in 2018[10], which emphasizes the development of effective strategies to mitigate these challenges. While several strategies have been proposed, ranging from the use of isotopically labeled internal standards[11] to broadly applicable statistical methods such as ComBat[12], the most widely accepted approach today is the implementation of quality control (QC) samples to characterize and correct for batch effects and drift[9,13,14]. QC samples are typically generated by pooling aliquots from all, or in large sample series representative subsets of, biological samples[15]. Repeated analysis of these pooled QC samples allows for systematic monitoring and correction of batch effects and drift. Such QC sample-based corrections have become fundamental in supporting data reliability of large-scale LC-MS studies[9,10,14].

Several QC sample-based normalization strategies have been proposed, including QC-RLSC, introduced by Dunn et al.[13], employing locally estimated scatterplot smoothing (LOESS) for within-batch drift correction at the single metabolic feature level. This approach was later refined to a cubic spline-based method (QC-RSC) by Kirwan et al.[16], reducing computational demands. More recently, methods such as MetaboQC[17], SERFF[18], and TIGER[19] employed polynomial regression and LOESS, random forest regression, and ensemble learning strategies, respectively. A comprehensive listing and description are beyond this work's scope.

Despite these advances, several challenges remain. In this work, we demonstrate that the presence of occasional, disproportionately high or low metabolite intensities (outliers) can deteriorate the performance of existing normalization methods. Outliers can occur infrequently, i.e., for a given (subset of) metabolite(s) (analyte outliers), or for all measurements in a sample (sample outliers); their treatment in this work does not differ. We subsequently show that such outliers go on to reduce statistical power in downstream analyses, such as differential metabolite abundance testing, likely contributing to numerous false negatives but also causing likely false positives. We introduce three robust approaches, built upon cross-validated robust LOESS, additive models (AMs), and generalized AMs (GAMs). We capitalize on (G)AMs' ability for flexible non-linear modeling, for hypothesis testing and for observation weighting, refinements that enhance performance through a data-driven joint or selective usage of QC and biological samples for normalization. Given common pitfalls in benchmarking normalization strategies, such as using a reduction of the relative standard deviation of QC samples or an increased number of differentially abundant metabolites as a proxy for good normalization[20], we propose and implement alternatives. To support application, we integrate both existing and the here introduced robust normalization methods into the Metanorm R package. Our implementations further capitalize on the problem's pleasingly parallel nature, resulting in efficient high-throughput normalization. In addition, the package provides complementary visualization options that support normalization performance verification.

Experimental Section

Current normalization strategies

For benchmarking we compared the three robust normalization approaches with the current QC-RLSC and QC-RSC strategies. Given that no metabolomics community-wide accepted reference implementations of these approaches exist[14], they were implemented based on details provided in the original manuscripts[13,16], insofar these details were available. Specifically, for QC-RLSC we used the loess function (stats package) with degree set to two and implementing a leave-one-out cross-validation (LOOCV) for span selection, with a span in the range $3/n \leq \alpha \leq 1$, n being the number of QC sample injections. The optimal span is selected as that span minimizing the mean-squared error of left-out observations. As spans below approximately 0.075 occasionally yield model fitting problems on experimental datasets, the minimal span taken is the highest value in the set $\{n/3, 0.075\}$. An alternative, faster implementation using generalized cross-validation (GCV) was also implemented, relying on the loess.as function in the fANCOVA package. For QC-RSC, following Kirwan et al.[16], we applied the smooth.spline function (stats package) of the R language, whose implementation allows for smoothness selection using either LOOCV or GCV, with default restrictions on the smoothness parameter.

For the evaluation on experimental datasets, the QC-RLSC and QC-RSC approaches, as well as SERFF[18] and TIGER[19] were included in the comparative analyses together with our three robust methods. SERFF was used through its Shiny graphical user interface provided by Fan et al.[18], at https://slfan.shinyapps.io/ShinySERRF/, whereas TIGER was available as an R package (Supplementary Table 1).

Three robust normalization methods

To increase robustness against outliers, the first normalization method uses a robust locally estimated scattersplot smoothing (LOESS) approach. Robustness is achieved by (iteratively) downweighing outlying observations, with weights determined by Tukey's biweight function (as implemented in the loess.as function in the R fANCOVA package). The optimal span is determined using either GCV or LOOCV.

116   Further normalization flexibility, while retaining robustness against outliers, is achieved by adopting one of

117   two distinct (generalized) additive model (GAM) formulations.

118   The first, which we named the robust GAM (rGAM) method, achieves robustness in a similar manner to

119   the rLOESS approach. For a given compound, an initial standard GAM fit is obtained for the model

120
$$\text{intensity}_i = \beta_0 + f(\text{order}_i) + \varepsilon_i, \quad \varepsilon_i \sim \mathcal{N}(0, \sigma^2),$$

121   with $i = 1, \dots, n$ the (QC) injection order index, β_0 an intercept, f a smooth function, and ε_i a Gaussian error

122   term. Next, observation weights are calculated based on the initial model fit's residuals, using Tukey's

123   biweight function,

124
$$w_i = \begin{cases} \left(1 - \left(\frac{r_i}{c}\right)^2\right)^2, & |r_i| \leq c \\ 0, & |r_i| > c \end{cases},$$

125   with r_i the fitted model's rescaled residuals, i.e. the model's residuals divided by a scaled median absolute

126   deviation (MAD) of the residuals ($\text{MAD} * 1.4826$), and $c = 4.6821$, a constant[21]. The model is then re-fitted

127   with these observation weights w_i,

128
$$\text{intensity}_i = \beta_0 + f(\text{order}_i) + \varepsilon_i, \quad \varepsilon_i \sim \mathcal{N}(0, \sigma^2/w_i).$$

129   The second strategy, which we named the tGAM method, achieves robustness more directly by adopting

130   a scaled-t distribution for the outcome,

131
$$\text{intensity}_i = \beta_0 + f(\text{order}_i) + \varepsilon_i, \quad \varepsilon_i \sim t_v(0, \tau^2),$$

with t_v a scaled-t distribution with v degrees of freedom. The use of a scaled-t distribution rather than a

Gaussian distribution reduces the impact of outliers on the estimated intensity for a given injection order[22].

Of note, while traditionally only QC samples are used[13,16], smooth function estimation can be based on QC

samples alone, biological samples alone, or their combination.

Optionally, for the additive models, observation weights can be supplied to assign more importance to any

given observation during model fitting, e.g., assigning higher weights to QCs than samples so that the

former exert a higher influence on the estimation of the smooth function.

Additive model refinements for dealing with batch effects

The additive model-based methods were further extended to properly handle batch effects. To achieve this, a batch covariate was added to the GAM model:

$$\text{intensity}_i = \beta_b + f_b(\text{order}_i) + \varepsilon_i, \quad \varepsilon_i \sim t_v(0, \tau^2),$$

where $b = 1, \dots, B$ denotes the B batches, i.e., the smooth function f_b, as well as the intercept β_b is allowed to differ by batch. Note that the scaled-t error term is replaced by a Gaussian error term, depending on the chosen model (tGAM $vs.$ rGAM). Due to the computational complexity that arises when many batches are involved, and because the residual variance between batches may differ, a 'batchwise' option was implemented: in this setting, an additive model is fitted per batch data subset, reducing model complexity and allowing for batch-specific residual variances,

$$\text{intensity}_{bj} = \beta_0^{(b)} + f^{(b)}(\text{order}_{bj}) + \varepsilon_{bj}, \quad \varepsilon_{bj} \sim t_v^{(b)}(0, \tau_b^2),$$

with $j = 1, \dots n_b$ a batch-specific index, n_b the number of runs in batch b, $\beta_0^{(b)}$ and $f^{(b)}$ a batch-specific intercept and smooth function respectively, and ε_{bj} a batch-specific error term (again, potentially replaced by a Gaussian error term depending on the chosen model).

Additive model refinements for verifying whether QCs are representative of biological samples

A final optional adjustment enables an evaluation of (within-batch) differences in intensities between biological samples and QCs. This is achieved by adding a 'type' covariate to the GAM model specification, indicating whether a run concerns a QC or a biological sample, resulting in separate smooth functions for biological samples and QCs:

$$\text{intensity}_i = \beta_{\text{type}} + f_{\text{type}}(\text{order}_i) + \varepsilon_i, \quad \varepsilon_i \sim t_v(0, \tau^2),$$

where β_{type} and f_{type} denote type-specific intercepts and smooth functions, respectively. Significant differences, i.e., a p-value lower than a user-specified cut-off, between QC- and sample-based intercepts and/or smooth functions, indicating unrepresentative QC samples, are determined using generalized likelihood ratio tests[23], and will then result in a model re-fit and normalization using biological samples only.

Implementation

The three robust methods rLOESS, rGAM and tGAM, along with the existing methods QC-RLSC and QC-RSC were implemented in the Metanorm R package (available from https://github.com/UGent-LIMET/Metanorm). Users can select a method of choice using the 'model' argument, with options 'QC-RLSC', 'QC-RSC', 'rLOESS', 'rGAM' or 'tGAM'. To reduce over- or underfitting, smoothness parameter estimation for the rLOESS, QC-RLSC and QC-RSC approaches are available with either LOOCV or GCV schemes ('cv' argument). All GAMs are fitted using restricted maximum likelihood[24] and thin plate regression splines (R mgcv package (Supplementary Table 1)), with the basis dimension ('k' argument) user-specified. Refinements can be combined in a single call of the normalization algorithm, i.e., observation weights ('weights' argument), the modeling of batch effects ('batch' argument), and QC versus biological sample modelling by using the 'QCcheck' argument for enabling comparison, and the 'QCcheckp' argument for setting the significance threshold.

Experimental data

Three experimental datasets were selected to investigate the impact and performance of the different normalization strategies. The first is the publicly available metabolomics BioHEART study dataset[25,26]. The BioHEART dataset comprises 1359 human plasma sample runs (of which 1002 unique biological samples) across 15 batches, quantifying the abundance of 53 targeted metabolites using an Agilent 1260 Infinity LC coupled to a QTRAP 5500 Sciex MS instrument. Data were preprocessed using Sciex' MultiQuant. Further details are provided by[25]. The occurrence of differentially abundant metabolites (DAMs) in this dataset was investigated for individuals with (n=390) or without (n=612) hypertension[25,26].

Secondly, a targeted metabolomics dataset from the ENVIRONAGE cohort was used[27]. A total of 322 children aged 4 to 12 years were included, of whom 48% (n=156) were boys. This dataset spans 393 human urine sample runs (of which 322 unique biological samples) across 6 batches, acquired using a Dionex Ultimate 3000 XRS UHPLC system (Thermo Fisher Scientific) coupled to a Q-Exactive MS instrument (Thermo Fisher Scientific). Further analytical details are provided by De Paepe et al.[28]. The resulting data were preprocessed using TARDIS[29], and metabolites with more than 10% missing values were removed. The final dataset used for assessing normalization performance comprised 269 targeted metabolites. DAMs in relation to biological sex were investigated[30]. Of note, batches in this dataset did not

always start with a QC sample; as QC-RLSC and QC-RSC cannot extrapolate beyond QCs within batches,

samples analyzed before the first QC in each batch could not be included for both methods.

Thirdly, an untargeted metabolomics dataset from the FAME cohort was utilized[31]. The FAME dataset

encompasses 618 human saliva sample runs (of which 486 unique biological samples), extracting 8913

metabolic features, acquired with a Vanquish Horizon ultra high performance LC system linked to an

Orbitrap Exploris 120 MS (Thermo Fisher Scientific). Data preprocessing was performed using Thermo

Fisher Scientific's Compound Discoverer 3.3 software. The occurrence of DAMs related to a healthy weight

(337 individuals) *vs.* overweight/obesity (99 individuals) was evaluated. Forty-four cases had no data for

weight status at the time of analysis and were excluded from the DAM analysis.

All intensities were log-transformed (base *e*) prior to normalization.

Comparing performance using simulated data

203   Drift was simulated *in silico* by sampling two hypothetical QC sample intensity values per 10 biological

204   samples, for a total of 1000 samples. This resulted in 84 QC sample intensities. Intensities were taken

205   from a sine function, offset by a randomly chosen value of 20 to avoid negative intensities, after which

206   Gaussian noise (standard deviation 0.3) was added:

$$\text{intensity}_i = 20 + \sin(x_i) + \varepsilon_i, \quad \varepsilon_i \sim \mathcal{N}(0, 0.3^2),$$

with $x_i = \frac{0}{999}, \frac{5}{999}, \frac{10}{999}, \ldots, \frac{4995}{999}$, chosen to represent part of a full sine period. The dataset was then split into

two equal parts, to obtain two distinct drift patterns (Supplementary Fig. S1). Next, zero, one, two or four

outliers were added, with the following characteristics: (i) outlier locations were selected randomly but

could not occur in the first five or last five observations, and (ii) outliers were created by subtracting

between 20 and 30% (randomly selected within that range), subtracting between 20 and 100%, or

subtracting 100% or adding 200% of the simulated intensity value. Outlier parameters were feature-

specific, i.e., differed between each simulation run, allowing to evaluate their impact across sizes and

locations in the analysis sequence.

In each of $k = 200$ simulation runs, encompassing simulation of a single feature, and for a given number

of outliers, QC-RLSC, QC-RSC, rLOESS, rGAM and tGAM models were used for data normalization, using

both one and two QC samples per 10 biological samples. Performance was then assessed by calculating,

for each method, the squared difference between the predicted and expected drift pattern at all QC indices

in each simulation run. Finally, the median across all runs was calculated, yielding an estimated median

squared prediction error (MSPE) for each of the five methods, having used one or both QC samples, and

zero to four outliers, i.e., a total of 40 MSPE estimates.

Comparing performance using experimental data

Significant differences between groups of interest (see section Datasets) after normalization were

compared between methods. First, significant DAMs were determined using two-sided Wilcoxon rank sum

tests, with p-values < 0.05 taken to indicate significance. A comparatively equal number of DAMs, and

especially a notable overlap in DAMs was taken to demonstrate similar normalization performance. In

contrast, much larger or smaller numbers of DAMs, or low overlap was taken to demonstrate a deviating

normalization performance, which was subsequently further investigated at the compound level.

Additionally, fine-grained comparability was assessed by calculating the pairwise Spearman correlations

of the methods' p-values. Similarity was then quantified as the pairwise Euclidean distance of one minus

the correlation vectors of any two normalization methods. These were visualized in a heatmap, with rows

and columns arranged according to a hierarchical clustering with complete linkage to support an

assessment of comparative or divergent normalization performance across metabolites, as manifested in

terms of biological signal discovery.

In the BioHEART study, a subset of biological samples was run in replicate in subsequent batches. As

normalization was performed batchwise, no between-batch information leakage occurred, thus allowing to

use the consistency of observed intensities of these replicate runs as a benchmark for appropriate

normalization. Consistency was assessed by first calculating the difference between the two observed

intensities (rescaled by their mean intensity) in each pair of replicate runs, for all compounds, then

obtaining the MAD of these observed differences per normalization approach. A lower MAD then indicated

better correspondence of intensities across batches, suggesting superior normalization.

Finally, after removal of runs with missing data, two-dimensional principal component analysis (PCA) score

plots were constructed to allow a qualitative evaluation of batch effects and outliers pre- and post-

normalization.

Computational time and compute details

All five methods implemented in the Metanorm package, TIGER, through its R package, and SERFF through its web interface, were evaluated for computational run times across scenarios. These scenarios involved both targeted (53 compounds, BioHEART) and untargeted (8913 features, FAME) experiments, large (1361 samples, BioHEART) and medium (618 samples, FAME) sample sets, and large (15 batches, BioHEART) and medium (9 batches, FAME) batch numbers. Computational time was determined for analyses using from 1 to 6 compute cores, to support an assessment of the potential time gains due to the parallel computing approach implemented in the Metanorm package. Note that this was not possible for SERFF as it was run through its web interface. All methods were run with default arguments and parameter settings, except for the rGAM and tGAM methods that were run with the QCcheck argument active. To prevent central processing unit throttling affecting the time required for the sequential analyses of different methods, a two-minute break between any two analyses was ascertained. Computational time required was expressed as the number of normalized compounds per minute.

All analyses were performed using a 10-core Apple M1 Pro processor and 16GB RAM. The analyses were performed using R version 4.4.1[32]. Package details are provided as supplementary information (Supplementary Table S1).

Results

Three outlier-robust metabolomics normalization methods

This work introduces three normalization methods allowing outlier-robust signal intensity drift and batch effect correction. The first and simplest method modifies the QC-RLSC method[13] by downweighting outliers, thereby reducing their influence on the signal intensity drift fit (Fig. 1a). This robust locally estimated scatterplot smoothing (rLOESS) model further incorporates generalized cross-validation (GCV) as a replacement for the traditionally used leave-one-out cross-validation (LOOCV)[33]. The other two robust methods employ (generalized) additive models (GAMs) for signal drift and batch effect correction. The first GAM-based method, a robust GAM (rGAM) downweights outliers to minimize their impact on the signal drift fit, analogous to the rLOESS method (Fig. 1a). The second GAM-based method adopts a *t*-distribution (tGAM) rather than a Gaussian distribution for the intensities, enabling to handle outliers effectively, as the *t*-distribution's heavier tails reduce the influence of these outlying intensities (Fig. 1a). The outlier-robustness of our three methods exceeds that of QC-RLSC, QC-RSC and SERFF, which showed inferior normalization performance in batches containing outliers, exemplified in Fig 1a (see below for additional results). Results from our evaluation on *in silico* generated data causally confirmed the superior normalization performance of our three robust methods, both in the absence and presence of outliers, but in particular in the latter situation. Moreover, the robust methods remained comparatively unaffected by the number of outliers and magnitude of deviation. (Fig. 1b, S2-S4).

Figure 1: Susceptibility of normalization method to outliers and batch effects. (a) Unnormalized, QC-RLSC, QC-RSC, SERFF normalized (left column, top to bottom), and TIGER, rLOESS, rGAM or tGAM normalized (right column, top to bottom) for an example metabolite from the BioHEART study (see below for additional results). Dots indicate QCs, whereas triangles indicate

288 The rLOESS, rGAM and tGAM methods are implemented in the Metanorm R package

289 (https://github.com/UGent-LIMET/Metanorm), alongside implementations of the QC-RLSC and QC-RSC

290 methods.

Flexible modelling boosts normalization performance: leveraging convoluted variance in biological samples, and data-driven normalization

While QC-sample-based normalization is widely established, biological samples themselves also carry information on signal drift patterns and batch effects. The tGAM and rGAM implementations in the Metanorm package enable differential weighting of QC and biological samples during normalization. By assigning greater weight to QC samples, technical variance predominantly drives estimation of the normalization smooth, while batch- and signal-related information from biological samples is still incorporated (Fig. 2a-2c).

Further, the Metanorm package supports visual assessments of normalization performance. Diagnostic plots of pre- and post-normalization compound abundances can be automatically generated (Fig. 2). These plots highlight whether normalization successfully reduces technical variance across batches or, conversely, whether it fails to do so. An issue recurring across datasets was that QC-based normalization did not sufficiently remove technical variance or, in some cases, even introduced additional variance in biological samples due to differences between QC and biological samples (Fig. 2a-2c, S5). Given the infeasibility of verifying, and potentially adjusting, QC-based normalization for every single compound and batch, especially in untargeted studies, the Metanorm package includes an optional statistical test (QCcheck argument) to assess the suitability of QC-based normalization at the single compound (and batch) level. This test, compatible with both GAM-based methods, models signal drift separately for QCs and biological samples within each batch. If significant differences between the two are detected, the rGAM/tGAM normalization reverts to sample-based rather than combined sample and QC-based normalization (Fig. 2d). The stringency of this decision is controlled using the QCcheckp parameter. Together, these functionalities and diagnostic tools allow to evaluate and finetune normalization, while maximally extracting signal drift and batch effect information.

Validation on experimental data suggests robust normalization reduces false positive and false negative findings, and improves reproducibility

Experimental results confirmed the improved normalization performance of our three robust methods

previously observed in the *in silico* datasets.

The analysis of the BioHEART dataset indicated that the tGAM, rGAM and rLOESS methods resulted in

the detection of largely the same DAMs (92% joint DAM findings, Fig. 3b-3c). SERFF, however, showed

strong disagreement with the robust methods (29-41% joint DAM findings; Fig. 3b-3c). Investigation of pre-

and post-normalization intensity-versus-order plots for these discrepant findings supported proper

normalization of the robust methods, which were little affected by outliers (Fig. 3a). In contrast, SERFF

was impacted by few outliers, often showing increased variance for those biological samples in proximity

to such outlying observations (Fig. 3a). This is supported by the PCA score plots, which show a strong

reduction in batch effects compared to non-normalized data for all normalization methods, but also small residual batch effects for SERFF, which are not seen for the tGAM method. (Fig. 3d). Support for outliers as the root cause for this sub-par performance was provided. Indeed, manual identification and removal of outliers improved SERFF's normalization performance, with reduced variance observed in the proximity of previous outlying intensities (Supplementary Fig. S6). Not only SERFF resulted in an increased number of DAMs: notably, the unnormalized, raw data showed the highest number of DAMs, followed by TIGER and the QC-R(L)SC approaches (Fig. 3b). In all cases, discrepancies in both significant and non-significant findings between the robust and other methods could be linked to remaining drift or batch effects (Fig. 3a, Supplementary Fig. S7-S8). Further supporting the enhanced normalization performance of the robust methods, the normalized intensities of between-batch sample replicates showed the lowest between-replicate normalized differences, i.e., the highest correspondence, for the robust methods (49-52% reduction in between-replicate normalized differences, compared to unnormalized data), followed by SERFF (41% reduction), TIGER (40% reduction), then QC-RLSC and QC-RSC (18-22% reduction; Fig. 4).

Figure 3: Impact of normalization methods on the BioHEART data. (a) Methionine intensities before (top), after SERFF (middle), and after tGAM (bottom) normalization (Figure S7 for all methods). Dots indicate QCs, whereas triangles indicate biological samples; colors correspond to different batches. (b) Number of significantly differentially abundant metabolites (DAMs) by normalization method. (c) Venn diagram of DAMs for the three robust methods, SERFF and QC-RLSC. (d) Principal component

Figure 4: Median absolute deviation of scaled between-batch differences of compound intensities in non-QC samples for which

two replicate runs were performed in the BioHEART study. Lower median absolute deviation indicates a better cross-batch

agreement, and suggests an improved removal of technical variance.

[Note: one-column figure]

For the ENVIRONAGE dataset, similar albeit less pronounced patterns were observed (Fig. 5), likely

explained by the comparatively smaller batch and drift patterns, and the fewer and less severe outliers

seen when compared to the BioHEART dataset (Fig. 5a, 5d). Specifically, the robust methods were in

reasonable agreement (74-88% DAM overlap, Fig. 5b-5c), whereas QC-RLSC and, to a lesser extent,

SERFF and TIGER differed more strongly from the robust methods (47-51%, 68-70% and 64-67% DAM

overlap, respectively, Fig. 5b-5c). Differences in significant DAMs were mostly due to relatively small

differences in *p*-values, illustrated by comparatively high cross-method correlations (Fig. 5e), though

occasional larger differences arose due to fitting of QC-RLSC to non-representative QC observations, and

due to SERFF's sensitivity to outliers (Fig. 5a and Supplementary Fig. S9).

Figure 5: Impact of normalization methods on the ENVIRONAGE data. (a) Phenylglycine intensities before (top), after SERFF

(middle), and after tGAM (bottom) normalization. Dots indicate QCs, whereas triangles indicate biological samples; colors

correspond to different batches. (b) Number of significantly differentially abundant metabolites (DAMs) by normalization method.

(c) Venn diagram of DAMs for the three robust methods, SERFF and QC-RLSC. (d) Principal component score plots before (left),

after SERFF (middle), and after tGAM (right) normalization. Symbol types correspond to different batches. (e) Heatmap of

correlations of p-values as obtained by Wilcoxon tests, per normalization method; methods arranged according to hierarchical

clustering.

[Note: two-column figure]

For the FAME cohort, again, good agreement between the robust methods was observed (79-87% DAM

overlap), whereas QC-RLSC showed weaker agreement (55-59% DAM overlap; Supplementary Fig. S10).

Disagreements between QC-RLSC and the robust methods could often be traced to differences in QC *vs.*

biological sample intensities (Supplementary Fig. S9). No results for SERFF could be obtained, likely due

to the size of the dataset exceeding the server's capacity.

Across datasets, qualitative comparisons of pre- and post-normalization intensity-versus-order plots

between the three robust methods suggested that the rLOESS method was more likely to show signs of

overfitting. This was evidenced by occasional more wiggly smooth functions when compared to the rGAM

and tGAM methods (Supplementary Fig. S11). Differences between the rGAM and tGAM methods were

tentatively traced to the tGAM method at times being more robust to (groups of) outliers than the two-step

rGAM method (Supplementary Fig. S12).

Spanning all datasets and methods, the choice of cross-validation scheme had comparatively little impact, the number of DAMs and the strength of evidence for differential abundance between either GCV or LOOCV being highly comparable within normalization methods (Fig. 3b, 3e, 5b, 5e, Supplementary Fig. S6).

Robust and flexible normalization is computationally expensive, but offset by a parallel computing implementation

An assessment of the computation requirements showed stark differences: QC-RSC was fastest overall, with the rLOESS and QC-RLSC with GCV also delivering fast. Using six-core processing, all three methods normalized the BioHEART targeted data (53 compounds) in under 10 seconds (Fig. 6a) and the FAME untargeted data (8913 compounds) in under 7 minutes (Fig. 6b).

The more complex methods, TIGER and the GAM-based approaches, took notably longer, taking approximately 18 (rGAM), 64 (TIGER) and 136 (tGAM) seconds for the BioHEART dataset (Fig. 6a), and approximately 11 (rGAM), 15 (tGAM) or 115 (TIGER) minutes for the FAME dataset (Fig. 6b). The difference in ordering noted between both datasets could be explained by differences in the number of runs (1361 *vs.* 618), and/or the number of batches (15 *vs.* 9). SERFF, only available through its web server, took 147 seconds for the BioHEART dataset and failed to complete for the FAME dataset.

The computational overhead associated with parallel processing resulted in marginally slower normalization for the fastest methods in the BioHEART dataset, as evidenced by the tapering and then declining curves as more cores were used (Fig. 6a). This was not seen for the larger FAME dataset, where, across methods, more cores led to a steady decrease in computational time required. This suggests that, for datasets encompassing many compounds, an even higher number of cores than used here would further expedite data normalization (Fig. 6b).

415 *Figure 6: Time required for compound normalization by method. (a) BioHEART targeted data. (b) FAME untargeted data.*

416 *[Note: single-column figure]*

Discussion

The three normalization methods introduced here, rLOESS, rGAM and tGAM, are founded in well-studied statistical models[23,24], and their implementation in the Metanorm R package facilitates robust, high-throughput, and efficient normalization. By integrating robust non-linear modelling with differential sample weighting and data-driven modelling into a single framework, along with visualization options, the Metanorm package supports reliable normalization of both small- and large-scale metabolomics data, as evidenced in both *in silico* and experimental data analyses, consistently across instruments, sample types, and laboratories. The implied reductions in false positives and false negatives observed in the experimental analyses, attributed to reduced susceptibility to outlying intensities, strengthen the reproducibility of downstream statistical analyses, unlocking more efficient biological knowledge discovery.

Overall, the tGAM method exhibited the strongest performance across the experimental datasets, whereas performance on simulated data was comparable between rLOESS, rGAM, and tGAM. A practical limitation of tGAM is its higher computational cost relative to rLOESS and rGAM; however, normalization remains computationally feasible, completing within minutes on current consumer-grade hardware even for datasets comprising thousands of metabolites and hundreds of samples. Taken together, and based on the evidence presented here, we therefore tentatively recommend the tGAM method as a general default choice. Comparison of multiple methods remains useful as method performance may be dataset-specific.

An alternative to the use of the outlier-robust normalization procedures introduced here could be outlier detection and removal prior to normalization. Such outlier removal would need to be automated, as manual identification of outliers is both subjective and labor-intensive for typical metabolomics datasets often constituting hundreds to thousands of features. While automated outlier detection is non-trivial[34], it is a potential alternative to the procedures introduced in this work. In particular, multivariate outlier detection may improve the current feature-level treatment of outliers. It is important to note that an observation that reduces normalization performance may still be correct and thus warrant exclusion or downweighting during normalization, but not necessarily during downstream statistical inference.

Besides the methods' increased robustness to outliers, we have shown that, while being widely applied[10,14], relying solely on QC sample-based normalization poses threats and misses opportunities. First, QC-based normalization assumes that QC samples ubiquitously and accurately mirror the technical and biological

variance in study samples. Data originating from different instruments and laboratories investigated in this

work show that this is not a universal truth. Such differences may arise from, e.g., different pre-analytical

treatment of QC *vs.* biological samples, repeated injection of the same QC sample, etc. When this

assumption of QCs being representative of biological samples does not hold, QC-based normalization

may not only underperform but may even reduce data quality by introducing artefacts. By adaptively testing

and, when necessary, reverting to a sample-based normalization strategy, Metanorm's GAM-based

procedures protect against such underperformance and artefacts. This adaptability is particularly important

for large-scale untargeted metabolomics studies, where the representativeness of QC samples is difficult

to verify manually across thousands of features. Second, biological samples themselves contain

exploitable information on drift and batch effects, not leveraged when using only QC samples for

normalization. By including the larger number of biological samples compared to QC samples (often a 5-

10-fold difference[14]), the available information on signal drift and batch effects is substantially increased,

although present in biological samples as a convolution of technical and biological variance. The

implementation of differential weighting in the tGAM and rGAM methods provides a compromise: by giving

QC samples stronger influence while still incorporating the drift information embedded in biological data,

a more precise normalization can be achieved. This is particularly useful to support normalization in

scenarios where QC sample coverage is sparse or uneven, arising when, e.g., QC sample analysis has

failed, or when QC samples are lacking altogether. Visualization tools further enhance quality control,

allowing to inspect whether normalization has achieved its desirable effects. The pre- *vs.* post-

normalization and PCA score plots readily generated by the Metanorm package support an efficient

identification of subpar data quality or aberrant normalization, and can highlight metabolites, samples or

batches that require further, detailed inspection. We emphasize that unexpected differences between QC

samples and biological samples should receive due analyst scrutiny, as such differences may also reflect

issues with the biological sample analysis. In addition, any differences between QC and biological samples

may invalidate filtering on e.g., relative standard deviation (RSD) observed in QC samples, if such

differences are due to issues with the QC samples, discussed next.

In terms of verifying appropriate normalization, traditionally, the workhorse metric is the RSD, also known

as the coefficient of variation (CV)[13,16,18,19], with substantially reduced RSDs after normalization being taken

as a reflection of good performance. Nonetheless, the RSD has been critiqued for favoring overfitting[20].

Indeed, some strategies, while having merit and reducing technical variance, can result in small RSDs due

to fitting non-signal drift related random noise[35]. The same is true when no proper cross-validation is

conducted. We avoided such evaluation metrics measures when assessing Metanorm as we believe such

surrogate measures are ideally replaced by those measures with a causal relationship with normalization

performance. One such approach broadly applied in the statistics and bioinformatics literature but, to our

knowledge, underexplored for (QC-based) data normalization methods in metabolomics is through *in silico*

simulation studies where the ground truth is known[36]. Such an approach was incorporated in this study but

could for future studies be further enhanced to more comprehensively verify normalization performance.

This could be achieved by better mimicking experimental metabolomics data, for example, by simulating

from observed data using resampling strategies, while accounting for cross-metabolite correlations.

Indeed, such a strategy would allow to also benchmark multivariate methods as SERFF and TIGER. In

addition, benchmarking a broader set of normalization methods remains important future work. In

benchmarking, care should be taken to assure neutrality, i.e., not potentially favor any of the benchmarked

methods which can arise from, e.g., simulating from a fitted model from one of the benchmarked methods

[37]. Other evaluation metrics should equally be interpreted with due care. For example, the extent to which

biological signal can be extracted does not necessarily correlate with normalization performance (e.g., De

Livera et al.[20]). As with RSDs, this is an indirect evaluation approach, and findings in this work suggest

that not only false negatives but also false positives could arise due to subpar normalization, a finding that

is also supported elsewhere[37]. An important nuance, for method benchmarking, p-value thresholding was

used for method ranking and relative comparisons, not for formal hypothesis testing with controlled error

rates. All normalization strategies were applied to the same feature set and evaluated under a single

nominal threshold. Applying a multiple testing correction would alter the number of selected features but

is unlikely to affect (i) the relative ordering of normalization strategies, or (ii) the overlap patterns that were

the primary focus of our evaluation. Indeed, conclusions are based on consistency and overlap of selected

features across normalization methods; the number of significant features should not be interpreted as a

proxy of normalization quality as inappropriate normalization can induce false positives and false

negatives. While not in the scope of this work, multiple testing correction is essential for downstream

statistical inference. Last, we employed technical replicates for evaluating normalization performance.

When these replicates are sufficiently spaced, e.g., analyzed in distinct batches, information leakage is

prevented when using per-batch normalization methods. Replicate concordance is thus also expected to

be an unbiased measure of normalization accuracy. We recommend inclusion of both QC and replicate

samples to support data quality and normalization performance investigation.

Our methods focus on interpretable normalization at the metabolite level. Fairly recently, machine learning

models for metabolomics data normalization have been proposed and tentatively shown to outperform

existing approaches[18,19]. While these methods have notable strengths, such as their capability to model

potential interactions between signal drift patterns across metabolites, they also suffer potential

drawbacks. For example, these approaches were demonstrated to have good performance on large

datasets (with up to thousands of samples, and several hundreds of metabolites), but their reliability for

smaller datasets has so far not been broadly investigated. In contrast, our metabolite-level normalization

methods perform equally well on targeted datasets investigating few metabolites and on untargeted

datasets, irrespective of whether they encompass dozens or thousands of samples. Further

enhancements of metabolite-level approaches, however, could be achieved by leveraging cross-

metabolite information.

Conclusion

Current approaches to normalization of metabolomics data can be sensitive to outliers in metabolite

intensities, leading to subpar normalization, and eventually false negative and false positive discoveries.

Three new methods, rLOESS, rGAM and tGAM, that are robust to such outliers were presented, with

evaluations suggesting improved normalization performance. Additional flexibility, such as the ability to

handle occasional discrepancies between biological samples and QCs in an automated way, can further

enhance normalization performance. Critically, normalization method selection was shown to strongly

affect the number of differentially abundant metabolites, with, consequently, potentially large effects for

downstream mechanistic knowledge discovery. These new methods, together with commonly used

alternatives, are implemented in the Metanorm R package, which exploits parallelization for efficient

processing. Visualization of metabolite intensities before and after normalization remains important for

assessing performance, and options supporting such performance assessments are included in the

Metanorm R package.

Supporting information

Supporting Information: Table of R packages and versions used (Table S1); supporting figures: an example simulated dataset (Figure S1), normalization performance on simulated data (Figures S2-S4), selected feature plots illustrating pre- and post-normalization feature intensities in a variety of settings (Figures S5-S9, S11-S12), and additional results of normalization performance on the FAME cohort data (Figure S10).

Data availability

The targeted metabolomics data from the BioHEART cohort is available at https://github.com/SydneyBioX/BioHEART_metabolomics. The targeted metabolomics data from the ENVIRONAGE cohort is available at https://zenodo.org/records/14548033. The untargeted metabolomics data from the FAME study is available at the Metabolomics Workbench with project ID PR002287 (http://dx.doi.org/10.21228/M80Z5F), under study ID ST003697.

Code availability

The Metanorm package is available at https://github.com/UGent-LIMET/Metanorm. The code used for the analyses and generating figures is available at https://github.com/UGent-LIMET/Metanorm_publication.

Acknowledgements

The authors thank the Laboratory of Integrative Metabolomics' administrative and technical personnel for their continuous support of the lab's research activities.

Author contributions

MV conceptualized and developed the ideas, implemented the methods, performed data analysis, created figures, wrote the initial draft and edited the draft paper. PV contributed to the development of the ideas and reviewed and edited the draft paper. EDP and VP contributed to the generation of the data, provided feedback on the software, and reviewed and edited the draft paper. TN contributed to the generation of the data, and reviewed and edited the draft paper. LV acquired funding, contributed to the development of the ideas, supervised the project, and reviewed and edited the draft paper.

Funding

This work is funded in part by the European Union (ERC project MeMoSA, 2023-CoG, 101124151, and ERC project ENVIRONAGE, 2012-StG, 310898). Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Research Council. Neither the European Union nor the granting authority can be held responsible for them. The work is further funded in part by FWO (G073315N (ENVIRONAGE) and GO12721N (FAME)) and the Interuniversity Special Research Fund (iBOF) from Flanders (BOFIBO2021001102).

Competing interests

The authors declare no competing interests.

References

1. Liu, R.; Hong, J.; Xu, X.; Feng, Q.; Zhang, D.; Gu, Y.; Shi, J.; Zhao, S.; Liu, W.; Wang, X.; Xia, H. Gut microbiome and serum metabolome alterations in obesity and after weight-loss intervention. *Nat. Med.* **2017**, *23*(7), 859–868.

2. Cubero-Leon, E.; De Rudder, O.; Maquet, A. Metabolomics for organic food authentication: Results from a long-term field study in carrots. *Food Chem.* **2018**, *239*, 760-770.

3. Yu, Q.; He, Z.; Zubkov, D.; Huang, S.; Kurochkin, I.; Yang, X.; Halene, T.; Willmitzer, L.; Giavalisco, P.; Akbarian, S.; Khaitovich P. Lipidome alterations in human prefrontal cortex during development, aging, and cognitive disorders. *Mol. Psych.* **2020**, *25*(11), 2952-2969.

4. Han, S.; Van Treuren, W.; Fischer, C. R.; Merrill, B. D.; DeFelice, B. C.; Sanchez, J. M.; Higginbottom, S. K.; Guthrie, L.; Fall, L. A.; Dodd, D.; Fischbach, M. A.; Sonnenburg, J. L. A metabolomics pipeline for the mechanistic interrogation of the gut microbiome. *Nature* **2021**, *595*, 415–420.

5. McLaughlin, S.; Zhalnina, K.; Kosina, S.; Northen, T. R.; Sasse, J. The core metabolome and root exudation dynamics of three phylogenetically distinct plant species. *Nat. Comm.* **2023**, *14*(1), 1649.

6. Lind, L.; Fall, T.; Ärnlöv, J.; Elmståhl, S.; & Sundström, J. Large-scale metabolomics and the incidence of cardiovascular disease. *J. Am. Heart Assoc.* **2023**, *12*(2), e026885.

7. Liang, D.; Tang, Z.; Diver, W.R.; Sarnat, J.A.; Chow, S.S.; Cheng, H.; Deubler, E.L.; Tan, Y.; Eick, S.M.; Jerrett, M.; Turner, M.C. Metabolomics signatures of exposure to ambient air pollution: A large-scale metabolome-wide association study in the cancer prevention study-II nutrition cohort. *Environ. Sci. Technol.* **2024**, *59*(1), 212-223.

8. D'Autry, W.; Wolfs, K.; Yarramraju, S.; Van Schepdael, A.; Hoogmartens, J.; Adams, E. Characterization and improvement of signal drift associated with electron ionization quadrupole mass spectrometry. *Anal. Chem.* **2010**, *82*(15), 6480-6486.

9. Dunn, W. B.; Wilson, I. D.; Nicholls, A. W.; Broadhurst, D. The importance of experimental

design and QC samples in large-scale and MS-driven untargeted metabolomic studies of

humans. *Bioanalysis* **2012**, *4*(18), 2249-2264.

10. Evans, A. M.; O'Donovan, C.; Playdon, M.; Beecher, C.; Beger, R. D.; Bowden, J. A.;

Broadhurst, D.; Clish, C. A.; Dasari, S.; Dunn, W. B.; Griffin, J. L.; Hartung, T.; Hsu, P.; Huan,

T.; Jans, J.; Jones, C. M.; Kachman, M.; Kleensang, A.; Lewis, M. R.; Monge, M. E.; Mosley,

J. D.; Taylor, E.; Tayyari, F.; Theodoridis, G.; Torta, F.; Ubhi, B. K.; Metabolomics Quality

Assurance, Quality Control Consortium (mQACC). Dissemination and analysis of the quality

assurance (QA) and quality control (QC) practices of LC–MS based untargeted

metabolomics practitioners. *Metabolomics* **2020**, *16*(10), 113.

11. Sysi-Aho, M.; Katajamaa, M.; Yetukuri, L.; Orešič, M. Normalization method for

metabolomics data using optimal selection of multiple internal standards. *BMC Bioinf.* **2007**,

8(1), 93.

12. Johnson, W. E. ; Li, C. ; Rabinovic, A. Adjusting batch effects in microarray expression data

using empirical Bayes methods. *Biostatistics* **2007**, *8*(1), 118-127.

13. Dunn, W. B.; Broadhurst, D.; Begley, P.; Zelena, E.; Francis-McIntyre, S.; Anderson, N.;

Brown, M.; Knowles, J. D.; Halsall, A.; Haselden, J. N.; Nicholls, A. W.; Wilson, I. D.; Kell, D.

B.; Goodacre, R.; The Human Serum Metabolome (HUSERMET) Consortium. Procedures

for large-scale metabolic profiling of serum and plasma using gas chromatography and liquid

chromatography coupled to mass spectrometry. *Nat. Protoc.* **2011**, *6*(7), 1060-1083.

14. Broeckling, C. D.; Beger, R. D.; Cheng, L. L.; Cumeras, R.; Cuthbertson, D. J.; Dasari, S.;

Davis, C. W.; Dunn, W. B.; Evans, A. M.; Fernández-Ochoa, A.; Gika, H.; Goodacre, R.;

Goodman, K. D.; Gouveia, G. J.; Hsu, P.; Kirwan, J. A.; Kodra, D.; Kuligowski, J.; Lan, R. S.;

Monge, M. E.; Moussa, L. W.; Nair, S .G.; Reisdorph, N.; Sherrod, S. D.; Holland, C. U.;

Vuckovic, D.; Yu, L.; Zhang, B.; Theodoridis, G.; Mosley, J. D. Current practices in LC-MS

untargeted metabolomics: a scoping review on the use of pooled quality control samples.

Anal. Chem. **2023**, *95*(51), 18645-18654.

15. Ulaszewska, M. M.; Weinert, C. H.; Trimigno, A.; Portmann, R.; Andres Lacueva, C.;

Badertscher, R.; Brennan, L.; Brunius, C.; Bub, A.; Capozzi, F.; Rosso, M. C.; Cordero, C. E.;

Daniel, H.; Durand, S.; Egert, B.; Ferrario, P. G.; Feskens, E. J. M.; Franceschi, P.; Garcia-

Aloy, M; Giacomoni, F.; Giesbertz, P;; González-Domínguez, R.; Hanhineva, K.; Hemeryck,

L. Y.; Kopka, J.; Kulling, S. E.; Llorach, R.; Manach, C.; Mattivi, F.; Migné, C.; Münger, L. H.;

Ott, B.; Picone, G.; Pimentel, G.; Pujos-Guillot, E.; Riccadonna, S.; Rist, M. J.; Rombouts,

C.; Rubert, J.; Skurk, T.; Sri Harsha, P. S. C.; Van Meulebroek, L.; Vanhaecke, L.; Vázquez-

Fresno, R. Wishart, D. Vergères, G. Nutrimetabolomics: an integrative action for

metabolomic analyses in human nutritional studies. *Mol. Nutr. Food Res.* **2019**, *63*(1),

1800384.

16. Kirwan, J. A.; Broadhurst, D. I.; Davidson, R. L.; Viant, M. R. Characterising and correcting

batch variation in an automated direct infusion mass spectrometry (DIMS) metabolomics

workflow. *Anal. Bioanal. Chem.* **2013**, *405*(15), 5147-5157.

17. Calderón-Santiago, M.; López-Bascón, M. A.; Peralbo-Molina, Á.; Priego-Capote, F.

MetaboQC: A tool for correcting untargeted metabolomics data with mass spectrometry

detection using quality controls. *Talanta* **2017**, *174*, 29-37.

18. Fan, S.; Kind, T.; Cajka, T.; Hazen, S. L.; Tang, W. W.; Kaddurah-Daouk, R.; Irvin, M. R.;

Arnett, D. K.; Barupal, D. K.; Fiehn, O. Systematic error removal using random forest for

normalizing large-scale untargeted lipidomics data. *Anal. Chem.* **2019**, *91*(5), 3590-3596.

19. Han, S.; Huang, J.; Foppiano, F.; Prehn, C.; Adamski, J.; Suhre, K.; Li, Y.; Matullo, G.;

Schliess, F.; Gieger, C.; Peters, A.; Wang-Sattler, R. TIGER: technical variation elimination

for metabolomics data using ensemble learning architecture. *Briefings Bioinf.* **2022**, *23*(2),

bbab535.

20. De Livera, A. M.; Sysi-Aho, M.; Jacob, L.; Gagnon-Bartsch, J. A.; Castillo, S.; Simpson, J. A.;

Speed, T. P. Statistical methods for handling unwanted variation in metabolomics data. *Anal.*

Chem. **2015**, *87*(7), 3606-3615.

21. Holland, P. W.; Welsch, R. E. Robust regression using iteratively reweighted least-squares. *Commun. Stat.-Theory Methods* **1977**, *6*(9), 813-827.

22. Wood, S. N.; Pya, N.; Säfken, B. Smoothing parameter and model selection for general smooth models. *J. Am. Stat. Assoc.* **2016**, *111*(516), 1548-1563.

23. Wood, S. N. GAM theory. In *Generalized Additive Models: An Introduction with R*, 2nd ed.; Chapman and Hall/CRC, Boca Raton, FL, 2017, 240-324.

24. Wood, S. N. Fast stable restricted maximum likelihood and marginal likelihood estimation of semiparametric generalized linear models. *J. R. Stat. Soc. B* **2011**, *73*(1), 3-36.

25. Vernon, S. T.; Tang, O.; Kim, T.; Chan, A. S.; Kott, K. A.; Park, J.; Hansen, T.; Koay, Y. C.; Grieve, S. M.; O'Sullivan, J. F.; Yang, J. Y., Figtree, G. A. Metabolic signatures in coronary artery disease: results from the BioHEART-CT study. *Cells* **2021**, *10*(5), 980.

26. Kim, T.; Tang, O.; Vernon, S. T.; Kott, K. A.; Koay, Y. C.; Park, J.; James, D. E.; Grieve, S. M.; Speed, T. P.; Yang, P.; Figtree, G. A.; O'Sullivan, J. F.; Yang, J. Y. H. A hierarchical approach to removal of unwanted variation for large-scale metabolomics data. *Nat. Comm.* **2021**, *12*(1), 4992.

27. Janssen, B. G.; Madhloum, N.; Gyselaers, W.; Bijnens, E.; Clemente, D. B.; Cox, B.; Hogervorst, J.; Luyten L.; Martens, D. S.; Peusens, M.; Plusquin, M.; Provost, E. B.; Roels, H. A.; Saenen, N. D.; Tsamou, M.. Vriens, A.; Winckelmans, E.; Vrijens, K.; Nawrot, T.S. Cohort Profile: The ENVIRonmental influence ON early AGEing (ENVIR ON AGE): a birth cohort study. *Internat. J. Epidemiol.* **2017**, *46(5)*, 1386-1387m.

662   28. De Paepe, E.; Van Meulebroek, L.; Rombouts, C.; Huysman, S.; Verplanken, K.; Lapauw, B.; Wauters, J.; Hemeryck, L. Y.; Vanhaecke, L. A validated multi-matrix platform for metabolomic fingerprinting of human urine, feces and plasma using ultra-high performance liquid-chromatography coupled to hybrid orbitrap high-resolution mass spectrometry. *Anal. Chim. Acta* **2018**, *1033*, 108-118.

667   29. Vangeenderhuysen, P.; Vynck, M.; Pomian, B.; De Windt, K.; Callemeyn, E.; De Paepe, E.; De Commer, L.; Raes, J.; Nawrot, T.; Rainer, J.; Hemeryck, L. Y.; Vanhaecke, L. Automated

Integration and Quality Assessment of Chromatographic Peaks in LC–MS-Based

Metabolomics and Lipidomics Using TARDIS. *Anal. Chem.* **2025**, *97*(18), 9927-9934.

30. Van Pee, T.; Engelen, L.; De Boevre, M.; Derrien, M.; Hogervorst, J.; Pero-Gascon, R.;

    Plusquin, M.; Poma, G.; Vich i Vila, A.; Covaci, A.; Vanhaecke, L.; De Saeger, S.; Raes, J.;

    Nawrot, T. S. Sex differences in the association between long-term ambient particulate air

    pollution and the intestinal microbiome composition of children. *Environ. Int.* **2025**, *199*,

    109457.

31. De Paepe, E.; Callemeyn, E.; De Windt, K.; Wijnant, K.; Plekhova, V.; Pomian, B.;

    Vangeenderhuysen, P.; De Henauw, S.; Michiels, N.: Viljakainen, H.; Leppänen, M.; Lakka,

    T.; Van De Maele, K.; Baeck, N.; De Bruyne, R.; Lefere, S.; Geerts, A.; Vynck, M.;

    Vanhaecke, L. A repository of the salivary metabolome and its key drivers in 1436 European

    children. *EBioMedicine* **2025**, 122, 106019.

32. R Core Team (2024). R: A Language and Environment for Statistical Computing. R

    Foundation for Statistical Computing, Vienna, Austria. https://www.R-project.org/.

33. Broadhurst, D.; Goodacre, R.; Reinke, S. N.; Kuligowski, J.; Wilson, I. D.; Lewis, M. R.;

    Dunn, W. B. Guidelines and considerations for the use of system suitability and quality

    control samples in mass spectrometry assays applied in untargeted clinical metabolomic

    studies. *Metabolomics* **2018**, *14*(6), 72.

34. Boukerche, A.; Zheng, L.; Alfandi, O. Outlier detection: methods, models and classification.

    ACM Comput. Surv. **2020**, 53(3), 1-37.

35. Kamleh, M. A.; Ebbels, T. M.; Spagou, K.; Masson, P.; Want, E. J. Optimizing the use of

    quality control samples for signal drift correction in large-scale urine metabolic profiling

    studies. *Anal. Chem.* **2012**, *84*(6), 2670-2677.

36. Morris, T. P.; White, I. R.; Crowther, M. J. Using simulation studies to evaluate statistical

    methods. *Stat. Med.* **2019**, *38*(11), 2074-2102.

694   37. Weber, L. M.; Saelens, W.; Cannoodt, R.; Soneson, C.; Hapfelmeier, A.; Gardner, P. P.;

695   Boulesteix, A., Saeys, Y.; Robinson, M. D. Essential guidelines for computational method

696   benchmarking. *Genome Biol.* **2019**, *20*(1), 125.