Qimai: a multi-agent framework for zero-shot DNA-protein interaction prediction

Cong Liu[1], Mina Yao[1], Wei Wang[1,2,3]

[1] Department of Chemistry and Biochemistry, University of California San Diego, La Jolla, CA 92093-0359, USA

[2] Department of Cellular and Molecular Medicine, University of California San Diego, La Jolla, CA 92093-0359, USA

[3] Bioinformatics and Systems Biology Graduate Program, University of California San Diego, La Jolla, CA 92093-0359, USA

Abstract

Accurate prediction of DNA-protein interactions, a fundamental task in genomics, is limited by the poor generalization of existing models to novel proteins not seen during training. To address this challenge, we introduce Qimai, a modular AI agent framework that integrates deep learning predictions with biological evidence using Large Language Model (LLM) as reasoning engine. Qimai combines direct motif evidence from the query protein, indirect motif evidence from its interactors, and quantitative prediction from a new transformer-based DPI model to produce explainable predictions with confidence scores. On a benchmark of 78 unseen proteins, Qimai consistently outperforms standalone deep learning models across all metrics, increasing the Area Under Curve of the Precision-Recall (AUC-PR), the Area Under Curve of the Receiver Operating Characteristic (AUC-ROC), and Matthews Correlation Coefficient (MCC) by 17.6%, 15.6%, and 244% respectively compared to the best standalone model. Ablation analyses reveal that this gain is driven by the LLM's ability to dynamically weigh diverse evidence, with indirect motif evidence of co-factors particularly critical for unseen proteins. Qimai establishes a generalizable and interpretable paradigm for integrating heterogeneous data in predictive genomics. This framework is accessible via the Qimai web portal (https://qimai.wanglab.ucsd.edu/).

Introduction

Transcription factors (TFs) bind to specific DNA sequences to control transcriptional programs, which are essential for cellular functions. While TF binding is partially determined by short sequence motifs, it is also highly context-dependent, modulated by local chromatin state, co-binding factors, and protein–protein interactions (PPIs)[1–3]. This complexity poses a persistent challenge for accurately predicting TF binding sites and generalizing these predictions to any protein from DNA sequence alone.

Deep learning has recently transformed this field. Models such as DeepSEA[4], Sei[5], and DNABERT[6] have leveraged large-scale ChIP-seq datasets to learn complex sequence-to-binding relationships. However, these models are often limited by a lack of interpretability and an inability to generalize beyond their training data, particularly to novel TFs not seen during training[7]. A critical challenge arises because many proteins detected in ChIP-seq do not bind DNA intrinsic sequence specificity. Instead, they are recruited by other DNA-binding proteins or function within larger complexes that assemble on chromatin. These indirect but functionally indispensable associations are fundamental to transcriptional regulation but are beyond the prediction capability of the existing models.

For example, a master regulator like RUNX1 often co-localizes with its binding partners TAL1 and GATA proteins to form a regulatory circuit, controlling pluripotency and self-renewal[8]. Likewise, structural proteins such as cohesin components (e.g., RAD21) are often co-precipitated with sequence-specific factors like CTCF, forming a complex critical for higher-order genome folding, stabilizing enhancer–promoter loops, and shaping the regulatory landscape[9]. Similarly, many chromatin-modifying enzymes lack intrinsic DNA-binding ability but are guided to precise loci by sequence-specific TFs[10]. These examples highlight that predicting DNA–protein interactions requires capturing not only motif-driven binding but also the recruitment of non-sequence-specific proteins essential for 3D genome organization, chromatin state maintenance, and signal integration. Importantly, by failing to disentangle these mechanisms, models become uninterpretable and cannot generalize to novel interactions mediated by proteins, creating a critical need for a new framework that can reason about these distinct modes of interaction.

Here, we introduce Qimai (**Q**uantitative **I**nference of **M**olecular interactions by **AI** agents), a multi-agent AI system for predicting DNA–protein interactions that integrates deep learning predictions with diverse biological evidence to improve generalization and interpretability. Our method consists of four distinct yet cooperative agents: a Decision Agent, a prediction model trained on ChIP-seq data; an Evidence Retriever, which determines whether the input sequence contains motifs of the target TF or of its known

protein-protein interaction (PPI) partners; and a Reasoning Agent and a Critique Agent, which together

integrate predictions and motif context to infer interactions, explains the reasoning and assesses prediction

confidence. This modular structure mimics human expert reasoning: a quantitative prediction from the

deep learning model is reinforced by the presence of the TF's own motif in the DNA, or, if absent, by

motifs of its known interactors. This indirect evidence is especially informative for proteins like novel

TFs without known motifs or cohesion and chromatin modifiers, which lack intrinsic sequence motifs but

exert central regulatory roles through recruitment by DNA-binding partners.

Across a range of benchmarks, Qimai significantly outperforms state-of-the-art models, including

DeepSEA[4], Sei[5], and DNABERT[6]—in both standard and zero-shot settings, accurately predicting binding

of previously unseen proteins on unseen DNA sequences. By disentangling sequence modeling from prior

biological knowledge, and recombining them in a transparent decision framework, our architecture

represents a conceptual shift in regulatory modeling: from end-to-end black boxes to modular,

interpretable agents informed by biological reasoning.

Results

The Qimai Framework: LLM-Driven Synthesis of Heterogeneous Evidence

To address the challenge of predicting DNA-protein interactions involving unseen proteins (i.e. proteins

not included in the training data), we developed Qimai, a multi-agent framework that employs Large

Language Model (LLM) to synthesize predictions from a deep learning model with direct and indirect

motif evidence (**Figure 1A**). We used Gemini-2.0-flash for performance evaluation and also assessed

other LLMs (see **Supplementary Note B**). The Decision Agent features a new dual-input transformer

DPI model (referred to as DPI model hereafter) that leverages pre-trained DNABERT and AlphaFold2

embeddings, enabling generalization to unseen DNA sequences and proteins (**Figure 1B**). The Evidence

Retriever Agent then collects relevant evidences by: (1) scanning the DNA sequence for direct binding

motifs, if known, of the query protein; (2) identifying motifs from known protein interactors (i.e. indirect

motif evidence) whose bindings suggest possible complex formation with the query protein; and (3)

generating a baseline prediction from the deep learning model such as the transformer DPI model we

developed in this work (**Supplementary Figure S1A**). This unified evidence is passed to an LLM

Reasoning Agent, which evaluates the evidence to produce a final, explainable prediction, and a Critique

Agent, which assigns a rule-based confidence score.

The new transformer DPI model achieves superior performance

We first compared the new transformer DPI model with the existing ones including DeepBind, DeepSEA,

and DNABERT (**Figure 1C**). We used the ChIP_690 dataset, a standard benchmark dataset on which the

other models were trained. It contains 690 TF ChIP-seq experiments from the ENCODE database

processed with the DeepBind[11] protocols. Instead of training a separate model for each experiment as

DeepBind, we combined all ChIP-seq experiments together and trained a unified model. DPI model

showed clear improvement over other models in almost every evaluation metric (**Figure 1C**), highlighting

the effectiveness of pre-trained DNA embeddings. While DPI and DNABERT showed similar

performances across most metrics, DPI achieved higher precision and lower recall, indicating our model

returned fewer, yet more accurate positive predictions.

Furthermore, we extracted the self-attention weights from protein module and compared the high-

attention regions with the annotated DNA-binding domains (DBDs). Thirty-two out of 34 proteins that

have documented DBDs in UniProt showed at least 50% overlapped regions (**Supplementary Figure**

1C). For example, DBDs of FOXA2 and PAX5 are marked with significantly high attention. RXRA, on

the other hand, has two high-attention regions: 133-159 and 261-430. The first region is related to DBD

(135-200) while the second overlaps with nuclear receptor ligand-binding domain (LBD) (183-417). It

demonstrated that pre-trained AlphaFold embeddings have encoded protein binding information,

facilitating prediction of DNA-protein interactions.

Qimai achieves robust performance on internal cross-validation

For a rigorous assessment, we generated five random train/test splits from Encode3and4 dataset, which is

a larger and more diverse dataset including 1877 ChIP-seq experiments across 844 TFs, each time holding

out 44 unseen proteins (**Methods**). When evaluated on the complete set of held-out proteins (averaged

across the five splits), the full Qimai system clearly outperformed all other models (**Figure 1D**). It

achieved a top F1 score of 0.537 and MCC of 0.178, a performance lift of approximately 35% and 13%

over the best standalone model, DPI (F1= 0.399, MCC=0.158). The other standalone models exhibited

distinct and often extreme biases: DeepSEA was highly conservative (high Specificity, low Recall), while

Sei was overly optimistic (low Specificity, high Recall) (**Supplementary Table 12**). Importantly,

Qimai's performance was remarkably more stable. For the F1 score, Qimai's standard deviation was only

0.012, nearly eight times smaller than DPI's deviation of 0.091. Similarly, its MCC deviation (0.018) was

almost five times smaller than that of DPI (0.088).

To dissect the contribution of each evidence type, we evaluated ablated versions of Qimai framework.

Withholding direct motif ("Qimai (w/o direct)") resulted in the most substantial performance decrease,

with the F1 score falling from 0.537 to 0.368. Similarly, exclusion of indirect motif evidence ("Qimai

(w/o indirect)") also dropped the predictive power (F1 = 0.501). This indicated that both direct and

indirect motif information provide unique, synergistic benefits for achieving optimal prediction.

Within each held-out set, we further identified "novel" proteins, defined as having less than 30%

sequence identity to any protein in the corresponding 800-protein training set. This resulted in five

distinct sets of novel proteins (6-12 per split) for evaluation (**Supplementary Figure S4A**). On these

truly novel proteins, Qimai's advantage was even more evident (**Supplementary Figure S4B;**

Supplementary Table 13). Here, Qimai achieved an F1-score of 0.497 and MCC of 0.272, while the best

standalone model, the transformer DPI, only managed an F1-score of 0.343 and MCC of 0.114,

representing a much larger performance lift of nearly 45% and 138%, respectively.

Qimai Achieves Superior Generalization on Novel Proteins in external dataset

To enable a more powerful prediction model, we re-trained the transformer DPI model on the whole

dataset Encode3and4. Note that this re-trained DPI model on Encode3and4 did not see ChIP_690 data at

all. We next incorporated this DPI model into Qimai and evaluated the full Qimai pipeline's performance

on the external ChIP_690 dataset, which contains unseen DNA sequences paired with 80 proteins present

(i.e. seen proteins) and 78 proteins not present in the training dataset (i.e. unseen proteins). Here, DNA

sequence-based models like Sei achieved strong performance (**Supplementary Figure S2A**). Qimai

system remained competitive in this setting, suggesting that DNA decoding dominates predictions for

known proteins.

A method's utility for novel discovery lies in its generalization ability to new proteins. We thus performed

a more stringent external validation on the 78 unseen proteins in ChIP_690. Qimai's methodological

advantage was clearly demonstrated here (**Figure 2A; Supplementary Table 7**). Qimai achieved the

highest performance across all key metrics, including an AUC-PR of 0.701, MCC of 0.308 and an F1-

score of 0.552. This represents a substantial improvement over the best standalone model, transformer

DPI, which had an AUC-PR of 0.596, MCC of 0.090 and an F1-score of 0.322. The other standalone

models, DeepSEA and Sei, struggled significantly, with Sei's performance falling to near-random levels

(AUC-PR 0.498, MCC -0.260), highlighting their limited ability to generalize to new proteins. Crucially,

the final confidence score produced by Qimai is not only highly discriminative, reflected by high AUC-

ROC and AUC-PR, but also well-calibrated (i.e. the confidence level corresponds to the actual likelihood

of a correct prediction), confirming that the score's value is a reliable proxy for the actual probability of a

correct prediction (**Supplementary Figure S2B**).

This superior performance was confirmed when focusing specifically on the novel proteins, defined as

having less than 30% sequence identity to any protein in the training set of 844 Encode3and4 proteins. In

total, 51 novel proteins out of 78 unseen proteins (65%) are identified (**Supplementary Figure S2C**),

which are diverse across multiple TF families. Almost half of the novel proteins are also in novel protein

families (23/51) (**Supplementary Figure S2D**). In this test, the full Qimai system consistently achieved

highest scores across most of the key metrics (**Figure 2B**). This represents a substantial improvement

over the standalone deep learning methods. For instance, Qimai's MCC (0.314) is more than double that

of the standalone model DPI's (0.122), DeepSEA (0.166), while Sei's negative MCC (-0.176) indicates

its predictions were worse than random guessing. The standalone models exhibited distinct and often

extreme biases: DeepSEA was highly conservative (high Specificity, low Recall), while Sei was overly

optimistic (low Specificity, high Recall) (**Supplementary Table 8**). This demonstrates that Qimai's

ability to integrate biological motif evidence is critical for truly novel protein prediction.

Ablation studies revealed that this gain of performance stems from Qimai's ability to integrate diverse

evidence. While removing direct motif evidence ("Qimai (w/o direct)") causes the most significant drop

in performance, demonstrating its high impact when available, the removal of indirect motif evidence

("Qimai (w/o indirect)") also consistently degraded performance compared to the full system. This

confirms that both evidence are essential and complementary for optimal prediction. The consistent

positive contribution of indirect evidence is particularly noteworthy, as it provides a robust and alternative

source of biological information. These results underscore Qimai's ability to intelligently integrate

biologically grounded motif information via LLM-based reasoning, offering critical resilience when

computational models operate outside their training domain.

LLM Agent Outperforms a state-of-the-art Classifier through Context-aware Reasoning

We next investigated whether LLM outperformed ensemble classifier for integrating information. We

compared the LLM Agent against a highly optimized LightGBM ensemble classifier on a challenging

hold-out test set of 5,000 protein-DNA interactions composed of 78 unseen proteins and unseen DNAs in

the ChIP_690 dataset. LightGBM performed well, achieving an AUC-ROC of 0.817 on the validation set.

As any classifier, the feature weights in LightGBM are fixed and the most important contribution comes

from the transformer DPI model.

Compared to LightGBM, the LLM Agent demonstrated consistently superior performance across all

evaluation metrics (**Figure 2C**). The most substantial improvement was observed in MCC, where the

LLM Agent achieved a score of 0.305, representing a 221% relative improvement over the baseline's

score of 0.095. This indicates a significantly better classification balance and highlights a key limitation

of standard classification models, whose feature weights are fixed and cannot adjust evidence weights

based on different contexts, such as weighing indirect evidence more if the deep learning model has a

borderline prediction or a novel protein does not have any known motif or bind to DNA directly. Indeed,

LightGBM applied the same weights learned from the training data to the unseen or novel proteins, which

led to poor performance.

The LLM Agent's performance stemming from its flexible, context-aware reasoning is exemplified in a

case study of AP2A protein (**Supplementary Figure S2E**). Here, the agent was faced with strong motif

evidence that contradicted a low-probability deep learning model prediction. The LightGBM classifier,

misled by its learned dependence on the model score, failed. In contrast, the LLM Agent correctly

identified the conflict, evaluated the quality of the evidence, and prioritized the strong motif evidence to

reach the correct conclusion. Additional examples are shown in **Supplementary Note D**.

To further validate the inferential process, we conducted an "LLM-as-a-Judge" evaluation where three

independent LLM judges (phi4, deepseek-r1, and qwen3) assessed 500 prediction explanations generated

by Qimai. This cross-examination confirmed consistently high quality of the agent's reasoning across all

evaluation criteria (**Supplementary Figure S2F**). All three judges awarded near-perfect scores for key

capabilities such as Factual Accuracy (avg. 4.99/5), Conflict Resolution (avg. 4.97/5), and Overall

Quality (avg. 4.95/5), indicating that the generated explanations are robust, coherent, and logically sound.

Agreement between diverse judges confirms the objective quality of the outputs and indicates that the

Qimai's superior performance is a direct result of its robust, evidence-based inferential capabilities. This

capacity to dynamically weigh and synthesize conflicting data streams, much like a human expert, marks

a significant advantage of the agent-based framework.

 Indirect Evidence is Critical for Predicting de novo Interactions

The importance of indirect evidence is most apparent when evaluating its performance on the most

challenging subset of proteins: 45 novel proteins (sequence similarity < 30%) that also lack known direct

binding motifs. This scenario represents a true *de novo* discovery problem where methods relying on

direct motif information or protein-specific training data are expected to fail. It is not surprising that the

standalone Sei and DeepSEA models collapsed to near-random performance on this cohort (**Figure 2D;**

Supplementary Table 9).

In stark contrast, Qimai demonstrated remarkably robust predictive power, a success driven almost

entirely by indirect evidence. The configuration relying only on indirect motif evidence ("Qimai (w/o

direct)") achieves the highest performance, with a MCC of 0.211, nearly triple that of the negative control

("Qimai (w/o indirect)", MCC = 0.076). The standalone transformer DPI model, while also outperforming

Sei and DeepSEA due to its better generalization, still falls significantly short of the Qimai configurations

that include indirect evidence. This observation decisively proves that Qimai's ability to leverage the

indirect evidence pathway is the primary driver of its success in these challenging cases. By identifying

interacting TFs and their motifs, the LLM agent can successfully reason about potential interactions even

when all direct information about the query protein is absent, a critical capability for expanding our

understanding of uncharacterized proteins.

Indirect motif evidence proves especially critical for predicting interactions involving non-canonical

transcription factors (non-TFs) or TFs without known direct motifs. In these cases, indirect evidence by

scanning for motifs of the query protein's PPI partners provides crucial, otherwise missing, clues about

potential DNA binding mediated through protein complex or co-factor recruitment. To quantify the

impact of this evidence, we analyzed 4713 correct predictions involving 186 unique non-TF proteins or

TFs without known motifs: 76.8% were "rescued" or strongly supported by significant indirect motif hits,

demonstrating its decisive, not merely supplementary, role, especially for proteins with limited or no

direct binding motif information.

A representative example is RAD21, a cohesin complex component rather than a TF, that does not have a

known motif in CisBP (**Figure 2E**). For example, for a query DNA sequence at chr9:127,360,766-

127,361,277, which is characterized by strong epigenetic signals indicative of an active regulatory

element, including enrichment for the active enhancer histone marks H3K27ac and H3K4me1, as well as

high DNase I hypersensitivity, signifying open chromatin (**Figure 2F**). The DPI model only produced a

borderline prediction (0.5789). However, Qimai's Evidence Retriever identified strong motif matches for

RAD21's key interactors, particularly CTCF. The genome browser view visually confirms this indirect

evidence: it not only shows co-localized ChIP-seq peaks for RAD21 and CTCF, but also highlights a

distinct CTCF motif instance (the green block in **Figure 2F**) directly within the binding peak. By

prioritizing this indirect evidence, the LLM Reasoning Agent inferred a medium-confidence prediction

(score = 0.66) that matched the ChIP-seq peak. This example illustrates how Qimai leverages indirect

evidence information to resolve ambiguous cases, enabling accurate prediction on non-TFs or novel

proteins. Additional examples representing different scenarios are shown in **Supplementary Note E**.

Discussion

The prediction of DNA-protein interactions remains a challenge in computational biology, particularly

because existing models often fail to generalize to novel proteins or cases where DNA-binding is

mediated indirectly. In this work, we introduce Qimai, an agent-based framework designed to address this

challenge. Rather than relying on a single monolithic and ever-larger predictive model, Qimai

intelligently synthesizes heterogeneous sources of information. Our results demonstrate that this new

paradigm, using a Large Language Model (LLM) as a reasoning engine to integrate deep learning

predictions with motif-based biological evidence, substantially improves generalization, particularly for

proteins not seen during training.

The strategic choice of an LLM as the reasoning engine is central to Qimai's success. Compared to a

highly optimized LightGBM ensemble classifier trained on the same structured features, the LLM Agent

achieved a 221% relative improvement in Matthews Correlation Coefficient (MCC), highlighting the

value of flexible, context-aware reasoning over rigid, fix-weighted evidence of LightGBM (**Figure 2D**).

As illustrated in the AP2A case study (**Supplementary Figure S2E**), Qimai correctly prioritized strong,

reliable motif evidence over low-probability model prediction, which is similar to human expert's

reasoning. This performance gain is not restricted to a single proprietary model: open-source Gemma-3-

27b-it performs comparably to proprietary Gemini models, particularly on the challenging "unseen"

protein dataset (**Supplementary Figure S3B**). This confirms that the superior performance is rooted in

the agent-based framework itself, which effectively leverages the general reasoning capacity of LLMs to

synthesize disparate biological data into coherent, evidence-backed predictions.

A central biological insight from this study is the importance of modeling proteins that do not directly

bind DNA. Many critical regulators, such as cohesin components (e.g., RAD21), chromatin remodelers,

or enzymes like histone acetyltransferases, reach their target loci through recruitment by DNA-binding

partners rather than by recognizing DNA sequences themselves. These proteins are indispensable for
chromatin organization, enhancer–promoter communication, and transcriptional activation, yet they
remain invisible to motif-centric models. Qimai's indirect evidence pathway is specifically designed to
capture these biologically important but challenging scenarios by considering motifs of known interaction
partners and reasoning about plausible recruitment mechanisms. This capability to hypothesize how a
protein is targeted to DNA, even in the absence of its own motif, represents a major conceptual advance
over end-to-end black-box models.
299
The superior performance of Qimai particularly on unseen proteins arises from two deliberate design
choices. First, foundation models like DNABERT and AlphaFold2 provide embeddings to our
transformer DPI model with a more generalizable feature space than models trained on more specific
sequence representations. Second, and more critically, the multi-agent reasoning layer incorporates direct
and indirect motif evidence, creating a biologically grounded safety net for generalization. Ablation
studies confirm that motif-based evidence is not a secondary input but a decisive factor that the LLM
reasoning agent can elevate or discount depending on context. This design enables Qimai to generalize
across diverse interaction models, direct, indirect, or structural, that underlie real regulatory systems.
308
309   Qimai's modularity is another strength. The framework treats the predictive model as an interchangeable
310   "Decision Agent.", allowing seamless upgrades as new state-of-the-art architectures emerge. Our ablation
311   studies on the seen proteins underscore this benefit (**Supplementary Figure S3C**). This adaptability
312   ensures that the system can remain cutting-edge while preserving the interpretability and evidence-
313   integration advantages of the agent-based structure.
314
There are limitations to our current implementation. Qimai depends on existing databases (CisBP,
STRING) for motif and interaction data, which are themselves incomplete. As a result, the accuracy of
predictions for non-DNA-binding proteins is partly constrained by the scope of existing annotations.
Furthermore, our current approach emphasizes motif and sequence-derived features. A natural next step is
to expand the Evidence Retriever to incorporate additional modalities such as epigenomic data (e.g., DNA
methylation, histone modifications, chromatin accessibility), which provides crucial cell-type-specific
context, as well as protein structure to assess the possibility of protein-protein interaction.
322
In conclusion, Qimai presents a new methodological paradigm for complex biological prediction tasks.
By separating evidence gathering from evidence synthesis, and leveraging an LLM as the reasoning core,
it creates a flexible and powerful framework that excels at generalization. This approach moves beyond

simple black-box prediction, offering explainable, evidence-backed hypotheses that are more aligned with

the process of scientific discovery. As foundation models and AI agents continue to evolve, frameworks

like Qimai will be pivotal in translating vast, multi-modal biological data into actionable knowledge.

Figures

Figure 1: Qimai framework and superior generalization performance on unseen proteins.

(A) Overall workflow. User input (DNA sequence, protein name) initiates the Evidence Retriever and Decision Agent. Retrieved motif evidence along with predicted probability is passed to a Reasoning Agent LLM, which generates an explanation and prediction. A Critique Agent then assigns a confidence score to produce the final output.

(B) DPI model architecture. We developed a new transformer-based deep learning model (DPI model) as one source of evidence. DNA and protein sequences are embedded (e.g., via DNABERT and AlphaFold2-derived embeddings, respectively) and processed by separate encoders. A cross-attentional decoder then integrates these representations to predict an interaction score and label. The true label is used for training via loss calculation (e.g., Binary Cross-Entropy, BCE) and metric evaluation. h: number of attention heads; m, n: sequence lengths; embedding dimensions are shown in parentheses.

(C) Benchmark DPI model with the state-of-the-art models. DPI model showed clear improvement over other models in almost every evaluation metrics, highlighting the effectiveness of pre-trained DNA embeddings.

(D) Five-fold Cross Validation performance within Encode3and4 dataset. The full Qimai system (lightest green) is compared against standalone deep learning models (DeepSEA, DPI, Sei) and ablated versions of the system. "Qimai (w/o direct)" and "Qimai (w/o indirect)" represents removing direct and indirect motif information from full Qimai respectively. This annotation is used throughout the paper. Results are averaged over five-fold cross validation results with error bars showing standard deviation.

Fig. 1 Qimai framework and performance

A   Qimai workflow

B   DPI model architecture

C   Comparison of DPI-bench with other TFBS models

D   Five-fold Cross Validation performance on held-out proteins

Figure 2: Qimai achieves superior generalization on unseen proteins by integrating motif evidence.

(A) Performance benchmark on 78 unseen proteins in ChIP_690 dataset. The full Qimai system consistently outperforms all standalone models (DPI, DeepSEA, Sei) and ablated configurations across all metrics, with error bars representing the standard deviation over ten runs. Each run was evaluated on 500 randomly sampled pairs.

(B) Performance on 51 novel proteins. The evaluation results from the "unseen" benchmark in Figure 2A were recalculated to include only the 51 proteins classified as novel (sequence similarity < 30%). The full Qimai system maintains the best performance, particularly in F1 and MCC.

(C) Performance of the LLM Agent versus LightGBM classifier on 78 unseen proteins. The LLM Agent (blue) and a highly optimized LightGBM baseline (green) were evaluated on a hold-out test set of 5,000 protein-DNA pairs containing only 78 unseen proteins. Error bars represent 95% confidence intervals estimated via bootstrapping. The LLM Agent consistently outperforms the strong classifier, with the most significant relative improvement seen in the MCC.

(D) Performance on 45 novel proteins without direct motifs. The evaluation results were recalculated from the "unseen" benchmark in Figure 2A to include only the 45 proteins classified as both novel and having no known direct motifs. Qimai's robust performance, driven by the "Qimai (w/o direct)" configuration, is maintained on this most challenging scenario while standalone models like DeepSEA and Sei collapse to near-random levels. The failure of "Qimai (w/o indirect)" negative control confirms that indirect evidence is the primary driver of success in this *de novo* prediction scenario.

(E) Representative analysis for a novel DNA-protein interaction. Qimai's output for the non-canonical DNA-binding protein RAD21. Faced with no direct motif hits and an uncertain DPI model prediction, the agent leverages strong indirect evidence from RAD21's known interactors (CTCF, CTCFL) to correctly predict an interaction with high confidence, demonstrating the framework's evidence synthesis capabilities in a real-world scenario.

(F) Regulatory landscape of query DNA sequence. Genomic tracks from the UCSC Genome Browser are shown. In the TF rPeaks track, the shade of the gray box is proportional to the maximum ChIP-seq signal observed across samples. The motif site is highlighted in green. The lower tracks display histone marks, where peak heights in the H3K4Me1, H3K4Me3, and H3K27Ac tracks correspond to the level of histone mark enrichment. The DNase track shows DNaseI hypersensitivity signal, indicating the open chromatin regions.

Fig. 2 Indirect evidence is crucial for superior generalization

A **Performance on 78 unseen proteins in external dataset ChIP_690**

B **Performance on 51 novel proteins**

C **Comparison with LightGBM classifier on 78 unseen proteins**

D **Performance on 45 novel proteins without direct motifs**

E **Representative analysis for novel DNA-protein interaction**

F **Regulatory landscape of query DNA sequence**

Online Methods

Data

We used a comprehensive set of human TF binding sites based on ChIP-seq experiments, where chromatin is immunoprecipitated by TF-specific antibody and the retained chromatin is then sequenced. The data (regions of enrichment also known as peak calls) we used in this study is generated by ENCODE with a uniform processing pipeline (**Supplementary Table 1**).

ChIP_690 dataset. This dataset contains 690 ChIP-seq experiments involving 158 TFs whose bindings were analyzed in different cell types or conditions. It was based on March 2012 ENCODE data freeze uniform TFBS peaks, which is a widely used dataset for training protein-DNA prediction models. Following *DeepBind* protocol[11] for processing the data, positive samples are 512 base-pair (bp) DNA sequences centered on ChIP-seq binding peaks. The negative samples are shuffled positive sequences with matching dinucleotide composition. The shuffling was performed using the "fasta-dinucleotide-shuffle" package implemented in MEME[12]. For each experiment, 100 sequences (positive:negative=1:1) were randomly sampled. If the original set included less than 100 peaks, all sequences were kept. We randomly split the data into training/validation/test sets with a ratio of 7:1:2 (**Supplementary Table 2**). We used this dataset to benchmark the performance of the DPI model (this model is thus referred to as "DPI-bench") with other models.

Encode3and4 dataset. This dataset contains 1877 ChIP-seq experiments involving 844 TFs, which includes all the available ChIP-seq experiments of phase III[13] and phase IV of ENCODE by September 2023. Following *DeepSEA* protocol[4] (see **Supplementary Note A** for this choice), human genome (hg38) was split into non-overlapping 200 bp bins. For each of the ChIP-seq experiments, we filtered out the binding peaks with signal value smaller than 50 and ran the intersection operation genome-wide with all 200 bp bins by constraining over a minimum overlapping of 50%. Then we kept the 200-bp bins with at least one TF binding event. Training samples are 512 bp DNA sequences centered at 200 bp bins. Some TFs have multiple experiments in different cell types or conditions. We took the majority vote as the final label if the training DNA sequence has different labels for the same TF. The bedtools software was used for genomic operations including intersection, merge, and overlap. Training/validation/test DNA sequences were split by chromosomes and strictly non overlapping. Each DNA-TF pair has a label of either 0 (not binding) or 1 (binding). We performed data down-sampling by sampling the negative DNA-TF pairs to keep the ratio of positive/negative samples as 1 (**Supplementary Table 3**). We used this dataset to train the final production model used in Qimai framework (referred to as "DPI").

DPI Model

DPI model is adapted from the original Transformer architecture in two aspects: (1) DNA as "source "
language and protein as "target" language; (2) instead of next-word prediction task, DPI is to predict
binary labels indicating interaction or not. Therefore, we removed the masking step in the decoder and
exposed the full sequence to the model training. We described the model details (**Figure 1B;**
Supplementary Figure S1B) in the following subsections.

Embedding extraction: We utilized a pre-trained DNA language model, DNABERT[6], to transform DNA
sequences into real-valued vectors. The pre-trained DNABERT-6mer model was selected since it
achieves the best performance. The maximum length of DNA sequence for DNABERT is 512 bp. The
hidden dimension of DNA embedding is 768. Protein sequences were downloaded from the UniProt
database. AlphaFold2[14] was applied to extract protein sequence embeddings. The maximum length of
protein sequences for extraction is 1200 amino acids (AAs) due to computational limitations, which
account for 95% of proteins in the dataset. The hidden dimension of protein embedding is 384.

Encode module: To capture the intra-protein and intra-DNA interactions, protein and DNA embeddings
were processed in the Transformer encoder module separately. The encoder module consists of two sub-
layers: the multi-head self-attention layer and fully connected feed-forward layer. A skip/residual
connection structure and layer-wise normalization are incorporated around each sublayer to greatly
facilitate training. The key feature within encoder is the multi-head self-attention layer which allows the
model to associate all the relevant positions in a context to better encode a specific sequence and develop
the "contextual understanding" in different aspects. DNA and protein encoders share the same
architecture but not the learned weights. Inside of each encoder, the embedding is first projected into the
hidden dimension of 240. Then the padded region is masked out in self-attention blocks. The output of
encoder is refined embedding incorporating intra-sequence features.

Decoder module: To capture the interactions between DNA and protein, outputs of encoders will be sent
to the decoder module, which adopts the original Transformer decoder architecture. Decoder module has
similar architecture as encoder, except it calculates the cross-attention between DNA and protein instead
of self-attention. Inside the decoder, interactions between two entities were learned and stored in the
weights of cross attention matrices, which can be extracted later for interpretation. The output of decoder
is interaction vector incorporating interaction information critical for binary prediction.

Prediction module: Lastly, we averaged the interaction vector across sequence dimensions to get a 240-dimensional vector. Then the vector goes through several linear layers with ReLU activations before the last linear layer, where a real-valued score is generated and sigmoid function is applied to get binary prediction.

Implementation and training

DPI model is implemented in PyTorch 1.12.1 with CUDA 11.6 and trained on a NVIDIA A6000 with 48 GB of memory. It minimizes the binary cross-entropy loss with the Adam optimizer. While Adam does not require a learning rate scheduler, we observed adding a LambdaLR scheduler improved performance. Given the large number of hyperparameters, we did not perform a comprehensive grid search due to high computational cost. Instead, we identified several key hyperparameters based on early validation performance (**Supplementary Table 4**).

We found that the model showed better performance with increasing sequence length, which holds true for both protein and DNA. Restricted by DNABERT model constriction, we used the maximum length of 512-bp for DNA. Restricted by computational memory, we used the maximum length of 768 AAs for protein. If a sequence exceeds this length, we randomly select a continuous 768 AA-long subset for each training instance, ensuring varied exposure to different sequence regions. Because we trained using mini-batches, we zero-pad sequences shorter than 768 AAs.

The other hyperparameters were optimized using the Ray Tune framework for efficient exploration of the search space. Hidden dimension (hid_dim) is optimized in the range of (96, 240). Batch size is optimized in the range of (2, 20). Number of layers is optimized in the range of (1, 6). Number of heads is chosen between 6 and 12. Learning rate is optimized in the range of (5e-5, 0.5). The primary metric used for model performance evaluation were validation loss and validation accuracy. We trained two models for benchmark (DPI-bench) and production (DPI) runs respectively. It took 150 hours on a single A6000 GPU card with 48G memory to train the full model for production run (DPI) while 20 hours to train the DPI-bench model on the same hardware. The optimal hyperparameters for each training process were summarized in **Supplementary Table 4**.

Interpretation of protein attention weights

We extracted the self-attention weights from protein encoder module. For each protein, the attention

weights were averaged across all layers, heads and testing instances. We then identified regions with

significantly large attention values. First, we calculated the mean and sd (standard deviation) of the whole

sequence as background. Next, we calculated z-score for each value in the sequence and found sub-

sequences no less than 8 AAs with z-scores larger than 0.2 (adjusted p-value of 0.001). Lastly, we

combined the sub-sequences if they are within a specified range. We downloaded the DNA-binding

domain information for all the TFs from the UniProt database and compared them with the regions

identified before.

CBenchmark with other methods

We compared the performance of DPI-bench with other popular TFBS prediction models such as

DeepBind, DeepSEA, and DNABERT. The details of the training and dataset can be found in

Supplementary Notes of original DNABERT[6] publication.

Adaptation of other models for Qimai

To serve as alternative "Decision Agents" in the Qimai framework, we adapted both DeepSEA and Sei

(the most updated version of DeepSEA with more complex convolutional neural network (CNN)

architecture) models for our dual-input task. The original DNA-only CNN model was modified to accept

a protein identifier as a second input. This identifier is mapped to a 50-dimensional embedding via an

nn.Embedding layer, which is then concatenated with the flattened DNA feature vector before being

passed to fully connected layers for final prediction. Training dataset is Encode3and4, which the same as

that of DPI model (**Supplementary Table 3**). The training hyperparameters are listed in **Supplementary**

Table 4. The performance on Encode3and4 test set for each of the prediction model is summarized in

Supplementary Table 5. Sei performed the best in this test set which included unseen DNA sequences

and seen proteins.

Strategy for predicting unseen proteins with DeepSEA and Sei

To enhance the performance of DeepSEA and Sei, we employed the following strategy for predicting

unseen protein:

1. Prediction via sequence homology. First, we check whether query protein has homologs (e.g. at least

40% sequence identity) in the model's training set using the sequence aligner MMseqs2[15]. If homologs

are found, an ensemble prediction is generated by running the model separately for each of the top N

(e.g., N=3) most similar homologs and then averaging their output logits to produce a final, homology-

informed probability.

2. Prediction via shared TF family. If no homolog is identified, we then check whether any training set

protein belongs to the same TF family as the query using TF family defined in the UniProt database. If so,

an ensemble prediction is generated by averaging the model's output logits for these functionally related

proteins.

3. Generalized baseline prediction. If neither sequence homology nor shared TF family provides a

match, a generalized baseline prediction is made using the average embedding vector of all proteins in

the training set.

Evidence Retriever Module

Direct Motif evidence: For the query protein, known binding motifs are fetched from a local instance of

the CisBP database (downloaded on 2025.04.16). If multiple motifs exist, up to three are selected based

on a priority score favoring directly determined motifs and those from reputable sources like JASPAR[16]

or HOCOMOCO[17]. The fetched Position Weight Matrices (PWMs) are converted to MEME format. The

input DNA sequence is then scanned for these motifs using FIMO from the MEME suite, with a

significance threshold of p-value (default: 1e-4). Results, including hit presence, p-values, scores, and

CisBP motif reliability are summarized.

Indirect Motif evidence: The query protein is used to find potential interacting proteins from the STRING

database[18] for the Homo sapiens, filtered by a minimum interaction score of 700. Up to 50 interactors are

considered. STRING interactors are cross-referenced with the CisBP TF list. For up to 3 known TFs

(prioritized by STRING score), their motifs are fetched from CisBP as described above. The input DNA

sequence is scanned for these indirect motifs using FIMO, and results are summarized similarly to direct

motif evidence.

Prediction model-based evidence: We offered multiple deep learning models for probability prediction,

primarily DPI, Sei, and DeepSEA. It is also possible to choose multiple models at the same time. Each

model might have learned nuancedly different information, allowing for a more comprehensive

interaction prediction.

Reasoning Agent LLM

The LLM receives the "Evidence Package" formatted into a specific prompt. Users can choose their preferred LLM, with options including Google's Gemini-flash, Gemma3, or other powerful open-source models. The results shown here were generated using Gemini-2.0-flash. The core of our method lies in a dynamic prompting strategy which instructs the LLM how to weigh the evidence. For proteins that the computational model has seen before, the LLM would trust the model's prediction more. For unseen proteins which are absent from model's training set, the LLM would prioritize the biological motif evidence instead. Example prompts for unseen and seen proteins are shown in **Supplementary Figure S6**. After the LLM generates its analysis, the system automatically extracts the final prediction label and the reasoning.

Critique Agent & Final Output

The final component of the Qimai framework is a Critique Agent, implemented as a deterministic, rule-based system that assigns a final confidence score (ranging from 0 to 1) to the final prediction. This process provides a quantitative measure of certainty based on the coherence and strength of the underlying evidence. Starting from a baseline confidence value of 0.5, the confidence score is adjusted based on five criteria:

1. *Agreement/Disagreement*: Confidence is increased when the final prediction aligns with the presence of direct or indirect motifs and the predictions of the computational model(s). Conversely, confidence is penalized when the final prediction contradicts these evidence streams, with stronger penalties for contradicting high-quality evidence (e.g., direct motifs from reliable sources).
2. *Evidence Quality*: The magnitude of adjustments is weighted by the quality of the evidence. For example, bonuses are awarded for many motif hits or for hits with exceptionally significant p-values (e.g., <1e-7), while penalties are scaled back if motif scans had no hit or yielded ambiguous results.
3. *Protein Novelty*: The influence of each computational model's prediction is modulated by a novelty factor. If a protein is unseen from the training set, the confidence (either positive or negative) from that computational model is reduced, reflecting a lower trust in its out-of-distribution performance.
4. *Prediction Model Certainty*: Independent of agreement, bonuses are awarded if a computational model's prediction is highly confident (i.e., probability is very close to 0 or 1), as this suggests a clear signal from the model.

5. *LLM Explanation Quality*: The Qimai system performs a check for low-quality LLM outputs. If the
explanation is unusually short, contains repetitive artifacts, or includes leftover template text, it is flagged
as unreliable, and the confidence score is overridden to a near-zero value (e.g., 0.01).

A detailed summary of these heuristic rules and their default values is provided in **Supplementary Table**
6. The final output of Qimai is a triplet: the final prediction label (i.e. 0 for no binding and 1 for binding),
the calculated confidence score, and the LLM's textual explanation.

Implementation Details

The framework is implemented in Python 3, utilizing libraries such as LangGraph for workflow
management, Pandas for data handling, PyTorch for deep learning models, Hugging Face Transformers
for DNABERT model, BioPython for sequence manipulation, Requests for API calls (STRING DB),
Google Generative AI SDK for Gemini, and DuckDB for local embedding databases. FIMO (MEME
suite) is used as an external tool for motif scanning. Inference time varies across different LLM backends
and prediction models with an average time of 20 seconds.

Benchmark Strategy and Performance Evaluation

We evaluated Qimai's performance and generalization capabilities through a two-stage process: first, a
rigorous internal cross-validation to assess robustness on held-out proteins from a single dataset of
Encode3and4, and second, an external validation on a distinct dataset ChIP_690 enriched with novel
proteins.

Internal Robustness Assessment via Repeated Random Subsampling

To validate the robustness of our findings and ensure that Qimai's generalization is not an artifact of a
single train-test split, we performed a repeated random subsampling validation using Encode3and4
dataset. From the total pool of 844 proteins, we generated five independent splits. For each split, we
randomly sampled 800 proteins to define the 'seen' training set for the underlying deep learning models.
The remaining 44 proteins were held out as the 'unseen' test set for that specific partition.

To identify novel proteins in each held-out set, we performed a sequence-based analysis for each of the
five splits. A reference sequence database was constructed from the 800-protein training set of that split.
Each of the 44 held-out proteins was then queried against this database using MMseqs2. A protein was

classified as "novel" for that split if its best hit failed to meet stringent homology criteria, defined as having a sequence identity of less than 30%, a bitscore below 50, or an E-value greater than 0.001. This process was repeated for all five splits, resulting in five distinct sets of novel proteins (ranging from 6 to 12 proteins per split) on which performance was specifically assessed (**Supplementary Figure S4A**).

External Validation on a Novel Protein-Enriched Dataset

To further challenge the system's generalization capabilities, we performed an external validation on the ChIP_690 dataset, which contains 78 "unseen" proteins that were not included in the Encode3and4 dataset. We analyzed whether these 78 proteins have homologs in the full 844-protein Encode3and4 training set using MMseqs2. A protein was classified as "novel" if its best hit failed to meet stringent homology criteria, defined as having a sequence identity of less than 30%, a bitscore below 50, or an E-value greater than 0.001. The ChIP_690 contains 51 novel proteins out of the 78 unseen proteins (65%).

Evaluation and Ablation Setup

We evaluated the performance of the full Qimai system against the standalone predictive models (DPI, Sei, and DeepSEA) across two validation schemes. For our internal 5-fold cross-validation, we generated a balanced test set of 1000 examples involving 44 held-out proteins for each partition. For the external dataset assessment, we evaluated performance on a balanced set of 500 examples, which included all interactions involving the 78 previously unseen proteins. This external validation was repeated 10 times using 10 different random seeds, and the averaged performance with standard variation is reported.

Furthermore, to probe the contribution of different motif evidence streams, we conducted ablation studies where indirect motif information ("Qimai (w/o indirect)") or direct motif information ("Qimai (w/o direct)") was removed from the system. The system's confidence scores were interpreted as probabilities of positive interaction; for negative interactions, the probability was taken as 1 minus the confidence score. These probabilities were used to generate Receiver Operating Characteristic (ROC) and Precision-Recall (PR) curves. A default probability threshold of 0.5 was used to derive binary classifications from the standalone predictive models, while the system's binary prediction was parsed directly from the LLM's response.

Evaluating the LLM Agent against a state-of-the-art Classifier

To rigorously evaluate the contribution of the LLM's reasoning capabilities, we compared the performance of our LLM Agent against a state-of-the-art ensemble classifier. All evaluations were

performed on a hold-out test set of 5,000 protein-DNA interaction pairs, each involving proteins that were
unseen during the training of any underlying prediction models.

We chose LightGBM, a state-of-the-art gradient boosting model for comparison. The model was trained
on a balanced dataset of 10,000 protein-DNA pairs (7,500 for training, 2,500 for internal validation and
early stopping). To ensure a fair comparison, the baseline was provided with all the same structured
evidence available to the LLM Agent. We collected a comprehensive set of 16 features designed to
capture the nuances of the available evidence (**Supplementary Table 10**). These features were organized
into three categories:

1. *Direct Motif Evidence*: Features describing the protein's own binding motifs, including the number of
significant hits, the $-log10(p\_value)$ of the best hit to represent statistical significance, and an ordinal
score for the reliability of the motif source.
2. *Indirect Motif Evidence*: Features derived from the protein's interaction partners, such as the number of
interacting transcription factors, the maximum STRING-DB interaction score, and the $-log10(p -$
$value)$ of the best indirect hit.
3. *Deep Learning Model Predictions*: Features summarizing the outputs of the underlying deep learning
models, including the raw binding probability, and a binary flag indicating if the protein was novel to that
model's training set.

Hyperparameters for the LightGBM model were selected to ensure robust generalization. We used a
standard learning_rate of 0.05 and a num_leaves of 31 to balance model complexity and performance.
The most critical hyperparameter, the number of boosting rounds (n_estimators), was determined
automatically using early stopping with a patience of 10 rounds. This technique prevents overfitting by
terminating training when the AUC score on the internal validation set ceased to improve, ensuring the
model converged at its optimal iteration. The LightGBM model converged at an optimal iteration of 172.

The LightGBM model automatically performed feature selection, ultimately utilizing the 14 most
informative features to make its predictions. Feature importances in LightGBM were calculated as the
total gain, representing the cumulative reduction in loss contributed by each feature across all trees in the
ensemble. Analysis of the trained model's feature importances confirmed its ability to identify salient
predictors (**Supplementary Table 10**). The final trained baseline achieved an AUC-ROC of 0.817 on its
internal 2,500-sample test set, confirming it as a well-trained strong classifier. We assessed the
performance of both the finalized LLM Agent and the trained LightGBM baseline on the 5,000 unseen

test examples. Performance was measured using five metrics: Accuracy, F1-Score, Matthews Correlation

Coefficient (MCC), AUC-ROC, and AUC-PR.

Evaluation on Qimai's explanations

To systematically quantify the reasoning quality of the Qimai agent's explanations, we implemented an

'LLM-as-a-Judge' framework. Three independent judge LLMs (open-source models phi4, deepseek-r1,

qwen3 were used) evaluated each of the 500 explanations against its corresponding evidence package.

Each judge generated scores on a 1-5 scale for the across five dimensions: Factual Accuracy, Evidence

Coverage, Conflict Resolution, Clarity and Conciseness, and Overall Quality. Scores were collected in a

structured format for quantitative analysis.

Supplementary Tables

Supplementary Table 1: ChIP-seq experiment statistics.

Dataset	Experiments	TFs
ChIP_690	690	158
Encode3and4	1877	844

Supplementary Table 2: Data statistics for DPI model used for benchmark.

Split	Total pairs	Positive pairs	Negative pairs	# of proteins	# of DNAs
Training	43,432	21,716	21,716	158	43,432
Validation	10,858	5,429	5,429	158	10,858
Test	21,546	10,773	10,773	158	21,546

Supplementary Table 3: Data statistics for DPI model used for production run.

Split	Total pairs	Positive pairs	Negative pairs	# of proteins	# of DNAs
Training	32,318,586	16,159,293	16,159,293	844	724,514
Validation	1,409,192	704,596	704,596	844	34,904
Test	2,567,990	1,283,995	1,283,995	844	65,180

Supplementary Table 4: Training hyperparameters for prediction models.

Model	DPI-bench	DPI	DeepSEA	Sei
max_dna_seq	512	512	512	512
max_protein_seq	512	768	-	-
protein_emb_dim	384	384	50	50
hid_dim	240	240	-	-
n_layers	6	2	-	-
n_heads	12	6	-	-
batch_size	16	128	64	64
epochs	50	2	10	10
learning_rate	0.01	0.05	0.001	0.001

Supplementary Table 5: Prediction model performance on Encode3and4 test set.

Model	Accuracy	F1 Score	MCC	Recall	Precision	Specificity	AUC-ROC	AUC-PR
DPI	0.820	0.822	0.640	0.837	0.812	0.803	0.900	0.887
DeepSEA	0.765	0.776	0.533	0.814	0.742	0.716	0.843	0.819
Sei	0.839	0.843	0.680	0.861	0.825	0.818	0.920	0.913

Supplementary Table 6: Heuristic rules and parameters for confidence score calculation.

Category	Condition	Description	Seen protein	Unseen protein	Code variable name
Baseline	Initial value	Sets the initial score before adjustment	0.50		CONFIDENCE_BASELINE
	Label=1 & Found	Bonus for agreement	+0.10	+0.30	DIRECT_MATCH_BOOST

Direct Motif	… & Reliable	Additional bonus for high-quality evidence	+0.05	+0.10	DIRECT_RELIABLE_MATCH_EXTRA
	Label=1 & Not Found	Penalty for missing evidence when predicting positive	-0.10	-0.20	DIRECT_MISSING_PENALTY
	Label=0 & Found	Penalty for contradiction	-0.20	-0.35	DIRECT_MISMATCH_PENALTY
	Label=0 & Not Found	Bonus for consistent absence of evidence	+0.05	+0.15	DIRECT_ABSENCE_BOOST
Indirect Motif	Label=1 & Found	Smaller bonus for indirect agreement	+0.10	+0.20	INDIRECT_MATCH_BOOST
	Label=1 & Not Found	Smaller penalty for missing indirect evidence	-0.05	-0.10	INDIRECT_MISSING_PENALTY
	Label=0 & Found	Smaller penalty for indirect contradiction	-0.15	-0.25	INDIRECT_MISMATCH_PENALTY
	Label=0 & Not Found	Smaller bonus for consistent absence	+0.05	+0.10	INDIRECT_ABSENCE_BOOST
Evidence Quality	Num. Hits > 1	Bonus per hit, up to a max value	+0.02/hit	+0.03/hit	...NUM_HITS_SCALE_FACTOR
	p-value is very low	Bonus for highly significant motif hits	+0.07	+0.10	...LOW_PVALUE_BONUS
	(Threshold)	p-value threshold for the above bonus	< 1e-7	< 1e-8	...LOW_PVALUE_THRESHOLD
Model Prediction	Vote agrees w/ model	Bonus for model agreement	+0.30	+0.10	TRANSFORMER_MATCH_BOOST
	… & Confident	Add'l bonus for high-confidence agreement (prob > 0.8 or < 0.2)	+0.10	+0.05	TRANSFORMER_CONFIDENT_EXTRA
	Vote disagrees	Penalty for model disagreement	-0.25	-0.15	TRANSFORMER_MISMATCH_PENALTY
	… & Confident	Add'l penalty for high-confidence disagreement	-0.15	-0.05	...CONFIDENT_MISMATCH_EXTRA
Multi-model	2nd+ model agrees	Diminishing bonus for subsequent agreeing models	0.3x of base bonus		SUBSEQUENT_MODEL_AGREEMENT_FACTOR
	2nd+ model disagrees	Diminishing penalty for subsequent disagreeing models	0.3x of base penalty		...MISMATCH_PENALTY_FACTOR
	Model/motif conflict	Amplifies penalty if >=2 models agree with LLM but contradict motifs	1.2x of base penalty		MOTIF_CONFLICT_AMPLIFICATION_FACTOR
Novelty	Protein is novel	Multiplicative factor to reduce impact of a model's adjustment	0.5x	0.7x	...CONFIDENT_MISMATCH_EXTRA
Quality control	LLM explanation fails	If explanation is too short, repetitive or has template text	Score overridden to 0.01		Hard-coded logic

704 **Supplementary Table 7**: Performance summary on 78 unseen proteins with error bars representing the
705 standard deviation over ten runs. Each run evaluated on 500 randomly sampled pairs.

	Accuracy	F1 Score	MCC	Recall	Precision	AUC-ROC	AUC-PR
Qimai	**0.632 ± 0.020**	**0.552 ± 0.030**	**0.308 ± 0.032**	0.435 ± 0.034	0.757 ± 0.017	**0.682 ± 0.026**	**0.701 ± 0.024**
Qimai (w/o indirect)	0.608 ± 0.023	0.494 ± 0.030	0.285 ± 0.034	0.363 ± 0.031	**0.777 ± 0.026**	0.663 ± 0.020	0.672 ± 0.024
Qimai (w/o direct)	0.542 ± 0.028	0.354 ± 0.037	0.154 ± 0.036	0.239 ± 0.032	0.689 ± 0.025	0.610 ± 0.020	0.620 ± 0.022
DPI	0.516 ± 0.016	0.322 ± 0.026	0.090 ± 0.035	0.218 ± 0.024	0.624 ± 0.045	0.590 ± 0.024	0.596 ± 0.025
DeepSEA	0.500 ± 0.021	0.122 ± 0.030	0.084 ± 0.068	0.067 ± 0.017	0.705± 0.147	0.471 ± 0.024	0.531 ± 0.032
Sei	0.414 ± 0.028	0.551 ± 0.046	-0.260 ± 0.035	**0.701 ± 0.082**	0.457 ± 0.028	0.418 ± 0.008	0.498 ± 0.019

707 **Supplementary Table 8**: Performance summary on 51 novel unseen proteins with error bars representing
708 the standard deviation over ten runs.

	Accuracy	F1 Score	MCC	Recall	Precision	AUC-ROC	AUC-PR
Qimai	**0.653 ± 0.020**	0.479 ± 0.038	**0.314 ± 0.042**	0.353 ± 0.037	0.759 ± 0.039	**0.683 ± 0.035**	**0.650 ± 0.042**
Qimai (w/o indirect)	0.621 ± 0.029	0.359 ± 0.061	0.273 ± 0.060	0.232 ± 0.048	**0.812 ± 0.071**	0.668 ± 0.034	0.636 ± 0.041
Qimai (w/o direct)	0.587 ± 0.030	0.337 ± 0.051	0.160 ± 0.053	0.231 ± 0.043	0.637 ± 0.056	0.628 ± 0.024	0.569 ± 0.036
DPI	0.570 ± 0.022	0.330 ± 0.044	0.122 ± 0.045	0.230 ± 0.038	0.593 ± 0.049	0.624 ± 0.022	0.569 ± 0.035
DeepSEA	0.585 ± 0.025	0.222 ± 0.049	0.166 ± 0.081	0.131 ± 0.030	0.731 ± 0.136	0.578 ± 0.051	0.536 ± 0.060
Sei	0.417 ± 0.034	**0.580 ± 0.030**	-0.176 ± 0.099	**0.890 ± 0.044**	0.431 ± 0.025	0.489 ± 0.018	0.485 ± 0.028

709
710

711   **Supplementary Table 9**: Performance summary on 45 novel proteins without direct motifs with error
712   bars representing the standard deviation over ten runs.

	Accuracy	F1 Score	MCC	Recall	Precision	AUC-ROC	AUC-PR
Qimai	0.624 ± 0.021	0.325 ± 0.042	0.197 ± 0.047	0.219 ± 0.033	**0.665 ± 0.065**	0.661 ± 0.034	0.563 ± 0.043
Qimai (w/o direct)	**0.631 ± 0.029**	**0.378 ± 0.043**	**0.211 ± 0.053**	**0.269 ± 0.038**	0.647 ± 0.061	**0.686 ± 0.029**	**0.584 ± 0.043**
DPI	0.599 ± 0.036	0.253 ± 0.053	0.140 ± 0.070	0.160 ± 0.037	0.628 ± 0.094	0.677 ± 0.034	0.580 ± 0.043
Qimai (w/o indirect)	0.587 ± 0.032	0.085 ± 0.038	0.076 ± 0.070	0.046 ± 0.021	0.625 ± 0.224	0.645 ± 0.034	0.535 ± 0.045
DeepSEA	0.585 ± 0.025	0.000 ± 0.000	0.000 ± 0.000	0.000 ± 0.000	0.000 ± 0.000	0.509 ± 0.039	0.445 ± 0.037
Sei	0.583 ± 0.026	0.004 ± 0.006	0.013 ± 0.024	0.002 ± 0.003	0.171 ± 0.303	0.430 ± 0.036	0.394 ± 0.045

Supplementary Table 10: Features provided to the baseline LightGBM classifier.

Category	Feature Name	Description	Feature importance learned by LightGBMl	Used by final model?
Direct Motif Evidence	direct_num_hits	Number of significant hits for the protein's own motifs.	165	**Yes**
	direct_lowest_pvalue_log	The -log10 transformed p-value of the best direct motif hit.	505	**Yes**
	direct_reliability_ordinal	Ordinal score for the reliability of the motif source (3=High, direct motif, 2=Moderate, inferred motif, 1=no known motif).	58	**Yes**
	direct_num_motifs_total_found	Total number of known motifs for the protein in the CisBP database.	526	**Yes**
	direct_num_motifs_selected	Number of top motifs selected for scanning after quality filtering.	10	**Yes**
	direct_num_direct_status_motifs	Count of selected motifs that were experimentally determined ("Direct").	117	**Yes**
	direct_num_inferred_status_motifs	Count of selected motifs that were computationally inferred ("Inferred").	36	**Yes**
Indirect Motif Evidence	indirect_num_hits	Number of significant hits from motifs of interacting proteins.	54	**Yes**
	indirect_lowest_pvalue_log	The -log10 transformed p-value of the best indirect motif hit.	257	**Yes**
	indirect_max_string_score	The highest STRING DB score among analyzed protein interactors.	790	**Yes**
	indirect_num_string_interactors	Total number of protein interactors found in the STRING database.	654	**Yes**
	indirect_num_tf_interactors	Count of interactors that are known transcription factors.	431	**Yes**
	indirect_num_tfs_analyzed	Number of top TF interactors whose motifs were scanned.	3	No
DL Model Prediction	model_dpi_prob	Binding probability from the DPI Transformer model.	1356	**Yes**
	model_dpi_is_known	Binary flag: was the protein known to the DPI model?	198	**Yes**
	model_dpi_run_success	Binary flag: did the DPI model run successfully?	0	No

Supplementary Table 11: Other variations of heuristic parameters for confidence score calculation.

Category	Condition	Description	Default	V1	V2	V3	Code variable name
Baseline	Initial value	Sets the initial score before adjustment	0.50	0.50	0.45	0.55	CONFIDENCE_BASELINE
Direct Motif	Label=1 & Found	Bonus for agreement	+0.30	+0.25	+0.20	+0.28	DIRECT_MATCH_BOOST
	… & Reliable	Additional bonus for high-quality evidence	+0.10	+0.10	+0.08	+0.12	DIRECT_RELIABLE_MATCH_EXTRA
	Label=1 & Not Found	Penalty for missing evidence when predicting positive	-0.20	-0.15	-0.18	-0.10	DIRECT_MISSING_PENALTY
	Label=0 & Found	Penalty for contradiction	-0.35	-0.30	-0.35	-0.25	DIRECT_MISMATCH_PENALTY
	Label=0 & Not Found	Bonus for consistent absence of evidence	+0.15	+0.10	+0.08	+0.15	DIRECT_ABSENCE_BOOST
Indirect Motif	Label=1 & Found	Smaller bonus for indirect agreement	+0.20	+0.10	+0.08	+0.15	INDIRECT_MATCH_BOOST
	Label=1 & Not Found	Smaller penalty for missing indirect evidence	-0.10	-0.05	-0.07	-0.03	INDIRECT_MISSING_PENALTY
	Label=0 & Found	Smaller penalty for indirect contradiction	-0.25	-0.15	-0.12	-0.10	INDIRECT_MISMATCH_PENALTY
	Label=0 & Not Found	Smaller bonus for consistent absence	+0.10	+0.05	+0.04	+0.08	INDIRECT_ABSENCE_BOOST
Evidence Quality	Num. Hits > 1	Bonus per hit, up to a max value	+0.03/hit	+0.02/hit	+0.015/hit	+0.025/hit	...NUM_HITS_SCALE_FACTOR
	p-value is very low	Bonus for highly significant motif hits	+0.10	+0.07	+0.05	+0.08	...LOW_PVALUE_BONUS
	(Threshold)	p-value threshold for the above bonus	< 1e-8	< 1e-7	< 1e-8	< 5e-7	...LOW_PVALUE_THRESHOLD
Model Prediction	Vote agrees w/ model	Bonus for model agreement	+0.10	+0.15	+0.12	+0.20	TRANSFORMER_MATCH_BOOST
	… & Confident	Add'l bonus for high-confidence agreement (prob > 0.8 or < 0.2)	+0.05	+0.10	+0.08	+0.12	TRANSFORMER_CONFIDENT_EXTRA
	Vote disagrees	Penalty for model disagreement	-0.15	-0.20	-0.18	-0.15	TRANSFORMER_MISMATCH_PENALTY
	… & Confident	Add'l penalty for high-confidence disagreement	-0.05	-0.10	-0.12	-0.08	...CONFIDENT_MISMATCH_EXTRA
Multi-model	2nd+ model agrees	Diminishing bonus for subsequent agreeing models	0.3x of base bonus				SUBSEQUENT_MODEL_AGREEMENT_FACTOR
	2nd+ model disagrees	Diminishing penalty for subsequent disagreeing models	0.3x of base penalty				...MISMATCH_PENALTY_FACTOR
	Model/motif conflict	Amplifies penalty if >=2 models agree	1.2x of base penalty				MOTIF_CONFLICT_AMPLIFICATION_FACTOR

		with LLM but contradict motifs					
Novelty	Protein is novel	Multiplicative factor to reduce impact of a model's adjustment	0.7x	0.6x	0.5x	0.8x	...CONFIDENT_MISMATCH_EXTRA
Quality control	LLM explanation fails	If explanation is too short, repetitive or has template text		Score overridden to 0.01			Hard-coded logic

Supplementary Table 12: Performance summary on 44 unseen proteins with error bars representing the standard deviation over five splits. Each run evaluated on 1000 randomly sampled pairs.

	Accuracy	F1 Score	MCC	Recall	Precision	AUC-ROC	AUC-PR
Qimai	**0.565 ± 0.017**	0.537 ± 0.012	**0.178 ± 0.018**	0.440 ± 0.010	0.691 ± 0.031	0.632 ± 0.028	**0.701 ± 0.036**
Qimai (w/o indirect)	0.548 ± 0.026	0.501 ± 0.024	0.155 ± 0.032	0.396 ± 0.028	0.683 ± 0.027	0.618 ± 0.032	0.685 ± 0.036
Qimai (w/o direct)	0.516 ± 0.023	0.368 ± 0.038	0.156 ± 0.039	0.247 ± 0.028	**0.730 ± 0.065**	**0.643 ± 0.029**	0.693 ± 0.037
DPI	0.550 ± 0.042	0.399 ± 0.091	0.158 ± 0.088	0.287 ± 0.079	0.673 ± 0.091	0.612 ± 0.048	0.653 ± 0.065
DeepSEA	0.462 ± 0.042	0.152 ± 0.118	0.079 ± 0.107	0.089 ± 0.071	0.577 ± 0.368	0.528 ± 0.037	0.611 ± 0.057
Sei	0.562 ± 0.042	**0.696 ± 0.040**	0.018 ± 0.070	**0.878 ± 0.037**	0.577 ± 0.045	0.525 ± 0.021	0.601 ± 0.044

Supplementary Table 13: Performance summary on 6-12 novel held-out proteins with error bars representing the standard deviation over five splits.

	Accuracy	F1 Score	MCC	Recall	Precision	AUC-ROC	AUC-PR
Qimai	0.693 ± 0.046	0.497 ± 0.234	0.272 ± 0.223	0.444 ± 0.230	0.577 ± 0.255	**0.633 ± 0.160**	**0.593 ± 0.231**
Qimai (w/o indirect)	**0.700 ± 0.062**	0.515 ± 0.242	**0.290 ± 0.245**	0.464 ± 0.230	**0.585 ± 0.266**	0.625 ± 0.159	0.573 ± 0.219
Qimai (w/o direct)	0.643 ± 0.065	0.348 ± 0.240	0.137 ± 0.236	0.277 ± 0.203	0.501 ± 0.295	0.588 ± 0.128	0.497 ± 0.200
DPI	0.620 ± 0.090	0.343 ± 0.200	0.114 ± 0.237	0.271 ± 0.162	0.498 ± 0.296	0.575 ± 0.113	0.502 ± 0.217
DeepSEA	0.608 ± 0.118	0.041 ± 0.092	-0.020 ± 0.045	0.027 ± 0.061	0.084 ± 0.189	0.555 ± 0.082	0.445 ± 0.077
Sei	0.417 ± 0.115	**0.560 ± 0.117**	0.104 ± 0.068	**0.985 ± 0.018**	0.399 ± 0.116	0.514 ± 0.034	0.398 ± 0.106

Acknowledgement

This work is partially supported by NIH (R01HG009626 to WW).

Code availability

Source code used to generate all results shown in this paper is deposited and publicly available at https://github.com/Wang-lab-UCSD/DPI-agent.

Supplementary Figures

Supplemental Figure 1: Framework details.

(A) Evidence Retriever workflow. This module gathers three types of evidence: 1. Direct Motif evidence (fetching the query protein's motifs from CisBP database and scanning the DNA); 2. Indirect Motif evidence (identifying protein interactors via STRING database, fetching their motifs, and scanning the DNA); 3. Computational Model Evidence (predicting interaction using a pre-trained model like the DPI transformer detailed in panel B, DeepSEA, or Sei).

(B) Details in each DPI module. Encoder includes a linear transformation and the basic building block including two sub-layers: the multi-head self-attention layer and fully connected feed-forward layer. Decoder module has similar architecture as encoder, except it calculates the cross-attention between DNA and protein instead of self-attention. Prediction module includes linear layer with ReLU activation.

(C) Self-attention weights of protein sequences. The regions with high attention weights extracted from encoder module are highlighted in yellow. True DNA-binding domains (DBDs) are highlighted in green. Yellow and green regions are overlapped.

(D) Performance of two DPI-bench models, one utilizing both protein and DNA information (gray) and the other using DNA information only (purple). The two models showed similar performance. "ns" stands for not significant difference for t-test.

Suppl. Fig. 1 DPI model performance

A Evidence retriever workflow

B Details in each DPI module

C Protein self-attention weight visualization

D Performance of two DPI-bench models

Supplemental Figure 2: Qimai framework superior performance in external ChIP_690 dataset.

(A) Performance on the seen protein in ChIP_690 dataset. The full Qimai system, incorporating the DPI model prediction and all motif evidence, is compared against standalone deep learning models (DPI, Sei, DeepSEA) on unseen DNA sequences with known proteins. The standalone Sei model shows the strongest performance, while the Qimai system is highly competitive.

(B) Calibration plot for the final System and standalone DPI model scores. This plot compares the mean predicted probability of a positive interaction (x-axis) against the empirical fraction of actual positive interaction (y-axis). The System (blue) is well-calibrated, closely tracking the ideal diagonal reference line. In contrast, the DPI model (orange) is consistently over-confident. The background histogram displays the distribution of the System's prediction scores, highlighting that its calibration is most effective in the highly populated low-confidence region.

(C) Similarity distribution of 78 unseen proteins. "Novel Proteins" represent proteins from the unseen set that showed no significant sequence similarity to any protein in the training set, i.e. <30% sequence identity, a bitscore below 50, or an E-value greater than 0.001. "Ambiguous Proteins" are those unseen proteins that didn't meet all the stringent criteria. "Similar Proteins" are those unseen proteins that did have at least one significant sequence match within the training set. The annotation is used throughout the paper.

(D) Family distribution of 51 novel proteins. Families with red boxes are the novel families which are absent from training data. Almost half of the novel proteins also belong to the novel protein families (23/51).

(E) The LLM Agent's context-aware reasoning resolves conflicting evidence where a state-of-the-art ensemble classifier fails. This case study of protein AP2A illustrates a scenario with contradictory inputs: strong, high-reliability direct motif evidence (4 hits) versus a low-probability deep learning model prediction (0.216). The baseline classifier, constrained by its fixed, learned feature weights where model probability has a higher learned importance, is misled by the low score and makes an incorrect prediction. In contrast, the LLM Agent dynamically reasons about the evidence quality, explicitly prioritizing the strong motif data over the single computational score to arrive at the correct classification.

(F) LLM-as-judge evaluation of explanation quality. A radar chart displaying the assessment of Qimai's generated explanations by an LLM-as-judge. The explanations received near-perfect scores (out of 5) across five criteria, highlighting their factual accuracy, clarity, and effectiveness in resolving conflicting evidence.

Suppl. Fig. 2 Qimai superior performance in external dataset

A Performance on seen proteins from ChIP_690 dataset

B Calibration plot for Qimai system

C Similarity distribution of 78 unseen proteins

D Family distribution of 51 novel proteins

E Case study of AP2A showing the strength of LLM agent

F LLM-as-judge evaluation on explanation quality

Supplemental Figure 3: Evaluation of Qimai framework robustness in external ChIP_690 dataset.

(A) Qimai's confidence score is robust to variations in heuristic parameter sets. Left panel shows key metrics for the system's predictions across four different heuristic configurations (**Supplementary Table 11**). The results demonstrate high and stable performance, with minimal variation across all test configurations. Error bars representing the standard deviation over ten runs. Each run was evaluated on 500 randomly sampled pairs. Right panel is the corresponding calibration curves. The close alignment of all four colored lines to this diagonal indicates that the confidence score remains a reliable and well-calibrated measure of prediction accuracy, regardless of the underlying heuristic model.

(B) Comparison across different LLM reasoning agents. Qimai's performance was evaluated using gemini-1.5-flash, gemini-2.0-flash, and the open-source gemma-3-27b-it on both the seen (left) and "unseen" (right) proteins in ChIP_690 dataset. Performance is shown to be robust and highly comparable across all LLMs, particularly on the challenging "unseen" dataset, demonstrating the framework's consistency. Error bars in all panels represent the standard deviation over ten runs. Each run was evaluated on 500 randomly sampled pairs.

(C) Comparison across different combinations of prediction models. Qimai's performance was evaluated using three different combinations of prediction models. On the seen proteins in external dataset (left), integrating predictions from two models ("DPI + Sei") yields the highest performance. In contrast, on the unseen proteins (right), providing only the single best-generalizing model (DPI) is the most effective strategy. Error bars in all panels represent the standard deviation over ten runs. Each run was evaluated on 500 randomly sampled pairs.

Suppl. Fig. 3 Evaluation of Qimai framework robustness in external dataset

A **Qimai is robust across heuristic parameters for confidence score calculation**

B **Comparison across different LLMs**

C **Comparison across different combinations of prediction models**

Supplemental Figure 4: Internal Cross-Validation of Qimai performance.

(A) Similarity distribution of unseen proteins vs training set for each of the five splits. "Novel

Proteins" represent proteins from the unseen set that showed no significant sequence similarity to any

protein in the training set, i.e. <30% sequence identity. "Similar Proteins" are those unseen proteins that

had at least one sequence match within the training set.

(B) Performance across five random splits on novel proteins. A comparison of the full Qimai System

against standalone deep learning modles (DPI, Sei, DeepSEA) and its ablated version ("Qimai (w/o

indirect)", "Qimai (w/o direct)") across five random splits. Results are averaged over five random splits

with error bars showing standard deviation.

Suppl. Fig. 4 Internal Cross-Validation of Qimai Performance

A Similarity distribution of unseen proteins vs training set

B 5-fold cross validation performance on novel held-out proteins

Supplemental Figure 5: Representative case studies across diverse evidence scenarios. ChIP-seq binding peaks were used as ground truth. Genome browser view at the bottom shows the true ChIP-seq binding peaks along with histone marks and DNase signal.

(A) "All Signals Green" Case. The TF SPI1 shows strong direct motif evidence, supportive indirect evidence, and a high DPI model score (0.7190), leading to a confident positive prediction.

(B) "Correct Rejection" Case. The TF IRF4 lacks both direct and indirect motif evidence, which, combined with a low DPI model score (0.1890), results in a confident negative prediction.

(C) "Conflict Resolution" (low model vs. positive motifs). For the TF BATF, strong direct and indirect motif evidence strongly suggests an interaction, prompting Qimai to override the conflicting low DPI model prediction (0.0255).

(D) "Conflict Resolution" (low model vs. positive direct motif). The TF ZBTB7A only has direct motif evidence. Qimai prioritizes the presence of direct binding over the low DPI model score (0.0263) to predict an interaction.

(E) "Conflict Resolution" (low model vs. positive indirect motif). For TF GATA1, weak indirect evidence from its partner KLF1 is insufficient to overcome the lack of direct motif evidence and a low DPI model score (0.0540), leading to a negative prediction.

(F) "Decisive Indirect Evidence" Case. For MTA3, a component of a chromatin remodeling complex, there is no known motif documented in CisBP (thus direct evidence is absent) and the model score is uncertain (0.5262). However, moderately strong indirect evidence for its partner MBD3 leads Qimai to predict an interaction.

(G) "Decisive Indirect Evidence" Case. The TF CBX3 has no known motif in CisBP and has a low model score (0.1668). Qimai correctly predicts an interaction by prioritizing the indirect evidence from E2F6, a known binding partner.

Suppl. Fig. 5 Other DNA-protein interaction examples

A "All Signals Green" Confirmatory Case

Input

Input Protein: SPI1

Input DNA:

CCCGCCCAGTTACTAGCACCCTGCCCCAGCCTATTTATACCTGGCTCTTCGCAAACTTTGTCCTCCATTCTTCTCAATATGCTT
GTACTAGAAAACTACCTTCCCTCCTTTTCTTCCTGCTGTTCTCGCTTCATCCATTAAATAGTTTTTTCCCTATCCTAAATTTTAACA
ATTCTTTACGATAAGACACATGCGAAGATCGCAAGCCCTGCCCATTGACAAGACTTCCTGGTTCTACCCCCGCCGCCGTTCCA
CTTCCGCTGACGTCGGAGGTCAGAGGTTACAGACAAGATGTCGGCGGATGGTAGCTTCGAGCCCTTGCGGAGAGGAGCATC
TCTGTGACAGAAGCTTGTCGACGGCGGCTTCTAGGAGCTAGTCGAAGGAGCGAGGTTGAGGCGGGCAGCGACCCGTCAGGT
CGCTCACCTGGGCACCGGCCAGCTGCGAGACGTGACTTGGGGACCGCAGGGGAGTGGAGAGTGTGAGGTGCCAAAGACTA
GTAATGCCCCGTATCC

Qimai

- **Prediction label: 1**

- **Confidence score: 1**

- **Explanation:**

  1. **Direct Evidence**: **The direct motif evidence is strong**. The protein has known motifs (High Reliability). A CisBP search found 3 direct motifs with high reliability. DNA scan results show hits for two of these motifs (M08402_3.00 and M10170_3.00) with significant p-values (p<=1.0e-04). This provides strong evidence for a direct interaction.

  2. **Indirect Evidence**: **The indirect motif evidence is also supportive.** A STRING DB search found 50 interactors, and the top 3 TFs (IRF8, IRF4, GATA1) were analyzed. DNA scan results show a hit for IRF8's motif (M10359_3.00) with a significant p-value (p<=1.0e-04). This further supports the possibility of an interaction.

  3. **Prediction Model Evidence**: **The DPI prediction model gives a probability of 0.7190, suggesting an interaction.** However, the protein is novel (absent from the DPI known set), and the model confidence is moderate. This means the model's prediction is less certain than it would be for a known protein.

  4. **Synthesis (Prioritizing Motif Evidence):** I am prioritizing motif evidence, especially direct motif evidence. The direct motif evidence is strong, with multiple high-quality hits in the DNA sequence. The indirect motif evidence also supports an interaction. While the DPI prediction model suggests an interaction with moderate confidence, the strong direct motif evidence takes precedence. The presence of multiple direct motif hits with good p-values strongly suggests that SPI1 interacts with this DNA sequence.

  5. **Conclusion**: Based on the strong direct motif evidence, I predict that an interaction occurs.

Regulatory landscape of query DNA sequence

Suppl. Fig. 5 Other DNA-protein interaction examples

B   **"Correct Rejection" Case (True Negative)**

Input

Input Protein: IRF4

Input DNA:

CCTCTCTTTTGGACCCAATCTCCGGTTCTCATTTCACTTGGAAAGTACCTGCTTAAAAGTTTACTTTCTTGTTGCTCAATTTAGAC
CATTTATTTTCCTTTCAGCTCACCAGAAAGCAGCATGATGGGTGACCAAGCTAGCGATCATGCAAAGCAGAAGTCATAGAGTAA
AAATGGTCAATGCGTTTGAAAAGTGTTTATTTGAGTTTCCCAAAAGTCAGGTTAACATGCAACAGCAAACTACAGGTGGTACCA
ACCATATCTTTTTGGGAAATTAGTGAGGCCCCAGGATTGAGGGCAAACTGAACAAGTTGGGTGGGAAATCAAGGGCCAGTTG
GCAACCTAGTTGCAGGCAGGGACTGAGGACGATGACCTGGTTAGCCTTAGAAAGCTAAGCGTGTGATACAATCAATACAGAC
CATCACAGGTCAAGTGTAGAGTAAACATGGTTAGCTCTCCCAGGCACACAATCAACTGCCCAGAGCTGTTCAACAATATGTATC
TCTCCAATAA

Qimai

- **Prediction label: 0**

- **Confidence score: 0.855**

- **Explanation:**

  1. **Direct Evidence:** IRF4 has known motifs (High Reliability). However, **no significant direct motif hits were found** in the provided DNA sequence. This suggests a lack of direct binding sites for IRF4 in this specific DNA. The direct motif evidence is therefore weak, indicating no interaction.

  2. **Indirect Evidence:** An indirect search was performed, analyzing the motifs of 3 interacting TFs (SPI1, BATF, STAT6). **No significant indirect motif hits were found in the DNA sequence.** This suggests that IRF4 is unlikely to be recruited to this DNA region through interactions with these specific TFs. The indirect motif evidence is also weak, indicating no interaction.

  3. **Prediction Model Evidence:** **The DPI prediction model gives a probability of 0.1890, which is low.** The confidence is moderate, but the protein is novel (not in the training set), which reduces the reliability of the prediction. This model suggests no interaction.

  4. **Synthesis (Prioritizing Motif Evidence):**
  - Direct Motif Evidence: No hits. Strong negative indicator.
  - Indirect Motif Evidence: No hits. Weak negative indicator.
  - DPI Prediction: Low probability (0.1890), moderate confidence, but less reliable due to protein novelty. Suggests no interaction. Prioritizing motif evidence, the absence of both direct and indirect motif hits strongly suggests that IRF4 does not interact with this DNA sequence. The DPI prediction aligns with this conclusion, although it is given less weight due to the protein's novelty and the relatively low confidence. The absence of motif hits is a stronger indicator than the DPI prediction in this case.

  5. **Conclusion:** Based on the prioritized synthesis of evidence, particularly the lack of direct and indirect motif hits, the final prediction is that no interaction occurs.

Regulatory landscape of query DNA sequence

Suppl. Fig. 5 Other DNA-protein interaction examples

C "Conflict Resolution" Case (low model vs. positive motifs)

Input

Input Protein: BATF

Input DNA:

CTAGACTCTAATCAGCTGGATTAGAATCAAGGTAATCTACTCCATGAATTTATAATCATGTAATATTACTCTGAGCACTCAGCCA
CATCAAACTTGATTGTGAATGGCCTCTCCAAGAGCCCATTCAATTGTACTATGAACTGACTCACTCCAAGCAGCGTCGCCTTAA
CTCTTGAGCTAGCTGCGCAAAGTAACATTCAGGGACCATCTCAGATGGTGCCGTGTAGTCAGTGACTCCCACTTATTGTACTAA
ATGCTAAGCTCTGACTCAGAGTGAGCCCTATTAGTTGCTGACTGACACTGTACTTGTTTGAATAGAAGCTCACATTGTGAGTCA
CCTGGTGGTGCACTGAAAACCAATCTGAAATATTCCCAATTGGACAGTGATTCACATTATAATCATATTGGGACCTAACTTGAC
ACATGTGATTTCAAAACTAAGTTCTGCCAAACTGGCTTGGGAGCATGCTAGAAAGTCACTCCCTTCTTAATGCCCTGTCCTTCT
GTCTAAG

Qimai

- **Prediction label: 1**

- **Confidence score: 1**

- **Explanation:**

    1. **Direct Evidence**: The protein BATF has known motifs (High Reliability). **Direct motifs were found** in the DNA sequence (True). The DNA scan results show two hits with p-values <= 1.0e-04, indicating significant matches. The reliability of the motif information is high. This is strong evidence for interaction.

    2. **Indirect Evidence**: An indirect search was performed, and **motifs of interacting TFs (JUNB, JUN, IRF4) were found in the DNA sequence.** The DNA scan results show hits for JUNB and JUN with p-values <= 1.0e-04. This provides additional evidence supporting an interaction.

    3. **Prediction Model Evidence: The DPI prediction model gives a low probability** (0.0255) and indicates that BATF is novel (absent from the DPI known set). The model confidence is high, but the novelty of the protein might reduce the reliability of the prediction.

    4. **Synthesis (Prioritizing Motif Evidence):**
    - Direct motif evidence is strong, with high reliability and significant hits in the DNA sequence.
    - Indirect motif evidence is also present, further supporting the possibility of interaction.
    - The DPI prediction model suggests no interaction, but this prediction is less reliable due to the protein's novelty and the low probability.
    - Given the strong direct and indirect motif evidence, I am prioritizing the motif evidence over the DPI prediction. The presence of multiple high-quality direct motif hits strongly suggests an interaction.

    5. **Conclusion**: Based on the prioritized synthesis, the final prediction is that an interaction occurs.

Regulatory landscape of query DNA sequence

Suppl. Fig. 5 Other DNA-protein interaction examples

D   **"Conflict Resolution" Case (low model vs. positive direct motif)**

Input

Input Protein: ZBTB7A

Input DNA:

CCAAATATGGGTGTTTCCAGAACTGTCATGGCCCTGGAAAGGTGTGTGATTTAGCATGGTAATGAGCATGTAATGAAGTTCTAG
GTGAAACCTAGGTCAAATCCAGCACCATGTTGGGTCCAGTCGGTCTAGCCAGCTTGGACCACGCCCTTGTTCTTCGGGGTCTT
ATCAGCCCCTCGCTTATGCAGCTATTTCAGCAGTTTCCTTTTGCTTAGTCATGTGAAACTGCTGCCTGGAATTTTCTTTTCTCCT
GTGACCACCCTGTATTATTCCTGCCTCAGTCAGAACAGCCATAGGAAACCAATGCACTCATATTTTGAACTTTAAATAGAATGA
GGCTAAGATATCTGAAATGTTATCATTTTTTTCTTTTTCATCAAGACAATTTCAGGAAATAATAACTCCTTCACAGCATTTCACTC
AGTTTTACTAATAAGTGGCTGAGTAATTGTCACTGGCAGCCCAGTAATGGATCTTAAAATAATACACAACTCTTCTTTTGAGGAA
ATGTG

Qimai

- **Prediction label: 1**

- **Confidence score: 0.72**

- **Explanation:**

  1. **Direct Evidence**: The direct motif evidence is strong. The protein has known motifs (Reliability: High). Direct motifs were found in the DNA sequence (True). The CisBP search was successful and reliable. Two hits for motif M10049_3.00 were found with p-values of 7.48e-05 and 9.84e-05, both below the threshold of 1.0e-04. This provides **strong evidence for a direct interaction.**

  2. **Indirect Evidence**: The indirect motif evidence is weak. While a STRING DB search found 4 interactors, none were known TFs in the CisBP database. Consequently, **no motifs of interacting TFs were analyzed** or found in the DNA sequence. This provides no support for an interaction.

  3. **Prediction Model Evidence**: The DPI prediction model **gives a probability of 0.0263, suggesting no interaction**. The confidence is high, but the protein is novel (absent from the DPI known set), which reduces the reliability of the prediction.

  4. **Synthesis(Prioritizing Motif Evidence):** We prioritize the direct motif evidence. The strong direct motif hits (two hits with p-values < 1.0e-04) strongly suggest an interaction. The indirect motif evidence is negligible. The DPI prediction model suggests no interaction, but its reliability is reduced due to the protein's novelty. Given the strong direct motif evidence, we override the DPI prediction.

  5. **Conclusion**: Based on the prioritized synthesis, the final prediction is that an interaction occurs.

Regulatory landscape of query DNA sequence

Suppl. Fig. 5 Other DNA-protein interaction examples

E   "Conflict Resolution" Case (low model vs. positive indirect motif)

Input

Input Protein: GATA1

Input DNA:

CATGGTTTCCCCAGGATTTGGGGTTAGTGGGCTACCCCCAGGAGTCTAGTGGGATCCACCTGGATTCTGTTTCCCCTGGAAAA
TATCACATTCTGCTGCAGTCAACCAGTCCATAAAAAATATCAGTTACATATCTCTCCTGTGCTAGGTCCTATATGAGCACTGGG
GACACAACATCTCTGCCTGCCAGTCTACCGGGGGAAGTCAGAGCAAACCACACATGAGGAAATACAAATCTCAGATAAGCTCA
GTTAGAGATCAGAGCCCTGAAGAAAGTGAAGCAGGTTAATGAGATAAAGTGTGAAAGTCAGGGAGTGCTGGGGGCGGGGCA
GCCCAGGGAAGGTCTCTTGCAGAGGTGATATTTGCACTGAGACCTAGAGGAAGAGATTTGGGGGATACATTTAAGACACAAG
GCAAAGACCCTGAGATAGAAAAAGTAAACCCTCAGTTCCTTTGAACCCCAGGACCCAGACTTCTTAAACAGTGGTCATTGTTGC
CTTGCTATGCCCTGT

Qimai

- **Prediction label: 0**

- **Confidence score: 0.505**

- **Explanation:**

  1. **Direct Evidence**: The direct motif analysis for GATA1 used high-reliability motifs from CisBP. However, the DNA scan **found no significant hits** for these motifs (p <= 1.0e-04). This is strong negative evidence against direct binding.

  2. **Indirect Evidence**: The indirect motif analysis, performed via GATA1's interactors, found that motifs of KLF1 (a known interactor) are present in the DNA sequence. This suggests that GATA1 *could* be recruited to this DNA region indirectly through interactions with KLF1. This is **weak positive evidence for interaction**.

  3. **Prediction Model Evidence:** The DPI prediction model gives **a low probability (0.0540) of interaction**. The model confidence is high, but the protein is novel (not in the training set), which reduces the reliability of the prediction. This is negative evidence.

  4. **Synthesis (Prioritizing Motif Evidence):**
  - Direct motif evidence is strong and negative (no direct motif hits).\n - Indirect motif evidence is weak and positive (KLF1 motifs present).
  - The DPI prediction is negative, but less reliable due to the protein's novelty.
  - I am prioritizing direct motif evidence. Since there are no direct motif hits, I am giving this the most weight. The indirect evidence is weak and only suggests a possible indirect interaction. The DPI prediction aligns with the lack of direct motif evidence

  5. **Conclusion**: Based on the prioritized synthesis, the final prediction is that GATA1 does not directly interact with this DNA sequence. The interaction label is: 0.

Regulatory landscape of query DNA sequence

Suppl. Fig. 5 Other DNA-protein interaction examples

F **"Decisive Indirect Evidence" Case**

Input

Input Protein: MTA3

Input DNA:

TAGGTGCGCGTCGGCGCCCAGGAGGACGTGTGGCGCGTGGACTACATCAGGTCCAGCCCTGCGGGACCCCAGCCAGCGCT
TCCGGGCAAGGTTCTGTGCACCTGTTTTCTCCTTCTACGCGAGTATCTTTCCCCTCCGGAAAGAATGGGATATGCCTGTGTCC
AAAGGACAAGAAGATGCGCGCCCAGCAAGCCTAAGTTAACCACAGCGCGGAAGTTGAGCCCAAAGCAAGAGCGTGCCGGGCA
CCTTTAAGCTGTTTGTAAGCCCACGTGACTCACCAAGTGCGGGCCCCAGCGGTCACGTGACGGCGCGCGCGCCCTCGCGCA
GGGAGAGCCGGCGGTGCGCGCGCGCCTTCGCCGCTGCCTCCCACCCACCCCCTCGACGGGAGGGTGAGGCGCGGCGCAGTG
ATCGGGCGGCCGGGGTCCTGTGCGCGTGCGCAGCGAACAGCTGTCACCTAGTGCGGAACAAGTCTCCCAAATTTCCCAAATC
TCCCTGGGCCGGAGGCCACTGTCTTC

Qimai

- **Prediction label: 1**

- **Confidence score: 0.69**

- **Explanation:**

   1. **Direct Evidence**: The direct motif analysis for MTA3 yielded no significant hits. The CisBP search also returned "**not_found_cisbp**". The reliability of the motif information is "Not Found". Therefore, the direct motif evidence is very weak and suggests no direct interaction.

   2. **Indirect Evidence**: The indirect motif analysis, performed via MTA3's interactors, found significant hits for MBD3 motifs in the DNA sequence. Three MBD3 motifs were found with p-values less than 1.0e-04. **This suggests that MTA3 might indirectly interact with the DNA through its interaction with MBD3.** The indirect motif evidence is moderately strong.

   3. **Prediction Model Evidence: The DPI prediction model gives a probability of 0.5262**, which is close to the decision boundary of 0.5. The confidence is low because MTA3 is novel (absent from the DPI known set). This model evidence is weak and uncertain.

   4. **Synthesis (Prioritizing Motif Evidence):**
   - Direct motif evidence is absent, indicating no direct interaction.
   - Indirect motif evidence is moderately strong, suggesting a possible indirect interaction through MBD3.
   - The DPI prediction model provides a weak and uncertain prediction. Prioritizing motif evidence, especially the indirect evidence, over the uncertain DPI prediction, I will lean towards predicting an interaction. The absence of direct motif evidence weakens the case, but the presence of MBD3 motifs, given that MBD3 interacts strongly with MTA3, provides a reasonable basis for predicting an interaction.

   5. **Conclusion**: The interaction label is: 1.

Regulatory landscape of query DNA sequence

Suppl. Fig. 5 Other DNA-protein interaction examples

G   **"Decisive Indirect Evidence" Case**

Input

Input Protein: CBX3

Input DNA:

AATGGATTCCACGCTTTTCACGAAGGGAGTTAAGACACTCGCTCAAACCAGCGTCTAGGAAGCCGGCTCAAGGCGCAGATGA
ATGTGCAGGGAATTTCCCATCAATCCCTTCGGCTTGCCTAGTCCTTCTCACAGTACCTCCCACAGTGCTCCGGGGGCTCCCTTG
TCACGTGATCGGGGTGGATCCGCTGAGGCAGAGGGAAGTTGATTCGCAGTTTGGGTGGCTGGGGCTACTACGCTTTCCTTCC
AACTCCCGACTCCCGGGCTTGCGTAATCTCGCGTTAAGTGGGGAGTAACTTCTCGCGAGAGCTAGATCGGGATCCCTCCAGG
TCCGCCTCCGTGGTGAGGAGGAGGAGGAGGAGGAGGCGGAGGTGGAGGGAGGAGGAGGAGGCCCCGTCGCGGCCTTCGC
CGCCGCCAACGGGGCTGTCCCTGTAGCTCCCGATGGAGTTTGAGGTCGTGAAACCTCCGCCGAGCTCTGCCCCGGCGAGAC
GAGGCGCCTCCGTCGCCAAGCCG

Qimai

- **Prediction label: 1**

- **Confidence score: 0.39**

- **Explanation:**

  1. **Direct Evidence**: The direct motif analysis for CBX3 yielded no significant hits. The CisBP search also returned "not_found_cisbp," indicating **a lack of known motifs for this protein in that database.** The reliability of the CisBP search is "Not Found," which suggests the search could not be performed or the protein is not present in the database. Overall, the direct motif evidence is weak and negative.

  2. **Indirect Evidence**: The indirect motif analysis, performed via interacting TFs, **found a significant hit for the E2F6 motif within the DNA sequence.** E2F6 is a known TF that interacts with CBX3 (STRING score 0.997). This provides positive, albeit indirect, evidence of a potential interaction.

  3. **Prediction Model Evidence**: The DPI prediction model gives **a low probability (0.1668) of interaction**. The protein is considered "Novel" by the model, which reduces confidence in the prediction. The model confidence is "Moderate".

  4. **Synthesis (Prioritizing Motif Evidence):**
  - Direct motif evidence is negative.
  - Indirect motif evidence is positive, with a hit for the E2F6 motif, an interactor of CBX3.
  - The DPI model predicts no interaction with low probability and moderate confidence, but it is less reliable for novel proteins.
  Prioritizing motif evidence, particularly the indirect evidence, suggests a potential interaction. While the direct motif search was negative, the presence of a motif for an interacting TF (E2F6) indicates that CBX3 might be recruited to this DNA region through its interaction with E2F6. The DPI model's low probability and novelty status make it less reliable than the indirect motif evidence in this case.

  5. **Conclusion**: Based on the prioritized synthesis, the presence of a motif for an interacting TF outweighs the negative direct motif search and the low-probability DPI prediction. Therefore, I predict an interaction.

Regulatory landscape of query DNA sequence

857   **Supplemental Figure 6: Prompts for reasoning LLM.**

858   **(A) Example prompt for unseen protein, which instructs LLM to prioritize biological evidence.**

859   **(B) Example prompt for known protein, which instructs LLM to weigh the computational model**

860   **prediction more.**

A Example Prompt for unseen protein

Analyze the potential interaction between the DNA sequence and the Protein 'RAD21' (Homo_sapiens). Your goal is to predict if an interaction occurs (1) or not (0), based *only* on the evidence provided below.

Input Data:

Protein: RAD21
DNA (Length: 512):
CTCTCTTAAAAAAAATAAAAAGTAATAAGTAGTTCATTCTATTGGTACTTTAAAATGATAACAAATAATGTATGGTGGTTGTAAAAATTCAAAACACAGACTTGTAACAAGTGAAGTAGGAACTGTACCTCTCCTAGCTG
GCTCTGCCTTCAGCCTTCCCTGTGATTCTGGGCTCAGCCCCCAGCTGAGAACCACTGGATTCTGGGCAGACGTCAAGATGAGGACCTGAGCCCCTCCCATAAACCAGGGACCCAGATCCCATGGCTATGCCTGC
AGTTCCCCCTAGAGGAGCACTTGGTTTTGGGAATGAGGTCAGTGCTGGTGGTTAAAGCAGCGGCAGTGGGTCACAGCAGGCCCACTGGTACAGTGAACTTGTCAGTGACTTTCAGAATGTTGCTTTAGTGCTTCT
TAAACATTTCCTCTCTTGAGCTAGGATTGTTACAGAACCCGGGGTGGGTACAAGCCTGAAATAGGTATCAAGTGGTCCTGGCTAAGAGAGGAGGAATGGGAGC

Evidence Summary:

- DPI Prediction: Prob: 0.5789, Known (vs DPI): False, Confidence: Low (Uncertain)
- Direct Motif Evidence (Protein's own motifs):
  - Protein has known motifs? No/Error (Reliability: Not Found)
  - Direct motifs found in this DNA sequence? False
- Indirect Motif Evidence (via Protein-Protein Interaction):
  - Indirect Search Performed? True
  - Interacting TFs analyzed? 3
  - Motifs of analyzed interacting TFs found in this DNA? True

Supporting Information Details:

1. **Direct Motif Analysis (Protein: RAD21):**

   - CisBP Search Result: Status: not_found_cisbp. Reliability: Not Found.
   - DNA Scan Results for Direct Motifs: No significant direct motif hits found (p <= 1.0e-04). Scan status: unknown

2. **Indirect Motif Analysis (via RAD21's interactors):** STRING DB Search: Found 50 interactors (Score > 700).

   - 7 interactors are known TFs. Analyzed top 3:
     - CTCF (STRING Score: 0.999)
     - YY1 (STRING Score: 0.902)
     - CTCFL (STRING Score: 0.887)
   - DNA Scan Results for Interacting TF Motifs: Hits in DNA from Interacting TFs (p<=1.0e-04, Top 3 by p-value):
   - TF:CTCFL (Mot:M10008_3.00) @Pos:273(-) Score:16.24 p:1.53e-06
   - TF:CTCF (Mot:M08734_3.00) @Pos:275(-) Score:14.67 p:4.32e-06
   - TF:CTCFL (Mot:M08388_3.00) @Pos:274(-) Score:13.66 p:7.39e-06

3. **DPI Prediction Details:**

   - Probability: 0.5789
   - Protein Status (vs DPI Known Set): Novel (Absent from DPI Known Set)
   - Model Confidence (derived): Low (Uncertain)
   - Model Info: DPI Transformer, trained on ~1500 ChIP-seq datasets (~800 TFs). Generally high accuracy on known TFs, potentially less certain on novel ones.

Analysis Task:

Please perform a step-by-step analysis based *strictly* on the provided evidence:

1. **Direct Evidence:** Evaluate direct motif evidence (reliability, hits, quality). Strength?
2. **Indirect Evidence:** Evaluate indirect motif evidence (TFs, hits, quality). Strength?
3. **Prediction Model Evidence (All Models):** For each model: probability, confidence, novelty impact.
4. **Synthesis (Prioritizing Motif Evidence):** Synthesize all evidence. **Crucially, give significant weight to direct and then indirect motif evidence.** If any model prediction conflicts with strong or clear motif evidence (e.g., multiple high-quality direct hits), the motif evidence should generally take precedence. If motif evidence is weak, absent, or ambiguous, the model prediction(s) can be more influential. Explicitly state how you are weighing the evidence. Note any conflicts between models or with motif data.
5. **Conclusion:** Based on your prioritized synthesis, state your final prediction (0 or 1).

MANDATORY Output Format:

Explanation: [Your detailed step-by-step reasoning following points 1-5 above, clearly showing the prioritized weighing]
The interaction label is: [0 or 1]

B   Example Prompt for known protein

Analyze the potential interaction between the DNA sequence and the Protein 'JUND' (Homo_sapiens). Your goal is to predict if an interaction occurs (1) or not (0), based *only* on the evidence provided below.

Input Data:

Protein: JUND
DNA (Length: 512):
TTGACAATTTAAAATAGTGAAAAAAACTAAAATAAAGAAAAAGAAAAAAACTAAGGAGAAAATATGACTTACGGAAAAAACACATTTCAAGGATAGATTTTGGGGAATTGGACAGTCCATAAGAGCTAGCCCTTCA
TGAGACAACCATTCTGTGATAGTGATTTCTTGGATTTAAGATATTAGGAAGTTTGGACTTCAGAGATTTTGATCTTTTGGGATTTCAACATTTGGGAGTATGCTGTTTGGAACTTTGTCTTTTGGGACACCAGAAC
TGGAAAGCAAACTTCCCCTAGATGGCTGCTGTCCAAGTTCCACATATTCTCACCAGCAAGGCCATTGCCCTGATGGGAAACTCCTATTGCTACAGGACTGGTTAAGTATTTCCGTTCTGCCCTAGCTTCCCCAT
AAATGCAAACGCAGTACAAGCACAAGCTCTCTGTCCCAGGGCACTATCCATGCTGCAGCCTGCTTTGTCTGTTTCAAGCACAACTCTCTGTAGAGACTAAGGGCAT

Evidence Summary:

- DPI Prediction: Prob: 0.5779, Known (vs DPI): True, Confidence: Low (Uncertain)
- Direct Motif Evidence (Protein's own motifs):
    - Protein has known motifs? Yes (Reliability: High (Direct, Reputable Source))
    - Direct motifs found in this DNA sequence? False
- Indirect Motif Evidence (via Protein-Protein Interaction):
    - Indirect Search Performed? True
    - Interacting TFs analyzed? 3
    - Motifs of analyzed interacting TFs found in this DNA? False

Supporting Information Details:

1. **Direct Motif Analysis (Protein: JUND):**

    - CisBP Search Result: Status: success_cisbp. Reliability: High (Direct, Reputable Source). Found 3 Direct, 0 Inferred motifs (Top 3 selected from 20). | M08698_3.00 (D/JASPAR) | M08699_3.00 (D/JASPAR) | M09920_3.00 (D/HocoMoco)
    - DNA Scan Results for Direct Motifs: No significant direct motif hits found (p <= 1.0e-04). Scan status: success_empty_output

2. **Indirect Motif Analysis (via JUND's interactors):** STRING DB Search: Found 37 interactors (Score > 700).

    - 23 interactors are known TFs. Analyzed top 3:
        - FOSL1 (STRING Score: 0.999)
        - JUNB (STRING Score: 0.999)
        - JUN (STRING Score: 0.999)
    - DNA Scan Results for Interacting TF Motifs: No significant indirect motif hits found (p <= 1.0e-04) for analyzed interacting TFs. Scan status: success_empty_output

3. **DPI Prediction Details:**

    - Probability: 0.5779
    - Protein Status (vs DPI Known Set): Known (Present in DPI Known Set)
    - Model Confidence (derived): Low (Uncertain)
    - Model Info: DPI Transformer, trained on ~1500 ChIP-seq datasets (~800 TFs). Generally high accuracy on known TFs, potentially less certain on novel ones.

Analysis Task:

Please perform a step-by-step analysis based *strictly* on the provided evidence:

1. **Direct Evidence:** Evaluate the direct motif evidence. Strength?
2. **Indirect Evidence:** Evaluate the indirect motif evidence. Strength?
3. **Prediction Model Evidence (All Models):** For each model: probability, confidence, novelty impact.
4. **Synthesis (Prioritizing Prediction Models):** Synthesize the evidence. **Crucially, give significant weight to the prediction model(s), especially if their confidence is High or Moderate.** If multiple models agree with high confidence, their consensus is very strong. If direct/indirect motif evidence is weak, absent, or contradicts confident model prediction(s), the model evidence should generally take precedence, particularly for proteins known to those models. Explicitly state how you are weighing the evidence. Note any conflicts between models or with motif data.
5. **Conclusion:** Based on your prioritized synthesis, state your final prediction (0 or 1).

MANDATORY Output Format:

Explanation: [Your detailed step-by-step reasoning following points 1-5 above, clearly showing the prioritized weighing]
The interaction label is: [0 or 1]

Supplemental Figure 7: Representative examples in comparison with LightGBM classifier.

(A) MEF2C example. It presents a clear conflict: strong direct motif evidence versus a low DPI model

prediction (0.2578). The LightGBM classifier was misled by the low score and failed. Qimai, however,

correctly prioritized the significant motif evidence over the unreliable model score for a novel protein,

making the correct positive prediction, which is confirmed by ChIP-seq data.

(B) STAT3 example. Despite overwhelming direct and indirect motif evidence, the DPI model returned

an extremely low score (0.0338). The LightGBM classifier failed again by adhering to this score. In

contrast, Qimai correctly identified the combined biological evidence as decisive, overriding the

unreliable model to make the correct positive prediction, which is validated by prominent ChIP-seq peaks.

Suppl. Fig. 7 examples in comparison with LightGBM classifier

A   **MEF2C example: ground truth is binding**

Input

Input Protein: MEF2C

Input DNA:

AAGTCACTTGTTCTGGTGAGGAACAGTTGAAAGGGCACATAATACTTTTGGTAATAATATTTAATGTAACTTATTTAGCAGTGCG
TGTTCATGATTGGCAAGGCAGGTGAGTAGATTAGGAAATGAGTCTGAAAAAGTAGGGCAGGACTGCTGGCTTAAAATAGGAGT
GAAAGCAGTGAACAGACATAGCTATTTAGGCAAATCCTAGTGTCCCATGAGGATAAGACTACCACAATAATCTAAAAATAATAG
CTTATAGGCCAATAACCTTTAAGGTTTATGTTTCATACTCACCGCAGGTCAACCCATGTGGCTGTTTCTCATTTATGCAGATCTA
CATCAGATTTTACTTGTGTTTACCTGAAAATACATATTGTTTATGTAGTCAATGTATATTGTAGTAGCATACAGAATCTGATCTTG
AAAAGGTTGCAGAATTTCTTGAGTGTACTTTAGGAACTTAGTTTTTCAAAATTTATTTAATTTTTATTTTGATAATTATAGATTCAC
AG

Qimai

- **Prediction label: 1**

- **Confidence score: 0.845**

- **Explanation:**

  1. Direct Evidence: The direct motif evidence is strong. The CisBP search was successful and reliable, finding 3 direct motifs. DNA scanning revealed hits for one of these motifs (M10371_3.00) within the provided DNA sequence at positions 238 and 153, with p-values of 1.39e-05 and 1.50e-05, respectively. These p-values are below the threshold of 1.0e-04, indicating significant hits.

  2. Indirect Evidence: The indirect motif evidence is weak. Although a STRING DB search identified 36 interactors, and the top 3 interacting TFs were analyzed, no significant motif hits were found for these interacting TFs within the provided DNA sequence (p <= 1.0e-04).

  3. Prediction Model Evidence: The DPI prediction model gives a probability of 0.2578, suggesting a low likelihood of interaction. The model confidence is moderate, and the protein is novel (absent from the DPI known set), which reduces the reliability of the prediction.

  4. Synthesis (Prioritizing Motif Evidence): We prioritize motif evidence, especially direct motif evidence. The direct motif analysis revealed significant hits for MEF2C's motifs within the DNA sequence. This strongly suggests that MEF2C can directly interact with the DNA. The indirect motif evidence is negative, but this is less important than the direct evidence. The DPI prediction model suggests a low probability of interaction, but given the strong direct motif evidence, we will override the model's prediction.

  5. Conclusion: Based on the strong direct motif evidence, we predict that MEF2C interacts with the DNA sequence.

LightGBM

prediction: no binding
probability: 0.263

Regulatory landscape of query DNA sequence

Suppl. Fig. 7 examples in comparison with LightGBM classifier

B   **STAT3 example: ground truth is binding**

Input

Input Protein: STAT3

Input DNA:

TCTTGTCTGTAATGATTTACTTAAAGAGAATTTTTTTTTTAAAAAGTGAAAGCATGTTTATTAAGAAAGTAAAGGAATAAAAGAATG
GCTACTCCACGAGCAGAACAGTGGCACGGGCTGCTCAGCTGAGTATACTGATAGTTGCTTCTTGGTTATATGCCAAACAAGGG
GTGGATTATTCATGAGTTTTCTGGGAAAGGGGCAAGGATTTTTAGACCATATAAGGTAACTTCTGGGCATTGCCATGGCATTTG
TAAACTGTCATGGTGCTGGTGGGAGTGTCTTTTAGCATGCTAATGTATTATAATTAGCATATAATGAGCAGTGAGGACGACCAG
AGGTCACTTTCCTCGCAGTCTTGGTTTTGGTGGGTTTTAGCTGGCTTCTTTACCGCAAACTGTTTTATCAGCAAAGTCTCTGTGA
CTTGTATCTTGTACTGACCTCCTATCTCATTCTGTGACTAAGAATGCCTAACCTTCTGGGAATGCAGCCCAGTAGGTCTCAGCC
TTATTT

Qimai

- **Prediction label: 1**

- **Confidence score: 1**

- **Explanation:**

  1. Direct Evidence: The direct motif evidence is strong. The protein has known motifs (High Reliability). Direct motifs were found in the DNA sequence with significant p-values (e.g., 1.99e-06 and 3.24e-06). The source of the motifs is also highly reliable (CisBP).

  2. Indirect Evidence: The indirect motif evidence is also strong. Interacting TFs were analyzed (STAT1, STAT5B, STAT5A), and motifs of these TFs were found in the DNA sequence with significant p-values (e.g., 9.29e-10, 1.18e-09, 4.18e-06).

  3. Prediction Model Evidence: The DPI prediction model gives a low probability (0.0038) and classifies the protein as novel. While the model has high confidence, it is potentially less certain on novel TFs.

  4. Synthesis (Prioritizing Motif Evidence):

  - Direct motif evidence strongly suggests an interaction.

  - Indirect motif evidence further supports an interaction.

  - The DPI prediction model suggests no interaction, but its confidence is potentially lower for novel proteins.

  - Given the strong direct and indirect motif evidence, I am prioritizing the motif evidence over the DPI prediction. The DPI prediction is downweighted due to the protein being novel and the strong presence of relevant motifs.

  5. Conclusion: Based on the strong motif evidence, I predict that an interaction occurs. The interaction label is: 1 (Binding)

LightGBM

prediction: no binding
probability: 0.069

Regulatory landscape of query DNA sequence

References

1.   Spitz, F. & Furlong, E. E. M. Transcription factors: from enhancer binding to developmental control.

Nat Rev Genet **13**, 613–626 (2012).

2.   Jolma, A. *et al.* DNA-binding specificities of human transcription factors. *Cell* **152**, 327–339 (2013).

3.   Li, X. *et al.* Transcription factors bind thousands of active and inactive regions in the Drosophila

blastoderm. *PLoS Biol* **6**, e27 (2008).

4.   Zhou, J. & Troyanskaya, O. G. Predicting effects of noncoding variants with deep learning-based

sequence model. *Nat Methods* **12**, 931–934 (2015).

5.   Chen, K. M., Wong, A. K., Troyanskaya, O. G. & Zhou, J. A sequence-based global map of

regulatory activity for deciphering human genetics. *Nat Genet* **54**, 940–949 (2022).

6.   Ji, Y., Zhou, Z., Liu, H. & Davuluri, R. V. DNABERT: pre-trained Bidirectional Encoder

Representations from Transformers model for DNA-language in genome. *Bioinformatics* **37**, 2112–

2120 (2021).

7.   Avsec, Ž. *et al.* Effective gene expression prediction from sequence by integrating long-range

interactions. *Nat Methods* **18**, 1196–1203 (2021).

8.   Sanda, T. *et al.* Core transcriptional regulatory circuit controlled by the TAL1 complex in human T

cell acute lymphoblastic leukemia. *Cancer Cell* **22**, 209–221 (2012).

9.   Parelho, V. *et al.* Cohesins functionally associate with CTCF on mammalian chromosome arms. *Cell*

132, 422–433 (2008).

10. Park, P. J. ChIP-seq: advantages and challenges of a maturing technology. *Nat Rev Genet* **10**, 669–

680 (2009).

11. Alipanahi, B., Delong, A., Weirauch, M. T. & Frey, B. J. Predicting the sequence specificities of

DNA- and RNA-binding proteins by deep learning. *Nat Biotechnol* **33**, 831–838 (2015).

12. Bailey, T. L. *et al.* MEME SUITE: tools for motif discovery and searching. *Nucleic Acids Res* **37**,

W202-208 (2009).

13. ENCODE Project Consortium *et al.* Expanded encyclopaedias of DNA elements in the human and

mouse genomes. *Nature* **583**, 699–710 (2020).

14. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* **596**, 583–589

(2021).

15. Steinegger, M. & Söding, J. MMseqs2 enables sensitive protein sequence searching for the analysis

of massive data sets. *Nat Biotechnol* **35**, 1026–1028 (2017).

16. Rauluseviciute, I. *et al.* JASPAR 2024: 20th anniversary of the open-access database of transcription

factor binding profiles. *Nucleic Acids Research* **52**, D174–D182 (2024).

17. Vorontsov, I. E. *et al.* HOCOMOCO in 2024: a rebuild of the curated collection of binding models

for human and mouse transcription factors. *Nucleic Acids Res* **52**, D154–D163 (2024).

18. Szklarczyk, D. *et al.* The STRING database in 2023: protein-protein association networks and

functional enrichment analyses for any sequenced genome of interest. *Nucleic Acids Res* **51**, D638–

D646 (2023).

Supplementary Notes

A. Identifying and Mitigating DNA Sequence Bias in Dataset Preparation

Considering the similar performances of DPI-bench and DNABERT shown in **Figure 1C**, we investigated the contribution of protein module in DPI-bench. We removed the protein encoder and decoder blocks from the original model. Thus, the refined DNA embedding was directly fed into the prediction module to generate binary prediction. We trained the "DNA only" model on the same training set and evaluated the performance on the same testing set. Full model (DNA + protein) and DNA only model performed almost equally well (**Supplementary Figure 1D**), suggesting the protein module made negligible contribution to the model performance. DNA information plays an overwhelming role as compared to protein information, consistent with that DPI-bench model improved only slightly from DNABERT. Thus, DPI-bench model mainly learns how to classify different DNA sequences rather than different DNA-protein pairs, resulting that DNA patterns mislead the model to make the same prediction (binding or non-binding) for the same DNA sequence regardless of proteins.

To resolve the DNA sequence bias, we adopted a more rigorous data preparation process. In the previous dataset, the positive DNA sequences are genome sequences centered around ChIP-seq peaks identified from experiment while the negative DNA instances are synthetic sequences. Although the dinucleotide frequency is kept the same, the positive and negative sequences can have otherwise different patterns. Considering the main interest lies in the human genome in future inference, it is more appropriate to construct both positive and negative sequences from the genome.

Furthermore, each ChIP-seq experiment has its own unique set of peaks. It is unlikely to find exactly the same two peaks from different experiments even for the same TF. It can be problematic because each DNA sequence always has the same label regardless of the interacting protein, providing a lazy "shortcut" for the model, i.e. the model can make satisfactory predictions by just looking at the input DNA sequence. Thus, we need to construct instances with different labels associated with different proteins for the same DNA sequence. In this way, the model will be forced to utilize protein information to understand interaction modes and make opposite predictions for the same DNA. If a model only memorized the DNA patterns, the prediction accuracy would only be 50%, equal to random guess. Therefore, this label reversal design will help alleviate the DNA sequence bias.

Following DeepSEA protocol with a few adaptations (**Methods**), we re-processed the ChIP_690 datasets. The positive DNA sequences are genome segments overlapped with ChIP-seq peaks while the negative

instances are genome segments without overlap of ChIP-seq peaks. Same DNA sequence can bind to

some proteins (positive labels) and not bind to others (negative labels).

B. Validation and Calibration of Qimai's Confidence score

A critical component of Qimai is its ability to generate a final confidence score for its predictions. To be

useful, this score must be not only discriminative (good at separating positive and negative cases, as

shown by AUC-ROC/PR in the main text) but also well-calibrated, meaning the confidence level should

correspond to the actual likelihood of a correct prediction. This supplementary analysis validates the

calibration of Qimai confidence score against the raw probability output of a standalone DPI model,

which serves as a primary input to our agent.

The results demonstrate a significant improvement of calibration by Qimai. As shown in the

Supplementary Figure S2B, the standalone DPI model is markedly under-confident; for instance, in the

lowest-confidence bin (predicted probability ≈ 0.1), the actual fraction of positives is more than 40%.

Qimai corrects this behavior, producing a more confident score that tracks the ideal calibration line much

more closely. The background histogram reveals that the majority of predictions fall into these lower-

confidence bins, highlighting that the Qimai's primary contribution is to improve reliability precisely

where it is most needed. This validation confirms that the Qimai's final confidence score is a trustworthy

and interpretable measure of prediction accuracy.

To assess the robustness of the final confidence score, we evaluated the system's performance on unseen

data using four distinct sets of heuristic parameters (**Supplementary Table 11**). These configurations

were designed to test different evidence-weighting philosophies: "Default" style prioritizing motif

evidence, "V1" style that gives greater weight to computational model predictions, "V2" style with more

conservative parameters (lower baseline confidence and smaller bonuses), and "V3" style with more

optimistic parameters (higher baseline and larger bonuses). As shown in the **Supplementary Figure S3A**

(left panel), key metrics remained highly stable across these different configurations. AUC-ROC was

consistently high, ranging from 0.641 to 0.682, while AUC-PR was similarly stable, ranging from 0.679

to 0.701. This minimal variation demonstrates that the system's overall predictive accuracy is not

dependent on a specific, fine-tuned set of heuristic parameters.

Furthermore, we generated calibration plots to evaluate the reliability of the confidence score produced by

each parameter set (**Supplementary Figure S3A**, right panel). The analysis shows that all four

configurations yield well-calibrated probabilities, with their curves closely tracking the ideal diagonal
line, which represents perfect calibration. This indicates that the confidence score is a reliable measure of
the likelihood of a correct prediction, regardless of the underlying heuristic strategy. Taken together, the
stability in performance metrics and the consistent calibration across diverse parameter sets provide
strong evidence for the robustness of our confidence scoring architecture.
986

987 *C. Robust performance across different LLMs and different combination of prediction models*

988 To further characterize the robustness of the Qimai framework, we performed additional analyses
989 evaluating its consistency across different Large Language Models (LLMs) and its sensitivity to the
990 combination of computational prediction models used as evidence.
991

992 A core component of the Qimai framework is its LLM-based Reasoning Agent. To ensure that the
993 system's strong performance is not dependent on a single proprietary model, we benchmarked Qimai's
994 performance using three distinct LLMs: Gemini-1.5-flash, Gemini-2.0-flash, and the open-source model
995 Gemma-3-27b-it (**Supplementary Figure S3B**). The evaluation was conducted on both the seen proteins
996 and the unseen proteins from external ChIP_690 dataset.
997

On the seen protein set, two Gemini-flash models enabled Qimai to achieve high performance while
gemma-3 model showing a slight disadvantage. However, on the "unseen" dataset, which is a more
critical assessment, all LLMs delivered comparable and strong performance, significantly outperforming
standalone models. The open-source Gemma-3-27b-it model performed on par with the proprietary
Gemini models across metrics like accuracy, F1-score, and AUC-ROC. This demonstrates that the Qimai
framework's architecture is robust and that its superior generalization capabilities are a product of its
evidence synthesis design rather than an artifact of a specific LLM. This flexibility allows for the
deployment of Qimai with powerful, locally-hosted open-source models, enhancing accessibility and
reproducibility.
1007

The Qimai framework is designed to synthesize evidence from one or more computational "Decision
Agent" models. We conducted an ablation study to determine whether integrating predictions from
multiple models simultaneously provides an advantage over using a single, best-performing model
(**Supplementary Figure S3C**). We compared three system configurations: "DPI", where only the DPI
model's prediction was provided to the LLM; "DPI + Sei", where predictions from both DPI and Sei were

provided; and "DeepSEA + DPI + Sei", where predictions from all three models were provided. This

comparison was performed on both the seen and unseen proteins.

1015

1016   On the seen protein set, integrating predictions from multiple models ("DeepSEA + DPI + Sei" and "DPI

1017   + Sei") resulted in the highest performance across most metrics. This suggests that for in-distribution

1018   proteins, the LLM can effectively leverage the diverse predictive strengths of multiple models to achieve

1019   a more nuanced and accurate final prediction.

1020

However, on the more challenging "unseen" dataset , this trend reverses. The configuration using only the

single best-generalizing model ("DPI") outperforms configurations that include predictions from Sei and

DeepSEA across most of the metrics. This highlights a key insight: the optimal strategy for evidence

integration depends on the novelty of the query. For out-of-distribution scenarios involving novel

proteins, providing the single most reliable computational prediction minimizes potentially conflicting or

less reliable signals from models that do not generalize as well, proving to be the most robust strategy.

1027

D. Representative examples of Qimai context-aware predictions

As stated in the main text, a key advantage of the Qimai is its flexible, context-aware reasoning, which

allows it to outperform traditional classifiers when faced with conflicting evidence. While the main text

highlights a case for the AP2A protein, the examples in **Supplementary Figure S7** for MEF2C and

STAT3 further illustrate the robustness of the LLM Agent compared to a LightGBM classifier trained on

the same evidence components.

1034

The MEF2C case (**Supplementary Figure S7A**) presents a classic conflict between strong biological

evidence and a misleading model prediction. The agent identified two highly significant direct motif hits

for MEF2C, providing strong evidence for a direct binding event. However, the underlying DPI

prediction model, being unfamiliar with this "novel" protein, produced a low probability score of 0.2578,

suggesting no interaction. The LightGBM classifier, having learned a strong dependency on the model

score during training, was misled by this low probability and incorrectly predicted no binding. In contrast,

Qimai correctly reasoned that the model's reliability is reduced for a novel protein and prioritized the

high-confidence direct motif evidence, leading to the correct positive prediction. This conclusion is

visually confirmed by the strong MEF2C ChIP-seq peak and active epigenetic marks in the provided

genome browser view.

1045

The example of STAT3 (**Supplementary Figure S7B**) offers an even more compelling demonstration.

Here, overwhelming biological evidence was presented: multiple strong direct motif hits for STAT3,

corroborated by strong indirect evidence from motifs of other STAT family members known to interact

with it. Despite this, the DPI model returned an extremely low probability of 0.0338. The LightGBM

classifier again failed decisively, adhering to the low model score and predicting no binding. Qimai,

however, synthesized the full context. It identified the protein's novelty, recognized the strength and

consistency of both the direct and indirect motif evidence, and correctly concluded that this biological

evidence far outweighed the unreliable model score. Therefore, it made a high-confidence positive

prediction, which is validated by the ChIP-seq signals for STAT3 at that genomic location.

1055

1056 Together, these cases underscore the brittleness of fixed-weight classifiers in novel biological contexts

1057 and highlight the superior performance of the Qimai's context-aware reasoning framework.

1058

1059 *E. Representative Case Studies of Qimai predictions*

1060 To provide a comprehensive view of the Qimai's reasoning capabilities, we presented a few distinct

1061 DNA-protein interaction scenarios. These cases illustrate how Qimai synthesizes different types of

1062 evidence to arrive at a final prediction, ranging from straightforward confirmations to complex conflict

1063 resolutions.

1064

Supplementary Figure S5A and **B** depict scenarios where all available evidence points in the same

direction. In the "All Signals Green" case for the transcription factor SPI1 (**Supplementary Figure S5A**),

Qimai's positive prediction (Label: 1) is strongly supported by converging evidence. SPI1, also known as

PU.1, is a well-established pioneer transcription factor that is essential for the development of myeloid

and B-lymphoid cells. As a pioneer factor, it binds to specific DNA sequences called PU-boxes to open

chromatin, making the presence of high-reliability direct motif hits a strong and expected indicator of

interaction. This direct evidence, combined with supportive indirect evidence from known interacting

partners like GATA1 and a high-probability score (0.7190) from the DPI model, makes for a high-

confidence prediction. This conclusion is visually confirmed by the strong SPI1 and GATA1 ChIP-seq

peak and active epigenetic marks in the provided genome browser view.

1075

Conversely, **Supplementary Figure S5B** illustrates a "Correct Rejection" for the protein IRF4. IRF4 is

another crucial transcription factor for the development and function of immune cells, including T-cells,

B-cells, and macrophages. Its activity is highly context-dependent and often relies on cooperation with

other transcription factors. In this specific instance, the lack of any significant direct motif hits for IRF4

or indirect hits for its partners aligns with the low interaction probability (0.1990) from the model. This

leads to a confident negative prediction (Label: 0), correctly identifying this as a non-binding site. This

conclusion is visually confirmed by the absence of IRF4 ChIP-seq peaks in the provided genome browser

view.

1084

A key strength of Qimai system is its ability to resolve conflicts between the initial computational

prediction and biological evidence, particularly when a protein is novel to the prediction model.

Supplementary Figure S5C and **D** showcase scenarios where the agent correctly prioritizes strong motif

evidence over a conflicting low-probability score from DPI model. For instance, BATF (**Supplementary**

Figure S5C), a member of the AP-1 family of transcription factors, is predicted to interact with the DNA

despite a very low model score. BATF often functions by forming heterodimers with JUN family proteins

to bind DNA. Although the DPI model returned a low probability (0.0255), likely due to the protein's

novelty to the model, Qimai identified strong direct motif evidence for BATF and, critically, indirect

evidence for its interacting partners JUN and JUNB. By prioritizing the strong, biologically plausible

direct and indirect motif evidence, Qimai correctly overrides the model's initial prediction to conclude

that an interaction occurs. This conclusion is visually confirmed by the strong BATF, JUN, JUNB, and

IRF4 ChIP-seq peak and active epigenetic marks in the provided genome browser view.

1097

Supplementary Figure S5D presents a complementary and even more stringent test with the protein

ZBTB7A. Like BATF, ZBTB7A is a known transcription factor, but the DPI model, being unfamiliar

with it, returned a similarly low probability of interaction (0.0263). The agent found two strong direct

motif hits with highly significant p-values (7.48e-05 and 9.84e-05). Critically, in this case, there was no

supporting indirect evidence. Despite the lack of secondary support, the agent's logic remained robust. It

identified the protein's novelty as a reason to reduce the reliability of the model's prediction and

prioritized the strong, unambiguous direct motif evidence as the most trustworthy signal, once again

overriding the model to correctly predict an interaction. This conclusion is visually confirmed by the

presence of ZBTB7A ChIP-seq peaks in the genome browser view.

1107

Qimai also demonstrates nuanced reasoning when direct evidence is absent. For instance, GATA1

(**Supplementary Figure S5E**) is a master regulator of red blood cell development. Here, Qimai was

faced with conflicting signals: there were no direct GATA1 motif hits (strong negative signal), but weak

positive evidence for a motif hit of its cofactor, KLF1, and the model score was low (0.0540). In this

scenario, Qimai assigned more weight to the absence of direct hit and concluded that the weak indirect

evidence was not sufficient to overcome this, resulting in a correct prediction of no interaction. This

conclusion is visually confirmed by the absence of GATA1 ChIP-seq and active epigenetic peaks in the

genome browser view.

1116

Supplementary Figure S5F and **G** highlight scenarios where indirect evidence becomes the deciding

factor, particularly for proteins that do not bind DNA directly. MTA3 (**Supplementary Figure S5F**) is a

component of the NuRD chromatin remodeling complex, which does not bind DNA in a sequence-

specific manner but is recruited to gene targets by other proteins. Here, direct motif evidence for MTA3

was absent, and the model's prediction was uncertain (0.5262). However, Qimai found moderately strong

indirect evidence of a motif for MBD3, another component of the NuRD complex. By prioritizing this

strong biological clue of a known partner protein, it correctly predicts that an interaction occurs, likely

through MTA3 being part of the recruited NuRD complex. This conclusion is visually confirmed by the

MBD2 and MTA3 ChIP-seq peaks and active epigenetic marks in the genome browser view.

1126

The case of CBX3 (**Supplementary Figure S5G**) further demonstrates this recruitment-based reasoning.

CBX3 is a chromobox protein that reads histone modifications and lacks a known DNA-binding motif.

As expected, the direct motif search failed, and DPI model produced a moderately low probability score

(0.1668). However, Qimai identified a significant motif for the TF E2F6, a known high-confidence

interaction of CBX3 and correctly reasoned that the presence of E2F6's motif is strong evidence for

recruitment. This conclusion is visually confirmed by the CBX3 and E2F6 ChIP-seq peaks and strong

open chromatin signals in the genome browser view.

1134

This provides a crucial contrast to GATA1 case ((**Supplementary Figure S5E**), where similar conflicting

evidence led to an opposite prediction. The key difference lies in the biological role of the primary

protein. For a sequence-specific transcription factor like GATA1, the absence of its own motif is strong

evidence against an interaction. In contrast, for a protein like CBX3 that is known to be recruited, the lack

of a direct motif is expected and does not constitute strong negative evidence. Therefore, the significant

E2F6 motif becomes the decisive piece of evidence for CBX3, compelling a positive prediction, whereas

the weaker KLF1 motif for GATA1 was insufficient to override the strong negative signal from its own

missing motif.

1143

1144