Title

A Fully Automated, Data-Driven Approach for Dimensionality Reduction and Clustering

in Single-Cell RNA-seq Analysis

Authors

Hyun Kim[1], Faeyza Rishad Ardi[2], Kévin Spinicci[1], Jae Kyoung Kim[1,3,4*]

Affiliations

1) Biomedical Mathematics Group, Pioneer Research Center for Mathematical and Computational
Sciences, Institute for Basic Science, Daejeon 34126, Republic of Korea

2) School of Computing, KAIST, Daejeon 34141, Republic of Korea

3) Department of Mathematical Sciences, KAIST, Daejeon 34141, Republic of Korea

4) Department of Medicine, College of Medicine, Korea University, Seoul, 02841, Republic of Korea

*Correspondence: jaekkim@kaist.ac.kr

Abstract

Single-cell RNA sequencing (scRNA-seq) provides deep insights into cellular heterogeneity but

demands robust dimensionality reduction (DR) and clustering to handle high-dimensional, noisy

data. Many DR and clustering approaches rely on user-defined parameters, undermining

reliability. Even automated clustering methods like ChooseR and MultiK still employ fixed

principal component defaults, limiting their full automation. To overcome this limitation, we

propose a fully automated clustering approach by integrating scLENS—a method for optimal PC

selection—with these tools. Our fully automated approach improves clustering performance by

~14% for ChooseR and ~10% for MultiK and identifies additional cell subtypes, highlighting the

advantages of adaptive, data-driven DR.

Keywords

Clustering analysis, Dimensionality reduction, scRNA-seq, Cell type identification, Automated

pipeline

Highlights

● Fully automated, data-driven clustering pipeline for scRNA-seq analysis.

● Addresses the limitation of fixed principal component defaults in DR.

● Data-driven pipeline improves clustering performance by 10-14%.

● Performance gains are most pronounced on high-sparsity, high-skewness data.

Author Summary

A fundamental goal in modern biology is to create detailed cellular maps of complex tissues to

understand their function in health and disease. Achieving this level of detail is now possible

through single-cell sequencing, a technology that generates massive, high-dimensional, and

noisy datasets of individual cells' genetic profiles. However, accurately identifying cell-types

from these datasets remains a major analytical hurdle, as current computational methods rely

on subjective parameters that compromise reliability and reproducibility.

To address this challenge, we developed a fully automated pipeline that integrates scLENS, an

adaptive noise filtering method, with automated cell grouping tools. By providing optimal

parameters for noise filtering and cell grouping, our pipeline eliminates their reliance on

subjective, fixed parameters, thereby significantly improving accuracy in cell-type classification.

This tool, characterized by its high clustering efficiency, can accelerate discoveries in fields like

cancer biology and immunology by providing a robust and reproducible analytical platform.

Introduction

Many recent studies utilize single-cell RNA sequencing (scRNA-seq) because it provides

extensive transcriptomic information[1,2]. Most scRNA-seq analysis pipelines begin by filtering

out low-quality cells and genes, followed by normalization to reduce distribution skewness, and,

if necessary, feature selection or batch correction before dimension reduction (DR) [2–5]. This

DR step mitigates the curse of dimensionality by extracting only biologically meaningful

information, and the resulting lower-dimensional embedding is then used for clustering [2–4,6].

After these preliminary analyses, various downstream steps become relevant, including

differential expression analysis (DEA) to identify cell functions, trajectory analysis to trace cell

lineage, and pseudotime analysis to capture cell differentiation over time [7–11]. Because both

DR and clustering directly influence these follow-up methods, they are regarded as

indispensable processes in the scRNA-seq workflow [2,4,6].

In practice, DR is performed via either linear methods like principal component analysis (PCA)

or nonlinear methods such as t-SNE, UMAP, and variational autoencoders (VAE). PCA, in

particular, remains a popular tool due to its computational efficiency and interpretability [12–19].

Despite its utility, misselecting the number of principal components (PCs) during the PCA

process can critically compromise the embedding quality [20]. Given this significance, many

studies still rely on default software settings or employ naïve criteria based on the dataset's total

number of cells [21–23]. To address this issue, several approaches—including Elbow plots,

variance-based criteria, and Horn's parallel analysis—have been proposed [24–26]. However,

each still depends partly on user decisions or has scalability issues. As a result, many widely

used packages, such as Seurat and Scanpy, continue to provide a fixed number of PCs as their

default [17,18]. Recently, however, scLENS emerged as a fast and accurate solution for

automatically determining the optimal number of PCs [27]. This prompts the question of whether

replacing the default PCA settings with scLENS's data-driven approach could enhance the

performance of existing pipelines.

In this study, we sought to answer that question by reimplementing scLENS—originally

developed in Julia—into a Python environment, where numerous analysis packages are widely

used [28]. This Python-based scLENS was combined with two data-driven clustering algorithms,

ChooseR and MultiK, both of which can automatically derive an optimal number of clusters via

consensus clustering (Fig. 1a-c; see details in Methods) [29,30]. However, the original

algorithms for these approaches rely on fixed PC defaults in the DR step ($N = 30$ for MultiK and

$N = 100$ for ChooseR; Fig. 1a-c), regardless of the biological complexity of the data [29,30].

By replacing these DR steps with scLENS, we developed a fully data-driven clustering pipeline

(Fig. 1c and 1d). To comprehensively evaluate this new approach, we benchmarked its

performance against the original algorithms and three alternative methods. These methods

were derived from the original algorithms by replacing the conventional DR with one of the

following: PCA with Scanpy's default settings [18] (Fig. 1b, $N = 50$), PCA using the elbow

method [24] for automatic PC selection, and VAE-based tool scVI [19] (Fig. 1e). Across 33

datasets containing ground-truth cell-type annotations, our results showed overall improvements

not only over the original MultiK and ChooseR but also over the alternative DR approaches

using the elbow method and scVI. These findings confirm that integrating scLENS with optimal

clustering algorithms enables more precise classification of cell populations, which, in turn, is

expected to benefit downstream analyses, such as DEA analysis, trajectory analysis, and

pseudotime analysis.

Methods

Quality Control (QC)

All analyses were performed on datasets that had undergone quality control. Specifically, cells

with fewer than 200 expressed genes and genes expressed in fewer than 15 cells were filtered

out. In addition, cells with a mitochondrial gene proportion exceeding 5% were removed. These

steps ensured that only high-quality cells were retained for downstream analyses.

Data Preprocessing

Following QC, data preprocessing was performed according to the specific requirements of

each analytical method. For standard downstream analyses, the filtered count matrix was

processed through a pipeline involving size factor normalization to correct for sequencing depth,

a log transformation ($log(x+1)$) to stabilize variance, and z-score scaling to normalize each

gene's mean to zero and standard deviation to one (Fig. 1b).

After z-score scaling, scLENS performs an additional L2-normalization step as its final

preprocessing stage to correct signal distortion [27] (Fig. 1d). In contrast, the scVI model was

applied directly to the raw count matrix after the initial QC filtering (Fig. 1e). This is because

scVI performs normalization internally as part of its generative modeling process and does not

require the aforementioned transformation and scaling steps [19].

Clustering Algorithms

• ChooseR [29]: Full clustering is initially performed on the preprocessed dataset to

establish reference labels at a given resolution. Next, after applying PCA to the entire

dataset, 100 clustering runs are conducted at this resolution on random 80%

subsamples extracted from the resulting 100-dimensional embedding (Fig. 1b, $N = 100$).

From each run, a pairwise co-clustering matrix is computed, with each entry

representing the frequency with which two cells are grouped together (Fig. 1c). This co-

clustering matrix is then converted into a distance matrix by subtracting each co-

clustering frequency from 1, and per-cell silhouette scores are calculated from these

distances. The scores of the cells within the same clusters are then averaged to obtain

the cluster-level silhouette scores, indicating the robustness of each cluster. This entire

process is repeated over a set of ten resolution parameters (resolution parameter = [0.3,

0.5, 0.8, 1, 1.2, 1.6, 2, 4, 6, 8]). For each resolution, the 95% confidence interval (CI) for

the distribution of cluster silhouette scores is calculated. After first identifying the 95% CI

with the highest lower bound, the near-optimal clustering parameter is selected as the

one that yields the most clusters whose median silhouette scores fall within this interval.

• MultiK [30]: First, 100 subsamples are generated by randomly selecting 80% cells from

the preprocessed data. PCA is then applied to each subsample to produce a 30-

dimensional embedding (Fig. 1b, $N = 30$). These 100 PCA embeddings are

subsequently used for clustering via the standard Seurat workflow across 40 resolution

parameters (ranging from 0.05 to 2.0 with a step size of 0.05), resulting in 4,000

candidate clustering results (Fig. 1c). For each candidate clustering result, a consensus

matrix is constructed to quantify the frequency with which cell pairs co-cluster. From the

cumulative distribution function (CDF) curve of this matrix, the relative proportion of

ambiguous clustering (rPAC) score is calculated to assess the stability for each number

of clusters (K), using the following formula:

$$\mathrm{rPAC}_K(\mu_1, \mu_2) = \frac{\mathrm{CDF}_K(\mu_2) - \mathrm{CDF}_K(\mu_1)}{\mathrm{CDF}_K(0)}, \tag{1}$$

where $\mu_1 = 0.1$, $\mu_2 = 0.9$. Finally, the optimal clustering result is chosen based on two

criteria: an rPAC score close to zero, which indicates robust clustering, and a high

frequency of occurrence for that K.

Integration with scLENS

Originally, scLENS was implemented in Julia, while ChooseR and MultiK were developed as R

packages [27]. To facilitate the integration of scLENS with ChooseR and MultiK, all three

packages were converted into Python implementations. Performance tests comparing the

converted packages with their original versions confirmed that the default settings yielded

equivalent performance. Once equivalence was verified, scLENS was integrated into the

clustering workflows to enable a fully automated, data-driven selection of PCs (Fig. 1d).

Specifically, for ChooseR, the conventional PCA step was replaced by scLENS in a single run.

On the other hand, for MultiK—which typically performs multiple PCA runs across

subsamples—scLENS was applied to the first subsampled dataset to determine the optimal

number of PCs, and this determined value was then reused in subsequent subsampling

iterations to enhance computational efficiency.

Alternative DR methods

• PCA with Scanpy's default settings [18]: First, the raw count data is preprocessed by

removing its size factors and applying a logarithmic transformation, following the

standard Scanpy pipeline. Subsequently, PCA is applied to this data to obtain the default

50 PCs (Fig. 1b, $N = 50$).

• scVI [19]: After QC, the scVI model is built from the raw count data using its default

parameters (Fig. 1e). Key parameters include a zero-inflated negative binomial

distribution for gene likelihood and a hidden layer size of 128 units. The model is then

trained for 400 epochs to obtain a 10-dimensional latent space from the final model (Fig.

1e).

• PCA with the Elbow Method: First, the raw count data is preprocessed through size-

factor removal, logarithmic transformation, and Z-score scaling[18] (Fig. 1e). PCA is then

performed on the resulting scaled data. Finally, we use the kneed Python package [31]

to identify the elbow point in the explained variance curve, which indicates the optimal

number of PCs (orange circle in Fig. 1e).

Results

scLENS integration increases the Clustering Performance of ChooseR and MultiK.

To benchmark the impact of different DR methods on consensus clustering, we assessed how

the clustering performance of the two consensus clustering packages, ChooseR and MultiK,

varied when provided with embeddings from: (1) scLENS, (2) PCA using Scanpy's default

settings, (3) PCA with the number of components selected by the elbow method, and (4) scVI

(Fig. 1b, 1d, and 1e) [18,19,24,27]. The performance of these combinations was assessed on

33 real and simulated datasets derived from three sources: ZhengMix, a PBMC blood cell

dataset; Tabula Muris, a comprehensive mouse tissue dataset; and a T-cell dataset obtained

from the Cross-Tissue Immune Cell Atlas, representing immune cell data [32–34]. These

datasets encompass varying levels of sparsity, skewness in data distributions, and population

sizes, which can significantly influence clustering performance (Table 1).

Across these 33 datasets, scLENS integration yielded the most substantial improvements in the

clustering performance. When integrated with scLENS, clustering performance, measured by

Element-Centric Similarity (ECS) [35] against true labels, increased by an average of ~ 14% for

ChooseR and ~ 10% for MultiK (Fig. 2a and 2b). In contrast, the alternative methods provided

only slight improvements and even caused considerable performance degradation in some

instances. For example, integrating ChooseR with Scanpy's PCA or scVI resulted in a

performance gain of merely ~ 6% or less (green and pink bars in Fig. 2a), which was

comparable to the baseline performance of the original packages. The elbow method for PC

selection was even less effective, decreasing the average performance of ChooseR by ~37%

and showing the worst results for MultiK (Fig. 2a, cyan bar). For MultiK, both Scanpy's PCA and

scVI also showed lower performance compared to the original package (Fig. 2b). These results

underscore the unique effectiveness of scLENS in enhancing clustering accuracy.

The improved embedding quality from scLENS drives the enhancement in clustering

performance of ChooseR and MultiK.

While these average results highlighted the overall superiority of scLENS, a closer analysis

revealed that the effectiveness of scLENS integration was highly dependent on the dataset (Fig.

3a). Specifically, it produced substantial performance gains for both ChooseR and MultiK on the

simulated T-cell and real ZhengMix datasets, with increases ranging from ~14% to ~18% over

their respective baselines (Fig. 3a). The simulated Tabula Muris data presented a unique case:

scLENS still improved ChooseR's performance by ~9%, while MultiK's performance remained at

its optimal baseline (ECS ≈ 1), precluding further gains (Fig. 3a).

These performance variations across different data types stem from differences in the quality of

embedding enhancement achieved by scLENS. For example, in one of the simulated T cell

datasets, "4249-2916," compared to the graph constructed on the default 30-PC embedding, the

graph built on the 28-PC embedding derived by scLENS showed substantially higher neighbor

purity (NP) [36]—defined as the proportion of neighboring nodes sharing the same cell type as a

given node (top panels in Fig. 3b). This elevated NP, indicating more cohesive clusters of cells

belonging to the same cell type, led to better cluster boundaries and subsequently enhanced the

clustering performance for MultiK (bottom panels in Fig. 3b). However, this performance

enhancement was not observed in one of the simulated Tabula-Muris datasets, "tmp_3," despite

a substantial difference between the number of PCs detected by scLENS and the default 30

PCs, as the NP increase remained minimal (Fig. 3c).

Easy vs. Difficult Problems: How data variability and sparsity levels affect clustering

performance

We further investigated why the degree of improvement from scLENS varied, especially in

MultiK, by examining embedding quality in terms of NP under different sparsity levels and

across inter-cell variability in total gene expression—quantified as the coefficient of variation of

total gene expression (CV(TGC)) [27]. This embedding quality, quantified via NP differences

between default and scLENS-driven embeddings, tended to show limited gains in data with low

sparsity (≤0.84) or low CV(TGC) (≤0.4), even when the PC gap was substantial (big circles

outside the blue dashed box in Fig. 3a). Such limited gains suggest that these "easier" datasets,

characterized by abundant information due to low sparsity and minimal distortions from lower

skewness in data distribution, are adequately handled by default preprocessing, leaving minimal

scope for further improvement. In contrast, for "difficult" datasets with greater sparsity (>0.84)

and CV(TGC) (>0.4), a larger PC gap can lead to greater NP gains (circles within the blue

dashed box in Fig. 3d). These NP gains, in turn, often result in improved clustering performance

as measured by ECS (Fig. 3e).

Discussion

In general, DR and clustering are essential steps in scRNA-seq analysis; however, determining

the optimal number of reduced dimensions and clusters still relies heavily on subjective user

input, which can undermine the reliability of the results [17,18,20]. To address this issue,

automated techniques, including ChooseR and MultiK, have been developed [29,30]. However,

these methods fix the number of PCs during the DR process, making it difficult to consider them

entirely data-driven. Therefore, we proposed a data-driven approach integrating scLENS [27]

into these algorithms, significantly reducing user intervention from dimension reduction to

clustering in scRNA-seq data analysis.

This combined algorithm was effective in enhancing clustering accuracy when applied to 33 real

and simulated scRNA-seq datasets (Fig. 2). Specifically, compared with the default settings,

ChooseR exhibited an improvement of ~ 14 % in performance, and MultiK ~ 10 % (blue bars in

Fig. 2). In particular, these improvements were most pronounced in challenging datasets, where

high CV(TGC) can lead to signal distortion, and greater sparsity indicates less information (Fig.

3d and 3e).

This significant performance gain becomes even more evident when contrasted with other

widely used DR approaches. For instance, while the elbow method offers the convenience of

automatically selecting PCs, it significantly degrades the clustering performance of ChooseR

and MultiK (cyan bars in Fig. 2). Furthermore, other widely used DR methods, such as scVI and

Scanpy's PCA, failed to deliver significant improvements, offering performance that was merely

comparable to the original packages (green and pink bars in Fig. 2). These results confirm that

the substantial performance gains are uniquely attributable to the integration of scLENS, an

advantage not replicated by the other methods.

Despite these clear performance advantages, the algorithm's comprehensive evaluation

process introduces scalability issues, as both memory usage and computation time increase

rapidly with large-scale data. Specifically, scLENS requires the computation of the complete set

of eigenvalues and eigenvectors, which significantly increases its memory requirements and

limits its speed when handling massive datasets [27]. Similarly, as the number of cells increases,

the repeated clustering required by MultiK or ChooseR leads to rapid increases in computation

time and memory consumption as well [29,30]. To mitigate these scalability issues, the

clustering algorithm employing MultiK and ChooseR can be replaced with the recently

developed GVE-Leiden clustering algorithm, which leverages parallel computing to improve

clustering speed significantly [37]. Furthermore, the speed and memory efficiency of scLENS

may be enhanced in future research through approximate spectral analysis [38].

In this study, we demonstrated that replacing the conventional DR process, which relies on a

fixed number of PCs, with the scLENS data-driven signal selection approach improves

performance by 10 - 15%. Given that most downstream analyses depend on low-dimensional

embedding and clustering results, combining scLENS with conventional algorithms is expected

to enhance the performance of many existing methods for scRNA-seq data analysis. For

instance, a recently developed package for evaluating clustering consistency has proven both

highly efficient and effective in estimating clustering stability by successfully utilizing scLENS for

its DR step [39].

Furthermore, this approach is applicable not only to scRNA-seq but also to various omics data,

such as single-cell chromatin accessibility sequencing and spatial transcriptomics, which

similarly require dimension reduction and clustering analysis [40–42]. Additionally, many

analysis tools employing nonlinear neural network models—such as autoencoders or VAEs—

have been developed for the dimension reduction step in extended data analyses [12,19]. To

properly evaluate the performance of these tools, rather than simply comparing them with PCA

results obtained using a fixed dimension, one can compare them with PCA results optimally

selected via scLENS, thereby determining the extent to which nonlinear models can overcome

the limitations of linear methods. In summary, the highly extensible Python version of the

scLENS algorithm proposed in this study is expected to be widely adopted in various

downstream analyses in the future, owing to its high user convenience and performance.

Data availability

The 33 real and simulated datasets used in this study were derived from three sources:

• Zheng datasets [33]: Ten real datasets representing PBMC blood cell data were

obtained from the Zheng datasets provided by 10x Genomics

(https://www.10xgenomics.com/resources/datasets). These datasets exhibit a wide

range of cluster sizes and ratios, thereby providing diverse clustering scenarios.

• Simulated Tabula Muris dataset [32]**:** Between 4 and 10 distinct cell types were

randomly selected from various tissue types within the Tabula Muris dataset

(https://tabula-muris.ds.czbiohub.org/) to minimize inter-cell type correlations. Using

scDesign2 [43], we trained a model on these selected cells to generate simulated

datasets with variable cluster sizes and imbalanced ratios, thereby providing diverse

clustering scenarios.

• Simulated T-cell datasets [34]**:** T-cell data were extracted from the immune cell dataset

available from the Cross-Tissue Immune Cell Atlas

(https://www.tissueimmunecellatlas.org). Subsequently, using scDesign2, we generated

multiple simulated T-cell datasets by varying sequencing depth and data skewness. This

procedure produced datasets with different levels of quality, as reflected in metrics such

as sparsity and the coefficient of variation of total gene expression (CV(TGC)).

In addition to the 33 datasets used in this study, the Python packages for scLENS, multiK, and

ChooseR are publicly available at https://github.com/Mathbiomed/scLENSpy. (the repository

URL will be disclosed upon acceptance; until then, the code is provided as supplementary

material).

Code Availability

A fully automated clustering package, integrating the MultiK and ChooseR optimal clustering

algorithms with the scLENS data-driven dimensionality reduction (DR) method, is freely

available on GitHub: https://github.com/Mathbiomed/scLENSpy.

Conflict of interest

None declared.

Ethics Statement

This study used publicly available and simulated datasets. All data were previously

published and did not involve any new experiments on human subjects. Therefore, this

research did not require an ethics statement or approval from an institutional review

board.

References

1. Macosko EZ, Basu A, Satija R, Nemesh J, Shekhar K, Goldman M, et al. Highly Parallel Genome-
wide Expression Profiling of Individual Cells Using Nanoliter Droplets. Cell. 2015;161:1202–14.

2. Luecken MD, Theis FJ. Current best practices in single-cell RNA-seq analysis: a tutorial.
Molecular Systems Biology. 2019;15:e8746.

3. Kharchenko PV. The triumphs and limitations of computational methods for scRNA-seq. Nat
Methods. 2021;18:723–32.

4. Andrews TS, Kiselev VY, McCarthy D, Hemberg M. Tutorial: guidelines for the computational
analysis of single-cell RNA sequencing data. Nat Protoc. 2021;16:1–9.

5. Ahlmann-Eltze C, Huber W. Comparison of transformations for single-cell RNA-seq data. Nat
Methods. 2023;20:665–72.

6. Kiselev VY, Andrews TS, Hemberg M. Challenges in unsupervised clustering of single-cell RNA-
seq data. Nat Rev Genet. 2019;20:273–82.

7. Finak G, McDavid A, Yajima M, Deng J, Gersuk V, Shalek AK, et al. MAST: a flexible statistical
framework for assessing transcriptional changes and characterizing heterogeneity in single-cell
RNA sequencing data. Genome Biol. 2015;16:278.

8. Trapnell C. Defining cell types and states with single-cell genomics. Genome Res.
2015;25:1491–8.

9. Trapnell C, Cacchiarelli D, Grimsby J, Pokharel P, Li S, Morse M, et al. The dynamics and
regulators of cell fate decisions are revealed by pseudotemporal ordering of single cells. Nat
Biotechnol. 2014;32:381–6.

10. Bergen V, Lange M, Peidli S, Wolf FA, Theis FJ. Generalizing RNA velocity to transient cell states
through dynamical modeling. Nat Biotechnol. 2020;38:1408–14.

11. Van Den Berge K, Roux De Bézieux H, Street K, Saelens W, Cannoodt R, Saeys Y, et al.
Trajectory-based differential expression analysis for single-cell sequencing data. Nat Commun.
2020;11:1201.

12. Tran D, Nguyen H, Tran B, La Vecchia C, Luu HN, Nguyen T. Fast and precise single-cell data
analysis using a hierarchical autoencoder. Nat Commun. 2021;12:1029.

13. Abdi H, Williams LJ. Principal component analysis. WIREs Computational Stats. 2010;2:433–59.

14. Becht E, McInnes L, Healy J, Dutertre C-A, Kwok IWH, Ng LG, et al. Dimensionality reduction for
visualizing single-cell data using UMAP. Nat Biotechnol. 2019;37:38–44.

15. McInnes L, Healy J, Saul N, Großberger L. UMAP: Uniform Manifold Approximation and
Projection. JOSS. 2018;3:861.

16. Kobak D, Berens P. The art of using t-SNE for single-cell transcriptomics. Nat Commun.
2019;10:5416.

17. Hao Y, Hao S, Andersen-Nissen E, Mauck WM, Zheng S, Butler A, et al. Integrated analysis of
multimodal single-cell data. Cell. 2021;184:3573-3587.e29.

18. Wolf FA, Angerer P, Theis FJ. SCANPY: large-scale single-cell gene expression data analysis.
Genome Biol. 2018;19:15.

19. Lopez R, Regier J, Cole MB, Jordan MI, Yosef N. Deep generative modeling for single-cell
transcriptomics. Nat Methods. 2018;15:1053–8.

20. Elhaik E. Principal Component Analyses (PCA)-based findings in population genetic studies are
highly biased and must be reevaluated. Sci Rep. 2022;12:14683.

21. Mima A, Kimura A, Ito R, Hatano Y, Tsujimoto H, Mae S-I, et al. Mechanistic elucidation of
human pancreatic acinar development using single-cell transcriptome analysis on a human iPSC
differentiation model. Sci Rep. 2025;15:4668.

22. Martins-Ferreira R, Calafell-Segura J, Leal B, Rodríguez-Ubreva J, Martínez-Saez E, Mereu E, et
al. The Human Microglia Atlas (HuMicA) unravels changes in disease-associated microglia subsets
across neurodegenerative conditions. Nat Commun. 2025;16:739.

23. Zhong H, Han W, Gomez-Cabrero D, Tegner J, Gao X, Cui G, et al. Benchmarking cross-species
single-cell RNA-seq data integration methods: towards a cell type tree of life. Nucleic Acids
Research. 2025;53:gkae1316.

24. Zhuang H, Wang H, Ji Z. findPC: An R package to automatically select the number of principal
components in single-cell analysis. Martelli PL, editor. Bioinformatics. 2022;38:2949–51.

25. Horn JL. A Rationale and Test for the Number of Factors in Factor Analysis. Psychometrika.
1965;30:179–85.

26. Jolliffe IT. Principal component analysis. 2nd ed. New York: Springer; 2002.

27. Kim H, Chang W, Chae SJ, Park J-E, Seo M, Kim JK. scLENS: data-driven signal detection for
unbiased scRNA-seq data analysis. Nat Commun. 2024;15:3575.

28. Virshup I, Bredikhin D, Heumos L, Palla G, Sturm G, Gayoso A, et al. The scverse project
provides a computational ecosystem for single-cell omics data analysis. Nat Biotechnol.
2023;41:604–6.

29. Patterson-Cross RB, Levine AJ, Menon V. Selecting single cell clustering parameter values using
subsampling-based robustness metrics. BMC Bioinformatics. 2021;22:39.

30. Liu S, Thennavan A, Garay JP, Marron JS, Perou CM. MultiK: an automated tool to determine
optimal cluster numbers in single-cell RNA sequencing data. Genome Biol. 2021;22:232.

31. Satopaa V, Albrecht J, Irwin D, Raghavan B. Finding a "Kneedle" in a Haystack: Detecting Knee
Points in System Behavior. 2011 31st International Conference on Distributed Computing Systems
Workshops [Internet]. Minneapolis, MN, USA: IEEE; 2011 [cited 2025 July 1]. p. 166–71. Available
from: http://ieeexplore.ieee.org/document/5961514/

32. The Tabula Muris Consortium, Overall coordination, Logistical coordination, Organ collection
and processing, Library preparation and sequencing, Computational data analysis, et al. Single-
cell transcriptomics of 20 mouse organs creates a Tabula Muris. Nature. 2018;562:367–72.

33. Zheng GXY, Terry JM, Belgrader P, Ryvkin P, Bent ZW, Wilson R, et al. Massively parallel digital
transcriptional profiling of single cells. Nat Commun. 2017;8:14049.

34. Domínguez Conde C, Xu C, Jarvis LB, Rainbow DB, Wells SB, Gomes T, et al. Cross-tissue
immune cell analysis reveals tissue-specific features in humans. Science. 2022;376:eabl5197.

35. Gates AJ, Wood IB, Hetrick WP, Ahn Y-Y. Element-centric clustering comparison unifies
overlaps and hierarchy. Sci Rep. 2019;9:8574.

36. Cheng C-H, Chan C-P, Sheu Y-J. A novel purity-based k nearest neighbors imputation method
and its application in financial distress prediction. Engineering Applications of Artificial
Intelligence. 2019;81:283–99.

37. Sahu S. GVE-Leiden: Fast Leiden Algorithm for Community Detection in Shared Memory Setting
[Internet]. arXiv; 2023 [cited 2025 Feb 10]. Available from: https://arxiv.org/abs/2312.13936

38. Lin L, Saad Y, Yang C. Approximating Spectral Densities of Large Matrices. SIAM Rev.
2016;58:34–65.

39. Kim H, Park I, Park J-E, Kim JK, Seo M, Kim JK. scICE: enhancing clustering reliability and
efficiency of scRNA-seq data with multi-cluster label consistency evaluation. Nat Commun.
2025;16:6031.

40. Rodriques SG, Stickels RR, Goeva A, Martin CA, Murray E, Vanderburg CR, et al. Slide-seq: A
scalable technology for measuring genome-wide expression at high spatial resolution. Science.
2019;363:1463–7.

41. Cusanovich DA, Hill AJ, Aghamirzaie D, Daza RM, Pliner HA, Berletch JB, et al. A Single-Cell
Atlas of In Vivo Mammalian Chromatin Accessibility. Cell. 2018;174:1309-1324.e18.

42. Ståhl PL, Salmén F, Vickovic S, Lundmark A, Navarro JF, Magnusson J, et al. Visualization and
analysis of gene expression in tissue sections by spatial transcriptomics. Science. 2016;353:78–
82.

43. Sun T, Song D, Li WV, Li JJ. scDesign2: a transparent simulator that generates high-fidelity
single-cell gene expression count data with gene correlations captured. Genome Biol.
2021;22:163.

Acknowledgments.

This work was supported by the Institute for Basic Science IBS-R029-C3 (to J.K. Kim (Jae Kyoung))

Figure 1. The dimensionality reduction (DR) step in conventional clustering workflows is replaced with scLENS a. Single-cell RNA sequencing (scRNA-seq) data from three different

tissues with varying numbers of sub-cell types. **b**. To identify sub-cell types from scRNA-seq

data, optimal clustering methods, such as ChooseR and multiK, have been developed. These

methods begin with a dimensionality reduction (DR) step. This DR process starts with data

preprocessing, such as log-normalization, to address bias and skewness in the scRNA-seq data

distribution. Optionally, feature selection is used to filter out genes with low variance. Then, the

dimension of this scaled data is reduced by applying principal component analysis (PCA).

During this step, conventional optimal clustering methods typically recommend using the default

number of principal components (PCs). As a result, all three datasets are reduced to identical

dimensions despite having different numbers of cells or types of cells and, hence, different

amounts of biological information. **c**. From these reduced datasets with identical dimensions,

ChooseR and MultiK construct a graph, which consists of vertices of cells. To identify this

graph's optimal sub-communities (i.e., clusters), both methods repeatedly perform graph-based

clustering to obtain multiple clustering results. Among the multiple clustering results, ChooseR

and MultiK select the optimal clustering results using the co-clustering-based clustering

robustness estimation and the clustering stability metric, reverse proportion of ambiguous

clustering (rPAC), respectively. **d**. In these consensus clustering procedures, we replaced the

conventional DR process with scLENS, a recently developed DR method that utilizes a data-

driven signal selection approach. By employing noise filtering methods based on random matrix

theory and a signal robustness test, scLENS adaptively determines the number of dimensions

according to the amount of biological information in the data. This adaptive feature of scLENS

enables ChooseR and MultiK to construct graphs that more effectively capture the biological

patterns from various datasets with diverse amounts of biological information, potentially

enhancing the quality of clustering results. For a comprehensive evaluation, we benchmarked

our pipeline against both the original algorithms and three alternative dimensionality reduction

(DR) approaches. The first is the default PCA setting in Scanpy(18), which uses a fixed number

of 50 PCs (N=50 in b). **e**. The second alternative uses the elbow method(24), which selects the

optimal number of PCs for PCA by identifying the point of diminishing returns in explained

variance (orange circle in Fig. 1e). The third is scVI(19), a deep generative model that uses a

variational autoencoder to learn a non-linear latent representation of the data as an alternative

to   PCA.

Figure 2. Integrating conventional clustering packages with scLENS enhances clustering output. a-b. The integration of scLENS significantly enhances the clustering performance of both ChooseR and MultiK, as measured by the element-centric similarity (ECS). Specifically, it substantially improves the performance of ChooseR by ~14% (a, blue bar) compared to that of the original package (a, yellow bar). In contrast, integrating Scanpy's PCA or scVI offers merely comparable performance to that of the original ChooseR (a, green and pink bars). Furthermore, using the elbow method for PC selection severely degrades ChooseR's performance by ~37% (a, cyan bar). Similarly, while alternative DR methods cause MultiK to underperform relative to its baseline (b, green, pink, and cyan bars), scLENS substantially improves its clustering performance by ~10% (b, blue bar).

Figure 3. Clustering performance improvements from applying scLENS vary depending on data properties. a. The effectiveness of scLENS is highly dependent on the data type.

scLENS integration yields substantial performance gains in clustering for both packages on T-

cell and ZhengMix data (dark blue and orange bars). On Tabula-Muris data, scLENS integration

improves ChooseR's performance while MultiK's performance remains at its maximum (ECS ~

1), having hit a ceiling. (dark blue bar in Sim. Tabula-Muris Data). **b**. The effectiveness of

scLENS integration stems from its ability to generate higher-quality embedding. For instance, in

the simulated T-cell dataset "4249-2916," a graph constructed from the 28-dimensional

embedding derived by scLENS has more edges within each cell type and fewer edges between

cell types than the graph constructed from MultiK's default 30-dimensional embedding. This

change in connectivity creates a clearer cell type separation (sub-graphs with two cell types in

small boxes). This clearer separation leads to a substantial increase in neighbor purity (NP)—a

measure of how well neighboring cells share the same type. Higher NP indicates a higher-

quality embedding, enabling MultiK to more accurately identify cell types and thereby enhance

clustering performance (bottom panels). **c**. In contrast, such performance gains are not

observed in one of the simulated Tabula-Muris datasets, "tmp_3." In that dataset, only marginal

improvements in NP (i.e., embedding quality) appear, despite a large gap between the 218

detected signals and the default of 30, leading to no meaningful increase in overall clustering

performance. **d-e.** The embedding quality difference (d) and clustering performance difference

(e) between MultiK with default settings and MultiK integrated with scLENS are quantified by NP

and ECS, respectively. Furthermore, the size of the circles indicates the absolute difference (PC

gap) between the dimension scLENS determines (based on its detected signals) and the fixed

default PC dimension of 30. The degree of improvement in graph quality afforded by scLENS -

depends on the sparsity level and coefficient of variation (CV) of total gene expression (TGC).

For instance, in datasets with low sparsity or CV(TGC) (outside of the dashed box), scLENS

and MultiK's original embedding lead to graphs with similar NP (a), and thus, their performances

are similar (b) although different numbers of signals are used (PC gap). On the other hand,

when CV(TGC) ≥ 0.4 and Sparsity level ≥ 0.845 (inside of the dashed box), MultiK integrated

with scLENS demonstrates more significant embedding-quality improvements in terms of NP as

the PC gap grows (inside the blue dashed box in d). This substantial improvement in embedding

quality, in turn, results in better clustering performance for most cases (inside the blue dashed

box in e).

Cat.	Name	Ncells	Ngenes	Sparsity	CV(TGC)	Avg. Cluster size	Imbalanced ratio	# of signals
sim_Tcell	2250-1220	2951	10652	0.91	0.52	230.77	53.00	20
sim_Tcell	2251-1179	3000	10975	0.91	0.52	230.77	71.50	19
sim_Tcell	2972-1523	3000	11361	0.89	0.51	230.77	85.78	20
sim_Tcell	3276-1042	3000	11518	0.88	0.32	230.77	119.50	22
sim_Tcell	3689-1878	3000	11622	0.88	0.51	230.77	81.89	19
sim_Tcell	4249-2916	2971	11600	0.87	0.68	230.77	79.88	28
sim_Tcell	4320-2134	3000	11818	0.86	0.49	230.77	81.33	22
sim_Tcell	4797-2332	3000	11942	0.86	0.49	230.77	71.10	21
sim_Tcell	5930-3210	2988	12048	0.85	0.54	230.77	63.27	26
sim_Tcell	5960-1400	3000	12086	0.84	0.24	230.77	81.56	21
sim_Tcell	5974-3858	2979	12050	0.85	0.64	230.77	52.15	29
sim_Tcell	6006-2261	2998	12072	0.84	0.38	230.77	102.71	24
sim_Tcell	6083-4496	2974	12086	0.85	0.73	230.77	73.11	31
Tabula_Muris	T_muris_1019	1019	12199	0.82	0.61	101.90	1.21	36
Tabula_Muris	T_muris_2006	2006	12812	0.83	0.68	200.60	1.19	49
Tabula_Muris	T_muris_3016	3016	13355	0.84	0.73	301.60	1.19	67
Tabula_Muris	T_muris_3966	3966	13556	0.85	0.67	396.60	1.19	75
Tabula_Muris	T_muris_5033	5033	13949	0.85	0.64	503.30	1.17	93
Tabula_Muris	tmp_1	4827	11355	0.83	0.35	689.57	18.33	150
Tabula_Muris	tmp_2	3501	12117	0.84	0.45	583.50	17.53	218
Tabula_Muris	tmp_3	4244	13107	0.79	0.66	606.29	12.70	228
Tabula_Muris	tmp_4	4313	13540	0.84	0.59	431.30	8.28	127
Tabula_Muris	tmp_5	2485	10294	0.8	0.47	621.25	27.17	139
ZhengMix	z_data_12073	11971	11850	0.95	0.46	1468.75	1.21	23
ZhengMix	z_data_2410	2396	8194	0.93	0.45	301.25	1.18	10
ZhengMix	z_data_3308	3288	9057	0.94	0.43	413.50	2.05	9
ZhengMix	z_data_3706	3668	9581	0.94	0.44	463.25	3.44	15
ZhengMix	z_data_3869	3838	9501	0.94	0.44	483.63	1.15	13
ZhengMix	z_data_4292	4254	9813	0.94	0.46	536.50	1.97	12
ZhengMix	z_data_4757	4721	9962	0.94	0.45	586.25	1.40	13
ZhengMix	z_data_5730	5683	10322	0.95	0.48	716.25	12.71	14
ZhengMix	z_data_785	778	4803	0.89	0.43	98.13	1.16	10
ZhengMix	z_data_7993	7941	11019	0.95	0.45	975.88	1.28	19

513   **Table 1.** To evaluate the effectiveness of replacing conventional dimensionality reduction (DR)

514   methods with scLENS in terms of clustering performance, we used 33 datasets with varying

515   amounts of information influenced by factors such as the number of cells, cell types, and the

516   sparsity level.