Beyond Single Algorithms: A Framework for Validating and Aggregating Active Modules in Genetic Interaction Networks

Jason Liu[1,2], Min Xu[3,*], and Jinchuan Xing[1,2,*]

[1]Department of Genetics, Rutgers, The State University of New Jersey, Piscataway, NJ, USA.
[2]Human Genetics Institute of New Jersey, Rutgers, The State University of New Jersey, Piscataway, NJ, USA.
[3]Department of Statistics, Rutgers, The State University of New Jersey, Piscataway, NJ, USA.

[*]To whom correspondence should be addressed.
Jinchuan Xing
Department of Genetics, Human Genetics Institute of New Jersey
Rutgers, The State University of New Jersey
145 Bevier Road, Piscataway, New Jersey 08854
Email: jinchuan.xing@rutgers.edu
Min Xu
Department of Statistics
Rutgers, The State University of New Jersey
110 Frelinghuysen Road Piscataway, NJ 08854
Email: mx76@stat.rutgers.edu

---

[0]Running Title: Aggregating Modules in Interaction Networks

1 Abstract

High-throughput sequencing methods have generated vast amounts of genetic data for candidate gene studies. However, the complexity of the disease genetic structure often results in a large number of candidate genes and poses a significant challenge for these studies. To explore the multi-gene interactions and elucidate the genetic mechanism, candidate genes are often analyzed through Gene-Gene interaction (GGI) networks. These networks can become very large, necessitating efficient methods to reduce their complexity. Active Module Identification (AMI) is a common method to analyze GGI networks by identifying enriched subnetworks representing relevant biological processes. Multiple AMI algorithms have been developed for biological datasets, and a comparative analysis of their behaviors across a variety of datasets is crucial to their application. In this study, we introduce a framework to compare and aggregate the modules produced by multiple AMI algorithms. We first used a modified Empirical Pipeline to validate the output of four AMI algorithms – PAPER, DOMINO, FDRnet, and HotNet2 – and find that no single algorithm performs well across the different datasets. Using the Earth Mover's Distance to measure pairwise module similarity, we find that the outputs of different algorithms are structurally distinct, suggesting that each captures different aspects of the underlying biology. These findings suggest that a comprehensive analysis requires the aggregation of outputs from multiple algorithms. We propose two methods to this end: a spectral clustering approach for module aggregation, and an algorithm that combines modules with similar network structures called Greedy Conductance-based Merging (GCM). The merging algorithm not only allows researchers to obtain a set of cohesive modules from multiple algorithms, it also has the potential of identifying "hidden" genes that are not present in the original input data from the network. Overall, our results advance our understanding of AMI algorithms and how they should be applied. Tools and workflows developed in this study will facilitate researchers working with GGI and AMI algorithms to enhance their analyses. Our code is freely available at `https://github.com/LiuJO/AMI-Benchmark/`.

2 Introduction

In recent years, high-throughput sequencing methods allow the production of large amounts of data for genetic research. Using the high-throughput data, the medical genetics field has advanced significantly in the understanding and treatment of many diseases and disorders, including hundreds of rare Mendelian disorders (Baxter et al.; 2022; Posey et al.; 2019), cancers (Swanson et al.; 2023), and complex diseases (Lowe and Reddy; 2015). Despite its success, current medical genetics research faces a major difficulty that impedes its full development: the complexity of the underlying genetic structure of the disease. That is, diseases often result from mutations in a large number of potential risk genes with a high degree of heterogeneity and interaction. Therefore, many disease-causing mutations and mutated genes are not present in all patients' genomics data. Focusing solely on genes with the strongest evidence would result in a high number of false negatives, while relaxing the selection criteria could result in a high number of false positives, which could lead to unproductive downstream experiments and unnecessary expenditure of resources.

To further prioritize the candidate genes, one standard analysis in complex disease genetic studies is constructing a gene-gene interaction (GGI) network to account for the genetic heterogeneity (Reviewed in Wong et al. (2021)). The GGI network treats each candidate gene as a node, and uses available biological information from knowledge databases to assign edges to connect the genes. The constructed GGI network typically has a large number of edges even for a small number of candidate genes. Moreover, researchers often need to add intermediate nodes to the network to ensure that the network is connected, which further increases the size and complexity of the network. When the network becomes too complex, researchers often take additional manual approaches to reduce the size of the network, either by referencing existing results from literature or by using more stringent criteria for candidate node selection. However, these ad-hoc methods have serious drawbacks: the literature-based approach may be biased by the systemic over-representation of certain genes in the literature, while more stringent selection criteria might reduce the power of the candidate gene discovery.

To address this problem, a number of *active module identification* (AMI) algorithms have been developed (Reviewed in Levi et al. (2021) and Lazareva et al. (2021)). These algorithms are designed to identify connected subnetworks called *modules*, which represent biological processes or functional units. The modules provide additional evidence for biologically meaningful enrichment in GGI networks and prioritize candidate

genes within the module for downstream analysis. However, these algorithms were developed using different clustering principles and some of them were developed for specific biological questions. It is still unclear if the modules produced by these algorithms also have different characteristics. This matters because most studies choose a single algorithm to use, which implicitly assumes that the choice of method does not significantly impact biological conclusions. If different algorithms capture different aspects of the biology, this can result in an incomplete picture.

In this study, we develop a framework for analyzing and aggregating the results of multiple AMI algorithms. First, we validated modules produced by the algorithms using a modified Empirical Pipeline and show that they produce many significant modules. Next, we use the Earth Mover's Distance as a way to determine the similarity between algorithms. We show that the methods produce complementary results with distinct module characteristics. Based on these findings, we developed a spectral clustering method to identify groups of genes that are consistently assigned to the same module by multiple methods. Finally, we introduce a novel Greedy Merging by Conductance (GCM) algorithm, which leverages the network structure to effectively combine modules produced by different methods, enhancing the biological interpretability of the identified modules. Together, these tools provide researchers with a principled approach to integrating AMI results from multiple algorithms rather than relying on a single method or ad-hoc selection.

3 Results

3.1 Overview of AMI algorithms

We study four algorithms for active module identification: PAPER (Crane and Xu; 2024), DOMINO (Levi et al.; 2021), HotNet2 (Leiserson et al.; 2015), and FDRnet (Yang et al.; 2021). We choose these four algorithms because they each have a distinct approach to the AMI problem and together cover a diverse spectrum of methodological paradigms: PAPER uses Bayesian modeling, DOMINO uses modularity minimization, HotNet2 uses network diffusion, and FDRnet uses constrained optimization. We briefly describe these algorithms below and in Figure 1. We give details on the implementation and parameter choices in the *Methods and Materials* section (Section 5). Detailed descriptions of the algorithms can be found in Additional File 1. The overall workflow of our evaluation approach, including the algorithm assessment, similarity analysis, and module aggregation steps, is illustrated in Figure 2.

- **PAPER** is a Bayesian method for detecting modules/communities on a general network. It models the observed network as being generated from a latent growth process. The growth process produces disjoint random tree-components according the preferential attachment mechanism and adds additional independent Erdős–Rényi random edges to ensure that the network is fully connected. The underlying disjoint trees partition the nodes into clusters and model the module structure.

  The disjoint tree-components are unobserved but PAPER uses Markov Chain Monte Carlo algorithms to sample from their posterior distribution given the observed network. Each MCMC sample is a plausible collection of modules and we aggregate them to output the final set of modules. We apply PAPER on the sub-network induced by the set of active genes.

- **DOMINO** is a coarse to fine modularity-based algorithm. Before seeing the AMI information, DOMINO first applies a preprocessing step where it partitions network into disjoint slices to improve computational efficiency. Once the AMI scores are obtained, DOMINO retains only those slices which contain a significant number of active genes. Each of the retained slices is further trimmed through a method based on prize collecting Steiner trees. Finally, DOMINO applies the Newman–Girvan modularity algorithm on the trimmed slices to produce a set of modules and retains only those modules deemed significant according to an over-representation test.

- **HotNet2** is based on a diffusion process where the initial AMI scores are represented as "heat" and diffused through the interaction network via a random walk process with restart. This induces an "exchanged heat" matrix H. HotNet2 then defines a directed graph which contains an edge between node i and j if H_{ij} is sufficiently large in magnitude. Finally, it outputs the strongly connected components of the directed graph as the output modules.

- **FDRnet** uses empirical Bayesian analysis to estimate local false-discovery rates (FDR) for a set of input genes. Genes with a local FDR less than the B parameter are considered seeds. For each seed, a random walk is conducted to compute a PageRank vector. The subnetwork identification problem is formulated as a mixed-integer linear programming problem, whose objective is to minimize the conductance (Definition 4) for the network while ensuring the FDR does not exceed the bound B.

3.2 Overview of the datasets

To evaluate the four algorithms, we selected four candidate gene datasets (Table 1) where the activity score of each gene represents either the significance of the mutation burden of a gene between the cases and the controls, or the significance of gene expression differences.

1. The dataset "**Aneuploidy1**" (Tyc et al.; 2021; Biswas et al.; 2024) contains data from whole exome sequencing (WES) of 178 patients undergoing in vitro fertilization (IVF) treatment, divided into high ($n = 93$) and low ($n = 85$) aneuploidy rate groups. Gene scores represent the significance of the variant burden in a gene in the high aneuploidy rate group compared to the low rate group, as determined using VAAST (Hu et al.; 2013).

2. The dataset "**Aneuploidy2**" (Tyc et al.; 2020) contains WES data from 160 patients undergoing IVF treatment, divided into high ($n = 68$) and low ($n = 92$) aneuploidy rate groups. Gene scores represent the significance of the variant burden in each gene in the high aneuploidy rate group compared to the low rate group, as determined using VAAST (Hu et al.; 2013).

3. The dataset "**TNFa**" (Schmidt et al.; 2015) contains RNA sequencing (RNA-seq) data from multiple cell types treated with tumor necrosis factor (TNF) for 90 minutes versus control. The gene scores represent the significance of the differential transcriptional activity between TNF-treated and vehicle control conditions.

4. The dataset "**Fly Transcriptome**" (Sun et al.; 2024) contains expression microarray data from different tissues of *Drosophila melanogaster*. Gene scores represent the significance of the expression of a gene in ovary versus other tissues.

Dataset	Technology	Total genes	Significant genes (p-value < 0.05)
Aneuploidy1	WES	18,327	401
Aneuploidy2	WES	18,976	374
TNFa	RNA-seq	13,478	823
Fly Transcriptome	Expression array	12,510	1,005

Table 1: Datasets

We use three network databases chosen based on their diversity in size and node-edge density ratio (Table 2). For the Aneuploidy1 and Aneuploidy2 datasets, we take our network to be the union of the STRING (Szklarczyk et al.; 2017), GIANT(v2) (Greene et al.; 2015; Wong et al.; 2018), and ConsensusPathDB (Herwig et al.; 2016) human GGI networks, as described in our previous studies (Sun et al.; 2022; Biswas et al.; 2024) and we abbreviate the network as **SGC**. For the TNFa dataset, we use the Database of Interacting Proteins (which we abbreviate as **DIP**) network (Xenarios et al.; 2000) because of its small size, high-confidence edges, and high performance in a gene set recovery task (see Section 5.2 for more details). For the Drosophila analysis we use a high-confidence subnetwork of Drosophila GGI from STRING that contains only interactions with a confidence score over 900, which means that they are supported by strong experimental or database evidence. We refer to this network as **STRING**.

3.3 Validation of AMI algorithms

Before we performed any validation on them, we sought to understand the basic characteristics of the AMI algorithms. We compared the size of the modules produced across the datasets (Figure 3), and see that the

PAPER

1. Network formed from candidate genes (red)

2. Model network as generative process

3. Compute posterior via MCMC to estimate modules

HotNet2

1. Heat diffuses

2. Find strongly connected components

DOMINO

1. Slicing

2. Relevant slices are refined based on active genes (red)

3. Active modules identified

FDRnet

1. Identify seeds (red)

2. For each seed s, find G_s to minimize $\phi(G_s)$ subject to

$$\frac{1}{|V(G_s)|} \sum_{v \in V(G_s)} \mathrm{fdr}(v) \leqslant B_2$$

Figure 1: **Overview of AMI algorithms.**

Four algorithms:
- PAPER
- DOMINO
- HotNet2
- FDRnet

Four datasets:
- Aneuploidy1
- Aneuploidy2
- TNFa
- Fly Transcriptome

1. Validation using a modified EMP

2. Earth Mover's Distance for similarity analysis

3. Spectral clustering on co-occurrence matrix

4. Greedy Conductance-based Merging (GCM)

Figure 2: **Project Workflow.**

Network	Number of genes/nodes	Number of interactions/edges	Edge density	Datasets used
SGC	18,113	604,629	3.68×10^{-3}	Aneuploidy1, Aneuploidy2
STRING	6,708	98,616	4.38×10^{-3}	Fly Transcriptome
DIP	3,054	5,024	1.07×10^{-3}	TNFa

Table 2: Network characteristics

different algorithms produce modules whose size distributions are quite different. PAPER and DOMINO tend to produce larger modules and have higher variation in modules sizes compared with HotNet2 and FDRnet. HotNet2 produces smaller modules (median size = 4) in much greater quantities (n = 300) than the other algorithms. FDRnet produces only 15 small modules (median size = 5) across all four datasets. The modules produced are recorded in Additional File 2: Table S1.

Figure 3: **Distribution of module sizes summed across all datasets.** n denotes total number of modules. Median is marked.

3.3.1 Validation using a modified Empirical Pipeline

We next sought to validate the modules we obtained, by determining which ones have a dataset-specific enrichment profile. To do this, we use a modification to the EMpirical Pipeline (EMP) framework proposed by Levi et al. (2021). First, we compute all the GO terms that pass a hypergeometric test with respect to each module. We refer to this set of GO terms as **HG terms**. Next, EMP performs a permutation-based null test where it permutes the gene activity scores in the dataset, runs the algorithm on the permuted datasets, and performs the same gene ontology enrichment analysis to generates a null distribution. We then fit a Generalized Pareto Distribution to the tail of the null distribution to obtain reliable estimates of the tail, and use this to reject any GO terms whose observed enrichment on the real dataset is sufficiently high. These are the *empirically-validated* terms or **EV terms** (see step 1 of Figure 2). The EHR is then defined as

$$\text{EHR} = \frac{\#(\text{EV terms across all modules})}{\#(\text{HG terms across all modules})}. \tag{1}$$

Intuitively, the EHR measures the specificity of an algorithm's output for a given dataset; high values indicate that the algorithm's output is more relevant to the dataset. The EHR for each algorithm and dataset is displayed in Table 3.

	Aneuploidy1	Aneuploidy2	TNFa	Fly Transcriptome
PAPER	0.167 (4/24)	0.000 (0/6)	0.080 (4/50)	0.439 (115/262)
DOMINO	0.000 (0/192)	0.017 (3/175)	0.266 (62/233)	0.356 (167/469)
HotNet2	0.012 (11/903)	0.009 (13/1501)	0.150 (25/167)	0.035 (32/923)
FDRnet	0.033 (1/30)	0.250 (2/8)	0.571 (20/35)	0.022 (1/45)

Table 3: **Empirically-Validated to Hypergeometric Ratio (EHR) values.** EHR value for each algorithm and dataset are followed by the number of EV and HG terms.

Figure 4: **mEHR distributions per algorithm and dataset.** "NE" (red bar) stands for no enrichment. Slashed bar with number indicates overflow.

While EHR provides a cohesive metric for the performance of an algorithm, biological insights are derived from the inspection of individual modules. Therefore, we also compute the mEHR by restricting the EV and HG terms to the module level. That is, for a given module,

$$\text{mEHR} = \frac{\#(\text{EV terms enriched in the module})}{\#(\text{HG terms enriched in the module})}.$$

We present the distribution of mEHR values across all modules for each algorithm and dataset in figure 4. Notably, algorithms can produce modules with an mEHR much higher than their overall EHR (see PAPER or HotNet2 on Fly Transcriptome).

3.4 AMI algorithms produce distinct outputs

Our validation showed that each algorithm produces at least some modules with a dataset-specific enrichment, but no single algorithm performs well across all datasets. Therefore, it is important to measure the similarity between the output modules. If they are very similar, running a single algorithm could suffice; otherwise using multiple algorithms may be necessary to provide a complete picture.

Figure 5: **Similar modules identified by different algorithms.** A: PAPER module and HotNet2 module in the Fly Transcriptome dataset, B: PAPER module and HotNet2 module in the Aneuploidy1 dataset, C: PAPER module and DOMINO module in the TNFa dataset.

To be sure that we only consider modules with a valid biological signal, we filtered out the modules that had an mEHR of 0 and choose to proceed only with the TNFa and Fly Transcriptome datasets, since very few valid modules were produced in the Aneuploidy1 and Aneuploidy2 datasets. The remainder of the analysis (Sections 2.4 and 2.5) will feature these datasets.

3.4.1 Earth mover's distance

To quantify the similarity between modules identified by the different algorithms, we use the earth mover's distance (EMD). The EMD is a way of measuring the distance between a pair of modules that take into account their distance on the network; it is thus more informative than the naive approach of computing the number of genes that overlap in the two modules. Intuitively, it is the minimum amount of work needed to move a unit of mass/earth (uniformly distributed on the genes) from one module to the other so that the genes of the other module are covered uniformly.

Definition 1 (Earth mover's distance). Let $\mathcal{G}$ be the global GGI network. Let $\text{dist}(v_i, v_j)$ be the distance of the shortest path between nodes $v_i, v_j \in V(\mathcal{G})$. Given modules M_1 and M_2 with n_1 and n_2 nodes, respectively, we say $\mathbf{C} \in [0, \infty)^{n_1 \times n_2}$ is a flow matrix if the row-sum of each row of $\mathbf{C}$ is $\frac{1}{n_1}$ and the column-sum of each column of $\mathbf{C}$ is $\frac{1}{n_2}$. Then, we define the earth mover's distance between modules M_1 and M_2 to be

$$d_{\text{EM}}(M_1, M_2) = \min_{\mathbf{C} \text{ flow matrix}} \sum_{i=1}^{n_1} \sum_{j=1}^{n_2} \mathbf{C}_{ij} \cdot \text{dist}(v_i, v_j).$$

Intuitively, entry $\mathbf{C}_{ij}$ is the amount of mass that flows from node i to node j, so the EMD is small when modules share genes that are close in the network, and large when the genes in the modules are far apart on the network. Therefore, it captures the similarity of modules, even when they share little or no overlap.

By computing the pairwise EMDs between modules, we can identify similar modules. In the fly transcriptome dataset, we identified two modules with EMD 2.2 that are not overlapping and not even adjacent, but still close to one another (separated by one gene, Figure 5A). In the Aneuploidy1 dataset we identify two modules with EMD 2.214 that are adjacent (Figure 5B). In the TNFa dataset we identify two modules with multiple overlapping genes with an EMD of 0.529 (Figure 5C). Gene names for each module can be found in Additional File 2: Table S1.

Computing similar modules can also uncover *hidden* genes, which are biologically relevant but do not appear in modules or datasets. For example, in Figure 5A, we identify *Chrac-14* (Chromatin accessibility complex 14kD protein, colored in gray) as the shortest path between the two modules. Notably, *Chrac-14* is not present in the Fly Transcriptome dataset. In section 4.2, we address the biological significance of this discovery.

To compare the similarity between the two sets of modules outputted by two different algorithms, we propose two approaches of extending the EMD: one based on matching and one based on sums of minimums. The matching similarity, given in Definition 2, computes a one-to-one matching between the two sets of

Figure 6: **Heatmap representations of similarity matrices for each dataset.** Darker colors indicate higher similarity. The upper diagonal represents the matching similarity (Definition 2) and the lower diagonal represents the sum similarity (Definition 3).

modules (from the smaller set to the larger set) such that sum of the EMDs between the matched pairs is minimized. We then take the sums of the EMDs and apply the function $x \mapsto \frac{1}{1+x}$ obtain a similarity measure that takes value in $[0, 1]$. Two identical sets of modules would have a matching similarity of 1. We give the mathematical formulation below:

Definition 2 (Matching Similarity). Let $\mathcal{G}$ be the global GGI network, and two sets of modules $\mathcal{M}^1 = \{M_1^1, \ldots, M_n^1\}$ and $\mathcal{M}^2 = \{M_1^2, \ldots, M_m^2\}$, where we assume without loss of generality that $n \leqslant m$. Define $S_{n,m}$ to be the set of one-to-one mappings from $\{1, 2, \ldots, n\}$ to $\{1, 2, \ldots, m\}$. The *matching similarity* between $\mathcal{M}^1$ and $\mathcal{M}^2$ is then

$$\operatorname{sim}_M(\mathcal{M}^1, \mathcal{M}^2) := \left(1 + \min_{\tau \in S_{n,m}} \sum_{j=1}^n d_{\mathrm{EM}}(M_j^1, M_{\tau(j)}^2)\right)^{-1}.$$

One drawback of matching similarity is that it can be misleading when one algorithm outputs many more modules than the other. We therefore also propose a similarity measure using sums of minimum distances (Definition 3). Here, we sum the minimum EMD from each module in one set to any of the modules in the other set to give another notion of distance between the two sets of modules. We then convert it into a similarity measure via the mapping $x \mapsto \frac{1}{1+x}$ in the same way as the before.

Definition 3 (Sum Similarity). Let $\mathcal{G}$ be the global GGI network, and two sets of modules $\mathcal{M}^1 = \{M_1^1, \ldots, M_n^1\}$, $\mathcal{M}^2 = \{M_1^2, \ldots, M_m^2\}$. The *sum similarity* between $\mathcal{M}^1$ and $\mathcal{M}^2$ is

$$\operatorname{sim}_S(\mathcal{M}^1, \mathcal{M}^2) := \left(1 + \frac{1}{2}\left\{\sum_{j=1}^n \min_{M \in \mathcal{M}^2} d_{\mathrm{EM}}(M_j^1, M) + \sum_{k=1}^m \min_{M \in \mathcal{M}^1} d_{\mathrm{EM}}(M_k^2, M)\right\}\right)^{-1}.$$

We computed the algorithm similarity for each of the datasets using both algorithms and present the results in Figure 6. The average matching-based similarity score (averaged across all pairs of algorithms) is 0.148 and the average sum-based similarity score is 0.033, which suggests that overall outputs of the algorithms are distinct although they may share a few similar modules.

3.5 Combining results across algorithms

Our similarity analysis suggests that the algorithms tend to identify distinct biological signals, which motivates the use of multiple algorithms in order to capture the biological signal more completely. To facilitate the integration of results from multiple algorithms, we introduce two complementary methods for combining their outputs.

3.5.1 Module aggregation with spectral clustering

First, we introduce a spectral clustering method that identifies groups of genes consistently assigned to the same module across multiple algorithms.

Given sets of modules $\mathcal{M}^{(1)}, \ldots, \mathcal{M}^{(K)}$, let $V = \cup_{k=1}^{K} \cup_{M \in \mathcal{M}^{(k)}} M$ be the set of unique genes that appear in them; we write $n := |V|$ and $V = \{v_1, \ldots, v_n\}$ using an arbitrary ordering on the genes. We define the n by n gene co-occurrence matrix C entrywise for genes v_i and v_j by

$$C_{ij} = \sum_{k=1}^{K} \mathbb{1}\{\exists M \in \mathcal{M}^k : v_i, v_j \in M\}.$$

In other words, C_{ij} is the number of times v_i and v_j are assigned to the same module. We performed spectral clustering using this matrix, more details of the method are provided in Section 5.6.

In our analysis, we excluded any modules disjoint from every other module. The clustering resulted in 5 clusters for the TNFa dataset, and 13 clusters for the Fly Transcriptome dataset (Figure 7). Notably, one cluster in the TNFa dataset shows significant consensus between all four algorithms (Figure 8).

Figure 7: **Heatmap representations of module aggregation.** The first four columns each represent the individual co-occurence matrices of PAPER, DOMINO, HotNet2, and FDRnet respectively. The fifth column is the sum of the heatmaps. The top left corner contains a cluster made up of modules from all four algorithms in the TNFa dataset.

3.5.2 Module merging using conductance

One drawback of spectral clustering is that it is not very informative if there is little overlap among the algorithms (see Fly Transcriptome in Figure 7). However, modules can be biologically related even without direct overlap. To address this limitation, we introduce the Greedy Conductance-based Merging (**GCM**) algorithm. GCM greedily merges modules based on their *conductance*, which measures how well-formed a given module is. The definition follows:

Definition 4. The *conductance* of a module M is

$$\varphi(M) := \frac{c}{2m + c},$$

where c is the number of edges on the boundary of M, and m is the number of edges in the interior of M.

Figure 8: **Module cluster in the TNFa dataset,** identified by the module aggregation method, as shown in figure 7. Genes with multiple colors belong to multiple modules. Notably, this cluster is not identified by the conductance merging algorithm (Algorithm 1).

The conductance of a module is minimized when m is large and c is small, a desirable quality of modules.

Definition 5. The *conductance ratio* between two modules M_1 and M_2 is

$$\rho(M_1, M_2) := \frac{\varphi(M_1 \cup M_2)}{\min\{\varphi(M_1), \varphi(M_2)\}}.$$

We choose to merge modules M_1 and M_2 when $\rho(M_1, M_2) \leqslant 1$ so that

$$\varphi(M_1 \cup M_2) \leqslant \min\{\varphi(M_1), \varphi(M_2)\},$$

meaning the resultant merged module is at least as well-contained as the better of the two original modules. Note that modules need not have any overlap to have a conductance ratio less than 1; thus, this merging condition can be thought of as weaker requirement than using direct overlap of modules.

At each iteration of the GCM algorithm, we find a suitable pair of modules $M_{i^*}^{k^*}$ and $M_{\ell^*}^{j^*}$ that minimizes the conductance ratio. Then, we merge them and remove the merged modules from consideration in the next iteration. However, we allow merged modules (already containing other component modules) to be merged again with modules from algorithms not already contained in the module. We set the conductance ratio of all modules contained in algorithms already merged to ∞, forbidding two modules from the same algorithm to be merged. This ensures that the merged output $\mathcal{M}^*$ has several desirable properties:

1. Every module in the input appears exactly once, either by itself or as a component in a merged module. Specifically, if M is an input module then $M \subset M^*$ for exactly one $M^* \in \mathcal{M}^*$.

2. Each module in $\mathcal{M}^*$ contains at most one module from any given algorithm, i.e. for any $M^* \in \mathcal{M}^*$ and M_1, M_2 input modules from the same algorithm, we have $M_1 \subset M^*$ implies $M_2 \cap M^* = \varnothing$.

Figure 9: **Venn diagrams to visualize GCM.** Overlap indicates modules merged together.

After running GCM on the resultant modules of each of the algorithms, we identify several merged modules (Figure 9). Notably, we group module 6 of DOMINO with module 1 of FDRnet as in the module aggregation procedure, but we do not group module 0 of PAPER with it (Additional File 4: Table S3). WE also identify more clusters (TNFa: 5, Fly Transcriptome: 9) despite the lack of overlap of genes.

4   Discussion

AMI algorithms are fundamentally important to the analysis of biological networks, but their comparative performance, especially for algorithms based on different design principles, is still poorly understood. In this study, we systematically evaluated the performance of four AMI algorithms - PAPER, DOMINO, HotNet2, and FDRnet - across diverse biological datasets and network types. These four recent algorithms used four different types of module identification approaches: including Bayesian modeling (PAPER), modularity minimization (DOMINO), network diffusion (HotNet2), and constrained optimization (FDRnet). Our analysis reveals that AMI algorithms perform inconsistently on different datasets, but they still produce modules with specific enrichment. Our application of the Earth Mover's Distance shows that algorithms play complementary roles, suggesting that the use of multiple algorithms for a given dataset could be beneficial. Finally, to streamline the joint analysis of multiple algorithms, we introduce a conductance merging algorithm that merges modules with similar network structures.

4.1   AMI algorithms capture sparse and complementary signals

Algorithms with a low EHR can still produce modules with a non-zero mEHR (for example HotNet2 on the Fly Transcriptome dataset). Also, the pairwise similarity between algorithms was consistently low (Figure 6). These facts implies that, each algorithm captures a sparse but valid subset of the biological signal, and that these subsets do not substantially overlap. Therefore, relying on a single algorithm, even if it performs well, can potentially lead to a loss of information available to other algorithms. This challenges current literature and common practice, which often recommends the use of a single "best" algorithm.

4.2   Computing similar modules using EMD can uncover hidden genes

Determining similar modules can aid the biological interpretation of them. For example, the module pair in Figure 5A play complementary roles in chromatin regulation. In the PAPER module, *Ada2b* and *WDA* are parts of the SAGA (Spt-Ada-Gcn5-Acetyltransferase) complex that contribute to histone acetylation (Soffers et al.; 2021). *D12* also plays a role as part of the ATAC complex, which stimulates nucleosome sliding (Suganuma et al.; 2012). Together, they act as a mechanism to promote gene expression. Meanwhile, the HotNet2 module contains *ACF*, which contributes to the establishment of a ground state of chromatin

(Scacchetti et al.; 2018) as well as *CtBP* which acts as a transcriptional corepressor (Chinnadurai; 2000-2013). As a module, they establish repressive chromatin states.

One interesting aspect of identifying similar modules is that it can also reveal relevant genes not present in the modules. For example, for modules in Figure 5A, *Chrac-14* (shown in gray) acts as the shortest path between the PAPER and HotNet2 modules. Notably, *Chrac-14* is not present in the Fly Transcriptome dataset (it appears only in the STRING network). Therefore, it acts as a *hidden* gene: it was not directly implicated by the original experimental data but is revealed through the network topology to potentially play an important role in connecting functional modules. Functionally, *Chrac-14* participates in DNA repair and chromosomal DNA replication. As a member of the chromatin accessibility complex, it facilitates nucleosome sliding, which plays a role in DNA damage response (FlyBase; 2019). Therefore, it plays an important role in accurate chromosome segregation. Errors in chromosome segregation are shown to be a major cause of aneuploidy (Smith and Nambiar; 2020).

4.3 Different grouping methods can be used in different scenarios

The spectral aggregation and conductance merging algorithms provide alternative approaches to module grouping that are valuable in different contexts. When the modules in consideration have little overlap, the spectral clustering algorithm can be uninformative (see Figure 7 for Aneuploidy1, Aneuploidy2, and Fly Transcriptome datasets). However, since the conductance merging algorithm permits merges of neighboring modules in addition to overlapping modules, it can still give informative results. On the other hand, spectral aggregation can be more informative when there is greater overlap: the module cluster shown in Figure 8 is not identified by the conductance merging algorithm (Figure 8). Researchers should therefore select the spectral clustering algorithm if there is high overlap, and the conductance merging algorithm if this condition does not hold.

4.4 FDRnet favors statistical significance over network structure

Both FDRnet and the conductance merging algorithm seek to optimize the conductance of the participant modules. In particular, we note that the merging algorithm also merges the modules of FDRnet. This means the merging algorithm introduces genes to the FDRnet modules that improve its conductance (and therefore modular structure), but that make the average FDR of the module too high to include. This suggests that FDRnet's strict adherence to FDR thresholds may come at the cost of excluding structurally relevant genes.

4.5 Merging algorithms could help overcome parameter selection

A significant challenge in using AMI algorithms is the parameter selection. For example, FDRnet depends primarily on a B parameter that controls the local FDR threshold of the modules produced. Even though this parameter can greatly influence the output modules, its selection can be arbitrary. Selecting optimal parameters is often done empirically through trial and error, which can be time-consuming.

The conductance merging (Algorithm 1) and the spectral aggregation method (Section 3.5.1) we propose can be used to overcome this issue. We suggest running the same algorithm with different parameters, and then using these methods to consolidate the outputs. This would reduce the dependency on parameter tuning, since modules that appear consistently across parameter settings are more likely to represent genuine biological signals. It also provides a measure of confidence in the identified modules, since those that emerge from a wide range of parameter settings can be considered more reliable. Future work could explore the usage of these methods to further overcome parameter selection.

4.6 Generalizations beyond GO enrichment and gene networks

The work we present here uses GO enrichment to assess module quality, but our approach is not limited to this evaluation metric. The validation pipeline we used can be easily modified to support other enrichment analysis matrix, such as Canonical Pathways or Hallmark Gene Sets from MSigDB (Subramanian et al.; 2005; Liberzon et al.; 2015), and KEGG Pathway annotations (Kanehisa and Goto; 2000). These alternative procedures emphasize different aspects of biological function, and thus can reveal dataset-specific enrichments that GO alone cannot capture. We delegate this exploration to future studies.

More broadly, the framework we developed (EMD similarity analysis, spectral aggregation, GCM) relies only on network data and module assignments, and does not necessarily require genetic data. Therefore, these methods could be applied to any domain where module or community detection is relevant, such as protein-protein interaction networks, metabolic networks, or social networks. Thus, the methods we have developed will be generally useful to researchers working with network-based clustering methods.

4.7   Comparisons and Limitations

Previous works that introduce an AMI algorithm usually demonstrate that the algorithm outperforms other algorithms (e.g., Levi et al. (2021); Yang et al. (2021)) across all datasets. Our evaluation using multiple algorithms and datasets suggests that AMI algorithms perform inconsistently across the different datasets, which challenges the "one-size-fits-all" paradigm.

Some studies (e.g., Boyd et al. (2023); Pasquier et al. (2023)) use strict overlap between modules as a way to determine the similarity of the algorithms. This method is not informative between modules that do not overlap, since they can be close or far apart. We use the EMD as a way to improve on this analysis, since the EMD is more sensitive to the overall structure of the network and provides useful information even when the modules are disjoint. Furthermore, to our knowledge, there are no studies that introduce ways to aggregate results of different outputs. We provide a greedy aggregation method for researchers who run multiple AMI algorithms and prefer one set of final modules for downstream analyses.

Our study has a few limitations. One limitation of this study is that each dataset is run only on a single GGI network. Previous studies show that many AMI algorithms do not learn from the input biological network, since they are equally capable of producing biologically relevant modules, even on random networks with the same degree distribution (Lazareva et al.; 2021). One way to control for this is to run each dataset on multiple networks, and do a cross-network comparison. On the other hand, the performance of the algorithms on the TNFa dataset (Table 3) seems to suggest that its higher-confidence edges lead to more dataset-specific results, which is counter to what is proposed in the study.

We were also unable to fine-tune the parameters of all the algorithms analyzed due to the long runtimes of EMP. This could potentially bias algorithms that are less sensitive to tuning or have ways to estimate parameters, such as HotNet2, as opposed to those that have arbitrarily selected parameters such as FDRnet.

Furthermore, our analysis primarily focuses on network topology as opposed to enrichment. We choose to do this because it is more informative for purposes other than enrichment, such as the identification of hidden genes or other important modules. Future studies could address this and provide a comprehensive analysis of similarity in terms of GO enrichment.

4.8   Conclusions and Future Directions

In conclusion, our evaluation of AMI algorithms reveals their complementary nature in the GGI network analysis. Our application of the EMD suggests that many algorithms capture different biological signals, and that multiple methods should be used to create a more complete picture. To integrate the results, we propose a conductance merging algorithm that offers a principled approach to combining outputs of these different methods. These contributions advance our understanding of AMI algorithms and how they should be used, and provides practical tools to further their analysis.

Beyond GGI network, the module merging algorithm we developed can also be used to analyze the outputs of any community detection or AMI algorithms on a given dataset. Because it only takes the full network and resultant modules as an input, its application is not limited to biological networks. To allow for further testing and more detailed investigation, we made our code freely available at `https://github.com/LiuJO/AMI-Benchmark/`.

5   Methods and Materials

5.1   Datasets

Candidate genes and associated p-values from datasets **Aneuploidy1** (Biswas et al.; 2024), **Aneuploidy2**, (Tyc et al.; 2020), and **TNFa** (Madsen et al.; 2015) were obtained from previous studies, respectively. For **Fly Transcriptome**, gene expression profiles in fly tissues were obtained from `http://flyatlas.org/data.html`,

(Chintapalli et al.; 2007). Unknown, non-protein coding, RNA, and ribosomal proteins were removed from the gene set. Enrichment values for the ovary were calculated as the ratio of ovary-specific expression to the mean expression across all tissues. Statistical significance was assessed using a one-tailed t-test to identify genes upregulated in the ovary. Multiple-testing correction was applied through Bonferroni adjustment of p-values. Genes with adjusted p-value < 0.05 are considered significant.

5.2 Networks

SGC: STRING integrates multiple data types including experimental data, pathway databases, and literature co-occurrence to create confidence-scored functional interactions. GIANT(v2) provides tissue-specific functional networks, while ConsensusPathDB integrates interaction data from 31 public databases to provide a comprehensive interaction landscape. For the network construction, we integrated and filtered interactions from all three databases using previously established methods (Sun et al.; 2022; Cao et al.; 2021). The network was built using custom Python software available at `https://github.com/JXing-Lab/network-ppi`.
DIP: The second network is the Database of Interacting Proteins (DIP), which is much smaller than the other networks (with 3,000 genes and 5,000 interactions) but maintains a higher confidence of edges. Specifically, it provides the highest value per interaction when correcting for network size (Huang et al.; 2018). The *value* is defined to be the network's improvement in the *gene set recovery task* compared to random networks of the same degree distribution, where a subset of genes is selected from a disease-associated gene set, and network propagation (see HotNet2 algorithm) is used to recover the ground-truth set. The network was retrieved from `https://dip.doe-mbi.ucla.edu/dip`.
STRING (fly): The Drosophila melanogaster network was derived from the STRING database (version 12), which contains 5,033,960 total interactions. Each interaction is scored between 0 and 999 according to a systematic benchmarking process against KEGG pathway maps. Note that each score does not indicate the strength of the interaction, but instead confidence. We select edges with a score above 900, meaning roughly 1 out of 10 interactions might be incorrect (Szklarczyk et al.; 2017).

5.3 Validation of GO Terms

To validate the algorithms using EMP, we implemented each algorithm as a class that can be directly used for EMP; it is accessible at `https://github.com/LiuJO/AMI-Benchmark`. The EMP code was originally retrieved from `https://github.com/Shamir-Lab/EMP`.

In our analysis, we found that EMP produces an EHR that is not properly calibrated. Under the null hypothesis (that no true signal exists), we expect that the EHR should be close to the significance threshold α. To test this, we treat a permuted dataset as real and compute the EHR, using the remaining permuted datasets as the null. Averaging the EHR across all permutations, we find that it is much higher than α. For example, the null EHR for PAPER on the Aneuploidy1 dataset was 0.452 when $\alpha = 0.05$. For more details, see Additional File 3: Table S2.

This miscalibration arises because in the real dataset, only HG-enriched GO terms are tested, but the null distribution is constructed from *all* permutations (including those that aren't HG enriched). The natural fix to this is to construct the null distribution of a given GO term from only permutations that are HG-enriched for that GO term. However, many GO terms are HG-enriched in only a small number of permutations, so that we cannot reliably compute p-values.

To overcome this, when constructing empirically validated GO terms, we apply a more strict multiple testing correction (Benjamini—Hochberg) with respect to the set of all the GO terms. To ensure that the more stringent correction does not overwhelm all the signal, we obtain more fine-grained p-values by estimating the tail of the distribution via fitting a Generalized Pareto Distribution, following Knijnenburg et al. (2009). In contrast to the previous method, this method is properly calibrated: the null EHR is below $\alpha = 0.05$ across all datasets. The procedure follows:

1. Generate $N = 1000$ permuted datasets. Run the AMI algorithm on each of the permuted datasets. Run the algorithm on the true (unpermuted) dataset.

   1.1. For each GO term g and $n \in [N]$, let $Z_g^{(n)}$ be the maximal enrichment of g across all modules obtained in permutation b. Let Z_g^{obs} be the maximal enrichment of g across all modules obtained

from the true dataset.

2. Using `scipy`, fit a Generalized Pareto Distribution with parameters μ, σ, ξ to the empirical conditional excess function

$$\hat{F}_g^{(u)}(y) = \frac{\hat{F}_g(u + y) - \hat{F}_g(u)}{1 - \hat{F}_g(u)}$$

where $\hat{F}_g(u) := \frac{1}{N} \sum_{n=1}^{N} \mathbb{1}\{Z_g^{(n)} \leqslant u\}$ is the empirical distribution function and u is the 90-th percentile

$$u := \inf \left\{ x \in \mathbb{R} : \frac{1}{n} \sum_{n=1}^{N} \mathbb{1}\{Z_g^{(n)} \leqslant x\} \geqslant 0.9 \right\}.$$

Let $\hat{\mu}, \hat{\sigma}, \hat{\xi}$ be the parameters obtained from fitting.

3. Define

$$h_g(z) = \begin{cases} (1 - \hat{F}_g(u)) \left(1 + \frac{\hat{\xi}(z - u - \hat{\mu})}{\hat{\sigma}}\right)^{-1/\hat{\xi}} & z \geqslant u \\ 1 - \hat{F}_g(z) & z < u \end{cases} \tag{4.3.1}$$

and define the p-value for g to be $\mathsf{P}_g := h_g(Z_g^{\text{obs}})$.

4. Let $\mathcal{R}$ be the set of rejections obtained by using the Benjamini-Hochberg procedure on $\{\mathsf{P}_g\}_g$.

5. Output $\text{EV} = \mathcal{R} \cap \{g : Z_g^{\text{obs}} \text{ passes the HG test}\}$.

Steps 2 and 3 were originally described in (Knijnenburg et al.; 2009), and can be justified by the Pickands-Balkema-de Haan theorem, which says that, as $u \to \infty$, $F_g^{(u)}(y)$ behaves like a Generalized Pareto Distribution, where $F_g^{(u)}$ is defined by the rule

$$F_g^{(u)}(y) = \frac{F_g(u + y) - F_g(u)}{1 - F_g(u)} = \mathbb{P}(Z_g - u \leq y \mid Z_g > u).$$

Then, (4.3.1) comes from plugging in our empirical estimates into the equation

$$\mathbb{P}(Z_g \geqslant t) = \mathbb{P}(Z_g \geqslant u)\mathbb{P}(Z_g \geqslant t \mid Z_g \geqslant u) = (1 - F_g(u))(1 - F_g^{(u)}(t - u)).$$

5.4 Algorithm implementations

We implemented the algorithms as follows:
PAPER: PAPER was originally implemented as a community detection algorithm (i.e., for networks without weights). To implement it as an AMI algorithm, we also weigh the edges by the rule $\mathbf{e}(v_i v_j) = \sqrt{\mathbf{v}(v_i)\mathbf{v}(v_j)}$ where $\mathbf{v} : V(\mathcal{G}) \to [0, 1]$ is the node weight, and $v_i, v_j \in V(\mathcal{G})$. We construct a subnetwork using the genes and edges with a weight less than some parameter (typically 0.05). Then, we identify the largest connected component and run PAPER on it. On the true dataset, we run PAPER with parameters M=5000, `Burn=1000`. Because it is expensive to use such resources for the computation of each permutation, we use parameters M=400, `Burn=10` for the permutations. In both cases, we set `size_thresh=0.02`, `birth_thresh=0.6`. Parameters were tuned empirically. Modules of size smaller than 3 were discarded to be consistent with the other algorithms. Code was retrieved from `https://github.com/nineisprime/PAPER`.
DOMINO: We run DOMINO with its default parameters (`slice_threshold=0.3`, `module_threshold=0.05`). Code was retrieved from `https://github.com/Shamir-Lab/DOMINO`.
HotNet2: HotNet2 depends on δ and β parameters. We used the provided parameter estimation scripts in `https://github.com/raphael-group/hotnet2` to determine δ and β. As HotNet2 takes in heat scores as its input, we compute them from the p-values using the rule $p \mapsto -\log_{10}(p)$. Because HotNet2 is very expensive to run, we pre-compute the network files. Modules of size smaller than 3 were discarded.
FDRnet: FDRnet depends primarily on the FDR bound parameter B. Since EMP requires the algorithm to be run on a large number of times on the permuted datasets, we modify it to be more efficient. Specifically,

we give FDRnet B_1 and B_2 parameters. Seeds are genes with an FDR less than B_1, and the subnetwork optimization problem instead requires that the subnetwork $\mathcal{G}_s^*$ be such that

$$\frac{1}{V(\mathcal{G}_s^*)} \sum_{v \in V(\mathcal{G}_s^*)} \text{fdr}(v) < B_2.$$

B_1 is chosen to be smaller than B_2 so that seeds of a higher FDR are not chosen in the subnetwork constraint problem. However, they can still appear in other significant subnetworks. On most datasets, we take $B_1 = 0.1$ and $B_2 = 0.3$. B_2 is chosen to be quite large because FDRnet tends to produce too few modules to meaningfully compare on more stringent thresholds. Modules of size smaller than 3 were discarded. Code was retrieved from `https://github.com/yangle293/FDRnet`.

5.5 Earth Mover's Distance

The EMD can naturally be formulated as a linear programming problem, according to its definition. Given a network $\mathcal{G}$ and two modules M_1 and M_2 whose vertices are $\{u_1, \ldots, u_{n_1}\}$ and $\{v_1, \ldots, v_{n_2}\}$ respectively, we seek to

$$\text{minimize}_{\{c_{ij}\}} \quad \sum_{i \in [n_1]} \sum_{j \in [n_2]} \text{dist}(v_i, v_j) \cdot c_{ij}$$

$$\text{subject to} \quad \sum_{j \in [n_2]} c_{ij} = \frac{1}{n_2} \quad \forall i \in [n_1]$$

$$\sum_{i \in [n_1]} c_{ij} = \frac{1}{n_1} \quad \forall j \in [n_2]$$

$$c_{ij} \geqslant 0 \quad \forall i \in [n_1], j \in [n_2]$$

where $\text{dist}(\cdot, \cdot)$ is computed by Dijkstra's algorithm. The optimization variables c_{ij} represent the flow from u_i to v_j. The optimization is solved separately for each pair of modules being compared. `PuLP` (version `2.9.0`) for Python `3.10.2` was used to solve the optimization problem.

5.6 Spectral Clustering

Given the gene-gene coocurence matrix C, we define the degree matrix D as a diagonal matrix whose entries are

$$D_{ii} = \sum_{j=1}^{n} C_{ij}.$$

We note that C is a symmetric matrix. We then perform spectral clustering on the normalized Laplacian

$$L = I - D^{-1/2} C D^{-1/2}.$$

We estimate the number of clusters using the eigengap heuristic. Specifically, let $0 = \lambda_1 \leqslant \lambda_2 \leqslant \cdots \leqslant \lambda_n$ be the eigenvalues of L arranged in nondecreasing order. We set the number of clusters to be

$$k^* := \underset{2 \leqslant i \leqslant n-1}{\arg\max} |\lambda_i - \lambda_{i+1}|.$$

A visualization of the eigenvectors in each dataset is shown in Figure 10. We obtain the clustering as follows: let $\mathbf{v}_1, \ldots, \mathbf{v}_{k^*}$ be the eigenvectors of L corresponding to $\lambda_1, \ldots, \lambda_{k^*}$. Let $U = [\mathbf{v}_1 \ \mathbf{v}_2 \cdots \mathbf{v}_{k^*}] \in \mathbb{R}^{n \times k^*}$ be the matrix whose columns are the eigenvectors. The row-normalized matrix T is given by

$$T_{ij} = \frac{1}{U_{ij}} \sqrt{\sum_{j=1}^{k^*} U_{ij}^2}.$$

Viewing each row in T as an element of $\mathbb{R}^{k^*}$, we apply k-means with default parameters, which selects initial cluster centers to be distant from each other, and runs the algorithm for a maximum of 300 iterations or until convergence within a tolerance of 10^{-4}. We used `scikit-learn` (version `1.5.1`) for Python `3.10.2`.

Figure 10: **Eigenvalues of the normalized Laplacian for each dataset.** We choose the number of clusters to be the index of the eigenvalue that maximizes the difference in consecutive eigenvalues. We set $k^* = 5, 13$ for TNFa and Fly Transcriptome, respectively.

5.7 GCM

We provide a detailed description of the GCM algorithm in Algorithm 1.

6 Declarations

6.1 Ethics approval and consent to participate

Not applicable.

6.2 Consent for publication

Not applicable.

6.3 Availability of data and materials

All datasets used in this study are either publicly available or can be accessed through the repositories listed in the Methods section. Code is available at `https://github.com/LiuJO/AMI-Benchmark`.

6.4 Competing interests

The authors declare that they have no competing interests.

6.5 Authors' contributions

MX and JX conceptualized the project and designed the overall strategy. JL developed and implemented the algorithms, performed data analysis, and wrote the manuscript. All authors revised and approved the final manuscript.

6.6 Acknowledgements

This study was partially supported by the National Institute of General Medical Sciences (NIGMS) (R01GM157610 to MX and JX), the National Science Foundation (DMS-2113671 to MX), and a grant from the Office of the Vice Provost for Research, Rutgers–New Brunswick. JL was partially supported by the David and Dorothy Bernstein Endowed Scholarship. The content is solely the responsibility of the authors and does not necessarily represent the official views of the Office of the Vice Provost for Research.

Algorithm 1 Greedy Conductance-based Merging (GCM)

INPUT: Global GGI network $\mathcal{G}$, collection of sets $\mathcal{M}^1, \ldots \mathcal{M}^K$ where each $\mathcal{M}^k$ is a set of modules
OUTPUT: Merged set of modules $\mathcal{M}^*$

1: Initialize $\mathcal{M}^{K+1} \leftarrow \varnothing$.
2: For all $k, \ell \in \{1, 2, \ldots, K\}$ such that $k < \ell$, initialize $R^{k\ell} : \mathcal{M}^k \times \mathcal{M}^\ell \rightarrow [0, \infty)$ as

$$R^{k\ell}(M_i^k, M_j^\ell) = \rho(M_i^k, M_j^\ell) \text{ for } M_i^k \in \mathcal{M}^k \text{ and } M_j^\ell \in \mathcal{M}^\ell . \tag{2}$$

3: **while true do**
4:    Let $M_{i*}^{k^*}$ and $M_{j*}^{\ell^*}$ be $\arg\min\{R^{k\ell}(M_i^k, M_j^\ell) : M_i^k \in \mathcal{M}^k, M_j^\ell \in \mathcal{M}^\ell, k, \ell \in \{1, 2, \ldots K+1\}, k < \ell\}$.
5:    **if** $R^{(k^*\ell^*)}(M_{i*}^{k^*}, M_{j*}^{\ell^*}) > 1$ **then break**
6:    Let $M^{\text{new}} = M_{i*}^{k^*} \cup M_{j*}^{\ell^*}$ and add M^{new} to $\mathcal{M}^{K+1}$
7:    Remove $M_{i*}^{k^*}$ from $\mathcal{M}^{k^*}$ and $M_{j*}^{\ell^*}$ from $\mathcal{M}^{\ell^*}$.
8:    Update $\{R^{k\ell}\}$ via (2).
9:    **if** $\ell^* \neq K+1$ **then**
10:        For all $k \in \{1, 2, \ldots, K\}$, for $M \in \mathcal{M}^k$, set

$$R^{k,K+1}(M, M^{\text{new}}) = \begin{cases} \infty & \text{if } k = k^* \text{ or } k = \ell^* \\ \rho(M, M^{\text{new}}) & \text{otherwise.} \end{cases}$$

11:    **else**
12:        For all $k \in \{1, 2, \ldots, K\}$, for $M \in \mathcal{M}^k$, set

$$R^{k\ell^*}(M, M^{\text{new}}) = \begin{cases} \infty & \text{if } k = k^* \text{ or } R^{k\ell^*}(M, M_{j*}^{\ell^*}) = \infty \\ \rho(M, M^{\text{new}}) & \text{otherwise.} \end{cases}$$

13: Output $\cup_{k=1}^{K+1} \mathcal{M}^k$.

References

Baxter, S. M., Posey, J. E., Lake, N. J., Sobreira, N., Chong, J. X., Buyske, S., Blue, E. E., Chadwick, L. H., Coban-Akdemir, Z. H., Doheny, K. F., Davis, C. P., Lek, M., Wellington, C., Jhangiani, S. N., Gerstein, M., Gibbs, R. A., Lifton, R. P., MacArthur, D. G., Matise, T. C., Lupski, J. R., Valle, D., Bamshad, M. J., Hamosh, A., Mane, S., Nickerson, D. A., Centers for Mendelian Genomics Consortium, Rehm, H. L. and O'Donnell-Luria, A. (2022). Centers for Mendelian Genomics: A decade of facilitating gene discovery, *Genetics in Medicine* **24**(4): 784–797.

Biswas, L., Tyc, K. M., Aboelenain, M., Sun, S., Dundović, I., Vukušić, K., Liu, J., Guo, V., Xu, M., Scott, R. T., J., Tao, X., Tolić, I. M., Xing, J. and Schindler, K. (2024). Maternal genetic variants in kinesin motor domains prematurely increase egg aneuploidy, *Proc Natl Acad Sci U S A* **121**(45): e2414963121.

Boyd, S. S., Slawson, C. and Thompson, J. A. (2023). Amend: active module identification using experimental data and network diffusion, *BMC Bioinformatics* **24**(1): 277.
   URL: *https://doi.org/10.1186/s12859-023-05376-z*

Cao, X., Zhang, Y., Abdulkadir, M., Deng, L., Fernandez, T. V., Garcia-Delgar, B., Hagstrøm, J., Hoekstra, P. J., King, R. A., Koesterich, J., Kuperman, S., Morer, A., Nasello, C., Plessen, K. J., Thackray, J. K., Zhou, L., Tourette International Collaborative Genetics Study (TIC Genetics), Dietrich, A., Tischfield, J. A., Heiman, G. A. and Xing, J. (2021). Whole-exome sequencing identifies genes associated with tourette's disorder in multiplex families, *Mol. Psychiatry* **26**(11): 6937–6951.

Chinnadurai, G. (2000-2013). Ctbp family proteins: Unique transcriptional regulators in the nucleus with diverse cytosolic functions, *Madame Curie Bioscience Database*, Landes Bioscience, Austin (TX). Available

from: https://www.ncbi.nlm.nih.gov/books/NBK6557/.
URL: *https://www.ncbi.nlm.nih.gov/books/NBK6557/*

Chintapalli, V. R., Wang, J. and Dow, J. A. T. (2007). Using flyatlas to identify better drosophila melanogaster models of human disease, *Nature Genetics* **39**(6): 715–720.
URL: *https://doi.org/10.1038/ng2049*

Crane, H. and Xu, M. (2024). Root and community inference on the latent growth process of a network, *Journal of the Royal Statistical Society: series B (statistical methodology)* **86**: 825–865.

FlyBase (2019). Gene snapshot: Chrac-14 [fbgn0043002], Retrieved from `https://flybase.org/reports/FBgn0043002`. Date last reviewed: 2019-03-21.

Greene, C. S., Krishnan, A., Wong, A. K., Ricciotti, E., Zelaya, R. A., Himmelstein, D. S., Zhang, R., Hartmann, B. M., Zaslavsky, E., Sealfon, S. C., Chasman, D. I., FitzGerald, G. A., Dolinski, K., Grosser, T. and Troyanskaya, O. G. (2015). Understanding multicellular function and disease with human tissue-specific networks, *Nat. Genet.* **47**(6): 569–576.

Herwig, R., Hardt, C., Lienhard, M. and Kamburov, A. (2016). Analyzing and interpreting genome data at the network level with ConsensusPathDB, *Nat. Protoc.* **11**(10): 1889–1907.

Hu, H., Huff, C. D., Moore, B., Flygare, S., Reese, M. G. and Yandell, M. (2013). VAAST 2.0: improved variant classification and disease-gene identification using a conservation-controlled amino acid substitution matrix, *Genet. Epidemiol.* **37**(6): 622–634.

Huang, J. K., Carlin, D. E., Yu, M. K., Zhang, W., Kreisberg, J. F., Tamayo, P. and Ideker, T. (2018). Systematic evaluation of molecular networks for discovery of disease genes, *Cell Systems* **6**(4): 484–495.e5.
URL: *https://www.sciencedirect.com/science/article/pii/S2405471218300954*

Kanehisa, M. and Goto, S. (2000). KEGG: kyoto encyclopedia of genes and genomes, *Nucleic Acids Res.* **28**(1): 27–30.

Knijnenburg, T. A., Wessels, L. F. A., Reinders, M. J. T. and Shmulevich, I. (2009). Fewer permutations, more accurate p-values, *Bioinformatics* **25**(12): i161–8.

Lazareva, O., Baumbach, J., List, M. and Blumenthal, D. B. (2021). On the limits of active module identification, *Briefings in Bioinformatics* **22**(5): bbab066.
URL: *https://doi.org/10.1093/bib/bbab066*

Leiserson, M. D., Vandin, F., Wu, H.-T., Dobson, J. R., Eldridge, J. V., Thomas, J. L., Papoutsaki, A., Kim, Y., Niu, B., McLellan, M. et al. (2015). Pan-cancer network analysis identifies combinations of rare somatic mutations across pathways and protein complexes, *Nature genetics* **47**(2): 106–114.

Levi, H., Elkon, R. and Shamir, R. (2021). Domino: a network-based active module identification algorithm with reduced rate of false calls, *Molecular systems biology* **17**(1): e9593.

Liberzon, A., Birger, C., Thorvaldsdóttir, H., Ghandi, M., Mesirov, J. P. and Tamayo, P. (2015). The molecular signatures database (MSigDB) hallmark gene set collection, *Cell Syst.* **1**(6): 417–425.

Lowe, W. L. J. and Reddy, T. E. (2015). Genomic approaches for understanding the genetics of complex disease, *Genome Research* **25**(10): 1432–1441. NIH Grants: R01 DK097534, R01 DK099820.

Madsen, J. G. S., Schmidt, S. F., Larsen, B. D., Loft, A., Nielsen, R. and Mandrup, S. (2015). iRNA-seq: computational method for genome-wide assessment of acute transcriptional regulation from total RNA-seq data, *Nucleic Acids Res.* **43**(6): e40.

Pasquier, C., Guerlais, V., Pallez, D., Rapetti-Mauss, R. and Soriani, O. (2023). A network embedding approach to identify active modules in biological interaction networks, *Life Science Alliance* **6**(9).
URL: *https://www.life-science-alliance.org/content/6/9/e202201550*

Posey, J. E., O'Donnell-Luria, A. H., Chong, J. X., Harel, T., Jhangiani, S. N., Coban Akdemir, Z. H., Buyske, S., Pehlivan, D., Carvalho, C. M. B., Baxter, S., Sobreira, N., Liu, P., Wu, N., Rosenfeld, J. A., Kumar, S., Avramopoulos, D., White, J. J., Doheny, K. F., Witmer, P. D., Boehm, C., Sutton, V. R., Muzny, D. M., Boerwinkle, E., Günel, M., Nickerson, D. A., Mane, S., MacArthur, D. G., Gibbs, R. A., Hamosh, A., Lifton, R. P., Matise, T. C., Rehm, H. L., Gerstein, M., Bamshad, M. J., Valle, D., Lupski, J. R. and Centers for Mendelian Genomics (2019). Insights into genetics, human biology and disease gleaned from family based genomic studies, *Genetics in Medicine* **21**(4): 798–812. NIH Grants: UM1 HG008900, UM1 HG006504, UM1 HG006542, K08 HG008986, UM1 HG006493, and others.

Scacchetti, A., Brueckner, L., Jain, D., Schauer, T., Zhang, X., Schnorrer, F., van Steensel, B., Straub, T. and Becker, P. B. (2018). CHRAC/ACF contribute to the repressive ground state of chromatin, *Life Sci. Alliance* **1**(1): e201800024.

Schmidt, S. F., Larsen, B. D., Loft, A., Nielsen, R., Madsen, J. G. S. and Mandrup, S. (2015). Acute TNF-induced repression of cell identity genes is mediated by NFκB-directed redistribution of cofactors from super-enhancers, *Genome Res.* **25**(9): 1281–1294.

Smith, G. R. and Nambiar, M. (2020). New solutions to old problems: Molecular mechanisms of meiotic crossover control, *Trends Genet.* **36**(5): 337–346.

Soffers, J. H. M., Alcantara, S. G.-M., Li, X., Shao, W., Seidel, C. W., Li, H., Zeitlinger, J., Abmayr, S. M. and Workman, J. L. (2021). The SAGA core module is critical during drosophila oogenesis and is broadly recruited to promoters, *PLoS Genet.* **17**(11): e1009668.

Subramanian, A., Tamayo, P., Mootha, V. K., Mukherjee, S., Ebert, B. L., Gillette, M. A., Paulovich, A., Pomeroy, S. L., Golub, T. R., Lander, E. S. and Mesirov, J. P. (2005). Gene set enrichment analysis: A knowledge-based approach for interpreting genome-wide expression profiles, *Proceedings of the National Academy of Sciences* **102**(43): 15545–15550.
URL: *https://www.pnas.org/doi/abs/10.1073/pnas.0506580102*

Suganuma, T., Mushegian, A., Swanson, S. K., Florens, L., Washburn, M. P. and Workman, J. L. (2012). A metazoan ATAC acetyltransferase subunit that regulates mitogen-activated protein kinase signaling is related to an ancient molybdopterin synthase component, *Mol. Cell. Proteomics* **11**(5): 90–99.

Sun, S., Defosse, T., Boyd, A., Sop, J., Verderose, F., Surray, D., Aziz, M., Howland, M., Wu, S., Changela, N., Jang, J., Schindler, K., Xing, J. and McKim, K. S. (2024). Whole transcriptome screening for novel genes involved in meiosis and fertility in drosophila melanogaster, *Scientific Reports* **14**(1): 3602.
URL: *https://doi.org/10.1038/s41598-024-53346-z*

Sun, S., Miller, M., Wang, Y., Tyc, K. M., Cao, X., Scott, Jr, R. T., Tao, X., Bromberg, Y., Schindler, K. and Xing, J. (2022). Predicting embryonic aneuploidy rate in IVF patients using whole-exome sequencing, *Hum. Genet.* **141**(10): 1615–1627.

Swanson, K., Wu, E., Zhang, A., Alizadeh, A. A. and Zou, J. (2023). From patterns to patients: Advances in clinical machine learning for cancer diagnosis, prognosis, and treatment, *Cell* **186**(8): 1772–1791. NIH Grant: F30 HL156478.

Szklarczyk, D., Morris, J. H., Cook, H., Kuhn, M., Wyder, S., Simonovic, M., Santos, A., Doncheva, N. T., Roth, A., Bork, P., Jensen, L. J. and von Mering, C. (2017). The STRING database in 2017: quality-controlled protein-protein association networks, made broadly accessible, *Nucleic Acids Res.* **45**(D1): D362–D368.

Tyc, K. M., El Yakoubi, W., Bag, A., Landis, J., Zhan, Y., Treff, N. R., Scott, Richard T, J., Tao, X., Schindler, K. and Xing, J. (2020). Exome sequencing links cep120 mutation to maternally derived aneuploid conception risk, *Human Reproduction* **35**(9): 2134–2148.
URL: *https://doi.org/10.1093/humrep/deaa148*

Tyc, K. M., Wong, A., Scott, R. T., Tao, X., Schindler, K. and Xing, J. (2021). Analysis of dna variants in mirnas and mirna 3'utr binding sites in female infertility patients, *Laboratory Investigation* **101**(4): 503–512.
  URL: *https://doi.org/10.1038/s41374-020-00498-x*

Wong, A. K., Krishnan, A. and Troyanskaya, O. G. (2018). GIANT 2.0: genome-scale integrated analysis of gene networks in tissues, *Nucleic Acids Res.* **46**(W1): W65–W70.

Wong, A. K., Sealfon, R. S. G., Theesfeld, C. L. and Troyanskaya, O. G. (2021). Decoding disease: from genomes to networks to phenotypes, *Nature Reviews Genetics* **22**(12): 774–790.

Xenarios, I., Rice, D. W., Salwinski, L., Baron, M. K., Marcotte, E. M. and Eisenberg, D. (2000). DIP: the database of interacting proteins, *Nucleic Acids Res.* **28**(1): 289–291.

Yang, L., Chen, R., Goodison, S. and Sun, Y. (2021). An efficient and effective method to identify significantly perturbed subnetworks in cancer, *Nature computational science* **1**(1): 79–88.

7   Additional Files

Additional File 1: Detailed description of AMI algorithms.
Additional File 2: Table S1. Complete listing of all modules identified by each algorithm across all datasets.
Additional File 3: Table S2. EHR Statistics.
Additional File 4: Table S3. Merged modules in TNFa and Fly Transcriptome datasets.