Rapid inversion of singleton distractor representations underlies learned attentional

suppression

Ziyao Zhang and Jarrod A. Lewis-Peacock

Department of Psychology, The University of Texas at Austin

Corresponding Author:

Ziyao Zhang

108 E. Dean Keeton St., Stop A8000

Austin, TX 78712

Email: ziyaoz@utexas.edu

Conflict of interest statement: The authors declare no competing financial interests.

Author Note

Jarrod A. Lewis-Peacock https://orcid.org/0000-0002-9918-465X

Ziyao Zhang https://orcid.org/0000-0003-3219-9221

Z.Z conceived of the idea. Z.Z analyzed the data and visualized results. Z.Z. wrote the original

draft of the manuscript. J.A.L.-P and Z.Z. reviewed and edited the final draft of the manuscript.

This work was completed with support from the National Institute of Health Grant
R01EY028746 awarded to J.A.L.-P. This content is solely the responsibility of the authors and
does not necessarily represent the official views of the National Institutes of Health.

Abstract

In visually complex and dynamically changing environments, humans must often filter out salient but task-irrelevant stimuli. Prior work shows that with repeated exposure to color singleton distractors, individuals can learn to divert attention away from these salient items. However, the neural mechanisms supporting such attentional suppression remain unclear. The present study examined the temporal trajectories of singleton distractor representations during visual search to address this gap. Using multivariate pattern analyses of EEG data in human subjects (N = 40, 30 females, 10 males), we identified two clusters of decodable singleton distractor representations: an early cluster from 100-200 ms and a later cluster from 200-400 ms. Temporal generalization analyses showed that the later representations were inverted versions of the early ones. Importantly, stronger late, but not early representations, predicted faster search responses, suggesting that the later signals support distractor suppression. This representational inversion facilitates suppressing singleton distractors in the spatial priority map. Comparing decoding evidence across locations revealed that singleton distractor locations were suppressed relative to non-singleton distractors. Moreover, comparing the neural coding of locations revealed that the spatial organization in the singleton distractor neural space was inverted relative to that in the target neural space. Together, these findings reveal a rapid representational inversion underlying salient distractor suppression at the onset of visual search. This inversion of singleton distractor signals was likely driven by top-down control mechanisms that transform bottom-up saliency signals, producing an inverted arrangement of target and distractor information within a shared neural space.

Significance Statement

A primary goal of attention is to select relevant information while ignoring irrelevant input from the external environment. Although the mechanisms of attentional enhancement have been extensively studied, the mechanisms underlying attentional suppression remain less well understood. While prior work has made important progress in identifying when attentional suppression is engaged, the neural mechanisms that implement suppression are still unclear. Here, we show that neural representations of salient singleton distractors undergo a rapid inversion approximately 200 ms after search onset. These inverted representations can subsequently be read out as suppression signals during the computation of spatial priorities. Together, our findings suggest that transforming initial pop-out distractor signals into an inverted representational format might drive rapid attentional suppression and support goal-directed visual search.

Introduction

The ability to filter distracting information is crucial for goal-directed behavior. Salient but irrelevant stimuli, such as website pop-ups, readily capture attention, raising the question of whether such stimuli can be actively suppressed within the attention system. Recent progress on this issue has come from studies of color singleton distractors (e.g., a red item among green items) in goal-directed visual search (Bacon & Egeth, 1994; Gaspelin et al., 2015). Color singletons readily capture attention and impair search performance (Jonides & Yantis, 1988; Theeuwes, 2010). However, accumulating evidence suggests that attentional capture by such distractors can be mitigated.

Repeated exposure to search arrays containing color singleton distractors can lead to

faster detection of shape-defined targets when a singleton is present than when it is absent

(Chang & Egeth, 2019; Gaspelin et al., 2015, 2017; Vatterott & Vecera, 2012). Although this

behavioral benefit has been interpreted as evidence for attentional suppression, alternative

mechanisms could also account for these effects, including ignoring singletons in a serial search

mode (Theeuwes, 2023), down-weighting the distractor feature dimension (Liesefeld & Müller,

2019, 2021), or rapid rejection of singleton distractors (Liesefeld et al., 2021, 2025).

Eye-tracking studies show that initial saccades are less likely to land on singleton

distractors than on non-singleton distractors (Gaspelin et al., 2017; Stilwell et al., 2023),

suggesting suppression in overt attention. However, oculomotor measures cannot rule out rapid

covert capture or fast reactive mechanisms that resolve distractor interference (e.g., Klink et al.,

2023). Converging electrophysiological evidence has identified the distractor positivity

component (Pd), emerging approximately 100 - 300 ms after stimulus onset in conditions

associated with behavioral suppression (Cosman et al., 2018; Gaspelin et al., 2023; Sawaki &

Luck, 2010; Sawaki et al., 2012). This suggests that the suppression might be associated with

early inhibitory processes. However, the functional role of Pd remains debated, with alternative

accounts proposing that it reflects upweighting of non-distractor representations (Kerzel &

Burra, 2020; Kerzel & Huynh Cong, 2023) or sensory imbalances between visual hemifields

(Oxner et al., 2025).

These findings have motivated the signal suppression hypothesis, which posits that

salient stimuli automatically generate bottom-up priority signals that can be suppressed by top-

down mechanisms before spatial attention is deployed (Gaspelin & Luck, 2018b; Sawaki &

Luck, 2010; Sawaki et al., 2012). In this framework, suppression operates by down-weighting

the distractor feature dimension prior to the initial attentional shift (Gaspelin et al., 2018b, 2025).

In contrast, the rapid disengagement hypothesis proposes that suppression occurs reactively, after

attention has been captured by the distractor (Theeuwes, 2010; Theeuwes et al., 2000). Recent

computational modeling suggests that these accounts may reflect differences in the relative

timing of target- and distractor-related priority signals rather than distinct mechanisms (Zhang et

al., 2025).

Despite advances in behavioral and computational accounts, the neural mechanisms

underlying attentional suppression remain unclear. One possibility is neural suppression,

whereby distractor-related activity or representations are reduced during visual search (Turatto et

al., 2018; Vatterott & Vecera, 2012; Won et al., 2019). Consistent with this account, fMRI and

non-human primate studies have reported reduced neural responses to, and weakened

representations of, repeated singleton distractors in early visual cortex and in priority-map

regions, including intraparietal cortex, frontal eye fields (FEF), and lateral intraparietal cortex

(LIP) (Adam & Serences, 2021; Cosman et al., 2018; Ipata et al., 2006; Won et al., 2020).

In contrast, recent evidence suggests that attentional suppression may rely on

mechanisms other than uniform neural suppression. Neuronal populations in V4, FEF, and LIP

exhibit heterogeneous response profiles to singleton distractors, rather than consistent reductions

in activity (Klink et al., 2023; Sapountzis et al., 2025). Moreover, decoding analyses indicate that

distractor representations remain stable with training, rather than being eliminated or suppressed,

raising the possibility that these representations are coded in a format that facilitates rather than

interferes with attentional allocation to targets (Sapountzis et al., 2025).

Here, we tested and provided evidence for representational transformation of singleton

distractors during visual search using temporal generalization analyses of EEG data. Whereas

neural suppression accounts predict that distractor representations weaken over time,

transformation accounts predict changes in representational format without necessarily implying

reduced representational strength. Consistent with the latter, we observed reliable representations

of singleton distractor locations across time. Notably, the representational format transformed

approximately 200 ms after search onset; specifically, later representations reflected an inverted

version of the early representations.

Materials and Methods

We reanalyzed data shared from Stilwell et al., 2022. Two groups of 20 participants were

recruited for experiment 1 and experiment 2, respectively (N = 40, 30 females, 10 males). In

each trial, participants searched for a predefined target item (circle or diamond, counterbalanced

between participants) in a search array. In the search array, the inner ring contained a target

shape and distractors that were in different shapes. On 75% of trials, a color singleton distractor

that had a distinct color from other items was presented in the inner ring. The color singleton

distractor was never the target, and participants were instructed to use the shape feature to locate

the target item. The specific color of the color singleton distractor (red or green) was fixed for

each participant but counterbalanced across participants. The outer ring contained non-target

shapes only to boost the relative salience of the singleton distractor. Overall, participants

completed 1296 singleton-present trials and 432 singleton-absent trials. Search arrays in

experiment 1 had an inner ring with four items (effective set size 4), while in experiment 2, the

inner ring had eight items (effective set size 8). EEG signals were collected and preprocessed

following the procedures outlined in Stilwell et al., 2022.

Decoding of target and singleton distractor locations

Location decoding was conducted separately for singleton and singleton-absent trials. For

singleton-absent trials, we used support vector machine (SVM) to classify the target item's

location based on the spatial distribution of the EEG signal across 17 posterior electrodes (Pz,

P3, P5, P7, P9, PO7, PO3, O1, POz, Oz, P4, P6, P8, P10, PO4, PO8, O2). We implemented this

model using the *svc* function from the *sklearn* package in Python. EEG data were downsampled

to 100 Hz, and decoding was performed for each time point (10 ms) ranging from -200 ms to 800

ms relative to the onset of the search array. For each time point, the dataset was divided into 3

folds. An equal number of trials from each location class were randomly selected for each fold

without replacement to ensure unbiased training. Two folds were used as the training set, and the

remaining fold served as the testing set. This procedure was repeated for the 3 folds, with each

one serving as the testing set in an iteration. The entire process was repeated 100 times (Wolff et

al., 2020), and decoding accuracies were averaged across 100 iterations. Decoding of target and

singleton distractor locations in singleton-present trials followed the same procedure as decoding

target locations in singleton-absent trials, except for adjusting the training set to match the

number of trials in singleton-absent trials. This adjustment aimed to ensure equal training data

for decoders in both singleton and singleton-absent trials. This should prevent biases in decoding

performance comparisons between singleton and singleton-absent trials resulting from uneven

training sets.

Linear models linking decoding evidence to reaction time

To link target location representations to reaction time, decoding evidence for the correct

target location in each trial was obtained from the *decision_function* in *sklearn*, which reflects

the model's confidence (distance to the decision hyperplane). Higher values indicate stronger

neural representations of the target location. Decoding evidence was averaged within the early

(100 - 200 ms) and later (200 - 400 ms) time windows. Both the averaged decoding values and

reaction times were z-scored within participants before fitting the linear models. Linear mixed

effects models were then fitted using the *lmer* function in *R*, with early and late decoding

evidence as predictors and reaction time as the outcome variable. To link singleton distractor

representations to reaction time, we applied the same analysis pipeline, except that decoding

evidence was extracted for singleton distractor locations rather than target locations.

Latency estimation

To estimate the onset latency of above-chance decoding, we applied a jackknife-based

bootstrapping procedure (Miller et al., 1998; Ulrich & Miller, 2001). We generated N

bootstrapped subsamples (N = 20 in both experiments), each created by leaving out one

participant. For each subsample, we performed a one-sample t-test comparing decoding accuracy

to chance. The latency for that subsample was defined as the onset of the earliest cluster of

significant time points. This procedure yielded N latency estimates. These estimates were then

used for statistical comparisons.

Temporal generalization analysis

Temporal generalization analyses were conducted for target locations in singleton-absent

trials and singleton locations in singleton-present trials. The same decoding procedures were

used, with the only difference being that trained decoders for each time point were used to

predict location labels for data at all time points.

Cross-condition generalization

Cross-condition generalization was performed between target locations in singleton-absent trials and singleton distractor locations in singleton-present trials. SVM decoders were trained exclusively on data from singleton-absent trials with labels indicating target locations. These trained decoders were then used to predict singleton distractor locations in singleton-present trials. Decoding accuracies were computed based on the probability of the decoders' predictions matching the actual singleton distractor location labels.

Activation scores

To compute activation scores for each location in singleton-present trials, decoders were first trained on target locations in singleton-absent trials. These trained decoders were subsequently used to predict location labels in singleton-present trials. Instead of generating prediction labels, prediction probabilities were produced to indicate the likelihood of a given location being the true label based on the neural patterns. Prediction probabilities for target locations, singleton locations, and non-singleton distractor locations were averaged across trials for each subject. For plotting the spatial priority map, the averaged prediction probabilities of non-singleton distractor locations (two in experiment 1, six in experiment 2) were used as the baseline activation. The activation for target and singleton distractor locations was computed as the difference between the prediction probabilities of these locations and the baseline.

Correlations between target and singleton representations

Raw EEG data of singleton-absent trials (200 - 400 ms) with the same target location were averaged to create the mean target representations for each potential target location (four in experiment 1 and eight in experiment 2). Likewise, singleton-present trials with the same singleton distractor location were averaged (200 - 400 ms) to generate singleton distractor

representations for all potential singleton distractor locations (four in experiment 1 and eight in

experiment 2). Pearson correlations in multi-channel EEG activities between target and singleton

representations were computed for each potential location and then averaged. Positive

correlations indicate similarity between the location representations in the target space and

location representations in the singleton distractor space, while negative correlations suggest

inverted representations.

Principal Component Analysis (PCA) was utilized to visualize the relation between the

target representational space and the singleton distractor representational space. For this purpose,

we identified the first two principal components (PCs) of the target representational space for

one example participant (99% variance explained). Both target and singleton distractor

representations were projected into the space defined by these two PCs. It should be noted that

PCA was used to visualize the relationship between the target and singleton distractor

representation only. The formal correlation analysis was performed based on the raw signal

space.

Statistics

We conducted one-sample (one-sided) t-tests to compare decoding accuracies against the

theoretical chance level, as below-chance decoding is not meaningful for this analysis. All other

comparisons were performed using two-sided t-tests. One-sample t-tests were also used to

compare temporal generalizability scores and cross-condition generalizability scores against the

theoretical chance level. In both cases, above-chance scores indicated positive generalizability,

whereas below-chance scores indicated negative generalizability. Paired t-tests were used to

compare prediction probabilities for target locations, singleton distractor locations, and non-

singleton distractor locations. Finally, one-sample t-tests were conducted to compare neural

correlations between target and singleton distractor representations against zero, with positive

values indicating positive correlations and negative values indicating negative correlations. All

analyses were performed in Python using standard statistical packages. Bayes factors for the

alternative hypothesis (*BF10*) were reported, with values between 1 and 3 indicating anecdotal

evidence, values between 3 and 10 indicating moderate evidence, and values greater than 10

indicating strong evidence. To account for multiple comparisons, Sidak correction was applied,

and adjusted p-values were reported.

Results

Participants searched for a predefined target item (circle or diamond, counterbalanced

between participants) in a search array. In the search array, the inner ring contained a target

shape and distractors that were in different shapes. On 75% of trials, a color singleton distractor

that had a distinct color from other items was presented in the inner ring. The color singleton

distractor was never the target, and participants were instructed to use the shape feature to locate

the target item. The outer ring contained non-target shapes only to boost the relative salience of

the singleton distractor.

Singleton distractor representations showed distinct temporal patterns compared to

target representations. We applied MVPA to track target and singleton distractor

representations across time. Both singleton distractor and target locations showed successful

decoding (**Fig 1**). Target location representations emerged around 200 ms and persisted for most

of the search period. Interestingly, the decoding of singleton distractor locations revealed an

earlier initial peak, spanning from 100 ms to 200 ms. This initial peak was followed by a

subsequent, more robust peak occurring between 200 ms and 400 ms for both set size 4, and set

size 8. The decoding accuracies of singleton distractor locations quickly dropped off following

247 the second peak whereas that for target locations persisted. The estimated latency for singleton

248 distractor representations was faster than that for target representations in both singleton-present

249 trials [experiment 1: $t(19) = -5.17$, $p < 0.001$, $d = 1.58$, *BF10* = 477.01; experiment 2: $t(19) = -$

250 259.0, $p < 0.001$, $d = 81.90$, *BF10 = 1.2 $\times$ 10^{31}*] and singleton-absent trials [experiment 1: $t(19)$

251 $= -9.92$, $p < 0.001$, $d = 3.15$, *BF10 = 2.0 $\times$ 10^{6}*; experiment 2: $t(19) = -46.15$, $p < 0.001$, $d =$

252 14.59, *BF10 = 4.3 $\times$ 10^{17}*]. Interestingly, the latency for target representations in singleton-

253 present trials was faster than in singleton-absent trials [experiment 1: $t(19) = -11.86$, $p < 0.001$, d

254 $= 3.87$, *BF10 = 3.1 $\times$ 10^{7}*; experiment 2: $t(19) = -12.11$, $p < 0.001$, $d = 3.79$, *BF10 = 4.4 $\times$*

255 *10^{7}*].

Fig. 1. Temporal profiles of target and singleton distractor representations. Participants searched for a specific target

shape (e.g., a green diamond) within the inner ring of a search array, and made a speeded button press to indicate the

direction of the line within the target shape (left vs. right). Time 0 ms represents the onset of search arrays. In

experiment 1 (a. set size 4) and experiment 2 (b. set size 8). a&c). decoding of singleton distractors showed an

earlier initial peak of decoding evidence from 100 ms to 200 ms, followed by a later peak from 200 ms to 400 ms.

Target decoding showed a gradual increase in evidence The horizontal black line indicates chance-level (25% for set

size 4, and 12.5% for set size 8). Shaded areas indicate standard errors. Colored dots indicate above chance-level

decoding performance ($p < .05$, one-sided t test). b&d). Latency of decoding accuracies estimated via the jackknife-

based procedure. *** indicates p < .001.

The identification of two early peaks in singleton distractor decodings suggests potential

shifts in representation during the search process. We conducted temporal generalization

analyses to further examine these potential changes. Our methodology involved training

decoders at one time point and then testing the decoder across all time points, repeating this

procedure for each time point. As shown in **Fig 2**, target representations were stable over time.

Trained decoders were able to generalize to neighboring time points. In contrast, the temporal

generalization analysis of singleton distractor representations showed two discernible clusters.

The initial cluster extended approximately from 100 ms to 200 ms, while the subsequent cluster

emerged at around 200 ms. Crucially, these two clusters showed an inverted relationship.

Decoders trained on activity from 100 ms to 200 ms had below-chance decoding performance

when tested on data from 200 ms to 400 ms and vice versa. This negative generalizability

performance suggests an inversion of representations for singleton distractors between the early

(100 - 200 ms) and the later (200 - 400 ms) time windows. It also provides preliminary evidence

for the signal transformation hypothesis that neural codings of singleton distractors were inverted

during the search. However, it is unclear yet how this inversion directly supported attentional

suppression.

Fig. 2. **Singleton distractor representations showed inverted transformations, whereas target representations**

remained stable. Across experiments, generalization analyses of singleton distractor representations (a & c)

revealed two clusters. Training decoders on activities from 100 ms to 200 ms resulted in below chance-level

decoding evidence when tested on activities from 200 ms to 400 ms, and vice versa. Target representations

demonstrated stability and could be generalized to neighboring time points (b & d). Orange boxes indicate key

generalization time windows. Black contours indicate significant areas ($p < .05$). Bright colors indicate above

chance-level decoding performance (denoted by orange triangles), and dark colors indicate below chance-level

decoding performance.

Singleton distractor representations facilitated visual search. We linked trial-by-trial

decoding evidence for target and singleton distractor locations to reaction time to examine their

functional roles. The relationship between early (100 - 200 ms) and late (200 - 400 ms) singleton

distractor representations and reaction time is particularly informative for distinguishing between

theoretical accounts of distractor processing. Under the reactive suppression (rapid

disengagement) framework, attentional suppression occurs after attention has been captured by

the singleton. Accordingly, early distractor representations would be expected to reflect

attentional capture, whereas later representations would reflect reactive suppression. Based on

this account, early distractor representations should be associated with slower reaction times,

whereas later representations should be associated with faster reaction times. In contrast, under

the proactive suppression framework (signal suppression), both early and late distractor

representations likely reflect different stages of active suppression. Under this framework, both

representations, particularly the later ones, should be associated with faster reaction times. Our

linear modeling results (Fig 3) showed that only late target representations negatively predicted

reaction times in both singleton-absent (experiment 1: β = -0.04, CI = [-0.06, -0.02], p = .001,

BF10 = 11.22; experiment 2: β = -0.06, CI = [-0.08, -0.03], p < .001, *BF10* = 76.21; combined: β

= -0.05, CI = [-0.06, -0.03], p < .001, *BF10* = 21555) and singleton-present trials (experiment 1:

β = -0.07, CI = [-0.08, -0.05], p < .001, *BF10* = 2.3×10^{20}; experiment 2: β = -0.08, CI = [-0.10,

-0.06], p < .001, *BF10* = 2.1×10^{29}; combined: β = -0.07, CI = [-0.08, -0.06], p < .001, *BF10* =

6.7×10^{50}), whereas early target representations did not (ps > .05). Critically, early singleton

distractor representations did not predict reaction times (experiment 1: β = 0.00, CI = [-0.01,

0.01], p = .942, *BF10* = 0.009; experiment 2: β = 0.01, CI = [-0.00, 0.03], p = .083, *BF10* =

0.021; combined: β = 0.01, CI = [-0.00, 0.02], p = .199; *BF10* = 0.011), whereas late distractor

representations negatively predicted reaction times (experiment 1: β = -0.02, CI = [-0.03, 0.00], p

= .008, *BF10* = 65.79; experiment 2: β = -0.02, CI = [-0.03, -0.00], p = .035, *BF10* = 3.52;

combined: β = -0.02, CI = [-0.03, -0.01], p = .001, *BF10* = 11.45). Together, these findings

indicate that both target and singleton-distractor representations in the late window are associated

with faster reaction times and thus enhanced behavioral performance. Distractor representations

in the early time window did not predict behavioral performance, which runs counter to a rapid

disengagement interpretation of our results. The signal suppression hypothesis could potentially

account for this pattern, but only if the early component of distractor processing reflects an initial

registration of salience that is subsequently used for diverting attention away. However, this

interpretation would be less consistent with a strict proactive suppression framework, which

posits that suppression is implemented prior to the onset of the search array.

Fig. 3. Target and singleton distractor representations predict faster reaction times. a–c) Target representations in

singleton-absent, singleton-present, and singleton distractor representations predicted reaction time in experiment 1.

Gray indicates the early window (100 - 200 ms); light green, dark green, and red indicate the late window (200 - 400

ms). d–f) Linear model results for experiment 2. g–i) Linear model results combining experiments 1 and 2. Shaded

areas represent confidence intervals. n.s indicates non-significant. * indicates p<.05, ** indicates p < .01, ***

indicates p < .001.

Singleton distractor locations were suppressed in the spatial priority map. To

investigate how the inversion of singleton representations supported attentional suppression and

facilitated visual search, we performed cross-condition generalization analyses. In this

procedure, decoders were trained on target representations in singleton-absent trials, where top-

down enhancements served as the primary guiding sources to boost target locations in the

priority map. Subsequently, these trained decoders were tested on singleton-present trials to

reveal the priority maps in instances where both target enhancement and singleton suppression

might influence spatial priorities. The cross-condition generalization analyses revealed that

singleton distractor locations were suppressed in the spatial priority map, resulting in below

chance-level decoding performance (**Fig 4.a & b**). This suppression of singleton distractor

locations started around 200 ms and persisted. Intriguingly, no generalization was observed

between target representations and singleton distractor locations during the early time window

from 100 ms to 200 ms, corresponding to the initial cluster of singleton distractor representation

observed in temporal generalization analyses.

Below-chance decoding performance could reflect suppression of singleton distractor

locations. Alternatively, it might be driven by a strong enhancement of target locations, which

would reduce decoding performance for all other locations. To rule out the alternative

possibility, we compared the spatial priority of singleton distractors against a baseline of non-

singleton distractors in the search array. We derived prediction probabilities from trained

decoders for each location in the search array and compared them across target locations,

singleton distractor locations, and non-singleton distractor locations. Activation scores for target

and singleton distractor locations were computed as the difference in prediction probabilities

compared to the baseline (non-singleton distractor locations, for one example time point, see **Fig**

4.c). For between 200 ms and 400 ms into the search, we found enhancement of target locations

compared to the baseline [experiment 1: $t(19) = 2.14$, $p = 0.045$, $d = 0.81$, $BF10 = 1.51$;

experiment 2: $t(19) = 2.93$, $p = 0.009$, $d = 1.02$, $BF10 = 5.78$]. Critically, suppression of

singleton distractor locations compared to the baseline was also observed across the experiment

[experiment 1: $t(19) = -2.11$, $p = 0.048$, $d = 0.32$, $BF10 = 1.42$; experiment 2: $t(19) = -2.62$, $p =$

0.017, $d = 0.68$, $BF10 = 3.30$]. As shown in **Fig 4.d & e**, prediction probabilities of target

locations displayed enhancement relative to the baseline from 200 ms onwards. In contrast,

prediction probabilities of singleton distractor locations were suppressed below the baseline.

Fig. 4. **Singleton distractor locations were suppressed in the spatial priority map.** a & b) Across experiments,

training decoders on target locations from singleton-absent trials demonstrated below chance-level decoding

performance (denoted by orange triangles) for singleton distractor locations, indicating the suppression of singleton

distractor locations. Dark colors indicate below chance level decoding performance for singleton locations. Black

contours indicate significant areas ($p < .05$). c) An example (250 ms in experiment 1) illustrates how we computed

activation scores from decoding prediction probabilities. Prediction probabilities of target locations (green) and

singleton distractor locations (red) were baselined to the averaged prediction probabilities of non-singleton distractor

locations (gray). d & e) The time course of prediction probabilities for target locations and singleton distractor

locations were plotted against the baseline (other locations). From 200 ms into the search, target locations showed

increased prediction probabilities, whereas singleton distractor locations showed decreased prediction probabilities

compared to the baseline. Shaded areas indicate standard errors. Colored dots indicate significant differences in

prediction probabilities between target, singleton distractor locations to non-singleton distractor locations ($p < .05$).

Singleton distractor and target locations were coded in a shared neural space but in

a reversed manner. Cross-condition generalization analyses suggested that singleton distractors

were suppressed in the neural space representing target locations. We hypothesized that this

suppression might be driven by coding distractor information in an inverted format relative to

target information. Such inverted coding of target and distractor information could facilitate the

integration of top-down enhancement and suppression in computing spatial priority (Awh et al.,

2012; Fecteau & Munoz, 2006; Itti & Koch, 2000; Luck et al., 2021). To directly test this

hypothesis, we conducted neural correlation analyses to examine the relationship between target

and singleton distractor representations.

In **Fig 5.a**, representations of both targets and singletons were shown for an example

subject from 200 ms to 400 ms into the search, projected in a 2D subspace for easier

visualization. This subspace was constructed using the first two principal components (a total of

99% variance explained) of the neural representations of target locations. The location

information demonstrated clear organization; the responses to four locations were well separated,

and the distance between neural representations corresponded closely to the physical distance

between locations (i.e., neighboring locations had neighboring representations). Interestingly,

singleton distractor and target representations showed a reversed pattern. For instance, the top

location (blue square) in the target representational space was projected to the top-right corner,

whereas the same location in the singleton distractor representational space was projected to the

bottom-left region (blue circle).

Formal correlation analyses were performed to link target representations and singleton

distractor representations in the raw signal space (dimension = channel). For between 200 ms

and 400 ms into the search, target and singleton distractor representations showed reliable

negative correlations [experiment 1: $t(19) = -3.22$, $p = 0.005$, $d = 0.72$, $BF10 = 9.99$; experiment

2: $t(19) = -3.05$, $p = 0.006$, $d = 0.68$, $BF10 = 7.29$]. As shown in **Fig 5.b &c**, negative correlation

emerged around 200 ms and persisted into the later search period, suggesting that singleton

distractor representations and target representations were coded with an inverted representational

geometry.

Fig. 5. **Singleton distractor suppression and target enhancement relied on inverted neural coding.** a) Singleton

distractor and target representations of an example subject were projected onto a 2D target representational space for

illustration purposes. Different colors indicate different locations. Singleton distractor and target representations

exhibited an inverted pattern. b & c) Correlations between singleton distractor and target representations. Starting

from around 200 ms, singleton distractor and target representations showed negative correlations. Shaded areas

indicate standard errors. Colored dots indicate significant correlations compared to zero ($p < .05$).

Pop-out

Target guidance

Inversion

Spatial priorities

Time

Fig. 6. **Proposed singleton suppression mechanism within the priority map framework.** The process initiates with the registration of singleton distractor information. Subsequently, distractor representations undergo inversion, around the same time as the emergence of target representations. Both distractor and target representations are coded within a shared neural space but in an inverted manner. The representations within this neural space are then accessed to compute the ultimate spatial priorities that guide visual attention.

Discussion

Recent attention research has increasingly shifted from an exclusive focus on target enhancement to a broader consideration of distractor suppression (Geng et al., 2019; Luck et al., 2021; Theeuwes, 2025; Wöstmann et al., 2022). Although converging evidence indicates that attention can be directed away from cued or learned distractors (Arita et al., 2012; Chang & Egeth, 2019; Gaspelin et al., 2015, 2017; Sawaki & Luck, 2010; Vatterott & Vecera, 2012; Won et al., 2019; Zhang et al., 2020, 2022; Zhang & Carlisle, 2023), it remains unclear how suppression unfolds over time and how to-be-suppressed information is represented neurally. The primary goal of the present study was to test a signal transformation mechanism underlying singleton distractor suppression during visual search. Using multivariate pattern analysis (MVPA) of EEG data, we characterized the temporal evolution of singleton distractor representations.

We found that singleton distractor representations emerged reliably earlier than target representations, consistent with the idea that salient distractors generate rapid bottom-up signals prior to the emergence of top-down target enhancement (Jonides & Yantis, 1988; Theeuwes, 2010). Increasing set size from four to eight items delayed the emergence of target representations but did not affect singleton distractor representations, in line with prior work showing that crowding weakens target signals (Reddy & VanRullen, 2007) while salience-driven signals remain relatively stable. Interestingly, target representations emerged earlier in singleton-present than singleton-absent trials. Although this pattern could suggest facilitation of target

processing by the presence of a singleton distractor, it may also reflect a limitation of spatial

decoding in displays where target and singleton locations are mutually exclusive, as discussed

below.

Decoding analyses revealed two distinct peaks in singleton distractor representations.

Temporal generalization analyses showed that target representations were stable across time,

forming a sustained cluster from approximately 200 ms onward. In contrast, singleton distractor

representations formed two temporally dissociable clusters: an early cluster from 100 - 200 ms

and a later cluster around 200 - 400 ms. Critically, these two singleton clusters exhibited

negative cross-temporal generalization, indicating a representational inversion around 200 ms.

This pattern provides direct evidence that singleton distractor representations undergo a

transformation rather than a monotonic attenuation.

To assess how this representational inversion influenced spatial priority computations, we

trained decoders on target locations from singleton-absent trials, where spatial priority is

primarily driven by top-down target enhancement, and applied them to singleton-present trials.

This cross-condition generalization yielded below-chance decoding at singleton distractor

locations. Such below-chance decoding could reflect either enhanced target representations,

which would push prediction probabilities for all non-target locations below chance, or

suppression specifically targeting the singleton location. To distinguish between these

possibilities, we compared prediction probabilities at singleton distractor locations with those at

non-singleton distractor locations. Target locations showed above-baseline enhancement

beginning around 200 ms, whereas singleton distractor locations showed reliable below-baseline

suppression over the same time window. These findings provide converging evidence that

singleton distractor representations are actively suppressed within the spatial priority map.

A key limitation of spatial decoding is that target and singleton distractor locations are

inherently anticorrelated. Consequently, negative decoding evidence could arise from either

suppression of a specific location or enhancement elsewhere. Although our comparison against

non-singleton distractor locations partially mitigates this concern, it cannot fully resolve this

ambiguity. Future work should test suppression using complementary approaches, such as

feature-based decoding or frequency tagging (Forschack et al., 2017; van Moorselaar et al.,

2020), particularly in paradigms where target and distractor features vary independently.

We hypothesized that suppression is implemented by coding singleton distractors in an

inverted representational format relative to targets. Such inverted coding would facilitate

downstream integration of target enhancement and distractor suppression within a shared neural

substrate. Consistent with this hypothesis, correlations between target and singleton distractor

representations revealed robust negative relationships beginning around 200 ms, indicating that

target and singleton distractor locations were inversely coded within a shared neural space. This

shared space likely underlies the computation of spatial priorities, allowing target and distractor

signals to exert opposing influences. While these findings support the existence of a common

coding framework, further work is needed to more precisely characterize the relationship

between target and distractor subspaces and their link to the hypothesized priority map.

A substantial body of behavioral, eye-tracking, electrophysiological, EEG, and fMRI

evidence supports successful suppression of salient color singleton distractors (Chang & Egeth,

2019; Cosman et al., 2018; Gaspelin et al., 2015, 2017; Sawaki et al., 2012; Sawaki & Luck,

2010; Stilwell et al., 2022; Vatterott & Vecera, 2012). Electrophysiological recordings in NHPs

and fMRI evidence in humans have shown reduced neuronal responses to singleton distractors

relative to non-singleton distractors (Cosman et al., 2018; Ipata et al., 2006; Adam & Serences,

2021; Won et al., 2020). These findings have been interpreted as evidence for signal attenuation.

However, recent work challenges a purely attenuation-based account. Neural responses to

singleton distractors appear highly heterogeneous in V4, FEF and LIP (Klink et al. 2023;

Sapountzis et al. 2025). Moreover, decoding analyses indicate that singleton distractor

representations persist rather than vanish, suggesting that they may play an active role in guiding

behavior. Together, these findings suggest that singleton distractor suppression may rely on

representational transformation rather than uniform attenuation.

The present study extends this work by providing direct evidence for a rapid inversion of

singleton distractor representations during visual search. We propose that attentional suppression

begins with early sensory registration of salient singleton distractors, reflected in the

representations observed between 100 - 200 ms. These early signals do not appear to drive

behavior. Instead, suppression involves transforming these signals into an inverted format that

downregulates the distractor's priority within a spatial priority map (Fig. 6). The timing of this

transformation coincides with the emergence of target representations, suggesting that it may be

driven by top-down feedback supporting target guidance rather than by feedforward attenuation

alone. Notably, the later inverted singleton representations predicted faster reaction times,

providing functional evidence that this transformation supports efficient behavior.

These findings bear directly on major theoretical accounts of singleton suppression. Both

the signal suppression hypothesis (Gaspelin & Luck, 2018b; Sawaki & Luck, 2010) and the rapid

disengagement hypothesis (Theeuwes, 2010) posit a transition from initial priority signals to

suppression, but differ in the proposed timing. Our results identify a representational

transformation beginning around 200 ms. Although the early singleton representations precede

this transformation, they were coded in a format distinct from both later singleton representations

and target representations. At face value, this pattern could be interpreted as consistent with rapid

disengagement hypothesis. However, linking decoding strength to behavior revealed that early

singleton representations did not predict reaction times, whereas later representations did. This

dissociation suggests that the early distractor representations are unlikely to reflect attentional

capture. Instead, these signals may reflect sensory registration of singleton distractors that neither

drives attentional capture nor suppression at that early stage of processing.

A limitation of the present study is the absence of eye-tracking data, which precludes

directly testing whether early singleton representations reflect covert attentional capture.

Nevertheless, several factors argue against this interpretation. First, attentional capture by

singleton distractors is rare in similar paradigms, with reported rates typically below 10%

(Gaspelin et al., 2017; Stilwell et al., 2023; Adam et al., 2023). Second, when capture does

occur, saccade latencies cluster around ~200 ms (Adam et al., 2023; Gaspelin et al., 2017),

coinciding with the onset of the observed transformation. Thus, even if capture occurs, it

overlaps temporally with the transformation rather than preceding it. These considerations

suggest that the observed representational inversion is unlikely to reflect a purely reactive

consequence of attentional capture. Importantly, recent modeling work suggests that the

distinction between proactive and reactive suppression may be less fundamental than

traditionally assumed. A single mechanism, preventing early distractor signals from triggering an

eye movement, can account for both suppression and capture effects depending on relative signal

timing (Zhang et al., 2025). Our findings align with this framework by demonstrating how early

salience signals can be transformed into suppression-supporting representations.

The two-stage pattern we observed parallels interpretations of ERP components

associated with singleton processing. An early positivity (Ppc; 80 - 150 ms) is thought to reflect

initial saliency or sensory imbalance, whereas the later Pd (100 - 300 ms) has been linked to

inhibitory processing (Barras & Kerzel, 2016; Fortier-Gauthier et al., 2012; Gaspelin et al., 2023;

Sawaki & Luck, 2010). Multivariate decoding allows these stages to be distinguished in

representational space, providing evidence for a transformation that bridges early saliency

signals and later suppression.

Finally, our findings speak to broader theories of spatial priority maps, which integrate

goal-driven, experience-driven, and stimulus-driven signals to guide attention (Awh et al., 2012;

Fecteau & Munoz, 2006; Luck et al., 2021). Using cross-condition generalization, we found

evidence that a common priority representation supports both target enhancement and distractor

suppression. However, this interpretation rests on assumptions about shared priority maps that

remain debated (Bisley & Mirpour, 2019; Wolfe, 2021). It remains possible that multiple priority

maps or representational subspaces coexist, enabling parallel implementation of enhancement

and suppression. Disentangling these possibilities remains an important challenge for future

work.

In conclusion, we provide evidence for a representational inversion mechanism

underlying singleton distractor suppression. Early salience signals are transformed into inverted

representations that suppress distractor locations within a shared neural space, supporting

efficient visual search.

Acknowledgements

We would like to acknowledge the invaluable contribution of Dr. Brad Stilwell, Dr. Howard
Egeth, and Dr. Nicholas Gaspelin for generously sharing their data. The dataset can be accessed
at https://osf.io/9xnsz/.

References

Adam, K. C. S., & Serences, J. T. (2021). History Modulates Early Sensory Processing of Salient

Distractors. *The Journal of Neuroscience*, *41*(38), 8007.

https://doi.org/10.1523/JNEUROSCI.3099-20.2021

Arita, J. T., Carlisle, N. B., & Woodman, G. F. (2012). Templates for rejection: Configuring

attention to ignore task-irrelevant features. *Journal of Experimental Psychology: Human*

Perception and Performance, *38*(3), 580–584. https://doi.org/10.1037/a0027885

Awh, E., Belopolsky, A. V., & Theeuwes, J. (2012). Top-down versus bottom-up attentional

control: A failed theoretical dichotomy. *Trends in Cognitive Sciences*, *16*(8), 437–443.

https://doi.org/10.1016/j.tics.2012.06.010

Bacon, W. F., & Egeth, H. E. (1994). Overriding stimulus-driven attentional capture. *Perception*

& Psychophysics, *55*(5), 485–496. https://doi.org/10.3758/BF03205306

Chang, S., & Egeth, H. E. (2019). Enhancement and Suppression Flexibly Guide Attention.

Psychological Science, *30*(12), 1724–1732. https://doi.org/10.1177/0956797619878813

Cosman, J. D., Lowe, K. A., Zinke, W., Woodman, G. F., & Schall, J. D. (2018). Prefrontal

Control of Visual Distraction. *Current Biology*, *28*(3), 414-420.e3.

https://doi.org/10.1016/j.cub.2017.12.023

Fecteau, J. H., & Munoz, D. P. (2006). Salience, relevance, and firing: A priority map for target

selection. *Trends in Cognitive Sciences*, *10*(8), 382–390.

https://doi.org/10.1016/j.tics.2006.06.011

Gaspelin, N., Lamy, D., Egeth, H. E., Liesefeld, H. R., Kerzel, D., Mandal, A., Müller, M. M.,

Schall, J. D., Schubö, A., Slagter, H. A., Stilwell, B. T., & van Moorselaar, D. (2023).

The Distractor Positivity Component and the Inhibition of Distracting Stimuli. *Journal of*

Cognitive Neuroscience, *35*(11), 1693–1715. https://doi.org/10.1162/jocn_a_02051

Gaspelin, N., Leonard, C. J., & Luck, S. J. (2015). Direct Evidence for Active Suppression of

Salient-but-Irrelevant Sensory Inputs. *Psychological Science*, *26*(11), 1740–1750.

https://doi.org/10.1177/0956797615597913

Gaspelin, N., Leonard, C. J., & Luck, S. J. (2017). Suppression of overt attentional capture by

salient-but-irrelevant color singletons. *Attention, Perception, & Psychophysics*, *79*(1),

45–62. https://doi.org/10.3758/s13414-016-1209-1

Gaspelin, N., & Luck, S. J. (2018a). Combined Electrophysiological and Behavioral Evidence

for the Suppression of Salient Distractors. *Journal of Cognitive Neuroscience*, *30*(9),

1265–1280. https://doi.org/10.1162/jocn_a_01279

Gaspelin, N., & Luck, S. J. (2018b). The Role of Inhibition in Avoiding Distraction by Salient

Stimuli. *Trends in Cognitive Sciences*, *22*(1), 79–92.

https://doi.org/10.1016/j.tics.2017.11.001

Geng, J. J., Won, B.-Y., & Carlisle, N. B. (2019). Distractor Ignoring: Strategies, Learning, and

Passive Filtering. *Current Directions in Psychological Science*, *28*(6), 600–606.

https://doi.org/10.1177/0963721419867099

Ipata, A. E., Gee, A. L., Gottlieb, J., Bisley, J. W., & Goldberg, M. E. (2006). LIP responses to a

popout stimulus are reduced if it is overtly ignored. *Nature Neuroscience*, *9*(8), 1071–

1076. https://doi.org/10.1038/nn1734

Itti, L., & Koch, C. (2000). A saliency-based search mechanism for overt and covert shifts of

visual attention. *Vision Research*, *40*(10), 1489–1506. https://doi.org/10.1016/S0042-

6989(99)00163-7

Jonides, J., & Yantis, S. (1988). Uniqueness of abrupt visual onset in capturing attention.

Perception & Psychophysics, *43*(4), 346–354. https://doi.org/10.3758/BF03208805

Kerzel, D., & Burra, N. (2020). Capture by Context Elements, Not Attentional Suppression of

Distractors, Explains the PD with Small Search Displays. *Journal of Cognitive*

Neuroscience, *32*(6), 1170–1183. https://doi.org/10.1162/jocn_a_01535

Kim, H., & Anderson, B. A. (2019). Dissociable Components of Experience-Driven Attention.

Current Biology, *29*(5), 841-845.e2. https://doi.org/10.1016/j.cub.2019.01.030

Klink, P. C., Teeuwen, R. R. M., Lorteije, J. A. M., & Roelfsema, P. R. (2023). Inversion of pop-

out for a distracting feature dimension in monkey visual cortex. *Proceedings of the*

National Academy of Sciences, *120*(9), e2210839120.

https://doi.org/10.1073/pnas.2210839120

Luck, S. J., Gaspelin, N., Folk, C. L., Remington, R. W., & Theeuwes, J. (2021). Progress

toward resolving the attentional capture debate. *Visual Cognition*, *29*(1), 1–21.

https://doi.org/10.1080/13506285.2020.1848949

Narhi-Martinez, W., Dube, B., & Golomb, J. D. (2023). Attention as a multi-level system of

weights and balances. *WIREs Cognitive Science*, *14*(1), e1633.

https://doi.org/10.1002/wcs.1633

Reddy, L., & VanRullen, R. (2007). Spacing affects some but not all visual searches:

Implications for theories of attention and crowding. *Journal of Vision*, *7*(2), 3–3.

https://doi.org/10.1167/7.2.3

Sawaki, R., Geng, J. J., & Luck, S. J. (2012). A Common Neural Mechanism for Preventing and

Terminating the Allocation of Attention. *The Journal of Neuroscience*, *32*(31), 10725.

https://doi.org/10.1523/JNEUROSCI.1864-12.2012

Sawaki, R., & Luck, S. J. (2010). Capture versus suppression of attention by salient singletons:

Electrophysiological evidence for an automatic attend-to-me signal. *Attention,*

Perception, & Psychophysics, *72*(6), 1455–1470. https://doi.org/10.3758/APP.72.6.1455

Serences, J. T., & Yantis, S. (2007). Spatially Selective Representations of Voluntary and

Stimulus-Driven Attentional Priority in Human Occipital, Parietal, and Frontal Cortex.

Cerebral Cortex, *17*(2), 284–293. https://doi.org/10.1093/cercor/bhj146

Sprague, T. C., Itthipuripat, S., Vo, V. A., & Serences, J. T. (2018). Dissociable signatures of

visual salience and behavioral relevance across attentional priority maps in human cortex.

Journal of Neurophysiology, *119*(6), 2153–2165. https://doi.org/10.1152/jn.00059.2018

Sprague, T. C., & Serences, J. T. (2013). Attention modulates spatial priority maps in the human

occipital, parietal and frontal cortices. *Nature Neuroscience*, *16*(12), 1879–1887.

https://doi.org/10.1038/nn.3574

Stilwell, B. T., Adams, O. J., Egeth, H. E., & Gaspelin, N. (2023). The role of salience in the

suppression of distracting stimuli. *Psychonomic Bulletin & Review*, *30*(6), 2262–2271.

https://doi.org/10.3758/s13423-023-02302-5

Stilwell, B. T., Egeth, H., & Gaspelin, N. (2022). Electrophysiological Evidence for the

Suppression of Highly Salient Distractors. *Journal of Cognitive Neuroscience*, *34*(5),

787–805. https://doi.org/10.1162/jocn_a_01827

Theeuwes, J. (2010). Top–down and bottom–up control of visual selection. *Acta Psychologica*,

135(2), 77–99. https://doi.org/10.1016/j.actpsy.2010.02.006

Theeuwes, J. (2025). Attentional Capture and Control. In *Annual Review of Psychology* (Vol. 76,

Issue Volume 76, 2025, pp. 251–273). Annual Reviews. https://doi.org/10.1146/annurev-

psych-011624-025340

Turatto, M., Bonetti, F., Pascucci, D., & Chelazzi, L. (2018). Desensitizing the attention system

to distraction while idling: A new latent learning phenomenon in the visual attention

domain. *Journal of Experimental Psychology: General*, *147*(12), 1827–1850.

https://doi.org/10.1037/xge0000503

Vatterott, D. B., & Vecera, S. P. (2012). Experience-dependent attentional tuning of distractor

rejection. *Psychonomic Bulletin & Review*, *19*(5), 871–878.

https://doi.org/10.3758/s13423-012-0280-4

Wolff, M. J., Jochim, J., Akyürek, E. G., Buschman, T. J., & Stokes, M. G. (2020). Drifting

codes within a stable coding scheme for working memory. *PLOS Biology*, *18*(3),

e3000625. https://doi.org/10.1371/journal.pbio.3000625

Won, B.-Y., Forloines, M., Zhou, Z., & Geng, J. J. (2020). Changes in visual cortical processing

attenuate singleton distraction during visual search. *Cortex*, *132*, 309–321.

https://doi.org/10.1016/j.cortex.2020.08.025

Won, B.-Y., Kosoyan, M., & Geng, J. J. (2019). Evidence for second-order singleton suppression

based on probabilistic expectations. *Journal of Experimental Psychology: Human*

Perception and Performance, *45*(1), 125–138. https://doi.org/10.1037/xhp0000594

Wöstmann, M., Störmer, V. S., Obleser, J., Addleman, D. A., Andersen, S. K., Gaspelin, N.,

Geng, J. J., Luck, S. J., Noonan, M. P., Slagter, H. A., & Theeuwes, J. (2022). Ten simple

rules to study distractor suppression. *Progress in Neurobiology*, *213*, 102269.

https://doi.org/10.1016/j.pneurobio.2022.102269

Zhang, Z., & Carlisle, N. B. (2023). Assessing recoding accounts of negative attentional

templates using behavior and eye tracking. *Journal of Experimental Psychology:*

Learning, Memory, and Cognition, *49*(4), 509–532. https://doi.org/10.1037/xlm0001183

Zhang, Z., Gapelin, N., & Carlisle, N. B. (2020). Probing early attention following negative and

positive templates. *Attention, Perception, & Psychophysics*, *82*(3), 1166–1175.

https://doi.org/10.3758/s13414-019-01864-8

Zhang, Z., Sahatdjian, R., & Carlisle, N. B. (2022). Benefits from negative templates in easy and

difficult search depend on rapid distractor rejection and enhanced guidance. *Vision*

Research, *197*, 108031. https://doi.org/10.1016/j.visres.2022.108031

Liesefeld, H. R., & Müller, H. J. (2019). Distractor handling via dimension weighting.

Current opinion in psychology, 29, 160-167.

Liesefeld, H. R., & Müller, H. J. (2021). Modulations of saliency signals at two hierarchical

levels of priority computation revealed by spatial statistical distractor learning.

Journal of Experimental Psychology: General, 150(4), 710.

Liesefeld, H. R., Liesefeld, A. M., & Müller, H. J. (2021). Attentional capture: An

ameliorable side-effect of searching for salient targets. Visual Cognition, 29(9), 600-

603.

Liesefeld, H. R., Lamy, D., Gaspelin, N., Geng, J. J., Kerzel, D., Schall, J. D., ... & Wolfe, J.

(2024). Terms of debate: Consensus definitions to guide the scientific discourse on

visual distraction. Attention, Perception, & Psychophysics, 86(5), 1445-1472.

Kerzel, D., & Burra, N. (2020). Capture by context elements, not attentional suppression of

distractors, explains the PD with small search displays. Journal of Cognitive

Neuroscience, 32(6), 1170-1183.

Kerzel, D., & Huynh Cong, S. (2023). The PD reflects selection of nontarget locations, not

distractor suppression. Journal of Cognitive Neuroscience, 35(9), 1478-1492.

Oxner, M., van Moorselaar, D., Müller, M. M., & Theeuwes, J. (2025). A flash in the pan?

Distractor suppression cannot be inferred from the early lateralized positivity.

Journal of Cognitive Neuroscience, 1-19.

Zhang, H., Sellers, J., Lee, T. G., & Jonides, J. (2025). The temporal dynamics of visual

attention. Journal of Experimental Psychology: General, 154(2), 435–456.

https://doi.org/10.1037/xge0001661

Zhang, X., Zhaoping, L., Zhou, T., & Fang, F. (2012). Neural activities in V1 create a

bottom-up saliency map. Neuron, 73(1), 183-192.

Li, Z. (2002). A saliency map in primary visual cortex. Trends in cognitive sciences, 6(1), 9-

16.

Poltoratski, S., Ling, S., McCormack, D., & Tong, F. (2017). Characterizing the effects of

feature salience and top-down attention in the early visual system. Journal of

neurophysiology, 118(1), 564-573.

Sprague, T. C., Itthipuripat, S., Vo, V. A., & Serences, J. T. (2018). Dissociable signatures

of visual salience and behavioral relevance across attentional priority maps in

human cortex. Journal of neurophysiology, 119(6), 2153-2165.

Sapountzis, P., Antoniadou, A., & Gregoriou, G. G. (2025). Diverse neuronal activity

patterns contribute to the control of distraction in the prefrontal and parietal

cortex. PLoS biology, 23(1), e3003008.

Forschack, N., Andersen, S. K., & Müller, M. M. (2017). Global enhancement but local

suppression in feature-based attention. Journal of Cognitive Neuroscience, 29(4),

619-627.

van Moorselaar, D., Lampers, E., Cordesius, E., & Slagter, H. A. (2020). Neural

mechanisms underlying expectation-dependent inhibition of distracting

information. elife, 9, e61048.

Theeuwes, J. (2023). The attentional capture debate: When can we avoid salient distractors

and when not?. Journal of Cognition, 6(1), 35.

Adams, O. J., Ruthruff, E., & Gaspelin, N. (2023). Oculomotor suppression of abrupt

onsets versus color singletons. Attention, perception, & psychophysics, 85(3), 613-

633.

Adams, O. J., & Gaspelin, N. (2021). Introspective awareness of oculomotor attentional

capture. Journal of Experimental Psychology: Human Perception and Performance,

47(3), 442.

Barras, C., & Kerzel, D. (2016). Active suppression of salient-but-irrelevant stimuli does

not underlie resistance to visual interference. Biological psychology, 121, 74-83.

Barras, C., & Kerzel, D. (2017). Salient□but□irrelevant stimuli cause attentional capture

in difficult, but attentional suppression in easy visual search. Psychophysiology,

54(12), 1826-1838.

Oxner, M., Forschack, N., & Müller, M. M. (2024). Testing the contributions of proactive

target and distractor templates in visual search performance. Visual Cognition, 1-

13.

van Moorselaar, D., Wang, N., & Theeuwes, J. (2025). Differential Neural Mechanisms

Underlying Inhibition of Color and Dynamic Motion Distractors. Journal of

cognitive neuroscience, 37(3), 543-554.

Hickey, C., Di Lollo, V., & McDonald, J. J. (2009). Electrophysiological indices of target

and distractor processing in visual search. Journal of cognitive neuroscience, 21(4),

760-775.

van Moorselaar, D., & Slagter, H. A. (2019). Learning what is irrelevant or relevant:

Expectations facilitate distractor inhibition and target facilitation through distinct

neural mechanisms. Journal of Neuroscience, 39(35), 6953-6967.

Ulrich, R., & Miller, J. (2001). Using the jackknife□based scoring method for measuring

LRP onset effects in factorial designs. Psychophysiology, 38(5), 816-827.

Miller, J., Patterson, T. U. I., & Ulrich, R. (1998). Jackknife-based method for measuring

LRP onset latency differences. Psychophysiology, 35(1), 99-115.