Uncovering distinct protein conformations using coevolutionary information and AlphaFold

Yongkai Chen[1], Samuel W.K. Wong[2*], S. C. Kou[1*]

[1]Department of Statistics, Harvard University, 1 Oxford Street, Cambridge, 02138, MA, United States.
[2]Department of Statistics and Actuarial Science, University of Waterloo, 200 University Avenue West, Waterloo, N2L 3G1, ON, Canada.

*Corresponding author(s). E-mail(s): samuel.wong@uwaterloo.ca; kou@stat.harvard.edu;

Abstract

Protein structure prediction has been revolutionized by AlphaFold, yet a key limitation remains: the challenge of characterizing the multiple conformations adopted by proteins that can switch between different folds. Current prevailing approaches rely on sampling the multiple sequence alignment (MSA) input, either through random sampling or clustering, but these methods are statistically inefficient and do not utilize coevolutionary information. To address this, we introduce an iterative sampling framework that systematically explores the MSA space using residue-specific frequencies and coevolutionary patterns inferred via Markov random fields. We also develop tools to identify a protein's variable regions and to subsequently extract representative structures. Together, our method yields a high-quality and compact set of final structural models for downstream analysis with good coverage of the distinct conformational states. On a benchmark set of fold-switching proteins, our method outperforms existing ones by substantially improving the diversity of the sampled structures. Overall, this work significantly advances our ability to characterize the conformational landscape of proteins capable of adopting distinct folds, which represents a key step towards understanding protein conformational dynamics and enabling the de novo design of protein switches.

1 Introduction

It is fair to say that AlphaFold2 (Jumper et al, 2021) has revolutionized the task of protein structure prediction from sequences. While AlphaFold2 has received incremental updates since its inception (Baek et al, 2021; Mirdita et al, 2022) and continues to be ubiquitous for structure prediction of single protein sequences, it is still challenging to adequately characterize distinct conformational states for a given protein. Many proteins, such as fold-switching or metamorphic proteins, are dynamic and change in response to their environment, multimerization, and/or binding partners (Bu and Callaway, 2011). In this regard, AlphaFold3 (Abramson et al, 2024) enhanced the prediction of specific protein complexes and binding-induced conformational changes. On the other hand, accurately predicting conformational switches for a protein's apo state, independent of binding partners, represents a substantially more difficult problem that has profound applications (Chakravarty et al, 2025). For example, traditional drug design focuses on a single, static target protein. However, if the target protein can exist in multiple conformations, a drug that targets one state may be ineffective or even harmful if it drives the protein toward a pathogenic state (Dishman and Volkman, 2022). Ideally, we would like to know the entire landscape of the possible conformations for a given protein. However, each entry in the Protein Data Bank (PDB, Berman et al, 2000) only provides a static experimentally-determined structure for most sequences; for proteins whose structures have been solved multiple times, the set of static experimental structures often confirms the presence of conformational variability (Wong and Liu, 2022). Laboratory techniques to capture protein dynamics are not readily available, and this limitation extends to AlphaFold, which is trained under the one-sequence-to-one-structure paradigm, assuming the protein will stabilize at its lowest-energy conformation in accordance with the energy landscape theory (Onuchic et al, 1997; Wong et al, 2017, 2018). When predicting the structures of fold-switching proteins, which have at least two distinct yet stable structures, AlphaFold2 by default can only predict one of the structures (Chakravarty and Porter, 2022).

This limitation has inspired studies into how AlphaFold2 can be enhanced to provide predictions that capture all possible foldings for a protein sequence. These efforts largely revolve around modifying the input to AlphaFold2, most notably in the form of the multiple sequence alignment (MSA). An MSA consists of a list of protein sequences that are evolutionarily or structurally related to the target sequence, usually retrieved by querying large databases of known protein sequences (Johnson et al, 2010; Remmert et al, 2012; Steinegger and Söding, 2017). With a well-constructed MSA, AlphaFold2 is generally regarded to be more accurate than protein language model-based folding algorithms that operate on the input sequence only, e.g., the ESM family (Hayes et al, 2025) and OmegaFold (Wu et al, 2022). Existing approaches to diversify AlphaFold2's predictions have focused on sampling the full MSA (or using multiple shallow MSAs) to generate structures from a larger conformational space. These include *random sampling* (Del Alamo et al, 2022; Monteiro da Silva et al, 2024), which draw fixed-size random subsets from the full MSA, and *AF-Cluster* (Wayment-Steele et al, 2024), where sequences similar to each other are grouped into clusters that are used as input MSAs to AlphaFold2.

However, these approaches have two main limitations. First, from a statistical perspective, they do not explore the space of MSA subsets in an effective or unbiased manner. The ideal case for fully leveraging prediction diversity via MSA sampling would be to exhaustively enumerate all possible subsets, ranging from subsets consisting of diverse sequences to subsets with highly homogeneous sequences, along with intermediate combinations. Clustering methods are inherently biased as they only sample those subsets with highly homogeneous sequences. In contrast, random sampling, though theoretically unbiased, suffers from low sampling efficiency and does not use any sequence information within the MSA. Second, both AF-cluster and random sampling treat each residue in the sequence independently: they compare the amino acid types for each residue marginally to guide the selection of MSA subsets, and disregard the interaction between different residues. Coevolutionary information, which refers to the statistical dependence between two residue positions (potentially far apart), is believed to play an important role in how AlphaFold makes predictions (Roney and Ovchinnikov, 2022). Emerging evidence also suggests that the prediction of multiple conformations through MSA sampling benefits from selecting subsets that contain distinct coevolutionary information patterns (Wayment-Steele et al, 2024). However, existing approaches, including AF-Cluster and random sampling, lack a direct mechanism to explicitly incorporate coevolutionary information when constructing MSA subsets.

To address these limitations, we propose an iterative sampling method, SMICE (**S**ampling **M**SA **I**teratively with **Co**Evolution information), which formally embeds MSA sampling into generative probabilistic models and incorporates the coevolutionary information into the sampling criterion. The method begins with sequentially sampling sequences based on each residue's marginal frequencies using Bayesian configurations that ensures high diversity across all sampled subsets. Subsequently, the sampled MSA subsets are used in AlphaFold2 to generate an initial set of structure predictions. Next, to increase the diversity of MSA subsets' coevolutionary information, we extract the structurally distinct predictions and profile the coevolutionary information from each corresponding MSA subset using a Markov random field (MRF) model (Kamisetty et al, 2013). This approach efficiently captures variations in the coevolutionary information that contributes to the structural diversity of the predictions. The fitted MRF models then guide the construction of a new round of MSA subsets with increasingly diverse coevolutionary information. These newly constructed MSA subsets are subsequently used in AlphaFold2 to predict structures. This process is iterated to generate a sufficiently large number of predictions.

During this iterative process, SMICE usually generates a large number of structure predictions (typically more than 1,000) to ensure thorough exploration of the conformational space. Extracting a compact set of representative structures is thus a critical next step for efficient downstream analysis. While previous studies have focused on using AlphaFold's confidence metrics (e.g., AlphaFold2's built-in learned predicted local distance difference test, pLDDT) to rank predictions (Wayment-Steele et al, 2024; Chakravarty et al, 2024), we found this approach problematic for fold-switching proteins due to a tendency for the confidence metrics to be overestimated (Supplementary Material S.4). In contrast, we developed an integrated procedure for extracting

representative structures that combines confidence metrics with structural clustering. This combined strategy efficiently reduces the number of final structures for examination from over 1,000 to fewer than 30 in most cases, while maintaining high-quality structures that ensure good coverage of the distinct conformational states.

Our results demonstrate the advantages of incorporating coevolutionary information into MSA sampling. For example, SMICE successfully captures both conformational states of the fold-switching protein RelB, whereas other methods, including AF-cluster and random sampling, which do not account for coevolutionary relationships, are unable to predict the fold-switching state. The performance of SMICE is demonstrated on a benchmark set of fold-switching proteins from Chakravarty et al (2024), where each protein is known to have two distinct conformations. In this benchmark dataset, SMICE consistently outperforms other methods in predicting both conformations while maintaining high prediction fidelity across most cases. Overall, our method provides a reliable solution for predicting multiple conformations of proteins capable of adopting distinct folds. These insights could lead to a deeper understanding of conformational dynamics and the critical role of fold-switching in protein function and evolution.

2 Results

2.1 Framework of SMICE

Our method consists of two steps: the sampling step (Fig. 1a) and the representative extraction step (Fig. 1b). In the sampling step, a statistical sequential sampling procedure is first applied to the full MSA to produce MSA subsets with diverse marginal statistics (amino acid proportions per residue), driven by a Bayesian framework. When sampling each different MSA subset, the sequence sampling probability is computed under a Bayesian prior distribution of amino acid proportions. Varying the Bayesian prior distribution enables a broader exploration of the conformational space by sampling MSA subsets with distinct conservation patterns in both the locations of conserved residues and the types of enriched amino acids. Next, the method leverages coevolutionary information that would not have been captured in the marginal statistics used by sequential sampling. This begins with selecting those MSA subsets that predict the most structurally diverse conformations. Then, to utilize the differences in the coevolutionary information of these representative MSA subsets, a Markov Random Field (MRF) model (Kamisetty et al, 2013) is fitted to each of the MSA subsets. We then rank sequences from the full MSA by their probability ratios under these competing MRF models. By selecting sequences that strongly favor one model over another, we construct new MSA subsets enriched with specific coevolutionary information. This process is iterated to ensure thorough exploration of the conformational space. The predicted structures from both the sequential sampling and the enhanced (coevolution-aware) sampling are combined as the sampling result of SMICE.

The second step of SMICE is extracting a compact set of representative structures from all the predictions. The procedure (Fig. 1b) is designed as follows: First, low-quality predictions are filtered out based on the pLDDT scores. An analysis of filtering metrics and threshold choices is provided in the Supplementary Material S.5. Then,

Fig. 1 SMICE workflow. **a**, Flowchart of SMICE's sampling step. MSA subsets are drawn from the full MSA using sequential sampling, which are initialized by modeling MSA subsets with different amino acid proportions. Then, structure predictions are made on the MSA subsets with AlphaFold2. Representative MSA subsets are selected by maximizing the diversity of their corresponding structures. For each representative MSA subset, we estimate its coevolutionary information using a Markov random field (MRF) model. Additional MSA subsets are constructed via enhanced sampling, which utilizes the differences in coevolutionary information embedded within the representative MSA subsets. **b**, Flowchart of SMICE's representative extraction step. First, low-quality predictions are filtered by a pLDDT threshold of 0.5. Next, the variance of the contact map is calculated across the remaining structures to identify the variable region. Predicted structures are then segmented according to the variable region, and clustered by TMscores to identify groups and outliers. The structure with the highest pLDDT score within each cluster is chosen as its representative.

the variance of the residue contact map is calculated across the remaining structures, and the variable region of the protein is identified (the definition of the variable region and the algorithm are provided in the Method section). Next, we cluster the high-quality structures based on their structural similarity in the variable region. After identifying the clusters and excluding the outliers, the structure with the highest pLDDT score within each cluster forms the final set of representative structures. A detailed description of SMICE is provided in the Method section.

2.2 Performance of SMICE's sampling step on RelB

Fig. 2 SMICE's sampling captures both known conformations of the fold-switching protein RelB. **a**, TMscores of AlphaFold2 predictions using MSA subsets generated by SMICE (red), AF-Cluster (blue), and random sampling (black). Black vertical and horizontal lines indicate TMscores between RelB's two conformations 3jv6A and 1zk9A. **b**, Crystal structures of RelB in its ground state (PDB: 3jv6A) and fold-switching state (PDB: 1zk9A) alongside their top SMICE-predicted structures. **c-e**, Principal component analysis (PCA) of predicted contact maps from SMICE (**c**), AF-Cluster (**d**), and random sampling (**e**). Each point represents the first two principal components of each predicted structure's contact map, colored by the signed max-TM score (sign[TMscore to 3jv6A minus TMscore to 1zk9A] × max of TMscores to 3jv6A and 1zk9A). Star markers denote the two conformational states 3jv6A (blue) and 1zk9A (red).

We consider the example of predicting the conformational states of the transcription factor RelB to illustrate the performance of SMICE's sampling step (Fig. 1a). RelB adopts two distinct structural states, each corresponding to a different dimerization mode (Vu et al, 2013): (1) heterodimerization with other NF-κB subunits (ground state, Fig. 2b, PDB ID, 3jv6A) or (2) homodimerization (transiently stable but not observed *in vivo*, Fig. 2b, PDB ID, 1zk9A).

To compare the efficacy of different methods, we ran SMICE, AF-Cluster, and random sampling on the full MSA of RelB (see Supplementary Material for implementation details) to predict its conformational states. To assess prediction accuracy, we computed TMscore, a widely used metric for evaluating structural similarity between two structures, for a combined region that includes the fold-switching region (fsr, as annotated by Porter and Looger (2018)) *and* its neighboring left and right segments, each with a length equal to half that of the fsr. As noted by Chakravarty et al (2024), whole-protein TMscores tend to overestimate prediction accuracy for the fsr; furthermore, we observed that TMscores calculated solely on the fsr often fail to distinguish conformations resulting from hinge motions (Bryant and Noé, 2024), where the global fold remains largely unchanged but relative orientations between regions shift. Therefore, we based the TMscore calculation on the fsr plus its neighboring segments.

Notably, only SMICE successfully generated predictions capturing the fold-switching state 1zk9A (Fig. 2a). The top predictions for state 3jv6A (TMscore: 0.989) and 1zk9A (TMscore: 0.910) by SMICE are visualized in Fig. 2b. Corresponding results, which instead use the whole-structure TMscore and whole-structure RMSD as comparison metrics, are provided in Extended Data Fig. 1 and support the same conclusion.

We were interested in the distribution of predicted structures from the three competing methods. We projected the contact maps of all predictions from the three methods into the principal component analysis (PCA) space (Fig. 2c-e). SMICE predictions are clearly separable into two clusters, each corresponding to a conformational state of RelB. In contrast, AF-Cluster and random sampling did not generate structures close to the fold-switching state 1zk9A. AF-Cluster also produced a significant number of predictions with low TMscores to the known states, whereas the predictions from random sampling lacked structural diversity.

2.3 Extracting Representative Structures from SMICE Predictions for RelB

We next extracted representative structures for RelB. This step (Fig. 1b) identified eighteen clusters, each with a representative structure. As visualized by the PCA embedding of these representative structures' contact maps (Fig. 3a), the representative structures successfully captured the conformational landscape sampled by the predictions. Moreover, clustering revealed an imbalanced prediction set, with a dominant cluster of over 1,500 structures corresponding to RelB's ground state and several smaller clusters of approximately 20 structures each. Extracting representative structures helped mitigate this imbalance. Notably, the fifth representative structure identified by SMICE corresponds to the known fold-switching state 1zk9A of RelB.

Comparison of the top five representative structures using our identified variable region (Fig. 3b) reveals three key findings. First, the primary source of variance is the contact distances between the variable region and the rest of the protein, which reflects the hinge motion of the variable region from the ground state 3jv6A to the fold-switching state 1zk9A. Second, our identified variable region well captured the region with the conformational changes. Third, the overall folds of the first four representative structures are similar but exhibit slight secondary or tertiary structural changes within

the variable region. For example, an α-helix in representative structure 1 changes to a β-sheet in structures 2 and 3.

Fig. 3 a, PCA of predicted contact maps from SMICE on RelB with the representative structures being marked by the stars. **b**, The heatmap of the variance of the predicted contact maps. The yellow rectangle highlights our identified variable region. **c**, The barplot of the cluster sizes, with the y-axis on a logarithmic scale. **d**, The top five representative structures. The variable region is colored yellow.

2.4 Experiments on a Fold-Switching Protein Benchmark

We next conducted a systematic examination of the performance of SMICE on a benchmark set of 92 fold-switching proteins provided in Chakravarty et al (2024).

We begin by comparing the proportion of successful predictions generated by each method. The prediction set of SMICE for each fold-switching protein consists of all predictions from SMICE's sampling step, as shown in Fig. 1a. For each pair of conformations of a given fold-switching protein, we use the Fold1 and Fold2 designation by Chakravarty et al (2024), where the conformation with higher TMscores for at least 3 out of 5 of their AlphaFold2 predictions is designated Fold1 and the other conformation is denoted as Fold2, which is more challenging to predict. First, taking each set of predictions generated for a given fold-switching protein, we check if the structures (1) predict Fold1, (2) predict Fold2, or (3) fail to predict either fold. To measure these,

Fig. 4 a-c, Comparison results of predictions from SMICE's sampling step against AF-Cluster and Random Sampling on the proportions of predicting Fold1, the proportions of predicting Fold2, and the minimum proportions of predicting both folds. For varying TMscore thresholds, we compute the median of the proportions across all fold-switching proteins. Different methods are colored differently. **d-f**, Comparison of the best prediction result for each method on each fold-switching protein. The top predictions of SMICE are from the final selected representative structures. The rows display the three evaluation metrics: **d**, max-TMscore1; **e**, max-TMscore2; and **f**, minimax-TMscore. In each row, the left panel shows the comparison between SMICE and AF-Cluster, while the right panel shows the comparison with random sampling. Each point represents one fold-switching protein. **g**, Comparison of the number of representative structures of SMICE against the number of predictions by AF-Cluster.

we compare the TMscores of both folds against a predefined threshold: a prediction is considered to successfully predict Fold1 if TMscore1 (TMscore to Fold1) exceeds both TMscore2 (TMscore to Fold2) and the threshold, to successfully predict Fold2 if TMscore2 exceeds both TMscore1 and the threshold, and as a failure if neither TMscore1 nor TMscore2 reaches the threshold. By varying the threshold, we calculate the proportions of predictions of these three cases across different levels of prediction confidence for each competing method. Intuitively, only those prediction sets with high proportions for both predicting Fold1 and Fold2 can be considered as successful. Therefore, we use the minimum of the two prediction proportions as a performance metric, representing the ability to successfully predict both folds simultaneously.

In Fig. 4a-c, we summarize the results across all fold-switching proteins with the median of the successful prediction proportions for Fold1, the median of the successful prediction proportions for Fold2, and the median of the minimum proportions for predicting both folds. The plotted curves represent the proportions over the fold-switching proteins, as a function of the TMscore threshold. It is seen that SMICE outperforms AF-Cluster and random sampling, achieving the highest prediction proportions for both folds and the highest minimum success rates across all the thresholds over 0.3. An interesting finding is that random sampling performs comparably to SMICE in predicting Fold1. This may be due to the random sampling's tendency to generate MSA subsets that share similar information with the full MSAs, leading to their predictions being closer to the more easily predictable Fold1 conformation.

We now compare the best prediction result for each method on each fold-switching protein. For each fold-switching protein, we compute three metrics on its prediction sets: (1) max-TMscore1, i.e., the maximum TMscore to Fold1; (2) max-TMscore2,

i.e., the maximum TMscore to Fold2; (3) minimax-TMscore, i.e., the minimum of max-TMscore1 and max-TMscore2, reflecting the worst-case prediction gap for either conformation. A high minimax-TMscore means that both folds are accurately predicted. For SMICE, we used the final predictions after its representative extraction step (Fig. 1b). The best prediction results from SMICE's sampling step are provided in Extended Data Fig. 2, which shows even higher prediction accuracy. The results comparing the top predictions of SMICE against the top predictions from AF-Cluster and random sampling are shown in Fig. 4d-f. We found that SMICE outperformed AF-Cluster in capturing both conformations in most cases. Random sampling performed comparably to SMICE for predicting Fold1 (structures that are easier to predict using AlphaFold2 without sampling), while it was outperformed by SMICE in predicting Fold2.

In Fig. 4g, we compare the number of representative structures identified by SMICE against the number of predictions generated by AF-Cluster for each fold-switching protein. We find that the number of structures finally selected by SMICE is typically below 30, with two outliers at approximately 200. In contrast, the number of predictions from AF-Cluster is generally 10 times larger than that of SMICE, with extreme cases yielding over 4,000 predictions per protein. In summary, SMICE outperformed the other methods in terms of both overall prediction quality and the accuracy of the top prediction.

3 Discussion

Our work addresses a critical limitation of AlphaFold in predicting the multiple conformations of proteins in their apo state. By reformulating MSA sampling as a probabilistic, coevolutionary information-aware procedure, we avoid the tendency of random sampling to choose uninformative MSA inputs and the tendency of clustering to choose only highly homogeneous sequences. For the thioesterase protein SP_1851, we found that MSA subsets with different levels of sequence diversity also exhibit distinct conformational prediction preferences (Extended Data Fig. 3a-c). This direct relationship demonstrates that sampling MSA subsets with multiple levels of sequence diversity (via Bayesian prior distributions) ensures broader coverage of the conformational space. Explicitly leveraging coevolutionary information (by modeling residue dependence) further increases the diversity of coevolutionary information in the MSA subsets. In the analysis of di-heme cytochrome c peroxidase from Paracoccus pantotrophus (Extended Data Fig. 3d-f), we found that sequential sampling alone, which only uses the marginal statistics of the MSA, failed to capture the fold-switching state. In contrast, the full sampling procedure of SMICE, which incorporates residue dependencies and diverse coevolutionary information in the sampled MSA subsets, did successfully predict both conformations. More ablation studies on the role of coevolutionary information are provided in the Supplementary Material S.3. Our findings demonstrate that MSAs may embed distinct evolutionary signals, and effectively using this information can significantly improve the diversity and accuracy of predicted conformations.

Extracting representative structures from a large ensemble of predicted structures is essential for characterizing the dynamics of proteins that can switch folds. Since these proteins typically exhibit only a few stable states, identifying these conformations could avoid the need to examine every predicted structure in downstream analyses. SMICE provides a systematic framework by identifying variable regions in the predicted structures, leveraging clustering and AlphaFold's confidence metrics, to extract representative structures. In benchmark studies, this approach effectively characterized the conformational landscape of most proteins using fewer than 30 representative structures, reduced from an ensemble of over 1,000 predictions.

Fold-switching proteins are likely widespread, but identifying them among the millions of known proteins is challenging since experimental validation is infeasible at such a scale. The presence of heterogeneous coevolutionary information within an MSA, as identified by SMICE, could serve as a computational marker for identifying fold-switching proteins. After detecting strong but diverse coevolutionary information, SMICE could generate a compact set of distinct structures to use for concrete, testable hypotheses. This integrated computational approach could greatly accelerate the discovery of novel fold-switching proteins by focusing costly experimental efforts on high-probability targets. Furthermore, understanding the evolutionary signals that enable fold-switching would facilitate the design of de novo protein switches, which in turn could find broad applications in the development of biosensors or targeted drug delivery systems.

A Method

The first three subsections describe the sampling step of SMICE. The two subsequent subsections describe the representative extraction step of SMICE.

A.1 Sequential Sampling on the Full MSA

In this section, we develop a sequential sampling procedure to create MSA subsets with diverse marginal statistics, i.e., the amino acid frequencies of each residue. Let $\mathcal{M} = \{\mathbf{Y}_1, \ldots, \mathbf{Y}_n\}$ denote the set of sequences in the full MSA for the target sequence, where $\mathbf{Y}_i$, a $L \times 22$ binary matrix, is the one-hot encoding of the i^{th} sequence. The 22 categories include the 20 standard amino acids, one for unknown amino acid types, and one for gaps in the alignment. Suppose we start with a small MSA subset $\mathcal{A} \subset \mathcal{M}$. To facilitate preservation of the evolutionary information in $\mathcal{A}$, our sequential sampling procedure randomly draws a new (i.e., unsampled in the current MSA subset) sequence $\tilde{\mathbf{Y}}$ with an acceptance probability proportional to its similarity to the current MSA subset $\mathcal{A}$. To achieve this, we design the acceptance probability of $\tilde{\mathbf{Y}}$ based on how its inclusion changes the amino acid proportions at all residues of $\mathcal{A}$.

Let $\boldsymbol{p}_l$ be the length-22 vector of probabilities for the different amino acid types at the l^{th} residue position, $l = 1, \ldots, L$. For an initialization of $\mathcal{A}$ starting from $\emptyset$, we estimate $\{\boldsymbol{p}_l\}_{l=1}^L$ using a Bayesian approach with a prior distribution specified by a $L \times 22$ matrix $\boldsymbol{\Pi}$, where the l^{th} row of $\boldsymbol{\Pi}$ is the prior vector for the l^{th} residue position. Specifically, we model that $\boldsymbol{p}_l$ independently follows a Dirichlet distribution,

$$\boldsymbol{p}_l \sim \text{Dirichlet}(\tau \boldsymbol{\Pi}^{\mathrm{T}} \boldsymbol{e}_l), \tag{1}$$

where $\tau > 0$ controls the strength of the prior and $\boldsymbol{e}_l$ is the l^{th} unit vector so that $\boldsymbol{\Pi}^{\mathrm{T}} \boldsymbol{e}_l$ gives the l^{th} row of $\boldsymbol{\Pi}$.

Given the current MSA subset $\mathcal{A}$ and the prior distribution of $\{\boldsymbol{p}_l\}_{l=1}^L$ in Eq.(1), the maximum a posteriori (MAP) estimate of $\boldsymbol{p}_l$ is

$$\widehat{\boldsymbol{p}}_l(\mathcal{A}, \boldsymbol{\Pi}) = \frac{(\sum_{\mathbf{Y} \in \mathcal{A}} \mathbf{Y} + \tau \boldsymbol{\Pi})^{\mathrm{T}} \boldsymbol{e}_l}{|\mathcal{A}| + \tau}. \tag{2}$$

Notice that in the early stages of sequential sampling, the MAP estimate is dominated by $\boldsymbol{\Pi}$. By assigning high sampling probability to sequences that make small changes to the MAP estimates, sequences that closely match $\boldsymbol{\Pi}$ will be more favored. This allows us to generate MSA subsets covering different local regions in the sequence space by varying the choices of $\boldsymbol{\Pi}$. The details of setting τ and $\boldsymbol{\Pi}$ are provided in the Supplementary Material.

To decide whether to accept a candidate sequence $\tilde{\mathbf{Y}}$, we first calculate the L_1 norm of the MAP estimate's change by including $\tilde{\mathbf{Y}}$ vs. not including it,

$$\begin{aligned}
\Delta_l(\tilde{\mathbf{Y}}, \mathcal{A}, \boldsymbol{\Pi}) &:= |\widehat{\boldsymbol{p}}_l(\mathcal{A}, \boldsymbol{\Pi}) - \widehat{\boldsymbol{p}}_l(\mathcal{A} \cup \{\tilde{\mathbf{Y}}\}, \boldsymbol{\Pi})|_1 \\
&= \frac{|\widehat{\boldsymbol{p}}_l(\mathcal{A}, \boldsymbol{\Pi}) - \tilde{\mathbf{Y}}^{\mathrm{T}} \boldsymbol{e}_l|_1}{|\mathcal{A}| + \tau + 1}.
\end{aligned} \tag{3}$$

To measure the overall change of the MAP estimate of $\{\boldsymbol{p}_l\}_{l=1}^{L}$, we consider two sources of heterogeneity across all residues: (1) different residues have different levels of evolutionary conservation, and (2) residues with many gaps may provide less reliable information. To address them, we rescale the changes for each residue through

$$Q_l(\tilde{\mathbf{Y}}, \mathcal{A}, \mathbf{\Pi}) = w_l \frac{\Delta_l(\tilde{\mathbf{Y}}, \mathcal{A}, \mathbf{\Pi})}{\sqrt{Var(\Delta_l(\tilde{\mathbf{Y}}, \mathcal{A}, \mathbf{\Pi}))}}, \tag{4}$$

where $Var(\Delta_l(\tilde{\mathbf{Y}}, \mathcal{A}, \mathbf{\Pi}))$ is computed by assuming the marginal distribution of the l^{th} row of $\tilde{\mathbf{Y}}$ is the one-trial multinomial distribution with probability vector $\widehat{\boldsymbol{p}}_l(\mathcal{A}, \mathbf{\Pi})$, and w_l is the proportion of gaps in the l^{th} position for the full MSA. The Supplementary Material provides the details of Eq.(4).

We now calculate the acceptance probability of the randomly drawn candidate sequence $\tilde{\mathbf{Y}}$ given the current MSA subset $\mathcal{A}$ through

$$\min\left\{1, \exp\{-\frac{\lambda}{L}\sum_{l=1}^{L} Q_l(\tilde{\mathbf{Y}}, \mathcal{A}, \mathbf{\Pi})\}/C\right\}, \tag{5}$$

where C is a tuning parameter controlling the overall sample size, and $\lambda \geq 0$ controls the homogeneity level in the sampled MSA subsets. When λ is larger, only sequences resulting in small changes to the MAP estimate are likely to be accepted. This leads to highly homogeneous subsets where sampled sequences are tightly clustered. In contrast, a small λ allows for greater diversity in the sampled MSA subsets. In the limiting case of $\lambda = 0$, sequential sampling reduces to uniform random sampling. For broader exploration, we recommend sampling with multiple λ values (see the Supplementary Material).

After we query all the sequences, or the size of the MSA subset $\mathcal{A}$ reaches the preset maximum size, we use $\mathcal{A}$ as the input MSA for AlphaFold2. By repeating this procedure multiple times with varying choices of the hyperparameters $\mathbf{\Pi}$ and λ, we induce a set of MSA subsets and their corresponding AlphaFold2 predictions.

A.2 Selection of Representative MSA Subsets

From the sequentially sampled MSA subsets, we then select the representative MSA subsets based on their structure predictions. Given the AlphaFold2 predictions obtained in the previous step, we expect that notably distinct structures also exhibit distinct evolutionary information within their corresponding MSA subsets. Thus, selecting representative structures and their MSA subsets could provide valuable information for further generation of new MSA subsets that lead to more diverse conformations.

Specifically, we first straighten the $L \times L$ contact map matrices of all predicted structures into vectors and then apply principal component analysis (PCA) to obtain low-dimensional representations of the contact map. The number of principal components is selected to explain at least 90% of the total variance. We then apply K-medoids clustering on the PCA coordinates to extract K distinct structures. Note

that AlphaFold2 is an ensemble model with five different sets of model weights, i.e., each MSA input generates five different structure predictions by AlphaFold2. Therefore, the selection of representative MSA subsets and all subsequent steps are performed independently for each of the five weight sets of AlphaFold2. Finally, for each of the K structures, we identify its corresponding MSA subset; these K MSA subsets will be used to extract the coevolutionary information.

A.3 Coevolutionary-Information-Aware MSA Sampling

By analyzing differences in coevolutionary information across representative MSA subsets, we develop an enhanced (coevolution-aware) sampling strategy to generate more diverse samples. The statistical model that we use for analyzing the coevolutionary information of the MSA is the Markov random field (MRF) model (Kamisetty et al, 2013) with the parameter $\boldsymbol{\Theta} = \left\{ \{\mathbf{V}_l\}_{l=1}^L, \{\mathbf{W}_{l,m}\}_{1 \le l < m \le L}^L \right\}$,

$$\mathrm{P}_{MRF}(\mathbf{Y}|\boldsymbol{\Theta}) \propto \exp\left(\sum_{l=1}^L \boldsymbol{e}_l^{\mathrm{T}} \mathbf{Y} \left[\mathbf{V}_l + \sum_{m>l}^L \mathbf{W}_{l,m} \mathbf{Y}^{\mathrm{T}} \boldsymbol{e}_m \right] \right), \qquad (6)$$

where $\mathbf{V}_l$ is a 22-dimensional vector capturing the marginal effect of the amino acid type at the l^{th} residue and $\mathbf{W}_{l,m}$ is a 22×22 symmetric matrix capturing the pairwise interaction effect between the m^{th} and l^{th} residues. $\mathbf{W}_{l,l} \equiv 0$ for $l = 1, \dots, L$.

Sampling MSA subsets with diverse coevolutionary information can enable AlphaFold2 to more effectively explore the conformational space. To leverage this coevolutionary information effectively, we first estimate the MRF model for each of the representative MSA subsets extracted in the previous steps using GREMLIN (Kamisetty et al, 2013); see the Supplementary Material for more details. Suppose there are K MSA subsets, so that the MRF model is estimated K times. Then, for each pair of estimated MRF models, denoting their parameters by $\boldsymbol{\Theta}$ and $\boldsymbol{\Theta}'$, we calculate the probability ratio $\mathrm{P}_{MRF}(\mathbf{Y}_i|\boldsymbol{\Theta})/\mathrm{P}_{MRF}(\mathbf{Y}_i|\boldsymbol{\Theta}')$ across all sequences in the full MSA. A high ratio indicates that a sequence is more consistent with the coevolutionary information captured by $\boldsymbol{\Theta}$ than $\boldsymbol{\Theta}'$. By pooling sequences with high probability ratios into a new MSA subset, we may strengthen their shared coevolutionary information. Finally, for each pair of estimated MRF models, we rank all sequences by their computed probability ratios and select the top M sequences, where M is a predetermined subset size. These M sequences are used as one input MSA subset for AlphaFold2 to generate new predictions (see Supplementary Material for the details of setting M). Since there are $K(K-1)$ such ordered pairs, this procedure generates $K(K-1)$ MSA subsets.

The steps of selecting representative MSA subsets and coevolutionary-information-aware MSA sampling are iterated in SMICE a few times (usually two or three rounds) to obtain the final structure predictions.

A.4 Identifying Regions of High Structural Variability

The conformational changes in fold-switching proteins can be broadly classified into two categories (Bryant and Noé, 2024): (1) The structures of individual subregions

remain largely unchanged, but their spatial arrangement shifts. This is often caused by the reorientation of a tail region (e.g., RelB protein). (2) The secondary or tertiary structure within a subregion changes.

Consequently, to locate regions of high structural variability from the predicted contact maps, we search for a contiguous region that meets the following criteria: it must exhibit high variance either in its intra-region contact distances or in its inter-region contact distances (i.e., its contacts with the rest of the protein), while the contact distances within the rest of the protein remain stable. Based on these criteria, we developed a stepwise algorithm to identify the variable region. The procedure is as follows:

(1) *Initialization*: The input is an ensemble of predicted contact maps for a protein of length L. We first compute an $L \times L$ matrix of variances, $\boldsymbol{\Sigma}$, where each entry $\boldsymbol{\Sigma}_{ab}$ represents the variance of the contact distance between a^{th} and b^{th} residues across the ensemble. This matrix quantifies the positional variability in the structural predictions.

(2) *Identify Initial Candidate Region*: An initial candidate region is identified by scanning the protein sequence with a sliding window of a fixed window size, w_{init}. For each sliding window, we compute the total pairwise variance of all residues *outside* the window and select the contiguous segment corresponding to the window that yields the minimum value. This ensures high variability of contacts, either within the segment or between the segment and the rest of the protein. The configuration of the window size, w_{init}, is detailed in the Supplementary Material.

(3) *Calculating the Baseline Variability of Structural Conservation*: The baseline variability of structural conservation, denoted as β, is calculated as the average variance of all contact pairs where both residues lie outside the initial candidate region (i.e., pairs from outside the window).

(4) *Iterative Refinement*: The boundaries of the candidate region are refined through an iterative process that removes one residue at a time from either end of the sequence. In each iteration, we evaluate the consequence of removing the leftmost or the rightmost residue. The algorithm selects for removal the residue (leftmost or rightmost) that, when excluded, minimizes the total pairwise variance for all residues outside the new region.

(5) *Termination*: The iterative deletion process terminates when the mean variance of all contact pairs between the last-removed residue and the residues outside the current region exceeds 4β, or when the size of the candidate variable region reaches a predefined minimum. The configuration of the minimum region size is detailed in the Supplementary Material.

The detailed algorithm pseudocode is provided in the Supplementary Material Algorithm S.3.

A.5 Representative Structures Extraction

We first filter out the low-quality predictions from SMICE's sampling step based on a pLDDT threshold of 0.5 (recall that pLDDT is AlphaFold2's built-in confidence measure). Next, to cluster the remaining predicted structures and identify the representative structures, we employed a stepwise clustering strategy based on structural similarity via the TMscore. Since large-scale pairwise structural comparison based on

TMscore is computationally prohibitive, we use Foldseek (Van Kempen et al, 2024) to rapidly approximate TMscores. The procedure for stepwise clustering is as follows:

(1) The procedure begins with the highest-confidence structure (i.e., the one with the highest pLDDT score) among the five AlphaFold2 predictions generated from the full MSA. This structure serves as the initial "seed" for the first cluster.

(2) We calculate the TMscores between this seed structure and all structure predictions that were retained after filtering. TMscores are computed based on the specific region that includes the identified variable region and its left and right neighboring segments, each of which is taken to be half the length of the variable region. All structures with a TMscore greater than 0.85 relative to the seed structure are aggregated to form the first cluster. The structure with the highest pLDDT within this cluster is selected as its representative.

(3) To form each new cluster, the new cluster seed is chosen as the unclustered structure that has the lowest TMscore to the representative(s) of the previous cluster(s). Then, all unclustered structures with a TMscore > 0.85 to this new seed are grouped into a new cluster, and the structure with the highest pLDDT within the new cluster is taken as its representative.

(4) Step (3) is repeated until all structures are clustered.

(5) Finally, to ensure statistical reliability, any clusters containing fewer than three members are discarded as outliers.

This approach efficiently partitions the predicted structural ensemble into well-populated, high-confidence conformational states.

A.6 Use of ChatGPT

During the preparation of this manuscript, the authors used ChatGPT (https://openai.com/) solely for improving the language, readability, and correcting the grammar.

Data availability

Data corresponding to SMICE and analysis presented here are publicly available at GitHub (https://github.com/StatCYK/SMICE).

Code availability

The code corresponding to SMICE and the analysis presented here are publicly available on GitHub (https://github.com/StatCYK/SMICE). ColabFold v.1.5.2 for structure prediction (https://colabfold.com). Foldseek for fast TMscore computing (https://github.com/steineggerlab/foldseek). For plotting, Python v.3.10.6 (https://www.python.org/), Matplotlib v.3.6.2 (https://matplotlib.org/), seaborn v.0.12.2 (https://github.com/mwaskom/seaborn)

Acknowledgements

S.W.K. Wong is supported in part by Discovery Grant RGPIN-2019-04771 from the Natural Sciences and Engineering Research Council of Canada. S.C. Kou is supported in part by an award from Harvard Data Science Initiative (HDSI).

References

Abramson J, Adler J, Dunger J, et al (2024) Accurate structure prediction of biomolecular interactions with AlphaFold 3. Nature 630:493–500

Baek M, DiMaio F, Anishchenko I, et al (2021) Accurate prediction of protein structures and interactions using a three-track neural network. Science 373(6557):871–876

Berman HM, Westbrook J, Feng Z, et al (2000) The protein data bank. Nucleic acids research 28(1):235–242

Bryant P, Noé F (2024) Structure prediction of alternative protein conformations. Nature Communications 15(1):7328

Bu Z, Callaway DJ (2011) Proteins move! Protein dynamics and long-range allostery in cell signaling. Advances in protein chemistry and structural biology 83:163–221

Chakravarty D, Porter LL (2022) AlphaFold2 fails to predict protein fold switching. Protein Science 31(6):e4353

Chakravarty D, Schafer JW, Chen EA, et al (2024) AlphaFold predictions of fold-switched conformations are driven by structure memorization. Nature communications 15(1):7296

Chakravarty D, Lee M, Porter LL (2025) Proteins with alternative folds reveal blind spots in alphafold-based protein structure prediction. Current Opinion in Structural Biology 90:102973

Del Alamo D, Sala D, Mchaourab HS, et al (2022) Sampling alternative conformational states of transporters and receptors with AlphaFold2. Elife 11:e75751

Dishman AF, Volkman BF (2022) Design and discovery of metamorphic proteins. Current opinion in structural biology 74:102380

Hayes T, Rao R, Akin H, et al (2025) Simulating 500 million years of evolution with a language model. Science p eads0018

Johnson LS, Eddy SR, Portugaly E (2010) Hidden Markov model speed heuristic and iterative HMM search procedure. BMC bioinformatics 11:1–8

Jumper J, Evans R, Pritzel A, et al (2021) Highly accurate protein structure prediction with AlphaFold. Nature 596(7873):583–589

Kamisetty H, Ovchinnikov S, Baker D (2013) Assessing the utility of coevolution-based residue–residue contact predictions in a sequence-and structure-rich era. Proceedings of the National Academy of Sciences 110(39):15674–15679

Kingma DP (2014) Adam: A method for stochastic optimization. arXiv preprint arXiv:14126980

Mirdita M, Schütze K, Moriwaki Y, et al (2022) ColabFold: making protein folding accessible to all. Nature methods 19(6):679–682

Onuchic JN, Luthey-Schulten Z, Wolynes PG (1997) Theory of protein folding: the energy landscape perspective. Annual review of physical chemistry 48(1):545–600

Porter LL, Looger LL (2018) Extant fold-switching proteins are widespread. Proceedings of the National Academy of Sciences 115(23):5968–5973

Remmert M, Biegert A, Hauser A, et al (2012) HHblits: lightning-fast iterative protein sequence searching by HMM-HMM alignment. Nature methods 9(2):173–175

Roney JP, Ovchinnikov S (2022) State-of-the-art estimation of protein model accuracy using AlphaFold. Physical Review Letters 129(23):238101

Monteiro da Silva G, Cui JY, Dalgarno DC, et al (2024) High-throughput prediction of protein conformational distributions with subsampled AlphaFold2. Nature communications 15(1):2464

Steinegger M, Söding J (2017) MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. Nature biotechnology 35(11):1026–1028

Suzek BE, Wang Y, Huang H, et al (2015) UniRef clusters: a comprehensive and scalable alternative for improving sequence similarity searches. Bioinformatics 31(6):926–932

Van Kempen M, Kim SS, Tumescheit C, et al (2024) Fast and accurate protein structure search with foldseek. Nature biotechnology 42(2):243–246

Vu D, Huang DB, Vemu A, et al (2013) A structural basis for selective dimerization by nf-κb relb. Journal of molecular biology 425(11):1934–1945

Wayment-Steele HK, Ojoawo A, Otten R, et al (2024) Predicting multiple conformations via sequence clustering and AlphaFold2. Nature 625(7996):832–839

Wong SW, Liu Z (2022) Conformational variability of loops in the sars-cov-2 spike protein. Proteins: Structure, Function, and Bioinformatics 90(3):691–703

Wong SW, Liu JS, Kou S (2017) Fast de novo discovery of low-energy protein loop conformations. Proteins: Structure, Function, and Bioinformatics 85(8):1402–1412

Wong SW, Liu JS, Kou S (2018) Exploring the conformational space for protein folding with sequential monte carlo. The Annals of Applied Statistics 12(3):1628–1654

Wu R, Ding F, Wang R, et al (2022) High-resolution de novo structure prediction from primary sequence. BioRxiv pp 2022–07

Extended Data Fig. 1 Results of SMICE's sampling step on the fold-switching protein RelB. **a**, TMscores of the whole protein structure for the AlphaFold2 predictions generated by the SMICE sampling step (red), AF-Cluster (blue), and random sampling (black). Black vertical and horizontal lines indicate the whole-structure TMscores between RelB's two experimentally determined conformations, 3jv6A and 1zk9A. **b**, RMSDs of the whole protein structure for AlphaFold2 predictions generated by SMICE sampling (red), AF-Cluster (blue), and random sampling (black).

Extended Data Fig. 2 Comparison of the max-TMscore1, max-TMscore2, and minimax-TMscore for the full set of predictions generated by SMICE's sampling step against AF-Cluster and Random Sampling. Each point represents one fold-switching protein.

Extended Data Fig. 3 a, TMscores of AlphaFold2 predictions generated by SMICE's sampling step. Black vertical and horizontal lines indicate TMscores between SP_1851's two experimentally determined conformations. Predictions are colored according to the values of the sequence diversity parameter λ, which is used by SMICE during the generation of their respective MSA subsets. λ explicitly controls the degree of sequence diversity in the sampled MSA subsets, with lower values selecting more diverse sequences. **b**, Crystal structures of SP_1851 in its ground (PDB: 4zrbC) and fold-switching (PDB: 4zrbH) states alongside their top SMICE-predicted structures. **c**, UMAP visualization of MSA sequences and the MSA subsets that make the top predictions of the two conformational states. The sampled sequences are colored in black, and the unsampled sequences are colored in gray. **d**, Comparison between predictions from sequential sampling (SMICE_SeqSamp, blue) only and coevolutionary-information-aware sampling (SMICE_enhanced, red). Black vertical and horizontal lines indicate TMscores between the two conformational states. **e**, Crystal structures of di-heme cytochrome c peroxidase in oxidized form (PDB: 2c1uC) and the active mixed valence form (PDB: 2c1vC) alongside their top SMICE-predicted structures. **f**, UMAP visualization of the distribution of coevolutionary information, measured by **W** in the Markov random field model Eq.(6), from sequential sampling and the coevolutionary-information-aware sampling.

Supplementary Material for "Uncovering distinct protein conformations using coevolutionary information and AlphaFold"

S.1 Details of the Methods

S.1.1 Setting Hyperparameters τ and Π

As described in the Method section, to promote diversity among the sampled MSA subsets, we vary the choices of Π in the prior distribution of the expected amino acid proportions.

We set these values in a data-driven manner. Specifically, for each sequence $\mathbf{Y}_i \in \{\mathbf{Y}_1, \ldots, \mathbf{Y}_n\}$, let $\mathcal{S}(i)$ represent the indices of $\mathbf{Y}_i$'s N-nearest sequences among the full MSA using the Hamming distance. We compute the average proportions of amino acids in all residues across $\mathbf{Y}_i$'s neighbors, $\bar{\mathbf{Y}}_i = \frac{1}{N} \sum_{j \in \mathcal{S}(i)} \mathbf{Y}_j$. We then apply K-medoids clustering to these average amino acid proportions $\{\bar{\mathbf{Y}}_i\}_{i=1}^n$ and obtain the resulting cluster centers. These cluster centers are used as K different choices for Π. In our experiment, we set $K = 10$. For MSAs with fewer than 100 sequences, we set $N = 10$, and for those with more than 100 sequences, we conduct the above procedure for both $N = 10$ and 30. Finally, we set the strength of the prior as $\tau = 0.5N$.

S.1.2 Setting Hyperparameters in the Acceptance Probabilities

Since λ controls the homogeneity of the sequences within a sampled MSA subset, using multiple choices of λ could also lead to diverse MSA subsets in terms of conservation patterns in both the locations of conserved residues and the types of enriched amino acids. In particular, we choose λ from $\{0, 1, 2, 3\}$. Moreover, C in Eq.(5) controls the overall acceptance probability. The common choice of C is set as $\operatorname{argmax}_{\tilde{\mathbf{Y}}} \exp\{-\frac{\lambda}{L} \sum_{l=1}^L Q_l(\tilde{\mathbf{Y}}, \mathcal{A}, \Pi)\}$ so that the acceptance probability can be no greater than 1.

S.1.3 Sequential Sampling Algorithm

The details of the sequential sampling algorithm are summarized in Algorithm S.1. Notice that we set a maximum subset size $n_{\max}$ for efficient computation, and a minimum subset size $n_{\min}$ to ensure reliable AlphaFold2 predictions. The empirical suggestion of $n_{\max}$ is as follows: $n_{\max} = 20$ if the full MSA size < 100, $n_{\max} = 100$ if the full MSA size $\in [100, 500]$, and $n_{\max} = 200$ otherwise. We set the minimum subset size $n_{\min} = 10$.

S.1.4 Estimating the MRF Model with GREMLIN

Given the MRF model in Eq.(6) and sequences $\{\tilde{\mathbf{Y}}_i\}_{i=1}^n$, the log-likelihood of Θ is

Algorithm S.1 Sequential Sampling for MSA Subsets

1: **Input:** Full MSA $\mathcal{M}$, target maximum subset size $n_{\max}$, set of $\boldsymbol{\Pi}$ configurations $\{\boldsymbol{\Pi}_1, \ldots, \boldsymbol{\Pi}_K\}$.
2: **for** each $\lambda \in \{0, 1, 2, 3\}$ **do**
3:     **for** each $\boldsymbol{\Pi} \in \{\boldsymbol{\Pi}_1, \ldots, \boldsymbol{\Pi}_K\}$ **do**
4:         Initialize $\mathcal{A} \leftarrow \emptyset$
5:         **while** $|\mathcal{A}| < n_{\max}$ **do**
6:             Sample candidate $\tilde{\mathbf{Y}}$: $\tilde{\mathbf{Y}} \leftarrow$ sample from $\mathcal{M}$ without replacement
7:             Accept $\tilde{\mathbf{Y}}$ and update $\mathcal{A} \leftarrow \mathcal{A} \cup \{\tilde{\mathbf{Y}}\}$ with the probability in Eq.(5)
8:         **end while**
9:         Store $\mathcal{A}$ in output collection if $|\mathcal{A}| > n_{\min}$
10:     **end for**
11: **end for**
12: **Output:** All sampled MSA subsets $\mathcal{A}$

$$l(\boldsymbol{\Theta}|\{\tilde{\mathbf{Y}}_i\}_{i=1}^n) = \sum_{i=1}^{n} \sum_{l=1}^{L} \boldsymbol{e}_l^{\mathrm{T}} \tilde{\mathbf{Y}}_i \left[\mathbf{V}_l + \sum_{m>l}^{L} \mathbf{W}_{l,m} \tilde{\mathbf{Y}}_i^{\mathrm{T}} \boldsymbol{e}_m \right] - $$

$$n \log \left\{ \sum_{\mathbf{Y}} \exp \left(\sum_{l=1}^{L} \boldsymbol{e}_l^{\mathrm{T}} \mathbf{Y} \left[\mathbf{V}_l + \sum_{m>l}^{L} \mathbf{W}_{l,m} \mathbf{Y}^{\mathrm{T}} \boldsymbol{e}_m \right] \right) \right\},$$

which is challenging to maximize directly due to the large number of values of $\mathbf{Y}$ in the summation. Given the high-dimensionality of $\mathbf{V}_l$ and $\mathbf{W}_{l,m}$, the GREMLIN method (Kamisetty et al, 2013) considers the penalized log pseudo-likelihood,

$$ppl(\boldsymbol{\Theta}|\{\tilde{\mathbf{Y}}_i\}_{i=1}^n) = \sum_{i=1}^{n} \sum_{l=1}^{L} \log P(\tilde{\mathbf{Y}}_{i,l}|\tilde{\mathbf{Y}}_{i,-l}, \boldsymbol{\Theta}) - \lambda_1 \sum_{l=1}^{L} \|\mathbf{V}_l\|_2^2$$

$$-\lambda_2 \sum_{m=1}^{L} \sum_{l=1}^{L} \|\mathbf{W}_{l,m}\|_F^2, \tag{S.1.1}$$

where $\tilde{\mathbf{Y}}_{i,l}$ is the one-hot encoding of the amino acid at position l in the i^{th} sequence, and $\tilde{\mathbf{Y}}_{i,-l}$ is the one-hot encoding of the amino acid at all other positions in the i^{th} sequence,

$$\log P(\tilde{\mathbf{Y}}_{i,l}|\tilde{\mathbf{Y}}_{i,-l}, \boldsymbol{\Theta}) = \tilde{\mathbf{Y}}_{i,l}^{\mathrm{T}} \mathbf{V}_l + \sum_{m=1, m \neq l}^{L} \tilde{\mathbf{Y}}_{i,l}^{\mathrm{T}} \mathbf{W}_{l,m} \tilde{\mathbf{Y}}_{i,m}$$

$$- \log \sum_{\boldsymbol{y}} \exp \left[\boldsymbol{y}^{\mathrm{T}} \mathbf{V}_l + \sum_{m=1, m \neq l}^{L} \boldsymbol{y}^{\mathrm{T}} \mathbf{W}_{l,m} \tilde{\mathbf{Y}}_{i,m} \right],$$

where $\boldsymbol{y}$ takes all one-hot encoding values of the amino acid types in the summation. The GREMLIN method then estimates $\boldsymbol{\Theta}$ by maximizing Eq.(S.1.1) with gradient descent using Adam (Kingma, 2014); λ_1 and λ_2 are set to their default values in GREMLIN.

S.1.5 Coevolutionary-Information-Aware Sampling

The details of enhanced (coevolutionary-aware) sampling using coevolutionary information are summarized in Algorithm S.2.

Algorithm S.2 Enhanced Sampling using Coevolutionary Information

---

1: **Input:** MSA subsets from sequential sampling $\mathcal{A}_1, \ldots, \mathcal{A}_{N_{\text{SeqSamp}}}$, target number of iterations n_{iter}, representative MSA subset size K, target MSA subset size for enhanced sampling M.

2: Make predictions on the MSA subsets $\mathcal{A}_1, \ldots, \mathcal{A}_{N_{\text{SeqSamp}}}$ across all five AlphaFold2 models

3: **for** each AlphaFold2 model **do**

4:     Obtain the PCA coordinates of the predicted structures' contact maps $\mathcal{C} = \{\mathbf{C}_1, \ldots, \mathbf{C}_{N_{\text{SeqSamp}}}\}$ for the AlphaFold2 model. The number of principal components is selected to explain at least 90% of the total variance.

5:     **while** iteration number does not exceed n_{iter} **do**

6:         Apply the K-medoids algorithm to the set $\mathcal{C}$ to extract K medoid centers and their corresponding MSA subsets $\tilde{\mathcal{A}}_1, \ldots, \tilde{\mathcal{A}}_K$.

7:         **for** k = 1,…,K **do**

8:             Estimate the MRF model's parameter $\boldsymbol{\Theta}_k$ for the MSA subset $\tilde{\mathcal{A}}_k$

9:         **end for**

10:         **for** each pair of (j, l) with $1 \leq j, l \leq K$, $j \neq l$ **do**

11:             obtain the MSA subset $\breve{\mathcal{A}}_{j,l}$ with size M such that every sequence $\breve{\mathbf{Y}} \in \breve{\mathcal{A}}_{j,l}$ has a larger value of $\frac{\mathrm{P}_{MRF}(\breve{\mathbf{Y}}|\boldsymbol{\Theta}_j)}{\mathrm{P}_{MRF}(\breve{\mathbf{Y}}|\boldsymbol{\Theta}_j)}$ than other sequences

12:         **end for**

13:         store all $\breve{\mathcal{A}}_{j,l}$ in the set of MSA subsets

14:         make predictions on the MSA subsets with the AlphaFold2 model

15:         Update $\mathcal{C}$ with the PCA coordinates of the new predicted structures' contact maps $\mathcal{C} = \{\mathbf{C}_1, \ldots, \mathbf{C}_{N_{\text{enhanced}}}\}$ for the AlphaFold2 model, where $N_{\text{enhanced}} = K(K-1)$

16:     **end while**

17: **end for**

18: **Output:** All sampled MSA subsets.

S.1.6 Identifying Regions of High Structural Variability

The details of identifying variable regions are summarized in Algorithm S.3. To ensure the target variable region is entirely contained within the initial candidate region, we

set an initial candidate region size that is sufficiently large. Additionally, the number of residues outside this region needs to be large enough to compute a reliable baseline of structural variance. Accordingly, we empirically set the initial candidate region size $w_{\text{init}} = \max(L - 40, 40)$, and the minimum variable region size $w_{\text{min}} = 40$, as stable protein domains are typically longer than 40 residues.

Algorithm S.3 Identifying Region of High Structural Variability

---

1: **Input:** protein length L, ensemble of N_{SMICE} predicted contact maps $(\mathbf{C}_1, \mathbf{C}_2, \ldots, \mathbf{C}_{N_{\text{SMICE}}})$, initial candidate region size w_{init}, desired minimum window size w_{min}.

2: **Step 1: Calculate Variance Matrix**

3: $\mathbf{\Sigma} \leftarrow \text{Var}(\mathbf{C}_1, \mathbf{C}_2, \ldots, \mathbf{C}_{N_{\text{SMICE}}})$ $\triangleright$ Compute the $L \times L$ variance matrix

4:

5: **Step 2: Find Initial Window**

6: $(i, j) \leftarrow \underset{1 \le i \le L - w_{\text{init}} + 1}{\text{argmin}} \left(\sum_{a \notin [i, i + w_{\text{init}} - 1]} \sum_{b \notin [i, i + w_{\text{init}} - 1]} \mathbf{\Sigma}_{ab} \right)$

7: $j \leftarrow i + w_{\text{init}} - 1$ $\triangleright$ Set initial window boundaries $[i, j]$

8:

9: **Step 3: Calculate Baseline**

10: $\beta \leftarrow \text{mean}\left(\{ \mathbf{\Sigma}_{ab} \mid \forall a \ne b \notin [i, j] \} \right)$ $\triangleright$ Baseline variance of conserved region

11:

12: **Step 4: Refine Region by Stepwise Deletion**

13: **while** $(j - i + 1) \ge w_{\text{min}}$ **do**

14:      $S_{\text{left}} \leftarrow \sum_{a \notin [i+1, j]} \sum_{b \notin [i+1, j]} \mathbf{\Sigma}_{ab}$ $\triangleright$ Score if left residue removed

15:      $S_{\text{right}} \leftarrow \sum_{a \notin [i, j-1]} \sum_{b \notin [i, j-1]} \mathbf{\Sigma}_{ab}$ $\triangleright$ Score if right residue removed

16:      **if** $S_{\text{left}} < S_{\text{right}}$ **then**

17:          $l \leftarrow i$

18:          $i \leftarrow i + 1$ $\triangleright$ Remove the leftmost residue

19:      **else**

20:          $l \leftarrow j$

21:          $j \leftarrow j - 1$ $\triangleright$ Remove the rightmost residue

22:      **end if**

23:      $\delta \leftarrow \text{mean}\left(\{ \mathbf{\Sigma}_{lb} \mid \forall b \notin [i, j] \} \right)$ $\triangleright$ Variance of candidate's external contacts

24:      **if** $\delta > 4\beta$ **then**

25:          **break** $\triangleright$ Terminate if variability of the conserved region increases

26:      **end if**

27: **end while**

28:

29: **return** $[i, j]$ $\triangleright$ Return indices of the variable region

30: **Output:** $[i, j]$: Start and end indices of the identified variable region

---

S.2 Experiment Implementation Details

S.2.1 MSA Generation

MSAs were generated using MMseqs2 (Steinegger and Söding, 2017) implemented in ColabFold (Mirdita et al, 2022) by querying the UniRef30 database (Suzek et al, 2015) of known sequences. Sequences were filtered to retain only those with $\geq 90\%$ identity to the target sequence. The minimum coverage required for the MSA sequences is 75%. The MSA was enforced to have at most 4,096 sequences.

S.2.2 SMICE, AF-Cluster and Random Sampling

As discussed in Section S.1, we consider 80 different hyperparameter configurations for MSA subset generation when the number of sequences exceeds 100, and 40 configurations when it is below 100. These configurations consist of four levels of λ, and 20 choices of Π for deep MSAs (sequence number ≥ 100) or 10 choices for shallow MSAs (sequence number < 100). For each configuration, we randomly draw four subsets using sequential sampling. We exclude any MSA subsets containing fewer than 10 sequences to ensure reliable AlphaFold2 predictions. Each remaining MSA subset is used to generate structures using ColabFold v1.5 with default settings, which outputs five predictions per run using AlphaFold2. No template structure is used in the prediction. The coevolutionary-information-aware sampling procedure is iteratively repeated twice ($n_{iter} = 2$), and we set the representative MSA subset K in Algorithm S.2 as five, and the target MSA subset size in this enhanced sampling as $M = 20$ if the full MSA has less than 300 sequences, and $M = 20$ and 100 if the full MSA has more than 300. This results in 200 predictions for deep MSA cases and 100 predictions for shallow MSA cases per iteration. In total, we obtain up to 1,800 predictions for deep MSAs and up to 900 predictions for shallow MSAs.

The results of *AF-Cluster* as well as *random sampling* are produced using the default setup of the AF-Cluster pipeline (Wayment-Steele et al, 2024). In the pipeline, uniform random sampling without placement is run up to 200 times on each MSA with sample sizes $= 10$ and 100 (if the full MSA has more than 100 sequences). The predictions are made using ColabFold v1.5 with default settings.

S.3 Ablation Study of SMICE's sampling step

We estimate the relative importance of key components of SMICE's sampling step by comparing several ablations on SMICE:

SMICE (Full). SMICE (Full), as described in the paper, returns the full set of predictions generated by SMICE's sampling step, including those from the sequential sampling and the enhanced sampling.

SMICE (not enhanced). SMICE (not enhanced) returns the predictions from the sequential sampling only.

SMICE (no coevol). For SMICE (no coevol), we remove the coevolutionary term in the MRF model when conducting the enhanced sampling, i.e., we replace Eq.(6)

with

$$P_{MRF_{nocoevol}}(\mathbf{Y}|\mathbf{\Theta}) \propto \exp\left(\sum_{l=1}^{L} \boldsymbol{e}_l^{\mathrm{T}} \mathbf{Y} \mathbf{V}_l\right), \tag{S.3.2}$$

and estimate $\mathbf{V}_l$ with the corresponding penalized log pseudo-likelihood,

$$ppl_{nocoevol}(\mathbf{\Theta}|\{\tilde{\mathbf{Y}}_i\}_{i=1}^n) = \sum_{i=1}^{n}\sum_{l=1}^{L} \log P_{nocoevol}(\tilde{\mathbf{Y}}_{i,l}|\tilde{\mathbf{Y}}_{i,-l},\mathbf{\Theta}) - \lambda_1 \sum_{l=1}^{L} \|\mathbf{V}_l\|_2^2$$

$$= \sum_{i=1}^{n}\sum_{l=1}^{L} \left[\tilde{\mathbf{Y}}_{i,l}^{\mathrm{T}}\mathbf{V}_l - \log\sum_{\boldsymbol{y}} \exp \boldsymbol{y}^{\mathrm{T}}\mathbf{V}_l\right] - \lambda_1 \sum_{l=1}^{L} \|\mathbf{V}_l\|_2^2,$$

SMICE (no coevol) returns the combined predictions from sequential sampling and enhanced sampling using the MRF model without the coevolutionary term.

Ablation results are presented in Fig. S.1. We found that both the overall prediction quality and the top prediction accuracy were improved by including the MRF model, even when coevolutionary information was not used in the MRF model. Incorporating coevolutionary information in SMICE (Full) further improved performance compared to SMICE (no coevol) in certain fold-switching protein cases.

S.4 Confidence Metrics Failed to Rank the Predictions of Fold-switching Proteins

AlphaFold2's built-in confidence metrics (pLDDT, predicted TMscore (PTM), and predicted aligned error (PAE)) are widely used for ranking predictions. While higher pLDDT/PTM (with range 0-1) and lower PAE (with range ≥ 0) typically indicate higher confidence, we find these scores unreliable for directly ranking predictions of fold-switching proteins.

Our analysis of SMICE's sampling step for the benchmark set of fold-switching proteins shows a general trend: pLDDT and PTM positively correlate with prediction accuracy (measured by TMscore1, TMscore2, and max-TMscore), and PAE shows a negative relationship (Fig. S.2). However, pLDDT and PTM are often overestimated, and PAE is usually underestimated. For example, predictions with high pLDDT scores (close to 1.0) exhibit a wide range of max-TMscore values (0.4–1.0).

This issue becomes clear when examining individual fold-switching proteins. For example, a fragment of the parainfluenza virus 5 fusion protein has two conformations (Fold1: 1svfC, Fold2: 4wsgC), and the Spearman correlation between the predictions' pLDDT and max-TMscore is statistically significantly negative (correlation value = -0.228, p-value = 1.146×10^{-15}; Fig. S.3a). This counterintuitive result extends to a substantial subset of all fold-switching proteins for other confidence metrics (PTM, PAE) across all TMscore measures (TMscore1, TMscore2, and max-TMscore) (Fig. S.3b).

We attribute this phenomenon to a systematic bias between the confidence scores of the two conformations. In the example above, predictions resembling 4wsgC (red) have systematically higher pLDDT but lower max-TMscore than those resembling

S.1 Comparing the sampling step of SMICE with and without MRF enhanced sampling, and the sampling step of SMICE without coevolutionary information in enhanced sampling. **a-c**, Comparison results on the max-TMscore1, max-TMscore2, and minimax-TMscore. **d-f**, Comparison results on the proportions of predicting Fold1, the proportion of predicting Fold2, and the minimum proportions of predicting both folds.

1svfC (blue). Consequently, while the relationship between pLDDT and max-TMscore is positive within the group of predictions similar to 4wsgC, the combination of both groups creates an overall negative relationship.

Nevertheless, pLDDT remains a useful metric for filtering out low-quality predictions, as low pLDDT values consistently correspond to low max-TMscores (Fig. S.2a).

S.5 Selecting the pLDDT Threshold for Prediction Filtering

We compared the full prediction set from the SMICE's sampling step against the prediction sets filtered by pLDDT thresholds (0.3, 0.4, 0.5, 0.6) to select the best threshold based on six metrics from our benchmark study. The three metrics, including max-TMscore1, max-TMscore2, and minimax-TMscore, assess the accuracy of the top prediction for each prediction set. Since filtering removes predictions, the values for

S.2 a, pLDDT versus max-TMscore, TMscore1, and TMscore2 for all fold-switching protein predictions. The filtering threshold (pLDDT = 0.5) is visualized with the red dashed line. **b**, PAE versus max-TMscore, TMscore1, and TMscore2 for all fold-switching protein predictions. **c**, PTM versus max-TMscore, TMscore1, and TMscore2 for all fold-switching protein predictions.

these metrics in the filtered prediction set cannot exceed those of the full set. Therefore, an optimal threshold is one that preserves these scores as close as possible to their values in the full prediction set. The other three metrics, including the proportion for predicting Fold1, the proportion for predicting Fold2, and the minimum proportion for both folds, measure the overall accuracy of the prediction set. For these metrics, the goal is to choose a threshold that maximizes their values.

Given this, we found that pLDDT thresholds of 0.3, 0.4, and 0.5 performed almost equally well in the top predictions' accuracy as the full prediction set (Fig. S.4a-c). Furthermore, a threshold of 0.5 provided the greatest improvement in overall prediction accuracy, making it our chosen value (Fig. S.4d-f). By uniformly applying a pLDDT threshold of 0.5 to all predictions, we successfully filtered out approximately 24% of the predictions.

In contrast, filtering based on either PTM or PAE did not yield a significant improvement in overall prediction accuracy, as shown in Fig. S.5.

S.3 **a**, For the fold-switching protein with the two conformations (PDB IDs: 1svfC and 4wsgC), the pLDDT scores and max-TMscore exhibit a negative correlation (red dashed line represents the regression fit of the pLDDT scores against max-TMscore). Predictions are colored by the signed max-TMscore (sign[TMscore1 – TMscore2] × max-TMscore). **b**, Spearman correlation between confidence metrics (pLDDT, PAE, and PTM) and max-TMscore versus the correlation test p-values across all fold-switching proteins. The red dashed line marks significance (p-value = 0.05). **c**, Spearman correlation between confidence metrics (pLDDT, PAE, and PTM) and TMscore1 versus the correlation test p-values across all fold-switching proteins. The red dashed line marks significance (p-value = 0.05). **d**, Spearman correlation between confidence metrics (pLDDT, PAE, and PTM) and TMscore2 versus the correlation test p-values across all fold-switching proteins. The red dashed line marks significance (p-value = 0.05).

S.4 Filtering prediction sets from the SMICE's sampling step based on pLDDT thresholds (greater than 0.3, 0.4, 0.5, 0.6). **a-c**, Comparison of the full prediction set against the filtered prediction set on the max-TMscore1, max-TMscore2, and minimax-TMscore. **d-f**, Comparison of the full prediction set against the filtered prediction set on the proportions of predicting Fold1, the proportions of predicting Fold2, and the minimum proportions of predicting both folds.

S.5 Filtering prediction sets from the SMICE's sampling step based on PAE and PTM thresholds. **a-c**, Comparison of the full prediction set against sets filtered by PAE thresholds ($< 0.05, 0.1, 0.2, 0.3$), showing the proportions of predicting Fold1, the proportions of predicting Fold2, and the minimum proportions of predicting both folds. (D)-(F). Comparison of the full prediction set against sets filtered by PTM thresholds ($> 0.2, 0.3, 0.4, 0.5$), showing the proportions of predicting Fold1, the proportions of predicting Fold2, and the minimum proportions of predicting both folds.