The persistence and loss of hard selective sweeps amid ancient human admixture

Mariana Harris[1], Ziyi Mo[2,3], Adam Siepel[2,3] and Nandita Garud[4,5,*]

[1] Department of Computational Medicine, University of California Los Angeles, Los Angeles California, USA

[2] Simons Center for Quantitative Biology, Cold Spring Harbor Laboratory, Cold Spring Harbor, New York, United States of America

[3] School of Biological Sciences, Cold Spring Harbor Laboratory, Cold Spring Harbor, New York, United States of America

[4] Ecology and Evolutionary Biology, University of California Los Angeles, Los Angeles California, USA

[5] Department of Human Genetics, University of California, Los Angeles, California, USA

[*] Correspondence to ngarud@ucla.edu

Abstract

The extent to which human adaptations have persisted throughout history despite strong eroding demographic events such as admixture, genetic drift, and fluctuations in selection pressures remains unknown. Understanding which loci are particularly resilient to such forces may shed light on the traits that were important for humans throughout multiple time periods. Yet, detecting ancient selection events is challenging from modern and ancient DNA due to the data and/or signal being severely degraded. Here we use a domain-adaptive neural network (DANN) trained on simulated data and applied to ancient and modern DNA for sweep detection. We show that the DANN can account for simulation misspecification, or discrepancies between the simulations and real aDNA, thereby improving the ability to detect sweeps in real data. Application of the DANN to more than 800 ancient and modern human genomes spanning the last 7000 years recovered 16 known sweeps at loci including *LCT*, *HLA*, *KITLG,* and *OCA2/HERC2*, and revealed 32 novel sweeps. All identified sweeps were classified as hard, consistent with historically low population sizes. While some sweeps were lost over time, 14 sweeps at loci involved in a range of functions including neuronal, reproductive, pigmentation, and signaling traits were found to persist from the most ancient time periods into the most recent time periods. Notably, the same top haplotype remained at high frequency across time at 9 of these 14 sweeps. Together, these results indicate that hard sweeps predominated in ancient human history and that several ancient selective events were resilient to strong admixture events and experienced sustained selective pressures.

Introduction

The growing availability of ancient DNA (aDNA) has revolutionized our ability to study how evolution has shaped human populations over the past ~12,000 years. The transition from mobile hunter-gatherer groups to sedentary, agriculture-based societies introduced profound selective pressures including shifts in diet, sustained contact with domesticated animals, and heightened pathogen exposure[1,2]. During this same period, repeated waves of migration and admixture among Western Hunter-Gatherers, Anatolian early farmers, and Steppe pastoralists continually reshaped the genetic landscape of Eurasia. These demographic events may have diluted or masked historical selective sweeps in present-day genomes[3], leaving the prevalence, persistence, and modes of selective sweeps across Eurasian populations largely unresolved.

Characterizing the targets as well as the mode and tempo of positive selection in aDNA can reveal the mechanisms and rate of human evolutionary change. However, the ability to detect adaptation in aDNA can be challenging for a number of reasons, including low read coverage, short read lengths, high levels of missing data, and the complex, often poorly characterized demographic history of human populations. Despite these challenges, several studies have shown that directional selection in humans may have been widespread[3–5]. However, these studies have largely been powered to detect classic 'hard' sweeps, in which a single adaptive variant rising to high frequency leaves behind a characteristic dip in diversity with a single dominant haplotype. In addition to hard sweeps, there may have been 'soft' sweeps, whereby multiple adaptive variants rise to high frequency simultaneously given large mutational inputs or abundant standing genetic variation (SGV) at the onset of selection[6,7]. Soft sweeps are more challenging to detect given that they leave behind more subtle signatures in the data due to there being multiple haplotypes rather than a single haplotype at high frequency[8,9]. Given the combination of data challenges, which can generate misleading signals that appear adaptive but actually stem from demographic forces or data artifacts[10–13], and the difficulty in detecting soft sweeps, it remains unknown how many historical sweeps have been missed and whether they were hard or soft.

Deep learning methods have emerged as a powerful tool in population genetics to address a wide variety of inference problems from genomic data including demographic inference[14,15], estimating recombination rates[16,17] and detecting selection[16,18–21]. In particular, convolutional neural networks (CNNs) have proven particularly effective in detecting selective sweeps, largely

due to their ability to extract complex patterns from noisy, high-dimensional population genetic

data. Notably, CNNs can natively handle multi-dimensional input, leveraging the full richness of

raw genotype matrices without reducing it to a small set of summary statistics[16,18]. Despite their

flexibility and strong performance on modern data and other organisms[16,19], deep learning methods

have not yet been applied to aDNA to detect selection.

A key limitation to current approaches is that they rely on large amounts of labeled training

data, which are typically generated through simulations based on simplified models that are

restricted in their ability to fully capture the complexities of real genomic data. Discrepancies

between simulated and real datasets can arise from inaccurate assumptions about demography,

mutation and recombination rates, or from data artifacts. Additionally, modeling features such as

large effective population sizes (N_e), heterogeneous recombination landscapes, or complex

demographic histories can be computationally intensive[17,22], making such simulations impractical

at the scale required for deep learning.

This mismatch between simulated training data and real genomic data, known as a

simulation mis-specification[23], can reduce model accuracy and lead to inferences from data that

are not robust. Several strategies have been proposed to address this issue including adaptive re-

weighting of training examples[15,24,25]. Domain adaptive neural networks (DANNs)[26,27], have

recently been proposed as another alternative to mitigate simulation mis-specification[26].

Domain adaptation aims to improve generalization by enabling a model trained on data

from a source domain, in this case simulated data, to perform well on a target domain with different

properties, such as real population genomic data[28]. This technique is widely applied in computer

vision; for example, facial recognition models trained on high-quality studio images can be

adapted to perform more reliably on lower-quality surveillance footage. It is also used in natural

language processing, where models trained on reviews of books may require adaptation to

accurately interpret sentiments in reviews of other products. In biology, domain adaptation has

been used to predict transcription factor binding across distinct species[29]. Building on these

applications, Mo and Siepel demonstrated that domain adaptation could also be leveraged to

improve population genetic predictions, including detecting selective sweeps, inferring selection

strength, and estimating recombination rates in the face of demographic misspecification[26] .

Given the unique challenges of aDNA, domain adaptation presents a powerful framework

for characterizing selection across different periods of human history. Here we propose a novel

application of a DANN to distinguish between hard sweeps, soft sweeps, and neutrality in aDNA and modern DNA. We find that hard sweeps were common throughout human history, consistent with historically low population sizes, and that several sweeps have persisted over multiple time periods, implying shared selective pressures over human history and resilience to major demographic events.

Results

Data

In this work, we train a DANN to detect selective sweeps from 708 aDNA samples from Europe that we analyzed previously[30], dated between ~7000 and 1345 years before present (BP) (**Fig. 1A,B**). These samples are from populations that underwent major admixture events, including the migration of Anatolian farmers into Europe and their admixture with local Mesolithic hunter-gatherers around 8,500 BP, as well as the mixing of European farmers with steppe pastoralists at the onset of the Bronze Age ~5000 BP[31] (**Fig. 1C**). This transitional period is particularly important for studying adaptation, as it has been hypothesized that admixture has obscured selective sweep signatures in modern humans and as a result the extent of selection has likely been underestimated[3].

Based on direct radiocarbon dates and archaeological context, the samples were grouped into four chronological periods with 177 samples per period as follows (**Fig. 1B**):

Neolithic (N): Individuals of European Hunter-Gatherer and Anatolian farmer ancestry dated between 6500 and 5019 BP.

Bronze Age (BA): Individuals from the Bell Beaker cultures of Western and Central Europe, dated between 4495 to 3808 BP.

Iron Age (IA): Individuals from Iron Age Britain and Western Europe dated between 3995 to 2350 BP.

Historic period (H): Individuals from Roman and late antique periods between 2300 to 1345 BP.

To ensure data quality, we only included samples for which a number of criteria could be met (Methods), including requiring hybridization capture on at least 1.2 million positions, having

a minimum of 15,000 SNPs such that robust population genetic inferences could be performed,

did not have significant contamination on the mtDNA or X chromosome (in males), were unrelated

up to the third degree, and treated with the same Uracil-DNA Glycosylase process during library

preparation. The last two bases were trimmed from each read to exclude the most damaged regions

of aDNA. After selecting high quality samples, to have similar power to detect sweeps across

different time periods, we chose the 177 hosts with highest coverage for each time period for

further analysis, resulting in a total of 708 genomes (**Table S1**). These 177 hosts were subsequently

down sampled per analysis window to the 150 individuals with the least amount of missing data.

Additionally, we analyzed 99 modern European individuals (CEU) from the 1000 genomes

project[32]. We restricted the 1000 genomes samples to the 1.2 million positions that were in the

aDNA capture array.

Figure 1. Location and age of samples included in study. **(A)** The locations of the 708 ancient

human samples colored by their corresponding time periods. **(B)** Archeological or radiocarbon

dates for each sample in years before present (BP). Each data point represents one sample and the

colors indicate broader groupings according to four time periods. **(C)** Diagram of West Eurasian

population history. Modern Europeans are composed of three main ancestries: Western Hunter-

Gatherers, Anatolian early farmers and Steppe pastoralists. The vertical grey segments represent

distinct population branches and arrows represent population splits and admixture events. Shown

are four main branches: the African (Mbuti) branch, Eurasian branch, West Hunter-Gatherers

(WHG), Caucasus Hunter-Gatherers (CHG) and Eastern Hunter-Gatherers (EHG). Highlighted are

the time ranges which our samples come from in the Eurasian branch. Also highlighted are the

admixture proportions and timing of events. The red arrow depicts a major admixture event

overlapping the timeframe during which our samples were collected. The full schematic of the

model with all associated parameters can be found in Souilmi et al. 2022 and original studies from

which these parameters were estimated[3,33–35] .

Architecture of the DANN for sweep detection

Before applying a DANN to aDNA, we tested its ability to (1) unlearn any differences

between simulated and real data including underlying demography or missing data rates and (2)

simultaneously distinguish between neutrality, hard sweeps, and soft sweeps. Since the goal of the

DANN is to both classify sweeps from neutrality and unlearn differences between domains, a

DANN differs from a more traditional neural network classifier by including not only a

classification branch, but also including a discriminator branch that distinguishes between a *source*

domain (e.g. simulations) and a *target* domain (e.g. real data) (**Figure 2**). One strategy for domain

adaptation, which we use here, is the addition of a gradient reversal layer (GRL)[27]. During

backpropagation, the sign of the gradient of the loss of the discriminator is reversed through the

GRL, penalizing features that discriminate between domains and promoting domain-invariant

features that are essential for sweep classification (Methods).

As input to the model, we provide images of haplotypes sorted by the frequency of most to

least common haplotype. Because of the low coverage nature of aDNA as well as ascertainment

bias in calling ancient SNPs, previous work has shown that heterozygous sites are not always

reliably determined. To address this issue, we used our previous approach[30] to 'pseudo haploidize'

the data by randomly selecting one of the reads mapping to a position and assigning the genotypes

of the read as the genotype of the sample at that site (Methods). This data was then used as input

to the DANN.

The images provided to the DANN are $n \times S$ bi-allelic genotypic matrices representing the

allelic states at $S=201$ segregating sites across $n=150$ pseudo haplotypes, downsampled from an

initial sample of 177 by retaining those with the least missing data (**Figure 2B**). These parameters reflect our previous findings[30] that a window size of 201 segregating sites, or approximately ~450 kb in aDNA, is adequate for capturing signals of selection in this dataset using haplotype homozygosity statistics. In addition, sorting haplotype images based on haplotype distances or frequencies has been shown to be essential for strong performance of CNN models[16,18,36]. We tested three different sorting approaches each designed to emphasize either elevated haplotype homozygosity typical of hard sweeps, or the presence of multiple high-frequency haplotypes characteristic of soft sweeps (Methods, **Fig. S1, Text S1**).

Figure 2. Domain Adaptive Neural Network (DANN) for detection of selective sweeps. (A) DANN Architecture. Haplotype images from both the source and target domains are passed through a series of convolutional layers, with dimensionality reduced by max-pooling steps

(green). The output is flattened into a feature vector, which is then processed by two branches of

fully connected layers: the classifier, which predicts the sweep class (blue), and the discriminator,

which distinguishes between domains (yellow). During backpropagation, the gradient reversal

layer (GRL) inverts the loss from the discriminator, discouraging the model from differentiating

between the domains and promoting domain-invariant features. The grey arrows indicate the

forward pass and black arrows indicate backpropagation. **(B) Genomic data representation.**

Genomic data is represented as images, with rows corresponding to sampled haplotypes and

columns to segregating sites (201 SNPs). Each pixel represents the occurrence of a specific allele

with major allele shown in red, minor allele in black, and missing data in white, coded as -1,1 and

0 respectively. On the left, we show a haplotype image of a simulated partial hard sweep where no

sorting was applied. To the right we show the same image but sorting the rows (haplotypes) by

frequency. Although the colors are used for visualization, the data is treated as a black and white

image, where alleles are biallelic (major vs. minor).

Benchmarking DANN on simulated data

To assess the ability of the DANN to correct for simulation misspecification we evaluated

the model using simulated data for both the source and target domains. We performed simulations

varying the degree of mismatch between the target and source domains in terms of demography

and missing data rates, as we expected these two variables to contribute the largest amount of

discrepancy between real data and simulations. In all scenarios evaluated, the target domain, used

as a proxy for real aDNA, consisted of simulations of a previously inferred admixture model

describing ancient Europeans[3,33–35] (**Fig. 1C**) with missing data at the rate of 43% per base pair,

reflecting the rates of missing data of the samples analyzed in this study (Methods, **Fig. S2**). To

evaluate the ability of the DANN to correct for misspecification, we compared the performance of

the DANN to that of a standard CNN lacking a discriminator branch but still having misspecified

source and target domains. We evaluated the CNN on two test sets, one on a hypothetical best case

scenario with matching target and source domains (hypothetical best case), and another one with

mismatched domains (standard CNN, **Fig. S3**). This comparison allowed us to assess how much

improvement the DANN could achieve under varying degrees of misspecification .

We found that for all simulation scenarios, the DANN outperformed the CNN, albeit

modestly, when the target and source domains did not match, demonstrating its ability to mitigate

misspecification (**Fig. 3A, Fig S4**). Moreover, we found that the DANN could correct for

mismatch in demography better than mismatch in missing data rates between target and source

domains with the DANN performing slightly better in mitigating the most extreme

misspecification in demography (constant N_e vs. Admixture; area under the precision-recall curve

(AUPRC) of 0.814) compared to the most extreme misspecification in missing data rates (5% vs

43%; AUPRC =0.80) (**Fig. 3A**). This suggests that missing data introduces a more challenging

form of misspecification, making it harder to correct using a domain-adaptive framework.

Additionally, the DANN outperformed the haplotype homozygosity statistic H12[37], recently

applied to aDNA data[30], with AUPRCs of 0.942 vs 0.898 for sweep detection, respectively

(**Fig. 3B, Fig S5,6**). Finally, we found that in a model trained on a source domain of constant N_e

with 43% missing data and target domain of admixture with 43% missing data, the DANN had an

AUPRC of 0.956 for hard sweeps and 0.844 for soft sweeps (**Fig. S5**). We found similar

performance when we trained with real aDNA for the target domain in order to explicitly unlearn

the differences between simulated and real data (**Methods, Fig. S8**).

Figure 3. Domain adaptive neural network improves the detection of selective sweeps in

simulated data that mimics aDNA. (A) AUPRC of the DANN (yellow). This is compared with

a hypothetical best case simulation benchmark CNN representing an upper bound on performance.

This benchmark was trained and tested on the source domain (grey). Additionally in red is a

standard application of the CNN tested on a misspecified domain with mismatching demographic

model and missing data (MD) compared to the source domain. **(B)** Precision-recall curve for

detection of sweeps (hard and soft) from neutrality using a constant N_e model as a source domain

and a human admixture model, both with an average of 43% missing data per site as a target

domain.

The ability to detect selective sweeps may vary with the strength of selection and the

softness of the sweep. To systematically evaluate the performance of the DANN across a range of

selection coefficients, we tested the model on weak (s~[0.005,0.05]) versus strong (s~[0.05,0.1])

selection, as well as on sweeps of varying softness modulated by rate of input of adaptive mutations

$\theta_A = 4N_e\mu_A$, where μ_A is the adaptive mutation rate. We found that when selection is strong,

irrespective of the softness of the sweep, we could distinguish sweeps from neutrality correctly

93% or more of the time (**Fig. S7**). However, when selection is weak, the ability to correctly

distinguish a sweep from neutrality drops to 60%, especially in the scenarios where sweeps are

extremely soft (θ_A =5). This result implies that the DANN has the greatest ability to detect sweeps,

either hard or soft, when selection is sufficiently strong.

We next asked how often soft sweeps are misclassified as hard sweeps and vice versa,

conditional on being distinguishable from neutrality (**Fig. S7**). We found that the majority of hard

sweeps (82%) are correctly classified as hard, with this percentage increasing to 93% for strong

selection. Similarly, we found that the majority of soft sweeps (~75%) are correctly classified as

soft, with this percentage increasing to 86% as θ_A increases to 5 when the signatures of hard vs

soft sweeps become most distinct.

Application of the DANN to aDNA and modern humans

Having confirmed the ability of the DANN to detect selective sweeps in simulations, we

trained a DANN using empirical aDNA as the target domain and simulations generated under the

admixture model shown in Figure 1 with a 43% missing data rate as the source domain. To identify

selective sweeps in aDNA, we next applied the DANN to genome-wide aDNA data across all time

periods. We used a sliding window of 201 SNPs, advancing each window by 10 SNPs. To ensure

predictions are well supported by more than one window, we averaged the predicted probabilities

every five consecutive, overlapping windows, generating the final class predictions (**Methods**).

Each window was assigned to the class with the highest predicted probability from the model's

multiclass output (hard sweep, soft sweep, or neutral). We show the resulting scan across the

aDNA time transect in **Fig. 4A**, where windows predicted to be hard sweeps are shown in red, soft

in blue, and neutral regions in grey. In addition, In **Fig. 4B**, we show a scan on the modern

European population (CEU). This scan was generated using a different model trained on modern

human data as the target domain (Methods).

To avoid calling the same selective sweep multiple times, we grouped consecutive non-

neutral windows into a single 'peak'. Additionally, to ensure distinct selective events, we further

required peaks to be at least 1.5 Mb apart. Within each peak, we identified the representative

window as the one with the highest sweep probability (the highest –log(probability of neutrality)).

We identified a total of 48 unique sweeps in ancient humans (**Fig 4A**) and 28 selective

sweeps in modern humans. Among the 48 ancient human sweeps, over half the sweeps recurred

across multiple periods with 5 detected in all periods, 8 in three, 12 in two, and 23 in only one

(**Fig. S9**). Additionally, 18 ancient sweeps were found to persist in modern humans with 5 of these

sweeps present in all ancient human time periods resulting in 58 unique peaks across all ancient

and modern periods. To assess the robustness of our sweep inferences in ancient humans, we

trained two additional models varying the source domain, and observed high concordance across

models both in sweep detection and classification, with 44 sweeps overlapping in all three scans

(**Fig. S10A**, **Fig. S11, Table S2**).

Out of the 48 sweeps detected in ancient humans (**Figure 4A)**, 16 overlap with recent

studies[3–5,30,38–40]. Among these are 5 sweeps overlapping well known targets of selection

highlighted in **Fig. 4**. The strongest signal across all time periods corresponds to the *HLA* region

and neighboring gene *ZKSCAN3*. *HLA* encodes cell surface proteins that are involved in the

adaptive immune system and has long been recognized as a target of selection[41,42] and *ZKSCAN3*

is involved in transcriptional regulation of autophagy-related genes and was reported as under

selection in Mathieson et al. 2015. We also detect a sweep spanning the *OCA2/HERC2* genes,

which is associated with light eye color in Europeans[38]. We identify this signature across all four

time periods, which was not observed in earlier scans across the same time transect[30,40]. Our scan

also recovers a strong sweep signal at the *LCT* locus, which is associated with lactase persistence

into adulthood[43,44]. This signal is restricted to the H period and the CEU population (**Fig. 4**),

consistent with the rapid rise in frequency of the causal variant rs4988235 during this time.

Notably, this allele was absent in Europe prior to the arrival of Steppe pastoralists in the Bronze

Age and therefore could not have been under selection earlier[30,38,40,45–47]. We also highlight a sweep

overlapping the gene *KITLG*, associated with light hair and skin pigmentation and recently

identified as a target of selection, and *SLC22A4,* associated with Crohn's disease[4]. We summarize

the number of sweeps that overlap with previous work in **Table S3** and **Fig. S12,S13**.

The remaining 32 ancient sweeps we identify represent novel candidates that, to our

knowledge, have not been identified in previous studies. We do not consider peaks as novel

candidates if they are within 1Mb away from genes that have been previously identified as sweep

candidates[3–5,30,38–40]. To understand if the genes within these 32 peaks are enriched for any

functions, we assigned peaks to genes by annotating all protein coding genes within 300 Kb

distance upstream and downstream of the representative SNP of each peak using Ensembl Variant

Effect Predictor (VEP) (Supplementary table S5). We next performed an enrichment analysis for

previously identified genome-wide association study (GWAS) annotations on the set of mapped

genes using Functional Mapping and Annotation of Genome-Wide Association Studies (FUMA)[48].

We observed an enrichment in many GWAS categories related to anthropometric traits as well as

disease and auto-immune related traits. These results are reported in **Fig. S14.**

Figure 4. Genome-wide selection scan with the DANN in ancient and modern data. Results

for the DANN are shown for all four ancient time periods highlighted at the top of each panel **(A)**

and for modern Europeans **(B)**. The time period range is specified as years before present (BP).

The y-axis shows the probability of selection -log(P_{neu}) predicted using the DANN, whereby a high

value indicates the window is likely under selection. The x-axis shows the genomic position. The

DANN was trained using a human admixture model with missing data as the source domain and

aDNA data as target domain. Windows predicted as hard sweeps are colored in red and windows

predicted as soft are colored in blue. Sweeps previously reported in the literature are highlighted above the peaks. We highlight with purple vertical bands 14 sweeps that are present across the two ends of the major admixture event that occurred ~4.5 kya, that is sweeps that are detected in earlier periods (N or BA) and are also detected in later periods (H or CEU).

Hard sweeps were common in ancient and modern humans

We next analyzed whether sweeps discovered in aDNA and modern humans were predominantly hard or soft. The DANN classified all 58 sweeps (ancient and modern) in **Fig. 4** as hard. In three cases, we observe that windows on the edges of the peak are classified as soft (chromosomes 6 and 15, **Figs. 4 and S15)**. This pattern is consistent with the "soft shoulder effect"[49], where recombination causes regions flanking a hard sweep to exhibit patterns that resemble a soft sweep. However, based on our peak calling approach, these flanking regions are not classified as independent soft sweeps. Instead, they are grouped with adjacent windows into a single peak, which is then labeled according to the window with the highest sweep probability.

To evaluate whether the predicted hard sweeps may reflect a high rate of soft-to-hard sweep misclassification by the model, we use simulated data from the human admixture model to estimate the proportion of predicted hard sweeps that may actually correspond to soft sweeps misclassified as hard. Applying these rates (**Fig. S16**) to our ancient hard sweep predictions, we estimate that, conservatively, 83% of detected sweeps are hard and 15% are soft, indicating that despite any potential for misclassification, hard sweeps were likely common in ancient human populations. It is important to note, however, that these error rate estimates are rough approximations based on simulated data, as the true labels in real aDNA are unknown.

Additionally, to assess robustness of our results to the underlying model of soft sweeps, we trained a model in which soft sweeps were simulated from standing genetic variation (SGV) rather than recurrent *de novo* mutations (**Fig. S10B**). We identified a total of 53 unique sweeps in aDNA, 43 of which overlap with the scan trained on *de novo* soft sweeps. Of the 53 sweeps, 38 are classified as hard, 9 as soft and 6 change classification from hard to soft across time periods. However, we note that the predicted probabilities for soft sweeps are low, ranging from 0.34-0.44, where 0.33 is the probability of predicting either hard, soft or neutrality at random. By contrast, the predicted probabilities for hard sweeps range from 0.34-0.93, suggesting that the support for peaks classified as soft is weak.

To further validate whether the peaks detected by the DANN are in fact hard sweeps, we

visualized the central window of all peaks detected in Figure 4. By visual inspection, we observe

a single haplotype at high frequency across all windows, consistent with partial hard sweeps, as

highlighted in 24 examples in **Fig. S17**. These windows are distinct from windows classified as

soft on chromosome 6 of period H (**Fig. S18**), whereby multiple haplotypes are at high frequency,

and distinct from windows classified as neutral, whereby no haplotypes are at high frequency (**Fig**

S18).

In addition to the above, to further confirm inferences about the softness of sweeps made

by the DANN, we compute the value of the haplotype homozygosity statistics H12 and H2/H1[37]

for the sweep candidates detected in Figure 4A. These statistics have been previously used to detect

and classify hard and soft selective sweeps, with both hard and soft sweeps showing elevated H12,

and soft sweeps exhibiting higher H2/H1 values than hard sweeps[37]. Using an approximate

Bayesian computation (ABC) approach to estimate whether each (H12, H2/H1) pair observed in

the aDNA is more likely to arise under a hard or soft sweep model (**Fig. S19**), we find that of the

23 sweep candidates with elevated H12 values in the 95th percentile of values under neutrality, 22

peaks are better supported by a hard sweep model (BF<1) with 15 showing strong support

(BF<0.5).

Finally, to assess if our DANN is able to recover known soft sweeps,we applied the DANN

to a North American population of *Drosophila melanogaster* that has three well established soft

sweeps that have been identified empirically at *Ace*[50–52], *CHkov1*[53,54] and *Cyp6g1*[55,56]. The sweeps

at *Ace* and *Cyp6g1* arose from recurrent de novo mutations while the sweep from *CHkov1* arose

from standing genetic variation. To run the scan on this data, we trained a new DANN using the

D. melanogaster data as the target domain and simulated data from a constant N_e model with

parameters relevant to this population for the source domain (Methods). Our model is able to

recover all three known positive controls and classify them as soft sweeps (**Fig. S20**). Additionally

we find that soft sweeps dominate across the autosomes of this population and that hard sweeps

are enriched on the X chromosome relative to the autosomes, consistent with our previous findings

that hemizygosity on the X results in an abundance of hard sweeps[57,58].

Selective sweeps through time

The massive admixture events in which large fractions of the European population
experienced genetic turnover may have important implications for the ability to detect selective
sweeps over time. Previous work has suggested that sweeps in ancient populations may no longer
be detectable in modern time periods due to a masking effect of admixture and drift[3,30]. Of
relevance to our dataset, 33% of the Anatolian population from which our samples were derived
was replaced by samples from the CHG population ~4.5kya, overlapping samples from the BA
and IA periods (**Fig. 1B, C**). We asked whether sweeps detected before this admixture event are
detectable subsequently, as this would imply resilience to major events and shared selective
pressures through time.

To investigate the potential impact of admixture events on sweep detection across time, we
quantified the overlap in selective sweep signals across the five time periods studied here. We
found that among the ancient time periods (N-H), 35 sweeps are detectable in only one or two time
periods, suggesting that admixture and drift may in fact have an impact on sweep detection.
However, at the same time, 14 sweeps that were identified before the admixture event in either the
N or BA time periods were also present after the admixture event in the H time period and modern
humans. This suggests that admixture events may not obscure all ancient sweeps and that some
sweeps are subject to sustained selection pressures over time (**Fig. S9**).

The genes identified in these 14 selective sweeps persisting across human epochs fall into
a few functional categories: These include neural and cognitive functions encoded by AUTS2,
ASCL1, and SEMA6A, of which AUTS2 was previously discovered to putatively be under
selection[59], neuronal signaling and calcium channels encoded by CACNB4, exocytosis encoded
by EXOC6B[60], and previously[4,38] discovered adaptations at pigmentation genes OCA2, HERC2,
and KITLG. Most of these genes are either found solo within the coordinates of their respective
selective sweeps, or with few other genes, narrowing the targets of selection. Contained in peaks
with more genes are metabolic and nutrient processing genes like PAH and SLC38A9,
reproductive and germ cell genes such as DDX4, SPAG4, and protein quality control and signaling
genes like LTN1, USP16, CCT8, and MAP3K7CL (**Table S4**). Together, the gene categories
present in the 14 sweeps persisting through history highlight functional classes, particularly
cognitive and pigmentation, that were potentially of great importance throughout the past 7000

years of history. Future work, however, is needed to fully understand the nature of positive
selection at these loci.

We next asked whether lack of overlap of sweep signals is correlated with the admixture
event 4.5kya. To do so, we measured the overlap in sweeps between pairs of ancestral time periods
(N-H) using the Jaccard similarity index (J), which measures the proportion of shared elements
between two sets relative to their union (Methods). We asked whether these observed Jaccard
values were larger or smaller than expected under a null where sweeps are randomly distributed
across time periods. We found that the farthest time periods, N and H, which have the admixture
event separating them, had significantly less sharing of sweeps than expected by chance (*J=0.17,*
p-val=0.03, permutation test, **Fig. S21,** Methods). This is consistent with some sweeps detected in
the earliest time period (N) being lost due to the impact of admixture and/or drift over long
timescales. However, the absence of sweeps in later periods may, in some cases, reflect limited
power rather than true biological loss. Additionally, we found that two sets of consecutive time
periods, (BA, IA) and (IA and H), have higher than expected sweep sharing (*J= 0.44-0.45,* p-val
<0.05, permutation test, **Fig. S21**, Methods), indicating that on shorter time scales sweeps can
persist.

Next, we asked whether sweeps that are shared across multiple time periods persist because
the same haplotype carrying the adaptive allele remained under selection, or whether the original
haplotype was replaced by a distinct haplotype, potentially introduced through admixture. To test
this, we calculated whether the most frequent haplotypes of peaks across time periods are more
similar than would be expected based on the average divergence between random pairs of
haplotypes (**Fig. S22, Fig. 5**). Out of the 14 sweeps detected on either end of the major admixture
event spanning our dataset (**Fig. 4**), 9 of these share the same top haplotype across at least 4 time
periods, including periods where our method does not detect the sweep. This implies that the
sweeping haplotype frequently persisted despite widespread admixture. In **Fig. 5A**, we highlight
6 examples of these sweeps. Among these we include a more recent sweep at the *LCT* locus where
the recent rise of the adaptive haplotype is particularly evident.

In addition to sweeps that persist across multiple time periods, we also tracked the
frequency of the top haplotype in cases where the sweep is only detected in the earliest period (**Fig.**
5B), clearly highlighting how, in some cases, a haplotype at high frequency in N is lost or masked
in subsequent periods. The temporal patterns highlighted in **Fig. 5A,B** are strikingly different from

    those in regions classified as neutral by the DANN (**Fig. 5C**), where no haplotype reaches high

476   frequency and the distances between top haplotypes fluctuate.

A   Sweep persistence.
    Distance to top haplotype in modern humans

B   Sweep loss.
    Distance to top haplotype in the Neolithic period

C   Neutral windows

Figure 5. Persistence of top haplotype across time. (A) Six examples where the most frequent

haplotype persists across multiple time periods. **(B)** Three examples of sweeps that become

masked after time period N. **(C)** Three examples of neutral windows across all time periods. In all

panels, the blue line (left y-axis) shows the frequency of the top haplotype in four ancient

populations (N–H) and in a modern population (CEU). The gray line (right y-axis) shows the

normalized Hamming distance between the top haplotype in each time period and the top

haplotype in CEU in the case of **(A)** or in period N in the case of **(B)**, **(C)**. The horizontal red

dashed line marks the 1st percentile of the distance between random haplotype pairs, with values

above this threshold indicating distinct haplotypes. We highlight with a star (*) the epochs for

which the window was classified as a sweep using the DANN.

Discussion

In this study, our goal was to characterize the targets and mode of adaptation in ancient

humans. To do this, we implemented a domain adaptive neural network that is able to detect and

classify selective sweeps in aDNA data and is robust to model misspecification. We applied our

model to empirical aDNA from 708 individuals spanning ~7000 years in the past as well as 99

modern Europeans, and identified 48 unique ancient hard selective sweeps and 28 modern hard

sweeps, recovering both previously known and novel candidates of selection. Finally, we found

that while some sweeps identified in the Neolithic have been masked in more recent time periods,

14 sweeps spanning neuronal, reproductive, pigmentation, and signalling traits, can be found in

the earliest and latest time periods despite the impacts of drift and admixture.

Past studies on humans have generally found few clear examples of hard sweeps in modern

genomes[61,62]. Souilmi et al. proposed that this paucity of classic sweeps reflects the impact of

complex population history, in particular the masking of sweep signatures by strong admixture

events. Using SweepFinder2[63], which is primarily powered to detect completed hard sweeps, they

identified 57 sweeps across ancient Eurasian human genomes, including many sweeps that are

undetectable in modern data. Our DANN recovers several sweeps that show a similar pattern: Out

of the 24 sweeps detected in the most ancient time period of our study, the Neolithic, 41% are not

detected in the following periods (**Fig. S9**, **Fig. 5B**). However, our results also reveal additional

dynamics not previously captured: the persistence of sweeps across time periods, even those most

impacted by admixture. First, we observed sweeps in which the top haplotype is shared across

multiple time periods, even when the sweep is not detected by the DANN in all time intervals.

This pattern might reflect standing genetic variation, where the haplotype has not been driven by

selection to a high enough frequency to be detected by the DANN. We also detect cases where the

same top haplotype appears in non-consecutive periods, suggesting more complex evolutionary

dynamics such as fluctuating selection or a temporary replacement of the top haplotype driven by

admixture or migration that obscure detection of the sweep in some time intervals.

The finding that hard sweeps were common in aDNA suggests that adaptation in humans

has largely been mutation limited, or that standing genetic variation available to seed adaptation

was low. Even accounting for a 16% misclassification rate of soft sweeps as hard sweeps

(**Fig. S16**), hard sweeps remain the dominant mode of selection in aDNA. The high frequency of

hard sweeps in the data is consistent with the notion that hard sweeps are expected to dominate in

populations with small population sizes, where the input of new adaptive mutations is low[7,64]. In

ancient human populations, the effective population size is estimated to be relatively small[35] (

$N_e \sim 10^4$), therefore the input of new adaptive mutations was likely moderate ($\Theta_A \sim 0.001$), making

adaptation through hard sweeps likely. Nonetheless, given the inherent challenges of

distinguishing between hard and soft sweeps, especially in regions of the parameter space where

their genomic signatures overlap, additional work will be needed to fully resolve the rapidity of

human adaptation.

Domain adaptation provides meaningful improvement on supervised machine learning

methods for analyzing genomic data. With the significant increase in available aDNA samples

over the past decade[65,66], domain adaptation may be especially valuable, as aDNA analyses may

be susceptible to false positives due to unmodeled or unknown demographic events as well as the

overall poor quality of the data. Domain adaptation was recently applied to SIA, a method that

detects selection using the ancestral recombination graph (ARG) inferred from sequence data[20,26].

Here, we bypass ARG inference, which is computationally intensive and can introduce an

additional layer of misspecification, by working directly with haplotype matrices. In other recent

work, site frequency spectra were used as inputs to the DANN, though this summary statistic

removes any linkage signal between SNPs[67]. By working with haplotypes[18], we can fully leverage

all available data without the need for additional inferences, making it more straightforward and

better suited hard vs soft sweep inference in aDNA. This framework is generalizable and in future

work could be extended to other organisms with low coverage data or where the demography is
not fully characterized.

Our findings highlight the power of deep learning for uncovering signatures of selection in
aDNA data. By applying a DANN to aDNA data, we find that hard sweeps have played an
important role in the evolutionary history of humans. Moreover, our approach opens the door to a
range of future applications of deep learning in aDNA to study adaptation, including incorporating
time as an explicit variable to examine how selection has fluctuated across historical periods or
extending our approach to detect other modes of selection. As aDNA datasets continue to grow
and deep learning methods for population genetics continue to improve, so will our ability to
disentangle the evolutionary forces that have shaped genetic diversity through human history.

Methods

Ancient DNA data

Data was downloaded from the Allen Ancient DNA Resource (AADR version 51;
https://reich.hms.harvard.edu/allen-ancient-dna-resource-aadr-downloadable-genotypes-present-
day-and-683). This includes genome-wide data from human populations from Holocene Europe
with samples dating from ~7,000 years before present (BP) to ~1,345 BP, covering the Neolithic
(N), the Bronze Age (BA), the Iron Age (IA) and the Historical periods (H) (**Fig. 1**).

We focused our analyses on the most reliable samples in our dataset. The criteria we used
to select samples are the same as in our previous work[30] and include enrichment for 1240k nuclear
targets with an in-solution hybridization capture reagent, removal of individuals with high
indication of contamination (see [30]) , and inclusion of unrelated individuals up to the third degree.
Additionally, like in our previous work we selected 177 individuals with the highest coverage
across all time periods, resulting in a total of 708 aDNA samples (Table S1). Finally, since aDNA
coverage is low and thus both alleles at heterozygous sites may not be sampled, and, since there is
ascertainment bias of alleles towards the SNPs included in the aDNA capture array[68] we pseudo-
haploidized the data by randomly selecting one of the reads that mapped to a given position and
assigned that read as the genotype of the sample at that site[30].

Simulations

We performed simulations of neutrality, hard sweeps and soft sweeps. We use two different demographic models: a constant $N_e = 10^4$ model and a human admixture demographic model that accounts for the major migratory movements contributing to the genetic diversity of contemporary Europeans[3,33–35] (**Fig. 1C**).

We simulated a total of 400,000 neutral simulations and 400,000 selective sweep simulations (200,000 hard sweeps and 200,000 soft sweeps) under each demographic model. Constant mutation rates and recombination rates were applied to each simulated genome and were drawn uniformly as follows: $\mu \sim U[1e\text{-}8, 1.5e\text{-}8]$ and $\rho \sim U[3e\text{-}9, 2e\text{-}8]$. Simulations were performed using SLiM 4.1[69,70] followed by recapitation with msprime[71].

We simulated hard sweeps by introducing a single adaptive mutation to the center of the chromosomal segment of length 450kb. We restarted the simulation and re-introduced the adaptive mutation if the mutation was lost. The simulation was allowed to proceed until the adaptive mutation reached a partial frequency (*PF*) drawn from a uniform distribution $PF \sim U[0.5, 0.95]$. In all simulations, 177 individuals were sampled and subsequently downsampled to the 150 individuals with the least amount of missing data, reflecting the same procedure applied to aDNA.

We simulated soft sweeps from recurrent *de novo* mutations by introducing adaptive mutations to the center of the chromosome at a rate determined by parameter $\Theta_A = 4N_e\mu_A$, where N_e is the effective population size and μ_A the mutation rate of the adaptive mutation. The value of Θ_A was drawn from a uniform distribution $\Theta_A \sim U[1,5]$ as soft sweeps are expected when $\Theta_A >= 1$[7,64]. Finally, the selection strength, *s,* for both hard and soft sweep simulations was drawn from a uniform distribution $s \sim U[0.005, 0.1]$.

Additionally, we simulated sweeps arising from standing genetic variation (SGV) by drawing the frequency of the adaptive mutation prior to the onset of selection from a uniform distribution $f_{init} \sim U[0.025, 0.1]$. Given the computational constraints of simulating a sweep from the SGV jointly with a complex admixture model, we only simulated SGV sweeps using the constant N_e model. Additionally, to improve computational efficiency, we used a hybrid approach where we first simulated a neutral process with msprime and selected a mutation m_i at frequency f_{init}. The resulting tree and mutation id of the variant m_i was then fed to SLiM, where m_i was assigned a selective advantage and allowed to rise in frequency, producing a sweep from SGV.

Simulations were processed to mimic the missing data rate observed in aDNA data.

Missing data was added to each site following a beta distribution with a mean of 0.43 per SNP and

a standard deviation of 0.28, mimicking the distribution of missing data observed in aDNA (**Fig.**

S2). Additionally, we pseudo-haploidized the data by randomly selecting one allele from each

sampled individual at each site[30]. Finally, since we ran our scan in 201 SNP windows in aDNA,

spanning roughly 450Kbs, we randomly selected 201 SNPs from the simulated chromosome.

DANN model architecture

The input to the DANN are raw genomic "images" or haplotype matrices (**Fig. 2B**), where

rows represent pseudo-haplotypes from each individual and columns represent the ordinal position

of each variant site in the sample. These haplotype matrices have dimensions n x L, where n=150

pseudo-haplotypes and L=201 SNPs in a given window. In these images, the color of each pixel

represents the occurrence of the major or minor allele[16,18,36]. We transformed the alleles into binary

values such that the major allele was coded as -1 and minor allele as 1. Missing data was coded as

0. Images were sorted by frequency of most to least frequent haplotype. In text S1 we test the

effectiveness of alternative sorting approaches and window sizes.

The feature extractor of the DANN consists of two convolutional layers each containing

64 filters with kernel size of 3x3 and ReLu activation (**Fig. 2A**). Each convolutional layer is

followed by 2x2 max-pooling. The last pooling layer is then flattened into a feature vector that is

shared between the two subsequent branches of the network: the classifier and the discriminator.

Each branch consists of two fully-connected dense layers of 128 neurons each. We use ReLu

activation functions and set a dropout rate of 0.5 after each dense layer. The classifier outputs a 3-

neuron softmax layer with the predicted probabilities for each of the three classes: hard sweep, soft

sweep, or neutral. The discriminator outputs a single sigmoid output layer, which predicts whether

the haplotype image comes from the source or target domain.

An important component of the DANN is a Gradient Reversal Layer (GRL) between the

feature vector and the discriminator branch. During the feed-forwards step of training, the GRL is

inactive and the data is passed along to the next layers. During backpropagation, the GRL inverts

the gradient of the loss before passing it back to the feature extraction layer[27]. This operation

penalizes features that discriminate between source and target domains, encouraging the model to

learn domain-invariant features critical for accurate classification.

Model training

We implemented the domain-adaptive neural network model described above using

TensorFlow (v2.18.0). All models were trained with the Adam optimizer and a batch size of 64.

The classifier branch utilized a categorical cross-entropy loss function, while the discriminator

branch used a binary cross-entropy loss function. We fed labeled data from simulations into the

classifier branch to compute the class prediction loss ($L_{classifier}$). Simultaneously, we fed a mix

of unlabeled data from the source domain (simulations) and target domain (aDNA data) into the

discriminator branch to compute the discriminator loss ($L_{discriminator}$). During back propagation,

the feature extractor's weights were updated based on a combination of the gradient from the

classifier loss and the reversed gradient from the discriminator loss. We use the same simulated

data for both branches, however the data is shuffled differently in each mini-batch. The real

empirical aDNA data was used on the discriminator branch only. To achieve this training

approach, we implement a custom data generator using the Sequence class

('tf.keras.utils.Sequence') that acts as a data generator interface for training Keras models.

The relative contribution of the model's branches can be adjusted via the hyperparameter

λ, such that

$$L_{total} = L_{classifier} + \lambda L_{discriminator}.$$

If λ=0 then the GRL is effectively "off" and only the classifier branch learns to classify sweeps

without attempting to unlearn domain differences. Conversely, when λ=1 the GRL is fully "on",

assigning equal importance to the tasks of classifying sweeps and unlearning domain differences

simultaneously. Following the approach proposed by Ganin & Lempitsky 2014[27], we gradually

increased λ from 0 to 1 in order to reduce potential noisy signal from the discriminator at early

stages of training. In Ganin & Lempitsky 2014 λ is defined as:

$$\lambda = \frac{2}{1 + exp(-\gamma \cdot p)} - 1,$$

Where p is the training progress changing linearly from 0 to 1 and is defined as $p = epoch_i / n_{epochs}$,

with n_{epochs} =30 total epochs and $i=1,..n_{epochs}$. In all models trained for this paper we set γ =10.

We trained the DANN for a total of 30 training epochs. Each epoch took ~282s to train on

a single A100 GPU. During training, the discriminator loss gradually increased as the model

"unlearned" the misspecification between the source and target. The loss eventually plateaued at

~0.693, consistent with the value expected when the domains become indistinguishable under

binary cross-entropy loss. Simultaneously, we observed that the classifier loss monotonically
decreased as it learned to distinguish between neutrality, hard sweeps, and soft sweeps (**Fig. S23**).

First, we trained and tested the DANN on simulated source and target domains. In this
scenario, we had labeled data from both domains, allowing us to evaluate the performance of the
DANN using a validation set from the target domain. In this setting, we selected the model weights
from the training epoch that achieved the lowest classifier validation loss when testing on the
validation dataset from the target domain.

Next, we trained and tested the DANN but this time using simulated data generated under
a human admixture model with an average of 43% missing data per site as the source domain and
aDNA data as the target domain. We included all aDNA data for training, where the data only
passed through the discriminator branch, not the classifier, since their labels are unknown. The
classifier only sees the aDNA data during inference (next section), avoiding any data leakage. In
this setting, we could not directly evaluate the performance of the model on a target validation set
due to the lack of labeled data. Instead, we assessed performance on simulated data by computing
the AUPRC for each class at every training epoch and then averaging across the three classes. We
restricted model selection to epochs beyond epoch four, when the GRL begins to influence training
($\lambda > 0.5$), and chose the epoch with the highest average AUPRC.

DANN genome-wide scan

We performed a genome-wide scan across all autosomes and all four time periods of aDNA
data from this study. We also include a scan on 99 samples of modern humans from the CEU
population from the 1000 Genomes Project[32]. This modern data scan was generated using a
different DANN than the one used on ancient samples, trained on CEU data as the target domain.

To apply the model to all autosomes, we use a sliding window of 201 SNPs, advancing
each window by 10 SNPs. To refine the predictions and reduce noise, we then averaged the
predicted probabilities every five consecutive, overlapping windows, generating the final
predictions used for the scan. The DANN outputs a probability for each of the three classes
(neutral, hard sweep or soft sweep). Each window was assigned to the class with the highest
probability. To make sure we are identifying distinct selective events, we grouped consecutive
non-neutral windows into a single peak and required peaks to be at least 1.5 Mb apart. Each peak
was represented by the window with lowest probability of neutrality, in other words, the strongest

signal within the peak. The classification of this representative window (hard or soft sweep) was

used to classify the whole peak.

ABC for hard/soft sweep classification with H12 and H2/H1 statistics

We assessed whether the predictions for hard vs soft sweeps in the data made by the DANN

are consistent with predictions made with the haplotype homozygosity statistics, H12 and H2/H1,

that can jointly discriminate between hard and soft sweeps[37]. H2/H1 is expected to be small for

hard sweeps and large for soft sweeps, conditional on H12 being larger than expected under

neutrality. As such, we only analyzed 23 peaks in total that had an H12 value greater than the 95th

percentile of H12 values from 400,000 neutral simulations under the human admixture model as

these were least likely to be neutral.

We used an approximate Bayesian computation approach to evaluate if a pair of (H12,

H2/H1) values in the data are more likely under a hard vs soft sweep model. To do so, we compare

observed values in the data to values measured from simulations of hard sweeps and soft sweeps

under the human admixture model. We calculated Bayes factors (BFs) for the observed data by

taking the ratio of the number of soft sweep and hard sweep simulations with a Euclidean distance

<0.1 from each (H12, H2/H1) data point[37].

Jaccard index and permutation test

To quantify the overlap of peaks across different time periods, we calculated a Jaccard

similarity index (*J*) quantifying peak overlap between pairs of time periods. *J* measures the

proportion of shared elements between two sets relative to their total combined elements and its

defined as

$$J(A,B) = \frac{|A \cap B|}{|A \cup B|},$$

or in other words, the number of shared elements in sets A and B divided by the total number of

elements in A and B. In this scenario A and B represent the peaks identified in two distinct time

periods, such as IA and H. *J(IA,H)* is obtained by dividing the number of peaks that are shared

between IA and H by the total number of peaks found across both periods.

Next, to identify whether the value of J was statistically significant, we performed a permutation test where we randomly shuffled the peaks and time periods, such that peaks were randomly distributed across time. We did this 5,000 times generating a null distribution of expected values of J. The p-value of the observed J value is given by the proportion of test statistics from the null distribution that are as extreme or more extreme than the observed value for a pair of time periods.

Code availability

All code developed and used in this study will be made publicly available via a GitHub repository upon acceptance of the manuscript.

Acknowledgements

The authors thank Vagheesh Narasimhan and Devansh Pandey for providing processed aDNA data and for helpful conversations. The authors also thank members of the Garud Lab, particularly Peter Laurin, for helpful conversations and feedback on the paper. This work was funded by an NIGMS NIH award (R35GM151023) to NRG, an NSF CAREER award (no. 2240098) to NRG, NIGMS NIH award (R35GM127070) to AS, a UCLA Dissertation Year Award to MH, and the CSHL School of Biological Sciences Gladys & Roland Harriman Fellowship ZM.

References

1.   Page, A. E. *et al.* Reproductive trade-offs in extant hunter-gatherers suggest adaptive mechanism for the Neolithic expansion. *Proc. Natl. Acad. Sci.* **113**, 4694–4699 (2016).

2.   Marciniak, S. *et al.* An integrative skeletal and paleogenomic analysis of stature variation suggests relatively reduced health for early European farmers. *Proc. Natl. Acad. Sci.* **119**, e2106743119 (2022).

3.   Souilmi, Y. *et al.* Admixture has obscured signals of historical hard sweeps in humans. *Nat. Ecol. Evol.* **6**, 2003–2015 (2022).

4.   Akbari, A. *et al.* Pervasive findings of directional selection realize the promise of ancient DNA to elucidate human adaptation. Preprint at https://doi.org/10.1101/2024.09.14.613021 (2024).

5.   Kerner, G. *et al.* Genetic adaptation to pathogens and increased risk of
inflammatory disorders in post-Neolithic Europe. *Cell Genomics* **3**, 100248 (2023).

6.   Hermisson, J. & Pennings, P. S. Soft Sweeps: molecular population genetics of
adaptation from standing genetic variation. *Genetics* **169**, 2335–2352 (2005).

7.   Pennings, P. S. & Hermisson, J. Soft Sweeps II—Molecular Population Genetics
of Adaptation from Recurrent Mutation or Migration. *Mol. Biol. Evol.* **23**, 1076–1084 (2006).

8.   Messer, P. W. & Petrov, D. A. Population genomics of rapid adaptation by soft
selective sweeps. *Trends Ecol. Evol.* **28**, 659–669 (2013).

9.   Hermisson, J. & Pennings, P. S. Soft sweeps and beyond: understanding the
patterns and probabilities of selection footprints under rapid adaptation. *Methods Ecol. Evol.* **8**,
700–716 (2017).

10.   Zheng, Y. & Wiehe, T. Adaptation in structured populations and fuzzy boundaries
between hard and soft sweeps. *PLOS Comput. Biol.* **15**, e1007426 (2019).

11.   Harris, R. B., Sackman, A. & Jensen, J. D. On the unfounded enthusiasm for soft
selective sweeps II: Examining recent evidence from humans, flies, and viruses. *PLOS Genet.*
14, e1007859 (2018).

12.   Garud, N. R., Messer, P. W. & Petrov, D. A. Detection of hard and soft selective
sweeps from Drosophila melanogaster population genomic data. *PLOS Genet.* **17**, e1009373
(2021).

13.   Kelley, J. L., Madeoy, J., Calhoun, J. C., Swanson, W. & Akey, J. M. Genomic
signatures of positive selection in humans and the limits of outlier approaches. *Genome Res.* **16**,
980–989 (2006).

14.   Sheehan, S. & Song, Y. S. Deep Learning for Population Genetic Inference. *PLOS*
Comput. Biol. **12**, e1004845 (2016).

15.   Wang, Z. *et al.* Automatic inference of demographic parameters using generative
adversarial networks. *Mol. Ecol. Resour.* **21**, 2689–2705 (2021).

16.   Flagel, L., Brandvain, Y. & Schrider, D. R. The Unreasonable Effectiveness of
Convolutional Neural Networks in Population Genetic Inference. *Mol. Biol. Evol.* **36**, 220–238
(2019).

17.   Adrion, J. R., Galloway, J. G. & Kern, A. D. Predicting the Landscape of
Recombination Using Deep Learning. *Mol. Biol. Evol.* **37**, 1790–1808 (2020).

18.	Torada, L. *et al.* ImaGene: a convolutional neural network to quantify natural selection from genomic data. *BMC Bioinformatics* **20**, 337 (2019).

19.	Xue, A. T. *et al.* Discovery of Ongoing Selective Sweeps within *Anopheles* Mosquito Populations Using Deep Learning. *Mol. Biol. Evol.* **38**, 1168–1183 (2021).

20.	Hejase, H. A., Mo, Z., Campagna, L. & Siepel, A. A Deep-Learning Approach for Inference of Selective Sweeps from the Ancestral Recombination Graph. *Mol. Biol. Evol.* **39**, msab332 (2022).

21.	Amin, M. R., Hasan, M. & DeGiorgio, M. Digital Image Processing to Detect Adaptive Evolution. *Mol. Biol. Evol.* **41**, msae242 (2024).

22.	Dabi, A. & Schrider, D. R. Population size rescaling significantly biases outcomes of forward-in-time population genetic simulations. *Genetics* **229**, iyae180 (2025).

23.	Shimodaira, H. Improving predictive inference under covariate shift by weighting the log-likelihood function. *J. Stat. Plan. Inference* **90**, 227–244 (2000).

24.	Burger, K. E., Pfaffelhuber, P. & Baumdicker, F. Neural networks for self-adjusting mutation rate estimation when the recombination rate is unknown. *PLOS Comput. Biol.* **18**, e1010407 (2022).

25.	Riley, R., Mathieson, I. & Mathieson, S. Interpreting generative adversarial networks to infer natural selection from genetic data. *Genetics* **226**, iyae024 (2024).

26.	Mo, Z. & Siepel, A. Domain-adaptive neural networks improve supervised machine learning based on simulated population genetic data. *PLOS Genet.* **19**, e1011032 (2023).

27.	Ganin, Y. & Lempitsky, V. Unsupervised Domain Adaptation by Backpropagation. Preprint at https://doi.org/10.48550/arXiv.1409.7495 (2014).

28.	Csurka, G. A Comprehensive Survey on Domain Adaptation for Visual Applications. in *Domain Adaptation in Computer Vision Applications* (ed. Csurka, G.) 1–35 (Springer International Publishing, Cham, 2017). doi:10.1007/978-3-319-58347-1_1.

29.	Cochran, K. *et al.* Domain-adaptive neural networks improve cross-species prediction of transcription factor binding. *Genome Res.* **32**, 512–523 (2022).

30.	Pandey, D., Harris, M., Garud, N. R. & Narasimhan, V. M. Leveraging ancient DNA to uncover signals of natural selection in Europe lost due to admixture or drift. *Nat. Commun.* **15**, 9772 (2024).

31.   Skoglund, P. & Mathieson, I. Ancient Genomics of Modern Humans: The First Decade. *Annu. Rev. Genomics Hum. Genet.* **19**, 381–404 (2018).

32.   The 1000 Genomes Project Consortium *et al.* A global reference for human genetic variation. *Nature* **526**, 68–74 (2015).

33.   Damgaard, P. D. B. *et al.* 137 ancient human genomes from across the Eurasian steppes. *Nature* **557**, 369–374 (2018).

34.   Jones, E. R. *et al.* Upper Palaeolithic genomes reveal deep roots of modern Eurasians. *Nat. Commun.* **6**, 8912 (2015).

35.   Kamm, J., Terhorst, J., Durbin, R. & Song, Y. S. Efficiently inferring the demographic history of many populations with allele count data. *J. Am. Stat. Assoc.* **115**, (2019).

36.   Zhao, H. & Alachiotis, N. Data preprocessing methods for selective sweep detection using convolutional neural networks. *Methods* **233**, 19–29 (2025).

37.   Garud, N. R., Messer, P. W., Buzbas, E. O. & Petrov, D. A. Recent Selective Sweeps in North American Drosophila melanogaster Show Signatures of Soft Sweeps. *PLOS Genet.* **11**, e1005004 (2015).

38.   Mathieson, I. *et al.* Genome-wide patterns of selection in 230 ancient Eurasians. *Nature* **528**, 499–503 (2015).

39.   Irving-Pease, E. K. *et al.* The selection landscape and genetic legacy of ancient Eurasians. *Nature* **625**, 312–320 (2024).

40.   Le, M. K. *et al.* 1,000 ancient genomes uncover 10,000 years of natural selection in Europe. *BioRxiv* (2022) doi:10.1101/2022.08.24.505188.

41.   de Bakker, P. I. W. & Raychaudhuri, S. Interrogating the major histocompatibility complex with high-throughput genomics. *Hum. Mol. Genet.* **21**, R29–R36 (2012).

42.   Leffler, E. M. *et al.* Multiple Instances of Ancient Balancing Selection Shared Between Humans and Chimpanzees. *Science* **339**, 1578–1582 (2013).

43.   Bersaglieri, T. *et al.* Genetic Signatures of Strong Recent Positive Selection at the Lactase Gene. *Am. J. Hum. Genet.* **74**, 1111–1120 (2004).

44.   Enattah, N. S. *et al.* Identification of a variant associated with adult-type hypolactasia. *Nat. Genet.* **30**, 233–237 (2002).

45.   Mathieson, I. & Terhorst, J. Direct detection of natural selection in Bronze Age Britain. *Genome Res.* **32**, 2057–2067 (2022).

46.   Segurel, L. *et al.* Why and when was lactase persistence selected for? Insights from
Central Asian herders and ancient DNA. *PLOS Biol.* **18**, e3000742 (2020).

47.   Evershed, R. P. *et al.* Dairying, diseases and the evolution of lactase persistence in
Europe. *Nature* **608**, 336–345 (2022).

48.   Watanabe, K., Taskesen, E., van Bochoven, A. & Posthuma, D. Functional
mapping and annotation of genetic associations with FUMA. *Nat. Commun.* **8**, 1826 (2017).

49.   Schrider, D. R., Mendes, F. K., Hahn, M. W. & Kern, A. D. Soft Shoulders Ahead:
Spurious Signatures of Soft and Partial Selective Sweeps Result from Linked Hard Sweeps.
Genetics **200**, 267–284 (2015).

50.   Mutero, A., Pralavorio, M., Bride, J. M. & Fournier, D. Resistance-associated point
mutations in insecticide-insensitive acetylcholinesterase. *Proc. Natl. Acad. Sci.* **91**, 5922–5926
(1994).

51.   Menozzi, P., Shi, M. A., Lougarre, A., Tang, Z. H. & Fournier, D. Mutations of
acetylcholinesterase which confer insecticide resistance in Drosophila melanogaster
populations. *BMC Evol. Biol.* **4**, 4 (2004).

52.   Karasov, T., Messer, P. W. & Petrov, D. A. Evidence that Adaptation in Drosophila
Is Not Limited by Mutation at Single Sites. *PLOS Genet.* **6**, e1000924 (2010).

53.   Aminetzach, Y. T., Macpherson, J. M. & Petrov, D. A. Pesticide Resistance via
Transposition-Mediated Adaptive Gene Truncation in Drosophila. *Science* **309**, 764–767
(2005).

54.   Magwire, M. M., Bayer, F., Webster, C. L., Cao, C. & Jiggins, F. M. Successive
Increases in the Resistance of Drosophila to Viral Infection through a Transposon Insertion
Followed by a Duplication. *PLOS Genet.* **7**, e1002337 (2011).

55.   Daborn, P., Boundy, S., Yen, J., Pittendrigh, B. & ffrench-Constant, R. DDT
resistance in Drosophila correlates with Cyp6g1 over-expression and confers cross-resistance
to the neonicotinoid imidacloprid. *Mol. Genet. Genomics* **266**, 556–563 (2001).

56.   Schmidt, J. M. *et al.* Copy Number Variation and Transposable Elements Feature
in Recent, Ongoing Adaptation at the Cyp6g1 Locus. *PLOS Genet.* **6**, e1000998 (2010).

57.   Harris, M. & Garud, N. R. Enrichment of Hard Sweeps on the X Chromosome in
Drosophila melanogaster. *Mol. Biol. Evol.* **40**, msac268 (2023).

58. Harris, M., Kim, B. Y. & Garud, N. Enrichment of hard sweeps on the X chromosome compared to autosomes in six *Drosophila* species. *GENETICS* **226**, iyae019 (2024).

59. Green, R. E. *et al.* A Draft Sequence of the Neandertal Genome. *Science* **328**, 710–722 (2010).

60. Evers, C. *et al.* Mosaic deletion of EXOC6B: further evidence for an important role of the exocyst complex in the pathogenesis of intellectual disability. *Am. J. Med. Genet.* **164A**, 3088–94 (2014).

61. Hernandez, R. D. *et al.* Classic Selective Sweeps Were Rare in Recent Human Evolution. *Science* **331**, 920–924 (2011).

62. Schrider, D. R. & Kern, A. D. Soft Sweeps Are the Dominant Mode of Adaptation in the Human Genome. *Mol. Biol. Evol.* **34**, 1863–1877 (2017).

63. DeGiorgio, M., Huber, C. D., Hubisz, M. J., Hellmann, I. & Nielsen, R. SweepFinder2: increased sensitivity, robustness and flexibility. *Bioinformatics* **32**, 1895–1897 (2016).

64. Pennings, P. S. & Hermisson, J. Soft Sweeps III: The Signature of Positive Selection from Recurrent Mutation. *PLOS Genet.* **2**, e186 (2006).

65. Mallick, S. & Reich, D. The Allen Ancient DNA Resource (AADR): A curated compendium of ancient human genomes. Harvard Dataverse https://doi.org/10.7910/DVN/FFIDCW (2023).

66. Mallick, S. *et al.* The Allen Ancient DNA Resource (AADR) a curated compendium of ancient human genomes. *Sci. Data* **11**, 182 (2024).

67. Cobb, K. A. & Smith, M. L. The reasonable effectiveness of domain adaptation for inference of introgression. Preprint at https://doi.org/10.1101/2025.01.17.633659 (2025).

68. Günther, T. & Nettelblad, C. The presence and impact of reference bias on population genomic studies of prehistoric human populations. *PLOS Genet.* **15**, e1008302 (2019).

69. Haller, B. C., Galloway, J., Kelleher, J., Messer, P. W. & Ralph, P. L. Tree-sequence recording in SLiM opens new horizons for forward-time simulation of whole genomes. *Mol. Ecol. Resour.* **19**, 552–566 (2019).

906   70.   Haller, B. C. & Messer, P. W. SLiM 4: Multispecies Eco-Evolutionary Modeling.

907   *Am. Nat.* **201**, E127–E139 (2023).

908   71.   Baumdicker, F. *et al.* Efficient ancestry and mutation simulation with msprime 1.0.

909   *Genetics* **220**, iyab229 (2022).