Sustained alpha oscillations serve attentional prioritization in working memory, not maintenance

Yuanyuan Weng[1], Jelmer P. Borst[2], & Elkan G. Akyürek[1]

[1] Department of Experimental Psychology, University of Groningen

[2] Bernoulli Institute for Mathematics, Computer Science and Artificial Intelligence, University of Groningen

Address correspondence to:

Yuanyuan Weng, Department of Experimental Psychology, University of Groningen

Grote Kruisstraat 2/1, 9712 TS Groningen, The Netherlands, y.weng@rug.nl, +31 (0)50 3637530

Abstract

Recent theory on the neural basis of working memory (WM) has attributed an important role to "activity-silent" mechanisms, suggesting that sustained neural activity might not be essential in the retention of information. This idea has been challenged by reports of ongoing neural activity in the alpha band during WM maintenance, however. The precise role of these alpha oscillations is unclear: Do they reflect attentional prioritization of stored information, or do they serve as a general maintenance mechanism, for instance to periodically refresh synaptic traces? To address this, we designed a visual WM task involving two memory items, one of which was prioritized for recall. The task included both a short (1 s) and a long (3 s) delay intervals between encoding and retrieval. The long delay was implemented to provide a more decisive test of WM maintenance, providing a point in time when any initially silent synaptic traces would likely need to be refreshed as well. Time-resolved decoding analyses revealed that both prioritized and deprioritized items were initially decodable following stimulus presentation. However, only the prioritized item exhibited sustained decodability throughout the delay, particularly in the long delay condition, where it transitioned into a stable coding scheme. This prolonged representation was selectively supported by induced alpha power, which reliably tracked the prioritized item, but not the deprioritized one. Impulse-based decoding further confirmed this asymmetry, highlighting a selective reactivation of the deprioritized item only upon contextual relevance. Together, these findings suggest that sustained alpha-band activity reflects attentional prioritization, rather than general memory maintenance. Unattended, non-prioritized items appear to transition into an activity-silent state, consistent with models of synaptic storage in WM.

Keywords: working memory; activity-silent maintenance; EEG; alpha oscillations

1. Introduction

Working memory (WM) is a crucial cognitive system that maintains and stores information, guiding thought and behavior in the absence of direct sensory input (Baddeley, 2003). Recently, interest has grown in understanding its underlying neural mechanisms, particularly regarding how neural activity sustains information during the retention periods. One traditional view is that WM retention depends on persistent activity, wherein sustained neural firing preserves representations of memory items across the delay periods (Constantinidis et al., 2018; Goldman-Rakic, 1995; Kojima & Goldman-Rakic, 1982), ensuring continuous availability of stored information. However, persistent activity has not consistently been observed during WM tasks. An alternative account is based on "activity-silent" [1] or - quiescent neural mechanisms (Stokes, 2015; Wolff et al., 2017), which proposes that information can (also) be maintained through short-term synaptic changes (Barak & Tsodyks, 2014; Buonomano & Maass, 2009; Choudhary et al., 2024; Kozachkov et al., 2022; Lundqvist et al., 2018; Miller et al., 2018; Mongillo et al., 2008; Pals et al., 2020; Panichello et al., 2024; Sprague et al., 2016). In this view, synaptic changes serve as a latent memory trace that can be rapidly reactivated when the stored information becomes relevant. Recent computational evidence supports the idea of activity-silent WM, demonstrating that short-term synaptic plasticity (STSP), modelled by calcium-dependent synaptic facilitation, effectively maintains memory representations without sustained neural firing (Pals et al., 2020).

Empirical research also seemed to provide evidence for the activity-silent framework, at least initially. For example, Wolff et al. (2017) presented two memory items, instructing participants to prioritize only one of them for the upcoming test, thereby deprioritizing the unattended item. Using a functional perturbation approach involving a high-contrast, task-irrelevant visual impulse during the maintenance period, they found that WM contents remained decodable from the neural impulse response, even in the absence of sustained delay-period activity (see also Rose et al., 2016). A key finding of this study was that unattended memory items that were deprioritized after a retrospective cue exhibited little to no sustained neural activity, suggesting they might be stored in an activity-silent state rather than through continuous neural firing. However, a later re-analysis, in which the same EEG data were examined using alpha-band (8-12 Hz) power rather than raw EEG voltage, challenged this

---

[1] The term "activity-silent" state refers to memory retention primarily through short-term synaptic changes rather than sustained neural firing. However, this does not imply a complete absence of neural activity, such as more subtle, intermittent neural firing that would by and of itself be insufficient to maintain memoranda in WM.

interpretation (Barbosa et al., 2021). In contrast to previous reports (LaRocque et al., 2013; Rose et al., 2016), Barbosa and colleagues (2021) showed that unattended items were decodable from alpha power during the delay period, although not consistently so throughout the entire delay interval. These outcomes suggest that maintenance in WM might be supported by oscillatory activity, which has been proposed by several authors (F.-W. Chen et al., 2023; Foster et al., 2017; Fulvio et al., 2024; Sutterer et al., 2019; ten Oever et al., 2020).

Alpha-band oscillations in particular may be crucial in WM, as they have been implicated in regulating attentional processes, inhibiting irrelevant information, and potentially influencing memory retention (Bonnefond & Jensen, 2012; X. Chen et al., 2023; Klimesch, 2012; Vries et al., 2020). Research also indicates that alpha power increases during WM retention, particularly in parietal and occipital regions, which may reflect active involvement in WM storage (Jensen et al., 2002). However, the exact function of alpha oscillations in WM maintenance remains unclear. Do alpha-band oscillations reflect attentional mechanisms actively prioritizing the maintained items (Bae & Luck, 2018), or could it represent a more general maintenance mechanism, constituting a persistent activity trace, or a means to periodically refresh synaptic connections, independent of attentional prioritization (cf. Fiebig & Lansner, 2017)?

The aim of the present study was to clarify the exact contribution of alpha oscillations to WM. In particular, we wanted to determine whether alpha band activity during WM maintenance primarily reflects attentional prioritization, or a more general maintenance mechanism. To address this question, we designed a visual WM experiment with functional perturbation, in which we compared the maintenance of prioritized and deprioritized items. Decoding of items in WM from neural activity in the alpha band should be similar for both items if it reflects generic maintenance. Conversely, if it reflects attentional mechanisms, then we might expect successful decoding of prioritized items, but not of deprioritized ones.

Our experiment featured two different retention intervals between the presentation of memory items and the subsequent memory probe: A short (1-second) and a long (3-second) interval. The rationale for incorporating an extended retention interval of up to 3 seconds was based on the idea of STSP as a maintenance mechanism in particular, as it predicts that residual calcium levels would progressively decline across an interval of up to one or two seconds (Mongillo et al., 2008; Zucker & Regehr, 2002), making longer intervals an ideal testcase for investigating potential neural reactivation mechanisms, which might be expressed in the alpha band specifically (Barbosa et al., 2021).

We were furthermore interested in the temporal dynamics of alpha oscillations during WM maintenance, as these might help to elucidate their functional role. Voltage-based decoding has previously shown that WM may maintain information through a stable coding scheme, while simultaneously exhibiting low-dimensional dynamic changes that reflect temporal progression or representational drift (Wolff, Jochim, et al., 2020). Assessing the temporal dynamics of alpha oscillations across both short and long delay intervals should provide information as to the nature and consistency of alpha oscillations during WM maintenance.

2. Materials and methods

2.1 Participants

Thirty healthy adults were initially recruited for the electroencephalography (EEG) experiment. Two participants were excluded due to excessive noise in their EEG data (more than 30% of trials contaminated), leaving 28 participants (21 females, mean age 24 years, range 18-36 years). The study received ethical approval from the Ethical Committee of the Faculty of Behavioral and Social Sciences at the University of Groningen (Study ID = PSY-2122-S-0255). All participants gave written informed consent before participation and were compensated at a rate of €10 per hour.

2.2 Stimuli and apparatus

The experiment was conducted in a well-lit room, with the lighting set to a level of approximately 100 lux. The task was generated and presented using OpenSesame 3.3.14 (Mathôt et al., 2012), running on a standard Windows 10 desktop computer. Participants were seated about 60 cm away from a 27-inch ASUS VG279Q monitor, which had a refresh rate of 100 Hz and a resolution of 1920 by 1080 pixels. A USB keyboard was provided for the participants to enter their responses.

All stimuli were shown in the center of the screen, against a gray background (RGB = 128, 128,128). Among these was a black fixation dot, which spanned 0.25° of visual angle. Memory items and probes were sine-wave gratings presented at 20% contrast, with a diameter of 6.5° and a spatial frequency of 1 cycle per degree. Their phase was randomized within and across trials. The memory items had orientations of 0.5° to 178.0° in steps of 2.5°. The angle differences between memory items and the corresponding memory probes were uniformly

distributed across 7 angle differences (±5°, ±10°, ±16°, ±24°, ±26°, ±32°, ±40°). The impulse stimuli consisted of white disks, with a diameter of 9.7°.

2.3 Experimental design and procedure

There were two blocked conditions in the experiment: The short maintenance delay condition (1 sec), and the long delay condition (3 sec). At the beginning of each block, a text ('short' or 'long') indicated the type of block to the participants. The trial procedure is shown in Figure 1. Participants were instructed to maintain central fixation throughout the trials: each trial started with the presentation of the fixation dot, which remained on the screen for the entirety of the trial. After a 300-500 ms delay, two memory items were sequentially presented, each for 200 ms and separated by a 900 ms inter-stimulus interval. The maintenance delay followed (1 or 3 sec), after which the first impulse was presented for 100 ms. As in previous functional perturbation studies, the impulse serves to 're-illuminate' WM representations during maintenance, even those that have become activity-silent state during the preceding delay, thereby allowing us to decode their representations. Following another 500 ms delay, participants were probed on the "prioritized" memory item, with the probe being shown for 200 ms. The testing order of the memory items was fixed within the first two sessions and the last two sessions, but switched between these two sets of sessions (i.e., the memory item that was presented first was tested first (prioritized) in one set of sessions and the memory item that was presented second was tested first in the other set of sessions). This testing order was counterbalanced across participants. Participants indicated whether the orientation of probe relative to the memory item was rotated clockwise or counterclockwise by pressing the 'm' key, or the 'c' key, respectively. During the response period, participants were allotted a maximum of 1500 ms to respond. After a delay of 900 ms, the second impulse was presented for 100 ms. Finally, after another 500 ms delay, the second memory probe was presented for 200 ms for the "deprioritized" item. The next trial then followed automatically after the response.

In the EEG experiment, participants completed a total of 1728 trials, which were divided into 72 blocks and distributed across four consecutive sessions, all conducted within a single day. When participants completed a block of 24 trials, they were presented with feedback depicting their average accuracy for that block. Participants could take breaks between the blocks. The experiment had a total duration of approximately 6 hours, which included EEG cap preparation and participant-paced breaks.

Fig 1. Trial schematic. Two randomly selected orientations were serially presented. Then two experimental conditions were implemented with either a short delay (1 s) or a long delay (3 s). After the delay, the first task-irrelevant impulse was presented, followed by a probe for the first (tested early) item. After an additional delay, the second task-irrelevant impulse was presented, followed by probing of the second (tested late) item.

2.4 EEG acquisition and preprocessing

The EEG data were acquired using 64 Ag/AgCl sintered electrodes, which were laid out according to the extended international 10-20 system. A TMSI Refa 8-64 amplifier was used to record EEG data at 1000 Hz, and CPz was used as online reference. Two additional electrodes were placed on the left and right mastoids, and the anterior midline frontal electrode (AFz) served as the ground. To record eye movements and blinks, the vertical electrooculogram (EOG) was derived from the voltage difference between an external electrode placed 2 cm below the left eye and the Fp1 electrode, while horizontal EOG was similarly obtained from the F9 and F10 electrodes. All electrode impedances were kept below 10 kΩ throughout the experiment.

The EEG data were pre-processed with EEGLAB v14.11 (Delorme & Makeig, 2004) and the FieldTrip toolbox (Oostenveld et al., 2011) in MATLAB. We first re-referenced the data to the average of right and left mastoids, downsampled to 500 Hz, and applied bandpass filtering (0.1-40 Hz). Then, the data were epoched relative to the onset of the first memory item (-200 ms to 900 ms), to the onset of the second memory item (short delay: -200 ms to 1200 ms, long delay: -200 ms to 3200 ms), and the onsets of the impulse stimuli (-200 ms to 600 ms). Each trial of each epoch was visually inspected for blinks, eye movements, and non-stereotypical artifacts, and epochs containing such artifacts were excluded from further analyses. Noisy channels were replaced through spherical spline interpolation. The average percentage of trials removed for each epoch were as follows: 10.77% in the item 1 epoch (short and long delay conditions together), 9.56% in the item 2 epoch (short and long delay conditions together), 9.88% in the short delay epoch, 12.91% in the long delay epoch, 7.54% in the

impulse 1 epoch (short and long conditions together), and 7.65% in the impulse 2 epoch (short and long conditions together).

To extract alpha power amplitude, the EEG voltage data were first bandpass filtered between 8 to 12 Hz, followed by a Hilbert transform. The magnitude of the analytic signal was then extracted to obtain the amplitude envelope, constituting time-resolved alpha power. This was done separately for both induced and evoked alpha power. We focused primarily on induced alpha power because our hypotheses concern the oscillatory mechanism that sustain and prioritize items during the delay, rather than the stimulus-locked sensory response. We computed induced alpha power by computing the alpha power of each trial's voltage trace. Evoked alpha power reflects phase-locked neural responses, and was obtained by first averaging voltage traces across a subset of trials within each orientation bin (see decoding analyses below), followed by computing the alpha power on these averaged traces.

2.5 Multivariate pattern analyses

We conducted several different multivariate pattern analyses (MVPA) on the raw voltage and alpha power signals to investigate the temporal dynamics of WM representations. Based on previous studies from our group, we selected 17 posterior channels (P7, P3, Pz, P4, P8, POz, O1, O2, P5, P1, P2, P6, PO3, PO4, PO7, PO8, Oz) for all decoding analyses (Kandemir, Wilhelm, et al., 2024; Kandemir & Akyürek, 2023; Wolff et al., 2017). These channels were chosen due to their relevance in capturing neural activity related to orientation processing in visual WM tasks.

The decoding analyses were performed to assess the neural representation of orientation information using different neural signals (time window of interest, raw voltage, and alpha power). Here, we present a concise summary of the shared methodological framework, followed by the specific differences characterizing each decoding analysis. The general decoding procedure involved baseline correction, down-sampling, orientation binning, cross-validated classification, and decoding accuracy computation. Firstly, baseline correction was performed by subtracting the mean signal computed within a pre-stimulus interval (-200 ms to 0 ms) from the entire time series for each trial and channel. To optimize computational efficiency, we then further downsampled the data to 100 Hz. For orientation decoding, trials were assigned to the closest one of 16 equal orientation angle bins by computing the minimal absolute distance between the stimulus orientation and the center values of the orientation bins. Trials were re-labeled with the center value of that bin. This binning process was repeated three times to cover the pre-determined orientation space (from 0° to 157.5°, 7.5° to 165°, and 15°

to 172.5°, each in steps of 22.5°). This approach resulted in three runs, each with 16 different orientation conditions, allowing for a comprehensive assessment of orientation decoding across different bin alignments. These three runs were averaged to generate a final decoding result for each condition.

To decode the neural representation of orientation, we employed a cross-validated classification approach using Mahalanobis distance (De Maesschalck et al., 2000) as the metric. The trials were portioned into 8 folds using stratified K-fold cross-validation. In each iteration, seven folds served as the training set, and the remaining fold served as the test set. Within each training set, random subsampling was performed to equalize the number of trials across orientation conditions, and the data within each orientation condition were then averaged to create 16 condition-specific spatiotemporal patterns. To reduce noise and pool information across similar orientations, we convolved the spatiotemporal neural patterns associated with each orientation condition with a half-cosine basis set raised to the 15th power (Kandemir, Wilhelm, et al., 2024; Kandemir, Wolff, et al., 2024; Wolff, Kandemir, et al., 2020). For each time point, pairwise Mahalanobis distances between the test trials and the averaged training patterns were computed. The covariance matrix estimated from the training data was computed by means of a shrinkage estimator (Ledoit & Wolf, 2003) to account for the variance structure of the data. Distances were mean-centered by subtracting the mean distance across all conditions, and sign-reversed, ensuring that positive values indicated higher similarity. For visualization, to summarize decoding accuracy, the Mahalanobis distances were sign-reversed and then averaged with weights based on the cosine of the orientation differences between orientations, spanning the full orientation space. The entire procedure was repeated 100 times with different random folds and subsampling to avoid sampling biases.

2.5.1 Raw voltage time-course decoding

The raw voltages time-course decoding analysis aimed to capture the temporal dynamics of neural representations by decoding raw voltage data at each time point within the epoch. The specific decoding procedure was performed as described in section 2.5. The final decoding output was averaged across orientation spaces, repetitions and trials for each participant.

2.5.2 Time window of interest decoding

To assess the overall decodability within specific epochs, the decoding values were averaged over channels and time. Specifically, we selected a time window of interest from 100 ms to 400 ms relative to the presentation of the relevant stimulus (i.e., memory item, or impulse). This time window was selected based on prior research indicating that the dynamic WM-dependent neural responses to visual stimuli occur mainly within this period (Wolff et al., 2017). Since we also aimed to assess WM maintenance, and to capture potential differences in sustained neural activity, we selected two further time-windows, corresponding to the end of the delay phase in each condition: 400-1000 ms for the short delay condition, and 2400-3000 ms for the long delay condition.

After adjusting the data as described in Section 2.5, we reshaped it for the time window of interest analyses by concatenating the channel and time dimensions into one feature dimension. This enabled decoding of the interested time window as a unified pattern, rather than analyzing time point by time point. The reported decoding accuracy for each participant was calculated by averaging the weighted, mean-centered distances across all repetitions, trials and orientation spaces. This averaging yielded a single value per participant, representing the overall ability to decode orientation information from the neural data.

2.5.3 Alpha power time-course decoding

The alpha power time-course decoding was highly similar to the decoding procedure of the raw voltage time-course decoding. For the alpha power time-course decoding, the analysis was conducted on alpha-band signals, separated into evoked and induced alpha power, following the same orientation binning procedure used in the preceding analyses. Then the data was divided into three folds using random stratified sampling, ensuring a balanced distribution of orientation bins across folds. To reduce trial-to-trial variability and enhance the reliability of decoding, pseudo-trials trials were generated by averaging trials within the same orientation bin for each fold. For induced alpha power decoding, trial-wise alpha power was computed before averaging, while for evoked alpha power decoding, voltage traces were averaged prior to filtering in the alpha frequency band.

For each time point, the classifier was trained on two folds (the training folds) and tested on the remaining fold (the test fold) using cross-validation. The covariance was computed from the training folds using a shrinkage estimator for stability. In the training folds, averaged pseudo-trials for each orientation bin were smoothed using a half-cosine basis function to pool neighboring orientations, raising it to the 7^{th} power to enhance selectivity. The Mahalanobis distances were computed between each test pseudo-trial and the averaged training pseudo-trials

across orientation bins. These distances were cosine-weighted, sign-reversed, and mean-centered to generate a similarity profile. A cosine vector mean was computed to summarize the similarity, where higher values indicated greater similarity between the neural representations of the tested and trained orientations, reflecting successful decoding of the orientation information from the alpha power signal. The entire decoding process was repeated 100 times with randomized fold assignments to ensure robustness. Decoding accuracy was also averaged over iterations, orientation spaces, and time points for each participant. The final decoding accuracy values for evoked and induced alpha power were averaged across all iterations, providing a stable estimate of the temporal dynamics of the alpha power representation for each participant.

2.5.4 Cross-temporal generalization

To further investigate the temporal dynamics of orientation information over time, we also conducted cross-temporal generalization (King & Dehaene, 2014). The decoding methodology remained consistent with the procedures outlined previously, except for the classifier's training and testing regimen. Specifically, instead of training and testing the classifier at each corresponding time point, we trained the classifier at a specific time point and then tested it across all other time points. This resulted in a two-dimensional temporal generalization matrix that provides classification accuracy for every combination of training and testing times, indicating whether neural coding is dynamic or static over time.

2.6 Statistical assessment

We applied repeated-measure ANOVAs and made planned comparisons between the delay conditions for prioritized and deprioritized items with paired samples t-tests, to test the differences in behavioral performance. To evaluate the significance of our decoding results across the different analyses, we employed permutation tests to generate null distributions against which the observed decoding performance was compared. Specifically, we performed 100,000 permutations where the sign of the decoding accuracy for each participant was randomly flipped with 50% probability. The proportion of the null distribution where the permuted mean decoding accuracy was greater than the observed mean decoding accuracy was calculated as the p-value. The decoding performance was considered statistically significant if this p-value was less than 0.05.

For the time-course decoding analysis and time window of interest decoding, a cluster-based correction was applied to control for multiple comparisons, identifying clusters of

consecutive time points where decoding performance exceeded chance levels. Bootstrapped confidence intervals were computed to estimate the variability of the mean decoding performance over time. All test of the time-course decoding and time window of interest decoding tests were one-sided, as negative values are not meaningful. We again used paired samples t-tests to test differences between the short and long delay conditions, as well as differences between prioritized and deprioritized items within each condition.

For the cross-temporal generalization analysis, a cluster-based permutation test was employed as well. Difference matrices were computed by subtracting diagonal decoding accuracies from off-diagonal elements along both training and testing time dimensions, to assess the temporal generalization of neural representations.

3. Results

3.1 Behavioral results

A 2 x 2 repeated-measure ANOVA was conducted to examine the effects of prioritization and retention interval (1s short-delay vs. 3s long-delay) on response accuracy (Figure 2). The analysis revealed that accuracy was significantly higher for the prioritized item than the deprioritized item, $F (1, 108) = 22.97$, $p < 0.001$, $\eta^2p = 0.175$. However, the retention interval had no significant effect on accuracy, $F (1, 108) = 0.078$, $p = 0.078$, $\eta^2p = 0.001$. There was also no interaction between test order and retention interval, $F (1, 108) = 0.85$, $p = 0.360$, $\eta^2p = 0.008$, suggesting that the difference between the prioritized item and deprioritized item remained consistent across both delay conditions.

Our planned comparisons revealed no significant difference in mean accuracy for the prioritized item between the long-delay ($M = 0.8409$, $SD = 0.0459$) and short-delay conditions ($M = 0.8346$, $SD = 0.0552$, $t (27) = 1.42$, $p = 0.168$, *Cohen's d* = 0.27). However, a significant effect was observed on the deprioritized item: accuracy in the short-delay condition ($M = 0.7963$, $SD = 0.0529$) was significantly higher than in the long-delay condition ($M = 0.7845$, $SD = 0.0545$) $t (27) = -3.30$, $p = 0.003$, *Cohen's d* = -0.62). These findings suggest that while the duration of the delay period did not influence retrieval performance for the prioritized item, it had a measurable impact on the deprioritized item, with prolonged delays leading to slightly reduced accuracy (from 79.63% to 78.45%).

Figure 2. Violin plot representing response accuracy (%) for the prioritized and deprioritized items in the short (1s) and long delay (3s) conditions. The width of each violin indicates the distribution density of accuracy values across participants. The black dots represent the mean accuracy, and the error bars indicate the 95% confidence intervals. A 2x2 repeated-measures ANOVA showed a significant main effect of test order (prioritized > deprioritized), but no significant effect of retention interval or interaction. Asterisks indicate statistically significant differences between conditions (***, $p < 0.001$ for test order main effect; *, $p < 0.05$ for planned paired-samples t-tests).

3.2 Voltage decoding of memory encoding

We first performed a time course decoding analysis to test whether our participants differentially encoded the memory items depending on the delay period they were expecting. Across both short and long delay conditions, as expected, the representations of item 1 and item 2 exhibited clear parametric similarity patterns, as illustrated in Figure 3A and Figure 3D. In the short delay condition, as shown in Figure 3A-C, item 1 could be decoded (Figure 3B, left, 62-1100 ms, $p < 0.001$, and Figure 3C, left, $p < 0.001$, both one-tailed, corrected) as well as item 2 after its respective presentation (Figure 3B, right, 72-1100 ms, $p < 0.001$, and Figure 3C, right, $p < 0.001$, both one-tailed, corrected).

In the long delay condition, shown in Figure 3D-F, decoding performance was very similar, and we observed robust decoding of memory item 1 (Figure 3E, left, 60-1100 ms, $p <$ 0.001, and Figure 3F, left, $p <$ 0.001, both one-tailed, corrected) and item 2 (Figure 3E, right, 63-1100 ms, $p <$ 0.001, and Figure 3F, right, $p <$ 0.001, both one-tailed, corrected).

Comparing overall decoding in the time window of interest between the short delay and long delay conditions, decoding of item 2 appeared to be slightly stronger in the short delay condition ($t (27) = 2.10$, $p = 0.045$, *Cohen's d* = 0.35), whereas no difference was observed for item 1 ($p > 0.05$).

In summary, these results reveal a robust and sustained neural representation during memory encoding of both item 1 and item 2 in the short and long delay conditions, with decoding performance remaining largely consistent, even though there was a slight enhancement for item 2 in the short delay condition. This indicates a consistent encoding of orientation-specific information across varying delay durations.

Figure 3. Decoding during item encoding. A-C, the short delay condition. D-F, the long delay condition. A and D, pattern similarity was quantified by computing mean-centered, sign-reversed Mahalanobis distances, averaged across trials for each time point, yielding a normalized measure of orientation-specific neural representations. B and E, decoding accuracy of memory item 1 and 2 during memory item presentation. Upper solid bars and corresponding shading indicate significant decoding areas (one-sided, $p < 0.05$). Error shading indicates 95%

CI of the mean. C and F, boxplots indicating decoding accuracy for memory items within the 100-400 ms time window of interest relative to the onset of item 1 and 2. The middle line within each box represents the median, while the box itself spans the 25th to 75th percentiles. Whiskers extend to 1.5 times the interquartile range. Mean decoding accuracy is marked by filled circles, with vertical error bars showing the 95% CI. Asterisks indicate decoding accuracies that are significantly above zero (***, $p < 0.001$).

3.3 Delay interval decoding
3.3.1 Voltage

While in the above we examined memory encoding by directly assessing the representations of the memory items in the order of their *presentation*, to assess maintenance of information in WM, the analyses below are based on the (session-wise) *report order* of the items, as the latter should reflect the priority of the items in WM. These analyses started after the presentation of item 2, when both items were available to the participants, and assessed their representations across the length of the respective delay intervals.

In the short delay condition, consistent with previous studies (Wolff et al., 2017; Wolff, Kandemir, et al., 2020), decoding accuracy of both the prioritized (Figure 4A, left, 166-740 ms, and 778-843 ms, $p < 0.001$, one-sided, corrected) and deprioritized item (Figure 4A, left, 166-694 ms, $p < 0.001$, one-sided, corrected) exhibited an early peak shortly after the onset of the second memory item, with the prioritized item having a smaller significant cluster towards the end of the delay interval as well. In the analysis of our predefined time windows of interest, both the prioritized and deprioritized items were decodable in the early (100-400 ms), as well as in the late (400-1000 ms) time window (Figure 4A, right, all $p < 0.001$, one-sided).

In the long delay condition, both the prioritized (Figure 4D, left, 28-693 ms, 2783-3200ms, $p < 0.001$, one-sided, corrected) and deprioritized items (Figure 4D, left, 43-564 ms, $p < 0.001$, one-sided, corrected) were decodable immediately after the onset of the memory item 2, with the prioritized item again showing a slightly later offset. However, decoding of the prioritized item seemed to ramp up towards the end of the interval, presumably in preparation of the moment when the probe would appear, and critically, the prioritized item could be decoded again at that moment, while the deprioritized item could not. The analysis of the early time window of interest (100-400 ms) revealed that both prioritized and deprioritized items were decodable (Figure 4D, right, both $p < 0.001$, one-sided). In the late time window (2400-3000 ms), the prioritized item exhibited a marginal effect (Figure 4D, right, $p = 0.05$,

one-sided), while the deprioritized item did not reach significance (Figure 4D, right, both $p = 0.108$, one-sided).

To determine whether decoding accuracy differed between prioritized and deprioritized items, we conducted further pairwise t-tests within both delay conditions. No significant differences were found between prioritized and deprioritized items in the short or long delay conditions for any of the predefined time windows (all $p > 0.05$). Given the potential impact of the duration of the maintenance interval on neural representations, we also examined whether decoding accuracy differed between short and long delay conditions. We again observed no significant differences between short and long delay conditions for prioritized and deprioritized items within the early time window (all $p > 0.05$). However, in the late time window, decoding accuracy for both prioritized ($t(27) = 3.52$, $p < 0.01$, *Cohen's d* $= 0.65$) and deprioritized items ($t(27) = 5.05$, $p < 0.001$, *Cohen's d* $= 0.93$) in the short delay condition was significantly higher than in the long delay condition (Figure 4D, right, $p = 0.05$, one-sided, corrected).

Overall, the raw voltage-based analyses largely replicated previous studies that have observed limited to no decoding after the initial stimulus-evoked response (e.g., Wolff et al., 2017; 2020a; 2020b). In the long delay condition in particular, decoding accuracy of the prioritized item showed a steady increase towards the end of the interval, presumably in anticipation of the ensuing probe. In line with this interpretation, no such increase was observed for the deprioritized item, for which the response was not yet due at that point.

Figure 4. Decoding during delay intervals. A-C, the short delay condition. D-F, the long delay condition. A and D, raw voltage time course decoding. B and E, evoked alpha power time course decoding. C and F, induced alpha power time course decoding. Upper solid bars and corresponding shading indicate significant decoding areas (one-sided, $p < 0.05$). Error shading represents 95% CI of the mean. Boxplots illustrate decoding accuracy for prioritized and deprioritized items across the two selected time windows of interest in the short delay condition (100-400 ms and 400-1000 ms) and the long delay condition (100-400 ms and 2400-3000 ms). The middle line within each box represents the median, while the box itself spans the 25th to 75th percentiles. Whiskers extend to 1.5 times the interquartile range, and individual dots indicate extreme values. Mean decoding accuracy is marked by filled circles, with vertical error bars showing the 95% CI. Asterisks indicate significant decoding performance (*, $p < 0.05$; **, $p < 0.01$; ***, $p < 0.001$).

3.3.2 Alpha power

As indicated above, we analyzed evoked as well as induced alpha power to distinguish between externally driven and internally generated neural processes, respectively. The decoding results for evoked alpha power in the short delay condition closely mirrored those observed in the raw voltage time-course analysis. Both the prioritized (Figure 4B, left, 12-752 ms, $p < 0.001$, one-sided, corrected) and deprioritized items (Figure 4B, left, 2-536 ms, $p < 0.001$, one-sided, corrected) were decodable, with decoding accuracy peaking shortly after item 2 onset and gradually declining during the maintenance period. Time window of interest analyses showed that in the early time window, both prioritized (Figure 4B, right, $p < 0.001$, one-sided) and deprioritized items (Figure 4B, right, $p < 0.001$, one-sided) were decodable. In the late time window, decoding accuracy was much reduced overall, but remained significantly above chance for both items (Figure 4B, right, all $p < 0.001$, one-sided).

Induced alpha power decoding in the short delay interval revealed that the prioritized item exhibited continuous decodability, whereas the deprioritized item showed two shorter stretches of decodability (Figure 4C, left; prioritized: 66-1198 ms, $p < 0.001$; deprioritized: 10-336 ms, $p = 0.004$, and 536-1108 ms, $p = 0.003$, both one-sided, corrected). However, our time-window analyses did not further support these differences: Prioritized as well deprioritized items could be decoded in both the early and late time windows (Figure 4C, right; 100-400 ms: prioritized: $p < 0.001$; deprioritized: $p < 0.001$; 400-1000 ms: prioritized: $p < 0.001$; deprioritized: $p = 0.003$; all one-sided).

Evoked alpha power in the long delay condition reflected both the prioritized (Figure 4E, left, 30-372 ms, $p = 0.001$, and 1640-2616 ms, $p = 0.005$, both one-sided, corrected) and deprioritized item (Figure 4E, left, 4-428 ms, $p < 0.001$, one-sided, corrected) immediately after stimulus presentation, similar to the raw voltage decoding results. Unlike raw voltage decoding, the prioritized item was not successfully decoded at the end of the long-delay period from evoked alpha power. Time window analyses confirmed that in the early time window (100-400 ms), both prioritized and deprioritized items were decodable (Figure 4E, right, all $p < 0.001$, one-sided), while in the late time window (2400-3000 ms), only the prioritized item remained decodable (Figure 4E, right, prioritized: $p = 0.032$; deprioritized: $p > 0.05$, one-sided).

Induced alpha power in the long-delay condition showed that the prioritized item was decodable during a substantial portion of the delay interval (Figure 4F, left, 406-3182 ms, $p < 0.001$, one-sided, corrected). By contrast, the deprioritized item was only transiently decodable (Figure 4F, left, 584-1340 ms, $p < 0.001$, and 1362-1738 ms, $p = 0.018$, both one-sided, corrected). Across the early time window of interest, both prioritized (Figure 4F, right, $p < 0.001$, one-sided) and deprioritized items (Figure 4F, right, $p < 0.01$, one-sided) could

nevertheless be decoded. However, in the late time window, only the prioritized item could be decoded (Figure 4F, right, $p < 0.01$, one-sided), while the deprioritized item could not (Figure 4F, right, $p > 0.05$, one-sided).

A direct comparison of prioritized and deprioritized items revealed a significant difference in the late time window of interest for the both short and long delay intervals, with lower induced alpha power decoding accuracy for the deprioritized item (short delay: $t(27) = 3.03$, $p < 0.01$, *Cohen's d* = 0.57; long delay: $t(27) = 2.99$, $p < 0.01$, *Cohen's d* = 0.56). No differences were observed in other cases (all $p > 0.05$). We further examined whether decoding accuracy differed between short and long delay conditions. In the late time window of interest, evoked alpha power decoding accuracy was significantly stronger for the short delay than the long delay for both the prioritized item ($t(27) = -3.19$, $p = 0.004$, *Cohen's d* = -0.60) and the deprioritized item ($t(27) = -3.01$, $p = 0.006$, *Cohen's d* = 0.57). No further differences in induced alpha power between the short and long delay conditions, in both time windows, were significant, and neither were any comparisons in evoked alpha power (all $p > 0.10$).

Taken together, the analyses of alpha power, in particular induced alpha, are compatible with the idea that internally generated alpha waves play a role in the sustained, attentional maintenance of prioritized items in WM specifically. As a general mechanism to maintain information in WM (i.e., pertaining to both prioritized and deprioritized items), it would nevertheless seem to fall short, as we did not find sustained alpha oscillations related to deprioritized items.

3.4 Impulse 1

3.4.1 Voltage

Decoding voltage in the impulse 1 epoch in the short delay condition revealed that the prioritized item remained decodable throughout the post-impulse period (Figure 5A, left, 72-600 ms, $p < 0.001$, one-tailed, corrected), while the deprioritized item, which had become completely silent prior to impulse 1 onset, also exhibited a brief period of significant decoding, peaking at approximately 200 ms post-impulse onset, and quickly returning to chance level (Figure 5A, left, 182-242 ms, $p = 0.006$, one-tailed, corrected). The analysis of the time window of interest (100-400 ms relative to impulse 1 onset) showed similar results. Both the prioritized (Figure 5A, right, $p < 0.001$, one-sided) and deprioritized items (Figure 5A, right, $p = 0.023$, one-sided) were decodable, yet the prioritized item exhibited a stronger representational signal compared to the deprioritized item ($t(27) = 5.07$, $p < 0.001$, *Cohen's d* = 1.11).

In the long delay interval, raw voltage time course decoding showed a significant response for the prioritized item (Figure 5D, left, 102-482 ms, $p < 0.001$, one-tailed, corrected), but not for the deprioritized item, even though participants responded accurately to the probe afterwards. The time-of-interest (100-400 ms) analysis also revealed that only the prioritized item could be decoded (Figure 5D, right, $p < 0.001$, one-sided), while the deprioritized item could not (Figure 5D, right, $p = 0.060$, one-sided). Moreover, a clear difference in decoding strength was evident between the two items ($t(27) = 4.29$, $p < 0.001$, *Cohen's d = 0.81*).

3.4.2 Alpha power

The results from evoked alpha power time course decoding showed that both the prioritized and deprioritized item were decodable from impulse 1 in the short delay condition (Figure 5B, left, prioritized: -20-416 ms, $p < 0.001$, one-sided, corrected; deprioritized: -80-148 ms, $p = 0.010$, one-sided, corrected). The analysis of the time window of interest revealed significant decoding for the prioritized item (Figure 5B, right, $p < 0.001$, one-sided), and for the deprioritized item (Figure 5B, right, $p = 0.006$, one-sided). Moreover, decoding accuracy was significantly higher for the prioritized than for the deprioritized items ($t(27) = 2.90$, $p = 0.007$, *Cohen's d = -0.55*). Similarly, the decoding results for induced alpha power showed that both the prioritized item (Figure 5C, left, -100-600 ms, $p < 0.001$, one-sided, corrected) and the deprioritized item (Figure 5C, left, -68-406 ms, $p < 0.001$, one-sided, corrected) were decodable. Within the time window of interest, both the prioritized (Figure 5C, right, $p < 0.01$, one-sided) and deprioritized items (Figure 6C, right, $p < 0.01$, one-sided) were decodable ($t(27) = 0.76$, $p = 0.454$, *Cohen's d = 0.14*).

In the long delay condition, consistent with raw voltage decoding, the prioritized item could be decoded from evoked alpha power (Figure 5E, left, 104-466 ms, $p = 0.001$, one-sided, corrected), while the deprioritized item could not. Within the time window of interest, significant decoding was observed for the prioritized item (Figure 5E, right, $p < 0.001$, one-sided), but not for the deprioritized item (Figure 5E, right, $p = 0.308$, one-sided). A direct contrast confirmed that there was higher decoding for the prioritized than the deprioritized item ($t(27) = 3.31$, $p = 0.003$, *Cohen's d = 0.62*). In the induced alpha power time-course analysis, only the prioritized item was decodable from induced alpha power following impulse 1 (Figure 5F, left, 104-600 ms, $p = 0.001$, one-sided, corrected). Across the 100-400 ms time window of interest, significant decoding emerged for the prioritized item (Figure 5F, right, $p < 0.001$, one-sided), as well as a significant difference between prioritized and deprioritized items ($t(27) = 3.36$, $p = 0.002$, *Cohen's d = 0.64*).

Figure 5. Decoding content from the first impulse response. A-C, the short delay condition. D-F, the long delay condition. A and D, raw voltage time course decoding. B and E, evoked alpha power time course decoding. C and F, induced alpha power time course decoding. Upper solid bars and corresponding shading indicate significant decoding areas (one-sided, $p < 0.05$). Error shading represents 95% CI of the mean. Boxplots illustrate decoding accuracy for prioritized and deprioritized items within the time window of interest (100-400 ms). The middle line within each box represents the median, while the box itself spans the 25th to 75th percentiles. Whiskers extend to 1.5 times the interquartile range, and individual dots indicate extreme values. Mean decoding accuracy is marked by filled circles, with vertical error bars showing the 95% CI. Asterisks indicate significant decoding performance (*, $p < 0.05$; **, $p < 0.01$; ***, $p < 0.001$).

3.5 Impulse 2

3.5.1 Voltage

The raw voltage time course decoding analysis for impulse 2 in the short delay condition revealed that the deprioritized item was decodable throughout almost the entire delay period (Figure 6A, right, 82-452 ms, $p < 0.001$, and 472-600 ms, $p = 0.032$, one-tailed, corrected). Note that this pattern for the deprioritized item is not unexpected, as at this stage, this item had become task-relevant for the upcoming second probe. By contrast, the prioritized item was only decodable within two narrow time windows (Figure 6A, right, 222-252 ms, $p = 0.037$, and 272-312 ms, $p = 0.033$, one-tailed, corrected). The analysis of the time window of interest (100-400 ms relative to impulse 2 onset) demonstrated that only the deprioritized item could be successfully decoded (Figure 6A, right, $p < 0.001$, one-sided), whereas the prioritized item could not (Figure 6A, right, $p = 0.080$, one-sided). Moreover, there was a marked difference in decoding strength between the two items (t (27) = -4.06, $p < 0.001$, *Cohen's d =* 0.76).

Decoding results for impulse 2 in the long delay showed that the deprioritized item was consistently decodable for about 300 ms after impulse 2 onset (Figure 6D, right, 72-392 ms, $p < 0.001$, one-tailed, corrected), while the prioritized item was again only significantly decoded in short, discrete time windows (Figure 6D, right, 222-282 ms, $p = 0.01$, 322-362 ms, $p = 0.047$, 382-422 ms, $p = 0.03$, and 492-532 ms, $p = 0.025$, one-tailed, corrected). In the time window of interest (100-400 ms) both the prioritized item (Figure 6D, right, $p < 0.001$, one-sided) and deprioritized items were decodable (Figure 6D, right, $p = 0.060$, one-sided), although the deprioritized item exhibited a higher decoding strength (t (27) = 3.24, $p = 0.003$, *Cohen's d =* 0.82).

3.5.2 Alpha power

In the short delay condition, the deprioritized item could be decoded from both evoked (Figure 6B, left, 154-600 ms, $p < 0.001$, one-sided, corrected) and induced alpha power (Figure 6C, left, -100-74 ms, $p = 0.035$, and 150-600 ms, $p < 0.001$, one-sided, corrected), with decoding accuracy remaining above chance for a sustained period after impulse presentation. In the time window of interest, only the deprioritized item could be reliably decoded (Figure 6B, right, $p < 0.001$, one-sided), while the prioritized item could not (Figure 6B, right, $p = 0.250$, one-sided). A notable difference emerged in the strength of their representations (t (27) = -3.41, $p = 0.002$, *Cohen's d =* -0.64). However, both the prioritized (Figure 6C, right, $p = 0.01$, one-sided) and deprioritized items (Figure 6C, right, $p < 0.001$, one-sided) remained

decodable from induced alpha power, without a significant difference between them (t (27) = -1.86, p = 0.074, *Cohen's d* = -0.36).

A similar pattern emerged in the long delay condition, with reliable decoding of the deprioritized item from both evoked (Figure 6E, left, 46-600 ms, p = 0.001, one-sided, corrected) and induced alpha power (Figure 6F, left, -100-600 ms, p < 0.001, one-sided, corrected). In addition, the prioritized item was decodable from induced alpha power during an early, short interval (Figure 6F, left, -100-148 ms, p = 0.005, one-sided, corrected). Decoding within the predefined time widow also indicated significant decoding for the deprioritized item only, from both evoked (Figure 6E, right, p < 0.001, one-sided) and induced alpha power (Figure 6F, right, p < 0.001, one-sided). Importantly, there was again a significant difference between prioritized and deprioritized items in both evoked (t (27) = -3.18, p = 0.004, *Cohen's d* = 0.60) and induced alpha power (t (27) = -2.88, p = 0.008, *Cohen's d* = -0.54). No further significant group-level differences were detected between the short and long delay conditions for either the prioritized or deprioritized items, across all signals (voltage, evoked and induced alpha power) and across both impulses.

Figure 6. Decoding content from the second impulse response. A-C, the short delay condition. D-F, the long delay condition. A and D, raw voltage time course decoding. B and E, evoked alpha power time course decoding. C and F, induced alpha power time course decoding. Upper solid bars and corresponding shading indicate significant decoding areas (one-sided, $p < 0.05$). Error shading represents 95% CI of the mean. Boxplots illustrate decoding accuracy for prioritized and deprioritized items within the time window of interest (100-400 ms). The middle line within each box represents the median, while the box itself spans the 25^{th} to 75^{th} percentiles. Whiskers extend to 1.5 times the interquartile range, and individual dots indicate extreme values. Mean decoding accuracy is marked by filled circles, with vertical error bars showing the 95% CI. Asterisks indicate significant decoding performance (*, $p < 0.05$; **, $p < 0.01$; ***, $p < 0.001$).

3.6 Cross-temporal generalization

To further investigate the temporal dynamics of WM content, we conducted cross-temporal generalization analyses during the delay period, specifically focusing on decoding performance for the prioritized item. The results revealed striking differences in temporal stability between the short and long delay conditions when analyzing raw voltage data. The short delay epoch exhibited highly dynamic decoding patterns where prioritized item representations changed rapidly over time (Figure 7A). The long-delay condition elicited an initial dynamic state similar to that in the short delay, but then shifted into a stable representational pattern from approximately midway through the delay period (Figure 7D).

As might be expected, evoked alpha power reflected mainly stimulus-related activity. In the short delay condition, neural activity was mainly dynamic, characterized by rapidly evolving neural representations following the onset of memory item 2, and ending after about half a second (Figure 7B). A similar dynamic phase was also observed in the early stage of the long delay condition, after which decoding performance significantly declined over time, and no discernible stable neural patterns emerged in the later period of the delay (Figure 7E).

Induced alpha power also initially exhibited minimal cross generalization, indicative of highly dynamic and temporally-specific neural activity (Figure 7C). In the long delay condition, while the initial dynamic pattern was also observed in the early stage, a clear shift toward a more stable neural representation emerged approximately one second post-stimulus (Figure 7F). This finding suggests a fundamental change in how WM representations are coded across time: In the short delay condition, neural representations remain transient and dynamic,

whereas in the long delay condition, they gradually stabilize, potentially reflecting a distinct neural mechanism for prolonged maintenance.

Figure 7. Cross-temporal decoding matrices for the prioritized item, derived from training and testing on all time-point combinations. A-C, the short delay condition. D-F, the long delay condition. A and D, cross-temporal generalization in raw voltage. B and E, cross-temporal generalization in evoked alpha power. C and F, cross-temporal generalization in induced alpha

power. Decoding accuracy is represented by color intensity. The black lines indicate time-points of significantly lower decoding relative to both equivalent time-points along the diagonal (same train and test time point, $p < 0.05$, cluster corrected). Note the scale difference illustrated by the grey outline in panels D, E, and F, which corresponds to the extent of time plotted in panels A, B, and C.

4. Discussion

To investigate how alpha-band activity supports the maintenance of WM items, we compared maintenance of prioritized and deprioritized items, across different delays between memory encoding and retrieval, comparing short (1-second) and long (3-second) retention intervals. This design allowed us to dissociate whether alpha oscillations are primarily a mechanism of attentional prioritization in WM, or rather support a broader maintenance process, to keep memoranda persistently activated, or a means to provide periodic refreshing of short-lived synaptic patterns. Our analyses demonstrated a clear dissociation between behaviorally prioritized and non-prioritized memory items. Impulse response decoding closely tracked priority; decoding of the prioritized item was strong in all measures from the first impulse, and while the deprioritized item could also be detected, it was clearly much weaker. At the second impulse the picture was reversed, where decoding of the now-relevant deprioritized item was strong, and that of the obsoleted prioritized item was very weak to absent entirely.

Importantly, our analyses of the long delay interval in particular showed how this priority pattern was supported by alpha oscillations. Specifically, while orientation-specific information for both prioritized and deprioritized items was initially decodable after encoding, only the prioritized item remained decodable throughout the extended three-second interval, from induced alpha power exclusively. By contrast, the deprioritized item faded into a non-persistent, if not activity-silent state, associated with a general lack of decoding from both raw voltage and alpha band power. That said, in the first half of the long delay interval, the deprioritized item was also visible in induced alpha, potentially indicating residual attentional maintenance of this item. However, this was not visible in the impulse decoding; the deprioritized item only seemed to be really reactivated again when it became task-relevant later, at which point it was decodable from the second impulse response. While less univocal in some respects, the patterns observed in the short delay interval condition were qualitatively similar. The overall priority-based difference between the items suggests that sustained alpha oscillations mainly support attentional prioritization rather than general maintenance in WM.

This finding aligns with broader theoretical frameworks proposing that alpha oscillations are involved in top-down attentional control and sensory gating (Bonnefond & Jensen, 2012; Jensen & Mazaheri, 2010; Klimesch, 2012). Accordingly, in the context of WM, alpha band oscillations are thought to play a role in guiding goal-directed action (Myers et al., 2017; van Ede et al., 2017), and have also been associated with inhibition of irrelevant information and/or further visual input in order to protect memory contents (Payne & Sekuler, 2014; Sauseng et al., 2009; Wianda & Ross, 2019). Although the idea that attention might support WM maintenance in this manner has intuitive appeal, it bears noting that the present results suggest that these functions are exclusively reserved for items that are prioritized in WM, not all items. In other words, the boundaries of attention are not the boundaries of WM (cf. Oberauer & Awh, 2022), which is contrary to some previous proposals (Chun, 2011; Cowan, 2001; Foster & Awh, 2019). The selective role of attention nevertheless fits well with proposals of prioritized (or "activated") WM, which is thought to constitute a privileged subset of WM (Borst et al., 2010; Manohar et al., 2019; Oberauer, 2002; Olivers et al., 2011), and which may exist without the need to sacrifice retention of other memoranda in WM (Myers et al., 2018).

As indicated, some previous studies have suggested a broader, more general role for alpha oscillations in WM maintenance. Foster and colleagues (2017; Sutterer et al., 2019) reported persistently active spatial representations in the alpha band, even arising regardless of task relevance, which suggest these oscillations might serve a more general maintenance process. Ten Oever and colleagues (2020) found that alpha phase modulated the EEG impulse response during WM maintenance, attributing the effect to an interaction with ongoing activity. Similarly, Barbosa and colleagues (2021) decoded WM items from alpha band power, and interpreted this as a sign of representational maintenance based on ongoing activity. Chen and colleagues (2023) even reported a causal link between parietal alpha oscillations and WM, linking it to retention processes. However, despite these prior findings, the idea that persistent alpha oscillations support WM maintenance in general, either as an active representational code, or as a refreshing mechanism to keep synaptic representations in place, was generally not supported by our data, especially when considering the decoding patterns in the long delay interval.

We can think of three main reasons for why our results might diverge from those of these previous studies that seemed to suggest a more general role for alpha oscillations in WM maintenance. First, we purposefully implemented a longer delay condition to tap into processes that might play out beyond the earliest phase of WM maintenance, during the first one or two

seconds. We reasoned that this early phase might be special, for instance because calcium-mediated short-term synaptic connectivity would be effective across this interval, but not beyond, as the supporting calcium residuals would then have dissipated (Mongillo et al., 2008; Pals et al., 2020). Previous analyses of WM maintenance have typically used short delay intervals within this relatively short range (e.g., Kandemir, Wilhelm, et al., 2024; Yang et al., 2025), which might have produced an incomplete picture of the maintenance process. In the present data, the outcomes in the short interval were also more ambiguous with regard to sustained activity, where we observed successful, albeit intermittent, decoding of the deprioritized item from alpha band power, for instance.

Second, studies of WM have often relied on tasks in which only a single item is retained during the delay interval (e.g., Thrower et al., 2023), which also applies to tasks in which one item is singled out from a larger set for eventual recall by a cue, and in which the other items can then be discarded altogether (e.g., F.-W. Chen et al., 2023; Karabay et al., 2025). When there is only a single task-relevant item, and particularly when attention has been called towards that item by a cue stimulus, it seems likely that it will stay in the focus of attention. In the present study, we were able to contrast this scenario with that of a second item that also had to be maintained, but which was placed temporarily outside the focus of attention. The data showed that in contrast to the attended, prioritized item, this second deprioritized item was maintained without the involvement of any detectable sustained activity, neither in broadband EEG, nor in the alpha band specifically.

Third, previous studies on WM have often analyzed alpha power without distinguishing between evoked and induced components, potentially conflating bottom-up and top-down processes (e.g., Barbosa et al., 2021; Kandemir, Wilhelm, et al., 2024; Sauseng et al., 2005). In our study, evoked and induced alpha activity showed distinct temporal and functional characteristics. Evoked alpha power, which was expected to reflect stimulus-locked responses, primarily associated with the initial encoding of WM items in our task, indeed showed robust decoding of both prioritized and deprioritized items shortly after stimulus presentation. However, this decoding was transient, with no sustained decoding observed during the later portions of the delay period. Importantly, induced alpha power, which should reflect internally generated, non-phase-locked oscillatory activity, remained the primary, sustained carrier of prioritized information throughout the long delay condition.

The present data cannot arbitrate whether alpha oscillations during WM maintenance serve mainly to protect attended representations against interference, or to prepare for associated action, which is thought to be an important function of WM (van Ede, 2020).

Against the former account, one might wonder why non-prioritized representations would then not need such protection. Against the latter account, one might consider the raw voltage decoding during the long delay interval. Towards the end of this interval, raw voltage decoding steadily increased, likely in anticipation of the probe, when action was needed. By contrast, such an increase was not apparent in the alpha band, suggesting that this preparatory effect has its roots elsewhere. As such, it would seem that further research is needed to more precisely determine the nature of the prioritization afforded by alpha oscillations in WM.

One further hint towards the functional role of alpha oscillations might be had from the temporal generalization that we observed. Initially, through most of the short delay interval, decoding patterns were highly dynamic and time-specific, consistent with rapidly evolving neural codes (Lundqvist et al., 2016; Wolff et al., 2017). After this initial period, we observed a transition from dynamic to stable representations, in both raw voltage and induced alpha power. The emergence of sustained cross-temporal decoding about 1 s post-stimulus suggests that prolonged maintenance may depend on temporally stable attractor-like states (Murray et al., 2017; Spaak et al., 2017), and may reflect a shift from perceptual encoding to abstract mnemonic representations over time (Kamiński & Rutishauser, 2020; Stokes, 2015). These results support mixed-state models of WM, in which initially dynamic activity gradually turns into a stable coding pattern over the course of the delay, rather than both codes coexisting throughout (Murray et al., 2017).

Overall decoding of deprioritized items, or rather the lack thereof, might speculatively be related to this change in representational format over time. Deprioritized item decoding fell back to baseline, or at least close to it, within 1.5 s across all measures. Possibly, the representational change that prioritized items go through is mirrored by a transition to a silent state for deprioritized items; a moment at which unattended information may lose active status. It is also interesting to note that this purported transition occurs when computational models of STSP would suggest that short-term synaptic traces that can sustain WM representations reach the end of their lifespan (Mongillo et al., 2008). Nevertheless, it should be noted that in spite of this convergence the possibility remains that this transition is one towards some other kind of ongoing activity that is undetectable by EEG (e.g., due to the involvement of other brain regions that might be less accessible due to cortical folding; Christophel et al., 2018).

To conclude, our results reveal that sustained neural representations in the alpha band during the delay interval are not uniformly present across all memorized items but instead selectively track the attentional prioritization of WM contents. Specifically, while early decoding accuracy for both prioritized and deprioritized items was evident across raw voltage

and evoked alpha power, these signals rapidly diminished over time and failed to support sustained maintenance, particularly for deprioritized items. By contrast, induced alpha power revealed temporally extended and selectively robust decoding of the prioritized item, especially in the long delay condition. Importantly, deprioritized items did not exhibit similarly sustained decoding, suggesting that induced alpha oscillations do not support the general maintenance of all memory contents but are instead selectively engaged by prioritized representations. These findings suggest that alpha oscillations serve as a neural substrate for attentional prioritization in WM, rather than a generic mechanism for maintaining all stored information therein.

Declarations

Data and code availability

All data, analysis scripts and results are available at the Open Science Framework: osf.io/4tejh. The repository is currently private for peer review and will be made publicly available upon acceptance of manuscript.

Declaration of competing interest

The authors declare no competing interests.

Author contributions

Yuanyuan Weng: Data curation, methodology, visualization, software, formal analysis, funding acquisition, investigation, writing – original draft, writing – review and editing.

Jelmer P. Borst: Conceptualization, methodology, formal analysis, supervision, funding acquisition, writing – review and editing.

Elkan G. Akyürek: Conceptualization, methodology, formal analysis, supervision, funding acquisition, writing – review and editing.

Funding

This research was supported by Chinese Scholarship Council, grant 202106990030.

References

Baddeley, A. (2003). Working memory: Looking back and looking forward. *Nature Reviews Neuroscience*, *4*(10), 829–839. https://doi.org/10.1038/nrn1201

Bae, G.-Y., & Luck, S. J. (2018). Dissociable decoding of spatial attention and working memory from EEG oscillations and sustained potentials. *The Journal of Neuroscience*, *38*(2), 409–422. https://doi.org/10.1523/JNEUROSCI.2860-17.2017

Barak, O., & Tsodyks, M. (2014). Working models of working memory. *Current Opinion in Neurobiology*, *25*, 20–24. https://doi.org/10.1016/j.conb.2013.10.008

Barbosa, J., Lozano-Soldevilla, D., & Compte, A. (2021). Pinging the brain with visual impulses reveals electrically active, not activity-silent, working memories. *PLoS Biology*, *19*(10), e3001436. https://doi.org/10.1371/journal.pbio.3001436

Bonnefond, M., & Jensen, O. (2012). Alpha oscillations serve to protect working memory maintenance against anticipated distracters. *Current Biology*, *22*(20), 1969–1974. https://doi.org/10.1016/j.cub.2012.08.029

Borst, J. P., Taatgen, N. A., & Van Rijn, H. (2010). The problem state: A cognitive bottleneck in multitasking. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, *36*(2), 363–382. https://doi.org/10.1037/a0018106

Buonomano, D. V., & Maass, W. (2009). State-dependent computations: Spatiotemporal processing in cortical networks. *Nature Reviews Neuroscience*, *10*(2), 113–125. https://doi.org/10.1038/nrn2558

Chen, F.-W., Li, C.-H., & Kuo, B.-C. (2023). Temporal expectation based on the duration variability modulates alpha oscillations during working memory retention. *NeuroImage*, *265*, 119789. https://doi.org/10.1016/j.neuroimage.2022.119789

Chen, X., Ma, R., Zhang, W., Zeng, G. Q., Wu, Q., Yimiti, A., Xia, X., Cui, J., Liu, Q., Meng, X., Bu, J., Chen, Q., Pan, Y., Yu, N. X., Wang, S., Deng, Z.-D., Sack, A. T., Laughlin, M. M., & Zhang, X. (2023). Alpha oscillatory activity is causally linked to working memory retention. *PLOS Biology*, *21*(2), e3001999. https://doi.org/10.1371/journal.pbio.3001999

Christophel, T. B., Iamshchinina, P., Yan, C., Allefeld, C., & Haynes, J.-D. (2018). Cortical specialization for attended versus unattended working memory. *Nature Neuroscience*, *21*(4), 494–496. https://doi.org/10.1038/s41593-018-0094-4

Chun, M. M. (2011). Visual working memory as visual attention sustained internally over time. *Neuropsychologia*, *49*(6), 1407–1409. https://doi.org/10.1016/j.neuropsychologia.2011.01.029

Constantinidis, C., Funahashi, S., Lee, D., Murray, J. D., Qi, X.-L., Wang, M., & Arnsten, A. F. T. (2018). Persistent spiking activity underlies working memory. *The Journal of Neuroscience*, *38*(32), 7020–7028. https://doi.org/10.1523/JNEUROSCI.2486-17.2018

Cowan, N. (2001). The magical number 4 in short-term memory: A reconsideration of mental storage capacity. *Behavioral and Brain Sciences*, *24*(1), 87–114. https://doi.org/10.1017/S0140525X01003922

De Maesschalck, R., Jouan-Rimbaud, D., & Massart, D. L. (2000). The Mahalanobis distance. *Chemometrics and Intelligent Laboratory Systems*, *50*(1), 1–18. https://doi.org/10.1016/S0169-7439(99)00047-7

Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of single-trial EEG dynamics including independent component analysis. *Journal of Neuroscience Methods*, *134*(1), 9–21. https://doi.org/10.1016/j.jneumeth.2003.10.009

Fiebig, F., & Lansner, A. (2017). A spiking working memory model based on hebbian short-term potentiation. *Journal of Neuroscience*, *37*(1), 83–96. https://doi.org/10.1523/JNEUROSCI.1989-16.2016

Foster, J. J., & Awh, E. (2019). The role of alpha oscillations in spatial attention: Limited evidence for a suppression account. *Current Opinion in Psychology*, *29*, 34–40. https://doi.org/10.1016/j.copsyc.2018.11.001

Foster, J. J., Bsales, E. M., Jaffe, R. J., & Awh, E. (2017). Alpha-band activity reveals

    spontaneous representations of spatial position in visual working memory. *Current*

    Biology, *27*(20), 3216-3223.e6. https://doi.org/10.1016/j.cub.2017.09.031

Fulvio, J. M., Haegens, S., & Postle, B. R. (2024). Single-pulse transcranial magnetic

    stimulation affects working-memory performance via posterior beta-band oscillations.

    Journal of Cognitive Neuroscience, *36*(9), 1827–1846.

    https://doi.org/10.1162/jocn_a_02194

Goldman-Rakic, P. S. (1995). Cellular basis of working memory. *Neuron*, *14*(3), 477–485.

    https://doi.org/10.1016/0896-6273(95)90304-6

Jensen, O., Gelfand, J., Kounios, J., & Lisman, J. E. (2002). Oscillations in the alpha band

    (9–12 hz) increase with memory load during retention in a short-term memory task.

    Cerebral Cortex, *12*(8), 877–882. https://doi.org/10.1093/cercor/12.8.877

Jensen, O., & Mazaheri, A. (2010). Shaping functional architecture by oscillatory alpha

    activity: Gating by inhibition. *Frontiers in Human Neuroscience*, *4*.

    https://doi.org/10.3389/fnhum.2010.00186

Kamiński, J., & Rutishauser, U. (2020). Between persistently active and activity-silent

    frameworks: Novel vistas on the cellular basis of working memory. *Annals of the New*

    York Academy of Sciences, *1464*(1), 64–75. https://doi.org/10.1111/nyas.14213

Kandemir, G., & Akyürek, E. G. (2023). Impulse perturbation reveals cross-modal access to

    sensory working memory through learned associations. *NeuroImage*, *274*, 120156.

    https://doi.org/10.1016/j.neuroimage.2023.120156

Kandemir, G., Wilhelm, S. A., Axmacher, N., & Akyürek, E. G. (2024). Maintenance of

    color memoranda in activity-quiescent working memory states: Evidence from

    impulse perturbation. *iScience*, *27*(4), 109565.

    https://doi.org/10.1016/j.isci.2024.109565

Kandemir, G., Wolff, M. J., Karabay, A., Stokes, M. G., Axmacher, N., & Akyürek, E. G. (2024). Concurrent maintenance of both veridical and transformed working memory representations within unique coding schemes. *Imaging Neuroscience*, *2*, 1–20. https://doi.org/10.1162/imag_a_00173

Karabay, A., Wolff, M. J., Ruuskanen, V., & Akyürek, E. G. (2025). Behaviorally irrelevant feature matching increases neural and behavioral working memory readout. *Psychophysiology*, *62*(2), e70020. https://doi.org/10.1111/psyp.70020

King, J.-R., & Dehaene, S. (2014). Characterizing the dynamics of mental representations: The temporal generalization method. *Trends in Cognitive Sciences*, *18*(4), 203–210. https://doi.org/10.1016/j.tics.2014.01.002

Klimesch, W. (2012). Alpha-band oscillations, attention, and controlled access to stored information. *Trends in Cognitive Sciences*, *16*(12), 606–617. https://doi.org/10.1016/j.tics.2012.10.007

Kojima, S., & Goldman-Rakic, P. S. (1982). Delay-related activity of prefrontal neurons in rhesus monkeys performing delayed response. *Brain Research*, *248*(1), 43–50. https://doi.org/10.1016/0006-8993(82)91145-3

Kozachkov, L., Tauber, J., Lundqvist, M., Brincat, S. L., Slotine, J.-J., & Miller, E. K. (2022). Robust and brain-like working memory through short-term synaptic plasticity. *PLOS Computational Biology*, *18*(12), e1010776. https://doi.org/10.1371/journal.pcbi.1010776

LaRocque, J. J., Lewis-Peacock, J. A., Drysdale, A. T., Oberauer, K., & Postle, B. R. (2013). Decoding attended information in short-term memory: An EEG study. *Journal of Cognitive Neuroscience*, *25*(1), 127–142. https://doi.org/10.1162/jocn_a_00305

Ledoit, O., & Wolf, M. (2003). *Honey, I shrunk the sample covariance matrix* (SSRN

      Scholarly Paper No. 433840). Social Science Research Network.

      https://doi.org/10.2139/ssrn.433840

Lundqvist, M., Herman, P., & Miller, E. K. (2018). Working memory: Delay activity, yes!

      Persistent activity? Maybe not. *Journal of Neuroscience*, *38*(32), 7013–7019.

      https://doi.org/10.1523/JNEUROSCI.2485-17.2018

Lundqvist, M., Rose, J., Herman, P., Brincat, S. L., Buschman, T. J., & Miller, E. K. (2016).

      Gamma and beta bursts underlie working memory. *Neuron*, *90*(1), 152–164.

      https://doi.org/10.1016/j.neuron.2016.02.028

Manohar, S. G., Zokaei, N., Fallon, S. J., Vogels, T. P., & Husain, M. (2019). Neural

      mechanisms of attending to items in working memory. *Neuroscience & Biobehavioral*

      Reviews, *101*, 1–12. https://doi.org/10.1016/j.neubiorev.2019.03.017

Mathôt, S., Schreij, D., & Theeuwes, J. (2012). OpenSesame: An open-source, graphical

      experiment builder for the social sciences. *Behavior Research Methods*, *44*(2), 314–

      324. https://doi.org/10.3758/s13428-011-0168-7

Miller, E. K., Lundqvist, M., & Bastos, A. M. (2018). Working Memory 2.0. *Neuron*, *100*(2),

      463–475. https://doi.org/10.1016/j.neuron.2018.09.023

Mongillo, G., Barak, O., & Tsodyks, M. (2008). Synaptic theory of working memory.

      Science, *319*(5869), 1543–1546. https://doi.org/10.1126/science.1150769

Murray, J. D., Bernacchia, A., Roy, N. A., Constantinidis, C., Romo, R., & Wang, X.-J.

      (2017). Stable population coding for working memory coexists with heterogeneous

      neural dynamics in prefrontal cortex. *Proceedings of the National Academy of*

      Sciences, *114*(2), 394–399. https://doi.org/10.1073/pnas.1619449114

Myers, N. E., Chekroud, S. R., Stokes, M. G., & Nobre, A. C. (2018). Benefits of flexible

      prioritization in working memory can arise without costs. *Journal of Experimental*

Psychology: Human Perception and Performance, *44*(3), 398–411.

https://doi.org/10.1037/xhp0000449

Myers, N. E., Stokes, M. G., & Nobre, A. C. (2017). Prioritizing Information during Working

Memory: Beyond Sustained Internal Attention. *Trends in Cognitive Sciences*, *21*(6),

449–461. https://doi.org/10.1016/j.tics.2017.03.010

Oberauer, K. (2002). Access to information in working memory: Exploring the focus of

attention. *Journal of Experimental Psychology: Learning, Memory, and Cognition*,

28(3), 411–421. https://doi.org/10.1037/0278-7393.28.3.411

Oberauer, K., & Awh, E. (2022). Is there an activity-silent working memory? *Journal of*

Cognitive Neuroscience, *34*(12), 2360–2374. https://doi.org/10.1162/jocn_a_01917

Olivers, C. N. L., Peters, J., Houtkamp, R., & Roelfsema, P. R. (2011). Different states in

visual working memory: When it guides attention and when it does not. *Trends in*

Cognitive Sciences, S1364661311000854. https://doi.org/10.1016/j.tics.2011.05.004

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2011). FieldTrip: Open source

software for advanced analysis of MEG, EEG, and invasive electrophysiological data.

Computational Intelligence and Neuroscience, *2011*(1), 156869.

https://doi.org/10.1155/2011/156869

Pals, M., Stewart, T. C., Akyürek, E. G., & Borst, J. P. (2020). A functional spiking-neuron

model of activity-silent working memory in humans based on calcium-mediated

short-term synaptic plasticity. *PLOS Computational Biology*, *16*(6), e1007936.

https://doi.org/10.1371/journal.pcbi.1007936

Payne, L., & Sekuler, R. (2014). The importance of ignoring: Alpha oscillations protect

selectivity. *Current Directions in Psychological Science*, *23*(3), 171–177.

https://doi.org/10.1177/0963721414529145

Rose, N. S., LaRocque, J. J., Riggall, A. C., Gosseries, O., Starrett, M. J., Meyering, E. E., &
Postle, B. R. (2016). Reactivation of latent working memories with transcranial
magnetic stimulation. *Science (New York, N.Y.)*, *354*(6316), 1136–1139.
https://doi.org/10.1126/science.aah7011

Sauseng, P., Klimesch, W., Heise, K. F., Gruber, W. R., Holz, E., Karim, A. A., Glennon, M.,
Gerloff, C., Birbaumer, N., & Hummel, F. C. (2009). Brain oscillatory substrates of
visual short-term memory capacity. *Current Biology*, *19*(21), 1846–1852.
https://doi.org/10.1016/j.cub.2009.08.062

Sauseng, P., Klimesch, W., Stadler, W., Schabus, M., Doppelmayr, M., Hanslmayr, S.,
Gruber, W. R., & Birbaumer, N. (2005). A shift of visual spatial attention is
selectively associated with human EEG alpha activity. *European Journal of
Neuroscience*, *22*(11), 2917–2926. https://doi.org/10.1111/j.1460-9568.2005.04482.x

Spaak, E., Watanabe, K., Funahashi, S., & Stokes, M. G. (2017). Stable and dynamic coding
for working memory in primate prefrontal cortex. *The Journal of Neuroscience*,
37(27), 6503–6516. https://doi.org/10.1523/JNEUROSCI.3364-16.2017

Stokes, M. G. (2015). 'activity-silent' working memory in prefrontal cortex: A dynamic
coding framework. *Trends in Cognitive Sciences*, *19*(7), 394–405.
https://doi.org/10.1016/j.tics.2015.05.004

Sutterer, D. W., Foster, J. J., Adam, K. C. S., Vogel, E. K., & Awh, E. (2019). Item-specific
delay activity demonstrates concurrent storage of multiple active neural
representations in working memory. *PLOS Biology*, *17*(4), e3000239.
https://doi.org/10.1371/journal.pbio.3000239

ten Oever, S., De Weerd, P., & Sack, A. T. (2020). Phase-dependent amplification of working
memory content and performance. *Nature Communications*, *11*(1), 1832.
https://doi.org/10.1038/s41467-020-15629-7

Thrower, L., Dang, W., Jaffe, R. G., Sun, J. D., & Constantinidis, C. (2023). Decoding

    working memory information from neurons with and without persistent activity in the

    primate prefrontal cortex. *Journal of Neurophysiology*, *130*(6), 1392–1402.

    https://doi.org/10.1152/jn.00290.2023

van Ede, F. (2020). Visual working memory and action: Functional links and bi-directional

    influences. *Visual Cognition*, *28*(5–8), 401–413.

    https://doi.org/10.1080/13506285.2020.1759744

van Ede, F., Niklaus, M., & Nobre, A. C. (2017). Temporal expectations guide dynamic

    prioritization in visual working memory through attenuated A oscillations. *Journal of*

    Neuroscience, *37*(2), 437–445. https://doi.org/10.1523/JNEUROSCI.2272-16.2016

Vries, I. E. J. de, Slagter, H. A., & Olivers, C. N. L. (2020). Oscillatory control over

    representational states in working memory. *Trends in Cognitive Sciences*, *24*(2), 150–

    162. https://doi.org/10.1016/j.tics.2019.11.006

Wianda, E., & Ross, B. (2019). The roles of alpha oscillation in working memory retention.

    Brain and Behavior, *9*(4), e01263. https://doi.org/10.1002/brb3.1263

Wolff, M. J., Jochim, J., Akyürek, E. G., Buschman, T. J., & Stokes, M. G. (2020). Drifting

    codes within a stable coding scheme for working memory. *PLOS Biology*, *18*(3),

    e3000625. https://doi.org/10.1371/journal.pbio.3000625

Wolff, M. J., Jochim, J., Akyürek, E. G., & Stokes, M. G. (2017). Dynamic hidden states

    underlying working memory guided behaviour. *Nature Neuroscience*, *20*(6), 864–871.

    https://doi.org/10.1038/nn.4546

Wolff, M. J., Kandemir, G., Stokes, M. G., & Akyürek, E. G. (2020). Unimodal and bimodal

    access to sensory working memories by auditory and visual impulses. *The Journal of*

    Neuroscience, *40*(3), 671–681. https://doi.org/10.1523/JNEUROSCI.1194-19.2019

Yang, C., He, X., & Cai, Y. (2025). Reactivating and reorganizing activity-silent working memory: Two distinct mechanisms underlying pinging the brain. *Cerebral Cortex*, *35*(2), bhae494. https://doi.org/10.1093/cercor/bhae494

Zucker, R. S., & Regehr, W. G. (2002). Short-term synaptic plasticity. *Annual Review of Physiology*, *64*(Volume 64, 2002), 355–405. https://doi.org/10.1146/annurev.physiol.64.092501.114547