Interpolation-Based Conditioning of Flow Matching Models for Bioisosteric Ligand Design

Yael Ziv[1,3], Martin Buttenschoen[1], Lukas Scheiblerger[3], Brian Marsden[2,3] & Charlotte M. Deane[1]

[1]Department of Statistics, University of Oxford, St Giles', OX1 3LB, Oxford, United Kingdom
[2]Nuffield Department of Medicine, University of Oxford, Old Road, OX3 7BN, Oxford, United Kingdom
[3]Centre for Medicines Discovery, Nuffield Department of Medicine, OX3 7FZ, Oxford, United Kingdom

E-mail: deane@stats.ox.ac.uk

Abstract

Fast, unconditional 3D generative models can now produce high-quality molecules, but adapting them for specific design tasks often requires costly retraining. To address this, we introduce two training-free, inference-time conditioning strategies, *Interpolate–Integrate* and *Replacement Guidance*, that provide control over E(3)-equivariant flow-matching models. Our methods generate bioisosteric 3D molecules by conditioning on seed ligands or fragment sets to preserve key determinants like shape and pharmacophore patterns, without requiring the original fragment atoms to be present. We demonstrate their effectiveness on three drug-relevant tasks: natural product ligand hopping, bioisosteric fragment merging, and pharmacophore merging.

1 Introduction

In drug discovery, the design of effective compounds is guided by information about the biomolecular target. This information can be direct, as in structure-based drug design (SBDD), where the target's 3D structure is known; or it can be indirect, as in ligand-based drug design (LBDD), where knowledge is inferred from molecules already known to bind the target. The difference can be illustrated with an analogy: SBDD is like having the blueprint for a lock, while LBDD is like trying to make a new key by only studying existing keys. While SBDD is powerful, the protein structure is often unknown, making LBDD a widely-used approach (Acharya et al.; Sharma et al., 2021; Palazzesi & Pozzan, 2022; Zhung et al., 2024). This work focuses on the challenges of LBDD. The central goal in LBDD is to preserve key interaction patterns (e.g., shape or pharmacophores, a specific 3D arrangement of interaction features) of a reference ligand while optimizing other properties like synthetic accessibility. This is applied in tasks like natural product ligand hopping, where complex molecules are redesigned into simpler analogues (Morrison & Hergenrother, 2014). Another application is fragment-based design, where information from multiple small, weakly-binding fragments is used to design a single, more potent molecule (Erlanson et al., 2004). A key strategy is bioisosteric fragment merging, which combines the interaction patterns from multiple fragments into a single new molecule (Wills et al., 2024). In this approach, the final product may discard the exact fragment atoms but must preserve their essential shape and pharmacophores.

Existing conditional generators that operate on ligand information alone involve specific trade-offs. For example, REINVENT (Olivecrona et al., 2017) is not 3D-native, instead optimizing SMILES with reinforcement learning toward user-defined objectives. Others, such as SQUID and Shape-Mol, generate molecules in 3D but condition only on a reference molecule's overall shape, not on more granular pharmacophore patterns (Adams & Coley, 2023; Chen et al., 2023). The state-of-the-art Shepherd model advances this by conditioning on a combination of shape, electrostatic potential (ESP), and pharmacophore grids (Adams et al., 2025). However, its application to multi-fragment conditioning requires a manual step of constructing the aggregate ESP and interaction profile of the fragments. Looking ahead, large-scale structural efforts such as the UK *OpenBind*

consortium—aiming to produce >500,000 protein–ligand complexes—will markedly expand fragment and pose libraries, highlighting the need for tools that can operate directly in this data-rich regime (OpenBind Consortium, 2025).

To address this gap, we adapt a pre-trained, unconditional models for controllable, goal-directed tasks. Recent advances in fast, unconditional SE(3)/E(3)-equivariant models provide realistic 3D molecule generators that support large-scale sampling (Buttenschoen et al., 2025). For molecule generation, there are already examples of this strategy (also called goal-directed or controllable generation), e.g. (Baillif et al., 2023; Xu et al., 2023; Morehead & Cheng, 2024; Le et al., 2024; Ziv et al., 2025). By repurposing these powerful foundational models, we can avoid costly retraining and create flexible, on-the-fly conditioning mechanisms.

In this work, we introduce two modular, training-free conditioning strategies for a state-of-the-art flow-matching model, enabling precise, ligand-based bioisosteric design at inference time. Our main contributions are:

- Two complementary, inference-time conditioning methods. *Interpolate–Integrate* designed for controlled similarity to a seed molecule and *Replacement Guidance* for bioisosteric merging with a user-controlled degree of relaxation. A key feature of our framework is the ability to automatically condition on a set of multiple fragments.

- Both methods are training-free and modular, operating on a pre-trained flow-matching model. This efficient approach avoids costly retraining, making the framework adaptable for various ligand-only design scenarios where protein structures are unavailable.

- We demonstrate the practical effectiveness of our framework across three challenging drug-relevant tasks—natural product ligand hopping, bioisosteric fragment merging, and pharmacophore merging—producing high yields of valid and synthetically accessible molecules that outperform specialized, state-of-the-art baselines.

2 RELATED WORK

2.1 UNCONDITIONAL MOLECULAR GENERATION

The Equivariant Diffusion Model (EDM) established a foundational baseline for 3D molecular generation by using an E(3)-equivariant network to jointly denoise atom types and coordinates (Hoogeboom et al., 2022). Since EDM, several unconditional 3D generators have advanced capacity and efficiency, including EQGAT-diff (Le et al., 2024), FlowMol (Dunn & Koes, 2024), GCDM (Morehead & Cheng, 2024), GeoLDM (Xu et al., 2023), and SemlaFlow (Irwin et al., 2024). A recent head-to-head evaluation (Buttenschoen et al., 2025) on GEOM-Drugs reports that SemlaFlow achieves the best overall performance, with an 87% success rate for generating valid, unique, and novel molecules without post-processing (92.4% with post-processing), and is the fastest method compared.

2.2 TRAIN-TIME JOINT CONDITIONAL MODELS (3D-NATIVE AND GOAL-DIRECTED)

Ligand-based conditional design has long used 1D/2D generators guided by 3D-derived constraints (e.g., shape/pharmacophores), which still require post hoc conformer generation (Skalic et al., 2019; Imrie et al., 2021a). In contrast, 3D conditional models place atoms in space directly. Both SQUID (Adams & Coley, 2023) and SHAPEMOL (Chen et al., 2023) condition generation on a target 3D shape, typically represented as a point cloud. SQUID couples an equivariant shape encoder with fragment-wise autoregressive assembly, and ShapeMol uses an equivariant shape encoder with a conditional diffusion decoder. Closest to our task, ShEPhERD learns a joint diffusion over molecules *and* interaction grids (shape, ESP, pharmacophores) on 1.6 M MOSES (Polykovskiy et al., 2020) structures (Adams et al., 2025). Despite its capabilities, ShEPhERD must be retrained for every new conditioning channel and still requires manual grid construction. As a non-joint alternative, REINVENT is a non-3D-native method that optimizes a SMILES policy with reinforcement learning, requiring post hoc conformer generation (Olivecrona et al., 2017).

2.3 INFERENCE-TIME CONDITIONING AND EDITING

Inference-time conditioning allows users to steer a pretrained generator without additional training. SBDD controls parallel diffusion-based inpainting and editing methods developed for images and point clouds (Lugmayr et al., 2022; Meng et al., 2022; Zeng et al., 2022). In SBDD, this is often applied to generate molecules directly in the protein pocket; examples include DiffSBDD (Schneuing et al., 2024) that apply inpainting and context injection to a pocket-conditioned SE(3) diffuser, while PILOT (Cremer et al., 2024) adds importance-sampling guidance on top of a large-scale pretrained model to meet multiple objectives. SILVR (Runcie & Mey, 2023) refines latent trajectories to satisfy pocket or fragment constraints, and MolSnapper (Ziv et al., 2025) projects explicit pharmacophore points (e.g., donors, acceptors) into the diffusion process. Fragment merging/linking provides a closely related setting: DiffLinker (Igashov et al., 2024) treats the linker as a 3D-conditioned diffusion sub-problem and reports higher validity and lower RMSD than inpainting; LinkerNet co-designs linker geometry and poses jointly (Guan et al., 2023). To speed up inference, TurboHopp replaces the diffusion backbone with a consistency model, enabling pocket-conditioned scaffold hopping (Yoo et al., 2024).

2.4 POSITIONING OF THIS WORK.

Our work introduces *Interpolate–Integrate* and *Replacement Guidance*, two **ligand-only, inference-time** conditioning methods for **bioisosteric design**, where the goal is to generate a ligand that preserves the key binding determinants of a reference molecule, such as overall shape and pharmacophoric interactions, without need to retain the original atoms. As a training-free framework on a fast flow-matching backbone, our approach avoids the costly retraining required by many conditional models. It provides modular, fine-grained control directly at sampling while preserving the high inference speed of the base model. This allows for the efficient generation of chemically diverse molecules that maintain key pharmacophoric and shape-based interactions.

3 METHODS: CONDITIONING FLOW MATCHING FOR MOLECULAR GENERATION

We propose two conditioning mechanisms for fast, controlled 3D molecular generation on top of *SemlaFlow* (Irwin et al., 2024), an E(3)-equivariant flow-matching model that jointly generates coordinates and discrete chemistry. We first summarize conditional flow matching (CFM) (Lipman et al., 2022; Campbell et al., 2024) and SemlaFlow's path and solver in particular. Finally, we formulate the interpolate-integrate and replacement guidance, our two conditioning methods.

3.1 BACKGROUND

3.1.1 CONDITIONAL FLOW MATCHING (CFM)

Let $z = (x, a, b, c)$ denote a molecule with atomic coordinates $x \in \mathbb{R}^{N \times 3}$, atom types $a \in \mathcal{A}^N$, bond types $b \in \mathcal{B}^{N \times N}$, and formal charges $c \in \mathcal{C}^N$. CFM trains a neural vector field $v_\theta(t, z)$ whose flow ϕ_t pushes a simple prior p_0 to a data distribution p_1 by regressing to a target *conditional* vector field $u_t(z \mid z_1)$ defined along a per-example probability path $p_t(z \mid z_1)$ connecting noise to a specific data point z_1. The learning objective is the conditional regression

$$\mathcal{L}_{\text{CFM}}(\theta) = \mathbb{E}_{\substack{t \sim \mathcal{U}[0,1], \\ z_1 \sim p_{\text{data}}, \, z_t \sim p_t(\cdot|z_1)}} \left\| v_\theta(t, z_t) - u_t(z_t \mid z_1) \right\|^2,$$

which yields the same optimum as regressing the (intractable) marginal vector field on the marginal path p_t obtained by integrating out z_1. This conditional formulation is simulation-free and admits many paths, including diffusion and optimal-transport (OT) Gaussian paths.

3.1.2 SEMLAFLOW INSTANTIATION FOR MOLECULES

Joint variables and paths. SemlaFlow models the joint $p(z)$ with: (i) a continuous OT-like interpolation for coordinates with small Gaussian jitter, and (ii) discrete conditional paths for atom and

bond types; charges are predicted but do not participate in the flow. Concretely, at training time

$$x_t \sim \mathcal{N}\big(t\,x_1 + (1-t)\,x_0,\ \sigma^2 I\big), \qquad t \sim \mathrm{Beta}(\alpha, \beta),$$

$$a_t \sim \mathrm{Cat}\Big((1-t)\,\tfrac{1}{|\mathcal{A}|}\,\mathbf{1}_{\mathcal{A}} \ + \ t\,\delta_{a_1}\Big), \qquad b_t \sim \mathrm{Cat}\Big((1-t)\,\tfrac{1}{|\mathcal{B}|}\,\mathbf{1}_{\mathcal{B}} \ + \ t\,\delta_{b_1}\Big),$$

after first aligning (x_0, x_1) by an equivariant OT alignment f_π (permutation + rotation/reflection) (Klein & Noé, 2024; Song et al., 2023) that minimizes squared transport cost. SemlaFlow trains a predictor $p_\theta(z_1 \mid t, z_t)$ of clean data (rather than the vector field directly), and uses it to reconstruct the vector field needed by the ODE sampler. The sampler is Euler with 100 steps and log-spaced. Here $\mathcal{A}$ and $\mathcal{B}$ are the finite sets of atom and bond types, respectively. $\mathbf{1}_{\mathcal{A}} \in \mathbb{R}^{|\mathcal{A}|}$ and $\mathbf{1}_{\mathcal{B}} \in \mathbb{R}^{|\mathcal{B}|}$ denote all-ones vectors (so $\tfrac{1}{|\mathcal{A}|}\mathbf{1}_{\mathcal{A}}$ and $\tfrac{1}{|\mathcal{B}|}\mathbf{1}_{\mathcal{B}}$ are the uniform distributions on $\mathcal{A}$ and $\mathcal{B}$, respectively), and δ denotes the Kronecker delta. $\delta_{a_1}, \delta_{b_1}$ denote one-hot point masses at a_1 and b_1.

SemlaFlow sampling ODE. With the predictor $p_\theta(z_1 \mid t, z_t)$, denote $\tilde{z}_1 = \mathbb{E}[z_1 \mid t, z_t]$. For coordinates the conditional vector field implied by the linear path is

$$u_t(x_t \mid x_1) = \frac{\tilde{x}_1 - x_t}{1-t}, \qquad \text{Euler step:} \quad x_{t+\Delta t} = x_t + \frac{\Delta t}{1-t}\big(\tilde{x}_1 - x_t\big).$$

Following *SemlaFlow* and the *Discrete Flow Models* (DFM) framework—categorical interpolation at train time and Continuous Time Markov Chain (CTMC) sampling at test time—the discrete variables are evolved via

$$a_{t+\Delta t} \sim \mathrm{Cat}\big(\delta_{a_t} + \Delta t\, R_t(a_t, \cdot)\big), \qquad b_{t+\Delta t} \sim \mathrm{Cat}\big(\delta_{b_t} + \Delta t\, R_t(b_t, \cdot)\big). \tag{1}$$

$$R_t(i, j) = \mathbb{E}_{a_1 \sim p_\theta(a_1 \mid t, z_t)}\left[\frac{\delta_{j,a_1}\,(1 - \delta_{i,a_1})}{1-t}\right] \quad \text{for atoms, and analogously with } b_1 \text{ for bonds.} \tag{2}$$

Intuitively, mass flows only toward the denoised label, with a strength that increases as $t \to 1$.

3.2 OUR CONDITIONING MECHANISMS

We now introduce two inference-time conditioning procedures. Both build on SemlaFlow's solver.

Notation.

- Fragment mask $M \in \{0,1\}^N$ indicates atoms belonging to seeding fragments; $\bar{M} = 1 - M$.
- For any tensor y indexed by atoms (or atom pairs), write $y[M]$ and $y[\bar{M}]$ for the masked and unmasked components respectively, and $\mathrm{Replace}_M(y; y^\star)$ for replacing $y[M] \leftarrow y^\star[M]$.
- Let $t_0 = 0 < t_1 < \cdots < t_K = 1$ be the integration grid (log-spaced as in SemlaFlow).

3.2.1 INTERPOLATE-INTEGRATE (SEED-GUIDED RESAMPLING)

Goal. Given a seed molecule $z_1 \sim p_{\mathrm{data}}$, produce a sample $\tilde{z}_1$ that is controllably similar in shape and pharmacophore while allowing global edits.

Key idea. Start in the middle of the probability path at time $\tau \in [0, 1]$: first interpolate from the seed toward noise to obtain z_τ, then integrate the ODE forward from $t = \tau$ to 1. Large τ yields conservative edits; small τ yields diverse rewrites. Optional noise injection at $t = \tau$ decorrelates geometry without discarding the seed entirely.

Construction. Let $z_0 \sim p_0$ and write the SemlaFlow path for $t = \tau$

$$x_\tau = \tau\,x_1 + (1-\tau)\,x_0 + \varepsilon, \qquad \varepsilon \sim \mathcal{N}(0, \sigma_\tau^2 I) \text{ (optional extra jitter)},$$

$$a_\tau \sim \mathrm{Cat}\Big(\tau\,\delta_{a_1} + (1-\tau)\tfrac{1}{|\mathcal{A}|}\mathbf{1}_{\mathcal{A}}\Big), \qquad b_\tau \sim \mathrm{Cat}\Big(\tau\,\delta_{b_1} + (1-\tau)\tfrac{1}{|\mathcal{B}|}\mathbf{1}_{\mathcal{B}}\Big).$$

From $(t, z_t) = (\tau, z_\tau)$, integrate the SemlaFlow ODE using $\tilde{z}_1 = \mathbb{E}[z_1 \mid t, z_t]$ at each step:

$$x_{t_{k+1}} = x_{t_k} + \frac{\Delta t_k}{1 - t_k}\Big(\tilde{x}_1(t_k, z_{t_k}) - x_{t_k}\Big), \qquad k : t_k \in [\tau, 1).$$

Discrete update. Apply the CTMC Euler step (Eqs. equation 1–equation 2):

$$a_{t_{k+1}} \sim \text{Cat}\Big(\delta_{a_{t_k}} + \Delta t_k \, R_{t_k}(a_{t_k}, \cdot)\Big), \qquad b_{t_{k+1}} \sim \text{Cat}\Big(\delta_{b_{t_k}} + \Delta t_k \, R_{t_k}(b_{t_k}, \cdot)\Big), \quad k : t_k \in [\tau, 1).$$

Effect. For $\tau \to 1$, $\tilde{z}_1$ matches z_1 up to small edits; for $\tau \to 0$, sampling reduces to unconditional generation. This 'mid-path restart' is conceptually related to editing techniques in diffusion models that manipulate the reverse sampling process from an intermediate timestep Zeng et al. (2022). However, our application to the deterministic ODE trajectory of a flow-matching model is distinct. To our knowledge, this is the first such interpolate-integrate conditioning scheme for flow-matching model, offering a computationally lightweight yet powerful method for controlled generation. SemlaFlow provides an OT-like linear path and the ODE needed to do so efficiently.

3.2.2 REPLACEMENT GUIDANCE (BIOISOSTERIC FRAGMENT MERGING)

Goal. Use a set of fragments to generate ligands that do not necessarily contain the exact fragment atoms but still preserve key binding interactions. As a complementary approach to the global, soft conditioning of *Interpolate-Integrate*, *Replacement Guidance* provides hard, localized control over a defined set of fragments, allowing for the generation of unconstrained parts of the molecule to merge or complete them.

Key idea. During ODE integration, after each Euler update, we replace the masked fragment region with the original, unperturbed fragment values. This "hard anchoring" maintains exact spatial and chemical identity of fragments throughout the trajectory, while leaving the complement $\bar{M}$ free to evolve. *Relaxation of the constraint is user-controlled:* starting from a chosen time $t_{\text{relax}} \in [0, 1]$ (with the convention that the final step is always free), replacement is disabled for all subsequent steps. More generally, one may specify a relaxation set $\mathcal{T}_{\text{free}} \subseteq \{t_k\}_{k=1}^K$ of steps at which replacement is skipped; the default is $\mathcal{T}_{\text{free}} = \{t_K\}$.

Masked ODE with replacement. Let z_{frag} denote the original fragments to preserve. For each step $t \to t + \Delta t$ with $t + \Delta t \notin \mathcal{T}_{\text{free}}$ (e.g., $t + \Delta t < t_{\text{relax}}$),

$$\text{(i) Euler proposal:} \quad x_{t+\Delta t}^{\text{prop}} = x_t + \frac{\Delta t}{1-t}\Big(\tilde{x}_1(t, z_t) - x_t\Big),$$

$$\text{(ii) Replacement:} \quad x_{t+\Delta t} = \text{Replace}_M\big(x_{t+\Delta t}^{\text{prop}}; \, x_{\text{frag}}\big),$$

$$\text{and analogously} \quad a_{t+\Delta t} = \text{Replace}_M(a_{t+\Delta t}^{\text{prop}}; a_{\text{frag}}), b_{t+\Delta t} = \text{Replace}_{M \otimes M}(b_{t+\Delta t}^{\text{prop}}; b_{\text{frag}}),$$

This yields a projected flow that exactly preserves the fragments up to relaxation time(s) while giving the model freedom to synthesize linkers and local substitutions thereafter, capturing the essence of bioisosteric merges. The novel components of this method are the introduction of the replacement operator and the user-controlled relaxation policy, which together adapt the pre-trained flow for bioisosteric merging.

3.2.3 INFERENCE RUNTIME.

All conditioning operates strictly at inference and preserves the original 100-step Euler integration schedule from *SemlaFlow*. (i) *Interpolate–Integrate* introduces a one-time $O(N)$ seed interpolation prior to integration. (ii) *Replacement Guidance* adds only a lightweight $O(N)$ masked tensor update per step, negligible relative to a model forward pass. Overall, both methods maintain inference efficiency comparable to the unconditioned baseline.

4 EXPERIMENTS

We demonstrate the effectiveness of our conditioning strategies on three challenging, drug-relevant tasks: natural product ligand hopping, bioisosteric fragment merging, and pharmacophore merging. Figure 4.1 provides a visual overview of the conditioning setups and showcases representative top-ranked molecules for each task, selected by a medicinal chemist after filtering. We evaluate all generated molecules on a suite of metrics designed to assess their validity, synthetic accessibility, and 3D similarity to reference compounds.

4.1 EVALUATION METRICS

We evaluate generated molecules on synthetic accessibility (SA) using the score from Ertl & Schuffenhauer (2009), where lower values are better. For validity, molecules must be parsable by RDKit and pass PoseBusters plausibility checks (Buttenschoen et al., 2023). We combine these to define a Success Rate: the percentage of initial samples that pass both validity and SA score filters. We also compute 3D similarity to a reference molecule by comparing surface, electrostatic, and pharmacophore features, following the protocol of Adams et al. (2025). Finally, we calculate an AutoDock Vina docking score (Eberhardt et al., 2021), using energy minimization for conditionally-generated poses to ensure robustness (Weller & Rohs, 2024).

Figure 1: Overview of the three drug-relevant tasks, with top-ranked molecules selected by a medicinal chemist from our conditioning strategies *Interpolate–Integrate* and *Replacement Guidance*. **Left:** The natural product ligand hopping task. The goal is to generate analogues withm-lower SA scores while preserving the key features of the original natural product (leftmost column). **Right (Top):** The bioisosteric fragment merging task is demonstrated on EV-D68 3C protease using three different conditioning setups (multi-fragment, random atom seeding, and manual extraction) to generate a single coherent molecule from multiple inputs. All molecules shown are filtered for SA < 4.0. **Right (Bottom):** The **pharmacophore merging** task on SARS-CoV-2 M_{pro}, involves generating a novel ligand that combines the interaction patterns from a diverse set of known fragments. All molecules shown are filtered for SA < 4.5. Created in https://BioRender.com.

4.2 NATURAL PRODUCT LIGAND HOPPING

Natural products are complex and diverse substances produced by organisms such as plants, microbes, and marine life. Their rich structural variety and biological relevance make them valuable starting points for small molecule drug discovery (Morrison & Hergenrother, 2014). However, their inherent complexity and limited synthetic tractability often hinder the development of analogues and optimization for drug-like properties (Lee & Schneider, 2001). Ligand hopping offers a strategy for generating novel compounds that retain the biological activity of known natural products while exploring more synthetically accessible chemical space.

We follow the SHEPHERD framework (Adams et al., 2025) using three structurally diverse natural products (NP1, NP2, NP3) from the COCONUT database (Sorokina et al., 2021), aiming to generate

analogues with SA scores below 4.5. We generated 2,500 candidate analogues with both *Interpolate–Integrate* and *Replacement Guidance*, conditioning on key pharmacophoric features from each reference NP. We compare our results against two baselines: MolSnapper, in a ligand-only mode, conditioned on the NP's pharmacophore points, and SHEPHERD, conditioned on its ESP and pharmacophore profiles. Further details on the generation parameters and post-processing are available in Appendix D.

Table 1: Performance summary for the NP hopping tasks. The table reports overall PoseBusters validity, the average SA score, the percentage of initial samples passing both validity and an SA score ≤ 4.5 filter (Success Rate), and top-10 similarity scores (ESP and pharmacophore) are calculated only on these successful candidates.

NP	Method	Valid ↑	SA Score ↓	Success Rate ↑	ESP sim (top 10) ↑	Pharma sim (top 10) ↑
NP1	MolSnapper	26.24%	6.43 ± 0.78	0.32%	0.51 ± 0.02	0.16 ± 0.02
	ShEPhERD	57.3%	4.75 ± 0.89	24.7%	0.63 ± 0.02	0.34 ± 0.03
	Interpolate–integrate	**71.5%**	4.67 ± 1.02	35.6%	$\mathbf{0.81 \pm 0.02}$	0.49 ± 0.06
	Replacement–guidance	60.5%	$\mathbf{3.74 \pm 1.01}$	**50.2%**	$\mathbf{0.81 \pm 0.02}$	$\mathbf{0.52 \pm 0.06}$
NP2	MolSnapper	19.88%	6.84 ± 0.79	0.16%	0.63 ± 0.02	0.19 ± 0.01
	ShEPhERD	51.0%	5.09 ± 1.2	17.4%	0.79 ± 0.01	0.34 ± 0.02
	Interpolate–integrate	**93.6%**	5.41 ± 1.03	16.0%	$\mathbf{0.86 \pm 0.01}$	$\mathbf{0.46 \pm 0.02}$
	Replacement–guidance	87.9%	$\mathbf{4.43 \pm 1.31}$	**48.8%**	0.85 ± 0.01	0.44 ± 0.04
NP3	MolSnapper	14.20%	6.32 ± 0.85	0.32%	0.46 ± 0.02	0.14 ± 0.01
	ShEPhERD	44.1%	4.69 ± 0.96	20.2%	0.60 ± 0.01	$\mathbf{0.30 \pm 0.02}$
	Interpolate–integrate	62.7%	5.92 ± 1.03	5.2%	0.56 ± 0.05	0.20 ± 0.03
	Replacement–guidance	**64.4%**	$\mathbf{4.07 \pm 1.27}$	**42.1%**	$\mathbf{0.65 \pm 0.03}$	0.29 ± 0.02

Our results (Table 1) demonstrate that our two conditioning strategies have distinct strengths, making them suitable for different design goals. *Replacement-guidance* consistently achieves the highest success rate of SA-compliant analogues—often more than doubling the rate of the ShEPhERD baseline—while also generating molecules with the most favorable SA scores across all three targets. In contrast, *Interpolate-integrate* is effective for high-fidelity generation. While its yield of SA-compliant molecules is lower in this task, the candidates it produces tend to show high similarity to the reference seed in both ESP and pharmacophore space. This focus on conservative edits, reflected in its lower overall diversity, suggests its utility as a tool for scenarios where preserving precise interaction patterns is the primary objective. Notably, the MolSnapper baseline struggled significantly on this task, achieving a success rate below 1%. As discussed in Appendix D, this suggests its mechanism of conditioning on discrete points is overly restrictive for the dense pharmacophore profiles of large natural products.

4.3 BIOISOSTERIC FRAGMENT MERGING.

Fragment-based screening identifies small molecules that bind to distinct regions of a target protein. Traditionally, these fragment hits are grown or linked to form larger ligands that retain the original fragments explicitly. However, recent work by (Wills et al., 2024) introduced a bioisosteric merging strategy, which aims to generate ligands that do not necessarily contain the exact fragment atoms while preserving key binding interactions. This approach enables greater chemical diversity while maintaining pharmacophoric fidelity.

Building on this framework, we perform bioisosteric merging on the EV-D68 3C protease system, using data from the Fragalysis platform[1]. Our input consists of 13 experimentally resolved fragment-bound structures, previously curated for the SHEPHERD study (Adams et al., 2025). We evaluate our methods across the following three conditioning setups (shown in Figure 4.1), which are designed to assess performance in both automated and expert-driven scenarios: **Multi-fragment Reference (Automated)**, where a composite input is formed by combining three known fragment-bound ligands; **Random Atom Seeding (Automated):** A sparse set of pharmacophore features is randomly sampled from the full fragment ensemble. This provides an automated way to leverage collective information from the raw fragment data without the need for manual expert curation; and **Full Interaction Profile (Manually Curated)**, a comprehensive 27-feature set curated for the SHEPHERD study that serves as an ideal but labor-intensive baseline (Adams et al., 2025).

---

[1] https://fragalysis.diamond.ac.uk/viewer/react/landing

Our goal is to evaluate how effectively the automated conditioning strategies can approach the performance of the manually curated profile, which represents a key challenge for real-world application.

Following the SHEPHERD study protocol, we generated 1,000 candidates per setup and applied a similar post-processing pipeline (see Appendix E.1 for full details). Since the input fragment poses contain implicit information about the target's binding pocket, a primary goal was to assess in-pocket fit. To do this, we filtered candidates for PoseBusters validity and a favorable SA score (SA $\leq$ 4.0, as used in SHEPHERD study). Only the successful candidates were then assessed using `AutoDock Vina`. We compare our results against several baselines: protein-aware (`clash-rate=0.1`) and protein-blind versions of MolSnapper, DiffSBDD, and SHEPHERD. A direct comparison across all methods is only possible on the manually curated 'Full Interaction Profile', as the baseline methods are not designed to handle the flexible inputs of our automated setups require a single, well-defined conditioning profile. Detailed setups for all methods and an analysis of unfiltered results can be found in Appendix E.3.

Table 2: Performance summary for the EV-D68 3C bioisosteric merging task across three conditioning setups. The table reports overall PoseBusters validity, the average SA score, the percentage of initial samples passing both validity and an SA score ≤ 4 filter (Success Rate), the fraction of successful molecules with zero clashes (No clash), and the top-10 Vina docking score.

Conditioning setup	Method	Valid ↑	SA Score ↓	Success Rate ↑	No clash ↑	Vina top10 ↓
Multi-fragment ref.	Interpolate–integrate	**59.3%**	4.65 ± 0.96	14.8%	12.1%	-5.30 ± 0.49
	Replacement–guidance	36.3%	3.57 ± 0.85	**25.0%**	**19.3%**	-5.59 ± 0.21
Random atom seeding	Interpolate–integrate	41.0%	5.18 ± 1.17	6.8%	5.3%	-4.73 ± 0.24
	Replacement–guidance	28.1%	3.84 ± 0.81	17.0%	13.5%	-5.78 ± 0.26
Full interaction profile	Interpolate–integrate	38.1%	4.83 ± 1.17	8.7%	7.0%	-4.84 ± 0.58
	Replacement–guidance	31.9%	$\mathbf{3.47 \pm 0.70}$	23.5%	18.7%	$\mathbf{-6.62 \pm 0.42}$

Table 3: Performance summary for the EV-D68 3C bioisosteric merging task (ShEPhERD profile setup). The table reports overall PoseBusters validity, the average SA score, the percentage of initial samples passing both validity and an SA score < 4 filter (Success Rate), the fraction of successful molecules with zero clashes (No clash), and the top-10 Vina docking score.

Target	Method	Valid ↑	SA Score ↓	Success Rate ↑	No clash ↑	Vina top10 ↓
EV-D68 3C	MolSnapper (ligand-based)	17.6%	7.04 ± 0.54	0%	—	—
	MolSnapper (clash-rate = 0.1)	14.5%	6.91 ± 0.53	0%	—	—
	DiffSBDD (largest frag)	**43.1%**	6.91 ± 0.53	0%	—	—
	ShEPhERD	33.8%	4.45 ± 0.99	10.8%	10.1%	-6.16 ± 0.50
	Interpolate–integrate	39.5%	4.96 ± 1.17	8.7%	7.0%	-4.84 ± 0.58
	Replacement–guidance	31.9%	$\mathbf{3.47 \pm 0.70}$	**23.5%**	**18.7%**	$\mathbf{-6.62 \pm 0.42}$

A comparison of the three conditioning setups in Table 2 reveals the trade-offs between automated and manually curated approaches. While the manually curated *'Full Interaction Profile'* was most effective at generating candidates with the highest predicted binding affinity (top-10 Vina score of -6.62), *'Multi-fragment reference'* setup produced the highest overall success rate of valid candidates (25.0%). The *'Random atom seeding'*, representing a more challenging scenario, resulted in a lower yield but still produced potent candidates (top-10 Vina score of -5.78). This highlights the robustness of our framework, demonstrating its ability to generate high-quality candidates across a range of conditioning scenarios from fully automated to expert-curated ('Full Interaction Profile').

When conditioned on the full, manually curated interaction profile, our Replacement-guidance method demonstrates advantages over the baselines. The results highlight that the conditioning mechanisms of DiffSBDD and MolSnapper—which are designed to strictly satisfy a set of discrete constraints—are less suited for this flexible bioisosteric merging task. Specifically, neither of these two baselines produced any candidates that passed the SA score filter; DiffSBDD failed to generate fully connected molecules, and both struggled with the accessibility constraint. *Replacement-guidance* outperforms the specialized SHEPHERD baseline (Table 3) with a more than two-fold

higher success rate (23.5% vs. 10.8%), an improved SA score (3.47 vs. 4.45), and a superior top-10 Vina score (-6.62 vs. -6.16).

4.4 PHARMACOPHORE-MERGING ON SARS-CoV-2 M$_{\text{PRO}}$

Fragment screening on the SARS-CoV-2 main protease (M$_{\text{pro}}$) provides a real-world test case. The Diamond/XChem campaign rapidly yielded a dense constellation of binding motifs, explicitly encouraging the merging of these fragment hits into more potent ligands[2]. From public Fragalysis data, we curated a conditioning set of 81 small fragments and a baseline set of 1,426 known binders, with the goal of merging pharmacophoric motifs from the fragments into novel ligands.

We generated 2,500 candidate molecules per method, using the 'random atom seeding' setup (Section 4.3). To identify promising candidates, we filtered all molecules for PoseBusters validity and a favorable SA score before evaluating them against baseline binders with AutoDock Vina (see Appendix F for the detailed setup). While we acknowledge the limitations of this high-throughput pipeline, such as docking to a single rigid receptor, it serves as a standard computational funnel to identify a manageable set of promising candidates from a large generative run.

The results, summarized in Table 4, demonstrate that our methods can successfully merge pharmacophoric motifs from a large set of small fragments into novel, synthetically feasible ligands. While the predicted binding affinities of our de novo candidates do not yet match the potency of the larger, established binders, these results show that our approach can generate molecules that serve as competitive starting points for a drug discovery campaign.

Table 4: Performance summary for the SARS-CoV-2 Mpro pharmacophore-merging task. The table reports overall PoseBusters validity, the average SA score, the percentage of initial samples passing both validity and an SA score filter (Success Rate), the fraction of successful molecules with zero clashes (No clash), and the top-10 Vina docking score.

Target	Method	Valid ↑	SA Score ↓	Success Rate ↑	No clash ↑	Vina top10 ↓
SARS-CoV-2 M$_{\text{pro}}$	Interpolate–integrate	41.0%	4.49 ± 1.20	23.5%	**15.4%**	-6.48 ± 0.24
	Replacement–guidance	32.2%	$\mathbf{3.61 \pm 0.90}$	**27.3%**	12.4%	$\mathbf{-7.63 \pm 0.42}$
	Known Binders	100%	3.70 ± 0.97	80.1%	67.5%	-9.95 ± 0.07

4.5 INFERENCE RUNTIME.

On a single RTX 6000 GPU, generating a batch of 10 takes 2.85 s with *Interpolate–Integrate* ($\tau = 0.75$) and 3.9 s with *Replacement Guidance*, measured on 50-atom molecules. CPU runtimes are 28.3 s and 38.5 s per sample (batch size 10). Batching improves efficiency but currently supports only identical input seeds per batch. In contrast, SHEPHERD requires approximately 3–4 minutes to generate a batch of 10 samples with 400 denoising steps on a single V100 GPU, or 5–10 minutes per sample on CPU (Adams et al., 2025).

5 CONCLUSION

We have introduced two *training-free*, inference-time conditioning strategies—*Interpolate–Integrate* and *Replacement Guidance*—that operate on top of the fast *SemlaFlow* model for ligand-only, bioisosteric design. Both methods require no retraining and can steer 3D molecular generation to satisfy interaction-level constraints such as shape and pharmacophore overlap. We demonstrate their effectiveness across three tasks: natural product ligand hopping, bioisosteric fragment merging, and pharmacophore merging, showing that they generate synthetically accessible molecules that match key reference features. Unlike prior methods that rely on explicit retraining or task-specific encoders, our framework preserves sampling efficiency and generalizes across tasks and conditioning modes. These results establish inference-time conditioning as a powerful and scalable strategy for goal-directed molecular design, whose modularity makes it readily extendable to new scientific domains such as protein design and materials discovery.

---

[2] https://fragalysis.diamond.ac.uk/viewer/react/preview/target/CoV-Mpro/tas/lb32627-272

ACKNOWLEDGEMENTS

We thank the authors of the SHEPHERD paper for their support, assistance with the experimental setups, and for guidance on code usage. The authors also thank Leo Klarner and Lucy Vost from the Oxford Protein Informatics Group for their helpful comments. This work was supported by the Centre of Artificial Intelligence in Precision Medicines (CAIPM), King Abdulaziz University, Jeddah, Saudi Arabia.

REFERENCES

Chayan Acharya, Andrew Coop, James E. Polli, and Alexander D. MacKerell. Recent Advances in Ligand-Based Drug Design: Relevance and Utility of the Conformationally Sampled Pharmacophore Approach. *Current Computer-Aided Drug Design*, 7(1):10–22. doi: 10.2174/157340911793743547. URL `https://www.eurekaselect.com/article/17929`.

Keir Adams and Connor W. Coley. Equivariant shape-conditioned generation of 3D molecules for ligand-based drug design. In *The Eleventh International Conference on Learning Representations*, 2023.

Keir Adams, Kento Abeywardane, Jenna C Fromer, and Connor W Coley. Shepherd: Diffusing shape, electrostatics, and pharmacophores for bioisosteric drug design. In *ICLR*, 2025.

Simon Axelrod and Rafael Gómez-Bombarelli. GEOM, energy-annotated molecular conformations for property prediction and molecular generation. *Scientific Data*, 9(1):185, 2022.

Benoit Baillif, Jason Cole, Patrick McCabe, and Andreas Bender. Deep generative models for 3d molecular structure. *Current Opinion in Structural Biology*, 80:102566, 2023.

Martin Buttenschoen, Garrett M. Morris, and Charlotte M. Deane. PoseBusters: AI-based docking methods fail to generate physically valid poses or generalise to novel sequences. *Chemical Science*, 2023.

Martin Buttenschoen, Yael Ziv, Garrett M Morris, and Charlotte M Deane. An evaluation of unconditional 3d molecular generation methods. *arXiv preprint arXiv:2505.00518*, 2025.

Andrew Campbell, Jason Yim, Regina Barzilay, Tom Rainforth, and Tommi Jaakkola. Generative flows on discrete state-spaces: Enabling multimodal flows with applications to protein co-design. *arXiv preprint arXiv:2402.04997*, 2024.

Ziqi Chen, Bo Peng, Srinivasan Parthasarathy, and Xia Ning. Shape-conditioned 3D molecule generation via equivariant diffusion models. In *NeurIPS 2023 Generative AI and Biology (GenBio) Workshop*, 2023.

Connor W Coley, Luke Rogers, William H Green, and Klavs F Jensen. Scscore: synthetic complexity learned from a reaction corpus. *Journal of Chemical Information and Modeling*, 58(2):252–261, 2018.

Julian Cremer, Tuan Le, Frank Noé, Djork-Arné Clevert, and Kristof T Schütt. Pilot: equivariant diffusion for pocket-conditioned de novo ligand generation with multi-objective guidance via importance sampling. *Chemical Science*, 15(36):14954–14967, 2024.

Ian Dunn and David Ryan Koes. Mixed continuous and categorical flow matching for 3D de novo molecule generation, 2024.

Jerome Eberhardt, Diogo Santos-Martins, Andreas F Tillack, and Stefano Forli. Autodock vina 1.2. 0: new docking methods, expanded force field, and python bindings. *Journal of chemical information and modeling*, 61(8):3891–3898, 2021.

Daniel A Erlanson, Robert S McDowell, and Tom O'Brien. Fragment-based drug discovery. *Journal of medicinal chemistry*, 47(14):3463–3482, 2004.

Peter Ertl and Ansgar Schuffenhauer. Estimation of synthetic accessibility score of drug-like molecules based on molecular complexity and fragment contributions. *Journal of cheminformatics*, 1(1):8, 2009.

Jiaqi Guan, Xingang Peng, PeiQi Jiang, Yunan Luo, Jian Peng, and Jianzhu Ma. Linkernet: Fragment poses and linker co-design with 3d equivariant diffusion. *Advances in Neural Information Processing Systems*, 36:77503–77519, 2023.

Emiel Hoogeboom, Vıctor Garcia Satorras, Clément Vignac, and Max Welling. Equivariant diffusion for molecule generation in 3d. In *International conference on machine learning*, pp. 8867–8887. PMLR, 2022.

Ilia Igashov, Hannes Stärk, Clément Vignac, Arne Schneuing, Victor Garcia Satorras, Pascal Frossard, Max Welling, Michael Bronstein, and Bruno Correia. Equivariant 3d-conditional diffusion model for molecular linker design. *Nature Machine Intelligence*, 6(4):417–427, 2024.

Fergus Imrie, Thomas E. Hadfield, Anthony R. Bradley, and Charlotte M. Deane. Deep generative design with 3D pharmacophoric constraints. *Chemical Science*, 12(43):14577–14589, 2021a.

Fergus Imrie, Thomas E Hadfield, Anthony R Bradley, and Charlotte M Deane. Deep generative design with 3d pharmacophoric constraints. *Chemical science*, 12(43):14577–14589, 2021b.

Ross Irwin, Alessandro Tibo, Jon Paul Janet, and Simon Olsson. Semlaflow–efficient 3d molecular generation with latent attention and equivariant flow matching. *arXiv preprint arXiv:2406.07266*, 2024.

Leon Klein and Frank Noé. Transferable boltzmann generators. *Advances in Neural Information Processing Systems*, 37:45281–45314, 2024.

Gregory A Landrum, Julie E Penzotti, and Santosh Putta. Feature-map vectors: a new class of informative descriptors for computational drug discovery. *Journal of Computer-Aided Molecular Design*, 20:751–762, 2006.

Tuan Le, Julian Cremer, Frank Noe, Djork-Arné Clevert, and Kristof T Schütt. Navigating the design space of equivariant diffusion-based generative models for de novo 3D molecule generation. In *The Twelfth International Conference on Learning Representations*, 2024.

Man-Ling Lee and Gisbert Schneider. Scaffold architecture and pharmacophoric properties of natural products and trade drugs: application in the design of natural product-based combinatorial libraries. *Journal of combinatorial chemistry*, 3(3):284–289, 2001.

Yaron Lipman, Ricky TQ Chen, Heli Ben-Hamu, Maximilian Nickel, and Matt Le. Flow matching for generative modeling. *arXiv preprint arXiv:2210.02747*, 2022.

Andreas Lugmayr, Martin Danelljan, Andres Romero, Fisher Yu, Radu Timofte, and Luc Van Gool. Repaint: Inpainting using denoising diffusion probabilistic models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 11461–11471, 2022.

Chenlin Meng, Yutong He, Yang Song, Jiaming Song, Jiajun Wu, Jun-Yan Zhu, and Stefano Ermon. SDEdit: Guided image synthesis and editing with stochastic differential equations. In *International Conference on Learning Representations*, 2022.

Alex Morehead and Jianlin Cheng. Geometry-complete diffusion for 3D molecule generation and optimization. *Communications Chemistry*, 7(1):150, 2024.

Harry L Morgan. The generation of a unique machine description for chemical structures-a technique developed at chemical abstracts service. *Journal of chemical documentation*, 5(2):107–113, 1965.

Karen C Morrison and Paul J Hergenrother. Natural products as starting points for the synthesis of complex and diverse compounds. *Natural product reports*, 31(1):6–14, 2014.

Marcus Olivecrona, Thomas Blaschke, Ola Engkvist, and Hongming Chen. Molecular de-novo design through deep reinforcement learning. *Journal of Cheminformatics*, 9(1):48, 2017.

OpenBind Consortium. OpenBind: Large-scale structural fragment initiative. `https://openbind.org`, 2025. accessed 2025-05-23.

Ferruccio Palazzesi and Alfonso Pozzan. Deep Learning Applied to Ligand-Based De Novo Drug DesignDe novo drug design. In Alexander Heifetz (ed.), *Artificial Intelligence in Drug Design*, pp. 273–299. Springer US, New York, NY, 2022. ISBN 978-1-07-161787-8. doi: 10.1007/978-1-0716-1787-8_12. URL `https://doi.org/10.1007/978-1-0716-1787-8_12`.

Daniil Polykovskiy, Alexander Zhebrak, Benjamin Sanchez-Lengeling, Sergey Golovanov, Oktai Tatanov, Stanislav Belyaev, Rauf Kurbanov, Aleksey Artamonov, Vladimir Aladinskiy, Mark Veselov, et al. Molecular sets (moses): a benchmarking platform for molecular generation models. *Frontiers in pharmacology*, 11:565644, 2020.

Santosh Putta, Gregory A Landrum, and Julie E Penzotti. Conformation mining: an algorithm for finding biologically relevant conformations. *Journal of Medicinal Chemistry*, 48(9):3313–3318, 2005.

Nicholas T Runcie and Antonia SJS Mey. Silvr: guided diffusion for molecule generation. *Journal of chemical information and modeling*, 63(19):5996–6005, 2023.

Arne Schneuing, Charles Harris, Yuanqi Du, Kieran Didi, Arian Jamasb, Ilia Igashov, Weitao Du, Carla Gomes, Tom L Blundell, Pietro Lio, et al. Structure-based drug design with equivariant diffusion models. *Nature Computational Science*, 4(12):899–909, 2024.

Vidushi Sharma, Sharad Wakode, and Hirdesh Kumar. Chapter 2 - Structure- and ligand-based drug design: concepts, approaches, and challenges. In Navneet Sharma, Himanshu Ojha, Pawan Kumar Raghav, and Ramesh k. Goyal (eds.), *Chemoinformatics and Bioinformatics in the Pharmaceutical Sciences*, pp. 27–53. Academic Press, January 2021. ISBN 978-0-12-821748-1. doi: 10.1016/B978-0-12-821748-1.00004-X. URL `https://www.sciencedirect.com/science/article/pii/B978012821748100004X`.

Miha Skalic, José Jiménez, Davide Sabbadin, and Gianni De Fabritiis. Shape-based generative modeling for de novo drug design. *Journal of Chemical Information and Modeling*, 59(3):1205–1214, 2019.

Yuxuan Song, Jingjing Gong, Minkai Xu, Ziyao Cao, Yanyan Lan, Stefano Ermon, Hao Zhou, and Wei-Ying Ma. Equivariant flow matching with hybrid probability transport for 3d molecule generation. *Advances in Neural Information Processing Systems*, 36:549–568, 2023.

Maria Sorokina, Peter Merseburger, Kohulan Rajan, Mehmet Aziz Yirik, and Christoph Steinbeck. Coconut online: collection of open natural products database. *Journal of Cheminformatics*, 13 (1):2, 2021.

Amol Thakkar, Veronika Chadimová, Esben Jannik Bjerrum, Ola Engkvist, and Jean-Louis Reymond. Retrosynthetic accessibility score (rascore) – rapid machine learned synthesizability classification from ai driven retrosynthetic planning. *Chem. Sci.*, 12:3339–3349, 2021.

Jesse A Weller and Remo Rohs. Structure-based drug design with a deep hierarchical generative model. *Journal of Chemical Information and Modeling*, 64(16):6450–6463, 2024.

Stephanie Wills, Ruben Sanchez-Garcia, Stephen D. Roughley, Andy Merritt, Roderick E. Hubbard, Frank Von Delft, and Charlotte M. Deane. Expanding the scope of a catalogue search to bioisosteric fragment merges using a graph database approach, 2024.

Minkai Xu, Alexander Powers, Ron Dror, Stefano Ermon, and Jure Leskovec. Geometric latent diffusion models for 3D molecule generation. In *IMCL 2023*, 2023.

Kiwoong Yoo, Owen Oertell, Junhyun Lee, Sanghoon Lee, and Jaewoo Kang. Turbohopp: accelerated molecule scaffold hopping with consistency models. *Advances in Neural Information Processing Systems*, 37:41157–41185, 2024.

Xiaohui Zeng, Arash Vahdat, Francis Williams, Zan Gojcic, Or Litany, Sanja Fidler, and Karsten Kreis. LION: Latent point diffusion models for 3D shape generation. In *Advances in Neural Information Processing Systems*, volume 35, pp. 10021–10039, 2022.

Wonho Zhung, Hyeongwoo Kim, and Woo Youn Kim. 3D molecular generative framework for interaction-guided drug design. *Nature Communications*, 15(1):2688, March 2024. ISSN 2041-1723. doi: 10.1038/s41467-024-47011-2. URL `https://www.nature.com/articles/s41467-024-47011-2`. Publisher: Nature Publishing Group.

Yael Ziv, Fergus Imrie, Brian Marsden, and Charlotte M Deane. Molsnapper: conditioning diffusion for structure-based drug design. *Journal of Chemical Information and Modeling*, 65(9):4263–4273, 2025.

A   APPENDIX OVERVIEW

This appendix contains material that supports and extends the main text.

- B: Ablation studies on inference-time conditioning parameters
  - B.1: Interpolate–Integrate ablations
  - B.2: Replacement Guidance ablations
- D: Extended results for natural product hopping
- E: Detailed evaluation of bioisosteric fragment merging
- F: Extended evaluation of pharmacophore-merging on SARS-CoV-2 M_{pro}

B   ABLATION: CONDITIONING PARAMETERS

We quantify how the principal inference-time hyper-parameters of the two conditioning schemes Interpolate–Integrate and Replacement Guidance, affect validity, diversity, and similarity.

Validity, uniqueness, and novelty.   *Validity* refers to passing all PoseBusters (Buttenschoen et al., 2023) intramolecular checks. *Uniqueness* and *novelty* are computed on canonical SMILES obtained via `RDKit MolToSmiles`. A generated molecule is *novel* if its SMILES is different from the seed molecule, and *unique* within a batch if its SMILES appears exactly once.

Similarity metrics.   *Shape and color similarity score (SC_{RDKit}):* assesses the 3D similarity between generated molecules and a reference molecule, as described in Imrie et al. 2021b. SC_{RDKit} scores range from 0 (no match) to 1 (perfect match). The color similarity function evaluates the overlap of pharmacophoric features, while the shape similarity measure involves a simple volumetric comparison between the two conformers. SC_{RDKit} uses two RDKit functions, based on the methods described in Putta et al. 2005 and Landrum et al. 2006.
ECFP4 Tanimoto is the Tanimoto coefficient between 2 048-bit Morgan fingerprints (Morgan, 1965) (radius 2) generated with `RDKit GetMorganFingerprintAsBitVect`—a standard measure of 2-D scaffold similarity.

B.1   INTERPOLATE–INTEGRATE

We analyze the effect of varying the restart time $\tau = t$ and the seed noise scale σ. All experiments use the first 1,000 molecules from the GEOM-Drugs (Axelrod & Gómez-Bombarelli, 2022) test set as reference seeds.

B.1.1   EFFECT OF TIME τ

In all ablation experiments, we use the 100-step, log-spaced ODE grid from SEMLAFLOW. In Interpolate–Integrate, the restart time τ is set by choosing a step index s in this grid; τ is simply the s-th value in the solver's precomputed log-spaced time schedule. Table 5 lists the restart step s (index in the log-spaced 100-step grid) and the corresponding continuous time τ.

Table 5: Mapping between restart steps in the log-spaced ODE grid and the corresponding continuous time τ used in Interpolate–Integrate.

Restart steps	τ (continuous time)
70	0.75
72	0.72
74	0.70
76	0.69
78	0.64
80	0.60

We restart the flow at six grid positions ($s \in [70, 80] \rightarrow \tau \in [0.75, 0.6]$). Larger τ (late restarts) preserves more of the seed; smaller τ yields greater novelty at the cost of similarity. Unless otherwise stated, the seed-noise scale is fixed to $\sigma = 0.1$.

Table 6: Validity of generated molecules conditioned on a reference at noise level $\sigma = 0.1$. Each row reports the number of molecules attempted and the percentage that were generated, connected, chemically valid, physically valid, and overall valid. A molecule is considered fully valid only if it passes all three criteria: connectedness, chemical validity, and physical validity.

s	% Generated	% connectedness	% chemical	% physical	% Valid
0.70	95.8	95.3	95.8	89.5	89.0
0.72	94.0	92.8	94.0	87.4	86.3
0.74	91.6	89.0	91.5	85.4	83.1
0.76	90.0	86.7	90.0	84.7	81.6
0.78	90.6	87.0	90.6	86.2	82.8
0.80	91.5	88.0	91.5	87.8	84.4

Table 7: Validity, uniqueness, and novelty of generated molecules conditioned on a reference molecule at noise level $\sigma = 0.10$. Values are reported as proportions of the total number of molecules that were to be generated.

s	Valid	Valid & Novel	Valid & Unique	Valid & Unique & Novel
0.70	89.05	85.18	20.63	20.36
0.72	86.31	83.38	39.03	38.74
0.74	83.08	81.41	61.99	61.70
0.76	81.56	80.88	76.38	76.12
0.78	82.78	82.57	82.13	81.97
0.80	84.45	84.34	84.37	84.24

The choice of the restart time, τ, reveals a clear trade-off between novelty and fidelity. Lower values of τ produce more novel and unique molecules, while higher values improve chemical validity and 3D similarity (SC_{RDKit}) to the seed molecule. These trends are detailed in Tables 6 and 7 and visualized in Figure 3.

(a) Distribution of SC_{RDKit} between the generated and reference molecules.

(b) Cumulative distribution of ECFP4 Tanimoto similarity. A sharper jump near 1.0 indicates more identical fingerprints.

Figure 2: Chemical and shape/pharmacophoric similarity between generated and reference molecules, measured by ECFP4 Tanimoto similarity and SC_{RDKit}, respectively. Curves are shown for different integration step counts at fixed noise level $\sigma = 0.1$. Only valid molecules are included.

B.1.2 EFFECT OF NOISE LEVEL σ

We fix $s = 0.72$ and vary the noise σ added to the interpolated seed. Higher σ injects more coordinate noise at the restart point.

Table 8: Validity of generated molecules conditioned on a reference molecule for restart step $s = 0.72$, across different noise levels σ. Each row reports the total number of molecules attempted and the percentage that were generated, connected, chemically valid, physically valid, and overall valid. A molecule is considered valid only if it meets all three criteria.

s	σ	Total	% Gen.	% Conn.	% Chem.	% Phys.	% Valid
	0.00	94956	95.0	94.2	94.9	88.5	87.8
	0.05	94765	94.8	93.9	94.8	88.1	87.3
	0.10	94019	94.0	92.8	94.0	87.4	86.3
0.72	0.15	92807	92.8	91.0	92.8	86.4	84.7
	0.20	91043	91.0	88.4	91.0	84.7	82.2
	0.25	89617	89.6	86.0	89.6	83.5	80.2

Table 9: Validity, uniqueness, and novelty of generated molecules conditioned on a reference molecule for $s = 0.72$, across varying noise levels σ. Values are reported as proportions of the total number of molecules that were to be generated.

s	σ	Valid	Valid & Novel	Valid & Unique	Valid & Unique & Novel
	0.00	87.83	84.42	30.80	30.52
	0.05	87.35	84.04	32.73	32.45
	0.10	86.31	83.38	39.03	38.74
0.72	0.15	84.69	82.31	49.57	49.26
	0.20	82.16	80.50	60.45	60.16
	0.25	80.18	79.23	69.52	69.26

Tables 8 and 9 show a clear trade-off: higher σ values increase novelty but reduce validity. This suggests σ should be tuned for each application based on desired diversity.

(a) Distribution of SC_{RDKit} between the generated and reference molecules.

(b) Cumulative distribution of ECFP4 Tanimoto similarity. A sharper jump near 1.0 indicates more identical fingerprints.

Figure 3: Chemical and shape/pharmacophoric similarity between generated and reference molecules across different noise levels σ in Interpolate–Integrate. We report SC_{RDKit} (a) and ECFP4 Tanimoto similarity (b), computed only for valid molecules. Curves are shown for different σ levels.

B.2 REPLACEMENT GUIDANCE

We investigate the effect of the relaxation time t_{free} in Replacement Guidance, where t_{free} denotes the integration step after which fragment masking is disabled. We also compare this strategy against an inpainting-based conditioning approach.

Experiments are conducted on the DIFFLINKER test set (Igashov et al., 2024), using a curated subset of 1,129 cases in which the objective is to generate a molecule that preserves the shape and pharmacophoric features of three bound fragments.

B.3 EFFECT OF TIME t_{FREE}

The relaxation time, t_{free}, directly affects the properties of the generated molecules, as shown in Table 10. Increasing t_{free}—which holds the fragment constraints for a longer duration—consistently improves the 3D similarity (SC_{RDKit}) to the reference fragments. Conversely, this stronger anchoring can negatively impact PoseBusters' validity across all metrics.

Table 10: Effect of relaxation time t_{free} in Replacement Guidance. We report the proportion of molecules that are successfully generated, pass all chemical and physical PoseBusters' validity checks, meet the full validity criteria, and the SC_{RDKit}. Larger t_{free} allows fragment replacement for more steps, leading to greater flexibility but weaker fragment anchoring.

t_{free}	% Generated	% Chemical	% Physical	% Valid	SC_{RDKit}
0.85	87.7	78.5	80.8	72.7	0.39 ± 0.08
0.90	88.4	79.3	80.9	73.1	0.40 ± 0.08
0.95	87.4	78.5	80.1	72.3	0.41 ± 0.08
1.00	85.2	75.8	76.2	68.3	0.43 ± 0.08

B.3.1 COMPARISON TO INPAINTING-BASED CONDITIONING

In this section, we compare our Replacement Guidance strategy to an inpainting-based approach. We evaluate the validity of generated molecules across four inpainting configurations: (1) inpainting only coordinates, (2) inpainting only atom types, (3) inpainting only bonds — in each case applying hard conditioning to the remaining components — and (4) inpainting all components simultaneously.

Table 11: Validity comparison between inpainting configurations and Replacement Guidance ($t_{\text{free}} = 1.0$) on the DIFFLINKER test subset (1,129 cases). We report the percentage of molecules that are successfully generated, chemically valid, physically valid, and valid overall (i.e., passing all checks).

Method	% Generated	% Chemical	% Physical	% Valid
Inpaint coords	61.8	41.4	49.7	35.6
Inpaint atoms	74.8	62.8	64.9	56.1
Inpaint bonds	80.8	66.4	70.0	59.3
Inpaint (all)	57.0	38.3	44.1	32.0
Replacement Guidance	**85.2**	**75.8**	**76.2**	**68.3**

Across all metrics, theReplacement Guidance strategy ($t_{\text{free}} = 1.0$) outperforms every inpainting configuration, achieving the highest PoseBusters validity.

C EVALUATION METRICS

We assess the generated molecules using the following metrics:

Synthetic Accessibility (SA) Score. Several scoring systems exist to estimate the synthetic accessibility of a compound (Coley et al., 2018; Thakkar et al., 2021; Ertl & Schuffenhauer, 2009). We use the SA score of Ertl and Schuffenhauer (Ertl & Schuffenhauer, 2009), which combines historical data from synthesized compounds with molecular complexity to assess synthetic feasibility. Lower scores indicate greater ease of synthesis.

Validity Checks. Molecules are validated at multiple stages:

- RDKit Validity: The molecule can be successfully parsed and sanitized by RDKit.

- PoseBusters Validity: The molecule passes chemical and physical plausibility checks using PoseBusters (Buttenschoen et al., 2023).

Similarity Metrics: We adapted similarity scores introduced in the ShEPhERD paper (Adams et al., 2025) with the same settings (xTB relaxtion in implicit water and ESP alignment with 400 surface points)

- Surface Similarity: Quantifies the volumetric overlap between two atomic point clouds of the generated and reference molecules. High scores indicate preservation of 3D shape.

- Electrostatic Similarity: Measures the similarity between the electrostatic potential fields of the generated and reference molecules, capturing charge complementarity relevant for molecular recognition.

- Pharmacophore Similarity: Assesses the overlap of key pharmacophoric features—hydrogen bond donors (HBD), acceptors (HBA), and aromatic centers—between the generated and reference molecules. Directional alignment is included when necessary to capture interaction specificity.

Docking Score. We used AutoDock Vina (Eberhardt et al., 2021) to further assess the quality of the generated molecules. We used the Vina scoring function to assess molecules with binding site conditional poses. Since such scoring functions are sensitive to the exact coordinates and can assign experimental structures poor scores without energy minimization (Weller & Rohs, 2024), we computed energy-minimized scores for generated molecules. This protocol evaluates the plausibility of the generated pose via local energy minimization and does not perform a global pose search (i.e., redocking). For this minimization step, the binding site was defined with a buffer of 5 Å around the reference ligand.

D NATURAL PRODUCT TASK: EXTENDED EVALUATION

To complement the main results, we provide an extended evaluation of model behavior on the natural product (NP) hopping task. We report molecular validity, synthetic accessibility scores, pharmacophore feature recovery, and conformational stability for generated analogues across all three NP targets.

D.1 EXPERIMENTAL DETAILS

For each seed NP, we generated 2,500 candidate analogues with total atom counts between 36 and 80 (including hydrogens). We used our two conditioning strategies: *Interpolate-Integrate* (restarting at a continuous time of $\tau = 0.75$) and *Replacement Guidance* (with a relaxation time of $t_{\text{relax}} = 1.0$). Both approaches were conditioned by sampling key pharmacophore features—hydrogen bond donors (HBD), acceptors (HBA), and aromatic atoms—from the reference NP. The remaining atoms in the seed structure were sampled randomly from the full set of atoms in the reference. All generated molecules were post-processed with xTB geometry relaxation and ESP alignment before evaluation.

D.2 VALIDITY AND FILTERING PIPELINE

Table 12 reports the validity of the generated molecules at each stage of our filtering pipeline. The first stage assesses RDKit validity, followed by a geometry quality check using PoseBusters. The final filter is based on synthetic accessibility (SA < 4.5), where `Replacement Guidance` demonstrates a significantly higher final yield of successful candidates.

Table 12: Reported validity of generated molecules for the natural product (NP) hopping task. For each NP target (NP1, NP2, NP3), 2,500 molecules were generated using two methods: *interpolate–integrate* and *replacement–guidance*. We report the percentage of molecules that (1) are valid according to RDKit parsing, (2) pass all PoseBusters (PB) geometry checks after xTB geometry relaxation and ESP alignment, and (3) additionally have a synthetic accessibility (SA) score < 4.5.

NP	Method	Valid (RDKit)	xTB + PB Valid	xTB + PB Valid+ SA < 4.5
	ShEPhERD	65.5%	57.3%	24.7%
	Interpolate–integrate	**89.4%**	**71.5%**	35.6%
NP1	Replacement–guidance	72.5%	60.5%	**50.2%**
	ShEPhERD	56.5%	51.0%	17.4%
	Interpolate–integrate	**98.5%**	**93.6%**	16.0%
NP2	Replacement–guidance	93.8%	87.9%	**48.8%**
	ShEPhERD	55.5%	44.1%	20.2%
	Interpolate–integrate	**77.1%**	62.7%	5.2%
NP3	Replacement–guidance	72.9%	**64.4%**	**42.1%**

D.3 PERFORMANCE ON FILTERED CANDIDATES (SA < 4.5)

Table 13 presents the primary performance metrics for the final set of candidates that passed all filters, including the SA <4.5 threshold. All molecules were subject to xTB geometry relaxation and ESP alignment before scoring. These results show that *Replacement-guidance* consistently produces the highest success rate of viable candidates and generates molecules with the best synthetic accessibility scores across all three natural product targets. In contrast, *Interpolate–integrate* is the superior method for achieving the highest 3D similarity scores.

Table 13: Performance summary for molecular generation across NP hopping tasks (NP1, NP2, NP3) after xTB geometry relaxation and ESP alignment. We report PoseBusters Success Rate (Valid and SA < 4.5), similarity metrics (ESP and pharmacophore), and SA score. Only molecules with synthetic accessibility (SA) scores less than 4.5 are included in this analysis.

NP	Method	Success Rate ↑	ESP sim ↑	ESP sim top10 ↑	Pharma sim ↑	Pharma sim top10 ↑	SA ↓
NP1	ShEPhERD	24.7%	0.48 ± 0.06	0.63 ± 0.02	0.17 ± 0.06	0.34 ± 0.03	3.95 ± 0.45
	Interpolate–integrate	35.6%	$\mathbf{0.51 \pm 0.11}$	$\mathbf{0.81 \pm 0.02}$	0.18 ± 0.09	0.49 ± 0.06	3.81 ± 0.55
	Replacement–guidance	**50.2%**	0.50 ± 0.09	$\mathbf{0.81 \pm 0.02}$	0.18 ± 0.08	$\mathbf{0.52 \pm 0.06}$	$\mathbf{3.36 \pm 0.66}$
NP2	ShEPhERD	17.4%	0.68 ± 0.06	0.79 ± 0.01	0.20 ± 0.06	0.34 ± 0.02	3.76 ± 0.57
	Interpolate–integrate	16.0%	$\mathbf{0.70 \pm 0.08}$	$\mathbf{0.86 \pm 0.01}$	$\mathbf{0.22 \pm 0.10}$	$\mathbf{0.46 \pm 0.02}$	3.90 ± 0.48
	Replacement–guidance	**48.8%**	0.69 ± 0.08	0.85 ± 0.01	0.20 ± 0.07	0.44 ± 0.04	$\mathbf{3.41 \pm 0.71}$
NP3	ShEPhERD	20.2%	$\mathbf{0.46 \pm 0.06}$	0.60 ± 0.01	$\mathbf{0.17 \pm 0.05}$	$\mathbf{0.30 \pm 0.02}$	3.84 ± 0.47
	Interpolate–integrate	5.2%	0.40 ± 0.07	0.56 ± 0.05	0.11 ± 0.04	0.20 ± 0.03	3.98 ± 0.44
	Replacement–guidance	**42.1%**	0.45 ± 0.06	$\mathbf{0.65 \pm 0.03}$	0.14 ± 0.04	0.29 ± 0.02	$\mathbf{3.33 \pm 0.72}$

D.4 PERFORMANCE ON ALL VALID MOLECULES (UNFILTERED)

For a more comprehensive analysis, Table 14 summarizes the same performance metrics for all molecules that passed the initial PoseBusters validity checks, prior to SA filtering. These unfiltered results reveal the inherent trade-offs of the methods: *Interpolate-integrate* is most effective at generating a high percentage of initially valid structures, while *Replacement-guidance* demonstrates a strong intrinsic bias towards producing molecules with better synthetic accessibility.

Table 14: Performance summary for molecular generation across NP hopping tasks (NP1, NP2, NP3) after xTB geometry relaxation and ESP alignment. We report PoseBusters validity, similarity metrics (ESP and pharmacophore), and SA score.

NP	Method	Valid ↑	ESP sim ↑	ESP sim top10 ↑	Pharma sim ↑	Pharma sim top10 ↑	SA ↓
NP1	ShEPhERD	57.3%	0.47 ± 0.07	0.66 ± 0.02	0.17 ± 0.06	0.37 ± 0.03	4.75 ± 0.89
	Interpolate–integrate	**71.5%**	**0.55 ± 0.13**	**0.89 ± 0.02**	**0.21 ± 0.11**	**0.73 ± 0.09**	4.67 ± 1.02
	Replacement–guidance	60.5%	0.52 ± 0.11	0.87 ± 0.01	0.19 ± 0.10	0.66 ± 0.08	**3.74 ± 1.01**
NP2	ShEPhERD	51.0%	0.68 ± 0.08	0.81 ± 0.01	0.21 ± 0.06	0.39 ± 0.02	5.09 ± 1.2
	Interpolate–integrate	**93.6%**	**0.77 ± 0.09**	**0.93 ± 0.01**	**0.35 ± 0.17**	**0.86 ± 0.07**	5.41 ± 1.03
	Replacement–guidance	87.9%	0.72 ± 0.09	0.91 ± 0.02	0.26 ± 0.12	0.82 ± 0.08	**4.43 ± 1.31**
NP3	ShEPhERD	44.1%	0.45 ± 0.06	0.62 ± 0.01	**0.17 ± 0.04**	0.32 ± 0.02	4.69 ± 0.96
	Interpolate–integrate	62.7%	**0.47 ± 0.09**	0.69 ± 0.02	0.14 ± 0.06	**0.39 ± 0.05**	5.92 ± 1.03
	Replacement–guidance	**64.4%**	**0.47 ± 0.07**	**0.73 ± 0.02**	0.16 ± 0.05	**0.39 ± 0.04**	**4.07 ± 1.27**

D.5 DISTRIBUTIONS OF KEY METRICS

The figures below provide a visual summary of the performance trade-offs between the methods. Figure 4 shows the relationship between surface and pharmacophore similarity, highlighting that *Interpolate–Integrate* consistently generates analogues with the highest 3D similarity to the reference. In contrast, Figure 5 demonstrates the clear advantage of *Replacement Guidance* in producing molecules with lower (better) SA scores. While *Interpolate–Integrate* yields more geometrically stable molecules post-relaxation (lower RMSD in Figure 6), Figure 7 confirms that *Replacement Guidance* and SHEPHERD generate a more chemically diverse set of candidates, reflecting broader exploration.

NP0: Similarity (SA < 4.5)   **NP1:** Similarity (SA < 4.5)   **NP2:** Similarity (SA < 4.5)

Figure 4: Surface similarity vs. pharmacophore similarity for generated analogues (filtered by SA < 4.5) across the three natural product tasks.

NP1   **NP2**   **NP3**

Figure 5: Synthetic accessibility (SA) score distributions for generated analogues across the three natural product tasks.

D.6 DETAILED POSEBUSTERS VALIDITY

Tables 15, 16, and 17 provide a detailed breakdown of the PoseBusters validity evaluation. Table 15 reports overall generation success and combined chemical/physical validity. Table 16 decomposes

NP1: RMSD (aligned vs. original) **NP2:** RMSD (aligned vs. original) **NP3:** RMSD (aligned vs. original)

Figure 6: RMSD between the xTB-relaxed/aligned and original generated conformers for each NP task.

NP0: Graph similarity to reference **NP1:** Graph similarity to reference **NP2:** Graph similarity to reference

NP0: Pairwise Tanimoto similarity **NP1:** Pairwise Tanimoto similarity **NP2:** Pairwise Tanimoto similarity

Figure 7: Graph similarity to the reference (top row) and pairwise Tanimoto similarity among generated ligands (bottom row) for the three NP hopping tasks.

chemical validity into sanitization, hydrogen compatibility, valence, and connectivity checks. Table 17 presents results from the PoseBusters suite, including bond lengths, angles, steric clashes, and energetic plausibility.

Table 15: Validity of generated molecules across the natural-product (NP) hopping tasks. Each method attempts 2,500 generations; we report the percentage of molecules that were generated (% Generated) and the proportion of those that pass chemical validity checks, physical PoseBusters checks, or both.

NP	Method	% Generated	% Chemical	% Physical	% Valid
NP1	Interpolate–integrate	81.6	81.6	71.6	71.5
	Replacement–guidance	68.2	68.2	60.5	60.5
NP2	Interpolate–integrate	96.7	96.7	93.6	93.6
	Replacement–guidance	92.6	92.6	88.0	87.9
NP3	Interpolate–integrate	69.0	69.0	62.8	62.7
	Replacement–guidance	67.6	67.6	64.4	64.4

Table 16: Chemical validity of generated molecules for the natural product (NP) hopping task. Shown are the percentages of generated molecules that pass each chemical validity check. These checks operate on the molecular graph and do not involve 3D conformations. The last column reports the percentage that passed all checks.

NP	Method	% Gen.	% Sanit.	% H-comp.	% No Rad.	% Conn.	% Chem.
NP1	Interpolate–integrate	81.6	81.6	81.6	81.6	81.6	81.6
	Replacement–guidance	68.2	68.2	68.2	68.2	68.2	68.2
NP2	Interpolate–integrate	100.0	96.6	96.6	96.6	96.6	96.7
	Replacement–guidance	92.6	92.6	92.6	92.6	92.6	92.6
NP3	Interpolate–integrate	100.0	68.9	68.9	68.9	68.9	69.0
	Replacement–guidance	67.6	67.6	67.6	67.6	67.6	67.6

Table 17: Physical validity of generated molecules for the natural product (NP) hopping task. Shown are the percentages of generated molecules that pass each intramolecular PoseBusters check. The final column shows the percentage passing all physical tests.

NP	Method	% Gen.	Bond Len.	Bond Ang.	Steric Clash	Ring Flat.	DB Flat.	Energy	% Phys.
NP1	Interpolate–integrate	81.6	81.4	81.6	72.3	81.6	81.0	81.3	71.6
	Replacement–guidance	68.2	68.0	68.2	61.2	68.2	67.6	68.0	60.5
NP2	Interpolate–integrate	96.7	96.5	96.6	94.0	96.6	96.5	96.3	93.6
	Replacement–guidance	92.6	92.5	92.5	88.4	92.6	92.3	92.0	88.0
NP3	Interpolate–integrate	69.0	68.3	68.8	65.1	68.9	67.7	67.8	62.8
	Replacement–guidance	67.6	67.6	67.5	65.3	67.6	66.9	67.1	64.4

D.7 PHARMACOPHORE FEATURE RECOVERY

To better understand how pharmacophoric features are preserved during generation, we analyzed a subset of ligands produced by the *Replacement Guidance* strategy. Molecules were selected based on pharmacophore similarity from the filtered set with SA score ≤ 4.5, and each recovered reference pharmacophore feature was matched within a 1.5Å threshold. While this is not a strict pharmacophore recovery metric, it allows us to examine which reference features are most consistently reconstructed in high-quality analogues.

Figure 8 presents the per-feature match fractions for each target. Spheres represent the reference pharmacophore features, and their color encodes the recovery rate across the selected molecules: green indicates features recovered in most analogues, yellow indicates moderate recovery, and red indicates rare recovery. In each subpanel, **Top** rows display the recovery rate for the ten highest-ranked analogues by pharmacophore similarity, while **Bottom** rows show rates for all filtered analogues meeting the SA ≤ 4.5 threshold.

For example, in NP1 (top row, left), most pharmacophoric features are green or yellow, showing high retention in top-ranked molecules. In contrast, the bottom row for NP3 contains more red features, indicating less consistent recovery.

The best-performing molecules recover nearly all pharmacophoric features for NP0 and NP1, including those that were inconsistently reproduced in the general population. This suggests that the model is capable of high-fidelity reconstruction when guided by appropriate selection criteria.

In contrast, the broader set of generated molecules shows greater variability in feature retention, particularly for features located on the molecular periphery. These features are more flexible and less scaffold-constrained, making them harder to consistently reproduce—despite their potential importance for binding interactions.

Figure 8: Pharmacophore feature retention for NP1, NP2, and NP3. **Top:** top 10 analogues ranked by pharmacophore similarity to the reference NP. **Bottom:** all filtered analogues with SA ≤ 4.5. Dummy atoms are colored by recovery rate. Reference molecules omitted for clarity.

D.8 PERFORMANCE OF MOLSNAPPER BASELINE

For the NP hopping task, we also evaluated MolSnapper in ligand-only mode (clash rate = 0) using the NP's HBA and HBD features as input as a secondary baseline to understand how a method conditioned on discrete pharmacophore points would perform. A limitation of this baseline is that it does not explicitly place hydrogens. The results for each natural product target are presented in Table 19.

We hypothesize that MolSnapper's performance is limited in this context due to the nature of its conditioning mechanism. MolSnapper is designed to strictly satisfy a set of discrete, fixed pharmacophore points, which acts as a "hard" constraint on the generation. While this is effective for tasks with a few key constraints, providing a dense set of points derived from a large, complex natural product may be overly restrictive, making it difficult for the model to generate novel and synthetically accessible scaffolds that satisfy all points simultaneously. This highlights the challenge of the NP hopping task and the effectiveness of conditioning strategies that allow flexibility and capture more holistic 3D information.

Table 18: Performance summary for the MolSnapper baseline on the NP hopping tasks after xTB geometry relaxation and ESP alignment. The table reports success rate (percentage of 2,500 samples passing validity and SA ≤ 4.5 filters), SA score, and top-10 similarity scores.

NP	Method	Success Rate ↑	SA Score ↓	ESP sim (top 10) ↑	Pharma sim (top 10) ↑
NP1	MolSnapper	0.32%	4.23 ± 0.36	0.32 ± 0.04	0.07 ± 0.05
NP2	MolSnapper	0.16%	4.22 ± 0.39	0.46 ± 0.1	0.09 ± 0.02
NP3	MolSnapper	0.32%	4.06 ± 0.43	0.22 ± 0.07	0.06 ± 0.01

Table 19: Performance summary for the MolSnapper baseline on the NP hopping tasks after xTB geometry relaxation and ESP alignment.

NP	Method	Valid ↑	SA Score ↓	ESP sim (top 10) ↑	Pharma sim (top 10) ↑
NP1	MolSnapper	26.24%	6.43 ± 0.78	0.51 ± 0.02	0.16 ± 0.02
NP2	MolSnapper	19.88 %	6.84 ± 0.79	0.63 ± 0.02	0.19 ± 0.01
NP3	MolSnapper	14.20 %	6.32 ± 0.85	0.46 ± 0.02	0.14 ± 0.01

E   BIOISOSTERIC FRAGMENT MERGING: EXTENDED EVALUATION

This section provides a detailed evaluation of the EV-D68 3C bioisosteric fragment-merging task. We assess molecule quality across synthetic accessibility, conformational stability, chemical validity, and performance against relevant baselines.

E.1   EXPERIMENTAL DETAILS

Data and Setups.   The input data, sourced from the Fragalysis platform[3], consisted of 13 experimentally resolved fragment-bound structures previously curated by SHEPHERD (Adams et al., 2025). Across all setups, generated molecules ranged from 50 to 89 atoms. From this set, the protein conformation from the `D68EV3CPROA-x1071_0A_bound` complex was randomly selected and used for all subsequent docking simulations.

MULTI-FRAGMENT REFERENCE.   For this setup, we created three distinct composite inputs, each by combining three of the known fragment ligands. We generated 400 candidate molecules for each of the three combinations (1,200 total per method). A key implementation detail is that for *Replacement-guidance*, the input was padded to accommodate the larger seed size, whereas for *Interpolate-integrate*, the original fragment size was retained due to architectural constraints.

RANDOM ATOM SEEDING.   The conditioning profile was created by randomly selecting a subset of pharmacophore features from the full fragment library. This selection was subject to spatial constraints to ensure physical realism: hydrogen bond features were kept at least 1 Å apart, and aromatic centers at least 2 Å apart. The remaining atoms for the seed were sampled from the broader pool of fragment-derived structures. For this setup, we generated 1,000 candidate ligands per method.

FULL INTERACTION PROFILE.   For the manually curated setup, we adopted the 27-feature pharmacophore profile reported in the SHEPHERD paper (Adams et al., 2025). This profile, which was originally extracted from Fragalysis annotations, represents the aggregate interaction features of the fragment ensemble. The conditioning scheme also defines an averaged ESP field, which was used by the SHEPHERD baseline but not by our methods. We generated 1,000 candidate ligands per method for this setup. A necessary step for our methods, MolSnapper and DiffSBDD baseline was to convert this abstract pharmacophore profile into a concrete atomic representation to serve as a seed. This involved instantiating specific atoms (e.g., a Nitrogen for an HBA) at the given coordinates.

Generation Parameters.   Across all setups, generated molecules ranged from 50 to 89 atoms. We used our standard conditioning parameters: *Interpolate-Integrate* was run with a restart time of $\tau = 0.75$, and *Replacement Guidance* was run with a relaxation time of $t_{\text{relax}} = 1.0$.

Evaluation Pipeline.   All candidate molecules in this section were evaluated using a standardized pipeline. Following generation, each ligand was subject to: (1) geometry relaxation using xTB, (2) alignment to the reference fragment constellation based on electrostatic potential (ESP), and (3) in-pocket energy minimization and scoring using `AutoDock Vina` with a 5 Å buffer.

E.2   COMPARISON OF CONDITIONING SETUPS (UNFILTERED)

We first compared the unfiltered performance of our two methods across the three conditioning setups to understand their inherent properties. Table 20 summarizes the results for all generated

---

[3]`https://fragalysis.diamond.ac.uk/viewer/react/landing`

molecules that passed initial PoseBusters validity checks, prior to applying the synthetic accessibility filter. This unfiltered analysis reveals the inherent tendencies of our two strategies. *Interpolate–integrate* consistently generates a higher percentage of geometrically valid molecules. In contrast, the molecules generated by *Replacement-guidance*, while fewer in number, tend to have better SA scores and stronger Vina scores. This highlights a trade-off between generating a high quantity of valid structures versus a higher quality of drug-like candidates.

Table 20: Performance comparison of *Interpolate–Integrate* and *Replacement Guidance* across three input conditioning setups for the EV-D68 3C merging task. We report PoseBusters validity, clash rate (fraction of molecules with zero steric clashes), SA and top 10 Vina scores.

Conditioning setup	Method	Valid (%)↑	No clash (%)↑	SA ↓	Vina top10 ↓
Multi-fragment ref.	Interpolate–integrate	59.3%	47.2	4.65 ± 0.96	-6.00 ± 0.36
	Replacement–guidance	36.3%	26.8	3.57 ± 0.85	-5.74 ± 0.22
Random atom seeding	Interpolate–integrate	41.0%	31.2	5.18 ± 1.17	-5.45 ± 0.20
	Replacement–guidance	28.1%	20.7	3.84 ± 0.81	-6.00 ± 0.31
Full interaction profile	Interpolate–integrate	**38.1%**	30.2	4.83 ± 1.17	-5.52 ± 0.18
	Replacement–guidance	31.9%	25.4%	3.47 ± 0.70	-6.70 ± 0.39

E.3 Detailed Comparison on the Full Interaction Profile

This section provides a deeper analysis on the manually curated 'Full Interaction Profile' setup, which allows for direct comparison against multiple external baselines.

E.3.1 Baseline Methods

Although our methods are ligand-only, we also benchmark against pocket-conditioned SBDD methods in this section. Because our input fragment poses contain implicit information about the binding site, this comparison serves as a stringent test of our method's ability to generate molecules that are compatible with the protein pocket. We evaluated three distinct baselines:

- **SHEPHERD: Adams et al. (2025)** The primary baseline, conditioned on the interaction profile and ESP in a ligand-only setting.
- **MolSnapper: Ziv et al. (2025)** We evaluated MolSnapper in two settings: a protein-blind mode ('clash-rate=0') and a protein-aware mode ('clash-rate=0.1') using the explicit protein structure.
- **DiffSBDD: Schneuing et al. (2024)** We used the official inpainting script with checkpoints pre-trained on the CrossDocked dataset. As a structure-based method, it conditions on the protein pocket geometry while using the provided pharmacophore points as a reference context to guide the inpainting.

A few key limitations and procedural details apply to the baselines. Both MolSnapper and DiffSBDD do not explicitly generate hydrogens and can only generate molecules larger than the input profile. To account for this, we generated 1,000 molecules for each within a heavy atom range of 36-46. Furthermore, for DiffSBDD, we selected the largest resulting fragment from the output, because we didn't get any fully connected molecules.

E.3.2 Validity and Filtering Pipeline

Table 21 details the validity rate of the methods at each stage of our filtering pipeline for the 'Full Interaction Profile' setup. While *Interpolate–integrate* shows high initial validity, *Replacement-guidance* ultimately produces a greater final yield of candidates passing all filters.

E.3.3 Performance Comparison

Table 22 summarizes the unfiltered performance of our methods against the baselines. The results highlight that the conditioning mechanisms of DIFFSBDD and MOLSNAPPER are less suited for

Table 21: Validity assessment of generated molecules for the bioisosteric merging task for EV-D68 3C (ShEPhERD profile setup). Each method generated 1000 molecules. We report the percentage of molecules that (1) are valid according to RDKit parsing, (2) pass all PoseBusters (PB) geometry checks after xTB geometry relaxation and ESP alignment, and (3) additionally have a synthetic accessibility (SA) score < 4.

Method	Valid (RDKit)	xTB + PB Valid	xTB + PB Valid + SA < 4
DiffSBDD (largest frag)	99.8%	43.1%	0%
MolSnapper (ligand-based)	31.1%	17.6 %	0%
MolSnapper (clash-rate = 0.1)	30.4%	14.5 %	0%
ShEPhERD	45.1%	33.8%	10.8%
Interpolate–integrate	**52.2%**	**39.5%**	8.7%
Replacement–guidance	39.7%	31.9%	**23.5%**

this bioisosteric merging task, yielding molecules with poor SA and Vina scores. Among the top-performing methods, *Interpolate-integrate*, *Replacement-guidance*, and SHEPHERD all achieve comparable performance in Vina scores and in generating valid, clash-free molecules. However, they exhibit distinct strengths in other metrics: *Replacement-guidance* produces candidates with the best synthetic accessibility (SA score of 3.47), while SHEPHERD achieves the highest pharmacophore similarity.

Table 22: Performance summary for molecular generation in the EV-D68 3C bioisosteric merging task (ShEPhERD profile setup), after xTB geometry relaxation and ESP alignment. We report PoseBusters validity, clash rate (fraction of molecules with zero steric clashes), SA score, top-10 pharmacophore similarity and top 10 Vina scores.

Target	Method	Valid ↑	No clash ↑	SA ↓	Pharma sim (top 10) ↑	Vina (top 10) ↓
EV-D68 3C	DiffSBDD (largest frag)	43.1%	38.0%	6.91 ± 0.53	0.1 ± 0.01	-4.35 ± 0.35
	MolSnapper (ligand-based)	17.6%	16.2%	7.04 ± 0.54	0.15 ± 0.03	-4.56 ± 0.12
	MolSnapper (clash-rate = 0.1)	14.5%	13.9%	6.91 ± 0.53	0.11 ± 0.01	-4.99 ± 0.42
	ShEPhERD	33.8%	29.8%	4.45 ± 0.99	0.3 ± 0.02	-6.74 ± 0.29
	Interpolate–integrate	39.5%	30.8%	4.96 ± 1.17	0.19 ± 0.01	-5.95 ± 0.39
	Replacement–guidance	31.9%	25.4%	3.47 ± 0.70	0.23 ± 0.02	-6.70 ± 0.39

(a) Pairwise Tanimoto similarity between generated molecules.

(b) SA score distribution across methods.

(c) RMSD between xTB-relaxed and aligned conformers vs. original 3D geometries.

Figure 9: Metrics for the EV-D68 3C bioisosteric fragment-merging benchmark (27-feature profile). All methods conditioned on full 27-feature profile.

We visualize graph-based diversity, SA scores, and post-relaxation conformational stability for all methods in Figure 9. Figure 9 (b and c) shows that *Replacement Guidance* achieves the lowest SA scores, and *Interpolate–Integrate* yields the most stable conformations, as evidenced by the lowest RMSD values between xTB-relaxed and original geometries. These trends mirror those

observed in the NP hopping task: *Replacement Guidance* favors diverse, synthesizable outputs, while *Interpolate–Integrate* prioritizes geometric regularity.

E.4 DETAILED POSEBUSTERS VALIDITY

Table 23: Validity of the generated and ground truth molecules for the bioisosteric fragment merging task for EV-D68 3C (ShEPhERD profile setup). The table contains the total number of molecules that was to be generated or that successfully passed the XTB process and alignment and the proportions of molecules that pass all the chemical validity test, all physical validity tests. The last columns is the percentage of molecules that pass all the tests together.

Method	% Generated	% Chemical	% Physical	% Valid
Interpolate–integrate	42.4	42.4	39.5	39.5
Replacement–guidance	35.3	35.3	31.9	31.9

Table 24: Components of the chemical validity of the generated molecules for the bioisosteric fragment merging task for EV-D68 3C (ShEPhERD profile setup). Each entry shows the percentage of molecules passing individual chemical validity checks. The final column (**Chemical**) indicates the proportion of molecules that pass *all* checks. These tests assess only the molecular graph (e.g., sanitization, radicals, hydrogen completion), not the 3D conformation.

Method	% Gen.	% Sanit.	% H-comp.	% No Rad.	% Conn.	% Chem.
Interpolate–integrate	42.4	42.3	42.3	42.3	42.3	42.4
Replacement–guidance	35.3	35.2	35.2	35.2	35.2	35.3

Table 25: Components of the physical validity of the generated molecules for the bioisosteric fragment merging task for EV-D68 3C (ShEPhERD profile setup). The numbers shown are the percentages of the molecules that pass each of the intramolecular PoseBusters tests. The last column is the percentage of molecules that pass all of the intramolecular tests. The physical tests check the 3D conformations of the generated molecules.

Method	% Gen.	% Bond Len.	% Bond Ang.	% Clash	% Arom. Flat.	% DB Flat.	% Int. Energy	% Physical
Interpolate–integrate	42.4	41.9	42.2	41.4	42.3	41.4	41.2	39.5
Replacement–guidance	35.3	34.8	34.9	32.6	35.2	34.9	34.8	31.9

Tables 23, 24, and 25 provide a detailed breakdown of molecular validity for the fragment merging task. Table 23 reports overall generation success and the percentage of molecules passing both chemical and physical filters. Table 24 decomposes chemical validity into sanitization, hydrogen compatibility, valence, and connectivity checks. Table 25 presents results from the PoseBusters suite, including bond lengths, angles, steric clashes, and energetic plausibility after xTB relaxation.

E.5 FRAGMENT RETENTION ANALYSIS

To provide a quantitative measure of novelty and to validate that our conditioning strategies perform true bioisosteric merging rather than simple fragment linking, we calculated the Fragment Retention Rate. This metric is defined as the percentage of successfully generated molecules that contain one or more of the original seed fragments as an exact chemical substructure.

The calculation was performed programmatically using the RDKit cheminformatics library. For each generated molecule, we iterated through the set of input fragments and used the HasSubstruct-Match function to detect the presence of any original fragment. A low retention rate is indicative of

successful bioisosteric replacement, demonstrating a model's ability to generate novel chemotypes that preserve pharmacophoric information without retaining the original chemical matter.

In our evaluation of the EV-D68 3C bioisosteric merging task (using the full interaction profile), our methods demonstrated a strong capacity for generating novel structures. The Replacement Guidance strategy yielded a Fragment Retention Rate of just 4.31%. Similarly, the Interpolate-Integrate strategy had a retention rate of 4.44%.

F PHARMACOPHORE-MERGING ON SARS-COV-2 M_{PRO}: EXTENDED EVALUATION

This section provides a detailed evaluation of the SARS-CoV-2 M_{pro} pharmacophore-merging task. We assess the quality of generated molecules by comparing their predicted binding affinity against a strong baseline of larger, known binders for the same target.

F.1 EXPERIMENTAL DETAILS

Datasets.   The data for this task was curated from the Fragalysis platform[4]. We created two distinct sets:

- **Conditioning Set:** A set of 81 small, non-covalent fragments (MW < 300 Da) from the initial Diamond/XChem screen.
- **Baseline Set:** A set of 1,426 larger, known binders (MW > 300 Da) for M_{pro}. This set serves as a challenging, real-world baseline for evaluating the predicted binding affinity of our generated molecules.

The full names for the conditioning set fragments, taken directly from the input SDF file, are listed below:

- `5rfp_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gf9_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rgi_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5reu_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gfv_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rf1_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r81_A_1001_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfh_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rgm_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfq_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rek_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfw_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gcm_A_403_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gdr_A_406_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rg3_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r82_A_1001_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rer_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rha_A_1001_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfm_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gc6_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gfy_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`

---

[4] `https://fragalysis.diamond.ac.uk/viewer/react/preview/target/CoV-Mpro/tas/lb32627-272`

- `7gel_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7ghi_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r80_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rg0_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gc8_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rhd_A_408_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gb3_A_406_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rgh_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfl_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rg2_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rgo_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7ghh_A_1001_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5reh_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rft_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7ghg_A_1001_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rez_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gco_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5ren_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r83_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r84_A_1001_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5re4_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rel_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfx_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5re9_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5res_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r7z_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5ret_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfk_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rew_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rgp_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rex_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gcp_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gcy_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfn_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfz_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gha_A_1001_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rgk_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfo_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7ghj_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfs_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gba_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gg3_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfy_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfe_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rhf_A_405_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rgl_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rf6_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`

- `5rf7_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gdq_A_406_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rez_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `7gco_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5ren_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r83_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r84_A_1001_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5re4_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rel_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5rfx_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5re9_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5res_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`
- `5r7z_A_404_1_SARS2_MproA-y0118+A+410+1__LIG`

Generation and Evaluation. We generated 2,500 candidate molecules per method, with total atom counts between 40 and 80, using our two conditioning strategies: *Interpolate-Integrate* (with a restart time of $\tau = 0.75$) and *Replacement Guidance* (with a relaxation time of $t_{\text{relax}} = 1.0$). The total atom count range of 40 to 80 was chosen to match the core distribution of the 1,426 known Mpro binders, as shown in Figure 10. The generation was conditioned by sampling pharmacophore features from the 81-fragment conditioning set, following the 'random atom seeding' setup (Section 4.3), where each seed was constructed by sampling atoms from the 81-fragment conditioning set: half of the atoms were randomly selected pharmacophore features, while the remaining half were non-pharmacophore atoms. The pharmacophore selection was subject to the spatial constraints described in Appendix E.1 to ensure physical realism. To ensure a fair comparison, both our generated candidates and the 1,426 baseline molecules were evaluated using an identical AutoDock Vina docking protocol to obtain their Vina scores. For this protocol, the rigid receptor structure was taken from a randomly selected crystal structure, **SARS-a0514b**, which defines the binding pocket for all docking runs.

Figure 10: Distribution of total atom counts (including hydrogens) for the baseline set of 1,426 known binders for SARS-CoV-2 Mpro. The generation range of 40–80 atoms was selected to cover the main peaks of this distribution.

F.2 VALIDITY AND FILTERING PIPELINE

Table 26 details the success rate of our methods at each stage of the filtering pipeline. Both methods demonstrate high initial validity, but `Replacement-guidance` produces a significantly higher final yield of candidates that pass the synthetic accessibility score filter.

F.3 PERFORMANCE ON UNFILTERED CANDIDATES

Table 27 summarizes the final performance metrics for all valid generated molecules, compared against the baseline set of known binders.

Table 26: Validity assessment of generated molecules for the pharmacophore-merging task on SARS-CoV-2 M_{pro}. Each method generated 2,500 molecules. We report the percentage of molecules that: (1) are valid according to RDKit parsing, (2) pass all PoseBusters (PB) geometry checks after xTB relaxation and ESP alignment, and (3) additionally satisfy a synthetic accessibility (SA) score ≤ 4.5.

Method	Valid (RDKit)	xTB + PB Valid	xTB + PB Valid + SA < 4.5
Interpolate–Integrate	**51.2%**	**41.0%**	23.5%
Replacement–Guidance	48.0%	32.2%	**27.3%**

Table 27: Performance summary for the SARS-CoV-2 M_{pro} pharmacophore-merging task. The table reports overall PoseBusters validity (**Valid**), the percentage of initial samples that are valid and clash-free (**No clash**), the average unfiltered SA score, and the top-10 Vina docking score.

Target	Method	Valid (%) ↑	No clash (%) ↑	SA ↓	Vina top10 ↓
SARS-CoV-2 M_{pro}	Interpolate–integrate	**41.0%**	**24.0%**	4.49 ± 1.20	-6.67 ± 0.13
	Replacement–guidance	32.2%	13.6%	$\mathbf{3.61 \pm 0.90}$	$\mathbf{-7.70 \pm 0.37}$
	Known Binders (Baseline)	100%	84.1%	3.70 ± 0.97	-10.03 ± 0.12

Table 28: Validity of the generated molecules for the pharmacophore-merging task on SARS-CoV-2 M_{pro}. Each method attempts 2,500 generations. We report the percentage of generated molecules that pass all chemical validity checks, all physical validity checks, and the percentage that pass both.

Method	% Generated	% Chemical	% Physical	% Valid
Interpolate–Integrate	51.3	51.3	41.0	41.0
Replacement–Guidance	48.0	48.0	32.2	32.2

Table 29: Components of the chemical validity of the generated molecules for the pharmacophore-merging task on SARS-CoV-2 M_{pro}. Each entry shows the percentage of molecules passing individual chemical validity checks. The final column indicates the percentage that pass all chemical checks.

Method	% Gen.	% Sanit.	% H-comp.	% No Rad.	% Conn.	% Chem.
Interpolate–Integrate	51.3	51.2	51.2	51.2	51.2	51.3
Replacement–Guidance	48.0	48.0	48.0	48.0	48.0	48.0

Table 30: Components of the physical validity of the generated molecules for the pharmacophore-merging task on SARS-CoV-2 M_{pro}. Each entry shows the percentage of molecules passing individual PoseBusters checks after xTB relaxation and ESP alignment. The final column shows the percentage that pass all physical checks.

Method	% Gen.	% Bond Len.	% Bond Ang.	% Clash	% Arom. Flat.	% DB Flat.	% Int. Energy	% Physical
Interpolate–Integrate	51.3	50.0	50.3	48.4	51.2	46.4	49.4	41.0
Replacement–Guidance	48.0	42.5	45.8	43.0	47.6	42.1	46.5	32.2

F.4 DETAILED POSEBUSTERS VALIDITY

Table 28 summarizes the validity metrics for the pharmacophore-merging task on SARS-CoV-2 M_{pro}. We report the percentage of generated molecules that pass all chemical validity checks (e.g., sanitization, valence), physical plausibility checks via PoseBusters (after xTB relaxation and ESP alignment), and the intersection

of both. *Interpolate–Integrate* yields higher overall validity, while *Replacement Guidance* shows competitive chemical correctness and stronger SA-filtered outputs (see Appendix F for extended analysis).

Although our method operates in a protein-blind setting, we further assessed the spatial plausibility of generated molecules by docking them into SARS-CoV-2 M_{pro} using `AutoDock Vina` in `--minimize` mode, with a 5 Å buffer centered on the reference fragment ensemble. As a post hoc sanity check, we computed the percentage of SA-filtered molecules (i.e., those passing xTB + PB checks and SA ≤ 4.5) that do not exhibit steric clashes following docking.