Generative inference unifies feedback processing for learning and perception in natural and artificial vision

Tahereh Toosi and Kenneth D. Miller

Center for Theoretical Neuroscience
Zuckerman Mind Brain Behavior Institute, Columbia University, New York, NY, USA

Abstract

We understand how neurons respond selectively to patterns in visual input to support object recognition; however, how these circuits support perceptual grouping, illusory percepts, and imagination is not understood. These perceptual experiences are thought to require combining what we have learned about the world with incoming sensory signals, yet the neural mechanism for this integration remains unclear. Here we show that networks tuned for object recognition implicitly learn the distribution of their input, which can be accessed through feedback connections that tune synaptic weights. We introduce Generative Inference, a computational framework in which feedback pathways that adjust connection weights during learning are repurposed during perception to combine learned knowledge with sensory input, fulfilling flexible inference goals such as increasing confidence. Generative Inference enables networks tuned solely for recognition to spontaneously produce perceptual grouping, illusory contours, shape completion, and pattern formation resembling imagination, while preserving their recognition abilities. The framework reproduces neural signatures observed across perceptual experiments: delayed responses in feedback-receiving layers of early visual cortex that disappear when feedback connections are disrupted. We show that, under stated assumptions, gradients of classification error approximate directions that are informative about the data distribution, establishing a theoretical connection between recognition and generation. Together, these findings show that pattern recognition and pattern generation rely on a shared computational substrate through dual use of feedback pathways. This principle explains how neural systems recognize familiar objects reliably while remaining flexible enough to interpret incomplete or ambiguous information, and suggests that reusing learning signals for perception may be a general feature of both biological brains and artificial networks.

Main

Artificial neural networks (ANNs) show remarkable convergence with both brain activation patterns across various domains. Neural activity patterns in visual cortex are accounted for by hierarchical vision models trained on object recognition[1–3], neural activity patterns in auditory cortex are captured by spectro-temporal models trained on auditory tasks[4], and neural activity patterns in language regions are explained by transformer models trained on language processing[5,6]. Despite this striking alignment between artificial and biological neural representations, a crucial mystery remains: the rich phenomenology of human perception bears no clear relationship to the computational operations of these models. Visual illusions and Gestalt principles reveal this explanatory gap most starkly: we perceive vivid contours, coherent objects, and meaningful structures that exist nowhere in the physical stimulus. What accounts for this failure of neural networks that otherwise successfully capture the information-processing machinery of vision?

The answer may lie in recognizing that while models excel at stimulus-driven pattern recognition, they lack mechanisms to integrate learned priors with incoming sensory evidence, a process central to perception. Human perception does not operate as a passive feature detector that simply registers whatever patterns stimulate the retina. Instead, it is an inference system that constructs interpretations by combining sensory data with prior knowledge. What we experience as distinct visual phenomena, from precise object recognition to the ethereal constructions of imagination, actually represent points along a single computational continuum (Figure 1 **A**). At one end, we find rapid, bottom-up processing that enables immediate recognition of clear visual signals[7]. At the other end lie the purely top-down constructions of mental imagery and dreams, where the visual system generates percepts independent of external input. The critical domain lies between these extremes: a rich middle ground where perception arises from a sophisticated inferential process that integrates sensory data with learned priors to fill gaps, resolve ambiguities, and extract coherent interpretations that the brain determines are implied by the sensory input.

Converging evidence suggests that the brain integrates learned priors with incoming sensory input through a generative process mediated by feedback from higher visual areas, especially when perception cannot rely on feedforward sensory cues alone. This evidence shows that, while clear, undistorted stimuli elicit rapid, primarily feedforward-driven responses[7,8], ambiguous[9], incomplete[10–12] or unusual stimuli[13] engage slower, feedback-dependent mechanisms that exhibit characteristic delayed responses and laminar-specific activation patterns[14–17]. These experiments reveal three hallmark signatures of the prior integration process (Figure 1**B**): (1) **temporal delays** of 70–100ms for ambiguous stimuli in early visual areas compared to 30–40ms for real contours[15,17], (2) **feedback dependence**, where optogenetic inhibition of higher areas eliminates responses to

illusory but not real stimuli[16;18], and (3) **laminar specificity**, with responses concentrated in feedback-receiving layers (L2/3, L5/6) rather than the primary input layer (L4)[15;16;19].

We hypothesize that feedback pathways serve dual computational roles in cortical processing. During learning, feedback carries error signals that guide synaptic modification[20], while during perception, the same pathways can implement inference processes as discussed above. Here we introduce the computational principle of Generative Inference, which formalizes this dual role, demonstrating how the same feedback pathways used during learning can be repurposed for inference (Figure 1**C**). During learning, feedback carries error signals to update synaptic weights, whether through gradient descent, as used in the backpropagation algorithm in ANNs and in postulated biological implementations[21], or through yet unknown biological algorithms. In current ANNs, these feedback connections remain unused during inference (which, in ANNs, means the process of producing network outputs with fixed weights, *i.e.* without learning; what in biology would simply be called perception). Generative Inference demonstrates that these same pathways can be activated during inference to iteratively update neural activations rather than weights, enabling dynamic integration of sensory evidence with learned priors. This reproduces a wide array of perceptual phenomena. While we demonstrate this in ANNs using backpropagation to drive feedback connections, we hypothesize that whatever algorithms are used to drive feedback-guided learning in biological systems can similarly be repurposed to integrate priors during perception.

This repurposing is theoretically grounded in the mathematical equivalence between gradient descent in weight space during learning and gradient ascent in activation space during inference. During learning, feedback pathways carry gradients $\nabla_W L$ that optimize weights via gradient descent. Our framework leverages the established theoretical link between gradients of classification loss and the score function of generative models ($\nabla_x L \approx \nabla_x log p(x)$) to show that these same feedback pathways can carry data distribution gradients during inference. This enables neural activity to navigate toward regions of higher probability under the learned statistical priors, effectively implementing score-based generative inference through the network's existing architecture. To test this theoretical framework empirically, we examined whether Generative Inference can account for the diverse perceptual phenomena where feedback modulates neural activity in biological vision. We focus on three key domains where standard feedforward models fail but biological systems excel: illusory perception, figure-ground segregation, and imagination from noise.

Generative inference: a unified framework for feedback processing

We demonstrate the capabilities of Generative Inference using the classic Kanizsa square illusion[13], in which four inducer segments positioned at the corners of an imaginary square evoke the perception of an illusory occluding shape. Neurophysiological studies have shown that neurons in early visual cortex respond to these non-existent contours, with activity emerging 70–100 ms after responses to real edges[15], and localized to feedback-receiving layers[15;19], suggesting a top-down generative process. To test whether this phenomenon can emerge in artificial neural networks, we present the Kanizsa square to a robustly trained convolutional network[22;23] and apply our Generative Inference framework, reusing the same feedback pathways involved in training to perform inference-time updates. This process—Generative Inference—progressively refines the internal representation of the stimulus, producing activation patterns that reveal the presence of the illusory square over time (Figure 2A–B).

Here, Generative inference uses an inference objective which is different from the learning objective: rather than optimizing weights for a fixed category label, the goal of inference here is to refine activations by moving away from the least likely class(es) at initial prediction. This "increase confidence" objective effectively pulls the network's internal activations toward regions of representation space that are more consistent with the learned data distribution (Supplementary B.1). As feedback updates are applied over multiple iterations, activation patterns across layers become increasingly structured, and illusory features—absent during the initial feedforward pass—emerge naturally from the model's own priors. This process provides a computational analogue of perceptual completion, mimicking the delayed and structured responses observed in the primate brain when perceiving illusory contours (Figure 2 C).

a Perceptual tasks and experiences along a continuum based on sensory information

Gestalt principles of perceptual organization

Pattern recognition | Noisy | Illusory colors | Closure | Continuation | Similarity | Figure-ground | Imagination

Sensory-driven

Prior-driven

Sensory-driven and Prior-driven

b Evidence for generative inference in neural dynamics, mediated by feedback

Figure-ground segregation | Illusory contours | Gestalt principle of continuation

Cued segment

V2 (LM)
V1
L2/3
L4
L5

Firing rate

Receptive field
— on figure
··· on uniform

Firing rate

Receptive field
— on induced line
··· on real line

Firing rate

Receptive field
— on the same group as attended
··· on the different group

Time (ms)

c Generative inference enables ANNs to use their learned priors

Learning (conventional)

Feedback carries the propagated errors
to *update the weights*

Inference (conventional)

(Learning feedback not used)

Generative Inference

Feedback carries the propagated errors
to *update the activations*

e_{learn}

Learning objective:
pattern recognition

$x \rightarrow$

$x \rightarrow$

e_{infer}

Felixable
inference objectives

$\tilde{x} \rightarrow$

Gradient descent in weight space

(Feedback during Learning)

$\nabla_w L$

$\nabla_x L \sim \nabla_x \log p(x)$

Gradient ascent in activation space

(The same feedback during Generative Inference)

$\nabla_x L$

Figure 1 Generative Inference as a unifying principle for feedback processing. a Visual perception tasks and experiences can be located on a continuum defined by degree of reliance on sensory evidence. As sensory evidence decreases, the integration of priors becomes increasingly crucial. This spectrum unifies seemingly disparate visual phenomena: from fast core object recognition, demanding minimal prior integration[1,7] through recognition despite noise or occlusion[10–12], or instances of Gestalt principles of organization such as figure-ground segregation[17,24], illusory contours[14–16,19], colors, or shapes[9], and ultimately imagination (entirely prior-dependent). While standard artificial neural networks excel at the sensory-dominated end of this spectrum, they typically fail at tasks requiring substantial prior integration[25,26]. **b** Neural dynamics reflecting prior integration reveal consistent feedback-mediated responses across diverse perceptual phenomena. Activity patterns in early visual cortices show characteristic laminar-specific signatures, with stronger modulation in feedback-receiving layers (L2/3) compared to input layers (L4). Similar feedback-driven temporal dynamics appear for figure-ground segregation[24], illusory contours[15,16,19], and Gestalt grouping principles of grouping[27]. **c** (*Top*) In conventional learning (left), feedback carries error signals e_{learn} to update synaptic weights[20]. During standard inference (middle), feedback connections which were previously used for learning are unused. Generative Inference (right) activates these same pathways to update neuronal activations based on iterative adjustments using errors for a flexible inference objective e_{infer}, enabling dynamic integration of sensory evidence with learned priors. This repurposing of feedback pathways allows networks to access their learned statistical regularities during perception. (*Bottom*) During learning (left), feedback pathways carry gradients $\nabla_W L$ for weight optimization via gradient descent. Leveraging the theoretical link we establish between gradients of loss with respect to input and gradients of the data distribution ($\nabla_x L \approx \nabla_x \log p(x)$), Generative Inference enables the same feedback pathways to carry data distribution gradients that guide activation optimization via gradient ascent (right). This allows neural activity to navigate toward regions of higher probability under the learned statistical priors (See Supplementary A).

To validate the specificity and robustness of these effects, we conduct a series of control

experiments. When the inducers are positioned too far apart, no illusory contour emerges,

matching human vision (Figure 2D). We also show that the effect is architecture-agnostic: networks

with differing structures (e.g., with or without skip connections, shallower or wider variants) still

exhibit generative contour completion, although the resulting patterns differ (Figure 2E). Critically,

the presence of the illusion depends on the statistical priors learned during training: models with

identical architecture trained on different datasets (e.g. Faces or Places) fail to generate the Kanizsa

square, whereas those trained on object-centric datasets (e.g., ImageNet) succeed (Figure 2F). These

findings highlight that both structural stimulus cues and learned priors are essential for generating

perceptual inferences, paralleling observations in biological systems and supporting the view that

feedback-driven generative inference is a plausible mechanism for visual completion.

a **Generative Inference**

Generative Inference

Inference objective = Increase confidence
by moving away from the less likely class(es) at initial inference

The least likely class(es) *Higher confidence*
(at initial inference)

iterations

itr 0 Class probabilities   *itr n* Class probabilities

1 **Feedforward** 2 **Inference objective** 3 **Feedback** 4 **Update activations** 5 **Repeat**

$\tilde{x}$ $\tilde{x}$ $\Delta\tilde{x}$ $\tilde{x} + \Delta\tilde{x}$

b **Emergence of illusory contours**

Iterations of generative inference

Feedback activation

Forward activation

no contour   Induced contour

c **Comparison to neural data**

Data   **Model**
(without fitting)

V1 neuron response

Firing rate   Unit activations

Time (ms)   Iterations

d **Effect of stimulus**

Input   Feedback activation / Forward activation

e **Effect of architectures**

Input   **No skip**   **Shallower**   **Wider**

f **Effect of data priors**

Objects   **Faces**   **Places**

g **Recurrent neural networks and predictive coding do not complete the pattern**

Recurrent Neural Networks
(CORNet-S)

input   conv gate   output

Feedback activation / Forward activation

Predictive coding (at scale)
(PredNetBpE)

image (r_0) r_1 r_2 r_3 r_4 r_5 r_6 r_7 r_8 classification

Feedback activation / Forward activation

Figure 2 Generative Inference produces illusory contour perception through feedback processing. **a** Kanizsa square[13] is presented to a generic convolutional neural network[22] trained for robust object recognition[28] on ImageNet[29]. Generative Inference reuses the feedback pathway involved in training to update activations at inference time, driven by a novel inference objective: increase confidence. Generative Inference implements an iterative procedure: (1) Feedforward pass: compute initial class probabilities and identify the least confident class; (2) Inference objective: select the least confident class as target for gradient computation; (3) Feedback error propagation: compute gradients of negative log-likelihood with respect to input activations, using the same feedback pathways employed during training; (4) Constrained activation update: move representations away from the least confident class by applying normalized gradients plus stochastic noise, while constraining updates within an ϵ-ball of the original input; (5) Iteration control: repeat steps 2-4 for T iterations. This objective iteratively shifts the network's internal representations away from less likely classes—those initially assigned low confidence—toward more confident interpretations consistent with learned priors. Black dashed line shows the temporal profile of neural responses to real contours, while red line shows the delayed emergence of responses to illusory contours. **b** Progressive emergence of illusory contours through feedback processing. Top row shows feedback activation patterns evolving over iterations, while bottom row shows corresponding forward activations, demonstrating how the Kanizsa square gradually emerges. [14–16;19;30]. **c** Comparison between neural data and model results, showing how illusory contour responses emerge with a characteristic delay compared to responses to real contours, matching observations in biological visual systems. **d** Control experiment showing specificity: when inducer segments are placed too far apart, illusory contours fail to form, consistent with perceptual thresholds observed in humans[31]. **e** Different network architectures all demonstrate contour completion but with distinct activation patterns, showing the generality of the effect (Small, No skip connections: vgg-16, Shallower:resnet18, Wider:resnet50-Wide). **f** The effect of training data priors: networks with identical architecture (ResNet50) but trained on different datasets show varying abilities to generate illusory contours. Networks trained on Object recognition (ImageNet) readily generate the illusion, while those with the same architecture but trained only on faces[32] or scenes from places[33] fail to do so, demonstrating that the appropriate statistical priors are essential for illusory contour perception. **g** Recurrent neural networks and predictive coding at scale (both large scale and trained on ImageNet) fail to complete the edges even though they benefit from feedback processing (see Supp. F).

Generative inference explains the interpretation of ambiguous inputs by iterative accumulation of priors

The Kanizsa square is often cited as a textbook example of the Gestalt principle of closure, where the brain perceptually completes missing edges to form a coherent shape. But closure is only one of several organizational principles Gestalt theory uses to explain perception. This raises a broader question: can a single computational mechanism, such as Generative Inference, also explain other perceptual phenomena traditionally attributed to Gestalt principles, including figure-ground segregation, grouping by similarity and proximity, and contextual illusions of brightness and color?

A particularly well-studied case of perceptual ambiguity is the Rubin face-vase illusion, where the same visual input can be interpreted either as two faces in profile or as a central vase. Functional imaging studies[9] show that activity in early visual cortex reflects the observer's interpretation rather than the stimulus itself (e.g., increased V1 activity for perceived faces), suggesting an active, generative process that shapes perception to resolve ambiguity in the pattern. To test whether Generative Inference could replicate this effect, we presented the Rubin stimulus to two versions of a ResNet-50 model: one trained on face recognition and one on object recognition. Despite having identical architectures, the face-trained network inferred face-like contours through feedback,

Figure 3 **Bistable perception emerges from accumulating learned priors through feedback processing**. **a** The Rubin face-vase illusion is an example of bistable perception, where the same visual stimulus can be interpreted as either two faces in profile or a central vase, with perception spontaneously alternating between these interpretations. Neuroimaging studies show that early visual brain areas (including primary visual cortex) reflect the observer's current perceptual state rather than just the physical stimulus, with neural activity varying according to whether participants report seeing faces or the vase despite identical retinal input[9]. **b** We trained a ResNet50 network for face recognition (VGGFace2, 500 classes) and used it along an identical architecture trained on object recognition (ImageNet, 1000 classes). Critically, neither network was exposed to any instance of Rubin's vase stimuli during training, ensuring that perceptual interpretations emerge purely from learned statistical priors. **C** When presented with an ambiguous face-vase stimulus, networks with different priors generate distinct interpretations through feedback. Top: A network trained for object recognition develops vase-like features. Bottom: A network, with the same architecture, ResNet50[22], trained for face recognition generates face-like patterns. For each, evolving activation patterns are shown across feedback iterations (left to right).

while the object-trained network produced vase-like interpretations. These interpretations did not emerge during the initial feedforward pass, but built up over inference iterations via feedback updates, demonstrating that perception depends jointly on stimulus structure and learned priors.

Another foundational Gestalt principle is figure-ground segregation, which allows the visual system to distinguish objects (figures) from their background. Even low-level texture cues can elicit this effect, as demonstrated in macaque V1 neural recordings where neurons respond more strongly to figure regions than to uniform textures, even when local features are identical—an effect that emerges with a 30-40 ms delay[17;24], implicating feedback-driven modulation. To test whether Generative Inference could account for this low-level texture-based segregation (in contrast to higher-level shape processing seen in the face-vase illusion), we devised an alternative

inference objective called Prior-Guided Drift Diffusion, which requires iteratively moving away from a noisy interpretation of input in intermediate layers (See Supp. B.2). Using Generative Inference by PGDD, we observed a similar enhancement of activations for figure regions in texture-defined stimuli (Figure 4A). The model progressively amplified boundaries and suppressed background texture, recapitulating both the timing and spatial selectivity of figure-ground effects observed in the cortex.

We next examined the Gestalt principles of continuation and similarity, which govern perceptual grouping: elements that are near each other or share visual features (e.g., color, shape) tend to be perceived as belonging to the same group[34]. In monkey electrophysiological studies, attentional modulation elicited on one cued element of a grouped set spreads to other uncued elements—suggesting that grouping is implemented via a delayed, feedback-mediated process[27]. Generative Inference replicates this effect: when stimuli contained multiple candidate groupings, feedback-driven updates selectively enhanced activity for elements sharing visual attributes or spatial proximity, even in the absence of explicit labels or attention (Figure 4B-C). These groupings were not hard-coded, but emerged from the network's learned priors and the structure of the stimulus.

Beyond shape and grouping, visual illusions of brightness, color, and contrast also reflect prior-dependent perception. In neon color spreading, for example, observers report illusory color filling-in across regions that lack physical color[18;35;36]. Similar contextual effects appear in Ehrenstein's illusion[37], the Cornsweet effect[38], and checker shadow illusions[39], where identical physical stimuli appear different due to their context. Generative Inference accounts for all of these by propagating activation through feedback: color and contrast gradients emerge progressively over inference iterations, driven by the model's internal priors (Figure 4D-H). While direct electrophysiological recordings for many of these illusions are limited[36], recent studies in mice have shown delayed V1 responses consistent with neon color filling-in[40], suggesting that feedback mechanisms similar to those implemented in our framework may underlie these perceptual phenomena in the brain.

Together, these results demonstrate that a single computational mechanism, Generative Inference, can account for a broad class of perceptual phenomena (Figure 1A) traditionally explained by distinct Gestalt principles. This finding challenges the century-old view that perceptual organization requires specialized, hard-wired mechanisms for different visual effects. Rather than invoking separate processes for closure, grouping, or figure-ground segregation, our framework shows that learned priors, integrated via feedback, can dynamically shape perception in a unified and biologically plausible manner.

a Figure-ground segregation

Updated activations by generative inference over iterations

b Gestalt principle of grouping by continuation

c Gestalt principle of grouping by similarity

d Neon-color spreading

e Ehrenstein's illusion

f Confetti illusion

g Cornsweet's block

h Checker shadow

Figure 4 Generative Inference unifies accounts for Gestalt principles of perceptual organization and contextual brightness illusions a Neural responses in animal studies show delayed, enhanced activation in early visual cortex for figure regions relative to uniform texture[17,24]. Generative inference replicates this effect through feedback-driven inference. The top row shows the evolution of activation updates over iterations, revealing progressive enhancement of figure boundaries. The bottom row depicts the corresponding forward activations, demonstrating that feedback refines perceptual interpretations beyond the initial feedforward pass. The bar plot quantifies the increase in unit activation for figure regions compared to uniform backgrounds, aligning with experimental data. **b** (Left) Input stimulus containing intersecting black lines with an embedded blue shape that induces the percept of neon color spreading[35,36]. (Right) Generative inference progressively enhances inferred brightness through feedback-driven updates. **c-f** Generative Inference predicts similar feedback-mediated effects for other classic visual illusions:[37] **c** Ehrenstein's illusion, where viewers typically perceive colored circular regions appearing at the intersection points of the radiating lines. Generative inference demonstrates how these intersections could transform from simple line crossings into filled-in colored circular regions **d** The confetti illusion, where identical colored spheres appear to take on different hues based on the colors of surrounding stripes. Generative inference shows how the model captures this color assimilation effect, enhancing the apparent differences between identically colored objects[41] **e** Cornsweet's brightness contrast, where physically identical regions appear to have different brightness levels[38,42], and **f** Checker shadow illusion, where two squares with identical absolute luminance appear different to human observers due to perceived shadows and context[39]. The bar graph quantifies the difference in intensity developed over 16 iterations of generative inference .

Generative Inference accounts for perceptual experiences in absence of sensory inputs

When sensory input is minimal or absent, the brain is still capable of generating rich perceptual experiences. Normally, this manifests as imagination—the ability to internally construct possible percepts or scenarios in the absence of direct stimuli[43,44]. In its pathological form, it may produce hallucinations, where internally generated content is mistaken for sensory input[45]. Both phenomena suggest that perception can be driven entirely by internal priors, without bottom-up input. This raises a key question: can a system trained only on sensory-driven tasks to recognize patterns spontaneously generate coherent structure when no reliable input is available?

To test this, we applied Generative Inference to networks given random noise as input, simulating unstructured sensory input. In the absence of meaningful feedforward activations, we used two alternative inference objectives to update the network's activations through feedback: the prior-guided drift-diffusion objective, which iteratively removes noise while preserving plausible structure, and the increased confidence objective, which moves representations away from unlikely interpretations while remaining on the learned data manifold, both of which were used above to account for illusions and Gestalt principles. Over successive feedback iterations, updates to activations instructed by generative inference objectives transformed the noise into structured patterns that reflected the network's learned priors (Fig. 5A-B). Interestingly, the layer at which feedback was applied influenced the granularity of hallucinated structure. Feedback to earlier layers resulted in finer textures and local edges, while feedback to deeper layers yielded more coherent object parts and semantic clusters (Fig. 5B). This mirrors cortical organization in biological

vision, where early visual areas encode low-level features and higher areas represent objects and concepts. These results suggest a plausible computational mechanism for how imagined content might be constructed hierarchically in the brain, layer by layer, through iterative integration of priors.

The nature of these hallucinated patterns depended strongly on the network's training domain (Fig. 5C). A network[22] trained on object recognition[29] generated geometric and object-like forms; the same architecture trained on faces[32] produced fragments resembling facial features; models trained on scenes[33] generated layouts and spatial configurations. This domain specificity demonstrates that the generative process is not universal or hand-engineered but arises naturally from the network's learned statistical regularities. In each case, the same feedback pathways used for learning were sufficient to hallucinate new structures, suggesting that imagination, like perception, may result from feedback-driven inference over internal priors.

Taken together, these findings extend the scope of Generative Inference beyond perception into the domain of internally generated experience. Without any architectural change or retraining, standard neural networks exhibit emergent generative capabilities—hallucinating content that reflects their acquired knowledge during training. This supports the idea that imagination and hallucination may arise from the same underlying mechanism as perception: the dynamic reuse of feedback to traverse the learned manifold of likely interpretations, even in the absence of sensory input.

Spontaneous imagination by different generative inference objectives

A **Increase confidence objective**

Input (same noise)   *activation updates by generative inference over iterations*

trajectory 1

trajectory 2

trajectory 3

B **Prior-guided drift diffusion objective**

last layer

forth layer

third layer

second layer

first layer

C **Other Data priors**

Faces

Places

Figure 5 Spontaneous pattern formation by generative inference When input is random noise, Generative Inference progressively imposes structured patterns reflecting the network's learned prior distribution. **a** The increase confidence objective drives activation patterns and converges on different patterns depending on the particular trajectory taken on the prior landscape. Note, this objective is necessarily applied at the last layer (one-hot representation of categories) and is back-propagated to all layers. **b** Using prior-driven drift diffusion applied at different layers (and back-propagated to all lower layers) reveals how distinct levels of the visual hierarchy contribute to pattern formation—from basic textures in lower layers to complex objects in higher layers. **c** Networks with identical architectures trained on different datasets (faces, places) generate domain-specific patterns using the same increase confidence objective, demonstrating how priors shape perceptual interpretation in the absence of structured sensory input.

Discussion

Our findings support a fundamental computational principle: the same feedback pathways that adjust synaptic weights during learning can also dynamically update neural activations during perception. This dual role of feedback explains how visual systems can seamlessly transition between rapid recognition and flexible perceptual inference. When feedback is used to update synaptic weights, it enables learning robust object representations from experience. When repurposed to update activations, it allows integration of learned statistical regularities with incoming sensory evidence, effectively implementing generative inference.

Why does generative inference work in a model that was never explicitly trained to generate? We showed that neural networks optimized to recognize patterns, mapping inputs to labels, do more than just form associations. Implicitly, they internalize the statistical structure of the data distribution. With robustness to noise training or probabilistic inference, this structure becomes accessible through the iterative accumulation of input gradients (see Supplementary A). Specifically, the network learns to shape its gradients such that updating activations in directions away from unlikely interpretations leads toward regions of higher likelihood under the learned data. In effect, the model's feedback pathways—typically reserved for error signals—can be repurposed to revise ambiguous or corrupted input in a generative direction, even though no generative objective was ever used.

The computational equivalence we have demonstrated between the gradient of classification loss and the score function of data which is typically used in generative models provides a formal mathematical basis for this unification. By showing that networks optimized for recognition inherently learn statistical regularities that can be accessed through feedback, we bridge traditionally separate paradigms in computational vision and provide a principled explanation for the diverse functions of cortical feedback. While the studied network use backpropagation of error to guide learning (and subsequently inference), which is not considered biologically plausible with our current knowledge about the neural circuits, we suggest that the more general principle is that the signals that guide learning, whether in artificial or in biological networks, will embody priors that can also guide inference.

This insight sets our approach apart from other frameworks that incorporate feedback, such as predictive coding and recurrent neural networks (see Supplementary F). Although these architectures are designed to use feedback connections, end-to-end training does not ensure that feedback carries meaningful prior information. Without an explicit mechanism that aligns feedback with the data distribution, these models often lack the ability to reshape inputs in a generative way. In contrast, our method shows that a standard feedforward network, trained to perform a task, can perform generative inference using its own gradients—offering a simple yet powerful route to modeling perception as a dynamic, prior-guided process.

Generative Inference captures key properties of cortical feedback processing observed across multiple experimental paradigms. At the level of neural circuitry, our framework provides a mechanistic explanation for how internal generative models are implemented in the brain. For decades, psychological and theoretical neuroscience frameworks have posited that the brain must contain internal generative models that enable prediction, inference, and imagination. The Hierarchical Bayesian framework proposed by Lee and Mumford[46] suggested that feedback plays a key role in combining top-down predictions with bottom-up signals, but direct computational implementations capturing this interaction in neural circuits have remained elusive. Generative Inference reveals that the very same feedback pathways that enable learning can also implement generative capabilities during perception. Our results demonstrate that this integration of priors need not be a separate computation but can be an intrinsic property of cortical processing, providing a concrete computational link between statistical inference and neural mechanisms. This unified principle supports the notion that illusions are not merely perceptual mistakes, but manifestations of the same statistical inference processes that enable robust perception under noise, effective completion of occluded objects, and generative mental imagery in the absence of sensory input.

At the activation level, our model replicates the laminar-specific response patterns observed during illusory contour perception. In both mice and monkeys, neurons in superficial layers and deep layers that receive abundant feedback connections show robust responses to Kanizsa figures, while the primary input layer (L4) remains largely unresponsive to illusory contours. This precise laminar distribution is consistent with our framework's prediction that feedback-driven inference selectively modulates layers receiving top-down inputs while preserving feedforward sensory representations. Similarly, our model reproduces the characteristic delayed onset of illusory responses (70-100ms in superficial layers versus 30-40ms for real contours), reflecting the iterative accumulation of prior information through feedback loops. Neuroimaging studies have further shown that early visual areas contain decodable information about occluded objects and bistable percepts like the Rubin face-vase illusion, demonstrating that feedback modulates neural representations even in primary sensory areas.

At the perceptual level, our framework accounts for the phenomenological experience of seeing contours, shapes, and complete objects where none physically exist. The feedback-driven activation patterns in our model directly correspond to the reported percepts in human

psychophysical experiments. For example, the model generates illusory contours only when inducer segments are properly aligned and within proximity thresholds that match human perceptual boundaries. In the face-vase illusion, the model's emergent interpretations reflect the bistable percepts reported by human observers, with different priors leading to distinct perceptual outcomes from identical inputs. Through this unified computational principle, our framework reconciles seemingly diverse experimental findings across species and experimental paradigms, suggesting that feedback-driven integration of learned priors may be a fundamental organizing principle of cortical computation in perception.

While our implementation uses backpropagation-trained networks, the theoretical connection between feedback-mediated learning and generative inference holds for any learning algorithm that estimates gradients accurately. This means that biologically plausible alternatives to backpropagation, such as feedback feedforward alignment[47], local learning rules with eligibility traces, or segregated dendrite models[48], would support the same computational framework as long as they approximate the true error gradients. Additionally, though our models use continuous-valued units rather than spiking neurons, Poisson spiking neural networks (SNNs) inherently implement the kind of signal averaging required for probabilistic generative inference through their Poisson encoding[49]. This suggests that as SNNs achieve recognition capabilities comparable to conventional deep networks, they could naturally implement generative inference through the same feedback pathways, providing a biologically plausible implementation of smooth inference without requiring explicit averaging over multiple noisy inputs. The stochastic nature of spike timing effectively performs the sampling needed for robust inference in a manner aligned with cortical computation.

Beyond explaining classic perceptual phenomena, our framework points toward a future where artificial systems might approach the fluid intelligence of biological vision—navigating uncertainty, completing fragmented inputs, and synthesizing novel percepts through the same adaptive mechanisms. The marriage of recognition with generative capabilities through feedback suggests a domain-general principle that likely extends beyond vision to audition, touch, and perhaps even abstract reasoning and conceptual thought. As we further explore this computational symmetry between learning and inference, we may ultimately discover that the brain's ability to both recognize and imagine—to perceive what is and envision what could be—springs from a singular computational principle expressed through the dynamic interplay of feedforward external drive and feedback internal modulation. In this light, Generative Inference offers not just a model of perception but potentially a fundamental organizing principle of intelligence itself.

References

1. Yamins, D. L. K. et al. Performance-optimized hierarchical models predict neural responses in higher visual cortex. Proceedings of the National Academy of Sciences **111**, 8619–8624 (2014).

2. Yamins, D. L. K. & DiCarlo, J. J. Using goal-driven deep learning models to understand sensory cortex. Nature Neuroscience **19**, 356–365 (2016).

3. LeCun, Y., Bengio, Y. & Hinton, G. E. Deep learning. Nature **521**, 436–444 (2015).

4. Kell, A. J. E., Yamins, D. L. K., Shook, E. N., Norman-Haignere, S. V. & McDermott, J. H. A task-optimized neural network replicates human auditory behavior, predicts brain responses, and reveals a cortical processing hierarchy. Neuron **98**, 630–644 (2018).

5. Schrimpf, M. et al. The neural architecture of language: Integrative modeling converges on predictive processing. Proceedings of the National Academy of Sciences **118**, e2105646118 (2021).

6. Tuckute, G., Kanwisher, N. & Fedorenko, E. Language in brains, minds, and machines. Annual Review of Neuroscience **47**, 277–301 (2024).

7. DiCarlo, J. J., Zoccolan, D. & Rust, N. C. How does the brain solve visual object recognition? Nature Neuroscience **15**, 415–434 (2012).

8. Kreiman, G. & Serre, T. Beyond the feedforward sweep: feedback computations in the visual cortex. Annals of the New York Academy of Sciences **1464**, 222–241 (2020).

9. Parkkonen, L., Andersson, J., Hämäläinen, M. & Hari, R. Early visual brain areas reflect the percept of an ambiguous scene. Proceedings of the National Academy of Sciences **105**, 20500–20504 (2008). https://www.pnas.org/doi/pdf/10.1073/pnas.0810966105.

10. Muckli, L. et al. Contextual feedback to superficial layers of v1. Current Biology **25**, 2690–2695 (2015). URL https://www.sciencedirect.com/science/article/pii/S0960982215010738.

11. Papale, P. et al. The representation of occluded image regions in area V1 of monkeys and humans. Curr. Biol. **33**, 3865–3871.e3 (2023).

12. Seignette, K. et al. Experience-dependent predictions of feedforward and contextual information in mouse visual cortex. bioRxiv (2024). URL https://www.biorxiv.org/content/early/2024/06/10/2024.06.10.598181. https://www.biorxiv.org/content/early/2024/06/10/2024.06.10.598181.full.pdf.

13. Kanizsa, G. et al. Margini quasi-percettivi in campi con stimolazione omogenea. Rivista di psicologia **49**, 7–30 (1955).

1. Grosof, D. H., Shapley, R. M. & Hawken, M. J. Macaque V1 neurons can signal 'illusory' contours. Nature **365**, 550–552 (1993).

2. Lee, T. S. & Nguyen, M. Dynamics of subjective contour formation in the early visual cortex. Proceedings of the National Academy of Sciences **98**, 1907–1911 (2001). https://www.pnas.org/doi/pdf/10.1073/pnas.98.4.1907.

3. Pak, A., Ryu, E., Li, C. & Chubykin, A. A. Top-down feedback controls the cortical representation of illusory contours in mouse primary visual cortex. The Journal of Neuroscience **40**, 648–660 (2019).

4. Lamme, V. A. The neurophysiology of figure-ground segregation in primary visual cortex. J. Neurosci. **15**, 1605–1615 (1995).

5. Saeedi, A. et al. Brightness illusions drive a neuronal response in the primary visual cortex under top-down modulation. Nature Communications **15**, 3141 (2024). URL https://www.nature.com/articles/s41467-024-46885-6.

6. Shin, H. et al. Recurrent pattern completion drives the neocortical representation of sensory inference (2023).

7. Francioni, V., Tang, V. D., Brown, N. J., Toloza, E. H. S. & Harnett, M. T. Vectorized instructive signals in cortical dendrites during a brain-computer interface task. bioRxiv (2023). Preprint.

8. Sacramento, J. a., Ponte Costa, R., Bengio, Y. & Senn, W. Dendritic cortical microcircuits approximate the backpropagation algorithm. In Bengio, S. et al. (eds.) Advances in Neural Information Processing Systems, vol. 31 (Curran Associates, Inc., 2018). URL https://proceedings.neurips.cc/paper_files/paper/2018/file/1dc3a89d0d440ba31729b0ba74b93a33-Paper.pdf.

9. He, K., Zhang, X., Ren, S. & Sun, J. Deep residual learning for image recognition (2015). 1512.03385.

10. Santurkar, S. et al. Image synthesis with a single (robust) classifier (2019). 1906.09453.

11. Schnabel, U. H., Bossens, C., Lorteije, J. A. M. et al. Figure-ground perception in the awake mouse and neuronal activity elicited by figure-ground stimuli in primary visual cortex. Scientific Reports **8**, 17800 (2018). Received: 13 March 2018; Accepted: 09 November 2018; Published: 12 December 2018.

12. Peters, B. & Kriegeskorte, N. Capturing the objects of vision with neural networks. Nat. Hum. Behav. **5**, 1127–1144 (2021).

13. Peters, B. et al. How does the primate brain combine generative and discriminative computations in vision? arXiv preprint arXiv:2401.06005 (2024).

Wannig, A., Stanisor, L. & Roelfsema, P. R. Automatic spread of attentional response modulation
along gestalt criteria in primary visual cortex. Nature Neuroscience **14**, 1243–1244 (2011).
Received 31 January 2011; Accepted 21 June 2011; Published 18 September 2011.

Madry, A., Makelov, A., Schmidt, L., Tsipras, D. & Vladu, A. Towards deep learning models
resistant to adversarial attacks. In International Conference on Learning Representations (2018).

Deng, J. et al. Imagenet: A large-scale hierarchical image database. In
2009 IEEE conference on computer vision and pattern recognition, 248–255 (IEEE, 2009).

de Haas, B. & Schwarzkopf, D. S. Spatially selective responses to kanizsa and occlusion stimuli in
human visual cortex. Sci. Rep. **8** (2018).

Watanabe, T. & Oyama, T. Are illusory contours a cause or a consequence of apparent differences
in brightness and depth in the kanizsa square? Perception **17**, 513–521 (1988).

Cao, Q., Shen, L., Xie, W., Parkhi, O. M. & Zisserman, A. Vggface2: A dataset for recognising faces
across pose and age. In
2018 13th IEEE International Conference on Automatic Face Gesture Recognition (FG 2018),
67–74 (IEEE, 2018).

Zhou, B., Lapedriza, A., Khosla, A., Oliva, A. & Torralba, A. Places: A 10 million image database
for scene recognition. IEEE Transactions on Pattern Analysis and Machine Intelligence **40**,
1452–1464 (2017).

Wagemans, J. et al. A century of gestalt psychology in visual perception i. perceptual grouping
and figure-ground organization. Psychological Bulletin **138**, 1172–1217 (2012). Author
manuscript; available in PMC: 2012 Nov 1.

van Tuijl, H. A new visual illusion: Neonlike color spreading and complementary color induction
between subjective contours. Acta Psychologica **39**, 441–IN1 (1975). URL
https://www.sciencedirect.com/science/article/pii/0001691875900426.

Sasaki, Y. & Watanabe, T. The primary visual cortex fills in color.
Proceedings of the National Academy of Sciences **101**, 18251–18256 (2004). URL
https://www.pnas.org/doi/abs/10.1073/pnas.0406293102.
https://www.pnas.org/doi/pdf/10.1073/pnas.0406293102.

Ehrenstein, W. Über abwandlungen der l. hermannschen helligkeitserscheinung.
Zeitschrift für Psychologie: Organ der Deutschen Gesellschaft für Psychologie (1941).

Cornsweet, T. Visual perception (Academic press, 2012).

Adelson, E. H. Checkershadow illusion. 1995.
URL http://web. mit. edu/persci/people/adelson/checkershadow_illusion. html (2005).

Saeedi, A. et al. Brightness illusions drive a neuronal response in the primary visual cortex under
top-down modulation. Nat. Commun. **15**, 3141 (2024).

Novick, D. & Kitaoka, A. The confetti illusion. Journal of Illusion **2** (2021).

Hung, C. P., Ramsden, B. M. & Roe, A. W. A functional circuitry for edge-induced brightness
perception. Nature neuroscience **10**, 1185–1190 (2007).

Pearson, J. The human imagination: the cognitive neuroscience of visual mental imagery.
Nature Reviews Neuroscience **20**, 624–634 (2019). URL
https://www.nature.com/articles/s41583-019-0202-9. Number: 10 Publisher:
Nature Publishing Group.

Conrad, K. Die beginnende schizophrenie. Versuch einer Gestaltanalyse des Wahns (1971).

Shine, J. M. et al. Imagine that: elevated sensory strength of mental imagery in individuals with
parkinson's disease and visual hallucinations. Proceedings of the Royal Society B **282**, 20142047
(2015).

Lee, T. S. & Mumford, D. Hierarchical bayesian inference in the visual cortex. JOSA A **20**,
1434–1448 (2003).

Toosi, T. & Issa, E. Brain-like flexible visual inference by harnessing feedback feedforward
alignment. In Advances in Neural Information Processing Systems, vol. 36, 56979–56997 (Curran
Associates, Inc., 2023).

Sacramento, J. a., Costa, R. P., Bengio, Y. & Senn, W. Dendritic cortical microcircuits approximate
the backpropagation algorithm. In
Proceedings of the 32nd International Conference on Neural Information Processing Systems,
NIPS'18, 8735–8746 (Curran Associates Inc., Red Hook, NY, USA, 2018).

Wu, K. et al. RSC-SNN: Exploring the trade-off between adversarial robustness and accuracy in
spiking neural networks via randomized smoothing coding. In
Proceedings of the 32nd ACM International Conference on Multimedia, 2748–2756 (ACM, 2024).
URL https://doi.org/10.1145/3664647.3680639.

Hyvärinen, A. Estimation of non-normalized statistical models by score matching.
Journal of Machine Learning Research **6**, 695–709 (2005). URL
http://jmlr.org/papers/v6/hyvarinen05a.html.

Song, Y., Garg, S., Shi, J. & Ermon, S. Sliced score matching: A scalable approach to density and
score estimation. In Proceedings of The 35th Uncertainty in Artificial Intelligence Conference,
574–584 (PMLR, 2019).

Kadkhodaie, Z. & Simoncelli, E. P. Solving linear inverse problems using the prior implicit in a
denoiser (2021). 2007.13640.

1. Whittington, J. C. R. & Bogacz, R. Theories of error back-propagation in the brain. Trends Cogn. Sci. **23**, 235–250 (2019).

2. Hooker, S., Erhan, D., Kindermans, P.-J. & Kim, B. A benchmark for interpretability methods in deep neural networks (2019). URL https://arxiv.org/abs/1806.10758. 1806.10758.

3. Grathwohl, W. et al. Your classifier is secretly an energy based model and you should treat it like one (2020). URL https://arxiv.org/abs/1912.03263. 1912.03263.

4. Santurkar, S. et al. Computer vision with a single (robust) classifier. In ArXiv preprint arXiv:1906.09453 (2019).

5. Ho, J., Jain, A. & Abbeel, P. Denoising diffusion probabilistic models (2020). URL https://arxiv.org/abs/2006.11239. 2006.11239.

6. Oymak, S., Fabian, Z., Li, M. & Soltanolkotabi, M. Generalization guarantees for neural networks via harnessing the low-rank structure of the jacobian (2019). URL https://arxiv.org/abs/1906.05392. 1906.05392.

7. Sagun, L., Evci, U., Guney, V. U., Dauphin, Y. & Bottou, L. Empirical analysis of the hessian of over-parametrized neural networks (2018). URL https://arxiv.org/abs/1706.04454. 1706.04454.

8. Hoffman, J., Roberts, D. A. & Yaida, S. Robust learning with jacobian regularization (2019). URL https://arxiv.org/abs/1908.02729. 1908.02729.

9. Nassar, J., Sokol, P., Chung, S., Harris, K. D. & Park, I. M. On 1/n neural representation and robustness. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M. F. & Lin, H. (eds.) Advances in Neural Information Processing Systems, vol. 33, 6211–6222 (Curran Associates, Inc., 2020). URL https://proceedings.neurips.cc/paper_files/paper/2020/file/44bf89b63173d40fb39f9842e308b3f9-Paper.pdf.

10. Papale, P. et al. V1 neurons are tuned to perceptual borders in natural scenes. Proc. Natl. Acad. Sci. U. S. A. **121**, e2221623121 (2024).

11. Geirhos, R. et al. Imagenet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. In International Conference on Learning Representations (2019).

12. Kubilius, J. et al. Brain-Like Object Recognition with High-Performing Shallow Recurrent ANNs. In Wallach, H. et al. (eds.) Neural Information Processing Systems (NeurIPS), 12785—-12796 (Curran Associates, Inc., 2019). URL http://papers.nips.cc/paper/9441-brain-like-object-recognition-with-high-performing-shallow-recurrent-anns.

13. Han, K. et al. Deep predictive coding network with local recurrent processing for object recognition (2018). URL https://arxiv.org/abs/1805.07526. 1805.07526.