alpseq: an open-source workflow to turbocharge nanobody discovery with high-throughput sequencing

Kathleen Zeglinski[1,2 ✉], Jakob Schuster[1], Jaison D. Sa[1,2], Amy Adair[1], Jing Deng[1], Matthew E. Ritchie[1,2], Rory Bowden[1,2], Wai-Hong Tham[1,2,3], and Quentin Gouil[1,2,4,5 ✉]

[1]Walter and Eliza Hall Institute of Medical Research, 1G Royal Parade, Parkville, Victoria, Australia
[2]Department of Medical Biology, The University of Melbourne, Parkville, Victoria, Australia
[3]Research School of Biology, Australian National University, Canberra, Australia
[4]Olivia Newton-John Cancer Research Institute, Heidelberg, Victoria, Australia
[5]School of Cancer Medicine, La Trobe University, Bundoora, Victoria, Australia

Nanobodies have emerged as promising tools for many biotechnological applications due to their small size, high stability, and remarkable binding specificity. Next-Generation Sequencing (NGS) enables deep profiling of large nanobody libraries and panning campaigns, however the scale and diversity of nanobody NGS datasets presents a significant bioinformatic challenge. To this end, we have developed *alpseq*, an optimised, open-source software pipeline designed specifically for the efficient and accurate processing of NGS data from nanobody libraries and panning campaigns. *alpseq* is also paired with a PCR-free sequencing library preparation protocol to allow researchers to easily generate their own data while avoiding biases. The *alpseq* software pipeline is composed of two parts: a pre-processing module written in Nextflow efficiently handles raw nanobody reads in a single line of code. These results are then fed into the analysis module, which contains a comprehensive suite of functions for quality control, diversity analysis, identification of enriched sequences and clustering. *alpseq* also creates a user-friendly interactive report which empowers scientists to explore their data without the need for extensive bioinformatic experience. Sophisticated panning campaign designs are supported, such as replicates and comparisons between different pans to find cross-binding leads. *alpseq* thus generates insights into the nanobody selection process and delivers a list of lead candidates for further experimental validation and downstream applications. *alpseq* is available at https://github.com/kzeglinski/alpseq.

nanobodies | biopanning | next-generation sequencing | bioinformatics | Nextflow | biologics | Illumina | display technologies
Correspondence: *zeglinski.k@wehi.edu.au, quentin.gouil@onjcri.org.au*

Introduction

Nanobodies, also known as single-domain antibodies, are the variable antigen-binding (VHH) regions from camelid heavy-chain-only antibodies (1). First discovered in 1989 in dromedary camels, heavy-chain-only antibodies are able to recognise a wide variety of antigens despite their smaller size (2). They have since been discovered in other camelids, including llamas and alpacas (3) as well as some species of cartilaginous fish, notably sharks (4). Irrespective of the species from which they are derived, the nanobodies' smaller size allows them to target obstructed epitopes, better penetrate tissues and even cross the blood-brain barrier (1). Nanobodies also have higher thermal stability and solubility than conventional monoclonal antibodies, as well as lower immunogenicity, making them attractive for clinical development (1).

Target-specific nanobodies are typically selected from libraries using display technologies such as phage display (5), yeast or ribosome display (6). These libraries are often derived from immunised animals, but may be also be naïve (from non-immunised animals) or synthetic (6). The selection process, known as 'biopanning' involves multiple rounds of selection against a target antigen, with non-binders being removed via washing to enrich for target-specific nanobodies. Following biopanning, the typical next step is to perform low-throughput Sanger sequencing of the final round output (6). This does not scale well and only captures a few hundred of the potentially tens of thousands of unique clones that remain after the panning process (7). Thus, in the field of antibody discovery, there has long been interest in coupling high-throughput, next-generation sequencing (NGS) with display technologies in order to capture a more diverse set of potential binders (7–9). Nanobodies, given their shorter length (~400 bp) and single chain, are even more suitable for NGS than antibodies (>800 bp) as they can be sequenced in their entirety with paired 2x300 bp reads. However until recently, NGS was used only 'sporadically' (6) in nanobody discovery (10–12), with a recent influx of publications suggesting that it is beginning to be more widely adopted by the field (13–16). Nevertheless, further optimisations of the sequencing method would likely increase the adoption of NGS in nanobody discovery. Currently, most studies rely on PCR-based approaches for sequencing library preparation (10, 16) which is known to introduce bias. Although the bias can be corrected bioinformatically through the use of unique molecular identifiers (UMIs) (17), a PCR-free approach would be more straightforward, eliminating the bias entirely.

Additionally, we believe a significant factor in the slow uptake of NGS by the nanobody field is the limited availability of open-source and user-friendly software with which to analyse the resulting data. Although several published studies share their analysis code, it is specific to a particular dataset or selection approach (10, 15) and bioinformatic expertise

would be required in order to replicate the results. Several commercial solutions exist (18–20) but the costs associated with these can be prohibitive and their closed-source nature can make it difficult to tailor analysis to specific projects. As nanobodies in their basic structure are similar to antibody heavy chain domains (1), it is often possible to use antibody analysis pipelines to process nanobody data, although there are some tools that require both a heavy and light chain (21, 22). Yet even in the larger field of antibody discovery, there are still few open source pipelines available, many of which are free for academic use only (23), specialise in dealing with repertoire-derived data rather than *in vitro* selection data (24, 25) or do not handle the full end-to-end analysis (from raw sequencing reads to top candidates)(26).

Open-source software has an important role in all forms of scientific data analysis, allowing researchers to freely explore their data and bioinformaticians to save time by tailoring existing code to suit their needs (27). When coupled with clearly documented laboratory protocols, open-source software has the power to democratise entire fields of research and drive innovation. To this end, we propose *alpseq*: a freely available end-to-end workflow that empowers researchers to routinely generate and analyse nanobody NGS data in-house. The insights gained through this analysis have the potential to accelerate nanobody discovery by identifying a more diverse range of sequences, and by generating large, pre-processed datasets that can be fed into various artificial intelligence algorithms.

Results

The *alpseq* sequencing workflow reliably generates large volumes of nanobody data.
The PCR-free *alpseq* library preparation protocol is outlined in Figure 1A, with further details in the Materials and Methods section (see below). Across >10 sequencing runs it has generated large volumes of data, with an average of 10 million full-length nanobody sequences per MiSeq run and 75 million per NextSeq 2000 P1 run (Figure 1B), after accounting for pairs of reads that do not merge and the phiX spike-in. Read quality in the NextSeq 2000 runs represented a significant improvement over MiSeq, particularly towards the end of read 2 (Figure 1C).

Fast and efficient nanobody data pre-processing with *alpseq*'s Nextflow pipeline.
Given the large volumes of data generated by *alpseq* (in contrast to Sanger sequencing), it was necessary to develop an efficient bioinformatic pipeline to pre-process the data prior to analysis of clone enrichment. The steps of this pipeline are outlined in Figure 2, and involve trimming and merging of reads to generate a contiguous nanobody sequence, before annotating them to identify their germline genes and CDRs. Quality control is performed throughout the pipeline, and collated in a comprehensive QC report (example report available on github). *alpseq* is written in the Nextflow workflow language (28), which efficiently parallelises the analysis of many samples (Figure 2B) at once and allows the entire pipeline to be executed with a single line of code. Nextflow also offers a graphical user interface

through the Seqera Platform (Supplementary Figure 1), facilitating the uptake of *alpseq* by users without extensive bioinformatics experience.

Despite parallelisation with Nextflow, the nanobody annotation step remains computationally intensive when performed with the gold-standard IgBLAST software (29), requiring hundreds of CPU hours for a single NextSeq run (Figure 2B). This limits the deployment of *alpseq* with IgBLAST annotation to high-performance or cloud computing systems, which can be expensive and difficult to access. To solve this issue, *alpseq* also implements a new annotation strategy using the recently released *matchbox* software (https://github.com/jakob-schuster/matchbox). *matchbox* annotates the V gene and CDR3 of nanobodies approximately 20 times faster than IgBLAST (Figure 2B), with the results being highly concordant (97.85% agreement, $r = 0.9425$; see Figure 2C). Given the speed of *matchbox*, and that the choice of annotation software has no effect on the selection of a top 100 set of sequences, *matchbox* is implemented as the default annotation method in *alpseq*. This makes analysis on personal computers possible.

Automated interactive reporting with *alpseq* facilitates discovery of enriched nanobody sequences.
Following pre-processing, *alpseq* can be used to perform enrichment analyses and reporting in two different ways: automated or manual. In the automated mode, interactive HTML reports that can be opened in any web browser are automatically generated by the *alpseq* Nextflow pipeline following template analyses specified from the samplesheet. The manual mode allows for more custom analysis via an accompanying R package (*alpseqR*) containing the comprehensive set of functions that underlie *alpseq*'s reports.

alpseq analyses nanobody sequences at the CDR3 level, and determines their enrichment by calculating their $\log_2$ fold change (logFC) across the panning process (see Materials and Methods). CDR3s are clustered using CD-HIT (30) to minimise redundancy when selecting top candidates to take forward for functional validation. Clusters with less than 100 counts per million (CPM) at the end of the panning process are discarded, as empirical validation suggests that these are likely false positive hits (Supplementary Figure 2A). Otherwise, all information about clusters is retained, as once binding data is available it allows the NGS data to be mined for related clones that may have better binding affinity or developability. These clusters and their associated enrichment or abundance values are presented in interactive MDS plots and cladograms (Figure 3) to visualise the overall sequence diversity landscape (which can reveal 'super-clusters' of nanobodies that may bind different epitopes of the target). The size of the dots in the MDS plot and cladogram further indicate the abundance of the enriched clones composing each cluster in the final round. The visualisations are linked to a table that can be filtered/sorted within the report, or downloaded for further external analysis (Figure 3B). With these interactive features, users are empowered to select their own favourite candidates from the NGS results, without requiring bioinformatic knowledge.

Fig. 1. Overview of the *alpseq* laboratory workflow(A) Steps involved in the *alpseq* laboratory workflow. Nanobody domain sequences are cut from nanobody library plasmids using different pairs of restriction enzymes (RE) to maintain sequence diversity near the sequencing adapters. Gel extraction is used to isolate the nanobody sequences, which are then purified with magnetic beads before having adapters ligated. Sequencing is finally performed using the NextSeq 2000 instrument with the P1 2x300 cycles kit. **(B)** Bar chart showing the number of reads generated across 12 *alpseq* runs, 1 on MiSeq and the rest on the NextSeq 2000. **(C)** FastQC mean quality score plots from representative *alpseq* runs using the Miseq (top) and NextSeq (bottom).

Fig. 2. Overview of the *alpseq* bioinformatics pipeline. (A) In the pre-processing step, paired sequencing reads are trimmed, merged and annotated to identify the nanobody sequences and their key features. Quality control of the sequencing is also performed. Finally, in the report generation step, users with bioinformatic experience can perform a manual analysis using the *alpseq* R package, or an interactive HTML report can be automatically generated using the provided sample sheet. **(B)** Performance of *alpseq* on public data from Hanke et al. (10) compared to running the steps sequentially, with and without matchbox for nanobody annotation. **(C)** Comparison of clone counts generated from the Hanke et al. (10) dataset using IgBLAST vs *matchbox*.

As there can be many hundreds of enriched nanobody clusters, it is often necessary to narrow these down further to a top 100 that can be validated in the lab. Although these can be selected manually by researchers as described above, *alpseq* also provides a list of 100 nanobodies that are likely to be good candidates for target-binding. Highly abundant (CPM > 1000) and highly enriched (logFC > 2.5) clusters are prioritised to fill this list, as ELISA and BLI data suggests that there are very few non-binders above these cutoffs (Supplementary Figure 2). The most abundant clones are chosen from each cluster. Typically, there are not 100 nanobody clusters in a dataset that meet these thresholds, so the remaining picks are taken from any enriched cluster and failing that, additional picks are made from within already-selected clusters.

alpseq effectively handles complex study designs. To highlight *alpseq*'s analysis capabilities, we describe two more advanced use cases: the handling of replicates and the comparisons of different pans.

Replicates. The enrichment of a particular sequence across multiple replicate pans has been shown to increase the robustness of candidate selection in peptide screens, given the large variability in phage display (31). Thus, *alpseq* supports the selection of top candidates from a set of replicate pans, by prioritising nanobodies that are enriched in multiple replicates when choosing the set of top 100 sequences. Replicate information is also present in all output, allowing users to see which replicate(s) a particular cluster appears in. For all pans containing replicates, a series of all-vs-all scatterplots comparing the normalised abundance of nanobodies is generated (Figure 4A). This can help to identify abnormal replicates that may be the result of an issue in the biopanning, mislabelled samples or other problems in the wet lab, which informs the selection of candidate nanobodies.

Comparing pans. *alpseq* can also be used to analyse nanobodies across multiple pans. For a single antigen, this could be to compare different panning conditions (different ways of preparing the antigen, or different display techniques). Comparing pans across multiple antigens might be used to find cross-reactive binders (e.g. nanobodies recognising multiple viral strains) or to subtract a set of enriched sequences (i.e. to find nanobodies that bind antigen x but not y). This is done by first clustering all nanobodies enriched in all pans to be compared, to account for the fact that highly similar (but not identical) clones may become enriched in different pans even if they bind in a similar way. Then, the overlap of clusters between pans is examined, and visualised in an UpSet plot (32), as well as a linked MDS plot and table, color-coded and labelled to show which pan(s) each enriched nanobody cluster belongs to (Figure 4B).

Demonstration of alpseq's capability on a public dataset. To demonstrate the robustness of the *alpseq* software pipeline to different sample preparation strategies, we ran *alpseq* on the publicly available data from Hanke *et al.* 2020 (10). *alpseq* was able to perform a complete analysis, from raw reads to interactive report in 30 minutes (using IgBLAST) or 12 minutes (using matchbox), with a single line of code. The Ty1 clone identified by Hanke *et al.* was also identified by *alpseq*, and featured in the list of top 100 sequences (Supplementary Figure 3). The interactive report generated from this data is available on github. 8 other highly similar nanobody sequences were clustered together with Ty1 by *alpseq*, and approximately 300 similar nanobody clusters were grouped together into a 'super cluster' on the MDS plot, suggesting that they may bind similar epitopes (Supplementary Figure 3).

Discussion

Given the increasingly important roles of nanobodies in research and medicine (1), streamlining their discovery process has been a long-standing goal for the field (12–14). High-throughput sequencing can achieve this by rapidly and deeply profiling phage, yeast or ribosome display outputs, thereby generating large datasets that are able to be mined for rare candidates or fed into machine learning algorithms for further insights. However, a lack of freely-available and easy to use tools with which to process this data has limited the uptake of NGS in the nanobody community (24–26). To address this gap, we have developed *alpseq*, an end-to-end wet- and dry-lab workflow that reliably generates large volumes of nanobody sequencing data, and processes it in a computationally efficient way. *alpseq* is designed to be straightforward to use, running in a single line of code, and generates interactive reports that can be used by researchers without computational skills to explore their data and choose top candidates for further experimental validation. To date, *alpseq* has been used to process hundreds of internal datasets (33, 34).

The support for analysis of complex experimental designs in *alpseq* lowers the barrier to using sophisticated and replicated selection strategies. By streamlining data generation, processing and interpretation, *alpseq* allows researchers to focus on higher-level experimental insights rather than having to spend time writing low-level data processing code. This not only enhances reproducibility but also accelerates nanobody discovery.

Beyond its automated capabilities, the *alpseq* R package provides a flexible interface that bioinformaticians can use to perform their own custom analyses. For example, all of the thresholds for abundance, enrichment and sequencing identity are tunable by the user, allowing them to chose values that are suitable for their dataset (e.g. if many unique clones remain at the end of panning, stricter thresholds can be set and vice versa if the sample is highly clonally restricted). Thus, the *alpseq* workflow can easily be applied to sequence and analyse the outputs of other display technologies, and the computationally efficient pre-processing module can be applied to any nanobody sequencing data, including repertoire sequencing. Pre-processed data from *alpseq* can also be used to train or run machine learning models for predicting developability (ideal drug properties), structure and even the residues involved in binding (35–38). Because *alpseq* is open-source, there is the flexibility to add these tools as ad-

Fig. 3. Functionality for selecting candidate binders. (A) An interactive MDS plot is used to visualise the sequence diversity landscape, revealing 'superclusters' of nanobodies that likely target the same/similar epitopes. **(B)** The plot is dymamically linked to a table that provides detailed information about the enrichment and abundance of each nanobody cluster throughout the biopanning process. **(C)** Cladogram visualisation of the diversity of the most abundant nanobody sequences in a given round.

ditional steps in the pipeline, allowing *alpseq* to continue to evolve and leverage the latest improvements in the bioinformatics and nanobody fields.

Although designed primarily for high-throughput sequencing data, the *alpseq* bioinformatics pipeline can also be used to process Sanger-derived nanobody sequences through its 'single-read' mode, allowing it to integrate seamlessly into existing workflows. This mode also allows *alpseq* to process data from long-read sequencing platforms.

In summary, *alpseq* is a comprehensive sample preparation and bioinformatic workflow that enables high-throughput sequencing of nanobody biopanning samples. *alpseq* is designed to be easy-to-use, and is freely available so as to facilitate the wider uptake of NGS in the nanobody commu-

nity. We hope that by making the generation and processing of large nanobody sequencing datasets accessible, that not only will it be easier for researchers to discover a wider range of nanobodies from their panning experiments, but also that a more open culture of data-sharing might develop which would benefit the entire research community.

Materials and Methods

NGS library preparation and sequencing. Plasmids from phage libraries were digested and purified by gel extraction to isolate the nanobody domain sequences. Three different pairs of restriction enzymes were used to maintain sequence diversity at both ends, which is critical for Illumina sequenc-

A

B

C

Fig. 4. *alpseq* supports complex study designs. (A) Scatterplots comparing the normalised abundance (CPM) of nanobodies across replicates. Density plots along the top and right sides show the distributions of nanobody abundance in each replicate. The $y = x$ line is annotated on all plots. **(B)** An UpSet plot showing the overlap of enriched nanobody sequence clusters in three pans against three different antigens. The pink dots along the x axis represent the overlaps, and the bar chart shows how many nanobody clusters belong to each overlapping category. **(C)** A variant on the interactive MDS plot and table that indicates which pan/antigen each cluster is enriched for.

ing with the 2-colour chemistry (39). Paired-end sequencing libraries were prepared using the NEBNext Multiplex Oligos for Illumina (Cat # E7395) in a PCR-free manner according to the manufacturer's instructions. The samples were size-selected using AMPure XP beads with a 0.7x ratio (Cat # A63881) and quantified by qPCR using the KAPA Library Quantification Kit (Cat # KK4873) and sequenced on an Illumina NextSeq 2000 instrument with the P1 2x300 cycle kit (with latest XLEAP-SBS chemistry) and a 20% PhiX spike-in.

Pre-processing of nanobody NGS reads. Raw sequencing reads were trimmed to remove sequencing adapters with TrimGalore (v0.6.7) (40) and then merged using FLASH (v1.2.11) (41) with a maximum overlap of 250 bp to avoid carrying adapter dimers through to the next step. Annotation of nanobody sequences was performed either using IgBLAST (v1.19.0) (29) with a reference database built from IMGT (42) or using matchbox (v0.1; available from https://github.com/jakob-schuster/matchbox). The default tool for nanobody annotation in *alpseq* is matchbox, although this can be changed using the '–use_igblast' parameter. In R (v4.4.1), nanobodies were collapsed into clones at the CDR3 level, and CDR3s with a count of 1 were removed as these likely result from sequencing errors. To allow for comparison between pans, the counts of clones were then normalised through conversion to counts per million (CPM). The entire pre-processing pipeline is automated using Nextflow (28), and can be run with a single line of code.

Determination of enriched and top 100 clones. Enrichment of clones with a count > 1 at the end of panning was measured using the $\log_2$ fold change (logFC), calculated as follows:

$$\log_2(\frac{final\ round\ CPM + 10}{round\ zero\ CPM + 10})$$

10 was added to the numerator and denominator to minimise the impact of lowly abundant clones on the analysis as their counts may not be reliable. In this particular analysis, clones with a logFC of at least 1.5 were considered enriched (although this is tunable). In order to minimise redundancy, enriched clones were then clustered by CDR3 amino acid sequences using CD-HIT (default length and identity threshold is 80%, but this can be tuned by the user) (30) and those clusters with less than 100 CPM at the end of panning were removed (as in our experience despite being enriched according to the logFC threshold, these nanobodies rarely bind the target by either ELISA or BLI, see Supplementary Figure 2). To visualise the sequence diversity landscape of enriched clones, a representative CDR3 from each cluster was chosen based on abundance. These CDR3s were then subjected to an all-vs-all pairwise alignment using the pwalign (43) (v1.4.0) R package with a gap opening penalty of -10 and a gap extension penalty of -1. The BLOSUM62 substitution matrix was used to try and account for similar chemical properties of certain amino acids. The result of this all-vs-all alignment (a distance matrix, where each element is a score measuring the similarity of two CDR3 sequences) was then used to

perform MDS plot using the prcomp_irlba function from the irlba R package (44) (v2.3.5.1). The result of this was used for the interactive MDS plots and cladograms.

To find a set of top 100 sequences for further testing, the most abundant representative from each cluster was selected, prioritising clusters with logFC > 2.5 or CPM > 1000 or that consistently increase in abundance across the rounds of panning. If this does not produce 100 unique sequences, additional picks are made from selected clusters until a top 100 can be filled. Custom selections of clones of interest are also possible, using either enrichment or abundance or both to filter/rank selections.

Overlap and subtraction. When comparing different pans, all enriched sequences from all pans are pooled and re-clustered to account for similar but not identical clones being shared across pans. These new clusters are then reported as overlapping (i.e. cross-reactive) or removed (in the case of subtraction).

ACKNOWLEDGEMENTS
We thank Daniel Brown and Jafar Jabbari for suggesting the PCR-free library preparation approach. We thank Stephen Wilcox and Sarah MacRaild from WEHI Genomics platform for their assistance in sequencing the nanobody libraries. We thank the WEHI Research Computing Platform for providing access to Seqera Cloud.

Declaration of interests. None declared

Data availability statement. The example sequencing data highlighted in this study is available at the ENA under accession PRJEB90877. The publicly available data from Hanke *et al.* (10) is available from the SRA, under BioProject ID PRJNA638614.

Funding. QG, WHT and MER are supported by Australian National Health and Medical Research Council (NHMRC) Investigator Grants (GNT2007996, GNT2016908 and GNT2017257, respectively), and GNT2001385 to WHT. The Walter and Eliza Hall Institute receives support from the Victorian State Government through its Operational Infrastructure Support Program. Additional support was provided by the Australian Government through the National Collaborative Research Infrastructure Strategy (NCRIS) program and an Australian National Health and Medical Research Council IRIISS grant (9000719).

Author contributions. Conceptualisation: KZ, QG, MER, WHT; Data acquisition: JDS, AA, JD; Data analysis: KZ; Software: KZ, JS; Interpretation: KZ, JDS, WHT, QG; Resources: MER, WHT, QG, RB Drafting of manuscript and figures: KZ; Review and editing: KZ, MER, WHT, QG. All authors read and approved the final manuscript.

Bibliography

1. Bo-Kyung Jin, Steven Odongo, Magdalena Radwanska, and Stefan Magez. NANOBODIES®: A Review of Diagnostic and Therapeutic Applications. *International Journal of Molecular Sciences*, 24(6):5994, March 2023. ISSN 1422-0067. doi: 10.3390/ijms24065994.

2. C. Hamers-Casterman, T. Atarhouch, S. Muyldermans, G. Robinson, C. Hamers, E. B. Songa, N. Bendahman, and R. Hamers. Naturally occurring antibodies devoid of light chains. *Nature*, 363(6428):446–448, June 1993. ISSN 0028-0836. doi: 10.1038/363446a0.

3. K. E. Conrath, U. Wernery, S. Muyldermans, and V. K. Nguyen. Emergence and evolution of functional heavy-chain antibodies in Camelidae. *Developmental and Comparative Immunology*, 27(2):87–103, February 2003. ISSN 0145-305X. doi: 10.1016/s0145-305x(02)00071-x.

4. A. S. Greenberg, D. Avila, M. Hughes, A. Hughes, E. C. McKinney, and M. F. Flajnik. A new antigen receptor gene family that undergoes rearrangement and extensive somatic diversification in sharks. *Nature*, 374(6518):168–173, March 1995. ISSN 0028-0836. doi: 10.1038/374168a0.

5. M. Arbabi Ghahroudi, A. Desmyter, L. Wyns, R. Hamers, and S. Muyldermans. Selection and identification of single domain antibody fragments from camel heavy-chain antibodies. *FEBS letters*, 414(3):521–526, September 1997. ISSN 0014-5793. doi: 10.1016/s0014-5793(97)01062-4.

6. Serge Muyldermans. A guide to: generation and design of nanobodies. *The FEBS journal*, 288(7):2084–2102, April 2021. ISSN 1742-4658. doi: 10.1111/febs.15515.

7. Wonjun Yang, Aerin Yoon, Sanghoon Lee, Soohyun Kim, Jungwon Han, and Junho Chung. Next-generation sequencing enables the discovery of more diverse positive clones from a phage-displayed antibody library. *Experimental & Molecular Medicine*, 49(3):e308–e308, March 2017. ISSN 2092-6413. doi: 10.1038/emm.2017.22.

8. U. Ravn, F. Gueneau, L. Baerlocher, M. Osteras, M. Desmurs, P. Malinge, G. Magistrelli, L. Farinelli, M. H. Kosco-Vilbois, and N. Fischer. By-passing in vitro screening–next generation sequencing technologies applied to antibody display and in silico candidate selection. *Nucleic Acids Research*, 38(21):e193, November 2010. ISSN 1362-4962. doi: 10.1093/nar/gkq789.

9. Ulla Ravn, Gérard Didelot, Sophie Venet, Kwok-Ting Ng, Franck Gueneau, François Rousseau, Sébastien Calloud, Marie Kosco-Vilbois, and Nicolas Fischer. Deep sequencing of phage display libraries to support antibody discovery. *Methods*, 60(1):99–110, March 2013. ISSN 10462023. doi: 10.1016/j.ymeth.2013.03.001.

10. Leo Hanke, Laura Vidakovics Perez, Daniel J. Sheward, Hrishikesh Das, Tim Schulte, Ainhoa Moliner-Morro, Martin Corcoran, Adnane Achour, Gunilla B. Karlsson Hedestam, B. Martin Hällberg, Ben Murrell, and Gerald M. McInerney. An alpaca nanobody neutralizes SARS-CoV-2 by blocking receptor interaction. *Nature Communications*, 11(1):4420, September 2020. ISSN 2041-1723. doi: 10.1038/s41467-020-18174-5.

11. Somesh Banerjee, Ajit Singh, Jagveer Rawat, Nitish Bansal, and Sushila Maan. Dataset of next-generation sequence reads of nanobody clones in phage display library derived from Indian desert camel (Camelus dromedarius L.). *Data in Brief*, 34:106663, February 2021. ISSN 2352-3409. doi: 10.1016/j.dib.2020.106663.

12. Kendrick B. Turner, Jennifer Naciri, Jinny L. Liu, George P. Anderson, Ellen R. Goldman, and Dan Zabetakis. Next-Generation Sequencing of a Single Domain Antibody Repertoire Reveals Quality of Phage Display Selected Candidates. *PLOS ONE*, 11(2):e0149393, February 2016. ISSN 1932-6203. doi: 10.1371/journal.pone.0149393.

13. Thillai V. Sekar, Eslam A. Elghonaimy, Katy L. Swancutt, Sebastian Diegeler, Isaac Gonzalez, Cassandra Hamilton, Peter Q. Leung, Jens Meiler, Cristina E. Martina, Michael Whitney, and Todd A. Aguilera. Simultaneous selection of nanobodies for accessible epitopes on immune cells in the tumor microenvironment. *Nature Communications*, 14(1):7473, November 2023. ISSN 2041-1723. doi: 10.1038/s41467-023-43038-z.

14. Hee Eon Lee, Ah Hyun Cho, Jae Hyeon Hwang, Ji Woong Kim, Ha Rim Yang, Taehoon Ryu, Yushin Jung, and Sukmook Lee. Development, High-Throughput Profiling, and Biopanning of a Large Phage Display Single-Domain Antibody Library. *International Journal of Molecular Sciences*, 25(9):4791, April 2024. ISSN 1422-0067. doi: 10.3390/ijms25094791.

15. Benjamin T. Porebski, Matthew Balmforth, Gareth Browne, Aidan Riley, Kiarash Jamali, Maximillian J. L. J. Fürst, Mirko Velic, Andrew Buchanan, Ralph Minter, Tristan Vaughan, and Philipp Holliger. Rapid discovery of high-affinity antibodies via massively parallel sequencing, ribosome display and affinity screening. *Nature Biomedical Engineering*, 8(3):214–232, October 2023. ISSN 2157-846X. doi: 10.1038/s41551-023-01093-3.

16. Michael J. Lowden, Eric K. Lei, Greg Hussack, and Kevin A. Henry. Applications of High-Throughput DNA Sequencing to Single-Domain Antibody Discovery and Engineering. In Michael Hust and Theam Soon Lim, editors, *Phage Display*, volume 2702, pages 489–540. Springer US, New York, NY, 2023. ISBN 978-1-07-163380-9 978-1-07-163381-6. doi: 10.1007/978-1-0716-3381-6_26. Series Title: Methods in Molecular Biology.

17. Mikhail Shugay, Olga V. Britanova, Ekaterina M. Merzlyak, Maria A. Turchaninova, Ilgar Z. Mamedov, Timur R. Tuganbaev, Dmitriy A. Bolotin, Dmitry B. Staroverov, Ekaterina V. Putintseva, Karla Plevova, Carsten Linnemann, Dmitriy Shagin, Sarka Pospisilova, Sergey Lukyanov, Ton N. Schumacher, and Dmitriy M. Chudakov. Towards error-free profiling of immune repertoires. *Nature Methods*, 11(6):653–655, June 2014. ISSN 1548-7105. doi: 10.1038/nmeth.2960.

18. PipeBio. https://pipebio.com/.

19. Specifica Inc. https://www.specifica.bio/abxtract/.

20. Geneious. https://www.geneious.com/features/biologics.

21. Marianne Bachmann Salvy, Luca Santuari, Emanuel Schmid-Siegert, Nikolaos Lykoskoufis, Ioannis Xenarios, and Bulak Arpat. Seq2scFv: a toolkit for the comprehensive analysis of display libraries from long-read sequencing platforms. *mAbs*, 16(1):2408344, December 2024. ISSN 1942-0862, 1942-0870. doi: 10.1080/19420862.2024.2408344.

22. Keith Mitchell, Samuel Hunter, Lutz Froenicke, Karl Murray, Matthew Settles, and James S. Trimmer. clonevdjseq: A workflow and bioinformatics management system for sequencing, archiving, and analysis of VDJ sequences from clonal libraries. *BMC Bioinformatics*, 26(1), July 2025. ISSN 1471-2105. doi: 10.1186/s12859-025-06107-2. Publisher: Springer Science and Business Media LLC.

23. Dmitriy A. Bolotin, Stanislav Poslavsky, Igor Mitrophanov, Mikhail Shugay, Ilgar Z. Mamedov, Ekaterina V. Putintseva, and Dmitriy M. Chudakov. MiXCR: software for comprehensive adaptive immunity profiling. *Nature Methods*, 12(5):380–381, May 2015. ISSN 1548-7105. doi: 10.1038/nmeth.3364.

24. Namita T. Gupta, Jason A. Vander Heiden, Mohamed Uduman, Daniel Gadala-Maria, Gur Yaari, and Steven H. Kleinstein. Change-O: a toolkit for analyzing large-scale B cell immunoglobulin repertoire sequencing data. *Bioinformatics*, 31(20):3356–3358, October 2015. ISSN 1367-4811, 1367-4803. doi: 10.1093/bioinformatics/btv359.

25. Vadim I. Nazarov, Vasily O. Tsvetkov, Siarhei Fiadziushchanka, Eugene Rumynskiy, Aleksandr A. Popov, Ivan Balashov, and Maria Samokhina. immunarch: Bioinformatics Analysis of T-Cell and B-Cell Immune Repertoires, https://immunarch.com/.

26. Christoffer V. Sørensen, Nils Hofmann, Puneet Rawat, Frederik V. Sørensen, Anne Ljungars, Victor Greiff, Andreas H. Laustsen, and Timothy P. Jenkins. ExpoSeq: simplified analysis of high-throughput sequencing data from antibody discovery campaigns. *Bioinformatics Advances*, 4(1):vbae020, 2024. ISSN 2635-0041. doi: 10.1093/bioadv/vbae020.

27. Katie Malone. Doing Data Science on the Shoulders of Giants: The Value of Open Source Software for the Data Science Community. *Harvard Data Science Review*, April 2020. doi: 10.1162/99608f92.268cc8e4.

28. Paolo Di Tommaso, Maria Chatzou, Evan W Floden, Pablo Prieto Barja, Emilio Palumbo, and Cedric Notredame. Nextflow enables reproducible computational workflows. *Nature Biotechnology*, 35(4):316–319, April 2017. ISSN 1087-0156, 1546-1696. doi: 10.1038/nbt.3820.

29. Jian Ye, Ning Ma, Thomas L. Madden, and James M. Ostell. IgBLAST: an immunoglobulin variable domain sequence analysis tool. *Nucleic Acids Research*, 41(W1):W34–W40, July 2013. ISSN 1362-4962, 0305-1048. doi: 10.1093/nar/gkt382.

30. Weizhong Li and Adam Godzik. Cd-hit: a fast program for clustering and comparing large sets of protein or nucleotide sequences. *Bioinformatics*, 22(13):1658–1659, July 2006. ISSN 1367-4811, 1367-4803. doi: 10.1093/bioinformatics/btl158.

31. Lindsey T. Brinton, Dustin K. Bauknight, Siva Sai Krishna Dasa, and Kimberly A. Kelly. PHASTpep: Analysis Software for Discovery of Cell-Selective Peptides via Phage Display and Next-Generation Sequencing. *PloS One*, 11(5):e0155244, 2016. ISSN 1932-6203. doi: 10.1371/journal.pone.0155244.

32. Alexander Lex, Nils Gehlenborg, Hendrik Strobelt, Romain Vuillemot, and Hanspeter Pfister. UpSet: Visualization of Intersecting Sets. *IEEE transactions on visualization and computer graphics*, 20(12):1983–1992, December 2014. ISSN 1941-0506. doi: 10.1109/TVCG.2014.2346248.

33. Melanie H. Dietrich, Jill Chmielewski, Li-Jin Chan, Li Lynn Tan, Amy Adair, Frankie M. T. Lyons, Mikha Gabriela, Sash Lopaticki, Toby A Dite, Laura F Dagley, Lucia Pazzagli, Priya Gupta, Mohd Kamil, Ashley M. Vaughan, Rattanaporn Rojrung, Anju Abraham, Ramin Mazhari, Rhea J. Longley, Kathleen Zeglinski, Quentin Gouil, Ivo Mueller, Stewart A. Fabb, Rekha Shandre-Mugan, Colin W. Pouton, Alisa Glukhova, Shabih Shakeel, and Wai-Hong Tham. Cryo-EM structure of endogenous *Plasmodium falciparum* Pfs230 and Pfs48/45 fertilization complex. *Science*, page eady0241, July 2025. ISSN 0036-8075, 1095-9203. doi: 10.1126/science.ady0241.

34. Frankie M. T. Lyons, Jill Chmielewski, Mikha Gabriela, Li-Jin Chan, Joshua Tong, Amy Adair, Kathleen Zeglinski, Quentin Gouil, Melanie H. Dietrich, and Wai-Hong Tham. Pfs48/45 nanobodies block Plasmodium falciparum transmission. *bioRxiv*, page 2025.04.24.650534, January 2025. doi: 10.1101/2025.04.24.650534.

35. Matthew I. J. Raybould and Charlotte M. Deane. The Therapeutic Antibody Profiler for Computational Developability Assessment. *Methods in Molecular Biology (Clifton, N.J.)*, 2313:115–125, 2022. ISSN 1940-6029. doi: 10.1007/978-1-0716-1450-1_5.

36. Shangru Li, Xiangpeng Meng, Rui Li, Bingding Huang, and Xin Wang. NanoBERTa-ASP: predicting nanobody paratope based on a pretrained RoBERTa model. *BMC bioinformatics*, 25(1):122, March 2024. ISSN 1471-2105. doi: 10.1186/s12859-024-05750-5.

37. Mahmood Kalemati, Alireza Noroozi, Aref Shahbakhsh, and Somayyeh Koohi. ParaAntiProt provides paratope prediction using antibody and protein language models. *Scientific Reports*, 14(1):29141, November 2024. ISSN 2045-2322. doi: 10.1038/s41598-024-80940-y.

38. Jeffrey A. Ruffolo, Lee-Shin Chu, Sai Pooja Mahajan, and Jeffrey J. Gray. Fast, accurate antibody structure prediction from deep learning on massive set of natural antibodies. *Nature Communications*, 14(1):2389, April 2023. ISSN 2041-1723. doi: 10.1038/s41467-023-38063-x.

39. Devin P. Bendixsen, Jessica M Roberts, Brent Townshend, and Eric J. Hayden. Phased nucleotide inserts for sequencing low-diversity RNA samples from in vitro selection experiments. *RNA (New York, N.Y.)*, 26(8):1060–1068, August 2020. ISSN 1469-9001. doi: 10.1261/rna.072413.119.

40. Felix Krueger, Frankie James, Phil Ewels, Ebrahim Afyounian, Michael Weinstein, Benjamin Schuster-Boeckler, Gert Hulselmans, and Sclamons. FelixKrueger/TrimGalore: v0.6.10 - add default decompression path, https://zenodo.org/record/5127898.

41. Tanja Magoč and Steven L. Salzberg. FLASH: fast length adjustment of short reads to improve genome assemblies. *Bioinformatics (Oxford, England)*, 27(21):2957–2963, November 2011. ISSN 1367-4811. doi: 10.1093/bioinformatics/btr507.

42. Marie-Paule Lefranc, Véronique Giudicelli, Patrice Duroux, Joumana Jabado-Michaloud, Géraldine Folch, Safa Aouinti, Emilie Carillon, Hugo Duvergey, Amélie Houles, Typhaine Paysan-Lafosse, Saida Hadi-Saljoqi, Souphatta Sasorith, Gérard Lefranc, and Sofia Kossida. IMGT®, the international ImMunoGeneTics information system® 25 years on. *Nucleic Acids Research*, 43(D1):D413–D422, January 2015. ISSN 1362-4962, 0305-1048. doi: 10.1093/nar/gku1056.

43. Patrick Aboyoun, Robert Gentleman, and Hervé Pagès. pwalign,

44. Jim Baglama, Lothar Reichel, and B.W. Lewis. Irlba: Fast truncated singular value decomposition and principal components analysis for large dense and sparse matrices, https://CRAN.R-project.org/package=irlba.