Multimodal Connectivity-based Cortical Segmentation with Graph Neural Networks

Agata Łabiak,[1,*] **Anees Kazi,**[2] **Chantal Pellegrini,**[1] **Aina Frau-Pascual,**[2,#] **and Iman Aganj** [2,*]

[1]*Chair for Computer-Aided Medical Procedures and Augmented Reality, Technical University of Munich, Germany*
[2]*Athinoula A. Martinos Center for Biomedical Imaging, Radiology Department, Massachusetts General Hospital, Harvard Medical School, MA, USA*

Correspondence*:
agata.labiak@tum.de, iaganj@mgh.harvard.edu

[#] AFP is now with *Better Care S.L.* and *Universitat Oberta de Catalunya, Spain*.

2 ABSTRACT

Due to the significant amount of time and expertise needed for manual segmentation of
the brain cortex from magnetic resonance imaging (MRI) data, there is a substantial need
for efficient and accurate algorithms to replace the need for human involvement. In this work,
we explore the capabilities of Graph Neural Networks (GNNs) to segment the brain surface
based on structural brain connectivity. We train three different GNN architectures, the Graph
Convolutional Network (GCN), the Graph Attention Network (GAT), and the Graph U-Net, and
evaluate their performances when trained on silver-standard cortical region labels created by
FreeSurfer. We take a multimodal approach to brain segmentation by examining the influence of
the structural connectivity values inferred from diffusion MRI (dMRI) in addition to using values
from structural MRI (sMRI). Our results demonstrate the utility of GNN models, particularly the
GAT architecture, which achieved Dice scores competitive to those reported in the literature with
non-graph methods. Additionally, structural connectivity derived from dMRI revealed significant
value in improving automatic segmentation, as models trained on combined attributes from dMRI
and sMRI outperformed those trained only on sMRI. Finally, we compared the GNN-based and
the FreeSurfer segmentations in their ability to predict demographic characteristics, where neither
of the two approaches was statistically significantly superior to the other.

Keywords: cortical segmentation, structural brain connectivity, connectome-based prediction, diffusion MRI (dMRI), FreeSurfer, graph
neural networks

1 INTRODUCTION

Development of *in vivo* imaging techniques such as Magnetic Resonance Imaging (MRI) has given
neuroscientists an unprecedentedly detailed and non-invasive view of the human brain. However, as the
brain is a highly complex structure consisting of billions of neurons, interpreting MRI images remains a
challenge. Brain segmentation provides a valuable way of reducing dimensionality by dividing the brain
into a limited number of regions of interest (Gallardo Diez, 2018; Wang et al., 2018; Desikan et al., 2006).
Further, segmentation greatly aids medicine and neuroscience by helping to advance our understanding of
neuroanatomy and providing deeper insight into the connection between brain structure and human clinical
and behavioral data (Gallardo Diez, 2018).

Manual brain labeling is a tedious and time-consuming process (Roy et al., 2018). As a result, there has been substantial research to fully automate the process. The vast majority of published methods use only structural MRI (sMRI) images as input, which provide important information about brain anatomy and allow measurements such as cortical thickness and curvature (Roy et al., 2018; Henschel et al., 2020, 2022; Fischl et al., 2004; Zhang et al., 2024). However, recent studies indicate that multimodal segmentation can provide novel insights and improve the utility of surface segmentation (Wang et al., 2018; Zhang et al., 2024). Specifically, measures of brain connectivity have been shown to improve brain segmentation algorithms (Eschenburg et al., 2021). Most of the current research uses functional connectivity measures obtained from functional MRI (Wang et al., 2018; Conroy et al., 2013). We explore here the impact of including structural connectivity, acquired from diffusion MRI (dMRI) based on the conductance model (Frau-Pascual et al., 2019), on cortical segmentation.

We train Graph Neural Networks (GNNs), such as the Graph Convolutional Network (GCN), the Graph Attention Network (GAT), and the Graph U-Net architectures, based on information from sMRI alone as well as combined sMRI and dMRI connectivity features, using the segmentation results obtained from FreeSurfer (Fischl, 2012) as the silver standard. Doing so enables us to compare the segmentation quality of a model trained on data from a single modality, in our case sMRI, with a model trained with the addition of connectivity data derived from dMRI. Furthermore, we explore the accuracy of different GNN architectures, as well as the influence of different sMRI-derived parameters on the final segmentation results.

We also validate the best-performing model by examining its effectiveness in a downstream task, thereby evaluating the applicability of the multimodal GNN and its possible improvement upon the silver-standard training set. Given that FreeSurfer segmentation labels are created automatically, as opposed to manually, they are not considered gold-standard ground truth (Fischl et al., 2004). Overlap measures between the labels resulting from GNN and those of FreeSurfer, therefore, cannot gauge any potential improvement over the training labels. Evaluating the usefulness of the final segmentation when applied to a downstream task, such as age prediction, however, provides us with a surrogate measure to compare the two segmentation methods.

We describe our methods in Section 2, provide our experimental results in Section 3, and discuss them and conclude the paper in Section 4.

2 METHOD

The basis of our cortical graph structure is the pial surface automatically created with FreeSurfer (Fischl, 2012) from the T1-weighted 3D MRI image. The final result is in the form of a triangular mesh approximating the pial surface, which is shown in Fig. 1 for one of the test subjects. The resulting graph is unweighted. A feature vector is assigned to each vertex (node) in the graph and can contain a combination of the characteristics derived from sMRI and dMRI.

Data collected from sMRI that we incorporate in the feature vector include (x, y, z)-coordinates of the node, cortical thickness, and curvature values. Thickness is defined as the distance between the white and pial surfaces, and curvature is defined as the inverse of the radius of the circle tangent to the surface at the position of the corresponding vertex (mean curvature was used, which is the average of the curvatures corresponding to the smallest and the largest tangent circles). Thickness and curvature are scalar values, and the coordinates are a vector of length 3. The curvature is negative in a gyrus and positive in a sulcus.

To compute structural connectivity of each vertex to the other vertices from dMRI, we used a conductance-based method (Frau-Pascual et al., 2019), which accounts for both direct and indirect brain connections

and has been shown to predict age and dementia (Frau-Pascual et al., 2021). We applied this method to
sMRI and dMRI of 97 subjects of the "100 Unrelated Subjects" group of the Human Connectome Project
(HCP) Young Adults study, which consists of healthy individuals aged 22-35 (Van Essen et al., 2013).
Three subjects were omitted due to failed connectivity computation. We were granted access to restricted
HCP data, which contains, among other sensitive information, the subjects' exact age, Mini-Mental State
Exam (MMSE) scores, and education level. The final connectivity map for each vertex is a feature vector
of length 642 (the number of vertices in the hemisphere).

We use three different GNN architectures for segmentation:

• **Graph Convolutional Network (GCN)** is based on the Convolutional Neural Network concept, but
designed to work on graph structures. With each layer, the information from the neighboring nodes is
incorporated in the next layer's feature vector (Kipf and Welling, 2017).

• **Graph Attention Network (GAT)** allows to assign a degree of usefulness to each neighboring node,
making it a more complex architecture than the GCN (Veličković et al., 2018).

• **Graph U-Net** is based on the U-Net model, a deep-learning architecture suited well for segmentation
of biomedical images. It contains Graph Pooling layers, which downsample the graph, followed by
Graph Unpooling layers, which expand it back to the original size (Gao and Ji, 2019).

3 RESULTS

86 We first report the outcomes of the GNN model training on the task of cortical segmentation with the
87 FreeSurfer segmentation as ground truth. Next, we detail the results of predicting the demographic
88 characteristics of the subjects based on the segmentation results, which compares the usefulness of the
89 model's and the FreeSurfer's outputs for a real-life task.

3.1 Graph-based cortical segmentation

91   Table 1 shows the final average Dice scores for the three model architectures and six different feature
92 vectors, for the right and left hemispheres. For ease of reading, the model trained on coordinates alone
93 is referred to as the "baseline" model. Furthermore, the model trained on coordinates, thickness, and
94 curvature will be referred to as the "fully structural" model, and the model trained on all possible attributes,
95 that is, coordinates, thickness, curvature, and structural connectivity, is called the "multimodal" model.

3.1.1 Influence of the Feature Vector

As can be seen in Table 1 for both hemispheres, using only (x, y, z) coordinates of the vertex produced the
lowest Dice scores. Adding either the thickness or curvature scalar value slightly improved the results, with
thickness often slightly more helpful than curvature. Adding them both further increased the final score,
suggesting non-overlapping information by them. The most notable finding is the results by the multimodal
model (when the connectivity values are added), where the Dice score is considerably increased, e.g. up to
a cross-hemisphere mean of 0.923 for the GAT model. Worth pointing out is also that the model trained on
the combination of (x, y, z) + conductance still outperformed all models trained on data solely from sMRI.

3.1.2 Comparison of the model architectures

105   In terms of model performance, GAT outperformed GCN in nine out of the twelve feature combinations,
106 including all that include connectivity values. Among models only trained on structural data, GCN either

107 outperformed the GAT model or scored slightly below it. Graph U-Net achieved the lowest final scores in
108 all examined cases.

109 3.1.3   Influence of the number of parameters on the model performance

As detailed in Section 3.1.1, the addition of connectivity values to the feature vector considerably
improved the segmentation results. For a fair comparison, the depth and width of the models were kept
constant regardless of the size of the feature vector. However, as shown in Table 2, the connectivity data
increase the size of the feature vector by 642, in turn increasing the number of trainable weights in our
multimodal models, whereas thickness and curvature each only add a single scalar value per vector. In
other words, when the sizes of the rest of the layers are kept constant, the number of trainable parameters
will increase with the length of the input feature vector. For example, for the GCN architecture, the number
of weights increases for a model trained solely on coordinates from 144k to 145k for a model trained on
a combination of coordinates, thickness, and curvature, and finally up to 474k for a model trained on all
available attributes.

It is worth pointing out that due to the possibility of overfitting, increasing the number of trainable
parameters does not always lead to enhanced performance. Having more parameters is therefore not
necessarily an advantage for a model trained on the connectivity values. However, for the sake of
completeness, we trained a GCN model with an increased width of the second layer on a feature vector
solely including attributes from sMRI, to see how much it would affect its performance. As can be seen in
Table 2, the final Dice score of the fully structural model is still significantly lower than the multimodal
model, even with more trainable weights in the former than in the latter. When the number of features in
the fully structural model is doubled relative to the original size, the score increases by 0.0223. However,
upon increasing the size again, the result plateaus.

129 3.2   Downstream task

130   We further evaluated the performance of the GNN model by employing it in a downstream task, which
131 tests the usefulness of the final segmentation results. As the multimodal GAT was the best-performing
132 model in both hemispheres, we chose this model for the downstream task.

133 3.2.1   Statistical correlation

To examine the applicability of the segmentation outputs of the trained model and FreeSurfer, we
correlated region-wise imaging attributes, namely average cortical thickness and average conductance, with
demographic characteristics such as age, MMSE score, and education level. Specifically, we calculated the
average thickness value for every segmented cortical region for both the FreeSurfer and the GAT model
segmentations, and then determined how the resulting values correlated with the subject's age.

When correlating the average of all within-region mean thickness values with age, for FreeSurfer
segmentation, the left hemisphere showed statistical significance with $r = -0.35$ and $p_{ave}^{FS} = 0.002$. The
negative linear correlation is consistent with what is reported in the literature (Aycheh et al., 2018). For the
right hemisphere, the values are slightly less significant, with $r = -0.23$ and $p_{ave}^{FS} = 0.02$. Model-based
segmentation performed similarly to FreeSurfer-based segmentation; for the left hemisphere, $r = -0.31$
and $p_{ave}^{model} = 0.002$, and for the right hemisphere $r = -0.23$ and $p_{ave}^{model} = 0.02$.

In region-wise correlation, four FreeSurfer regions passed the Bonferroni-corrected threshold ($\alpha_B = $
$\frac{0.05}{35} = 0.0014$) in the left hemisphere and two in the right hemisphere. For model-based segmentation,
five regions fulfilled the threshold for the left hemisphere, and two for the right hemisphere. Table 3

shows the p-values for the specific regions in which at least one of the segmentation sources passed the
significance threshold α_B. While this shows certain regions' strong correlation with cortical thickness,
the model and FreeSurfer performed similarly, as a paired Wilcoxon signed rank test on the region-wise
p-values revealed no statistically significant difference ($p_W = 0.16$ and $p_W = 0.88$ for the left and right
hemispheres, respectively).

No correlation between other brain attributes in a brain region and other demographic features passed the
α_B significance threshold.

3.2.2   Age prediction

For the prediction task, we combined regions from both hemispheres, resulting in an input vector of
length 70. We used seven available machine learning models from the Matlab regression learner toolbox.
We also trained different-sized Multi-Layer Perceptrons (MLPs). The performance was determined with
the Root Mean Square Error (RMSE), which should be at the very least below the standard deviation of the
label data, $\sigma_{age} = 3.70$ years, in order to show any form of utility.

FreeSurfer segmentation outperformed the GAT segmentation, achieving a lower RMSE for four out of
seven models when using thickness as a brain characteristic and for all models when using conductance.
However, the results for both methods were not satisfactory enough for a clear conclusion - the lowest
reported RMSE was 3.44, i.e. only 0.26 below σ_{age}, for the Regression Trees when using the FreeSurfer
segmentation and the average conductance.

MLP showed poor training results, either indicating over- or underfitting, and a large variation in the
RMSE between different validation splits. This significant training instability suggests that the model was
not capable of properly generalizing on the dataset, making the comparison between the two segmentation
methods difficult to interpret. As such, no strong conclusions could be drawn from the final results.

4   DISCUSSION

We demonstrated that GNNs are a suitable network architecture for the task of cortical surface segmentation,
comparable to the non-deep-learning based algorithms such as the one employed by FreeSurfer. While
the direct comparison with other methods in the literature is limited due to the difference in datasets and
cortical atlases used, the final reported scores of 0.768 for the model solely trained on sMRI-derived data
and, especially, 0.927 for the model trained by including connectomic data are comparable to the currently
reported state-of-the-art results (Henschel et al., 2020, 2022; Roy et al., 2018; Wu et al., 2019; Cucurull
et al., 2018; Eschenburg et al., 2021).

The considerable increase in the final Dice scores for the model trained in a multimodal fashion indicates
the significant utility of structural connectivity in the task of brain segmentation. Notably, the model trained
on the combination of (x, y, z) and conductance outperformed models trained on all available features
from sMRI, which suggests that connectivity values provide more useful information than the thickness or
curvature, even though those are the parameters that are utilized by the FreeSurfer segmentation algorithm
(Fischl et al., 2004). This addresses the gap in the current research landscape, as most of the current studies
on segmentation with connectivity explore functional connectivity obtained from fMRI (Zhang et al., 2024),
and provides an important insight into a previously under-explored research topic.

When considering network architecture, GAT was the strongest one when connectivity data were included.
However, GCN performed comparatively well when only sMRI values were considered. This is possibly
because the more complicated architecture of the GAT model performs better when it needs to generalize

on a more complex training set, and the GCN is not powerful enough to process the significantly longer
feature vector once the connectivity data are introduced, even when it has more training weights. When the
training data include only attributes from sMRI, a less powerful model such as a GCN might be enough.

It is worth noting that the Graph U-Net layers needed to be kept narrower than those in the other two
architectures due to memory constraints, resulting in a much smaller number of training weights, 170403,
for a Graph U-Net, in comparison to 473705 for a GCN and 242863 for a GAT model (for a feature vector
of length 647). However, the fact that the GAT model, while having significantly fewer training weights
than the GCN model, still managed to outperform it, indicates that a suitable model architecture should
still be able to perform well with fewer trainable parameters.

The influence of trainable weights on the network performance was further explored in Section 3.1.3.
The results from Table 2 indicate that, as expected, simply increasing the training weights is not a suitable
alternative to introducing new attributes in the feature vector and adding new information to the training
set.

In the second part of the project, we aimed to examine whether the GNN model has the capability to
generalize upon FreeSurfer labels well enough to show higher utility in a downstream task posed. However,
the results failed to unequivocally prove an improvement in the GNN-based segmentation. The RMSE
from the Matlab toolbox models did not show clear superiority of one method over the other, and the MLP
showed typical behavior of an overfitted model, suggesting that the model most likely simply learned
to memorize the input vector and their age labels, and did not have enough data to generalize on. It is
therefore not possible to state whether the model was able to improve upon the silver-standard labels it was
trained on.

For future research, training on more subjects could improve the performance of the model in the
downstream task. Nonetheless, as graph segmentation is intrinsically a node classification task, 97 subjects
were enough for high training and validation scores. However, for the model to improve upon FreeSurfer, it
may require a larger amount of data to be able to generalize upon the variation in the input. It is possible
that with the amount of data provided, the model was capable of matching FreeSurfer's segmentation, but
not necessarily improving upon it.

Additionally, it would be beneficial to see if the models are equally capable of generalizing on a more
diverse group of subjects. As stated before, the brain surfaces used for training were all from a young and
healthy population. However, for neuroscientific research as well as in clinical settings, patients and elderly
individuals are often of more interest. Even more insightful would be to compare the influence of brain
connectivity on the segmentation of the brains of patients with neurological disorders that are known to
influence both the structure and connectivity of the brain, such as Alzheimer's disease.

CONFLICT OF INTEREST STATEMENT

221 The authors declare that the research was conducted in the absence of any commercial or financial
222 relationships that could be construed as a potential conflict of interest.

AUTHOR CONTRIBUTIONS

223 AŁ: Conceptualization, Formal analysis, Investigation, Methodology, Validation, Visualization, Writing
224 – original draft, Writing – review & editing. AK: Conceptualization, Supervision, Writing – review &
225 editing. CP: Conceptualization, Supervision, Resources, Writing – review & editing. AFP: Data curation,

226 Resources, Writing – review & editing. IA: Conceptualization, Data curation, Funding acquisition, Project
227 administration, Resources, Supervision, Writing – review & editing.

FUNDING

228 This work was supported by the National Institutes of Health (NIH), specifically the National Institute
229 on Aging (RF1AG068261, R01AG068261). Computational resources were provided by the Chair for
230 Computer-Aided Medical Procedures and Augmented Reality at the Technical University of Munich.

DATA AVAILABILITY STATEMENT

Magnetic resonance images were provided by the Human Connectome Project (HCP) (Van Essen
et al., 2013), WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil):
https://www.humanconnectome.org/study/hcp-young-adult.

The conductance model of structural brain connectivity (Frau-Pascual et al., 2019) was computed using
our public toolbox at https://github.com/ainafp/FVT4DWI. FreeSurfer (Fischl, 2012) is publicly available
at https://surfer.nmr.mgh.harvard.edu. The models employed here were built using the PyTorch Geometric
library (Fey and Lenssen, 2019).

REFERENCES

Aycheh, H. M., Seong, J.-K., Shin, J.-H., Na, D. L., Kang, B., Seo, S. W., et al. (2018). Biological brain
age prediction using cortical thickness data: A large scale cohort study. *Front Aging Neurosci* 10, 252
Conroy, B. R., Singer, B. D., Guntupalli, J. S., Ramadge, P. J., and Haxby, J. V. (2013). Inter-subject
alignment of human cortical anatomy using functional connectivity. *NeuroImage* 81, 400–411. doi:https:
//doi.org/10.1016/j.neuroimage.2013.05.009
Cucurull, G., Wagstyl, K., Casanova, A., Veličković, P., Jakobsen, E., Drozdzal, M., et al. (2018).
Convolutional neural networks for mesh-based parcellation of the cerebral cortex. In *Medical Imaging
with Deep Learning*
Desikan, R. S., Ségonne, F., Fischl, B., Quinn, B. T., Dickerson, B. C., Blacker, D., et al. (2006). An
automated labeling system for subdividing the human cerebral cortex on mri scans into gyral based
regions of interest. *NeuroImage* 31, 968–980. doi:https://doi.org/10.1016/j.neuroimage.2006.01.021
Eschenburg, K. M., Grabowski, T. J., and Haynor, D. R. (2021). Learning cortical parcellations using
graph neural networks. *Front Neurosci* 15, 797500
Fey, M. and Lenssen, J. E. (2019). Fast graph representation learning with pytorch geometric
Fischl, B. (2012). Freesurfer. *Neuroimage* 62, 774–781
Fischl, B., van der Kouwe, A., Destrieux, C., Halgren, E., Ségonne, F., Salat, D. H., et al. (2004).
Automatically Parcellating the Human Cerebral Cortex. *Cerebral Cortex* 14, 11–22. doi:10.1093/cercor/
bhg087
Frau-Pascual, A., Augustinack, J., Varadarajan, D., Yendiki, A., Salat, D. H., Fischl, B., et al. (2021).
Conductance-Based structural brain connectivity in aging and dementia. *Brain Connect* 11, 566–583
Frau-Pascual, A., Fogarty, M., Fischl, B., Yendiki, A., and Aganj, I. (2019). Quantification of structural
brain connectivity via a conductance model. *Neuroimage* 189, 485–496
Gallardo Diez, G. A. (2018). *Inferring and comparing structural parcellations of the human brain using
diffusion MRI*. Theses, Université Côte d'Azur
Gao, H. and Ji, S. (2019). Graph u-nets. *CoRR* abs/1905.05178

Henschel, L., Conjeti, S., Estrada, S., Diers, K., Fischl, B., and Reuter, M. (2020). Fastsurfer - a fast
and accurate deep learning based neuroimaging pipeline. *NeuroImage* 219, 117012. doi:10.1016/j.
neuroimage.2020.117012

Henschel, L., Kügler, D., and Reuter, M. (2022). Fastsurfervinn: Building resolution-independence into
deep learning segmentation methods—a solution for highres brain mri. *NeuroImage* 251, 118933.
doi:10.1016/j.neuroimage.2022.118933

Kipf, T. N. and Welling, M. (2017). Semi-supervised classification with graph convolutional networks

Roy, A. G., Conjeti, S., Navab, N., and Wachinger, C. (2018). Quicknat: A fully convolutional network for
quick and accurate segmentation of neuroanatomy

Van Essen, D. C., Smith, S. M., Barch, D. M., Behrens, T. E., Yacoub, E., and Ugurbil, K. (2013). The
wu-minn human connectome project: An overview. *NeuroImage* 80, 62–79. doi:https://doi.org/10.1016/
j.neuroimage.2013.05.041. Mapping the Connectome

Veličković, P., Cucurull, G., Casanova, A., Romero, A., Liò, P., and Bengio, Y. (2018). Graph attention
networks

Wang, C., Ng, B., and Garbi, R. (2018). Multimodal brain parcellation based on functional and anatomical
connectivity. *Brain Connect*

Wu, Z., Zhao, F., Xia, J., Wang, L., Lin, W., Gilmore, J. H., et al. (2019). Intrinsic Patch-Based cortical
anatomical parcellation using graph convolutional neural network on surface manifold. *Med Image*
Comput Comput Assist Interv 11766, 492–500

Zhang, F., Cho, K. I. K., Seitz-Holland, J., Ning, L., Legarreta, J. H., Rathi, Y., et al. (2024). DDParcel:
Deep learning anatomical brain parcellation from diffusion MRI. *IEEE Trans Med Imaging* 43, 1191–
1202

Figure 1. Visualization of the pial surface of an example subject from the training dataset. The zoomed-in regions show the triangular tessellation of the surface in greater detail. Note that while the structure of the mesh is the final structure of the graph, the positioning of the nodes in the 3D space is not set, and was only used here to show the brain in 3D. The (x, y, z) coordinates are in fact used as part of the feature vector of each vertex.

Feature vector	GCN	GAT	Graph U-Net
Left hemisphere			
(x, y, z) coordinates	0.712 ± 0.009	0.707 ± 0.017	-
(x, y, z) coordinates + thickness	0.743 ± 0.003	0.744 ± 0.005	-
(x, y, z) coordinates + curvature	0.742 ± 0.003	0.745 ± 0.007	-
(x, y, z) coordinates + thickness + curvature	0.761 ± 0.008	0.768 ± 0.004	0.744 ± 0.003
(x, y, z) coordinates + thickness + curvature + conductance	**0.9104 ± 0.0008**	**0.927 ± 0.003**	**0.882 ± 0.003**
(x, y, z) coordinates + conductance	0.8930 ± 0.0006	0.914 ± 0.003	-
Right hemisphere			
(x, y, z) coordinates	0.708 ± 0.005	0.711 ± 0.004	-
(x, y, z) coordinates + thickness	0.735 ± 0.004	0.728 ± 0.008	-
(x, y, z) coordinates + curvature	0.725 ± 0.007	0.722 ± 0.009	-
(x, y, z) coordinates + thickness + curvature	0.753 ± 0.007	0.760 ± 0.003	0.734 ± 0.004
(x, y, z) coordinates + thickness + curvature + conductance	**0.900 ± 0.001**	**0.919 ± 0.002**	**0.876 ± 0.009**
(x, y, z) coordinates + conductance	0.886 ± 0.002	0.904 ± 0.002	-

Table 1. Final Dice scores on the test dataset for GCN, GAT, and Graph U-Net architectures for both left and right hemispheres. The highest value in each row is highlighted in green. The row with the highest values is in bold. Graph U-Net was trained only for two types of input feature vectors due to the significantly longer training time required and poor initial results.

(x, y, z) **coordinates + thickness + curvature**	
Number of parameters	**Dice Score**
145001	0.7410 ± 0.0013
285801	0.7633 ± 0.0031
499201	0.7630 ± 0.0017
(x, y, z) **coordinates + thickness + curvature + conductance**	
Number of parameters	**Dice Score**
473705	0.9104 ± 0.0008

Table 2. The influence of the number of model parameters on the final Dice score for a GCN model.

Region	FreeSurfer	GAT Model
Left Hemisphere		
Superior frontal gyrus	$p = 0.002,$ $r = -0.332$	$p = 0.0008,$ $r = -0.334$
Inferior frontal gyrus, Pars triangularis	$p = 1.86e - 07,$ $r = -0.500$	$p = 9.3e - 07,$ $r = -0.474$
Inferior parietal cortex	$p = 0.002,$ $r = -0.315$	$p = 0.001,$ $r = -0.321$
Superior temporal gyrus	$p = 0.001,$ $r = -0.321$	$p = 0.0009,$ $r = -0.332$
Banks of the superior temporal sulcus	$p = 7.0e - 05,$ $r = -0.392$	$p = 7.7e - 05,$ $r = -0.390$
Right Hemisphere		
Middle frontal gyrus, Rostral division	$p = 0.0011,$ $r = -0.325$	$p = 0.0009,$ $r = -0.332$
Middle frontal gyrus, Caudal division	$p = 0.0001,$ $r = -0.383$	$p = 0.0002,$ $r = -0.366$

Table 3. Brain regions with mean cortical thickness statistically significantly correlated with age (by at least one method), for FreeSurfer and GNN-based (GAT) segmentation.