Predicting pyrazinamide resistance in *Mycobacterium tuberculosis* using a graph convolutional network

Dylan Dissanayake[1], Joseph A. Morrone[2], Philip W. Fowler[1,3,4*]

[1]Nuffield Department of Medicine, University of Oxford, Oxford, UK.
[2]IBM TJ Watson Research Center, IBM Research, 1101 Kitchawan Rd., Yorktown Heights, 10598, NY, USA.
[3]National Institute of Health Research Oxford Biomedical Research Centre, John Radcliffe Hospital, Oxford, UK.
[4]Health Protection Research Unit in Healthcare Associated Infections and Antimicrobial Resistance, University of Oxford, Oxford, UK.

*Corresponding author(s). E-mail(s): philip.fowler@ndm.ox.ac.uk;

Abstract

Background: Pyrazinamide is an important first-line antibiotic for treating tuberculosis and resistance is primarily caused by mutations in the *pncA* gene. Traditional machine learning models have been shown to be able to predict pyrazinamide resistance with some success, but are limited in their ability to incorporate three-dimensional protein structural information. Graph neural networks offer the potential to integrate protein structure and residue-level features to better predict the impact of mutations on drug resistance.

Results: We trained a graph convolutional network model on PncA variants containing missense mutations and evaluated its ability to classify resistance to pyrazinamide. Each PncA variant was represented as an amino acid-level graph, with edges based on 3D spatial proximity and node features derived from chemical properties and mutation meta-predictors. We used AlphaFold2 to generate predicted structures of the PncA variants, which we used to create the protein graphs. The predicted structures of resistant PncA variants showed greater deviation from the wild-type structure compared to susceptible variants. Our model

achieved an F1 score of 81.6 %, sensitivity of 81.6 % and specificity of 80.4 % on the test set and either matched or exceeded the performance of a published set of traditional machine learning models. We show that both structural graph connectivity and node features contribute significantly to model performance.

Conclusions: Our study demonstrates that graph-based deep learning can effectively leverage protein structure and biochemical features to accurately predict antimicrobial resistance, in spite of being trained on a small dataset with little variation. We present this as a proof-of-concept for applying these methods to resistance phenotype prediction. Our approach has the potential to be extended to modelling more complex patterns and mechanisms of resistance, particularly in more genetically diverse pathogens.

Keywords: tuberculosis, machine learning, graph neural networks, graph convolutional networks, pyrazinamide, PncA, antimicrobial resistance

Background

Antimicrobial resistance (AMR), in particular in the context of bacterial infections, is a growing challenge and is one of the most serious threats to global public health [1–3]. *Mycobacterium tuberculosis* has long been recognised by the World Health Organization (WHO) as a bacterial pathogen that is a significant concern for global healthcare and is prone to developing resistance to major antibiotics [4–7].

Tuberculosis (TB) remains the world's leading cause of death by a single infectious agent [8]. Global TB efforts are hindered by the spread of multidrug-resistant TB (MDR-TB) strains, which are defined as being resistant to the first-line drugs rifampicin and isoniazid, and extensively drug-resistant TB (XDR-TB) strains, which are also resistant to the fluoroquinolones and at least one second-line drug [6]. TB is always treated with a regimen of multiple (usually four) antibiotics and all need to be effective to maximise the probability of a good outcome for the patient. Hence, the rising proportion of strains developing resistance to one or more antibiotics is a significant challenge [9].

Drug resistance in TB is generally acquired by mutations occurring in chromosomal genes [6]. Exposure to TB drugs results in a selection pressure that leads to the emergence of resistant *M. tuberculosis* strains via spontaneous mutations that not only lead to a poor outcome, but also often infect other people. An example of this is the acquisition of resistance to the first-line drug pyrazinamide through mutations in *pncA* [10–13]. Pyrazinamide is a prodrug that is converted to pyrazinoic acid, its active form, by the pyrazinamidase PncA, encoded by the *pncA* gene. Once converted to pyrazinoic acid, it diffuses out of the cell and disrupts membrane transport by depleting the membrane potential [14].

Mutations in *rpsA*, *panD* and *clpC1*, as well as in the efflux pumps *Rv0191*, *Rv3756c*, *Rv3008*, and *Rv1667c*, have also been associated with pyrazinamide resistance but these are rare [15–18]. The net effect is that over 90% of pyrazinamide-resistant isolates are found to have mutations in *pncA* or its promoter region [19]. In addition to this, mutations can accumulate across the entire *pncA* gene (Figure 1), as the gene is non-essential and mutations or loss of function results in little fitness cost to the bacteria [20]. Mutations are therefore frequently observed to be continually distributed across the gene and its upstream promoter [21, 22]. Pyrazinamide-resistant variants can also arise due to the presence of mutations across almost the entire length of the gene (Figure 1), unlike genes such as *rpoB* and *katG* which have well-defined so-called "resistance-determining regions" where the majority of resistance-conferring mutations to rifampicin and isoniazid, respectively, occur [23–25].

To date, methods for predicting resistance from *M. tuberculosis* whole genome sequencing data rely on catalogues [26, 27] listing mutations that have been statistically-associated with resistance to one or more drugs. This has been made possible by the availability of large clinical datasets where each sample has been both whole genome sequenced and undergone drug susceptibility testing (DST) [28]. This

Fig. 1: Both resistant and susceptible mutations are found throughout the full length of PncA. (A) PncA structure with pyrazinamide bound. Positions of mutations from the aggregated datasets are mapped onto the protein structure. Susceptible mutation positions are shown in green, resistant mutation positions are shown in red, and positions where both resistant and susceptible mutations are found are shown in blue. Bound pyrazinamide is shown in orange and the Fe^{2+} ion in purple. **(B)** Distribution of mutations across the PncA protein sequence. Only one residue (G150) in the PncA sequence did not feature any mutations in the dataset.

approach is fundamentally *inferential* and therefore cannot predict the effect of novel or rare mutations as it is constrained by e.g. the drugs that have been tested, and the mutations observed in the samples. To tackle this issue, machine learning methods, such as logistic regression, random forests, decision trees and gradient-boosted decision trees, as well as deep learning approaches using neural networks, have all been applied to the problem of *de novo* resistance prediction in *M. tuberculosis* [29, 30]. Traditional tabular machine learning methods, however, have limitations: they are restricted to using solely genetic sequence information or features of a single amino acid mutation for their predictions, and struggle to incorporate structural information and more expressive features based on the chemical properties of individual amino acids.

Previous studies have shown that using both sequence-based and structure-based features with traditional machine learning methods can improve sensitivity and specificity of resistance prediction [12, 31]. In the study by Carter *et al.* [31], logistic regression, a multi-layer perceptron (neural network), and gradient-boosted decision tree models were trained to predict if missense mutations in *pncA* conferred resistance to pyrazinamde. The train/test dataset comprised 664 non-redundant missense amino acid mutations in the *pncA* gene, each of which had a label of either resistant or susceptible derived from the associated DST data. The dataset was built by combining mutations from an *in vitro / in vivo* mutagenesis study by Yadon *et al.* [13] with mutations from the first edition of the WHO catalogue of resistance-associated mutations [32]. The validation dataset was built by aggregating previously-published clinical samples which had both a missense mutation in *pncA* and a DST result, however the reported performance on this dataset was poor [31], in part due to the variability in the DST results.

While these models included some structural features, traditional machine learning models, due to the constraints of having a tabular input, cannot access information embedded in the full three-dimensional structure of the protein. Another limitation of tabular input was that only PncA sequences with a single missense mutation could be used; any samples with two or more mutations were discarded. As a result, the models are limited to predictions based on the presence of only a single mutation in the resistance-associated gene *pncA*.

Deep learning [33] has been successfully applied to many problems in computational biology. Geometric deep learning methods, like graph neural networks (GNNs), have the significant benefit of being able to handle protein structural data as a 3D representation [34]. Graph convolutional networks (GCNs) [35] allow convolution operations, originally developed for image data processing, to be applied to molecular graph representations of proteins [36]. Such models can therefore extract interaction-aware features from nodes and their neighbours in a network. This can be useful in protein representation learning since a degree of contextual information can be captured from an amino acid's neighbouring residues in 3D space, as these relationships are expressed in the network's connectivity. Adding further information, for example edge weights based on the distance between two residues in the protein structure, can further enrich the graph representation of the protein. Graph neural networks naturally account for the translational and rotational symmetries of molecular structures and stacking multiple GCN layers allows for information to be propagated through the graph so that relationships between distant residues can be learned.

Whilst GCNs show significant potential as a method for learning which mutations confer resistance to an antibiotic, they require sufficient genetic variability and a large dataset for training, due to their inherent expressivity. The slow mutation rate of 0.2-0.5 single nucleotide polymorphisms (SNPs) per year of *M. tuberculosis*

[37] ensures that the overall genetic variability is low; this made it easier to apply tabular machine learning methods [12, 31]. In addition, the current gap in resistance prediction for TB can be small for some drugs, as catalogues generally perform well, especially for drugs with well-defined "resistance-determining regions" [38]. For pyrazinamide, an added problem is the inherent unreliability of the DST methods used to determine the resistance phenotype of *M. tuberculosis* isolates [39, 40]. This means the labelling error is high in training data which places an upper limit on the performance of machine-learning models. We can therefore expect the performance improvements from using GCNs for resistance prediction in TB to be smaller than in other pathogens which don't suffer from these shortcomings.

In this paper, we show that a GCN can accurately predict pyrazinamide resistance in PncA and has comparable performance to the best performing tabular machine learning methods. The latter is enabled by using the same dataset and train/test split as Carter *et al.* [31]. Whilst some studies have applied GCNs to AMR prediction [41–43], we believe this is the first to do this by explicitly modelling the structure of the protein in the graph. We hope this study serves as a proof of concept and leads to GCNs being applied to other pathogens, for example *E. coli* [44], where a greater degree of genetic variation constraints current prediction methods, and therefore the potential benefit of using expressive methods like GCNs, are comparatively greater.

Methods

A full end-to-end overview of the methods used to train the GCNs presented in this paper can be seen in Fig. 2.

Dataset

The train and test datasets were downloaded from the GitHub repository that accompanied the study by Carter *et al.* [45] and consisted of 664 unique missense mutations split 70:30 (Table 1). The exact same train-test split was maintained for this study. From the list of mutations, we constructed an equivalent dataset of PncA alleles, each containing a single mutation incorporated into the wild-type PncA sequence.

Table 1: Sample counts across dataset splits and phenotypes (labels).

Phenotype	Dataset		
	Full	Train Set	Test Set
All	664	464	200
S	315	218	97
R	349	246	103

We used this dataset of 664 *pncA* sequences to generate predicted structures using the ColabFold [46] implementation of AlphaFold2 [47]. For each input sequence from our constructed dataset, AlphaFold generated five structures ranked by the average predicted Local Distance Difference Test (pLDDT) - an estimate of the confidence in position of each residue. For each allele, we selected the top-ranked structure.

Since the *M. tuberculosis* structure of PncA [48] does not contain the structure of bound pyrazinamide we followed Carter *et al.* [31] and structurally fitted each

Fig. 2: Overview of the workflow from dataset creation to model training and validation. The test/train dataset from a previous study was used to facilitate comparison [31]. Mutations from published catalogues and a mutagenesis study are used to create a dataset of PncA sequences with phenotype labels. Predicted structures of these sequences are then generated using AlphaFold2, and protein graphs are constructed to be used as inputs to the GCN. Each node is attached with a node feature vector and each edge is attached with an edge weight. The GCN model is trained on the train dataset and then evaluated using bootstrapping and ten-fold cross validation.

of the AlphaFold2 predicted structures onto the experimentally-determined structure of *Acinetobacter baumannii* PncA [49], retaining the coordinates of the bound pyrazinamide and the Fe^{2+} ion in each case (Supplement).

Protein Graph Representation

Protein graphs were then derived from the structural coordinates of each of the AlphaFold2 predicted structures. Nodes in each graph corresponded to amino acid residues with edges indicating that the two connected residues lay within a defined distance which was itself determined during hyperparameter tuning. A distance of 12 Å between nodes was found to be the optimal threshold for defining an edge, where a given node's position was specified by the centre of mass of the atoms of that residue. Self-loops were not included as edges.

Each node was annotated with features that were derived using `sbmlcore` [50], a Python package that calculates amino acid features for structural machine learning tasks. Features were chosen to best encode an amino acid's chemical and structural properties and/or the effect that the amino acid substitution has on the protein's function, in cases where that residue has been mutated. Along with features based on the amino acid's chemical properties, distance features of each amino acid to the pyrazinamide molecule and Fe^{2+} ion were included (Table S1). Nodes corresponding to mutated residues had scores from meta-predictors (DeepDDG [51], RaSP [52], MAPP [53] and SNAP2 [54]) attached. All other (wild-type) nodes were given a value representing a neutral or no change in the prediction of these features (-100 for SNAP2 and 0 for DeepDDG, RaSP and MAPP). Node features were normalised to have values between zero and unity using `MinMaxScalar`. The scaler was fit only on the train set (to avoid data leakage) and then applied to the full train and test set.

An edge weight was attached to every edge in the graph. Edge weights were derived from distances between the centre of masses of residues in PncA structure.

Determing the edge weight calculation method from a choice of options (Table 2) was done as part of the hyperparameter tuning sweep. Exponentially decaying edge weights resulted in the best performance. The value of λ was also optimised during hyperparameter tuning.

Table 2: Edge weight calculation methods. The edge weight between nodes i and j is $w(i, j)$, $\mathbf{r}_i, \mathbf{r}_j \in \mathbb{R}^3$ represent the 3D position vectors of the centres of mass of residues i and j and *cutoff* is the predefined cutoff distance such that if $\|\mathbf{r}_i - \mathbf{r}_j\| < cutoff$, then an edge exists between $\mathbf{r}_i$ and $\mathbf{r}_j$. λ is a positive constant.

Method	Calculation ($w(i, j)$)
None	1
Distance	$\|\mathbf{r}_i - \mathbf{r}_j\|$
Inverse Distance	$\frac{1}{\|\mathbf{r}_i - \mathbf{r}_j\|}$
Linear Decay	$1 - \frac{\|\mathbf{r}_i - \mathbf{r}_j\|}{cutoff}$
Exponential Decay	$e^{-\lambda \cdot \|\mathbf{r}_i - \mathbf{r}_j\|}$

Graph Convolutional Network

GCNs were implemented using the PyTorch Geometric library [55] with the protein graphs as inputs. We use the graph convolution layers `GraphConv`, based on Morris *et al.* [56]. Each layer takes as an input the adjacency matrix $\mathbf{A}$ and the node-level embeddings from the previous layer. The `GraphConv` operation aggregates node embeddings from a node's neighbours and combines it with its own embedding to produce updated node embeddings for the next layer. The graph convolution operation for the input feature vector or embedding of a given node $\mathbf{x}_i$, and the resulting embedding $\mathbf{x}'_i$, is defined as

$$\mathbf{x}'_i = \mathbf{W}_1 \mathbf{x}_i + \mathbf{W}_2 \sum_{j \in \mathcal{N}(i)} w_{j,i} \cdot \mathbf{x}_j$$

where $\mathbf{W}_1$ and $\mathbf{W}_2$ are learnable weight matrices, $\mathcal{N}(i)$ is the set of all node neighbours of i, and $w_{j,i}$ is the edge weight between two given nodes j and i.

The main GCN architecture consisted of three convolution layers followed by a fully connected linear layer for final classification. `BatchNorm` layers were incorporated after each of the first two convolution to improve stability and smoothness of training. The model was trained using the `AdamW` optimiser and `CrossEntropyLoss`, to output a binary classification of resistant or susceptible. Model tuning was performed using Weights & Biases [57] which efficiently runs hyperparameter tuning sweeps and tracks experiments. The number of hidden layers, dropout probability, learning rate and weight decay were all selected by iteratively performing random sweeps. In all tuning sweeps, we maximised the F1-score of the test set.

Fig. 3: Architecture of layers in the GCN model. The batch size is b, N represents the number of nodes in the graph whilst F is the number of node features. The output dimension size for that layer, or the number of hidden channels for a given layer, is denoted by C.

We compared the GCN performance and that of several simple machine learning models (logistic regression, a simple neural network and gradient-boosted decision tree) as reported by Carter *et al.* [31]. The bootstrapping method from that study was replicated using with the same random seeds to ensure that the same samples were included in each bootstrap.

Results

A GCN model can accurately predict pyrazinamide resistance

The use of three convolution layers each followed by ReLU is standard practice for GCNs designed for protein structure and similar applications [36]. Despite this, initial experiments showed significant variability and oscillations per step in the train and test loss as training progressed. Including batch normalisation, in the form of `BatchNorm` layers after each of the first two `GraphConv` layers and before ReLU, stabilised training and reduced the variance in loss between steps. This regularisation improved training dynamics and led to more stable convergence.

The GCN was trained on the train dataset and hyper-parameter tuning sweeps were iteratively run using a random search strategy. The model was then evaluated using ten-fold cross-validation and bootstrapping on the test set. This model was compared to the previously published results [31] of three tabular machine learning methods that were trained (and tested) on the same datasets: logistic regression (LR), gradient-boosted decision tree (XB), and a single layer neural network (NN). Of these, the XB model performed best on the test set (Table 3) and after evaluating with bootstrapping (Fig. 4).

Table 3: The performance of our GCN model compared to three published simple machine learning models [31]. All models used the same train/test dataset.

Model	Test F1	Test Sensitivity	Test Specificity	Test ROC AUC	TN	FP	FN	TP
LR [31]	77.4 %	79.6 %	72.2 %	0.828	70	27	21	82
NN [31]	70.6 %	75.7 %	58.8 %	0.751	57	40	25	78
XB [31]	80.2 %	80.6 %	78.4 %	0.822	76	21	20	83
GCN (this work)	**81.6 %**	**81.6 %**	**80.4 %**	**0.828**	**78**	**19**	**19**	**84**

Our GCN model achieved higher scores in all performance metrics than XB on the test set with a sensitivity of 81.6 % and a specificity of 80.4% (Table 3). The GCN model performed equivalently well to XB after bootstrapping (Fig. 4A, paired t-test, all metrics $P \geq 0.05$, hence no significant difference). The GCN model performed significantly better than both the NN and LR models for all four performance metrics (Fig. 4A) except ROC-AUC where it was only significantly better compared to the NN model. The GCN model had two fewer major errors (ME) and one fewer very major error (VME) in the test set compared to the existing XB model (Fig. 4B). MEs are defined as susceptible samples incorrectly classified as resistant (false positives) and VMEs are resistant samples incorrectly classified as susceptible (false negatives).

Fig. 4: GCN outperforms or matches the performance of previously-published classical tabular machine learning methods. (A) The GCN model performance on the bootstrapped test set *(n=10)*. The performance of XB, NN and LR taken as reported in Carter *et al.* [31] Error bars represent 95% confidence intervals. Brackets represent significant differences (paired t-test) with respect to the GCN model. **(B)** Confusion matrices of the GCN model for the test set, compared to XB. Very Major Errors (VME) are coloured red and are considered worse than Major Errors (ME), which are coloured orange.

Node features and graph structure both contribute to GCN performance

Next we investigated the relative effects of node features and graph structure in our GCN model by performing a series of exclusion experiments. The meta-predictor features (SNAP2, DeepDDG, MAPP and RaSP) were included as node features as they are expressive measures from other neural network models that aim to quantify the impact a mutation has on a protein. SNAP2 estimates the effect on function due to a mutation [54] whilst DeepDDG and RaSP predict how a point mutation in a protein affects its stability [51, 52], and MAPP quantifies the evolutionary constraints imposed on a given position in a protein [53]. It is therefore likely that, as node features, these could provide important information about whether a certain mutation could result in a resistant or susceptible phenotype. These features were also found to be four of the top five most discriminatory individual features in the previous study [31], as measured by the ROC AUC of univariable logistic regression models trained on each of the individual features. However, these meta-predictor features could have been influencing the GCN model by, in effect, flagging where in the protein a mutation has occured, as the meta-predictors' values were only attached to mutated residues (with wild-type residues all having the same zero-equivalent value).

To investigate the contribution of these features to the GCN, we trained and tested a GCN using just SNAP2, DeepDDG, MAPP and RaSP as node features (Fig. 5 - "MPFs only"). We also trained a model having excluded these four features, hence the model only had available node features based on chemical properties and distances, (Fig. 5 - "No MPFs") and compared performance to the full GCN model. Both models performed significantly worse than the full GCN.

A major advantage provided by graph machine learning is the capacity to represent the protein structure through the connectivity of the graph. We evaluated the contribution of the graph structure to model performance by training a GCN with

Fig. 5: Exclusion of different aspects of node features or graph structure results in a significant reduction in GCN performance. GCN control experiment models performance on bootstrapped test set *(n=10)*. Error bars represent 95% confidence intervals. Brackets represent significant differences (paired t-test) only for comparisons with the full GCN model.

protein graphs containing scrambled edges (and a full set of node features). Edge scrambling was implemented by maintaining the source node of each edge and then randomly shuffling the target node and edge weight. This avoided totally destroying the graph network by keeping the the global number of edges and node degree distribution unchanged. Any reduction in performance therefore reflected a loss of meaningful topological structure. The GCN model trained on scrambled graph (Fig. 5 - "Scrambled Edges") exhibited lower performance, from which we can infer that the spatial and structural information being represented by the graph contributes positively to performance.

For each exclusion experiment, we performed independent hyper-parameter sweeps, although the optimal parameters remained consistent across setups. This suggests that the drop in performance was caused by the omission of key features or the disruption of graph connectivity, not a lack of optimisation in hyperparameter space.

Meta-predictors, particularly DeepDDG, were the features that most influenced the GCN's predictions

To gain additional insight into the relative effect that each node feature has on the model inference we applied a feature attribution method; these calculate importance scores for a given feature, representing the contribution of that feature to the model's prediction output [58]. Gradients of the model prediction with respect to the input features reflect the change in output in response to small changes in the input, hence can be a good approximation for explainability of a model's feature importance, akin to saliency maps in image classification [59]. We implemented a gradient-based feature attribution method where we calculated the gradients of the output logit for the predicted class with respect to the input features, for inferences made on samples in the test set.

The DeepDDG score had the highest relative feature importance followed by the scores of RaSP, MAPP and Snap2 (Fig. 6). DeepDDG predicts the change in stability of a protein, measured by the change in Gibbs free energy ($\Delta\Delta G$), as a consequence of a missense mutation [51]. Protein stability is often connected to function, as a loss in stability is likely to result in a loss or alteration of enzymatic function. A reduction in the enzymatic activity of PncA would prevent activation of the pro-drug pyrazinamide and could therefore lead to resistance [14]. Therefore, it is reasonable to hypothesize that a large change in $\Delta\Delta G$ of a protein results in a resistant phenotype. A molecular dynamics study also found that significant differences in $\Delta\Delta G$ between

Fig. 6: Gradient-based feature attribution showed meta-predictor features had the most influence on the model's output. Box plots of feature importances of each feature across the test set. Hydropathy WW/KD apply the Wimley–White and Kyte-Doolittle residue hydrophobicity scales, respectively, to each residue; SASA = surface accessible surface area; Hbond Acceptors/Donors count the number of hydrogen bond acceptors and donors on each sidechain; Mw = molecular weight; Rings is a count of the number of aromatic rings in the sidechain; psi and phi are the backbone Ramachandran angles

wild-type and mutant PncA can be be a useful predictor of pyrazinamide resistance [60].

Aside from meta-predictor features, whilst the remaining node features generated by `sbmlcore` individually contribute only a little to the model output, together they are predictive. This is shown by the comparative performance of GCNs trained with differing sets of features, which demonstrates that the features based on the amino acid's chemical properties and structural distances are still predictive (Fig. 5). Distances (from either the bound pyrazinamide or catalytic Fe^{2+}) did not have noticeably higher feature importances than other `sbmlcore` features (Fig. 6). This is perhaps surprising as one would expect the distance of a residue from the bound drug or the catalytic Fe^{2+} ion to inversely correlate with how likely a mutation at

that position is to result in a resistant or susceptible phenotype. For example a perturbation is likely to have more impact on the binding of the drug if it occurs to a residue near the active site, or if it is close enough to directly disrupt the catalytic Fe^{2+} ion [61]. One possible reason as to why the distance features did not exhibit higher importances could be that this distance information is implicitly represented in the graph structure or even in the meta-predictors themselves.

The evaluation of individual feature performance by univariable logistic regression by Carter *et al.* [31] also found Snap2 (0.81 AUC), DeepDDG (0.80 AUC), MAPP (0.74 AUC) and RaSP (0.73 AUC) to be the 1st, 2nd, 3rd and 5th best performing features respectively, where features were selected to be used in models if they achieved 0.55 AUC or greater.

Edge weights aid the GCN when making an inference

Next we investigated the effect that edge weights have on GCN training and performance. The `GNNExplainer` class from PyTorch Geometric provides algorithms that can generate explanations to help understand why a GNN makes a certain decision. We used `GNNExplainer` to evaluate edge importances which are calculated by masking each edge in the graph in turn and measuring the effect this has when the model subsequently makes an inference. This was run on every sample in the test set and an average edge importance was calculated for each edge, as denoted by the combination of the source and target node indexes. The frequency of each edge occurring across the dataset is not considered (although we expect this to be very similar for all samples). The average edge importances of the GCN showed a flat distribution (Fig. 7A). We hypothesised that this is because the edge weights were informing the model, with sufficient accuracy, about the relative value of each edge, so the edge masking algorithm of `GNNExplainer` suggested that the GCN was not employing any further bias when making an inference.

Fig. 7: Greater variability in average edge importance is observed for the GCN model when trained without edge weights. Heatmaps show the average edge importance across all PncA graphs in the test set for each given edge. Average edge importances are centred around the median for each model respectively. Edge importance is obtained from the edge mask calculated by `GNNExplainer` for the GCN trained with edge weights **(A)** and without edge weights **(B)**. **(C)** Kernel density estimate plot of the edge importances of edges in the GCN model with edge weights (red) and without edge weights (green). There is a significant difference between the two distributions (Wilcoxon signed-rank test $P < 0.001$).

As a comparison, we trained a GCN without edge weights and evaluated the edge importances. The edge cutoff distance (12 Å) was kept the same so that the corresponding protein graphs in the datasets of both models have identical edge

indexes. The GCN without edge weights achieved significantly lower performance, notable an F1 score of 78.3 % (Fig. 5 - "No Edge Weights"), than the full GCN (with exponential decay edge weights, $\lambda = 2$, Table 2), whilst the average edge importances showed significantly more variability (Fig. 7C). This suggests that the absence of edge weights caused the GCN to bias some edges more than others when making an inference. The pattern in the heatmap of edge importances (Fig. 7B) can be seen in some regions to resemble corresponding regions in the heatmap of edge weights (Fig. S3) used in the full GCN. This suggests the edge weights, based on inter-residue distances, are providing biologically relevant information, and the model trained without edge weights is, in some capacity, attempting to learn these relationships.

AlphaFold2 predicted structures showed small deviations that were greater in resistant PncA variants than susceptible variants

Each protein graph is constructed based on the atomic coordinates of residues in the respective protein, as specified in the PDB file. In order to predict protein structures for every PncA variant, we used the AlphaFold2 implementation, ColabFold [46]. Given the importance of DeepDDG, we hypothesised that the structures of resistant alleles might be more distorted than those of susceptible alleles and hence calculated the structural variation between the predicted structures and the wild-type structure. To control for any bias introduced by AlphaFold2, we calculated the root mean square deviation (RMSD, over Cα atoms) against an AlphaFold2 predicted structure of the wild-type sequence. For all 664 structures across both the train and test set, the mean RMSD was 0.107 Å (Table 4) and ranged from 0.031 Å to 0.540 Å, suggesting there was some predicted structural variability (Fig. S1).

Interestingly the predicted structures of resistant alleles were more likely to have higher RMSD values than susceptible alleles (Fig. 8). We also note that this trend is largely observed across the whole sequence (Fig. S4). This suggests that mutations

Table 4: The root mean square deviation (mean ± SD, Å) across dataset splits and phenotypes of the C$_\alpha$ atoms in the AlphaFold2 predicted structures relative to an AlphaFold2 predicted wild-type structure.

| Phenotype | Dataset | | |
	Full	Train Set	Test Set
All	0.107 ± 0.074	0.105 ± 0.069	0.111 ± 0.086
S	0.090 ± 0.069	0.089 ± 0.066	0.093 ± 0.075
R	0.122 ± 0.076	0.119 ± 0.069	0.127 ± 0.093

that make PncA resistant to pyrazinamide are more likely to lead to, on average, a greater perturbation to the protein's structure. Such perturbations could directly affect the binding site, resulting in the disruption of pyrazinamide binding, or could affect the stability of the protein as a whole.

Fig. 8: The AlphaFold2 predicted structures of resistant PncA alleles are more different to the wild-type sequence than susceptible alleles. (A) Kernel density estimate plot of the root mean square deviations (RMSD, Å) of predicted structures of susceptible (green) and resistant (red) PncA alleles. RMSD is measured over the C_α atoms with respect to the AlphaFold2-predicted wild-type structure. Selected structures of PncA variants (red) aligned with wild-type PncA (blue) are shown on the plot. **(B)** Box plot of RMSDs of susceptible (green) and resistant (red) PncA alleles, further split into whether they belong to the training (orange) or test (purple) sets. Resistant alleles have a significantly different RMSD distribution than susceptible variants (paired t-test $P < 0.001$).

Discussion

We have shown that a GCN trained to predict whether PncA variants confer resistance to pyrazinamide achieves comparable performance to the best performing tabular machine-learning models [31]. This is perhaps surprising as, whilst GCNs are powerful and parameter-heavy, they can be prone to overfitting and learning noise when trained on small datasets with little variation. In contrast, methods like XGBoost are well-suited for small to medium sized datasets, as we have here, and have a lower risk of noise amplification. GCNs are also more computationally expensive to train than XGBoost and other classical machine learning models and require slightly more time to make an inference. However, the inference time increases significantly when the generation of a structural prediction using AlphaFold2 (or an equivalent method) is included and accounted for.

There are several shortcomings in our approach. Better methods could be employed for attaching the drug to the AlphaFold2-predicted structures than by using a structural fit, as this assumes the mutations result in little to no perturbation to the binding site. Recent advancements in AlphaFold3, which can now perform structural predictions with ligand docking, will likely better represent the interaction between the drug and the protein [62]. This could also open the door to including the bound drug as a node(s), which might further refine our graph representation. That said, using AlphaFold2-predicted structures for each PncA allele may already provide most of the benefit by introducing variability in the graph connectivity as well as allowing for more accurate distance-based node features (distance to pyrazinamide or Fe^{2+}) and protein secondary structure-based features. As discussed in the Results, a key limitation of our feature engineering is how we have attached meta-predictor features. Since the output of these models is only attached to the nodes representing the mutated amino acid, this could act as a flag to the model indicating where the site of the mutation is. This could bias the model to learn just the amino

acid substitution and not infer from the protein as a whole when predicting the phenotype. Finally we could potentially improve our representation of amino acids by using embeddings from protein language models such as ESM3 [63].

One can expect that, with a larger dataset, GCNs will scale and generalise even better. In particular, we see significant potential benefit in the application of GCNs in predicting drug resistance in pathogens which intrinsically have greater genetic variability than *M. tuberculosis*, for example in *E. coli* [64]. GCNs can also capture certain elements that traditional machine learning methods cannot: this includes, but is not limited to, incorporating alleles with insertions and deletions, as well as the presence of multiple mutations in a single allele – all cases that were not included in our dataset so as to maintain a direct comparison with previous studies. It is our hope and intention to extend this GCN-based approach to learn, and therefore predict *de novo*, antimicrobial resistance in other pathogens.

Conclusions

We demonstrate that a GCN can predict pyrazinamide resistance in *M. tuberculosis* by learning structural and chemical features in the context of the predicted structure of each *pncA* allele. Our GCN model achieves equivalent performance to the best performing traditional machine learning methods, in spite of being trained on a small dataset with low variability. GCNs have the potential to learn and predict the antimicrobial resistance profile of genes for a far wider range of pathogens, potentially leading to significant improvements in both our understanding of resistance mechanisms and drug susceptibility testing.

Declarations

Availability of data and materials

An accompanying GitHub repository is available [65]: this contains the train/test dataset and Python code to retrain the model as well as states of the final models and code to redraw the main figures in this manuscript.

Competing interests

PWF works as a consultant by the Ellison Institute of Technology, Oxford Ltd.

Funding

This research is funded by the National Institute for Health Research (NIHR) Oxford Biomedical Research Centre (BRC) and the National Institute for Health and Care Research (NIHR) Health Protection Research Unit in Healthcare Associated Infections and Antimicrobial Resistance (NIHR207397), a partnership between the UK Health Security Agency (UKHSA) and the University of Oxford. DD is supported by the IBM Computational Discovery Programme, which is jointly funded by IBM Research and the Engineering and Physical Sciences Research Council (EPSRC). The views expressed are those of the authors and not necessarily those of the NIHR, UKHSA or the Department of Health and Social Care. For the purpose of open access, the author has applied a CC BY public copyright licence to any Author Accepted Manuscript version arising from this submission.

Authors' contributions

DD and PWF conceived of the study. DD carried out the data preparation, model building, training and analysis steps with JAM & PWF providing advice. DD, JAM and PWF wrote the manuscript.

Acknowledgements

We are grateful to Dylan Adlard and Viktoria Brunner for helpful discussions.

References

[1] Prestinaci F, Pezzotti P, Pantosti A. Antimicrobial resistance: a global multi-faceted phenomenon. Pathogens and Global Health. 2015;109(7):309–318. https://doi.org/10.1179/2047773215Y.0000000030.

[2] Mancuso G, Midiri A, Gerace E, Biondo C. Bacterial Antibiotic Resistance: The Most Critical Pathogens. Pathogens. 2021;10(10):1310. https://doi.org/10.3390/pathogens10101310.

[3] Murray CJL, Ikuta KS, Sharara F, Swetschinski L, Aguilar GR, Gray A, et al. Global burden of bacterial antimicrobial resistance in 2019: a systematic analysis. The Lancet. 2022;399(10325):629–655. https://doi.org/10.1016/S0140-6736(21)02724-0.

[4] World Health Organization.: Global tuberculosis report 2023. Available from: https://www.who.int/publications/i/item/9789240083851.

[5] Tacconelli E, Carrara E, Savoldi A, Harbarth S, Mendelson M, Monnet DL, et al. Discovery, research, and development of new antibiotics: the WHO priority list of antibiotic-resistant bacteria and tuberculosis. Lancet Infectious Diseases. 2018;18(3):318–327. https://doi.org/10.1016/S1473-3099(17)30753-3.

[6] Almeida Da Silva PEA, Palomino JC. Molecular basis and mechanisms of drug resistance in Mycobacterium tuberculosis: classical and new drugs. J Antimicrob Chemotherapy. 2011;66(7):1417–1430. https://doi.org/10.1093/jac/dkr173.

[7] Bagcchi S. WHO's Global Tuberculosis Report 2022. The Lancet Microbe. 2023;4(1):e20. https://doi.org/10.1016/S2666-5247(22)00359-7.

[8] World Health Organization.: Global tuberculosis report 2024. ISBN: 978-92-4-010153-1. Available from: https://www.who.int/publications/i/item/9789240101531.

[9] Alsayed SSR, Gunosewoyo H. Tuberculosis: Pathogenesis, Current Treatment Regimens and New Drug Targets. Int J Mol Sci. 2023;24(6):5202. https://doi.org/10.3390/ijms24065202.

[10] Ali A, Khan MT, Khan A, Ali S, Chinnasamy S, Akhtar K, et al. Pyrazinamide resistance of novel mutations in pncA and their dynamic behavior. RSC Advances. 2020;10(58):35565–35573. https://doi.org/10.1039/D0RA06072K.

[11] Allana S, Shashkina E, Mathema B, Bablishvili N, Tukvadze N, Shah NS, et al. pncA Gene Mutations Associated with Pyrazinamide Resistance in Drug-Resistant Tuberculosis, South Africa and Georgia. Emerging Infectious Diseases. 2017;23(3):491. https://doi.org/10.3201/eid2303.161034.

[12] Karmakar M, Rodrigues CHM, Horan K, Denholm JT, Ascher DB. Structure guided prediction of Pyrazinamide resistance mutations in pncA. Sci Reports. 2020;10(1):1875. https://doi.org/10.1038/s41598-020-58635-x.

[13] Yadon AN, Maharaj K, Adamson JH, Lai YP, Sacchettini JC, Ioerger TR, et al. A comprehensive characterization of PncA polymorphisms that confer resistance to pyrazinamide. Nature Communications. 2017;8(1):588. https://doi.org/10.1038/s41467-017-00721-2.

[14] Zhang Y, Shi W, Zhang W, Mitchison D. Mechanisms of Pyrazinamide Action and Resistance. Microbiology spectrum. 2013;2(4):1–12. https://doi.org/10.1128/microbiolspec.MGM2-0023-2013.

[15] Shi W, Cui P, Niu H, Zhang S, Tønjum T, Zhu B, et al. Introducing RpsA Point Mutations Δ438A and D123A into the Chromosome of Mycobacterium tuberculosis Confirms Their Role in Causing Resistance to Pyrazinamide. Antimicrob Agents Chemotherapy. 2019;63(6):e02681–18. https://doi.org/10.1128/AAC.02681-18.

[16] Gopal P, Nartey W, Ragunathan P, Sarathy J, Kaya F, Yee M, et al. Pyrazinoic Acid Inhibits Mycobacterial Coenzyme A Biosynthesis by Binding to Aspartate Decarboxylase PanD. ACS Infectious Diseases. 2017;3(11):807–819. https://doi.org/10.1021/acsinfecdis.7b00079.

[17] Yee M, Gopal P, Dick T. Missense Mutations in the Unfoldase ClpC1 of the Caseinolytic Protease Complex Are Associated with Pyrazinamide Resistance in Mycobacterium tuberculosis. Antimicrob Agents Chemotherapy. 2017;61(2):e02342–16. https://doi.org/10.1128/AAC.02342-16.

[18] Zhang Y, Zhang J, Cui P, Zhang Y, Zhang W. Identification of Novel Efflux Proteins Rv0191, Rv3756c, Rv3008, and Rv1667c Involved in Pyrazinamide Resistance in Mycobacterium tuberculosis. Antimicrob Agents Chemotherapy. 2017;61(8):10.1128/aac.00940–17. https://doi.org/10.1128/aac.00940-17.

[19] Ei PW, Mon AS, Htwe MM, Win SM, Aye KT, San LL, et al. Pyrazinamide resistance and *pncA* mutations in drug resistant *Mycobacterium tuberculosis* clinical isolates from Myanmar. Tuberculosis. 2020;125:102013. https://doi.org/10.1016/j.tube.2020.102013.

[20] Shrestha D, Maharjan B, Thapa J, Akapelwa ML, Bwalya P, Chizimu JY, et al. Detection of Mutations in pncA in Mycobacterium tuberculosis Clinical Isolates from Nepal in Association with Pyrazinamide Resistance. Current Issues in Molecular Biology. 2022;44(9):4132. https://doi.org/10.3390/cimb44090283.

[21] Baddam R, Kumar N, Wieler LH, Lankapalli AK, Ahmed N, Peacock SJ, et al. Analysis of mutations in pncA reveals non-overlapping patterns among various lineages of *Mycobacterium tuberculosis*. Scientific Reports. 2018;8(1):4628. https://doi.org/10.1038/s41598-018-22883-9.

[22] Cheng SJ, Thibert L, Sanchez T, Heifets L, Zhang Y. pncA Mutations as a Major Mechanism of Pyrazinamide Resistance in Mycobacterium tuberculosis: Spread of a Monoresistant Strain in Quebec, Canada. Antimicrob Agents Chemotherapy. 2000;44(3):528–532. https://doi.org/10.1128/aac.44.3.528-532.2000.

[23] Whitfield MG, Soeters HM, Warren RM, York T, Sampson SL, Streicher EM, et al. A Global Perspective on Pyrazinamide Resistance: Systematic Review and Meta-Analysis. PLoS One. 2015;10(7):e0133869. https://doi.org/10.1371/journal.pone.0133869.

[24] Zaw MT, Emran NA, Lin Z. Mutations inside rifampicin-resistance determining region of *rpoB* gene associated with rifampicin-resistance in Mycobacterium tuberculosis. Journal of Infection and Public Health. 2018;11(5):605–610. https://doi.org/10.1016/j.jiph.2018.04.005.

[25] Ando H, Kondo Y, Suetake T, Toyota E, Kato S, Mori T, et al. Identification of katG Mutations Associated with High-Level Isoniazid Resistance in Mycobacterium tuberculosis. Antimicrob Agents Chemotherapy. 2010;54(5):1793–1799. https://doi.org/10.1128/AAC.01691-09.

[26] Walker TM, Miotto P, Köser CU, Fowler PW, Knaggs J, Iqbal Z, et al. The 2021 WHO catalogue of Mycobacterium tuberculosis complex mutations associated with drug resistance: a genotypic analysis. Lancet Microbe. 2022;3(4):e265–e273. https://doi.org/10.1016/S2666-5247(21)00301-3.

[27] World Health Organization.: Catalogue of mutations in Mycobacterium tuberculosis complex and their association with drug resistance, 2nd ed. ISBN: 978-92-4-008241-0. Available from: https://www.who.int/publications-detail-redirect/9789240082410.

[28] The CRyPTIC Consortium. A data compendium associating the genomes of 12,289 Mycobacterium tuberculosis isolates with quantitative resistance phenotypes to 13 antibiotics. PLOS Biology. 2022;20(8):e3001721. https://doi.org/10.1371/journal.pbio.3001721.

[29] Kuang X, Wang F, Hernandez KM, Zhang Z, Grossman RL. Accurate and rapid prediction of tuberculosis drug resistance from genome sequence data using traditional machine learning algorithms and CNN. Scientific Reports. 2022;12(1):2427. https://doi.org/10.1038/s41598-022-06449-4.

[30] Kouchaki S, Yang Y, Walker TM, Sarah Walker A, Wilson DJ, Peto TEA, et al. Application of machine learning techniques to tuberculosis drug resistance analysis. Bioinformatics. 2019;35(13):2276–2282. https://doi.org/10.1093/bioinformatics/bty949.

[31] Carter JJ, Walker TM, Walker AS, Whitfield MG, Morlock GP, Lynch CI, et al. Prediction of pyrazinamide resistance in Mycobacterium tuberculosis using structure-based machine-learning approaches. JAC-Antimicrobial Resistance. 2024;6(2):dlae037. https://doi.org/10.1093/jacamr/dlae037.

[32] World Health Organization. Catalogue of mutations in *Mycobacterium tuberculosis* complex and their association with drug resistance. 2021;.

[33] LeCun Y, Bengio Y, Hinton G. Deep learning. Nature. 2015;521(7553):436–444. https://doi.org/10.1038/nature14539.

[34] Bronstein MM, Bruna J, LeCun Y, Szlam A, Vandergheynst P. Geometric Deep Learning: Going beyond Euclidean data. IEEE Signal Processing Magazine. 2017;34(4):18–42. Conference Name: IEEE Signal Processing Magazine. https://doi.org/10.1109/MSP.2017.2693418.

[35] Kipf TN, Welling M. Semi-Supervised Classification with Graph Convolutional Networks. 2017;ArXiv:1609.02907. https://doi.org/10.48550/arXiv.1609.02907.

[36] Gligorijević V, Renfrew PD, Kosciolek T, Leman JK, Berenberg D, Vatanen T, et al. Structure-based protein function prediction using graph convolutional networks. Nature Communications. 2021;12(1):3168. https://doi.org/10.1038/s41467-021-23303-9.

[37] Comín J, Cebollada A, Samper S. Estimation of the mutation rate of *Mycobacterium tuberculosis* in cases with recurrent tuberculosis using whole genome sequencing. Scientific Reports. 2022;12(1):16728. https://doi.org/10.1038/s41598-022-21144-0.

[38] Chen Y, Zhang X, Liang J, Jiang Q, Peierdun M, Xu P, et al. Advantages of updated WHO mutation catalog combined with existing whole-genome sequencing-based approaches for Mycobacterium tuberculosis resistance prediction. Genome Medicine. 2025;17(1):31. https://doi.org/10.1186/s13073-025-01458-0.

[39] Davies AP, Billington OJ, McHugh TD, Mitchison DA, Gillespie SH. Comparison of Phenotypic and Genotypic Methods for Pyrazinamide Susceptibility Testing with Mycobacterium tuberculosis. Journal of Clinical Microbiology. 2000;38(10):3686–3688. https://doi.org/10.1128/jcm.38.10.3686-3688.2000.

[40] Mok S, Roycroft E, Flanagan PR, Montgomery L, Borroni E, Rogers TR, et al. Overcoming the Challenges of Pyrazinamide Susceptibility Testing in Clinical Mycobacterium tuberculosis Isolates. Antimicrob Agents Chemotherapy. 2021;65(8):10.1128/aac.02617–20. https://doi.org/10.1128/aac.02617-20.

[41] Harris J, Yadalam PK, Anegundi RV, Arumuganainar D, Harris J, Yadalam Pk, et al. Comparing Graph Sample and Aggregation (SAGE) and Graph Attention Networks in the Prediction of Drug-Gene Associations of Extended-Spectrum Beta-Lactamases in Periodontal Infections and Resistance. Cureus. 2024;16(8). https://doi.org/10.7759/cureus.68082.

[42] Sielemann J, Sielemann K, Brejová B, Vinař T, Chauve C. plASgraph2: using graph neural networks to detect plasmid contigs from an assembly graph. Frontiers in Microbiology. 2023;14. https://doi.org/10.3389/fmicb.2023.1267695.

[43] Zhao F, Qiu J, Xiang D, Jiao P, Cao Y, Xu Q, et al. deepAMPNet: a novel antimicrobial peptide predictor employing AlphaFold2 predicted structures and a bi-directional long short-term memory protein language model. PeerJ. 2024;12:e17729. https://doi.org/10.7717/peerj.17729.

[44] Denamur E, Clermont O, Bonacorsi S, Gordon D. The population genetics of pathogenic Escherichia coli. Nature Reviews Microbiology. 2021;19(1):37–54. https://doi.org/10.1038/s41579-020-0416-x.

[45] Carter JJ, Fowler PW.: `predict-pyrazinamide-resistance`. Available from: https://github.com/fowler-lab/predict-pyrazinamide-resistance.

[46] Mirdita M, Schütze K, Moriwaki Y, Heo L, Ovchinnikov S, Steinegger M. ColabFold: making protein folding accessible to all. Nature Methods. 2022;19(6):679–682. https://doi.org/10.1038/s41592-022-01488-1.

[47] Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, et al. Highly accurate protein structure prediction with AlphaFold. Nature. 2021;596(7873):583–589. https://doi.org/10.1038/s41586-021-03819-2.

[48] Petrella S, Gelus-Ziental N, Maudry A, Laurans C, Boudjelloul R, Sougakoff W. Crystal Structure of the Pyrazinamidase of *Mycobacterium tuberculosis*: Insights into Natural and Acquired Resistance to Pyrazinamide. PLoS One. 2011;6(1):e15785. https://doi.org/10.1371/journal.pone.0015785.

[49] Fyfe PK, Rao VA, Zemla A, Cameron S, Hunter WN. Specificity and mechanism of acinetobacter baumanii nicotinamidase: Implications for activation of the front-line tuberculosis drug pyrazinamide. Angew Chem Int Ed. 2009;48(48). https://doi.org/10.1002/anie.200903407.

[50] Adlard D, Lynch C, Fowler PW.: sbmlcore: a collection of core classes and functions for structure-based machine learning to predict antimicrobial resistance. Available from: https://github.com/fowler-lab/sbmlcore.

[51] Cao H, Wang J, He L, Qi Y, Zhang JZ. DeepDDG: Predicting the Stability Change of Protein Point Mutations Using Neural Networks. Journal of Chemical Information and Modeling. 2019;59(4):1508–1514. https://doi.org/10.1021/acs.jcim.8b00697.

[52] Blaabjerg LM, Kassem MM, Good LL, Jonsson N, Cagiada M, Johansson KE, et al. Rapid protein stability prediction using deep learning representations. eLife. 2023;12:e82593. https://doi.org/10.7554/eLife.82593.

[53] Stone EA, Sidow A. Physicochemical constraint violation by missense substitutions mediates impairment of protein function and disease severity. Genome Research. 2005;15(7):978–986. https://doi.org/10.1101/gr.3804205.

[54] Hecht M, Bromberg Y, Rost B. Better prediction of functional effects for sequence variants. BMC Genomics. 2015;16(8):S1. https://doi.org/10.1186/1471-2164-16-S8-S1.

[55] Fey M, Lenssen JE. Fast Graph Representation Learning with PyTorch Geometric. In: ICLR Workshop on Representation Learning on Graphs and Manifolds; 2019. .

[56] Morris C, Ritzert M, Fey M, Hamilton WL, Lenssen JE, Rattan G, et al.: Weisfeiler and Leman Go Neural: Higher-order Graph Neural Networks. ArXiv:1810.02244. Available from: http://arxiv.org/abs/1810.02244.

[57] Biewald L.: Experiment Tracking with Weights and Biases. Software available from wandb.com. Available from: https://www.wandb.com/.

[58] Wang Y, Zhang T, Guo X, Shen Z.: Gradient based Feature Attribution in Explainable AI: A Technical Review. ArXiv:2403.10415. Available from: http://arxiv.org/abs/2403.10415.

[59] Simonyan K, Vedaldi A, Zisserman A.: Deep Inside Convolutional Networks: Visualising Image Classification Models and Saliency Maps. ArXiv:1312.6034. Available from: http://arxiv.org/abs/1312.6034.

[60] Khan MT, Ali S, Zeb MT, Kaushik AC, Malik SI, Wei DQ. Gibbs Free Energy Calculation of Mutation in PncA and RpsA Associated With Pyrazinamide Resistance. Frontiers in Molecular Biosciences. 2020;7. https://doi.org/10.3389/fmolb.2020.00052.

[61] Nangraj AS, Khan A, Umbreen S, Sahar S, Arshad M, Younas S, et al. Insights Into Mutations Induced Conformational Changes and Rearrangement of Fe2+ Ion in pncA Gene of Mycobacterium tuberculosis to Decipher the Mechanism of

Resistance to Pyrazinamide. Frontiers in Molecular Biosciences. 2021;8:633365. https://doi.org/10.3389/fmolb.2021.633365.

[62] Abramson J, Adler J, Dunger J, Evans R, Green T, Pritzel A, et al. Accurate structure prediction of biomolecular interactions with AlphaFold 3. Nature. 2024;630(8016):493–500. https://doi.org/10.1038/s41586-024-07487-w.

[63] Hayes T, Rao R, Akin H, Sofroniew NJ, Oktay D, Lin Z, et al. Simulating 500 million years of evolution with a language model. Science. 2025;387(6736):850–858. https://doi.org/10.1126/science.ads0018.

[64] Jin C, Jia C, Hu W, Xu H, Shen Y, Yue M. Predicting antimicrobial resistance in E. coli with discriminative position fused deep learning classifier. Computational and Structural Biotechnology Journal. 2023;23:559–565. https://doi.org/10.1016/j.csbj.2023.12.041.

[65] Dissanayake D, Fowler PW.: `tb-pnca-gnn`: a graph convolutional neural network for predicting pyrazinamide resistance in Mycobacterium tuberculosis based on mutations in the pncA gene. Available from: https://github.com/fowler-lab/predict-pyrazinamide-resistance.