igv-reports: Embedding interactive genomic visualizations in HTML reports to aid variant review

James T. Robinson[1], Helga Thorvaldsdottir[2], Jill P. Mesirov[1,3]

[1] Department of Medicine, School of Medicine, University of California San Diego, La Jolla, CA, USA
[2] Broad Institute of MIT and Harvard, Cambridge, MA, USA
[3] Moores Cancer Center, University of California San Diego, La Jolla, CA, USA

Abstract

We present igv-reports, a command-line tool to create standalone HTML pages embedding interactive genomic visualizations of read alignments and associated annotations to support variant inspection workflows. The reports contain all data and code required for visualization of the variant sites, with no dependencies on the input data files.

Introduction

The accuracy of sequencing technologies and the tools that identify genomic variants based on the sequencing data has greatly improved over the years. However, incorrect variant calls still occur due to sequencing anomalies and other causes, and expert human review of the underlying data can help identify false positives and validate correctly called variants. Therefore, visual inspection of read alignments in a genome browser is an important step in many sequencing workflows [1-3] such as validating variants in clinical settings using BAM or CRAM files. To support this a number of desktop and web applications have been developed or modified to support alignment viewing. Tools like the Integrative Genomics Viewer (IGV) [4,5] and web-based browsers such as JBrowse [6] and the UCSC Genome Browser [7] are powerful and widely used. However, they all require direct access to underlying data files during operation, which can complicate or prevent the sharing of the variant visualizations. To address this, tools have been developed to create static screenshots or precomputed images for reports or downstream analysis, e.g., IGV snapshot automator [8] and Alignoth [9]. However, this approach has a significant limitation: the visualization options are fixed at the time of image creation. Reviewers lack the ability to dynamically adjust coloring, sorting, grouping, and other visualization settings in response to specific variant characteristics, which would significantly enhance variant interpretation.

To address this, we present igv-reports, a tool that creates self-contained HTML reports for variant review by embedding the popular IGV plugin igv.js [10]. Unlike static screenshots, igv-reports support the extensive visualization options developed for IGV, aiding in variant validation and interpretation. Once generated, these report files no longer depend on the original data files, making them easy to open as local files, share via email, post as static web pages, or integrate as output into variant pipelines.

Features

The igv-reports tool takes as input (1) a list of genomic sites, specified as a VCF, BED, MAF, BEDPE, or tab-delimited file; (2) the reference genome, specified as a genome identifier, or as a FASTA or TwoBit file that defines the reference sequence; and (3) one or more track files in BAM, CRAM, VCF, BED, GFF, MAF, or BEDPE format. Output is an HTML report file containing a table of variants and an igv.js genomic view of the tracks for each variant.

The reports can be shared and opened with a web browser from the local file system, or hosted on a server or web portal without the need to access the original files. This is possible because all data for the regions of interest are embedded in the report file.

An example report is illustrated in Figure 1. The report was created with the following command, using test data from the igv-reports GitHub repository.

```
create_report test/data/variants/variants.vcf.gz --genome hg38
    --info-columns GENE TISSUE TUMOR COSMIC_ID GENE SOMATIC
    --tracks test/data/variants/variants.vcf.gz test/data/variants/recalibrated.bam
    --output example_vcf.html
```

The report includes a collapsible table view of variants coupled to a genomic view of supporting read alignments. Clicking on a variant in the table will display the tracks in the igv.js viewer, with the genomic view centered on the selected variant, including flanking regions to either side. The size of the flanking region is a user option, defaulting to 1 kilobase. The displayed tracks can be explored interactively using the igv.js track configuration and context menus, for example to change coloring or sorting schemes. Details of individual alignments and other displayed objects are available as popup text.

Figure 1. A variant report containing two main sections: **(1)** a table view of variants sites, and **(2)** an igv.js genomic visualization of variants and associated alignments. Overlaid on the igv.js viewer are four popups associated with the alignment track. Clicking on an element in the track displays further details, including metadata for a particular alignment **(a)**, and coverage details for the variant base **(b)**. The track has two menus: a context menu to control sorting of the alignments **(c)**, and a track configuration menu **(d)**. The interactive report can be accessed at https://igvteam.github.io/igv-reports/examples/example_vcf.html.

igv-reports offers multi-locus views for structural variants too large for a single display. This feature allows users to input two regions that encompass the variant endpoints, specified as BEDPE files or VCF files with CHR2 and POS2 SV info fields. Multi-locus views are also employed for variants exceeding a length threshold specified as a command-line argument. See Supplementary Figure 1 for an example.

A number of command-line options are available to customize a report. These include, for example, options to customize the variant table columns, include custom headers and footers, filter and sort alignments by various attributes, and adjust the size of the variant flanking region. Additionally, track options are fully customizable using igv.js track configuration objects. Finally, the report itself can be customized by supplying an alternative HTML template. Templates are standard HTML with placeholder tokens for the variant table data and dictionary of encoded igv.js sessions. In addition to the standard variant template, illustrated in Figure 1, igv-reports provides alternate templates in the GitHub repository. They include an alternative variant template with filterable table columns (see Supplementary Figure 2), as well as templates for supporting output from the Trinity Cancer Transcriptome Analysis Toolkit (CTAT) gene fusion [11] and splice junction tools (see Supplementary Figures 3 and 4). Users can also provide their own custom templates.

The only tool we are aware of with a comparable set of features is jigv [12]. This tool, written in Nimble, takes a similar approach of creating a standalone HTML report containing interactive igv.js track views in the regions of a pre-defined list of variant sites, but augments it with special support for working with family pedigrees. While similar in design and operation, igv-reports offers some advantages when creating reports not involving pedigrees. First, jigv reports do not include a table view which means there is no annotated variant summary, and navigation is limited to clicking on next and previous buttons or the arrow keys to move between variants. Additionally, igv-reports offers more extensive customization options and supports a broader array of file formats.   Finally jigv does not support multi-locus views and therefore cannot handle the display of large structural variants.

Implementation

The igv-reports tool is a command-line application written in Python. Input files include a reference sequence, list of variant sites, and one or more track files containing alignments, annotations, and other genomic data. Input files can be loaded from the local file system or remotely by URL. Variant sites can be input as a VCF, BED, MAF, BEDPE, or tab-delimited file. Processing proceeds as a loop through variant sites. For each site, metadata is extracted from the variant file for populating the corresponding row in the variant selection table. This data is stored in a TABLE_JSON dictionary. Next, data is extracted from the reference sequence file and track files for a genomic region centered on the variant site. For fast processing, data extraction uses the Python packages pysam [13] and py2bit [14] which take advantage of file indexing. Indexes are required for sequence and alignment formats, and recommended for all large files. The extracted data slices are then compressed and base64 encoded to form a data URI. The data URIs for each variant are incorporated in an igv.js session object stored in the SESSION_DICTIONARY object. Finally, the TABLE_JSON and SESSION_DICTIONARY objects are converted to JSON and injected into the HTML template at the corresponding token locations in the HTML template.

Limitations

igv-reports is designed to generate self-contained HTML reports for the visual inspection and validation of variant sites. However, because all genomic data is embedded directly within the HTML file, the tool is not ideal for extremely large sets of variants. The exact limits on variant set size can vary depending on factors such as the number of visualized tracks, the average depth of coverage in alignment tracks, the

amount of metadata associated with variants and alignments, and the available memory on the client computer viewing the reports. A benchmark with an alignment file from the 1000 Genomes Project [15] of approximately 50x coverage produced a report of about 100 MB for 1,000 variants. While viewable on most modern web browsers, this is considered near the upper limit. For larger datasets, the report could be split into multiple files; although 1,000 variants may already surpass the limit of practical usefulness for visual validation.

In summary, igv-reports is suitable for producing reports for variant sets ranging from hundreds up to 1,000 distinct sites.

Availability

igv-reports is freely available under an MIT license. The Python package can be installed from PyPI at https://pypi.org. Source code, installation instructions, user documentation, and examples are available at https://github.com/igvteam/igv-reports.

Acknowledgements

This work was supported by the National Institutes of Health [U24CA258406].

References

1. Koboldt DC. Best practices for variant calling in clinical sequencing. Genome Med. 2020 Oct 26;12(1):91. doi: 10.1186/s13073-020-00791-w. PMID: 33106175; PMCID: PMC7586657.

2. Crooks KR, Farwell Hagman KD, Mandelker D, Santani A, Schmidt RJ, Temple-Smolkin RL, Lincoln SE. Recommendations for Next-Generation Sequencing Germline Variant Confirmation: A Joint Report of the Association for Molecular Pathology and National Society of Genetic Counselors. J Mol Diagn. 2023 Jul;25(7):411-427. doi: 10.1016/j.jmoldx.2023.03.012. Epub 2023 May 17. PMID: 37207865.

3. Koay BT, Chiow MY, Ismail J, Fahmy NK, Yee SY, Mustafa N, Arip M, Ripen AM, Mohamad SB. Visual inspection reveals a novel pathogenic mutation in PKD1 missed by the variant caller in whole-exome sequencing. Mol Med Rep. 2022 Dec;26(6):365. doi: 10.3892/mmr.2022.12882. Epub 2022 Oct 25. PMID: 36281931; PMCID: PMC9644422.

4. Robinson JT, Thorvaldsdóttir H, Winckler W, Guttman M, Lander ES, Getz G, Mesirov JP. Integrative genomics viewer. Nat Biotechnol. 2011 Jan;29(1):24-6. doi: 10.1038/nbt.1754. PMID: 21221095; PMCID: PMC3346182.

5. Robinson JT, Thorvaldsdóttir H, Wenger AM, Zehir A, Mesirov JP. Variant Review with the Integrative Genomics Viewer. Cancer Res. 2017 Nov 1;77(21):e31-e34. doi: 10.1158/0008-5472.CAN-17-0337. PMID: 29092934; PMCID: PMC5678989.

6. Diesh C, Stevens GJ, Xie P, De Jesus Martinez T, Hershberg EA, Leung A, Guo E, Dider S, Zhang J, Bridge C, Hogue G, Duncan A, Morgan M, Flores T, Bimber BN, Haw R, Cain S, Buels RM, Stein LD, Holmes IH. JBrowse 2: a modular genome browser with views of synteny and structural variation. Genome Biol. 2023 Apr 17;24(1):74. doi: 10.1186/s13059-023-02914-z. PMID: 37069644; PMCID: PMC10108523.

7. Perez G, Barber GP, Benet-Pages A, Casper J, Clawson H, Diekhans M, Fischer C, Gonzalez JN, Hinrichs AS, Lee CM, Nassar LR, Raney BJ, Speir ML, van Baren MJ, Vaske CJ, Haussler D, Kent WJ, Haeussler M. The UCSC Genome Browser database: 2025 update. Nucleic Acids Res. 2025 Jan 6;53(D1):D1243-D1249. doi: 10.1093/nar/gkae974. PMID: 39460617; PMCID: PMC11701590.

8. Available from https://github.com/stevekm/IGV-snapshot-automator

9. Available from https://github.com/alignoth

10. Robinson JT, Thorvaldsdottir H, Turner D, Mesirov JP. igv.js: an embeddable JavaScript implementation of the Integrative Genomics Viewer (IGV). Bioinformatics. 2023 Jan 1;39(1):btac830. doi: 10.1093/bioinformatics/btac830. PMID: 36562559; PMCID: PMC9825295.

11. Qin Q, Popic V, Wienand K, Yu H, White E, Khorgade A, Shin A, Georgescu C, Campbell CD, Dondi A, Beerenwinkel N, Vazquez F, Al'Khafaji AM, Haas BJ. Accurate fusion transcript identification from long- and short-read isoform sequencing at bulk or single-cell resolution. Genome Res. 2025 Apr 14;35(4):967-986. doi: 10.1101/gr.279200.124. PMID: 40086881; PMCID: PMC12047241.

12. Available from https://github.com/brentp/jigv

13. Available from https://github.com/pysam-developers/pysam

14. Available from https://github.com/deeptools/py2bit

15. Fairley S, Lowy-Gallego E, Perry E, Flicek P. The International Genome Sample Resource (IGSR) collection of open human genomic variation resources. Nucleic Acids Res. 2020 Jan 8;48(D1):D941-D947. doi: 10.1093/nar/gkz836. PMID: 31584097; PMCID: PMC6943028.