PathogenSurveillance: **an automated pipeline for population genomic analyses**

and pathogen identification

Zachary S. L. Foster (https://orcid.org/0000-0002-5075-0948)[1], Martha A. Sudermann

(https://orcid.org/0000-0001-6912-3461)[2], Camilo Parada-Rojas (https://orcid.org/0000-0002-

8372-6012)[2], Logan K. Blair (https://orcid.org/0009-0003-0972-4320)[1], Fernanda Iruegas-

Bocardo (https://orcid.org/0009-0002-6817-3162)[2,#], Upasana Dhakal (https://orcid.org/0009-

0007-3427-8544)[2], Ricardo I. Alcalá-Briseño (https://orcid.org/0000-0002-7031-2195)[2,#], Hung

Phan[2], Tori R. Schummer (0009-0003-4213-6619)[2], Alexandra J. Weisberg

(https://orcid.org/0000-0002-0045-1368)[2], Jeff H. Chang (https://orcid.org/0000-0002-1833-

0695)[2], and Niklaus J. Grünwald (https://orcid.org/0000-0003-1656-7602)[1]

[1] Horticultural Crops Disease and Pest Management Research Unit, USDA Agricultural

Research Service, Corvallis, Oregon 97330, USA

[2] Department of Botany and Plant Pathology, Oregon State University, Corvallis, Oregon 97331,

USA

[#] Now at: Department of Plant Pathology and Environmental Microbiology, Pennsylvania State

University, University Park, Pennsylvania 16802, USA

Abstract

Whole genome sequencing (WGS) offers a comprehensive, organism-agnostic method that

effectively meets the need for efficient, reliable, and standardized responses to emerging threats

from pathogens and pests. Here, we present *PathogenSurveillance*, an open-source and

automated Nextflow pipeline for population genomic analyses of WGS data. It is designed with

features tailored for biosurveillance and is suitable for in-field or point-of-care diagnostics.

PathogenSurveillance is flexible, accommodating short- and long-read datasets and mixed

samples of prokaryotes and/or eukaryotes. It automates all steps, including reference

identification and retrieval from the NCBI Assembly database, and produces customizable

interactive reports with summaries, phylogenetic trees, and minimum spanning networks that

enable species and subspecies level identification. It also outputs quality control metrics and

carefully names and organizes output files to facilitate downstream analyses. The pipeline runs

on any Linux-based system and minimizes the need for advanced computational expertise.

Source code is available on GitHub under the open-source MIT license. The pipeline expands

the toolkit for real-time biosurveillance, enabling rapid detection and monitoring of pathogens

and pests for rapid response to novel variants.

Keywords: bioinformatics, biosurveillance, epidemics, epidemiology, Nextflow, One Health,

pipeline, pandemic, pathogen genomics, population genomics

Introduction

Emerging invasive pathogens and pests pose an escalating global threat, largely driven by

anthropogenic factors such as intensified international trade (Meyerson and Mooney 2007;

Hulme 2009; Fisher et al. 2012; Liebhold et al. 2012). Their sudden appearance and potential to

spread rapidly can outpace existing biosurveillance systems, making it difficult to mount timely

responses (Carvajal-Yepes et al. 2019). Consequently, diseases caused by these novel organisms

may reach epidemic levels before effective diagnostic methods are developed. To address this

challenge, biosurveillance efforts require faster and more reliable detection that enables timely

interventions (Gardy and Loman 2018; Hamelin et al. 2022). This is especially relevant for

OneHealth frameworks, which emphasize the interconnected movement of pathogens across

human, animal, and environmental domains, as seen in cases of antimicrobial resistance

(Djordjevic et al. 2024).

Whole Genome Sequencing (WGS) is an important tool for biosurveillance, particularly in the

early detection of infectious disease outbreaks (Weisberg et al. 2021). Methods for analyzing

WGS data are highly effective for detecting emerging or reemerging invasive pathogens and

pests, as they do not require *a priori* knowledge or optimization for specific organisms and can

be applied to diagnosing rapidly developing threats even when the causative agent is unknown

(Gardy and Loman 2018; Weisberg et al. 2021). However, key hurdles to the adoption of WGS

are the need for appropriate infrastructure and domain expertise in both computational methods

and pathogen biology (Oakeson et al. 2017; Iles et al. 2021). Thus, it is essential to design

computational workflows that directly confront these challenges and empower users without

specialized training to work with WGS data for disease detection.

WGS-based approaches commonly used for characterizing genetic clustering can be broadly

grouped as *k*-mer, multigene, or variant-based phylogenies. *K*-mer based methods have the

advantage of being extremely fast and computationally efficient (Pierce et al. 2019). They work

by comparing the presence of only exact sequences of a given length (known as *k*-mers). The *k*-

mer contents of genome sequences can be summarized by a systematically selected subset of

hashed *k*-mers called a sketch and compared to a database of other sketches corresponding to

reference genomes (Tian et al. 2020; Irber et al. 2022; Irber et al. 2024). However, sketch-based

approaches are limited in their ability to infer taxonomic breadth, as their reliability declines

with decreasing genome sequence similarity (Ondov et al. 2016). Conversely, multigene

phylogenies can be used to group samples at various taxonomic levels, making such methods

ideal for placing organisms of unknown identities in a phylogenetic context. But these

approaches have limited resolution, are less scalable, and require domain knowledge to select

appropriate marker gene and reference sequences. The major strength of variant-based (single

nucleotide polymorphisms (SNPs)) analyses lies in their high resolution, which enables

clustering of closely related samples to identify clonal relationships and reveal potential

transmission events. Variant-based approaches have similar limitations as multigene phylogeny-

based approaches and are even more sensitive to reference selection and assembly quality

(Weisberg et al. 2021).

Various pipelines have been developed for pathogen surveillance. *GATK PathSeq* enables

identification of pathogens from host-derived samples and is highly efficient, integrating well

with standard computational environments, although it requires a reference database of potential

microbes and host sequences (Walker et al. 2018). *Bactopia* and *Galaxy@Sciensano* are

collections of seamlessly integrated tools designed for analyses of prokaryotes, but they require

domain knowledge to select appropriate reference sequences (Petit and Read 2020a; Bogaerts et

al. 2025). *CZ ID* (formerly *IDseq*) is a web-based pipeline for analyzing metagenomic data for

pathogen detection but does not provide tools for multigene phylogeny construction or variant

analyses (Kalantar et al. 2020). *Pathogenwatch* is a web service that supports phylogenetic

analyses, primarily through Multi-Locus Sequence Alignment (MLSA) based phylogenetic

approaches, and has utility for in-depth analyses (Argimón, David, et al. 2021; Argimón, Yeats,

et al. 2021; Sánchez-Busó et al. 2021). However, *Pathogenwatch* is not optimized for use on

local machines or private clouds and is largely limited to specific pathogen groups. *PathoGFAIR*

provides a Galaxy-based workflow to detect and track pathogens from metagenomic Nanopore

sequencing (Nasr et al. 2025).

Here we present nf-core/*PathogenSurveillance,* an open-source pipeline for automated

population genomic and evolutionary analysis. This pipeline was released within nf-core, a

collaborative, community-driven framework for developing and sharing standardized pipelines

built on the Nextflow workflow management system (Di Tommaso et al. 2017).

PathogenSurveillance leverages nf-core modules and community peer review to ensure robust

functionality, while its implementation in Nextflow provides scalability, reproducibility, and

portability. *PathogenSurveillance* automatically processes and analyzes short- and long-read

WGS data along with publicly available genome assemblies. It features specialized capabilities

for pathogen and pest identification, including flexible support for user-defined or automated

reference sequence identification and retrieval, as well as the ability to concurrently analyze

mixed prokaryotic and eukaryotic samples and populations. Other distinctive features include the

integration of *k*-mer-, multigene phylogeny-, and variant-based approaches to deliver multiple

levels of phylogenetic resolution for pathogen identification. The interactive output presents

easily interpretable results, facilitating actionable responses. Moreover, output files are

organized for deeper downstream investigation, extending use of *PathogenSurveillance* to

population genomic studies to a wider range of organisms. To validate and illustrate its utility,

we applied *PathogenSurveillance* to test datasets, demonstrating accuracy in automated

reference selection and sample identification.

Implementation

We developed *PathogenSurveillance* for WGS data analyses of pathogens or pests. This pipeline

is user-friendly and automates all steps from reference sequence selection and retrieval to the

generation of interactive reports detailing sample identity, phylogenetic relationships, and

population structure (Figure 1). The pipeline was designed according to widely accepted core

principles, with a particular focus on minimizing the need for advanced computational expertise

by end users and incorporating specialized features for pathogen surveillance.

PathogenSurveillance follows the FAIR (Findable, Accessible, Interoperable and Reusable)

principles for processing data using workflows (De Visser et al. 2023).

PathogenSurveillance streamlines installation by leveraging Nextflow, an open-source software

tool and domain-specific language that simplifies the creation and execution of data-intensive,

scientific computational workflows (Di Tommaso et al. 2017). Nextflow uses container

frameworks, such as Docker, Apptainer, or Conda, to automatically and reproducibly install all

required dependencies as needed upon first execution. Each process runs in its own isolated

container and file system, eliminating software incompatibilities and ensuring consistent

behavior across any Linux-based environment. As part of *PathogenSurveillance*'s development,

we contributed seven new modules and made updates or bug fixes in eight existing nf-core

modules (Supplementary Table 1).

The input process is also streamlined without sacrificing flexibility or configurability.

PathogenSurveillance minimally requires a tab-separated value (TSV) file as input, with the only

mandatory field being source of sequence data. This field can be populated with any

combination of paths to local files or URLs to remote files, NCBI Short Read Archive (SRA)

accession numbers, or NCBI Biosample IDs associated with SRA accessions. Input data may

correspond to a single sample, multiple taxonomically disparate samples (including both

prokaryotic and eukaryotic organisms), populations of related samples, or any combination

thereof. While *PathogenSurveillance* also has flexibility in analyzing samples with raw reads

derived from Illumina, PacBio, or Oxford Nanopore technologies, it does not support data

combined for the same sample from multiple sequencing platforms. For the latter case, users will

need to select one source of read data. All other metadata for samples are optional but

recommended if available, to support downstream analyses. Users can also provide a second

optional TSV file to specify reference genomes. Furthermore, users can indicate whether user-

defined reference genomes should be included along with automatically selected references or

used as the sole source, thereby excluding other possible references from analyses.

The pipeline is initiated with a single command. Upon initiation, it automatically generates a *k*-

mer sketch from each sample's raw reads and compares these to sketches of all of NCBI RefSeq

using bbmap sendsketch (Figure 1) (Bushnell 2014). If chosen by the user, it then identifies and

retrieves assemblies that are possible reference sequences. Next, *PathogenSurveillance* processes

and assembles sample reads and generates new *k*-mer sketches using sourmash to infer Average

Nucleotide Identity (ANI) values that can be used to refine reference selection (Konstantinidis

and Tiedje 2005; Pierce et al. 2019). The pipeline selects the next workflow branches based on

whether the sample is inferred to be of prokaryotic or eukaryotic origin. For prokaryotic datasets,

it will annotate genome assemblies, generate ortholog clusters, identify shared orthologs among

samples and their references, and construct a core genome phylogenetic tree. If the pipeline

identifies clusters of closely related samples, it will map reads to their common reference

assembly, call SNPs, and generate a SNP tree as well as a minimum spanning network. For

eukaryotic datasets, *PathogenSurveillance* does not annotate genome sequences, as automated

annotation is impractical because taxonomic groups require specialized training datasets. Instead,

the pipeline generates a phylogenetic tree based on identified Benchmarking Universal Single-

copy Orthologs (BUSCO) sequences (Manni et al. 2021). A final interactive report is generated

as an HTML file wherein users can define groups and adjust visualizations. All intermediate

files, such as assemblies and annotations, are stored and made accessible for additional analyses

(Supplementary Figure 1). *PathogenSurveillance* also produces quality control reports for reads

and assemblies. Details on key workflow steps of the pipeline are provided in the following

sections. The report created lists all the references and sources for computational tools used in

the analysis (Sample reports can be downloaded at

https://github.com/grunwaldlab/pathogensurveillance_publications/tree/main/publication/exampl

e_reports).

PathogenSurveillance is portable and can be executed on any Linux platform, including local

desktops, high performance computing (HPC) clusters, and commercial cloud environments. In

addition, *PathogenSurveillance* can be launched from Sequera Platform, a web-based platform.

A comprehensive guide to executing the pipeline, including input formats and optional

parameters, is available online (https://nf-co.re/PathogenSurveillance).

Automated reference selection and population-level analyses

Effective selection of reference genome sequences is critical for accurate pathogen identification

(Grünwald and Goss 2011; Weisberg et al. 2021). However, the likely taxonomic classification

of a sample may not be readily known, particularly for emerging pathogens and pests. To

mitigate this limitation, we implemented a rule-based system for context-aware selection and

retrieval of reference genome sequences that balances per-sample accuracy with the potential for

coherent population-level analyses (Figure 2). By default, *PathogenSurveillance* attempts to

automatically detect and group related samples within the analyzed dataset. Users also have the

option of manually assigning references to samples or specifying which subgroups of samples

should be analyzed together.

As described in the overview, rules are executed in two stages (Figure 1). In the first stage, a

subset of possible reference assemblies relevant to the aggregated set of samples are downloaded

(Figure 2A). For every unique family identified for samples analyzed, *PathogenSurveillance* will

download the corresponding NCBI Assembly metadata, used to further refine reference selection

based on genera, species, and strain information. If multiple references are available for a

selected taxon, selection is additionally based on the prevalence of the associated taxon in the

database indicating it is typical by NCBI standards, whether the assembly corresponds to a type

strain, is in RefSeq, and associated with a Latin binomial. Additional criteria include assembly

features such as assembly level, predicted assembly coverage of the genome sequence, absence

of contaminating reads, and contig L50. In the second stage, the pipeline uses estimated ANI

values to identify two types of reference assemblies among those downloaded (Figure 2).

Contextual references are of well-characterized organisms selected to represent different

taxonomic levels for phylogenetic analyses while mapping references are used for SNP calling.

To facilitate population-level analysis, the pipeline identifies contextual references that are

shared across samples. This reduces the total number of distinct references and enables grouping

of related samples for phylogenetic inference (Figure 2B). References are first partitioned into

equal-sized bins based on a rescaled estimated ANI value for each sample. References most

similar to each sample and those specified by the user are selected as initial candidates.

PathogenSurveillance then iteratively selects additional references that best serve the entire

group of samples. In each iteration, it prioritizes references that span the greatest number of bins

across all samples, recalculating bin coverage after each selection. This process continues until

every bin is filled by at least one selected reference. This process also helps reduce runtime and

computational resources needed to construct the phylogeny.

For prokaryotic samples, core gene sequences are used to construct a phylogeny while for

eukaryotic samples, BUSCO gene sequences are used (Manni et al. 2021). If

PathogenSurveillance determines that too few gene homologs are shared among samples, it

partitions the dataset into the fewest possible number of clusters such that each cluster meets the

minimum threshold of shared gene homologs required to support robust phylogenetic inference.

The default threshold is set to 10 gene homologs.

Mapping reference assembly quality and phylogenetic distance from samples affects the

accuracy of SNP calling after read mapping (Iruegas-Bocardo et al. 2023). Moreover, only

samples whose reads are aligned to the same mapping reference assembly are directly

comparable in SNP analyses. *PathogenSurveillance* addresses these limitations by using

estimated ANI values to cluster samples with their most closely related references in a sequential

manner (Figure 2C). The process begins by selecting a reference that exceeds a defined

minimum similarity threshold and is shared by the largest number of samples. When multiple

references meet estimated ANI thresholds for the same number of samples, the one with the

highest average similarity across those samples is chosen. This process is repeated iteratively

until no samples can be matched to a reference. For each resulting cluster containing two or

more samples assigned to the same reference, a pangenome graph method is executed to call

SNPs (Eggertsson et al. 2019). This method is more robust to variation in phylogenetic distance

and reference sequence quality (Eggertsson et al. 2019; Weisberg et al. 2021; Iruegas-Bocardo et

al. 2023). SNP data are then used to create phylogenetic trees or minimum spanning networks.

PathogenSurveillance **outputs**

PathogenSurveillance produces a rich set of data that is synthesized in tables and plots in

interactive HTML reports for each user-defined group of samples (See for example:

https://github.com/grunwaldlab/pathogensurveillance_publications/tree/main/publication/exampl

e_reports). A sunburst plot provides a summary of taxonomic classifications of the samples,

predicted based on initial *k*-mer sketches of raw reads and is associated with a table that presents

254 the statistics for each match. These preliminary classifications, based on analysis of raw reads,

255 serve to guide *PathogenSurveillance* in the next round for selecting reference assemblies. Next,

256 estimated ANI and Percent of Conserved Proteins (POCP) values are displayed as both

257 interactive heatmaps and in a table of best matches for each sample (Qin et al. 2014). These give

258 essential context for interpretation of predicted taxonomic identities, as ANI reflects similarity

259 across homologous regions while POCP captures overall genomic similarity between compared

260 genome sequences (Weisberg et al. 2021). Multilocus, phylogenetic trees provide taxonomic

261 placements of samples (Minh et al. 2020). A minimum spanning network constructed from

262 genetic distances is used to visualize clonal lineages within populations (Kamvar et al. 2014).

263 Tables and plots are accompanied by expandable tooltips that explain how to interpret data and

264 outline methods used.

266 In addition to the main report, *PathogenSurveillance* writes results from each step into structured

267 folders that can be mined further for downstream analyses (Supplementary Figure 1). These

268 output folders are organized hierarchically and named intuitively. Likewise, output files

269 corresponding to specific samples, references, or groups of samples and references are

270 consistently named based on user-definable identifiers. The organization and naming are

271 intentionally designed to be both human-readable and machine-parseable, facilitating seamless

272 integration into downstream analyses. The kind of analyses used by *PathogenSurveillance*

273 necessarily output large and numerous files, not all of which are equally likely to be useful for

274 downstream analysis. Nearly all intermediate files that take up little space are included in the

275 output, but care has been taken to only include large files if their potential utility justifies their

276 storage footprint. For example, quality filtering of BAM and VCF files occurs in several steps,

each of which produces large files, but only the raw and final filtered versions of BAM and VCF

files are preserved in the output. Additionally, by default all files in the output directory are links

to files stored in a cache rather than the files themselves. This is the same cache that is used to

resume pipeline runs and skip redundant steps. This has the benefit of only storing a single file

when multiple runs of the pipeline produce the same file, as is common when testing multiple

variations of a given dataset or pipeline parameters. Together, the careful curation of output files

combined with the deliberately streamlined design significantly reduces the need for disk space,

enabling larger analyses and efficient reanalysis of changing datasets.

The outputs also include quality control reports that support the interpretation of results.

PathogenSurveillance automatically executes several standard quality control programs. FastQC

is used to report basic and per read statistics for short read datasets while NanoPlot serves the

same purpose for long read datasets (De Coster and Rademakers 2023). The adapter-trimming

software, fastp, provides detailed reports on read filtering, trimming, and overall read quality

(Chen et al. 2018). Quast is used to assess assembly quality metrics such as contiguity and

completeness (Gurevich et al. 2013). BUSCO provides an additional estimate of genome

assembly completeness by reporting the presence/absence of expected core genes. Finally,

MultiQC is used to compile results from each of these programs into a single, comprehensive

report, presenting quality control data for all samples in a consistent and well-organized format

(Ewels et al. 2016).

Additional user-friendly features

PathogenSurveillance incorporates extensive parallelization, error recovery mechanisms, and

caching of intermediate results, enabling improved efficiency and resilience in automated

execution of large-scale, long-running analyses. Parallel processing occurs as system resources

and API limits allow. In HPC clusters and commercial clouds, this can scale to hundreds or

thousands of jobs running in parallel, each using all available central processing units (CPUs) on

its assigned node or virtual machine. Processes that encounter errors are automatically retried a

set number of times, with each attempt incrementally increasing Random Access Memory

(RAM) and CPU allocation to accommodate resource demands. Processes that communicate

with external web services will pause before retrying after a failed attempt, allowing time for

temporary network issues to resolve. Information about pipeline execution, including any

warnings or errors encountered during the process, are presented in output reports.

Caching of intermediate results by *PathogenSurveillance* offers three key advantages. First, if

the pipeline terminates prematurely either due to an excessive number of failed processes or a

user-issued command, it can be restarted from the point at which it stopped. This is made

possible by using the "-resume" option. Second, caching gives users opportunities to incorporate

additional data or adjust parameters. Only the affected portions of the analysis are recomputed

and as a result, rerun executions are dramatically faster. Third, and similarly, caching enables

users to iteratively refine evolutionary and population-level analyses. Users can first run

PathogenSurveillance without specifying references, relying exclusively on automated reference

selection, and then manually choose more appropriate references after inspecting results. Reruns

will be executed quickly and potentially be more robust. A drawback of caching is its large

storage footprint, as seen in other comprehensive pipelines such as *Bactopia* (Petit and Read

2020). We mitigated this to some extent by designing the pipeline to intentionally avoid storing

redundant intermediate files.

Validation of *PathogenSurveillance*

We used various datasets to evaluate the accuracy and performance of *PathogenSurveilance*.

First, a subset of publicly available *Serratia* genome sequences were used to test the accuracy of

automated phylogenetic inference (Williams et al. 2022). In the original work, authors used two

methods to quality control sequence data and used two different methods to assemble long-read

PacBio and short-read Illumina data. From their original set of 664 samples, we manually

selected a subset of 302 that captured the species and ecological diversity of the full set

(Supplementary Table 2). The subset represented 11 species identified previously, with

sequencing reads generated using long- and short-read technologies. We input their accession

numbers and metadata into a TSV file. We also manually selected accessions of reference

assemblies that were used in the original study (Williams et al. 2022). The pipeline was executed

with a single command and in a mode that prevents *PathogenSurveillance* from automatically

identifying and retrieving additional reference assemblies:

```
nextflow run nf-core/PathogenSurveillance -r 1.1.0 -resume -
```

342   ```
profile docker,serratia_full --outdir serratia_results
```

*PathogenSurveillance* generated a phylogenetic tree, along with all the other associated

intermediate assemblies, annotations, and ortholog cluster files as well as quality control metrics.

The resulting tree was concordant in topology to the core gene phylogeny previously reported,

and importantly, the species and lineage assignments were highly similar between the two

analyses, with minor discrepancies restricted to placements of samples within clonal lineages

(Figure 3) (Williams et al. 2022). Overall, evaluation of this test dataset demonstrates that with

minimal user input, *PathogenSurveillance* can generate reliable phylogenetic and taxonomic

insights.

To assess the accuracy of automated reference selection and taxonomic assignment by

*PathogenSurveillance* we required a read dataset derived from samples with predictable

taxonomic identities. We also required that no corresponding assemblies be available in public

databases to ensure the pipeline will not automatically select them as references. Therefore, we

generated a new Oxford Nanopore dataset from bacteria cultured from the guts of honeybees,

which has a low complexity microbiota of only five core genera and is thus expected to yield

strains of known taxonomic identity (Motta and Moran 2024). DNA sequenced from several

colonies were preliminarily analyzed using *Kraken 2* and showed that most colonies were

mixtures of strains (Wood et al. 2019). We selected two that were largely pure and, predicted to

be from *Gilliamella apicola* strains by *Kraken 2*. The reads corresponding to *G. apicola* were

extracted from these two samples and used to evaluate the efficacy of rules implemented for

automatic reference selection (Supplementary Figure 2).

*PathogenSurveillance* automatically downloaded metadata for all possible reference assembles

within the Orbales family, based on initial analysis by *Sendsketch*, and prioritized the candidate

list according to a set of sorting criteria (listed in order of priority as columns in supplementary

figure 2; (Bushnell 2014)). *PathogenSurveillance* then downloaded multiple references for each

family, genus, and species for use as contextual references and for mapping. Importantly, the

pipeline selected references for each of the six recognized *Gilliamella* species, Candidatus

*Schmidhempelia*, and five other genera within the Orbaceae family. For *G. apicola,*

*PathogenSurveillance* downloaded reference sequences from three distinct *G. apicola* strains*,*

while avoiding those that lack key discriminating information, to maximize species-level

diversity. Additionally, because *PathogenSurveillance* uses ANI as the key criterion to select

mapping references, it selected the more similar *Gilliamella apicola* SCGC AB-598-B02

(GCF_000725165.1) over *Gilliamella apicola* (GCF_000599985.1), which was initially

identified as the best representative of the species based on metadata (Supplementary Figure 2).

We also simulated sequence divergence of *G. apicola* samples to evaluate the robustness of

reference selection. We simulated Illumina reads from the Oxford Nanopore-based assemblies

and introduced up to 10% sequence divergence using the ART read simulator (Supplementary

Figure 3)(Huang et al. 2012). Predictably, *PathogenSurveillance,* using simulated Illumina reads

with no sequence divergence, selected the same references as the original dataset. Each

increment of simulated sequence divergence, with the exception of 2% divergence, resulted in

the selection of the same reference sequence. In the one exception, *PathogenSurveillance*

selected *Gilliamella* sp. wkB7 (GCF_001693435.1), which is closely related and had highly

similar ANI values. Therefore, the pipeline robustly selected references for phylogenetic

inference and read mapping.

Lastly, we used publicly available genome sequences to generate prokaryotic and eukaryotic

datasets to evaluate the impact of sample and genome sizes on runtime and RAM usage. One

dataset was derived from a study of *Klebsiella pneumoniae*, which has an average genome size

of 5.7 Mb (David et al. 2020)(Supplementary Table 3). To evaluate the effect of sample size, we

randomly subsampled the dataset to form sets of 1, 3, 5, 10, 25, 50, 75, 100, 150, and 200

samples. The pipeline was executed with caching disabled to analyze three replicates of each of

the sets. As expected, runtime showed a linear increase from 0.4 to 11.7 hours as the number of

samples increased from 1 to 200 samples (Figure 4A). RAM also increased linearly from 4.3 GB

for 1 sample to 12.2 GB for 200 samples (Figure 4B).

We also created a dataset of taxonomically disparate organisms with genome sizes that vary

from 2.1 Mb to 224.8 Mb (David et al. 2020)(Supplementary Table 4). Each dataset was

composed of three samples of a single species and was run in triplicate. Each consists of

Illumina paired-end reads, which were subset to 25x coverage for prokaryotes and 50x for

eukaryotes. The results for prokaryote and eukaryote genome sequences  are displayed in

different colors because they are processed by different workflow branches (Figure 1).

Prokaryote data, regardless of genome size, were each completed in less than one hour of

automated analyses (Figure 4C) with RAM usage less than 15.0Gb (Figure 4D). In contrast, the

runtime for eukaryotic genome sequences had a substantial range that scaled linearly to genome

size. The largest genome took 13.6 hours of runtime. RAM usage ranged between 6.0 GB and

70.0 GB for the eukaryotic dataset.

All tests were run on a System 76 Thelio Major Linux Desktop with a Ryzen 9 7950x 16-core

processor.

**Discussion**

Pests and pathogens can emerge and rapidly adapt, often evading detection by traditional

biosurveillance methods (Korber et al. 2020). In response to these challenges, we developed

*PathogenSurveillance,* a user-friendly computational workflow for analyzing WGS data, with

features specific for pest and pathogen detection. *PathogenSurveillance* provides a scalable

computational workflow that is highly portable for implementation on any Linux cloud or

workstation. Our implementation follows the FAIR principles. Importantly, the pipeline works

for samples belonging to either known or unknown taxa and can resolve clonality or novel

variants if WGS data is available for the clades in question.

A key design principle of *PathogenSurveillance* is its commitment to lowering the barrier to

entry and accelerating the analyses of WGS data. Population-level analysis requires domain

specific knowledge in molecular evolution and bioinformatics, particularly for selecting

appropriate references, installing software and dependencies, and constructing robust

phylogenies. At its core, *PathogenSurveillance* is a generalizable population genomics pipeline,

featuring a rules-based system that automates reference selection. Leveraging the Nextflow

workflow management system, this design empowers users from diverse backgrounds, including

those without formal training in molecular evolution and bioinformatics, to effectively analyze

WGS data. Additionally, the organization of results reflects a deliberate design intended to

support further in-depth investigations, both through manual and automated approaches.

Collectively, *PathogenSurveillance* provides a streamlined and accessible framework for

automating initial population genomic analysis, supporting both applied and fundamental

research applications.

There are constraints to *PathogenSurveillance* that should be considered. First, the pipeline does

not support analyses of viruses, as they would require their own workflow branch to parse

metagenomic data and employ specialized approaches for taxonomic identification (Rangel-

Pineros et al. 2023). Second, the accuracy in which the pipeline predicts taxonomic identities is

constrained by the contents of databases used and the correctness of the taxonomic names they

contain. Third, *PathogenSurveillance* was designed for WGS data derived from cultured

organisms, which may limit applicability to metagenomic or environmental samples. Fourth,

*PathogenSurveillance* employs default parameters across all steps, which may require

appropriate adjustments for non-standard cases or refining reference selection. Finally, the

pipeline can be computationally demanding. While the Nextflow framework allows efficient

memory allocation per task, certain processes and samples may require substantial memory.

Moreover, the pipeline generates numerous intermediate files, requiring storage capacity that is

approximately five times greater than the size of input files.

Nonetheless, there are ways to apply *PathogenSurveillance* that mitigate these constraints. For

example, we have identified contaminating reads in some sample datasets, which is analogous to

a low complexity metagenome dataset. When left unfiltered, the pipeline successfully resolved

the taxonomic identity of the primary organism, suggesting potential use in metagenome

analyses. Regarding use of default parameters, caching gives users the flexibility of running the

pipeline with a preliminary assessment and rerunning it with refined parameters or references

without repeating the entire analysis. This not only saves considerable time but also supports

reproducibility through automated, consistent execution. To mitigate storage requirements, users

can clear the cache after analysis. However, for taxa that are repeatedly analyzed, retaining

cached results may be advantageous, as it offsets rerun times.

In summary, *PathogenSurveillance* automates the analyses of WGS data with a single command.

It enhances traditional diagnostic approaches by improving analytical resolution and enriching

the data available for more robust interpretation. It can also aid in identifying novel or emerging

pathogens as well as place variants within taxa. These features underscore the potential use of

*PathogenSurveillance* in global pathogen and pest biosurveillance (Carvajal-Yepes et al. 2019;

Weisberg et al. 2021).

**Data and Source Code Availability**

*PathogenSurveillance* is free and open source under the MIT license. The source code is hosted

on Github ([https://github.com/nf-core/*PathogenSurveillance*](https://github.com/nf-core/PathogenSurveillance)) and documentation is available on

nf-core ([https://nf-co.re/*PathogenSurveillance*/](https://nf-co.re/PathogenSurveillance/)). All data used in the validation of the pipeline

presented here are available in the test data repository on GitHub ([https://github.com/nf-](https://github.com/nf-)

[core/test-datasets/tree/*PathogenSurveillance*](https://github.com/nf-core/test-datasets/tree/PathogenSurveillance)). The scripts and input data used to create figures in

this manuscript are also available on GitHub

([https://github.com/grunwaldlab/*PathogenSurveillance*_publications](https://github.com/grunwaldlab/PathogenSurveillance_publications)).

Test datasets consisting of sequences that are automatically downloaded from NCBI are

available as profiles and can easily be run as documented at [https://github.com/nf-core/test-](https://github.com/nf-core/test-)

datasets/tree/*PathogenSurveillance*. Supplementary tables and figures are found at

https://github.com/grunwaldlab/pathogensurveillance_publications/tree/main/publication/supple

mentary_data.

## Acknowledgements

We thank members of the Chang and Grünwald laboratories for their valuable input and support.

We also thank Melodie Putnam for her thoughtful advice on the design principles of

*PathogenSurveillance,* Dr. Maude David for providing bacteria of the honeybee microbiota, and

Charles Paulsen for extracting DNA and making libraries. We also thank the nf-core community

for developing the infrastructure and resources for Nextflow pipelines, in particular Harshil

Patel, Phil Ewels, Matthias Hörtenhuber, Mahesh Binzer-Panchal, and Maxime Garcia, for their

assistance in reviewing and releasing the pipeline. Lastly, we thank the Center for Quantitative

Life Sciences (CQLS) and Department of Botany and Plant Pathology (BPP) at Oregon State

University and SCINet at the United States Department of Agriculture – Agricultural Research

Service (USDA-ARS) for supporting high-performance computing infrastructures.

## Funding

503   This work was supported by grants from USDA ARS (2072-22000-045-000-D) to NJG, USDA

504   NIFA (2021-67021-34433; 2023-67013-39918) to JHC and NJG, USDA NIFA (2023-51181-

505   41170) to JHC, USDA Plant Disease Recovery System (NPDRS) to NJG, and USDA APHIS to

506   NJG.

## Author Contributions

510  ZSLF designed and implemented nf-core/*PathogenSurveillance*. MAS, CPR, LKB, FIB, AJW,

511  and HP contributed scripts and modules, and/or enhanced or tested pipeline reliability, usability

512  and performance, and TRS cultured bacteria from honeybees. ZSLF, MAS, CPR, JHC, and NJG

513  wrote the manuscript, with input from all authors. NJG and JHC led the conceptualization and

514  planning of nf-core/*PathogenSurveillance*, supervised its development, and secured funding.

## Conflict of Interest

518  The authors declare no conflict of interest.

## References

Bushnell B. 2014. BBMap: a fast, accurate, splice-aware aligner. Available from:
https://www.osti.gov/biblio/1241166

Carvajal-Yepes M, Cardwell K, Nelson A, Garrett KA, Giovani B, Saunders DGO, Kamoun S,
Legg JP, Verdier V, Lessel J, et al. 2019. A global surveillance system for crop diseases.
*Science* 364:1237–1239.

Chen S, Zhou Y, Chen Y, Gu J. 2018. fastp: an ultra-fast all-in-one FASTQ preprocessor.
*Bioinformatics* 34:i884–i890.

David S, Cohen V, Reuter S, Sheppard AE, Giani T, Parkhill J, the European Survey of
Carbapenemase-Producing Enterobacteriaceae (EuSCAPE) Working Group, the
ESCMID Study Group for Epidemiological Markers (ESGEM), Rossolini GM, Feil EJ,
et al. 2020. Integrated chromosomal and plasmid sequence analyses reveal diverse modes
of carbapenemase gene spread among *Klebsiella pneumoniae*. *Proc. Natl. Acad. Sci.*
*U.S.A.* 117:25043–25054.

De Coster W, Rademakers R. 2023. NanoPack2: population-scale evaluation of long-read
sequencing data.Alkan C, editor. *Bioinformatics* 39:btad311.

De Visser C, Johansson LF, Kulkarni P, Mei H, Neerincx P, Joeri Van Der Velde K,
Horvatovich P, Van Gool AJ, Swertz MA, Hoen PAC 'T, et al. 2023. Ten quick tips for
building FAIR workflows.Palagi PM, editor. *PLoS Comput Biol* 19:e1011369.

Di Tommaso P, Chatzou M, Floden EW, Barja PP, Palumbo E, Notredame C. 2017. Nextflow
enables reproducible computational workflows. *Nat Biotechnol* 35:316–319.

Djordjevic SP, Jarocki VM, Seemann T, Cummins ML, Watt AE, Drigo B, Wyrsch ER, Reid CJ,
Donner E, Howden BP. 2024. Genomic surveillance for antimicrobial resistance — a
One Health perspective. *Nat Rev Genet* 25:142–157.

Eggertsson HP, Kristmundsdottir S, Beyter D, Jonsson H, Skuladottir A, Hardarson MT,
Gudbjartsson DF, Stefansson K, Halldorsson BV, Melsted P. 2019. GraphTyper2 enables
population-scale genotyping of structural variation using pangenome graphs. *Nat
Commun* 10:5402.

Ewels P, Magnusson M, Lundin S, Käller M. 2016. MultiQC: summarize analysis results for
multiple tools and samples in a single report. *Bioinformatics* 32:3047–3048.

Fisher MC, Henk DanielA, Briggs CJ, Brownstein JS, Madoff LC, McCraw SL, Gurr SJ. 2012.
Emerging fungal threats to animal, plant and ecosystem health. *Nature* 484:186–194.

Gardy JL, Loman NJ. 2018. Towards a genomics-informed, real-time, global pathogen
surveillance system. *Nat Rev Genet* 19:9–20.

Grünwald NJ, Goss EM. 2011. Evolution and population genetics of exotic and re-emerging
pathogens: Novel tools and approaches. VanAlfen, NK and Bruening, G and Leach, JE,
editor. *Annual Review of Phytopathology* 49:249–267.

Gurevich A, Saveliev V, Vyahhi N, Tesler G. 2013. QUAST: quality assessment tool for
genome assemblies. *Bioinformatics* 29:1072–1075.

Hamelin RC, Bilodeau GJ, Heinzelmann R, Hrywkiw K, Capron A, Dort E, Dale AL, Giroux E,
Kus S, Carleson NC, et al. 2022. Genomic biosurveillance detects a sexual hybrid in the
sudden oak death pathogen. *Commun Biol* 5:477.

Huang W, Li L, Myers JR, Marth GT. 2012. ART: a next-generation sequencing read simulator.
*Bioinformatics* 28:593–594.

Hulme PE. 2009. Trade, transport and trouble: managing invasive species pathways in an era of
globalization. *Journal of Applied Ecology* 46:10–18.

Iles LC, Fulladolsa AC, Smart A, Bonkowski J, Creswell T, Harmon CL, Hammerschmidt R,
Hirch RR, Rodriguez Salamanca L. 2021. Everything is faster: How do land-grant

university–based plant diagnostic laboratories keep up with a rapidly changing world?
*Annu. Rev. Phytopathol.* 59:333–349.

Irber L, Pierce-Ward NT, Abuelanin M, Alexander H, Anant A, Barve K, Baumler C, Botvinnik
O, Brooks P, Dsouza D, et al. 2024. sourmash v4: A multitool to quickly search,
compare,and analyze genomic and metagenomic data sets. *JOSS* 9:6830.

Irber L, Pierce-Ward NT, Brown CT. 2022. Sourmash branchwater enables lightweight petabyte-
scale sequence search. *bioRxiv*:2022.11.02.514947.

Iruegas-Bocardo F, Weisberg AJ, Riutta ER, Kilday K, Bonkowski JC, Creswell T, Daughtrey
ML, Rane K, Grünwald NJ, Chang JH, et al. 2023. Whole genome sequencing-based
tracing of a 2022 introduction and outbreak of *Xanthomonas hortorum* pv. *pelargonii*.
*Phytopathology®* 113:975–984.

Kamvar ZN, Tabima JF, Grünwald NJ. 2014. *Poppr*: an R package for genetic analysis of
populations with clonal, partially clonal, and/or sexual reproduction. *PeerJ* 2:e281.

Konstantinidis KT, Tiedje JM. 2005. Genomic insights that advance the species definition for
prokaryotes. *Proc. Natl. Acad. Sci. U.S.A.* 102:2567–2572.

Korber B, Fischer WM, Gnanakaran S, Yoon H, Theiler J, Abfalterer W, Hengartner N, Giorgi
EE, Bhattacharya T, Foley B, et al. 2020. Tracking Changes in SARS-CoV-2 Spike:
Evidence that D614G Increases Infectivity of the COVID-19 virus. *Cell* 182:812-
827.e19.

Liebhold AM, Brockerhoff EG, Garrett LJ, Parke JL, Britton KO. 2012. Live plant imports: the
major pathway for forest insect and pathogen invasions of the US. *Frontiers in Ecology*
*and the Environment* 10:135–143.

Manni M, Berkeley MR, Seppey M, Simão FA, Zdobnov EM. 2021. BUSCO Update: Novel and
Streamlined Workflows along with Broader and Deeper Phylogenetic Coverage for
Scoring of Eukaryotic, Prokaryotic, and Viral Genomes.Kelley J, editor. *Molecular*
*Biology and Evolution* 38:4647–4654.

Meyerson LA, Mooney HA. 2007. Invasive alien species in an era of globalization. *Frontiers in*
*Ecology and the Environment* 5:199–208.

Motta EVS, Moran NA. 2024. The honeybee microbiota and its impact on health and disease.
*Nat Rev Microbiol* 22:122–137.

Oakeson KF, Wagner JM, Mendenhall M, Rohrwasser A, Atkinson-Dunn R. 2017.
Bioinformatic analyses of whole-genome sequence data in a public health laboratory.
*Emerg. Infect. Dis.* 23:1441–1445.

Ondov BD, Treangen TJ, Melsted P, Mallonee AB, Bergman NH, Koren S, Phillippy AM. 2016.
Mash: fast genome and metagenome distance estimation using MinHash. *Genome Biol*
17:132.

Petit RA, Read TD. 2020. Bactopia: a Flexible Pipeline for Complete Analysis of Bacterial
606            Genomes.Segata N, editor. *mSystems* 5:e00190-20.

607    Pierce NT, Irber L, Reiter T, Brooks P, Brown CT. 2019. Large-scale sequence comparisons
608            with sourmash. *F1000Res* 8:1006.

609    Qin Q-L, Xie B-B, Zhang X-Y, Chen X-L, Zhou B-C, Zhou J, Oren A, Zhang Y-Z. 2014. A
610            Proposed Genus Boundary for the Prokaryotes Based on genomic insights. *J Bacteriol*
611            196:2210–2215.

612    Rangel-Pineros G, Almeida A, Beracochea M, Sakharova E, Marz M, Reyes Muñoz A, Hölzer
613            M, Finn RD. 2023. VIRify: An integrated detection, annotation and taxonomic
614            classification pipeline using virus-specific protein profile hidden Markov
615            models.Ouzounis CA, editor. *PLoS Comput Biol* 19:e1011422.

616    Tian L, Huang C, Mazloom R, Heath LS, Vinatzer BA. 2020. LINbase: a web server for
617            genome-based identification of prokaryotes as members of crowdsourced taxa. *Nucleic*
618            *Acids Research* 48:W529–W537.

619    Weisberg AJ, Grünwald NJ, Savory EA, Putnam ML, Chang JH. 2021. Genomic approaches to
620            plant-pathogen epidemiology and diagnostics. *Annu. Rev. Phytopathol.* 59:311–332.

621    Williams DJ, Grimont PAD, Cazares A, Grimont F, Ageron E, Pettigrew KA, Cazares D,
622            Njamkepo E, Weill F-X, Heinz E, et al. 2022. The genus *Serratia* revisited by genomics.
623            *Nat Commun* 13:5195.

624    Wood DE, Lu J, Langmead B. 2019. Improved metagenomic analysis with Kraken 2. *Genome*
625            *Biol* 20:257.

## 627    Figures

**Figure 1. *PathogenSurveillance* automates comprehensive analysis of prokaryotic and**

**eukaryotic whole genome sequencing data.** A TSV file indicating paths or URLs to FASTQ or

FASTA files of short or long read sequencing data initiates the process of downloading and

formatting of input files and references. The next part of the main branch quality controls

sequencing reads and generates assemblies as well as *k*-mer sketches. It then diverges into three

branches. The left branch is for samples of prokaryotic origin and will generate core phylogenies

based on all shared orthologous gene sequences and variants, respectively, for each group of

related samples. The right branch is for samples of eukaryotic origin and will build a

phylogenetic tree for each group of related samples based on shared, single-copy BUSCO gene

sequences. The middle branch creates SNP phylogenies for both prokaryotic and eukaryotic

samples. Finally, the branches converge and *PathogenSurveillance* will generate a final HTML

report with interactive plots and tables as well as quality control reports. Prominent steps in the

workflow are printed in black beside each node with select corresponding tools used printed

below in green.

**Figure 2.** *PathogenSurveillance* **automates reference selection for phylogenetic analyses.**

Shown is a hypothetical example illustrating sampling of genomes from **(A)** publicly available

references for **(B)** multigene phylogenies and **(C)** SNP-based phylogenies or minimum spanning

networks, respectively. **(A)** First, *PathogenSurveillance* compares *k*-mer sketches of raw reads to

sketches of all NCBI RefSeq assemblies using BBmap sendsketch. Taxa likely present in

samples are identified based on match similarity metrics (shown as red nodes in the taxonomic

tree in (**A**)) and representative assemblies of subtaxa are downloaded for each detected taxon

(black nodes). The pipeline prioritizes enrichment of candidate references from more closely

related taxa but also includes more distant taxa in case the initial identification was incorrect. (**B**)

From the set of references downloaded a subset are selected to provide context for multi-gene

phylogenetic trees based on pairwise ANI estimates between samples and references. References

estimated to be most similar to each sample are always included in addition to a minimal set of

references selected for the set of samples as a whole that occur at a range of similarities to each

sample. Each cell in the matrix represents a role that references can fit into. References are

ordered by how many cells each can fill, as is shown in the histogram, and selected in this order

until all cells are filled.  (**C**) Mapping references are also selected for SNP calling based on

estimated ANI values. A conceptual heatmap illustrates pairwise ANI comparisons, with cells

exceeding the minimum threshold required shown in color. The reference with an estimated ANI

exceeding a threshold for the most samples is chosen and this process is repeated until all

samples have an assigned reference. Ties are broken based on mean ANI. A conceptual SNP-

based phylogenetic tree demonstrates that only clusters with mapping references A and B met

the minimum group size criteria for SNP calling and phylogenetic inference.

**Figure 3.** *PathogenSurveillance* **core genome phylogeny reproduces a previously published**

**phylogeny fully resolving species and lineages.** The tanglegram shows congruence between

671     (**A**) a maximum likelihood core gene phylogeny generated by *PathogenSurveillance*, and (**B**) a

672     phylogeny reproduced from the literature. Matched samples are linked across trees by lines, with

673     color-coding denoting lineage assignments. Major species and lineages (L#) are labeled as

674     published. Scale bars represent the number of nucleotide substitutions per site. See narrative for

675     reference citation.

**Figure 4.** *PathogenSurveillance* **demonstrates linear and scalable performance across a**

**wide range of sample and genome sizes.** Two test datasets were used to evaluate how the RAM

and runtime of the pipeline scaled with number of samples and genome size. (**A**) and (**B**) show

results for datasets increasing in sample sizes, while (**C**) and (**D**) show results for datasets with

increasing genome sizes. Runtime (in clock hours) is plotted in (**A**) and (**C**), and maximum

random-access memory (RAM) usage (in gigabytes (GB)) is plotted in (**B**) and (**D**). For genome

size tests, each data set consisted of three samples of a given species and eukaryotes and

prokaryotes are summarized separately since they are analyzed with different methods. Each

dataset was analyzed in triplicate by *PathogenSurveillance*.

686    **Supplementary data**

```
output_directory
├── aligned_reads
│   ├── <reference_id>--<sample_id>.bam                            : Unfiltered read alignments to references in BAM format
│   ├── <reference_id>--<sample_id>.formatted.bam                  : Quality filtered read alignments to references in BAM format
│   ├── <reference_id>--<sample_id>.formatted.bam.csi              : Index for the filtered BAM files produced by samtools index
│   └── <reference_id>--<sample_id>.formatted.MarkDuplicates.metrics.txt : Output from picard MarkDuplicates containing summary data tables
├── annotations
│   └── <method>
│       ├── <sample_id>.embl                                       : Genome annotations and sequences in (multi) EMBL format
│       ├── <sample_id>.faa                                        : CDS/ORF amino acid sequences in FASTA format
│       ├── <sample_id>.ffn                                        : Feature nucleotide sequences in FASTA format
│       ├── <sample_id>.fna                                        : Replicon/contig DNA sequences in FASTA format
│       ├── <sample_id>.gbff                                       : Annotations of genomes in (multi) GenBank format
│       ├── <sample_id>.gff3                                       : Annotations of genomes in GFF3 format
│       ├── <sample_id>.hypotheticals.faa                          : Hypothetical protein CDS amino acid sequences in FASTA format
│       ├── <sample_id>.hypotheticals.tsv                          : Information on hypothetical protein CDSs in TSV format
│       ├── <sample_id>.tsv                                        : Information for protein CDSs in TSV format
│       └── <sample_id>.txt                                        : Genome annotation summary statistics in plain text format
├── assemblies
│   ├── flye
│   │   ├── <sample_id>.assembly_graph.gfa.gz                      : Genome assembly graphs in gzipped GFA format
│   │   ├── <sample_id>.assembly_graph.gv.gz                       : Genome assembly in gzipped Graphviz format
│   │   ├── <sample_id>.assembly_info.txt                          : Statistics on contigs produced by Flye in TSV format
│   │   ├── <sample_id>.assembly.fasta.gz                          : Genome assemblies in gzipped FASTA format
│   │   ├── <sample_id>.flye.log                                   : Log file produced by Flye in plain text format
│   │   └── <sample_id>.params.json                                : Parameters used to run Flye in JSON format
│   └── spades
│       ├── <sample_id>.assembly.gfa.gz                            : Genome assembly graphs in gzipped GFA format
│       ├── <sample_id>.scaffolds.fa.gz                            : Genome assemblies in gzipped FASTA format
│       ├── <sample_id>.spades.log                                 : Log file produced by Spades in plain text format
│       └── <sample_id>.warnings.log                               : Warnings produced by Spades in plain text format
├── busco
│   ├── <sample_id>--<database>-busco                              : BUSCO output directory
│   ├── <sample_id>--<database>-busco.batch_summary.txt            : BUSCO analysis summary statistics in TSV format
│   └── <sample_id>--<database>-busco.log                          : Log file produced by BUSCO in plain text format
├── downloads
│   ├── annotations
│   │   └── <reference_id>.gff.gz                                  : Genome annotations downloaded by the pipeline in gzipped GFF format
│   ├── assemblies
│   │   └── <reference_id>.fasta.gz                                : Genome assemblies downloaded by the pipeline in gzipped FASTA format
│   └── reads
│       └── <reference_id>_<orientation>.fastq.gz                  : Reads downloaded by the pipeline in gzipped FASTQ format
├── fastp
│   ├── <sample_id>.fastp.html                                     : FASTP report with read quality and adapter trimming statistics in HTML format
│   ├── <sample_id>.fastp.json                                     : FASTP report with read quality and adapter trimming statistic in JSON format
│   └── <sample_id>.fastp.log                                      : Log file produced by FASTP
├── metadata
│   ├── reference_metadata.tsv                                     : Reference metadata in TSV format
│   └── sample_metadata.tsv                                        : Sample metadata in TSV format
├── pipeline_info
│   ├── execution_report_<date>.html                               : Statistics like time and ram usage for pipeline execution as a HTML report
│   ├── execution_trace_<date>.txt                                 : Statistics like time and ram usage for pipeline execution in TSV format
│   ├── messages.tsv                                               : Errors, warnings, and messages produced by the pipeline in TSV format
│   ├── params_<date>.json                                         : Parameters used when running the pipeline in JSON format
│   ├── pathogensurveillance_run_info.yml                          : Pipeline run metadata in YML format
│   ├── pipeline_dag_<date>.html                                   : Flowchart of the pathogensurveillance pipeline automatically generated by Nextflow
│   └── version_info.yml                                           : Versions of software used in the pipeline in YML format
├── pirate
│   └── <report_id>_results                                        : Pirate output directory with gene orthology information
├── pocp
│   └── <report_id>_pocp.tsv                                       : Percentage of conserved proteins in TSV format
├── quality_control
│   ├── fastqc
│   │   ├── <reads_id>_fastqc.html                                 : FastQC report on read quality in HTML format
│   │   └── <reads_id>_fastqc.zip                                  : Zipped directory of FastQC output
│   ├── multiqc
│   │   └── <report_id>_multiqc                                    : Directory of MultiQC output with intermediate files used to make the MultiQC report
│   │       └── multiqc_report.html                                : MultiQC report combining the summary quality control output in HTML format
│   ├── nanoplot
│   │   ├── <sample_id>_nanoplot-report.html                       : Nanoplot report on read quality in HTML format
│   │   └── <sample_id>_NanoStats.txt                              : Nanoplot report on read quality in plain text format
│   └── quast
│       ├── <sample_id>.tsv                                        : Quast summary statistics on genome assembly quality in headerless TSV format
│       └── <sample_id>
│           └── report.html                                        : Quast report with data on genome assembly quality in HTML format
├── reference_data
│   ├── considered
│   │   └── <taxon_id>.tsv                                         : Metadata of available assemblies on NCBI in TSV format
│   ├── downloaded
│   │   └── <sample_id>.tsv                                        : Metadata of references selected for download from NCBI in TSV format
│   └── selected
│       ├── <report_id>_busco_references.tsv                       : IDs of references selected for multigene phylogenies in TSV format
│       ├── <report_id>_core_references.tsv                        : IDs of references selected for multigene phylogenies in TSV format
│       └── <report_id>_mapping_references.tsv                     : IDs of references selected for multigene phylogenies in TSV format
├── reports
│   └── <report_id>_pathsurveil_report.html                        : Primary report for pathogensurveillance in HTML format
├── sendsketch
│   └── <sample_id>.txt                                            : Table returned by BBmap sendsketch with initial identifications in TSV format
├── shared_genes
│   └── <method>
│       └── <gene_id>.aligned.fas                                  : Aligned sequences for each gene shared among a group of organisms in FASTA format
├── sketch_comparisons
│   ├── ani_matricies
│   │   └── <report_id>_comp.csv                                   : Estimated ANI similarity matrix made by sourmash compare in CSV format
│   └── sketches
│       └── <id>.sig                                               : FracMinHash signature of the given sequence made by sourmash sketch in JSON
├── trees
│   ├── busco
│   │   └── <report_id>--<cluster_id>.treefile                     : Trees infered from multigene phylogeny in Newick format
│   ├── core
│   │   └── <report_id>--<cluster_id>.treefile                     : Trees infered from multigene phylogeny in Newick format
│   └── snp
│       └── <report_id>--<reference_id>.treefile                   : Trees inferred from variant analysis in Newick format
└── variants
    ├── <report_id>--<reference_id>.fasta                          : Filtered variants in FASTA format
    ├── <report_id>--<reference_id>.vcf.gz                         : Unfiltered variants in VCF format
    └── <report_id>--<reference_id>.vcffilter.vcf.gz               : Filtered variants in VCF format
```

688   **Supplementary Figure 1.** *PathogenSurveillance* organizes and names output files for

689   **further analyses.** The left side displays the hierarchical structure of output files. Angle brackets

690   (<>) show run specific identifiers for references, samples, and reports. The right side provides

691   brief descriptions of each file type, highlighting their applications in downstream analyses.

Supplementary Figure 2. *PathogenSurveillance* **automates downloading of references based**

on taxa found in the initial identification. Representatives of taxa predicted by sendsketch are

chosen based on available metadata relevant to assembly quality and downloaded. This shows

the criteria used to choose references for two samples of *Gilliamella apicola*. Representatives of

the species, genus, and family are chosen, in case the species-level identification is incorrect.

Potential references are represented by rows and sorted from best to worst based on the selection

criteria represented by columns. Selection criteria columns are sorted from most important to

least important.

ANI values for samples 305 and 379 with a range of simulated error rates

Potential reference assemblies	Contextual	Mapping	305 (NA)	379 (NA)	305 (0)	379 (0)	305 (0.01)	379 (0.01)	305 (0.02)	379 (0.02)	305 (0.03)	379 (0.03)	305 (0.05)	379 (0.05)	305 (0.1)	379 (0.1)
Gilliamella apicola SCGC AB-598-B02 (GCF_000725165.1)	✓	✓	**0.97**	**0.98**	**0.97**	**0.98**	**0.96**	**0.97**	0.95	**0.96**	**0.94**	**0.95**	**0.92**	**0.93**	**0.87**	**0.88**
Gilliamella sp. wkB7 (GCF_001693435.1)	✓	✓	0.97	0.97	0.97	0.97	0.96	0.96	**0.95**	**0.95**	0.94	0.94	0.92	0.92	0.88	0.88
Gilliamella apicola (GCF_000599985.1)	✓	✗	0.95	0.95	0.95	0.95	0.94	0.94	0.93	0.93	0.92	0.92	0.91	0.91	0.86	0.86
Gilliamella apicola SCGC AB-598-I20 (GCF_000725175.1)	✓	✗	0.87	0.88	0.87	0.88	0.86	0.87	0.86	0.86	0.85	0.85	0.84	0.84	0.80	0.78
Gilliamella bombicola (GCF_900094945.1)	✗	✗	0.87	0.87	0.87	0.87	0.86	0.86	0.85	0.86	0.85	0.85	0.84	0.83	0.80	0.79
Gilliamella apis (GCF_002142155.1)	✗	✗	0.87	0.87	0.87	0.87	0.86	0.86	0.85	0.85	0.85	0.85	0.84	0.83	0.79	0.77
Gilliamella mensalis (GCF_900103085.1)	✗	✗	0.87	0.87	0.87	0.87	0.86	0.86	0.85	0.85	0.85	0.85	0.84	0.84	0.79	0.79
Gilliamella bombi (GCF_900103255.1)	✗	✗	0.86	0.86	0.86	0.86	0.85	0.86	0.84	0.85	0.84	0.84	0.83	0.83	0.79	0.77
Gilliamella intestini (GCF_900094935.1)	✗	✗	0.86	0.86	0.86	0.86	0.85	0.86	0.83	0.85	0.83	0.84	0.82	0.83	0.79	0.00
Frischella perrara (GCF_000807275.1)	✓	✗	0.86	0.86	0.86	0.86	0.84	0.85	0.84	0.85	0.82	0.83	0.82	0.83	0.81	0.77
uncultured Gilliamella sp. (GCF_945271295.1)	✓	✗	0.84	0.85	0.84	0.85	0.84	0.84	0.82	0.83	0.82	0.83	0.80	0.82	0.77	0.00
Zophobihabitans entericus (GCF_011745665.1)	✗	✗	0.83	0.82	0.83	0.82	0.82	0.81	0.80	0.81	0.81	0.81	0.79	0.79	0.77	0.00
Orbaceae bacterium ac157xtp (GCA_045014155.1)	✓	✗	0.82	0.82	0.82	0.82	0.82	0.82	0.81	0.81	0.79	0.81	0.79	0.77	0.79	0.00
Candidatus Schmidhempelia bombi str. Bimp (GCF_000471645.3)	✓	✗	0.80	0.83	0.80	0.83	0.80	0.82	0.80	0.82	0.80	0.80	0.79	0.79	0.79	0.00
Orbus sturtevantii (GCF_036251875.1)	✗	✗	0.81	0.81	0.81	0.81	0.81	0.81	0.79	0.81	0.77	0.81	0.77	0.77	0.00	0.77
Utexia brackfieldae (GCF_036251705.1)	✗	✗	0.78	0.77	0.78	0.77	0.78	0.77	0.78	0.77	0.00	0.00	0.00	0.00	0.00	0.00

Supplementary Figure 3. *PathogenSurveillance* **automates selection of contextual and mapping references from those downloaded.** Nanopore reads of two samples of *Gilliamella apicola* (305 and 379) were used as test data. Short reads were simulated from the nanopore reads with a range of error rates (indicated in the parentheses in column names starting third column). *Pathogensurveillance* was run on each pair of samples from which references were selected for multigene phylogenies (contextual) and variant calling (mapping). ANI values estimated by sourmash are shown in cells and bolded ANI values represent which mapping reference was chosen for each pair of samples.