SOORENA: Self-lOOp containing or autoREgulatory Nodes in biological network Analysis

Hala Arar[1], Jehad Aldahdooh[2], Payman Nickchi[1], Mohieddin Jafari*[3,4,5]

1) Department of Statistics, University of British Columbia, Vancouver, BC, Canada
2) Research Programs Unit, University of Helsinki, Helsinki, Finland
3) Department of Biochemistry and Developmental Biology, University of Helsinki, Helsinki, Finland
4) Faculty of Medicine and Health Technology, Tampere University, Tampere, Finland
5) Tampere Institute for Advanced Study, Tampere University, Tampere, Finland

* Corresponding author:

Mohieddin Jafari,

mohieddin.jafari@helsinki.fi

Abstract

Autoregulatory mechanisms, in which proteins modify their own activity or expression, are

fundamental components of biological regulatory systems but remain challenging to identify

systematically within the scientific literature. Manual curation is outpaced by publication growth,

with self-regulation often described implicitly. To address the lack of automated tools for

identifying   protein   autoregulatory   mechanisms,   we   present   SOORENA

(https://soorena.it.helsinki.fi/soorena/), a two-stage transformer-based model designed to predict

and classify such mechanisms within PubMed abstracts. In the first stage, the model determines

whether a publication describes any form of protein autoregulation. In the next stage, positive

instances are further classified into one of seven mechanistic categories: autophosphorylation,

autoubiquitination, autocatalytic activity, autoinhibition, autolysis, autoinducer production, and

autoregulation. SOORENA was fine-tuned from PubMedBERT using a curated dataset of 1,332

experimentally validated abstracts sourced from UniProt-referenced publications. On a held-out

test set, the first stage achieved an accuracy of 96.0% and a precision of 97.8%, effectively

minimizing false positive propagation. The second stage showed robust performance across all

classes, with an overall accuracy of 95.5% and a macro-F1 score of 96.2%, including perfect

classification on the test set for the two least-represented categories. Error analysis revealed that

most misclassifications occurred between mechanistically related categories, suggesting that the

model's learned representations reflect underlying biological relationships. We deployed SOORENA

across 3,340,955 PubMed abstracts, identifying 85,145 publications containing autoregulatory

mechanisms. After gene annotation extraction, these yielded 97,657 protein-specific records.

Integration with curated databases (1,332 UniProt annotations, 995 SIGNOR, 61 TRRUST, 20

OmniPath interactions) yielded an extensive resource of 100,065 records accessible through an

interactive Shiny application. Pattern-matching analysis identified cross-regulation as a source of

false positives (3.1% of predictions), arising from the model's inability to identify which protein in

multi-protein abstracts exhibits autoregulatory behavior. These results demonstrate that domain-

specific language models can scale the discovery and curation of biologically critical self-regulatory

mechanisms.

1. Introduction

Autoregulation refers to a biological process in which a protein modulates its own abundance or activity through direct molecular feedback, enabling precise control of cellular function [1]. These self-regulatory processes are widespread across signaling, transcriptional, and metabolic networks, where they contribute to homeostasis, robustness, and rapid adaptation to changing environments [2]. Autoregulatory motifs are among the most common topological features observed in biological regulatory systems, particularly in transcription factor networks and enzyme signaling pathways [3–5]. Although they are often ignored in static network modeling due to limitations in current methods and algorithms, such as those used for centrality or module detection analyses, these motifs cannot be disregarded in dynamic network modeling. Notably, when represented as self loops in network models, they cannot be eliminated by any known model reduction techniques [6,7]. This underscores their fundamental importance in preserving the integrity and functionality of biological models.

Autoregulation operates through diverse molecular mechanisms. Enzymatic self-modification includes autophosphorylation by kinases, autoubiquitination by E3 ligases, autocatalytic reactions in metabolic enzymes, and autolysis in proteases [8–11]. At the gene expression level, transcription factors can activate or repress their own transcription, forming positive or negative feedback loops that modulate response dynamics and reduce expression noise [12–14]. These mechanisms play essential roles in human disease. Dysregulated autoregulatory signaling contributes to oncogenic kinase activation, neurodegenerative protein dysfunction, and bacterial quorum-sensing (QS) pathways that

drive antimicrobial resistance, making autoregulatory proteins promising therapeutic

targets [15,16].

Despite their importance, autoregulatory mechanisms remain under-characterized

in public databases and are difficult to extract computationally from scientific literature.

Mechanistic descriptions are often embedded implicitly in text, using heterogeneous

phrasing rather than standardized vocabulary. For example, a statement such as "the

kinase phosphorylates itself" implies autophosphorylation without naming the mechanism

explicitly. Our keyword presence analysis supports this challenge. For example, fewer than

half of autophosphorylation publications include the literal term in their abstracts, and

similar gaps were observed across other mechanisms. As a result, conventional keyword-

based search and rule-based text mining struggle to retrieve relevant literature when

mechanistic descriptions are phrased implicitly.

Although manually curated resources such as UniProt provide high-quality

mechanistic annotations [17], expert review cannot keep pace with the rapid expansion of

biomedical literature. Publishing output now exceeds 1.5 million new scientific articles

annually [18], meaning that reviewing even a targeted subset of 250,000 abstracts would

require a tremendous amount of effort. This creates a substantial bottleneck in keeping

biological knowledge current and comprehensive.

Natural language processing (NLP) approaches using neural language models have

transformed information extraction in biomedicine by enabling semantic interpretation

beyond surface keywords [19, 20]. Domain-specific transformer architectures (for

example, PubMedBERT) capture biomedical terminology and contextual meaning more

effectively than general-domain models. This facilitates the detection of specialized

mechanistic relationships in text, such as autoregulation.

Here, we present Self-lOOp containing or autoREgulatory Nodes in biological

network Analysis (SOORENA), a transformer-based model with two stages for automated

identification and mechanistic classification of protein autoregulation in scientific

literature. In the first stage, the model identifies abstracts describing any form of

autoregulation. In the second stage, positive abstracts are classified into seven mechanistic

categories: autophosphorylation, autoubiquitination, autocatalytic activity, autoinhibition,

autolysis, autoinducer production, and autoregulation of gene expression. This architecture

improves computational efficiency by restricting the fine-grained classification to relevant

publications while preserving high precision in mechanism screening.

SOORENA was fine-tuned on 1,332 manually curated and experimentally validated

mechanism annotations mapped from UniProt to PubMed abstracts. Because our dataset

was highly unbalanced (with 711 examples of autophosphorylation but only 38 of

autoinducer production), we used a weighted loss function and evaluation metrics that

better captured performance on the underrepresented classes [24, 40]. These design

choices enabled robust recognition of both common and rare autoregulatory mechanisms.

Finally, we deployed SOORENA across 3,340,955 PubMed abstracts, identifying

85,145 publications (2.5%) containing autoregulatory mechanisms, which yielded 97,657

protein-specific records after gene annotation extraction. Integration with 1,332 UniProt

annotations and 1,076 interactions from pathway databases (SIGNOR [36], TRRUST [37],

OmniPath [35]) yielded a total of 100,065 curated autoregulatory records, creating the

largest resource to date for protein self-regulation in the literature. An interactive web

application allows researchers to explore predictions, filter by metadata, and access

ontology-linked standardized terms. SOORENA provides a practical framework to

accelerate the discovery and curation of protein self-regulatory mechanisms by integrating

expert-curated training data, domain-specific language models, and scalable inference

tools.

2. Methods

2.1 Data Collection

We constructed a large-scale biomedical text corpus by integrating publication

metadata from PubMed with manually curated annotations of autoregulatory mechanisms

from UniProt. Specifically, we utilized the Swiss-Prot subset of UniProt, which contains

reviewed protein entries with experimentally validated mechanism annotations [17].

Although UniProt references a vast number of publications (estimated at over 200 million,

many of which remain unverified), our dataset focuses on a high-confidence subset derived

from curated entries [17]. Abstracts were retrieved via the PubMed API and used for

language modeling, while UniProt served as the source of validated autoregulatory labels,

which are embedded within individual protein records [39].

2.1.1 PubMed Corpus

We obtained a subset of 262,819 publications from PubMed, each containing a

PubMed Identifier (PMID), Title, Abstract, Journal, and Authors. These publications were

randomly selected from over two million abstracts corresponding to journals indexed in

UniProt to ensure representative coverage of literature relevant to protein function. The

dataset included 8,607 records lacking abstracts but contained no duplicate PMIDs.

2.1.2 UniProt Annotations

We extracted experimentally validated autoregulatory mechanism annotations from

the Universal Protein Resource [17]. These annotations are generated by expert curators

based on experimental evidence reported in the referenced publications. The UniProt

dataset consisted of 1,323,976 rows and 13 metadata fields describing protein-level

experimental findings. Each entry is tied to a protein via a UniProt accession number (AC)

and may reference supporting literature using PMIDs embedded in the RX field. Each

unique AC may have more than one reference available. Up to three fields (RP, RT, and RC,

which we later named as Term_in_RP, Term_in_RT, Term_in_RC) contain mechanistic terms

indicating evidence that a protein regulates its own activity or abundance. These term

columns were aggregated into a single "Terms" column for model training. Of all entries,

1,823 were labeled with autoregulatory mechanisms (number of rows with a known

autoregulatory mechanism), while 1,322,153 were unlabeled. A total of 181,779 rows had

missing PMIDs, including 10 labeled entries, which were removed because the model

required PubMed-linked text for training. Additionally, 89,620 PMIDs appeared multiple

times, since each protein record occupied its own row; these were later aggregated so that

each PMID corresponded to a single, combined entry. After aggregation, the dataset was

reduced from 1,142,197 rows to 268,619 unique PMIDs, of which 1,374 were labeled with

autoregulatory mechanisms. The reduction in labeled entries occurred because multiple

protein records often referenced the same PMID, and these were merged into a single

aggregated entry.

2.1.3 External Resources Integration

To augment coverage of experimentally validated autoregulatory interactions, we

integrated curated data from three established pathway databases: OmniPath, SIGNOR, and

TRRUST. OmniPath aggregates protein-protein interactions and regulatory relationships

from over 100 literature-curated sources [35]. We extracted all self-directed regulatory

interactions where source and target protein identifiers matched. SIGNOR provides

manually annotated causal interactions in human signaling pathways [36]. We queried

SIGNOR for instances where regulator and target proteins were identical. TRRUST contains

transcription factor-target regulatory relationships derived from text mining and manual

curation [37]. We extracted cases where a transcription factor regulates its own gene

expression. Duplicate interactions across sources were deduplicated while retaining source

attribution. Integration of external databases contributed 1,076 additional validated

autoregulatory cases (SIGNOR: 995, TRRUST: 61, OmniPath: 20), representing 1.1% of the

final dataset. These external resources were not used for model training but were

integrated into the final database for extensive coverage. External databases use varied

vocabulary for equivalent concepts (e.g., SIGNOR's "self-phosphorylation" maps to

autophosphorylation, "self-cleavage" maps to autolysis). SOORENA harmonizes source-

specific terms to enable unified cross-database queries.

2.1.4 Gene Annotation Extraction

To associate model predictions with specific proteins, we extracted gene and

protein annotations from publications using PubTator3 [38], a state-of-the-art named

entity recognition system for biomedical literature. PubTator3 processes full-text articles

(when available) rather than abstracts alone, providing more comprehensive entity

coverage. For each publication predicted as containing autoregulatory content, we

retrieved all gene/protein mentions and created individual database records for each

protein-publication pair. This approach accounts for papers describing multiple

autoregulatory proteins, resulting in more records than unique publications. Extracted

annotations include UniProt accession numbers, gene names, protein names, and organism

identifiers when available.

<u>2.2 Label Construction and Data Integration</u>

2.2.1 Merging PubMed and UniProt

UniProt annotations were mapped to PubMed metadata using PMIDs as a common

identifier. A join between two tables was applied to ensure that all PubMed publications

were retained, even if no corresponding UniProt record existed. Mechanism labels from

UniProt were added only when a PMID match was found. The resulting merged dataset

contained 262,819 PubMed publications in total, of which 1,349 were labeled with

autoregulatory mechanisms and 261,470 were unlabeled. The slight reduction in labeled

entries from 1,374 to 1,349 occurred because a small number of labeled PMIDs from

UniProt were not present in the PubMed corpus. A total of 8,607 entries from the PubMed

dataset were dropped because they lacked abstracts. Only two of these were labeled, and

abstracts were required for model training, leaving 1,347 labeled entries at this stage.

2.2.2 Term Analysis

To characterize the labeled data, all mechanistic terms associated with

autoregulatory behavior were extracted from the UniProt annotations. We identified a total

of 15 unique terms across the labeled subset, which shows substantial class imbalance. The

most frequent mechanism was autophosphorylation (711 instances), followed by

autocatalytic activity (133), autoubiquitination (121), autoregulation (119), and

autoinhibition (84). Less common terms included autolysis (41) and autoinducer

production (31), while several variants, such as autokinase, autocatalysis, and

autophosphatase, appeared only rarely. The ratio between the most and least frequent

terms (711:1) highlights the strong skewness toward phosphorylation-related

mechanisms. This is not surprising, as this is a common trend in molecular biology due to

extensive kinase research. These distributions informed later normalization and filtering

steps to ensure that rare but biologically meaningful mechanisms were retained during

modeling.

To assess how often mechanistic terms appeared explicitly in the literature, we

examined whether each annotated term occurred literally within its corresponding

abstract text. The results showed wide variability across mechanism types. Terms such as

autoactivation, autoinduction, and autolysis appeared in nearly all labeled publications,

while others were frequently absent from the text despite being experimentally confirmed

in UniProt - most notably autoubiquitination (14.0%), autophosphorylation (47.3%), and

autocatalytic (41.4%). This finding highlights that many descriptions of autoregulatory

mechanisms are phrased implicitly (for example, "the kinase phosphorylates itself") rather

than through standardized terminology. As a result, keyword searches or rule-based text

mining miss a large portion of the relevant literature. This highlights the need for a context-

aware language model that can understand implicit mechanistic descriptions.

A small subset of publications contained more than one autoregulatory mechanism

within the same abstract. Specifically, 31 publications (approximately 2.3% of all labeled

data) referenced multiple mechanisms, with an average of 2.1 mechanisms per publication

and a maximum of 3.

2.2.3 Feature Engineering

To prepare the text for model training, the title and abstract of each publication

were concatenated into a single text field to provide richer contextual information for

mechanism detection. The resulting field was stored as text and served as the primary

input for all subsequent modeling stages. The text was then cleaned using a series of

preprocessing steps: HTML entities such as "&" were decoded, URLs and email addresses

were removed, and excess whitespace was normalized. These operations ensured that the

model processed standardized and noise-free text while preserving important biomedical

terminology.

To evaluate data quality, text length was measured as the number of characters per

abstract. Only two publications contained fewer than 100 characters, indicating minimal

issues with incomplete text. Both of these publications were unlabeled. Across the dataset,

the mean text length was 1,348 characters (SD = 432, median = 1,351), suggesting a

consistent abstract structure across publications - with no apparent outliers in length.

Labeled publications were slightly longer (mean = 1,403, SD = 382; median = 1,402) than

unlabeled ones (mean = 1,348; SD = 433, median = 1,351).

We further standardized the labeled data by normalizing spelling and variant forms

of mechanistic terms to ensure consistent representation. Terms such as autoregulatory,

autoinhibitory, autocatalysis, and autoinduction were replaced with their canonical forms

(autoregulation, autoinhibition, autocatalytic, and autoinducer). After normalization, 11

unique mechanisms remained. To ensure balanced training, we retained only terms with at

least 35 examples, resulting in seven mechanism classes summarized in the total facet of

Fig. 1. Despite this filtering, a 711:38 imbalance persisted between the most and least

common mechanisms.

A small subset of publications (18 publications, 1.3 % of labeled data) referenced

multiple mechanisms, with up to three mechanisms in a single abstract. However, this

subset was insufficient to train a reliable multi-label classifier because of the sample size.

Therefore, in the current version of SOORENA, each publication was assigned a single

primary mechanism label (the first listed term) to maintain class balance and ensure stable

model training. After all cleaning, normalization, and filtering steps, the final modeling

dataset consisted of 254,197 total publications, of which 1,332 were labeled with one of the

seven supported mechanisms.

2.3 Train-Validation-Test Splits

Following dataset preparation, a total of 254,197 publications were retained, of which 1,332 contained experimentally validated autoregulatory mechanisms. These labeled examples were stratified by mechanism type to preserve class proportions across training, validation, and test sets. This stratification ensured that each mechanistic category was proportionally represented during model development, thereby minimizing sampling bias toward the mechanism class with the majority proportion (autophosphorylation).

Using this stratified procedure, 70% of labeled publications (n = 932) were assigned to the training set, while the remaining 30% (n = 400) were split evenly between validation and test sets (n = 200 each). This split was performed only on the labeled subset, meaning that the remaining 252,865 unlabeled publications were excluded from these initial splits and later incorporated during binary classification (Stage 1). The overall composition of datasets across the original stratified split, Stage 1 (binary detection), and Stage 2 (multiclass classification) is summarized in **Table 1**.

Table 1. Dataset composition across original, Stage 1, and Stage 2 splits

Split	Original (labeled only)	Stage 1 (pos + neg)*	Stage 2 (multi-class)
Train	932	2,796 (932 + 1864)	932
Test	200	600 (200 + 400)	200
Validation	200	600 (200 + 400)	200

| Total | 1,332 | 3,996 | 1,332 |

In the original split, the data were used to train a single-stage supervised model

limited to the labeled corpus. For Stage 1, the task was reformulated as binary

classification, where publications describing autoregulatory mechanisms were labeled 1,

and randomly sampled unlabeled publications were treated as 0. Each split was expanded

by adding unlabeled negatives at a 2:1 ratio, tripling the training volume while preserving

the same class balance across validation and test sets. This strategy improved the model's

ability to distinguish between mechanistic and non-mechanistic abstracts, reducing the

likelihood of false positives before passing candidates to Stage 2. Because unlabeled

publications were treated as negatives, a small number of true positives may exist within

the negative set. However, the expected contamination rate is low: only 1,332 of 254,197

publications (0.5%) carried validated labels, and the prevalence of autoregulatory content

in the broader literature is estimated at 2.5% based on deployed predictions. This level of

label noise is consistent with prior work showing that BERT-based classifiers are robust to

low rates of mislabeled negatives in positive-unlabeled settings [41].

For Stage 2, only the original labeled subsets (932 train, 200 validation, 200 test)

were used. This stage addressed multi-class mechanism classification, predicting one of

seven mechanism types. Because the dataset remained highly imbalanced (dominated by

autophosphorylation), class weights were applied during loss computation to equalize

contributions from minority classes. The class-wise counts within the labeled corpus are

shown in **Fig. 1.**

Figure 1. Per-class distribution of autoregulatory mechanisms across training, validation, test, and total subsets of the labeled dataset (n = 1,332). X-axes are scaled independently per panel.

These counts confirm that stratified sampling preserved each mechanism's class proportions across splits. The training subset captured ~70% of each class, while

validation and test sets maintained balanced representation for evaluation. Together, this

framework produced a robust two-stage learning design: Stage 1 for binary detection of

autoregulatory mechanisms across both labeled and unlabeled literature, and Stage 2 for

fine-grained classification of mechanism type within the labeled subset.

<u>2.4 Model Architecture</u>

SOORENA is a two-stage trained transformer-based classification model built on

PubMedBERT (microsoft/BiomedNLP-PubMedBERT-base-uncased-abstract-fulltext), a

BERT-base architecture pretrained solely on PubMed abstracts and full-text articles to

capture biomedical terminology and contextual semantics [20,21]. Stage 1 detects whether

a publication describes any autoregulatory mechanism, serving as a screening layer to filter

the broader biomedical literature. Stage 2 then assigns Stage 1-positive publications to one

of seven distinct mechanism categories. PubMedBERT has demonstrated superior

performance over general-domain BERT variants in biomedical entity recognition and

relation extraction tasks [20].

Both stages use the same architecture: a PubMedBERT encoder followed by a

dropout layer (p = 0.1) and a linear classification head. The stages are fine-tuned

independently, allowing hyperparameter optimization and checkpoint selection specific to

the prediction task (**Fig. 2**).

Figure 2. **Overview of the SOORENA two-stage autoregulatory mechanism detection**

architecture.

2.5 Training Procedure

Both stages were fine-tuned using PyTorch 2.0 and the Hugging Face Transformers

library (v4.30). Inputs were tokenized to a maximum length of 512 tokens and processed in

mini-batches of 16 samples. The AdamW optimizer (learning rate of 2×10^{-5}) was used

with a linear warmup schedule applied to the first 10% of training steps. All data splits and

model initialization used a fixed random seed (42) for reproducibility. All experiments

were conducted on an Apple M1 Max (32 GB unified memory) without GPU acceleration.

Because training was performed on CPU, results are fully deterministic and do not depend

on non-deterministic CUDA operations. AdamW was chosen for its improved stability and

regularization when fine-tuning transformers compared to standard Adam [22].

Stage 1 training employed binary cross-entropy loss and ran for three epochs (525

update steps). Model selection was based on the validation F1 score, which balances

precision and recall to minimize false positives entering Stage 2. Stage 2 training used

weighted cross-entropy loss to handle class imbalance across mechanism types and ran for

four epochs (236 update steps). The class weights, inversely proportional to class

frequency, are shown in **Fig. 3C**. The final Stage 2 model checkpoint was chosen based on

the highest validation macro-F1 score, ensuring balanced performance across both

common and rare mechanisms.

2.6 Evaluation

2.6.1 Performance Metrics

We assessed model performance using multiple complementary metrics: Accuracy,

Precision, Recall, F1 Score, Macro-F1, and Weighted-F1. For Stage 2, macro-F1 was

prioritized as the primary metric because it prevents strong performance on common

classes (autophosphorylation) from masking poor performance on rare ones (autolysis,

autoinducer). This is critical in biomedical classification, where underrepresented

mechanisms may be scientifically important despite low frequency.

2.6.2 Error and Confidence Analysis

Confusion matrices were generated to inspect class-specific error patterns.

Prediction confidence was used to identify uncertain classifications, especially in Stage 1,

where the negative class contains label noise.

2.7 Computational Resources

All training and inference were performed on an Apple M1 Max (32 GB unified

memory) without dedicated GPU acceleration, demonstrating that the pipeline is accessible

on consumer hardware. Training time was approximately 33 minutes per epoch for Stage 1

and 12 minutes per epoch for Stage 2.

2.8 Ontology Development

To enable consistent terminology across heterogeneous data sources and support

biologically interpretable outputs, we developed a curated ontology for the seven

autoregulatory mechanism classes used by SOORENA. The ontology organizes mechanisms

into a two-branch hierarchy rooted at "Autoregulatory Mechanisms" : (i) enzymatic self-

modification, encompassing post-translational mechanisms (autophosphorylation,

autoubiquitination, autocatalytic activity, autolysis), and (ii) gene expression regulation,

encompassing transcriptional and signaling feedback (autoregulation of gene expression,

autoinhibition, autoinducer production).

Each mechanism entry includes a formal definition, controlled synonyms and

antonyms, related terms, and a set of core ontology relations following OWL-inspired

conventions: is-a (class membership), part-of (biological process membership), regulates

(functional effect), has-input and has-output (molecular participants), and occurs-in

(biological context).

Each mechanism was additionally assigned a polarity indicator based on its

functional direction: positive (+) for self-amplifying mechanisms (autophosphorylation,

autocatalytic activity, autoinducer production), negative (–) for self-limiting mechanisms

(autoinhibition, autoubiquitination, autolysis), and context-dependent (±) for

autoregulation of gene expression, which can act as either a positive or negative feedback

depending on the specific regulatory interaction.

The ontology also serves as a cross-database harmonization layer, mapping source-

specific terminology from integrated databases to SOORENA's canonical terms (for

example, SIGNOR's "self-phosphorylation" maps to autophosphorylation, and "self-

cleavage" maps to autolysis). In the web application, each predicted record is linked to its

ontology entry, providing users with standardized definitions and mechanism context

alongside model predictions.

3. Results

<u>3.1 Stage 1: Binary Classification Performance</u>

Stage 1 classified publications as either containing or not containing evidence of an

autoregulatory mechanism. On the held-out test set (n = 600), the model achieved strong

performance, accurately identifying publications that should progress to mechanistic

classification. Overall accuracy was 96.0%, with a precision of 97.8% and a recall of 90.0%

for the positive class, yielding an F1 score of 93.8% (**Fig. 3**). The model's high precision

ensured that very few false positives were propagated into Stage 2.

Errors were dominated by false negatives, with 20 mechanism-containing

publications missed and 4 publications incorrectly flagged as positive. This conservative

behavior aligns with the design objective of minimizing uncertain cases passed to Stage 2.

The confusion matrix (**Fig. 3**) illustrates that misclassifications did not arise from

systematic bias toward specific negative subsets but rather from ambiguous descriptions in

the original text.

Validation F1 improved from 90.2% at epoch-1 to a peak of 91.8% at epoch-2,

followed by a slight decrease at epoch-3, indicating minor overfitting. The best epoch-2

checkpoint was therefore selected for final evaluation. Collectively, these results

demonstrate that Stage 1 acts effectively as a high-precision filtering stage for biomedical

corpora for fine-grained mechanistic classification.

3.2 Stage 2: Multi-Class Mechanism Classification

Stage 2 assigned each Stage 1-positive publication to one of seven autoregulatory

mechanism categories. On the held-out test set (n = 200), the model achieved 95.5%

accuracy, 96.2% macro-F1, and 95.5% weighted-F1 (**Fig. 3**). These results demonstrate

robust generalization despite substantial class imbalance in the training data.

Performance across individual mechanism types was similarly strong (**Fig. 4**).

Autophosphorylation, the most common mechanism, achieved 99.0% precision and 92.5%

recall (F1 = 95.6%), indicating effective representation learning even when class

prevalence might bias toward overprediction. Mechanisms with intermediate

representation, including autoregulation, autocatalytic activity, autoinhibition, and

autoubiquitination, achieved F1 scores above 91%.

Strikingly, the rarest mechanisms, autolysis and autoinducer production (n = 6

each), were classified perfectly (100% precision, recall, and F1). However, the small

support for these classes means that a single misclassification would reduce F1 to

approximately 67%. These results should therefore be interpreted with caution until

validated on larger held-out samples. Nevertheless, the perfect classification of these rare

classes highlights the effectiveness of weighted loss in preserving minority-class

performance and preventing collapse toward majority categories. Together, these findings

show that Stage 2 reliably captures mechanistic diversity across the full spectrum of

autoregulatory behaviors.

Figure 3. Stage 1 and Stage 2 model evaluation. (A) Stage 1 binary classifier test-set

422 performance (n = 600), showing accuracy, precision, recall, and F1 score. (B)

423 Confusion matrix for Stage 1 predictions on the test set. (C) Inverse-frequency class

424 weights assigned to each autoregulatory mechanism type for Stage 2 training; the

Figure 4. Per-class classification performance of the Stage 2 mechanism classifier on the test set. Each panel shows Precision, Recall, and F1 score for one autoregulatory mechanism class; support (n) indicates the number of test-set instances per class. The x-

axis is held constant across all panels to allow direct comparison. Scores are derived from

the held-out test set (n = 200 instances total).

3.3 Error & Uncertainty Analysis

Across the Stage 2 test set, the model misclassified 9 of 200 publications (4.5% error

rate). Most errors occurred between mechanistically related categories, particularly

autophosphorylation and autocatalytic activity, which share overlapping biochemical

terminology describing self-activation mediated by the enzyme. Importantly, no

misclassifications occurred between mechanistically distant categories (e.g., autolysis vs.

autoinducer production), indicating that the model captures biologically meaningful

distinctions rather than relying on superficial keyword patterns (**Fig. 5**).

Prediction confidence scores, representing the model's estimated probability for

each predicted class, provided additional insight into model reliability. Correctly classified

Stage 2 examples had a mean confidence of 92.7%, whereas misclassified examples showed

substantially lower confidence (mean: 67.3%). This separation suggests that confidence

estimates can function as a practical uncertainty measure for downstream expert review.

Similar trends were observed in Stage 1. False negatives were more frequent than

false positives, reflecting the model's intentional bias toward high precision. Negative

predictions also exhibited a higher mean confidence (93.3%) than positive predictions

(89.2%). Together, these findings indicate that SOORENA not only achieves strong

classification accuracy but also provides interpretable confidence signals that support high-

confidence curation while safely flagging ambiguous literature for manual evaluation.

To assess potential cross-regulation false positives in deployed predictions, we

applied pattern matching to identify cases where the abstract text explicitly describes

heteroregulation (e.g., "Protein A regulates Protein B"). Of the 97,657 predicted

autoregulatory publications, 3,034 (3.1%) contained explicit cross-regulation patterns.

Manual inspection confirmed that these represent a source of false positives arising from a

known system limitation: the model predicts whether an abstract describes autoregulation

but cannot identify which protein is autoregulatory. Gene annotations are extracted

separately via PubTator3 from full-text articles, and the system pairs predictions with all

extracted gene mentions. Consequently, when an abstract describes heteroregulation

(Protein A ⯈ Protein B), the prediction may be incorrectly associated with the target

protein (B) rather than the actor (A). This pairing error accounts for an estimated 3% of

deployed predictions and highlights the need for subject-protein identification in future

model iterations.

467

Figure 5. **Confusion matrix for Stage 2 multi-class classification showing true versus**

469 **predicted mechanism labels for 200 test abstracts.**

470 3.4 Interactive Database: SOORENA Web Application

471 We developed SOORENA, an R Shiny application that integrates model predictions

472 with experimentally validated records from multiple curated databases (**Fig. 6**). The

473 database contains 100,065 autoregulatory interaction records: 97,657 predicted from

474 3,340,955 PubMed abstracts, 1,332 UniProt annotations, 995 SIGNOR interactions, 61

475 TRRUST interactions, and 20 OmniPath interactions. Gene annotations for predicted

records were extracted using PubTator3 [38] from full-text articles. Each record is assigned

a unique identifier (SOORENA-{SourceCode}-{PMID}-{Counter}), where SourceCode

indicates the data source (P = Predicted, U = UniProt, S = SIGNOR, T = TRRUST, O =

OmniPath), PMID is the PubMed identifier of the source publication, and Counter is a

sequential integer that disambiguates multiple records sharing the same PMID and source

(arising when a single publication describes more than one autoregulatory protein),

enabling traceability to original publications and source databases. The application

supports search, filtering, inspection, and export, and includes an embedded ontology to

standardize terminology and aid interpretation.

Figure 6. SOORENA web interface showing the Search tab, which supports field-specific

filtering (e.g., Protein ID, PMID, organism, and data source), and displays interactive,

sortable table columns, and CSV export functionality.

The model processed 3,340,955 PubMed abstracts and identified 85,145

publications (2.5%) as containing autoregulatory mechanisms. After PubTator3-based gene

extraction, these predictions yielded 97,657 protein-specific autoregulatory records,

reflecting that multiple genes may be extracted from a single publication. Integration with

external databases (1,332 UniProt annotations + 1,076 interactions from

SIGNOR/TRRUST/OmniPath) brought the total database to 100,065 records. The

distribution of predicted mechanism types is summarized in **Fig. 7**. The table shows a

dominance of autophosphorylation followed by autoubiquitination and autocatalytic

activity.

Figure 7. Distribution of predicted autoregulatory mechanism types compared to the

curated dataset. Left panel: percentage breakdown of 97,657 mechanism predictions

across 3,340,955 unseen PubMed abstracts. Right panel: percentage breakdown of

the 1,332 manually curated instances used for model training. Both panels share the

same x-axis scale to facilitate direct comparison.

On the Search tab, users can filter by protein identifiers (Protein ID, UniProt AC),

organism (OS), PMID, author, journal, data source (Predicted, UniProt, SIGNOR, TRRUST,

OmniPath), autoregulatory mechanism, polarity (+/−/±), and publication year range -

details for polarity are explained shortly. A free-text box enables case-insensitive keyword

search across titles and abstracts. Results are rendered as an interactive table (DT) with

sortable columns: AC, UniProt AC, Protein ID, Protein Name, Gene Name, OS, PMID, Title,

Abstract, Journal, Authors, Year, Month, Source, Autoregulatory Type, Polarity, Mechanism

Probability, and Type Confidence. Probabilities are shown as percentages, and long fields

are truncated with a magnifier button for full inspection in a modal. Users can apply

confidence cut-offs via the Has Mechanism and Autoregulatory Type controls, then export

the filtered results as CSV for downstream review. Each record includes a Polarity indicator

derived deterministically from mechanism type: positive (+) for self-amplifying

mechanisms (autophosphorylation, autocatalytic, autoinducer), negative (–) for self-

limiting mechanisms (autoinhibition, autoubiquitination, autolysis), and context-

dependent (±) for autoregulation.

The Statistics tab includes interactive visualizations that display the distribution of

autoregulatory types, publication timeline (bubble chart by year), top contributing

journals, and data source composition. Histograms of Mechanism Probability and Type

Confidence distributions help users select filtering thresholds. Model training performance

metrics are also displayed.

The Ontology tab provides the curated vocabulary used by SOORENA. A hierarchical

tree presents high-level groupings followed by mechanism pages for the seven classes, each

with a prose definition, core relations (is-a, part-of, regulates, has-input, has-output,

occurs-in), and key references. From the Search table, each classified record includes a pop-

up that shows the ontology path and the same definition block, keeping model outputs tied

to consistent semantics.

The app is versioned through a Patch Notes tab that lists dated changes to data

columns, evaluation summaries, UI components, ontology content, and About tab credits

contributors and partners. Together, these elements make the system auditable and

reproducible: users can trace any row back to its PMID, see the model's probability for

mechanism presence and type, consult standardized definitions, and export subsets for

manual validation.

538
539

3.5 Comparing Source of Autoregulation Data

The SOORENA database integrates autoregulatory data from two complementary

sources: literature-derived predictions generated by the two-stage NLP pipeline and

entries drawn from four manually curated external databases (UniProt, SIGNOR, TRRUST,

and OmniPath). Of the 100,065 total autoregulatory entries, 97,657 (97.6%) originate from

SOORENA predictions spanning 3,340,955 PubMed abstracts, while the remaining 2,408

entries (2.4%) are sourced from curated databases (UniProt, n = 1,332; SIGNOR, n = 995;

TRRUST, n = 61; OmniPath, n = 20) (**Fig. 8A**). This disparity reflects both the breadth of the

literature search and the inherently limited coverage of manually curated resources.

Analysis of the publication years associated with predicted entries reveals a

sustained growth in autoregulation-related literature from the 1970s onward, peaking in

the mid-2000s and plateauing thereafter, with an apparent decline in recent years

attributable to publication indexing lag rather than a true reduction in research output

(**Fig. 8B**). The Journal of Biological Chemistry contributed the largest number of entries

(13,091), followed by PNAS (5,116) and the Journal of Bacteriology (3,443), reflecting the

predominantly biochemical and microbiological character of the autoregulation literature

(**Fig. 8C**).

Prediction confidence scores for both pipeline stages exhibit right-skewed

distributions, indicating that the majority of predictions are made with high certainty (**Fig.**

8D). Stage 1 (mechanism detection) scores are bounded at 0.5 by the binary classification

threshold, with a pronounced accumulation of entries above 0.9 and a sharp peak at 0.98.

Stage 2 (mechanism classification) scores span a wider range (0.18–0.95), reflecting the

greater difficulty of the seven-class task, yet similarly concentrate above 0.8, with a peak at

0.93. Together, these distributions demonstrate that low-confidence predictions represent

a minority of the dataset and that the pipeline assigns decisive probabilities across the

majority of entries.

570
Figure 8. Overview of the SOORENA autoregulation dataset. (A) Number of entries
contributed by each data source on a log scale. SOORENA predictions (orange; n = 97,657)
account for 97.6% of all entries; curated database contributions (blue) range from 20
(OmniPath) to 1,332 (UniProt). (B) Annual distribution of publications associated with
predicted entries (1970–2024), illustrating the growth of autoregulation research over five
decades. (C) Top 10 journals by number of associated entries; the Journal of Biological
Chemistry (n = 13,091) is the dominant source. (D) Prediction confidence score
distributions for Stage 1 (mechanism detection; range 0.50–0.99) and Stage 2 (mechanism

classification; range 0.18–0.95). Both distributions are right-skewed, with the majority of
entries assigned high-confidence predictions.

4. Discussion

This study presents SOORENA, a transformer-based system for automated discovery
and mechanistic classification of protein autoregulatory mechanisms in biomedical
literature. The two-stage architecture achieved strong performance across all seven
mechanism classes, including rare ones, and enabled large-scale deployment across
millions of PubMed abstracts. Integrated with experimentally validated annotations from
UniProt, SIGNOR, TRRUST, and OmniPath, SOORENA provides the first comprehensive,
searchable database of protein self-regulatory mechanisms.

Manual curation remains the gold standard for accuracy but scales poorly and
cannot keep pace with the rapid growth of publications [29]. Rule-based text mining can
identify explicit mechanistic terms but often fails when descriptions are implicit or context-
dependent, which is common for post-translational and feedback processes. SOORENA
bridges this gap by combining transformer-based language understanding with domain-
specific fine-tuning, achieving expert-comparable interpretation while enabling
continuous, automated updates to regulatory knowledge bases.

Transformer models pretrained on biomedical corpora, particularly PubMedBERT,
show major advantages in biomedical reasoning over general-domain models such as
BERT-base [19,20,30,31]. In preliminary experiments on an earlier formulation of this task,
vanilla BERT achieved only 42.6% F1 compared to 94.7% for BioBERT and 98.2% for
PubMedBERT, confirming that domain-specific pretraining is essential for biomedical

mechanism detection. Our findings reinforce the importance of domain alignment during

pretraining, especially when training labeled datasets are small, which is a frequent

bottleneck in biomedical NLP.

The staged architecture reflects the structure of the biological question and

improves reliability. Stage 1 prioritizes high precision to prevent irrelevant publications

from propagating errors downstream, a well-established requirement in hierarchical

classification pipelines [23]. Stage 2 uses weighted loss to counter class imbalance, a well-

established requirement for biomedical ML tasks where minority classes are often

scientifically most important [24]. This formulation addresses the limitations of single-

stage classification, where class imbalance and task heterogeneity commonly degrade

performance. Additionally, routing only ~2.5% of publications into Stage 2 reduces

computational cost by approximately 94%, enabling scalable whole-corpus inference on

standard hardware.

Misclassifications were concentrated among mechanistically adjacent categories.

For example, autophosphorylation was occasionally misclassified as autocatalytic activity.

Biochemically, these mechanisms are closely related: autophosphorylating kinases are

executing a specific form of enzymatic autocatalysis [25,26]. Likewise, confusion among

ubiquitin-dependent processes suggests contextual ambiguity in abstracts, where

enzymatic roles (E2 vs. E3 ligases) are often unstated or implicitly described.

Crucially, no misclassifications occurred between mechanistically distant biological

categories (e.g., autolysis vs. autoinduction), indicating that the model's representations

capture mechanistic semantics rather than relying on lexical co-occurrence patterns.

Probability calibration analysis further supports its practical usability: correctly classified

predictions displayed higher confidence scores than misclassified ones, allowing

confidence-threshold filtering to assist expert curation and quality control review [27].

Reliance on UniProt introduces several known curation biases. Positive examples

are skewed toward well-studied proteins and pathways, particularly kinase signaling,

thereby inflating the autophosphorylation frequency relative to biological reality. A second

key limitation is the use of abstracts rather than full-text articles. Mechanistic assertions

often appear in results sections, figures, or supplemental materials [28], meaning that both

training labels and predictions are constrained by incomplete contextual information. This

likely underestimates true model capability. Handling of multi-mechanism publications

remains simplified. Although biologically meaningful co-regulation exists (e.g.,

autophosphorylation-dependent autoinhibition), only 18 such cases were identified,

insufficient for a reliable multi-label model. The model's reliance on transformer-based

semantics inference introduces a potential for latent confounders. For instance, detecting

phosphorylation-related language does not guarantee that the event is auto-directed;

distinguishing cis- from trans-regulatory contexts remains challenging at the abstract level.

A critical limitation affecting deployed predictions is the system's inability to

identify which specific protein exhibits autoregulatory behavior when multiple proteins

are mentioned. The two-stage model predicts whether an abstract describes autoregulation

but does not perform subject identification. Gene annotations are extracted post-hoc using

PubTator3 from full-text articles, and predictions are paired with all extracted gene

mentions. This architecture introduces systematic false positives when abstracts describe

heteroregulation (Protein A regulates Protein B): the target protein (B) may be incorrectly

flagged as autoregulatory. Pattern-matching analysis identified 3,034 such cases (3.1% of

deployed predictions), representing a known error class that requires subject-protein

identification in future iterations.

Beyond these limitations, SOORENA provides a scalable framework for expanding

biochemical knowledge by identifying regulatory findings that remain uncurated. The

integration of 1,076 interactions from pathway databases (SIGNOR, TRRUST, OmniPath)

alongside 97,657 literature-derived predictions creates an extensive resource that

complements manual curation efforts. High-confidence predictions indicate literature that

may contain overlooked experimental evidence, and this helps accelerate the update cycle

for resources such as UniProt. The comprehensive mapping of mechanism types across

thousands of proteins also enables comparative biological analysis, offering potential

insights into how self-regulatory processes have diversified evolutionarily across kinases,

proteases, and quorum-sensing systems. Moreover, linking predicted mechanisms with

protein domains, structural motifs, and interaction partners may support new hypotheses

regarding the molecular features that predispose certain proteins to self-regulate,

consistent with prior studies suggesting structural correlates of autoregulation [32,33].

Temporal patterns in autoregulatory discoveries may further reveal research trends

and highlight neglected regulatory processes that warrant renewed experimental focus.

Finally, integrating SOORENA predictions with structural and functional annotation

pipelines could directly support targeted experimental design by identifying proteins most

likely to exhibit self-regulatory control and thus prioritizing them for validation.

Future extensions of this work will focus on increasing the granularity,

completeness, and biological context of autoregulatory mechanism detection.

Incorporating full-text articles instead of abstracts would substantially improve

mechanistic recall, as essential experimental details often appear in figure legends,

methods, and supplementary materials. Addressing this challenge will likely require long-

sequence or hierarchical transformers capable of processing multi-kilobyte documents

efficiently [34]. Addressing the subject-protein identification limitation is a priority. Future

versions should incorporate entity-aware architectures or sequence tagging approaches to

identify which protein in a multi-protein abstract exhibits the autoregulatory behavior,

eliminating the current 3.1% cross-regulation error rate introduced by post-hoc gene

pairing. Expanding beyond the current single-label formulation to support multi-

mechanism prediction is also important since many proteins employ layered regulatory

strategies such as autophosphorylation-dependent autoinhibition. This will likely require

modified classification architectures and additional annotated examples of co-occurring

mechanisms. In parallel, advancing toward knowledge-augmented inference by leveraging

protein interaction networks, domain annotations, and curated mechanistic pathways

could provide a biologically grounded framework for disambiguating closely related

mechanisms. Finally, integrating active learning driven by the model's well-calibrated

uncertainty estimates could make expert validation more efficient, allowing iterative

refinement of both the system and the underlying curated knowledge.

Acknowledgements

We gratefully acknowledge the contributions of Zheng He, Yining Zhou, and Mingyang Zhang in the early prototyping and application development phases of this work. This study was financially supported by the Tampere Institute for Advanced Study and the Jane and Aatos Erkko Foundation [Grant 220031 to M.J.].

Data and code availability

The script and data are publicly available at (https://github.com/jafarilab/SOORENA).

Author Contributions

M.J. conceived the research project, and M.J. and P.N. jointly supervised and coordinated its execution. H.A. contributed to the modeling and prepared the initial draft of the manuscript. J.A. contributed to data collection for the training and test sets. All authors participated in writing, editing, and revising the manuscript.

Conflict of interest

The authors declare no conflicts of interest.

References

1. Alon U. Network motifs: theory and experimental approaches. Nat Rev Genet. 2007;8:
450–461.

2. Tyson JJ, Novák B. Functional motifs in biochemical reaction networks. Annu Rev Phys
Chem. 2010;61: 219–240.

3. Veliz-Cuba A, Stigler B. Boolean models can explain bistability in the lac operon. J
Comput Biol. 2011;18: 783–794.

4. Ma'ayan A, Jenkins SL, Neves S, Hasseldine A, Grace E, Dubin-Thaler B, et al. Formation
of regulatory patterns during signal propagation in a Mammalian cellular network.
Science. 2005;309: 1078–1083.

5. Jafari M, Sadeghi M, Mirzaie M, Marashi S-A, Rezaei-Tavirani M. Evolutionarily
conserved motifs and modules in mitochondrial protein-protein interaction networks.
Mitochondrion. 2013;13: 668–675.

6. Saadatpour A, Albert R, Reluga TC. A REDUCTION METHOD FOR BOOLEAN NETWORK
MODELS PROVEN TO CONSERVE ATTRACTORS. SIAM J Appl Dyn Syst. 2013;12: 1997–
2011.

7. Veliz-Cuba A. Reduction of Boolean network models. J Theor Biol. 2011;289: 167–172.

8. Hubbard SR, Till JH. Protein tyrosine kinase structure and function. Annu Rev
Biochem. 2000;69: 373–398.

9. Komander D, Rape M. The ubiquitin code. Annu Rev Biochem. 2012;81: 203–229.

10. Kapust RB, Waugh DS. Controlled intracellular processing of fusion proteins by TEV
protease. Protein Expr Purif. 2000;19: 312–318.

11. Blackmond DG. "If pigs could fly" chemistry: a tutorial on the principle of microscopic
reversibility. Angew Chem Int Ed Engl. 2009;48: 2648–2654.

12. Becskei A, Serrano L. Engineering stability in gene networks by autoregulation. Nature.
2000;405: 590–593.

13. Rosenfeld N, Elowitz MB, Alon U. Negative autoregulation speeds the response times of
transcription networks. J Mol Biol. 2002;323: 785–793.

14. Nevozhay D, Adams RM, Murphy KF, Josic K, Balázsi G. Negative autoregulation
linearizes the dose-response and suppresses the heterogeneity of gene expression.
Proc Natl Acad Sci U S A. 2009;106: 5123–5128.

15. Soto C. Transmissible proteins: expanding the prion heresy. Cell. 2012;149: 968–977.

16. Papenfort K, Bassler BL. Quorum sensing signal–response systems in Gram-negative
bacteria. Nature Reviews Microbiology. 2016;14: 576–588.

17. UniProt Consortium. UniProt: the universal protein knowledgebase in 2021. Nucleic
Acids Res. 2021;49: D480–D489.

18. González-Márquez R, Schmidt L, Schmidt BM, Berens P, Kobak D. The landscape of
biomedical research. Patterns. 2024;5(6):100968. doi:10.1016/j.patter.2024.100968

19. Lee J, Yoon W, Kim S, Kim D, Kim S, So CH, et al. BioBERT: a pre-trained biomedical
language representation model for biomedical text mining. Bioinformatics. 2020;36:
1234–1240.

20. Gu Y, Tinn R, Cheng H, Lucas M, Usuyama N, Liu X, et al. Domain-specific language
model pretraining for biomedical natural language processing. ACM Trans Comput
Healthc. 2022;3: 1–23.

21. Devlin J, Chang M-W, Lee K, Toutanova K. BERT: Pre-training of deep bidirectional
transformers for language understanding. Proceedings of NAACL-HLT 2019.
doi:10.18653/v1/n19-1423

22. Loshchilov I, Hutter F. Decoupled weight decay regularization. arXiv [cs.LG]. 2017.
doi:10.48550/ARXIV.1711.05101

23. Silla CN Jr, Freitas AA. A survey of hierarchical classification across different
application domains. Data Min Knowl Discov. 2011;22: 31–72.

24. Johnson JM, Khoshgoftaar TM. Survey on deep learning with class imbalance. J Big
Data. 2019;6. doi:10.1186/s40537-019-0192-5

25. Reinhardt R, Leonard TA. A critical evaluation of protein kinase regulation by
activation loop autophosphorylation. Elife. 2023;12. doi:10.7554/eLife.88210

26. Endicott JA, Noble MEM, Johnson LN. The structural basis for control of eukaryotic
protein kinases. Annu Rev Biochem. 2012;81: 587–613.

27. Desai S, Durrett G. Calibration of pre-trained transformers. Proceedings of the 2020
Conference on Empirical Methods in Natural Language Processing (EMNLP).
Stroudsburg, PA, USA: Association for Computational Linguistics; 2020.
doi:10.18653/v1/2020.emnlp-main.21

28. Fang L, Chen Q, Wei C-H, Lu Z, Wang K. Bioformer: an efficient transformer language
model for biomedical text mining. ArXiv. 2023. Available:
https://www.ncbi.nlm.nih.gov/pubmed/36945685

29. Amberger JS, Bocchini CA, Scott AF, Hamosh A. OMIM.org: leveraging knowledge
across phenotype-gene relationships. Nucleic Acids Res. 2019;47: D1038–D1043.

30. Aldahdooh J, Tanoli Z, Tang J. Mining drug-target interactions from biomedical
literature using chemical and gene descriptions-based ensemble transformer model.
Bioinform Adv. 2024;4: vbae106.

31. Aldahdooh J, Vähä-Koskela M, Tang J, Tanoli Z. Using BERT to identify drug-target
interactions from whole PubMed. BMC Bioinformatics. 2022;23: 245.

32. Kobe B, Heierhorst J, Feil SC, Parker MW, Benian GM, Weiss KR, et al. Giant protein
kinases: domain interactions and structural basis of autoregulation. EMBO J. 1996;15:
6810–6821.

33. Jafari M, Ansari-Pour N, Azimzadeh S, Mirzaie M. A logic-based dynamic modeling
approach to explicate the evolution of the central dogma of molecular biology. PLoS
One. 2017;12: e0189922.

34. Zaheer M, Guruganesh G, Dubey A, Ainslie J, Alberti C, Ontanon S, et al. Big bird:
Transformers for longer sequences. arXiv [cs.LG]. 2020.
doi:10.48550/ARXIV.2007.14062

35. Türei D, Korcsmáros T, Saez-Rodriguez J. OmniPath: guidelines and gateway for
literature-curated signaling pathway resources. Nat Methods. 2016;13(12):966-967.
doi:10.1038/nmeth.4077

36. Perfetto L, Briganti L, Calderone A, Cerquone Perpetuini A, Iannuccelli M, Langone F, et
al. SIGNOR: a database of causal relationships between biological entities. Nucleic
Acids Res. 2016;44(D1):D548-D554. doi:10.1093/nar/gkv1048

37. Han H, Shim H, Shin D, Shim JE, Ko Y, Shin J, et al. TRRUST: a reference database of
human transcriptional regulatory interactions. Sci Rep. 2015;5:11432.
doi:10.1038/srep11432

38. Wei C-H, Allot A, Lai P-T, Leaman R, Tian S, Luo L, Jin Q, Wang Z, Chen Q, Lu Z. PubTator
3.0: an AI-powered literature resource for unlocking biomedical knowledge. Nucleic
Acids Res. 2024;52(W1):W540-W546. doi:10.1093/nar/gkae235

39. Sayers EW, Bolton EE, Brister JR, et al. Database resources of the National Center for
Biotechnology Information in 2025. Nucleic Acids Res. 2025;53(D1):D26-D38.
doi:10.1093/nar/gkae1206

40. Sokolova M, Lapalme G. A systematic analysis of performance measures for
classification tasks. Inf Process Manag. 2009;45(4):427–437

41. Zhu D, Hedderich MA, Zhai F, Adelani DI, Klakow D. Is BERT robust to label noise? A
study on learning with noisy labels in text classification. Proceedings of the Third
Workshop on Insights from Negative Results in NLP. 2022.
doi:10.18653/v1/2022.insights-1.8