SpecLig: Energy-Guided Hierarchical Model for Target-Specific 3D Ligand Design

Peidong Zhang[1,2]**, Rong Han**[1,2]**, Xiangzhe Kong**[1, 4]**, Ting Chen**[1,2,*]**, and Jianzhu Ma**[3,4,*]

[1]Department of Computer Science and Technology, Tsinghua University, Beijing, China
[2]Institute of Artificial Intelligence, Tsinghua University, Beijing, China
[3]Department of Electronic Engineering, Tsinghua University, Beijing, China
[4]Institute for AI Industry Research, Tsinghua University, Beijing, China
[*]Correspondence should be addressed to tingchen@mail.tsinghua.edu.cn and majianzhu@tsinghua.edu.cn

ABSTRACT

Structure-based generative models often optimize single target affinity while ignoring specificity, producing candidates prone to off-target binding. We introduce SpecLig, a unified, structure-based framework that jointly generates small molecules and peptides with improved target affinity and specificity. SpecLig represents a complex as a block-based graph, combining a hierarchical SE(3)-equivariant variational autoencoder with an energy-guided geometric latent diffusion model. Chemical priors derived from block–block contact statistics are explicitly incorporated, biasing generation toward pocket-complementary fragment combinations. We benchmark SpecLig on peptide and small-molecule tasks using standard public datasets and propose precision/breadth testing paradigms to quantify specificity. Across multiple evaluations, ligand candidates generated by SpecLig usually bind the target pocket with high specificity and affinity while maintaining competitive advantages in other attributes. Ablations indicate that both hierarchical representation and energy guidance contribute to the success. Finally, we provide multiple real applications to demonstrate how SpecLig improves ligands in natural complexes to avoid potential off-target risks. SpecLig therefore provides a practical route to prioritize higher-specificity designs for downstream experimental validation. The codes are available at: https://github.com/CQ-zhang-2016/SpecLig.

1 Introduction

Designing ligands with target specificity advances both mechanistic biology and drug discovery[1,2]. Recent deep-learning generative models[3–8] have shifted ligand discovery from large-scale screening[9–12] toward rational, structure-guided design. Structure-based drug design (SBDD) is central to this trend because it leverages receptor's three-dimensional (3D) geometry to constrain generation in chemically and spatially relevant regions of ligand space[13–15].

Ligands have diverse chemical modalities, including small molecules, peptides, and antibodies. Each class has distinct pharmacokinetic and functional profiles (e.g., oral bioavailability for small molecules[16]; recognition motifs for peptides[17]). Despite differences in scale and physicochemical properties, ligand–receptor binding follows the same physicochemical rules, such as bond types, bond angles and lengths, and steric clashes[18,19]. Common generative paradigms such as autoregressive models[20–22], diffusion-based methods[23–26], flow-matching[27–29], retrieval-augmented generation[30,31], energy optimization[32–35], iterative refinement[36–39], and voxel-based models[40,41] have been successfully applied across these ligand classes. Recent works[42–46] have considered unified generative frameworks that accommodate representational differences among ligand types.

Most SBDD models learn ligand distributions conditioned on a single target structure and therefore emphasize recurring motifs from training data. While such motifs can increase predicted affinity, their systematic reuse can reduce target specificity. For examples (Figure 1a and b), voxbind and PepGLAD produced candidates with higher predicted affinity than native ligands for receptors (UniProt IDs: P14779 and P33247) but also showed enhanced binding to unrelated proteins. This decoupling of affinity and specificity indicates a systematic bias toward generating promiscuous binders, which increases off-target risk and constrains translational potential[47–49]. In the interaction analyzes shown in Figure 1a and 1b, some fragments in the designed ligands contributed little to binding with the intended target yet dominated interactions with off-targets. We further analyzed several advanced SBDD models and categorized their outputs by specificity. As shown in Figure 1c, small molecules with low specificity tend to contain a markedly higher fraction ($\approx$5–10%) of polar groups, which promote promiscuous binding across multiple targets. Figure 1d shows that highly specific peptides typically contain a higher fraction ($\approx$3–10%) of helical structure, whereas non-helical flexible segments increase exposure risk. Experimental details are provided in Chapter 3 of the Supplementary Information. These pervasive generative biases in deep-learning models highlight the need to explicitly consider specificity in ligand design.

Standard SBDD benchmarks focus on single-target docking scores, measuring spatial and electrostatic complementarity[50,51]. Generative models can produce candidates with high docking scores through excessive modifications, masking potential promiscuity. Prior attempts[52], which quantify specificity in small molecular design by comparing against a random non-target, are limited by randomness and provide little actionable guidance. To address this, we design a suite of specificity metrics that quantify binding preference across multi-target contexts and is applicable to both small-molecule and peptide design. Using these metrics, we find that many model-generated ligands with improved single-target affinity exhibit reduced specificity relative to reference ligands. It is consistent with the empirical difficulty of improving selectivity versus affinity[53].

We think achieving target specificity requires moving beyond single-structure conditioning to incorporate evolutionary binding preferences. We address this by introducing energy-guided diffusion that leverages statistical contact frequencies between molecular fragments derived from native protein-ligand complexes. Unlike conventional energy functions based on physical potentials, our potential terms quantify the empirical preference of specific inter-fragment interactions across diverse targets. Based on this, we propose SpecLig (shown in Figure 1), a unified generative framework that integrates structure-based design with statistical energy guidance to simultaneously design high-specificity small molecules and peptides. SpecLig employs a hierarchical graph neural network (GNN): an atom-level encoder for local chemistry and bond order, and a block-level encoder that represents residues or predefined molecular fragments to capture global topology with reduced cost. Fragments are derived by subgraph partitioning[54] of a molecular library to form a reusable vocabulary. Crucially, chemical priors derived from native complexes are incorporated both as features in training and as additive guidance during latent diffusion sampling. It biases generation toward chemical space that is more likely to enhance specific binding under the given conditions, improving binding affinity while preserving geometric accuracy.

Figure 1. Off-target analyzes and main architecture of SpecLig. We present two representative cases in (a) and (b). Existing SBDD models generate small-molecule and peptide ligands with high predicted affinity for their intended receptors (pink) but also exhibit undesired binding to unrelated proteins (blue). (c) and (d) provide comparative analysis of chemical and structural features distinguishing high- and low-specificity designs. (c) differences in polar-group ratios among small molecules, and (d) differences in helical content among peptides. (e) and (f) show the overview of the proposed SpecLig framework. (e) depicts the construction of the block–block frequency matrix used as a statistical energy prior, and (f) illustrates how this prior guides the latent diffusion–based generation process, with the hierarchical VAE architecture of SpecLig.

We evaluated SpecLig on both peptide and small molecule benchmarks. The results show that our unified framework attains competitive performance on standard benchmarks while consistently producing ligands with higher specificity. Moreover, we demonstrate that SpecLig can simultaneously optimize affinity and specificity for native ligands that exhibit potential off-target risks, illustrating its practical utility for advancing candidate molecules toward safer leads.

2 Methods

SpecLig addresses the critical challenge of binding specificity in structure-based ligand design through statistical energy guidance. SpecLig models protein–ligand complexes as graphs of molecular fragments (blocks) and combines a hierarchical variational autoencoder (VAE[55]) with an E(3)-equivariant latent diffusion model. A hierarchical encoder extracts multi-scale geometric representations, and a decoder with similar architecture reconstructs block types and full-atom 3D coordinates. The core innovation lies in an energy-guided diffusion process that leverages empirical block–block interaction statistics from natural complexes, steering generation toward target-specific binding configurations while maintaining high affinity. Supplementary Chapter 2 discusses related work about SpecLig.

2.1 Notations and overview of SpecLig

We denote a protein–ligand complex as a block-based graph $G = (V, E)$. Each node, $v_i \in V$, is an unordered set of atoms represented as $v_i = \left\{ (\alpha_i, \vec{x}_i) \,\middle|\, \alpha_i \in \mathbb{Z}^{n_i}, \ \vec{x}_i \in \mathbb{R}^{n_i \times 3} \right\}$, consisting of all the element types and 3D coordinates for the n_i atoms in the ith block. Edges E record intra- and inter-block chemical bonds

and spatial adjacency. A block vocabulary S (canonical amino-acid residues and predefined small-molecule fragments) assigns each block a type $s_i \in S$. For controllable generation, we introduce a flag $p_i \in \{0, 1\}$ in per block: $p_i = 1$ restricts sampling in canonical residues, otherwise in the full vocabulary. The pre-computed empirical block–block frequency matrix is denoted as $\mathbf{F} \in \mathbb{R}^{n_S \times n_S}$, where n_s is the length of S.

For conditional design, the pocket and the ligand are represented as G_P and G_L, and the task is to model the conditional generation distribution $p(G_L \mid G_P)$. Assuming that ξ, ϕ, and θ respectively represent the parameter sets of the VAE encoder, decoder, and the latent diffusion model, the generation probability can be written in the marginalized form:

$$p(G_L \mid G_P) = \int p_\theta(Z_L^0 \mid Z_P) \, p_\phi(G_L \mid Z_L^0, Z_P) \, dZ_L^0, \tag{1}$$

$$p_\theta(Z_L^0 \mid Z_P) = \int p(Z_L^T) \prod_{t=T}^{1} p_\theta(Z_L^{T-1} \mid Z_L^T, Z_P) \, dZ_L^{1:T}, \tag{2}$$

In Equations 1 and 2, Z_P denotes the latent representation of the pocket, Z_L^0 denotes the noise-free latent representation of the ligand, and Z_L^T is the terminal latent state approaching the prior (Gaussian noise). Finally, the pocket is defined as blocks whose reference points (C_β or the fragment centroid) lie within 10Å of any native ligand atom, preventing information leakage[21].

2.2 Implementation of hierarchical VAE

We decompose the VAE into hierarchical modules $\mathcal{E}_\xi = \{\mathcal{E}_{\xi,1}, \mathcal{E}_{\xi,2}\}$ and $\mathcal{D}_\phi = \{\mathcal{D}_{\phi,1}, \mathcal{D}_{\phi,2}\}$. All networks are implemented with SE(3)-equivariant transformers[56] to guarantee translation–rotation equivariance.

Atom-scale to block-scale encoding. The atom-scale encoder $E_{\xi,1}$ encodes each atom with its element type, parent block type, canonical-residue flag, and chain id. We augment atom features with a correlated projection learned from the empirical frequency matrix $\mathbf{F}$ after temperature-scaled normalization.

As shown in Figure 1f, information flow is restricted to operate within G_L and G_P separately when constructing the k-nearest neighbors (KNN) graph. Edge features are defined as $\{e_{ab}, \mathbf{d}_{ab}, \boldsymbol{\beta}_{ab}\}$, indicating whether the two atoms belong to the same block, their relative distance, and any candidate chemical-bond types. The block-scale encoder $E_{\xi,2}$ constructs a coarser KNN graph on top of $E_{\xi,1}$'s outputs. The edge features are updated to the relative distances between block centroids. Define $\{\boldsymbol{\mu}_i, \boldsymbol{\sigma}_i, \vec{\boldsymbol{\mu}}_i, \vec{\boldsymbol{\sigma}}_i\}$ as the distributional parameters learned by encoders. After reparameterized sampling[57], we could get the block-level latent representations for G_L and G_P expressed as:

$$Z_P = \mathcal{E}_{\xi,2}(\mathcal{E}_{\xi,1}(G_P)), \quad Z_L^0 = \mathcal{E}_{\xi,2}(\mathcal{E}_{\xi,1}(G_L)), \tag{3}$$

The latent representation of ith block could be defined as $\{(\mathbf{z}_i, \vec{\mathbf{z}}_i) \mid \mathbf{z}_i \in \mathbb{R}^d, \vec{\mathbf{z}}_i \in \mathbb{R}^3\}$, where d is set to 8. Before decoding, gaussian noise is injected to model deviations encountered during latent diffusion process and thus improve robustness.

Block-scale to atom-scale decoding. The hierarchical decoders decode block types and reconstruct atomic coordinates at their respective scales. Information flow is constrained to be unidirectional from G_P to G_L (shown in Figure 1f). The block-scale decoder predicts block type probabilities and coarse block centroid positions. Outputs are normalized with softmax. Querying the block vocabulary S then gets the set of the atom types, intra-block bonds, and the initial atomic positions.

$$h, \vec{r} = \mathcal{D}_{\phi,2}(Z_P, Z_L), \quad s = \text{MLP}_{\text{block}}(h), \tag{4}$$

We then adopt an iterative, flow-matching–like decoding scheme[58]. For each block i and each time step t, we predict two atom-level features h_i^t and v_i^t, which indicate per-atom feature representations and relative coordinate updates, respectively. Initial atom positions $\vec{\mathbf{x}}_i^1$ are sampled randomly around the predicted centroids. Time step t decreases from 1.0 to 0.0 with $\Delta t = 0.1$. The update dynamics follow:

$$h_i^t, \vec{v}_i^t = \mathcal{D}_{\phi,1}\left(\left\{\boldsymbol{\alpha}_i, \boldsymbol{\beta}_i, \vec{\mathbf{x}}_i^t\right\}, h_i\right), \tag{5}$$

$$\vec{\mathbf{x}}_i^{t-\Delta t} = \vec{\mathbf{x}}_i^t + \Delta t \, \vec{v}_i^t, \tag{6}$$

Chemical bond prediction. From the final atomic representations $\{h_i^0, \vec{\mathbf{x}}_i^0\}$ produced by the hierarchical decoder, we predict inter-block bond distributions using a two-stage procedure (shown in Equations 7 and 8). A small MLP-based frontier predictor first selects spatially-proximal (distance < 3.5Å), inter-block atom pairs. Then another MLP-based bond predictor is used.

$$p(a, b) = \delta\left(\text{MLP}_{\text{focal}}\left(h_i^0, h_j^0, d\left(\vec{\mathbf{x}}_i^0, \vec{\mathbf{x}}_j^0\right)\right)\right), \tag{7}$$

$$\boldsymbol{\beta}_{ij,ab} = \sigma\left(\text{MLP}_{\text{bond}}\left(h_{i,a}^0, h_{j,b}^0\right)\right), \tag{8}$$

Where (a, b) are the indices of two different atoms in ith block and jth block, separately. $d(\cdot)$, $\delta(\cdot)$, and $\sigma(\cdot)$ respectively indicate the distance calculation, gated function and softmax activation. In practice, predicted bond assignments are accepted based on confidence ranking and valence compatibility. To refine geometric and chemical accuracy, the entire encoder–decoder pipeline may be iteratively run for multiple design cycles depending on the task.

2.3 Energy-guided geometric diffusion model

We perform conditional diffusion in the latent space and inject a data-driven energy guidance during sampling that explicitly favors fragment pairings empirically associated with cognate binding.

Statistical prior construction. As illustrated in Figure 1e, we precomputed empirical block–block contact priors from from multiple curated sources. (i) Fragment-fragment occurrences from over million small molecules sampled from ZINC15[59] and ChEMBL[60] databases, decomposed by principal-subgraph algorithm[54]. (ii) Residue pairs bound by inter-chain hydrogen bonding from RCSB PDB[61] and PepBDB[62] databases, using trajectory-based hydrogen-bond analysis software. (iii) protein–ligand interaction frequencies from PDBbind[63] and Binding-MOAD[64] analyzed with BINANA. Source-wise frequency matrices are normalized to reduce modal bias and log-transformed to yield continuous statistical potentials. These potentials encode empirical preferences for block–block adjacencies observed in native complexes.

Why it improves specificity. Frequent fragments in training data often reflect general potential rather than pocket specificity. Using $\mathbf{F}$ as a statistical potential reweights sampling toward fragment combinations that historically co-occur in native complexes for pockets similar to the query, thereby reducing the generation of promiscuity-prone motifs.

Standard diffusion process. We adopt a standard diffusion forward–backward scheme. Let the encoder outputs for the pocket and ligand (Z_P and Z_L) be the clean latent variables Z_P^0 and Z_L^0, respectively. Z_L^0 is normalized following empirical practices[65]. We apply a discrete-time Gaussian forward noising process with cosine schedule $\{\beta_t\}_{t=1}^T$, then define $\alpha_t = 1 - \beta_t$ and $\overline{\alpha}_t = \prod_{k=1}^t \alpha_k$. Using the attribute latents z_i^t as an example, the forward Markov chain is given by:

$$q\left(\mathbf{z}_i^t \,\middle|\, \mathbf{z}_i^{t-1}\right) = \mathcal{N}\left(\mathbf{z}_i^t;\, \sqrt{\alpha_t}\,\mathbf{z}_i^{t-1},\, \beta_t\mathbf{I}\right) \tag{9}$$

$$q\left(\mathbf{z}_i^t \,\middle|\, \mathbf{z}_i^0\right) = \mathcal{N}\left(\mathbf{z}_i^t;\, \sqrt{\overline{\alpha}_t}\,\mathbf{z}_i^0,\, (1 - \overline{\alpha}_t)\,\mathbf{I}\right) \tag{10}$$

The reverse denoising is parameterized conditionally as:

$$p_\theta\left(\mathbf{z}_i^{t-1} \,\middle|\, Z_L^t, Z_P^0\right) = \mathcal{N}\left(\mathbf{z}_i^{t-1};\, \mathbf{z}_\theta\left(Z_L^t, Z_P^0, t\right),\, \beta_t\mathbf{I}\right) \tag{11}$$

$$\mathbf{z}_\theta\left(Z_L^t, Z_P^0, t\right) = \frac{1}{\sqrt{\alpha_t}}\left(\mathbf{z}_i^t - \frac{\beta_t}{\sqrt{1 - \overline{\alpha}_t}}\,\boldsymbol{\varepsilon}_\theta\left(Z_L^t, Z_P^0, t\right)[i]\right) \tag{12}$$

Where $\boldsymbol{\varepsilon}_\theta$ also uses the SE(3)-equivariant network. The latent representation of block position $\vec{\mathbf{z}}_i^t$ follows the same forward–backward scheme.

Energy integration into sampling. During sampling, we guide each reverse step with an energy term derived from the block–block bonding prior to favor chemically plausible ligands. Given a denoised estimate $\hat{Z}_L^0$ reconstructed from the current predicted noise, we decode block-type probability vectors $\hat{s}$ with the frozen $\mathcal{D}_{\phi,2}$ following Equation 4. For a block pair (i, j), the pairwise energy term is defined as:

$$E_{ij} = -\log\left(\left(\hat{\mathbf{s}}_i^\top \mathbf{F} \hat{\mathbf{s}}_j\right)^{1/\tau}\right) \cdot \omega_{ij} \tag{13}$$

Where τ is a temperature smoothing factor and ω_{ij} is a distance-dependent decay. For stability, we apply thresholding to the predicted probabilities. The total energy E is normalized based on the ligand's molecular

mass. Crucially, this energy term quantifies how well the current fragment combination matches target-selective binding patterns observed in nature.

We integrate the energy into the reverse dynamics by backpropagating the energy gradient from the block probabilities into the noise space. From the reverse format of Equation 10, we could get the denoised representation $\hat{Z}_L^0$ reconstructed by current predicted noise $\left(\hat{\varepsilon}_{\theta,t}, \hat{\vec{\varepsilon}}_{\theta,t}\right)$. Thus the backpropagation follows:

$$g_\varepsilon = \sum_{i<j} \nabla_{\left(\hat{\varepsilon}_{\theta,t}, \hat{\vec{\varepsilon}}_{\theta,t}\right)} E = \sum_{i<j} \nabla_{\hat{\mathbf{s}}} E \cdot \nabla_{\hat{Z}_L^0} \hat{\mathbf{s}} \cdot \nabla_{\left(\hat{\varepsilon}_{\theta,t}, \hat{\vec{\varepsilon}}_{\theta,t}\right)} \hat{Z}_L^0, \tag{14}$$

Gradient update only the noise-prediction network. Using the attribute latents as an example, we adjust the sampling process by stepping in the negative energy gradient direction:

$$\hat{\varepsilon}_{\theta,t} = \hat{\varepsilon}_{\theta,t} - \omega_t \cdot g_\varepsilon \cdot \min\left(1, \frac{G_{\text{set}}}{\|g_\varepsilon\|_2}\right) \tag{15}$$

To guarantee stability, gradients are clipped by their norm to a preset bound G_{set}, and the guidance weight ω_t decays with time steps. Pseudocodes for the full training and guided sampling algorithms are provided in Chapters 4 and 5 of the Supplementary Information.

2.4 Training procedure and loss design

We design a composite loss to optimize multiple objectives. The hierarchical VAE and the latent diffusion model are trained sequentially following practice. In the hierarchical VAE stage, atom-scale loss terms include: (i) a focal atom-pair classification loss and bond-type cross-entropy for inter-block bond prediction, (ii) a mean-squared error (MSE) loss on the predicted velocity fields produced during iterative decoding, and (iii) a paired-distance loss between atom pairs. The velocity-field supervision is obtained by interpolating between noisy and ground-truth coordinates. The paired-distance loss is applied only for adjacent ($\leq 6\text{Å}$) atoms in native structure and during early decoding steps ($t \leq 0.25$).

At the block scale, we impose Kullback–Leibler (KL) regularization on both attribute latents and coordinate latents, and supervise block-type classification and coarse centroid regression. Lastly, we consider the contrastive loss to align ligand and target pocket, from global perspective. Global descriptors are obtained by averaging per-node features. The triplet-based contrastive loss pulls the ligand descriptors closer to its corresponding pocket and pushes it away from a randomly sampled pocket. The training objective is the weighted sum of the atom-scale, block-scale and global contrastive terms. The training uses teacher forcing: atomic types, intra-block bonds and 50% of inter-block bonds are exposed to the VAE. Additionally, 5% of pocket residues are also masked during training.

For the latent diffusion stage we train with a weighted sum of the denoising MSE loss and a latent perceptual loss (LPL). The LPL term follows the original formulation[66], and the detailed implementation is provided in Supplementary Chapter 6. The overall diffusion-stage loss follows below. Lastly we provide the default hyperparameters in Supplementary Chapter 9:

$$\mathcal{L}_{\text{LDM}} = \mathbb{E}_{t \sim \text{U}(1,\dots,T)} \left[\|\varepsilon - \hat{\varepsilon}_{\theta,t}\|_2^2 + \left\|\vec{\varepsilon} - \hat{\vec{\varepsilon}}_{\theta,t}\right\|_2^2 \right] + \mathcal{L}_{\text{lpl}}\left(\hat{Z}_L^0, Z_L^0\right) \tag{16}$$

3 Experiments

We evaluated SpecLig on peptide (PepBench[42], ProtFrag[42], and LNR[67]) and small-molecule (CrossDocked2020[68]) design benchmarks with standardized protocols, following splitting recommendation by authors. Domain-specific baselines were trained only on their respective domain data, whereas the unified frameworks were trained on the multi-domain training data. To enhance small-molecule chemistry modeling, we augmented training with 100,000 ChEMBL[60] compounds under 20% structural masking. All dataset details are provided in Supplementary Chapter 1.

Evaluation employed commonly used domain metrics grouped by evaluation objective. We report (i) per-category ranking scores and (ii) per-metric ranks, for clarity. Ranking scores were computed as $(N - \bar{r})$, where N is the number of competing models in each category and $\bar{r}$ is the mean rank across the category's individual metrics.

We introduce two paradigms to quantify specificity. The precision paradigm docks designs against the target and one randomly chosen non-target using a high-accuracy engine; the breadth paradigm screens designs against a protein set that includes the target to mimic multi-target pharmacological environments. For peptides we use PyRosetta side-chain docking (multiple precision modes, set size 100); for small molecules we use Uni-Dock[69] (breadth scans, set size 2000) and AutoDock Vina[70] (precision). Finally, comprehensive ablations appear in Supplementary Chapter 10.

3.1 Small molecules

Figure 2. Performance comparison of small-molecule generative models across five categories of metrics: Substructure (a), Geometry (b), Chemistry (c), Specificity (d), and Interaction (e).

Setup. We follow previous benchmark[71] and organize metrics into five metric categories: **Substructure**, **Geometry**, **Chemistry**, **Specificity**, and **Interaction**. **Substructure** measures agreement at atom-type, ring and functional-group levels using the JSD ($\downarrow$) for distributional shift and per-molecule mean absolute error (MAE, $\downarrow$) for frequency deviations. **Geometry** assesses local geometric validity via JSD of bond lengths (JSD_{BL}, $\downarrow$) and bond angles (JSD_{BA}, $\downarrow$), and atom-collision statistics: mean collided-atom fraction ($Ratio_{cca}$, $\downarrow$) and fraction of collided molecules ($Ratio_{cm}$, $\downarrow$). **Chemistry** quantifies drug-likeness (QED, $\uparrow$), normalized synthetic accessibility (SA, $\uparrow$), LogP ($-0.4 \lesssim$ ideal $\lesssim 5.6$), and ratio satisfying Lipinski rules (LPSK, $\uparrow$). **Specificity** is quantified by two complementary docking experiments. ΔE_{pair} ($\downarrow$) and $Ratio_{pair}$ ($\uparrow$) report the score difference between target and non-target dockings and the fraction of cases where the target scores better, respectively; ΔE_{mean} ($\downarrow$) and $Ratio_{20}$ ($\uparrow$) report the extent to which the target score exceeds the set mean and the ratio of designs in the top 20%. **Interaction** evaluates binding performance: mean AutoDock Vina score (E, $\downarrow$) and fraction exceeding the reference ligand (IMP, $\uparrow$). To correct the effects of molecular size, we report per-pocket mean relative energy gain (MPBG, $\uparrow$) and ligand binding efficiency normalized per atom (LBE, $\uparrow$). Interaction patterns are further characterized via seven PLIP-detected[72] interaction types: population-level agreement is quantified by JSD_{OA} ($\downarrow$) and MAE_{OA} ($\downarrow$), per-pocket agreement by JSD_{PP} ($\downarrow$) and MAE_{PP} ($\downarrow$). Besides, JSD_{bs} ($\downarrow$) compares the fragment composition in binding-site.

Baselines. We compare SpecLig to representative methods with various generative paradigms: 3D autoregressive (AR[20], Pocket2Mol[21], ResGen[22]), diffusion-based (TargetDiff[24], DecompDiff[25]), fragment-

based (FLAG[36], D3FG[37], DrugGPS[39]), voxel-based (LiGAN[40], VoxBind[41]), and continuous-space approaches (MolCRAFT[73], UniMoMo[43]). Baseline designs follow CBGBench and MOLCRAFT benchmarks where available; others used standard reported settings.

Table 1. Overall comparisons for de novo small molecule design.

Model	Substruct. 0.15	Chem. 0.15	Interact. 0.25	Geom. 0.15	Speci. 0.30	Weighted Score	**Rank**
AR	0.56	0.86	1.18	0.83	0.96	4.37	10
LIGAN	0.56	0.60	<u>2.08</u>	0.90	1.26	5.39	8
Pocket2Mol	0.20	0.45	1.50	0.53	0.96	3.63	11
TargetDiff	1.00	0.50	1.83	1.05	2.61	6.99	5
ResGen	1.10	1.16	1.15	0.56	1.80	5.76	7
FLAG	0.78	1.16	0.70	0.26	0.66	3.55	12
D3FG	0.80	1.20	1.15	0.56	1.41	5.11	9
DecompDiff	1.16	0.75	1.63	1.16	2.10	6.79	6
MOLCRAFT	1.23	0.50	2.00	1.43	3.15	8.30	3
DrugGPS	0.23	0.65	0.68	0.18	0.00	1.73	13
VoxBind	0.93	1.10	1.80	1.28	<u>3.21</u>	<u>8.31</u>	<u>2</u>
UniMoMo	<u>1.50</u>	<u>1.35</u>	1.73	<u>1.46</u>	1.65	7.68	4
SpecLig	**1.70**	**1.46**	**2.15**	**1.50**	**3.51**	**10.31**	**1**

Results and discussion. Table 1 and Figure 2 summarize SpecLig's performance on the small-molecule task and complete results are shown in Chapter 7 of the Supplementary Information. SpecLig exhibits robust gains across multiple categories. On Specificity, it ranks first or second for all metrics ($\Delta\mathbf{E}_{\text{pair}} = -0.83$, $\text{Ratio}_{\text{pair}} = 58.73\%$, $\Delta\mathbf{E}_{\text{mean}} = -0.75$, $\text{Ratio}_{20} = 30.17\%$, shown in Table S3), indicating that generated compounds preferentially form stronger interactions at the intended pocket rather than broadly binding off-targets. In Interaction metrics, SpecLig achieves near-optimal mean Vina scores and the highest MPBG ($= 15.17$). Comparing with the second-ranked baseline VoxBind, SpecLig yields a 53.4% relative improvement in MPBG (shown in Table S5). Chemistry metrics are also leading, showing that pocket specificity is achieved without sacrificing drug-likeness or synthetic accessibility. On Substructure, SpecLig achieves best or near-best ranks across multiple natural fragment classes, indicating more agreement with the training fragment prior. Geometrically, collision rates are very low overall, but predicted bond-length distributions have residual room for improvement.

Despite these advances, the magnitude of improvement in specificity and affinity is smaller for small molecules than for peptides. We attribute this to task-specific chemical differences. Small-molecule space is more discrete and higher dimensional: combinatorial variation in functional groups, aromatic systems and rotatable bonds produces a highly multimodal energy landscape, limiting the coverage power of a single block-level vocabulary. Amino acids present more uniform semantics, so frequency-based priors capture complementary features more effectively. Moreover, small-molecule binding is more sensitive to geometric precision. In practice, overly strong energy guidance caused mode collapse, while insufficient guidance failed to overcome the model's sampling inertia and reduced specificity. It suggests that block–block frequency priors provide a useful foundation for a general framework, but further improvements for small molecules will require richer cues (e.g., explicit force-field terms, electrostatic fields, or conformational ensemble information).

3.2 Peptides
Setup. Referring to benchmark[43], we organize metrics into five categories: **Specificity**, **Recovery**, **Interaction**, **Structural Validity**, and **Diversity**. **Specificity** follows the protocol described above. **Recovery** measures agreement with the reference sequence and conformation. Amino-acid recovery (AAR, ↑) is the per-position sequence match rate. conformational recovery includes complex-aligned RMSD (C-RMSD, ↓) and ligand-aligned RMSD (L-RMSD, ↓). **Interaction** is primarily evaluated by the mean binding energy computed with PyRosetta (ΔG, ↓) and by the proportion of designed peptides that outperform the native ligand on their targets (IMP, ↑). We additionally report Jensen–Shannon divergence (JSD_{bs}, ↓) to quantify

Figure 3. Comparison of peptide design models across five metric categories: Recovery (a), Interaction (b), Structural validity (c), Diversity (d), and Specificity (e).

differences in fragment-type distributions within the binding site. **Structural validity** is assessed via atomic clash rates: Clash_{in} ($\downarrow$) and $\text{Clash}_{\text{out}}$ ($\downarrow$) record intra-peptide and peptide–receptor residue collisions (collision defined as C_α distance < 3.6574Å). Besides, backbone and side-chain dihedral deviations are summarized by JSD_{bb} ($\downarrow$) and JSD_{SC} ($\downarrow$) using $10°$ bins. **Diversity** is reported as the ratio of unique clusters to total designs (cluster threshold: sequence identity $> 40\%$ and RMSD < 2Å).

    Baselines.

    Peptide baselines include RFDiffusion[23], PepFlow[27], PepGLAD[42] and UniMoMo[43]. Our RFDiffusion follows the published two-stage pipeline but is limited to a single inverse-fold and relax cycle to avoid extra optimization that would bias physical metrics. PepFlow implements multimodal flow-matching for joint sequence–structure generation. PepGLAD performs latent diffusion to produce sequences and all-atom conformations. UniMoMo is the unified multimodal baseline. All methods were executed under recommended settings.

    Results and discussion. Peptides could be viewed as "big" molecules, and SpecLig shows consistent performance. Table 2 reports SpecLig's weighted scores and ranks across metric categories, and Figure 3 presents per-metric rankings. We provide the complete numerical results in Chapter 8 of the Supplementary Information. SpecLig shows a clear overall advantage on the peptide task, most pronounced in specificity and interaction. On the Specificity metrics (shown in Table S8), SpecLig raises the second-best model's $\text{Ratio}_{\text{pair}}$ and Ratio_{20} from 68.75% and 52.91% to 75.43% and 75.00%, respectively. For reference, native ligands score 80.72% and 78.31% on these metrics. In Interaction benchmarks, SpecLig is the only method whose designed peptides attain a negative mean $\Delta G = -1.92$, while the second-ranked model UniMomo yields 29.21 (shown in Table S11). These results indicate substantive improvements in suppressing off-target binding and in producing high-affinity designs. SpecLig also ranks strongly on structural validity and recovery, achieving

Table 2. Overall comparisons for de novo peptide design.

Model	Recov. 0.15	Struc. 0.15	Interact. 0.25	Div. 0.15	Speci. 0.30	Weighted Score	Rank
RFDiffusion	0.00	0.23	0.00	0.08	0.15	0.45	5
PepFlowww	0.30	0.18	0.25	0.08	0.15	0.96	4
PepGLAD	**0.45**	0.18	0.60	**0.60**	0.60	2.43	3
UniMoMo	0.35	**0.48**	<u>0.68</u>	<u>0.38</u>	<u>0.90</u>	<u>2.78</u>	<u>2</u>
SpecLig	<u>0.41</u>	<u>0.41</u>	**1.00**	<u>0.38</u>	**1.20**	**3.39**	**1**

the lowest Clashout and L-RMSD. They indicate geometrically self-consistent outputs. Some reduction in Diversity is observed, which we attribute to the constraining effect of the energy guidance.

Mechanistically, the gains stem from two design choices. Firstly, the hierarchical representation preserves fragment semantics and filters atom-level noise, simplifying identification and localization of critical local units. Secondly, incorporating interaction priors into latent diffusion biases sampling toward chemically plausible, pocket-complementary solutions. Ablation studies shown in Figure S1 confirm that removing either component degrades Specificity and Interaction. Overall, SpecLig attains a favorable balance across competing objectives, prioritizing specificity and affinity, which materially improves downstream candidate triage.

3.3 Case study

We present two case studies that illustrate how SpecLig reduces off-target risk in real applications, including small-molecule (Figure 4a–4d) and peptide (Figure 4e–4h) design. In both examples the SpecLig designs failed to produce valid docking poses on the non-target protein (Figure 4d and 4h).

The native small-molecule ligand bound to Cytochrome P450BM-3 (UniProt id: P14779) shows moderate affinity (Figure 4a, Vina $= -6.08$), driven primarily by a terminal carboxylate that forms hydrogen bonds with residues 47, 72 and 73 and by extensive hydrophobic contacts along a long alkyl chain. Paradoxically, this ligand scores better on a non-target aldehyde decarbonylase (UniProt id: Q54764; Figure 4b, Vina $= -7.32$), consistent with a topology and reusable carboxylate motif that promote off-target binding. In contrast, SpecLig proposes a molecule containing thiadiazole fragment that forms directional hydrogen bonds with residues 330 and 437 in the target pocket and establishes a broader hydrophobic contact network (Figure 4c; Vina $= -9.58$). No valid docking pose is found within the non-target pocket (Figure 4d). It indicates that SpecLig learns fragment combinations that improve both pocket-specific geometric and chemical complementarity, thereby reducing off-target risk.

On the Ferrichrome-iron receptor (UniProt id: P06971), the native peptide microcin J25 forms four hydrogen bonds in the native complex (Figure 4e) but establishes up to nine hydrogen bonds with a non-target rhodopsin (UniProt id: P02699; Figure 4f). The stronger, non-specific binding yields a much lower ΔG on the off-target (-30.46) than on the target (-8.71), illustrating that promiscuous contact motifs may lead to off-target risk. The SpecLig-designed peptide forms up to twelve hydrogen bonds in the target pocket accompanied by extensive hydrophobic contacts (Figure 4g, $\Delta G = -60.21$), and fails to adopt a feasible pose on the off-target (Figure 4h). It demonstrates the simultaneous improvement of target affinity and suppression of non-specific binding.

In methodological, coupling block-level modeling with an empirical energy prior shifts the model from learning generic interfacial fragments to performing pocket-conditioned fragment selection, thereby producing chemically and geometrically customized ligands. Importantly, SpecLig does not merely fill pockets by agglomerating fragments. Analyses in Chapter 11 of the Supplementary Information indicate an adaptive sizing mechanism within SpecLig: it is pocket topology, rather than blocks' initial setting, to predominantly determine the designed ligand's size. Lastly, additional target examples are provided in the Chapter 12 of the Supplementary Information.

4 Conclusion

SpecLig demonstrates that integrating block-wise chemical priors with hierarchical equivariant modeling yields ligand designs that better balance affinity and specificity than existing generative baselines. The hierarchical VAE reduces atom-level noise and preserves fragment semantics, while energy-guided latent sampling steers generation toward pocket-conditioned, chemically plausible solutions. Empirical evaluation suggests consistent and interpretable improvements of specificity and interaction in both peptides and small molecules design. Ablations verify the complementary roles of each module. Some limitations also remain. Gains in small molecule design are constrained by discrete chemical complexity and geometric sensitivity, indicating opportunities to incorporate richer physical cues (force-field terms, electrostatics or conformational ensembles). Besides, prospective experimental validations are still in need. Overall, SpecLig is a pioneering step toward designing ligands with enhanced specificity, and may inspire future advancements in this promising direction.

Figure 4. Case studies illustrating SpecLig's reduction of off-target binding. Native small molecule targeting cytochrome P450BM-3 (a, pink) and its non-target aldehyde decarbonylase (b, blue). (c) and (d) show SpecLig-designed small molecule bind with target and non-target, separately. Similarly, (e-f) and (g-h) show the native peptide and designed peptide bind to the target ferrichrome-iron receptor (pink) and non-target rhodopsin (blue), separately. All docking scores were computed using Schrödinger Glide and Rosetta under high-precision settings. Interaction analyses were performed with MOE for small molecules and newest PLIP for peptides. The sequences of native and designed ligands are given in gray boxes.

References

1. Glögl, M. *et al.* Target-conditioned diffusion generates potent tnfr superfamily antagonists and agonists. *Science* **386**, 1154–1161 (2024).

2. Wang, Z. *et al.* Naturally enhanced neutralizing breadth against sars-cov-2 one year after infection. *Nature* **595**, 426–431 (2021).

3. Jumper, J. *et al.* Highly accurate protein structure prediction with alphafold. *nature* **596**, 583–589 (2021).

4. Baek, M. *et al.* Accurate prediction of protein structures and interactions using a three-track neural network. *Science* **373**, 871–876 (2021).

5. Brandes, N., Ofer, D., Peleg, Y., Rappoport, N. & Linial, M. Proteinbert: a universal deep-learning model of protein sequence and function. *Bioinformatics* **38**, 2102–2110 (2022).

6. Ross, J. *et al.* Large-scale chemical language representations capture molecular structure and properties. *Nature Machine Intelligence* **4**, 1256–1264 (2022).

7. Zhang, P., Xia, C. & Shen, H.-B. High-accuracy protein model quality assessment using attention graph neural networks. *Briefings Bioinformatics* **24**, bbac614 (2023).

8. Gujral, O., Bafna, M., Alm, E. & Berger, B. Sparse autoencoders uncover biologically interpretable features in protein language model representations. *Proceedings National Academy Sciences* **122**, e2506316122 (2025).

9. Gao, B. *et al.* Drugclip: Contrasive protein-molecule representation learning for virtual screening. *Advances Neural Information Processing Systems* **36** (2024).

10. Singh, R., Sledzieski, S., Bryson, B., Cowen, L. & Berger, B. Contrastive learning in protein language space predicts interactions between drugs and protein targets. *Proceedings National Academy Sciences* **120**, e2220778120 (2023).

11. Zhang, P.-D., Ma, J. & Chen, T. Escaping the drug-bias trap: using debiasing design to improve interpretability and generalization of drug-target interaction prediction. *bioRxiv* 2024–09 (2024).

12. Honarparvar, B., Govender, T., Maguire, G. E., Soliman, M. E. & Kruger, H. G. Integrated approach to structure-based enzymatic drug design: molecular modeling, spectroscopy, and experimental bioactivity. *Chemical reviews* **114**, 493–537 (2014).

13. Xie, W., Wang, F., Li, Y., Lai, L. & Pei, J. Advances and challenges in de novo drug design using three-dimensional deep generative models. *Journal Chemical Information Modeling* **62**, 2269–2279 (2022).

14. Du, Y. *et al.* Machine learning-aided generative molecular design. *Nature Machine Intelligence* 1–16 (2024).

15. Bepler, T. & Berger, B. Learning protein sequence embeddings using information from structure. *arXiv preprint arXiv:1902.08661* (2019).

16. Beck, H., Härter, M., Haß, B., Schmeck, C. & Baerfacker, L. Small molecules and their impact in drug discovery: A perspective on the occasion of the 125th anniversary of the bayer chemical research laboratory. *Drug Discovery Today* **27**, 1560–1574 (2022).

17. Derakhshankhah, H. & Jafari, S. Cell penetrating peptides: A concise review with emphasis on biomedical applications. *Biomedicine & Pharmacotherapy* **108**, 1090–1096 (2018).

18. Bissantz, C., Kuhn, B. & Stahl, M. A medicinal chemist's guide to molecular interactions. *Journal medicinal chemistry* **53**, 5061–5084 (2010).

19. Haynes, W. M. *CRC handbook of chemistry and physics* (CRC press, 2016).

20. Luo, S., Guan, J., Ma, J. & Peng, J. A 3d generative model for structure-based drug design. *Advances Neural Information Processing Systems* **34**, 6229–6239 (2021).

21. Peng, X. *et al.* Pocket2mol: Efficient molecular sampling based on 3d protein pockets. In *International Conference on Machine Learning*, 17644–17655 (PMLR, 2022).

22. Zhang, O. *et al.* Resgen is a pocket-aware 3d molecular generation model based on parallel multiscale modelling. *Nature Machine Intelligence* **5**, 1020–1030 (2023).

23. Watson, J. L. *et al.* De novo design of protein structure and function with rfdiffusion. *Nature* **620**, 1089–1100 (2023).

24. Guan, J. *et al.* 3d equivariant diffusion for target-aware molecule generation and affinity prediction. *arXiv preprint arXiv:2303.03543* (2023).

25. Guan, J. *et al.* Decompdiff: diffusion models with decomposed priors for structure-based drug design. *arXiv preprint arXiv:2403.07902* (2024).

26. Xie, X., Valiente, P. A., Kim, J. & Kim, P. M. Helixdiff, a score-based diffusion model for generating all-atom α-helical structures. *ACS Central Science* **10**, 1001–1011 (2024).

27. Lin, H. *et al.* Ppflow: Target-aware peptide design with torsional flow matching. *arXiv preprint arXiv:2405.06642* (2024).

28. Wu, F. *et al.* D-flow: Multi-modality flow matching for d-peptide design. *arXiv preprint arXiv:2411.10618* (2024).

29. Jing, B., Berger, B. & Jaakkola, T. Alphafold meets flow matching for generating protein ensembles. *arXiv preprint arXiv:2402.04845* (2024).

30. Zhang, P., Peng, X., Han, R., Chen, T. & Ma, J. Rag2mol: structure-based drug design based on retrieval augmented generation. *Briefings Bioinformatics* **26** (2025).

31. Lee, S. *et al.* Molecule generation with fragment retrieval augmentation. *Advances Neural Information Processing Systems* **37**, 132463–132490 (2024).

32. Gu, S. *et al.* Aligning target-aware molecule diffusion models with exact energy optimization. *Advances Neural Information Processing Systems* **37**, 44040–44063 (2024).

33. Huang, Z. *et al.* Protein-ligand interaction prior for binding-aware 3d molecule diffusion models. In *The Twelfth International Conference on Learning Representations* (2024).

34. Karnaukhov, V. K. *et al.* Structure-based prediction of t cell receptor recognition of unseen epitopes using tcren. *Nature Computational Science* **4**, 510–521 (2024).

35. Schneuing, A. *et al.* Structure-based drug design with equivariant diffusion models. *Nature Computational Science* **4**, 899–909 (2024).

36. Zhang, Z., Min, Y., Zheng, S. & Liu, Q. Molecule generation for target protein binding with structural motifs. In *The Eleventh International Conference on Learning Representations* (2023).

37. Lin, H. *et al.* Functional-group-based diffusion for pocket-specific molecule generation and elaboration. *Advances Neural Information Processing Systems* **36**, 34603–34626 (2023).

38. Jiang, Y. *et al.* Pocketflow is a data-and-knowledge-driven structure-based molecular generative model. *Nature Machine Intelligence* **6**, 326–337 (2024).

39. Zhang, Z. & Liu, Q. Learning subpocket prototypes for generalizable structure-based drug design. In *International Conference on Machine Learning*, 41382–41398 (PMLR, 2023).

40. Ragoza, M., Masuda, T. & Koes, D. R. Generating 3d molecules conditional on receptor binding sites with deep generative models. *Chemical science* **13**, 2701–2713 (2022).

41. Pinheiro, P. O., Jamasb, A., Mahmood, O., Sresht, V. & Saremi, S. Structure-based drug design by denoising voxel grids. *arXiv preprint arXiv:2405.03961* (2024).

42. Kong, X., Jia, Y., Huang, W. & Liu, Y. Full-atom peptide design with geometric latent diffusion. *Advances Neural Information Processing Systems* **37**, 74808–74839 (2024).

43. Kong, X. *et al.* Unimomo: Unified generative modeling of 3d molecules for de novo binder design. *arXiv preprint arXiv:2503.19300* (2025).

44. Peng, X. *et al.* Atom-level generative foundation model for molecular interaction with pockets. *bioRxiv* 2024–10 (2024).

45. Gao, Z. *et al.* Uniif: Unified molecule inverse folding. *Advances Neural Information Processing Systems* **37**, 135843–135860 (2024).

46. Abramson, J. *et al.* Accurate structure prediction of biomolecular interactions with alphafold 3. *Nature* **630**, 493–500 (2024).

47. Liu, J. *et al.* In silico off-target profiling for enhanced drug safety assessment. *Acta Pharmaceutica Sinica B* **14**, 2927–2941 (2024).

48. Wei, L., Ye, X., Sakurai, T., Mu, Z. & Wei, L. Toxibtl: prediction of peptide toxicity based on information bottleneck and transfer learning. *Bioinformatics* **38**, 1514–1524 (2022).

49. Atz, K. *et al.* Prospective de novo drug design with deep interactome learning. *Nature Communications* **15**, 3408 (2024).

50. Zheng, L. *et al.* Improving protein–ligand docking and screening accuracies by incorporating a scoring function correction term. *Briefings Bioinformatics* **23**, bbac051 (2022).

51. Jing, B., Jaakkola, T. & Berger, B. Equivariant scalar fields for molecular docking with fast fourier transforms. *arXiv preprint arXiv:2312.04323* (2023).

52. Gao, B. *et al.* Rethinking specificity in sbdd: Leveraging delta score and energy-guided diffusion. *arXiv preprint arXiv:2403.12987* (2024).

53. Huggins, D. J., Sherman, W. & Tidor, B. Rational approaches to improving selectivity in drug design. *Journal medicinal chemistry* **55**, 1424–1444 (2012).

54. Kong, X., Huang, W., Tan, Z. & Liu, Y. Molecule generation by principal subgraph mining and assembling. *Advances Neural Information Processing Systems* **35**, 2550–2563 (2022).

55. Vincent, P. *et al.* Stacked denoising autoencoders: Learning useful representations in a deep network with a local denoising criterion. *Journal machine learning research* **11** (2010).

56. Jiao, R., Kong, X., Yu, Z., Huang, W. & Liu, Y. Equivariant pretrained transformer for unified geometric learning on multi-domain 3d molecules. In *ICLR 2024 Workshop on Generative and Experimental Perspectives for Biomolecular Design* (2024).

57. Kingma, D. P. & Welling, M. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114* (2013).

58. Lipman, Y., Chen, R. T., Ben-Hamu, H., Nickel, M. & Le, M. Flow matching for generative modeling. *arXiv preprint arXiv:2210.02747* (2022).

59. Sterling, T. & Irwin, J. J. Zinc 15–ligand discovery for everyone. *Journal chemical information modeling* **55**, 2324–2337 (2015).

60. Gaulton, A. *et al.* Chembl: a large-scale bioactivity database for drug discovery. *Nucleic acids research* **40**, D1100–D1107 (2012).

61. Burley, S. K. *et al.* Rcsb protein data bank: biological macromolecular structures enabling research and education in fundamental biology, biomedicine, biotechnology and energy. *Nucleic acids research* **47**, D464–D474 (2019).

62. Wen, Z., He, J., Tao, H. & Huang, S.-Y. Pepbdb: a comprehensive structural database of biological peptide–protein interactions. *Bioinformatics* **35**, 175–177 (2019).

63. Wang, R., Fang, X., Lu, Y., Yang, C.-Y. & Wang, S. The pdbbind database: methodologies and updates. *Journal medicinal chemistry* **48**, 4111–4119 (2005).

64. Hu, L., Benson, M. L., Smith, R. D., Lerner, M. G. & Carlson, H. A. Binding moad (mother of all databases). *Proteins: Structure, Function, Bioinformatics* **60**, 333–340 (2005).

65. Luo, S. *et al.* Antigen-specific antibody design and optimization with diffusion-based generative models for protein structures. *Advances Neural Information Processing Systems* **35**, 9754–9767 (2022).

66. Berrada, T. *et al.* Boosting latent diffusion with perceptual objectives. In *The Thirteenth International Conference on Learning Representations* (2025).

67. Tsaban, T. *et al.* Harnessing protein folding neural networks for peptide–protein docking. *Nature communications* **13**, 176 (2022).

68. Francoeur, P. G. *et al.* Three-dimensional convolutional neural networks and a cross-docked data set for structure-based drug design. *Journal chemical information modeling* **60**, 4200–4215 (2020).

69. Yu, Y. *et al.* Uni-dock: Gpu-accelerated docking enables ultralarge virtual screening. *Journal chemical theory computation* **19**, 3336–3345 (2023).

70. Trott, O. & Olson, A. J. Autodock vina: improving the speed and accuracy of docking with a new scoring function, efficient optimization, and multithreading. *Journal computational chemistry* **31**, 455–461 (2010).

71. Lin, H. *et al.* Cbgbench: fill in the blank of protein-molecule complex binding graph. *arXiv preprint arXiv:2406.10840* (2024).

72. Schake, P., Bolz, S. N., Linnemann, K. & Schroeder, M. Plip 2025: introducing protein–protein interactions to the protein–ligand interaction profiler. *Nucleic Acids Research* gkaf361 (2025).

73. Qu, Y. *et al.* Molcraft: Structure-based drug design in continuous parameter space. *arXiv preprint arXiv:2404.12141* (2024).