CapuchinAI 1.0: Development of a machine learning-based touchscreen paradigm to test

cognition in wild capuchins

<u>**Alternative Short Title**</u>**: CapuchinAI: Leveraging AI to study wild primate cognition**

Federico Sánchez Vargas[1, a], Sai Rakshith Potluri[2,3], Jacob Abernethy[2], Marcela E. Benítez[1]

[1]Department of Anthropology, Emory University, Atlanta, GA, USA

[2]School of Computer Science, Georgia Institute of Technology, Atlanta, GA, USA

[3]ExtraHop Networks, Seattle, WA, USA

[a] Corresponding author. Contact information:

Email: federico.sanchez.vargas@emory.edu

Phone number: +1 585 981 8146

Research Highlights:

• We present CapuchinAI, a field-ready touchscreen testing station that uses real-time facial

recognition to study cognition in wild capuchin monkeys

• We developed a YOLOv7-based facial recognition model (Multiple Capuchins v1.0) that

identifies individual capuchins with >97% precision and recall from static images, video, and

live footage, enabling fully automated, individualized testing in the wild.

• We integrated a version of this model into a closed-loop touchscreen–reward pipeline that

detects an approaching monkey, presents a basic learning task, and automatically delivers food

rewards based on the monkey's responses.

• Wild capuchins rapidly habituated and learned touchscreen–reward associations, showing that

AI-enabled touchscreens provide a scalable field method for deploying lab-style cognitive tests

and mapping individual differences across tasks, species, and sites.

Funding: Research reported in this publication was supported by the National Institute on Drug

Abuse of the National Institutes of Health under Award Number R34DA061925. The content is

solely the responsibility of the authors and does not necessarily represent the official views of the

National Institutes of Health. Additional support was provided by the National Science

Foundation (BCS-2127373; awarded to Benítez ME), an Emory A.I. Humanity Seed grant

(awarded to Benítez ME and Abernethy J), a Lewis and Clark Fund for Exploration and Field

Research grant (awarded to Sánchez Vargas F), a graduate stipend from the Laney Graduate

School at Emory University to Sánchez Vargas F, and a student travel grant from the Center for

Mind, Brain, and Culture at Emory University (awarded to Sánchez Vargas F).

Declaration of interest: none.

ABSTRACT (250 words)**:**

Advancing the study of primate cognition requires methods that preserve ecological validity while enabling the experimental control typical of laboratory research. We introduce **CapuchinAI**, a field-deployable touchscreen system that integrates real-time facial recognition with automated cognitive testing, providing a novel methodological framework for studying cognition in wild primates. Our approach combines a high-performing (>97% accuracy) YOLOv7-based facial recognition model (*Multiple Capuchins v1.0*) with a portable Raspberry Pi–driven touchscreen–reward apparatus designed for automated operation in natural habitats. The system detects approaching capuchins, initiates video recording, presents touchscreen stimuli, and dispenses food rewards contingent on task performance. During a two-week presentation to two habituated groups of wild white-faced capuchins (*Cebus imitator*) at the Taboga Forest Reserve, **16 individuals** voluntarily interacted with the apparatus, **10 learned to trigger rewards**, and **8 formed and retained robust screen–reward associations**. The rapid habituation and learning rates demonstrate the feasibility of deploying AI-mediated cognitive experiments in the wild. CapuchinAI addresses several long-standing challenges in field cognition research by enabling: (1) autonomous, individualized task administration without researcher intervention; (2) standardized, repeatable trials across individuals and sessions; (3) scalable deployment across groups and sites; and (4) parallel data collection on behavior, identity, and performance. This methodology provides a blueprint for integrating machine learning, touchscreen testing, and automated reward delivery to study within- and between-individual cognitive variation under natural conditions. CapuchinAI represents a significant step toward long-term comparative research on primate cognition by making laboratory experimental paradigms accessible in the wild, bridging the gap between lab and field.

Key Words: Primate cognition, machine learning, field experiments

1. INTRODUCTION

Primates stand out from other mammals by having unusually large brains and advanced cognition (Roth & Dicke, 2012). This has established primates as key models for the study of cognitive evolution, with their complex and diverse social world, extended development and life history, and species-specific ecological adaptations marking them as prime candidates to study how brains and minds evolve and adapt (Dunbar & Shultz, 2007; Grabowski et al., 2023; Leigh, 2004). Understanding primate cognitive evolution is an interdisciplinary objective, uniting anthropologists focused on the pressures that have selected for larger brains with psychologists exploring the mechanisms driving cognitive choices. A central assumption in both approaches is that cognitive abilities are adaptive (Byrne, 2000; Dukas, 2004): individuals who are more effective at acquiring, processing, and using information to make informed decisions should be more likely to survive and reproduce (i.e., fitness). Yet, despite this foundational premise, surprisingly few studies have directly linked cognitive performance to real-world fitness outcomes in primates (Huebner et al., 2018). One primary reason for this gap is methodological. Cognition has traditionally been studied in captivity, where experimental control and replicability allow researchers to isolate the mechanisms underlying complex behaviors (Shettleworth, 2001). While these settings provide experimental precision, they are necessarily detached from the rich social and ecological contexts in which primate cognition evolved. Consequently, it is difficult to distinguish what primates *can do* in the laboratory from what they *actually do* in nature. Field studies, by contrast, capture the ecological validity and functional significance of cognitive traits but often lack the experimental rigor and control necessary to infer underlying mechanisms. The strengths of one approach, therefore, highlight the weaknesses of the other: captive experiments provide control but lack ecological validity, field studies provide ecological validity but lack controls.

Field experiments have begun to narrow the gap between captive and wild research by introducing shared frameworks for testing cognition under natural conditions (reviewed in Benítez et al., 2022). Approaches such as artificial-fruit "puzzle boxes" and field-adapted foraging tasks have provided valuable insights into how primates innovate, learn, and cooperate in ecologically relevant contexts (e.g., van de Waal et al., 2010; Canteloup & van de Waal., 2020; Amici et al., 2020; Molesti & Majolo 2016). These studies demonstrate that interactive experiments are feasible in the wild and can yield meaningful data on social learning, problem-

solving, and cooperation. Yet they remain constrained in scale and resolution: participation is

often unpredictable, dominant individuals can monopolize access, and most designs allow only

single interactions, limiting replication, sample size, and standardization (Lopresti-Goodman et

al., 2022; Thornton & Samson, 2012). As a result, while these field experiments have been

pivotal in extending cognitive research beyond captivity, they have yet to yield the long-term,

fine-grained data needed to quantify individual variation across multiple cognitive domains —a

critical step in understanding the evolution and adaptive significance of primate cognition.

Here, we describe a novel method to study cognition in the wild. Our "smart testing

stations" integrate advances in machine learning with a field-friendly touchscreen interface to

investigate cognition in wild white-faced capuchins (*Cebus imitator*) at the Taboga Forest

Reserve in Costa Rica. Recent advances in machine learning and computer vision now make it

possible to automatically recognize and track individual primates in natural environments

(Schofield et al., 2019). These tools have already been used to reconstruct social networks and

quantify the stability of individual social tendencies in wild chimpanzees (*Pan troglodytes*;

Schofield et al., 2023), offering unprecedented opportunities to monitor behavior at scale.

Building on these advances, our rugged testing stations combine machine-learning–based

identification with a remotely operated touchscreen apparatus that can tailor cognitive testing to

each individual in real time. This design is equipped with a 3D-printed food dispenser that

dispenses 32 rewards (in our case, dried forest bananas), enabling controlled, repeatable trials

within natural group settings. This integration overcomes key logistical and methodological

barriers in field cognition research—allowing for the automated, high-resolution collection of

multi-timepoint data on individual performance across multiple cognitive domains (Benítez et

al., 2022).

We see several immediate and long-term goals for this design. In the short term, it

enables researchers to (1) assess individual variation across multiple domains of cognition, (2)

test whether performance in one domain predicts performance in others, and (3) examine how

such variation relates to how successfully individuals navigate social and ecological challenges.

Over the long term, our goal is to (1) systematically track within-individual changes in cognitive

performance across life history stages, and (2) generate one of the most comprehensive

longitudinal datasets on cognition in a wild primate population. By pairing long-term cognitive

data with long-term demographic, behavioral, ecological, and hormonal data, we can begin to

connect individual variation in cognitive trails to fitness-relevant outcomes such as social

success, reproduction, and survival. This methodology fills a critical gap, offering a scalable,

field-ready approach for systematically testing multiple domains of cognition in the wild and

linking cognitive variation to the evolutionary processes that shape it.

In this paper, we detail the methodology of this new approach, including the facial

recognition model, data processing, model pipelines, and touchscreen design. Specifically, we

address three key questions: (1) Can we develop a high-quality facial recognition model for

capuchins? (2) Can we create a field-friendly touchscreen device that runs this model in real time

to deliver and adapt cognitive experiments, controlling task presentation and reward? And (3)

will wild capuchins reliably interact with this system? Together, these steps outline a practical

roadmap for integrating artificial intelligence and experimental cognition in the wild, providing,

for the first time, a systematic way to evaluate and monitor the cognitive abilities of wild

primates.

1.1 CapuchinAI: A new paradigm for studying wild capuchin cognition

Capuchin monkeys are a key species for studying comparative cognition. They share several

traits with humans, such as large brains relative to body size (Rilling and Insel, 1999), extensive

cooperation both in captivity (Brosnan, 2011; Brosnan et al., 2006) and in the wild (Perry, 1996;

Scarry, 2017), prosocial behaviors (Brosnan, 2011; Claidière et al., 2015), and sophisticated

skills in extractive foraging (Barret et al., 2018). Since capuchins and humans diverged

approximately 23 million years ago (Glazko & Nei, 2003), they serve as a valuable comparative

model to explore the social and ecological factors that selected for the evolution of larger brains.

Compared to many other non-human primates, both tufted capuchins (*Sapajus apella* spp.) and

white-faced capuchins (*Cebus capucinus* spp.) are particularly skilled at innovation, learning,

and solving complex problems. In captivity, tufted capuchins are easily trained on a range of

manual and computer-based tasks (e.g., Parrish et al., 2015), providing a detailed understanding

of their cognitive capabilities. However, because most of what we know about capuchin

cognition comes from captive studies mainly of *Sapajus*, there is still much to learn about how

they use their large brains in natural environments.

White-faced capuchins have been studied extensively in the field, yielding rich descriptions

of their social structure, cooperation, extractive foraging, and social learning capabilities. What

remains comparatively unclear are the cognitive mechanisms underlying these behaviors: how

individuals acquire, represent, and use information to make decisions, and how such variation

maps onto socioecological conditions. One reason is practical. Unlike their *Sapajus* relatives,

white-faced capuchins are not readily studied in captivity, which has constrained experimental

work and left a gap between documented behavioral observations in the wild and direct measures

of cognition.

The white-faced capuchins at the Capuchinos de Taboga field station in the Guanacaste

region of Costa Rica represent an ideal population to begin such an investigation. This site

contains the highest-density population of white-faced capuchins recorded in the wild (Tinsley

Johnson et al., 2020). At this site, four groups have been fully habituated and are subject to daily

behavioral observations and hormone sample collection. Furthermore, three of these groups have

also been habituated to testing platforms installed in their home ranges, where they voluntarily

participate in multiple non-invasive cognitive experiments. These testing platforms have been

used to conduct several cognitive experiments, generating a large, multi-year dataset of high-

resolution videos and images of individuals who frequent the platforms. These videos provided

the dataset for training our models (**Section 2.1**), and these platforms provide the foundation for

deploying smart testing stations (**Section 3.1**).

Our main objective is to develop and implement "smart" testing stations for long-term

cognitive assessment of the wild capuchins at Taboga. Each station uses a machine learning

facial-recognition model to detect an approaching monkey, identify the individual in real time,

and retrieve the "bookmark" for where that individual left off in the cognitive testing battery.

The station then presents the appropriate next task and level on the touchscreen interface,

automatically guiding subjects through a scaffolded cognitive battery of tasks (see **Figure 1** for a

visual representation of this workflow).

This design offers two central advantages. First, our AI facial recognition software

enables autonomous, individualized cognitive testing, allowing researchers to manage

participation remotely and adjust task difficulty to each monkey's performance, so each

individual progresses at their own pace. In typical lab workflows, researchers manually program

a station for a single, preselected subject, which is not feasible in the wild. Our approach

preassigns tests for all potential participants before a session begins. As individuals arrive and

depart, the integrated facial-recognition system detects both the presence of a capuchin and its

specific identity in real time, then serves the individualized task list to the animal at the screen.

Because detection and identification refresh continuously at millisecond resolution, changes in

participants—for example, when one individual displaces another—do not disrupt testing; the

software immediately switches to the tests preassigned to the new participant.

Second, the touchscreen interface will permit us to administer cognitive tests already

employed and highly validated in lab settings (e.g., Richardson et al., 1990; Butler et al., 2019)

and, more recently, in wild vervet monkeys (Harrison et al., 2023). These include simple

association formation paradigms (**Section 3**), delayed match-to-sample tasks to test working and

long-term memory (Colares Leal et al., 2020; Sosnowski & Brosnan, 2025), 'go/no-go' tasks to

test impulse control (Picanço & Barros, 2015), and rule reversal tasks to test cognitive flexibility,

among others.

Between July and August 2025, we piloted the initial version of our machine learning-based

touchscreen cognitive testing device, **'CapuchinAI v1.0,'** with two groups at Taboga Forest

Reserve. Below, we explain the development and operation of the software (**Section 2.1**) and

hardware (**Section 2.2**), and demonstrate how wild capuchin monkeys habituated and interacted

with the device (**Sections 2.3, 3.1 – 3.2**). We conclude by outlining future development steps

(**Section 3.3**) and discussing the strengths, limitations, and potential for adaptation to other

primate species and field stations (**Section 4**).

2. DESCRIPTION

Over the past decade, the computer vision community has invested much effort into a

new class of models, known as *deep convolutional neural networks* (CNNs), one of the staples of

deep learning (LeCun et al., 2015). There has been significant progress in the success of ML-

based object detection in recent years, with the best models achieving essentially human-level

performance on computer vision tasks (Wang & Deng, 2021). This has been driven in large part

by methodological improvements, aided by massive advances in chips designed for learning (i.e.,

GPU technology) and the vast amount of available data.

Recently, there has been growing interest in using deep learning models to detect animal

species and to deploy them in conjunction with camera traps in the wild (Norouzzadeh et al.,

2018; Tabak et al., 2018). In primates, machine learning has been used to successfully identify

species and individuals within a species, for example, red-bellied lemurs (*Eulemur rubriventer,*

Crouse et al., 2017), rhesus macaques (*Macaca mulatta,* Witham, 2018; Zhang et al., 2025), and

golden snub-nosed monkeys (*Rhinopithecus roxellana,* Guo et al., 2020). However, nearly all

this work is based on data collected in highly structured environments, often with monkeys in

captivity, or with stationary camera setups. A key exception is fully automated, face-based

identification of wild chimpanzees from long-term field video (Schofield et al., 2019), which

demonstrates the feasibility of AI models under field conditions. Building on this work, our

model adds two capabilities to the current AI facial recognition work in primates: 1) a reliable

operation in arboreal, forest habitats with shifting light, occlusion, and rapid movement, and 2)

millisecond-level identity resolution, allowing the model to recognize multiple individuals in real

time.

Figure 1 — **Diagram of real-time, automated facial detection and cognitive testing touchscreen apparatus:** As a monkey
approaches the apparatus (left), the machine learning facial recognition model detects the presence of a potential participant. The
model determines that the approaching animal is a capuchin and then, in real time, recognizes the individual's identity based on
its training dataset. With this information, the model can then automatically administer touchscreen cognitive tasks, collect and
store data, record video of the participating monkey, and administer food rewards for correct responses. Note that, since the
model runs inferences at more than 30 frames per second, any sudden change in the identity of the participating individual will
seamlessly trigger downstream changes in the stimuli presented and the data collected. Illustration based on testing conditions at
Taboga Forest Reserve, Costa Rica.

2.1. Can we develop a high-quality capuchin facial recognition model?

The first step was to create the dataset for training a precise, accurate, and robust

capuchin facial recognition model. At Capuchinos de Taboga, we gathered an extensive

collection of high-quality close-up GoPro videos of capuchins interacting with cognitive

experiments on testing platforms. Each video was manually coded, identifying capuchins in each

frame and their behaviors of interest using an open-source event-logging software, Behavioral

Observation Research Interactive Software (BORIS; Friard & Gamba, 2016). Using the

timestamped BORIS output, we configured a Python script to extract high-quality frames from

these videos every second that a capuchin was present. Once frames were extracted, they were

stored as individually labeled images.

These images were then uploaded to Roboflow (Dwyer et al., 2025), where we manually

placed bounding boxes around each capuchin's face to define the region of interest. Roboflow is

an advanced tool designed to streamline and optimize the process of preparing datasets for

machine learning, particularly in the field of computer vision. To ensure our model was trained

on a balanced dataset, we applied an additional sampling step after frame extraction. This post–

frame extraction sampling ensured that each subject contributed an equal number of frames to

the final dataset, preventing any single subject from dominating the training data. To bolster

model robustness and ensure strong performance under varying lighting and color conditions, we

used Roboflow's dataset augmentation tools to generate altered versions of the training images.

These augmentations modified lighting, resolution, and image blur to create additional examples

for the model that mimic the variability of filming conditions in the wild. The final dataset

consisted of 2,160 unique images — over 4000 images with the augmented dataset — evenly

distributed across six adult male capuchins (Pery, Pirulo, Pele, Pesto, Pio, and Pedro).

For our model, Multiple Capuchins v1.0, we used Ultralytics YOLOv7 (You Only Look

Once, version 7-nano) object detection model architecture (Wang et al., 2023). This architecture

is specialized for rapid, real-time object detection, making it well-suited for high-accuracy

identification and classification of objects in live video streams. The model was trained with a

batch size of 8 for 300 epochs. All settings were defined in a YAML file (e.g., class names,

number of classes, and paths to the training and validation sets). The Multiple Capuchins v1.0

model performed exceptionally well on the held-out test dataset (images the model was not

trained on), including perturbed images, achieving 97.5% precision and 98.2% recall. In practical

terms, this means that when the model was presented with a capuchin face—even when lighting

or resolution were altered—it detected and attempted to classify that face 98.2% of the time, and

when it did so, it assigned the correct monkey ID 97.5% of the time. We found that Multiple

Capuchins v1.0 can successfully classify static images and pre-recorded videos (**Figure 2**). The

next step was to figure out how to integrate a version of this model to run on a low-energy, field-

friendly computer interface.

Figure 2 — **MultipleCapuchins v1.0 Facial Recognition Model Performance:** Sample still images taken from output videos of the MultipleCapuchins v1.0 machine learning model performing capuchin facial detection. This model was developed on Ultralytics YOLOv7 architecture and trained on the identities of six male capuchins from video footage collected during previous cognitive experiments at Taboga Forest Reserve, Costa Rica. Bounded boxes indicate the area where the model recognizes a capuchin face. Names and percentages in the upper left corner of the bounded boxes indicate the model's guess and confidence in the identity of the individual within the box. Note that the four individuals pictured here are each looking in different directions under distinct lighting conditions – yet the model retains high confidence.

280   **2.2. Can we create a field-friendly touchscreen device that runs this model in real time to**

281   **deliver and adapt cognitive experiments, controlling task presentation and rewards?**

282   Having developed a highly accurate capuchin facial-recognition model, our next step was

to build a field-friendly touchscreen apparatus that could run live facial detection, present tasks

to interacting monkeys, and dispense food rewards. Our apparatus, **CapuchinAI v1.0**, runs on a

Raspberry Pi 5 (RPi5), a compact Linux-based computer well suited for multi-input/output

applications that must operate reliably in remote locations (e.g., primatology field sites) (Mathe

et al., 2024).

CapuchinAI, controlled by the RPi5, integrates the following components:

1. A 15-inch screen to display stimuli to participating monkeys.

2. An infrared touch overlay that converts the screen into a touch display. This type of

touchscreen is ideal for work with primates because it is inexpensive, durable, and can be

activated with any part of the primate's body (e.g., finger, whole hand, mouth, nail,

tongue).

3. A high-definition USB webcam that provides a live video feed for the model to run

detection on.

4. An electronic relay device, connected to a 3D-printed food reward dispenser, that

controls reward delivery by closing a circuit for a defined period whenever a monkey

touches the screen.

The entire setup is powered by two low-cost, widely available travel power banks (one for the

display and one for the RPi5) and a 12-volt battery pack for the food dispenser's motor. Initial

tests showed that the apparatus could run uninterrupted on this power supply for at least 8 hours.

It is encased in a wooden frame measuring ($19 \times 21 \times 5$ inches) that fits into the cognitive testing

platforms at Taboga and is internally organized to allow easy access to all components,

facilitating on-the-fly adjustments (e.g., adjusting screen or camera placement, replacing power

sources, refilling the food dispenser). **Figure 3** provides a visual schematic of this setup.

*Figure 3 — **CapuchinAI v.1.0 Cognitive Testing Apparatus.**
A) Diagram of functional components of apparatus:
CapuchinAI v.1.0 integrates multiple peripheral components
through a series of python scripts run on a Raspberry Pi 5 (**a**). The
Raspberry Pi 5 connects via USB to a full-HD webcam (**b**), which
feeds live video footage to a continuously running facial
recognition machine learning model. Simultaneously, cognitive
testing visual stimuli are presented to primate participants via a
display screen (**c**), and participants' screen touches are recorded
via an infrared touchscreen overlay (**d**). If a participant
successfully completes an assigned task, the Raspberry Pi 5 sends
a signal to a relay device (**e**) via its GPIO (general purpose
input/output) pins. This relay device completes an electrical
circuit powering a 12-volt DC motor (**f**) for a defined amount of
time, allowing a rotary food reward dispenser (**g**) to rotate exactly
the degrees needed to release one food reward. Note: components
not drawn to scale.

**B) CapuchinAI v.1.0. apparatus deployed at testing platforms
in Taboga Field Site, Costa Rica**. The image shows the

completed apparatus ready for interaction by primate participants. Key visible components are described.

For our prototype, we deployed a modified version of our Multiple Capuchins v1.0 model on

the RPi5, reimplemented using the Ultralytics YOLOv5 architecture. YOLOv5 is a lighter

weight, widely used model that has been successfully run on Raspberry Pi platforms, making it a

practical choice for efficient, real-time inference in our field setting. In this prototype, we

simplified the model detection categories to detect any capuchin face rather than classify

individual identities, as the model would be encountering capuchins it was not trained on. This

design served two goals: first, it enabled the system to trigger video recording whenever any

capuchin approached the touchscreen, rapidly generating a larger, more up-to-date dataset of

faces from interacting monkeys; second, it allowed us to offer the touchscreen task to all

habituated capuchins, not only those included in the original YOLOv7 training set. Because the

identities of all participating individuals are already known from long-term monitoring, the

resulting videos and images can be used to train the next, more comprehensive version of our

individual-level facial recognition model (see **Section 3.2**).

To integrate our facial recognition model with our apparatus, we developed two Python

scripts. The first of these, "**capuchin_recorder.py**", initializes the webcam and starts running

detection on the camera's live feed at approximately 30 frames per second, providing high-

resolution, real-time facial detection. Since our goal at this stage was to collect videos of all

individuals approaching the platform, this script instructs the camera to start recording when face

detection occurs and to stop recording after 10 seconds elapse with no capuchins in view of the

camera. This loop continues for as long as the script runs, generating multiple videos per session

without quickly overloading the RPi5's storage or processing capacity. At the end of the session,

the script places all recorded videos in a designated folder, along with a log of the start and end

times for each video.

The second Python script, "**touchscreen_reward_interface.py**" uses pygame v.2.6.0

(McGugan, 2007), a python library designed to facilitate the creation of interactive stimuli for

use in games, cognitive testing, or other user-facing interfaces. Using pygame, we developed a

simple habituation stimulus for monkeys: a screen-wide blue square that records when an

interacting monkey touches it. When a touch event occurs, our script signals the relay device to

close the dispenser's motor circuit, triggering the automatic dispensation of a food reward. The

screen next flashes black for 2 seconds during a cooldown period, then returns to blue, signaling

that it is ready to register a new touch.

These two Python scripts are integrated to run simultaneously and share key information.

Critically, the stimulus presentation and reward dispensing script only signals the relay device to

deliver a reward if a capuchin face has been detected. As a result, the system prevents rewards

from being dispensed to non-study species (e.g., other species that may interact with the

apparatus) and provides the foundation for individual-level control over the number of trials each

monkey can complete per day, a promising aspect of our methodology that we elaborate in

Section 4.

3. EXAMPLE

3.1. Will wild capuchins reliably interact with this system?

Between July and August 2025, we presented our CapuchinAI v1.0 prototype to two

groups of wild white-faced capuchins at the Taboga Forest Reserve that have been under near-

daily observation by the Capuchinos de Taboga project since 2017. These two groups of

capuchins, Tenori (N = 25 individuals) and Palmas (N = 26 individuals), are fully habituated to

testing platforms within their home ranges and have participated in ongoing cognitive tasks. The

apparatus was secured on testing platforms opportunistically, depending on the focal group's

location on any given day. The setup was always conducted outside the view of any capuchin

groups to prevent associations between the researchers and the food rewards. Food rewards

consisted of sliced, dried banana pieces, a natural food at Taboga that these capuchins readily

eat. At this stage, our goals were to habituate monkeys to interact with the new apparatus

voluntarily and to assess the performance of the real-time capuchin face-recognition model in the

field, both by triggering video recordings to generate training data for an expanded model and by

driving the automated stimulus–reward pipeline described above.

During our brief pilot habituation phase, we conducted six sessions with each group.

Throughout all sessions, 16 monkeys (see Table 1 & Table 2) interacted with the testing

apparatus, while an additional 14 individuals observed these interactions. All individuals who

engaged with the apparatus displayed exploratory behaviors such as touching, licking, sniffing,

and/or aggressing the touchscreen station. Of the 16 capuchins that interacted with the testing

stations, 10 learned to trigger the reward mechanism by touching the screen, and each of these

continued to make exploratory touches that yielded additional rewards. Eight capuchins

demonstrated behaviors consistent with having formed a full association between touching the

screen and receiving a reward (5 in Palmas group and 3 in Tenori group), with one additional

individual from Tenori possibly having formed this association (though we could not confirm as

rewards had run out). We defined a full association as being established when an individual 1)

directed most or all touches towards the screen area, and 2) showed anticipatory behaviors, such

as turning to face the dispenser opening before or during touching the screen, or reaching for it

immediately after a deliberate touch, prior to receiving a reward. For five of these individuals,

we also observed that the association was retained after a week of no interaction with the

apparatus. A brief narrative description of each individual's behavior across sessions for Palmas

group can be found in Table 1, and for Tenori group in Table 2.

Individual	Sex/Age class	Session 1	Session 2	Session 3	Session 4	Session 5	Session 6
PAPI	Male,	Exploratory behavior, no	N/A	**Full association**	**Full association**	N/A	**Full association**

		Alpha	screen touch		**formed**	**retained**		**retained**
PLUTO	Male, Adult	N/A	N/A	N/A	N/A	N/A	Exploratory touches, observes PIBE touching screen and steals food rewards, **full association formed**
PIBE	Male, Subadult	N/A	N/A	Exploratory touches, close observation of PAPI	**Full association formed**	N/A	**Full association retained**
PARIS	Male, Subadult	N/A	N/A	N/A	N/A	Exploratory behavior, no screen touches	Exploratory touches, **Full association formed**
PROBOSCIS	Male, Juv.	N/A	Exploratory behavior and screen touch.	Exploratory screen touches, displaced by PAPI and PIBE	Exploratory screen touches, observing PAPI and PIBE	**Full association formed**	N/A
POZA	Male, Juv.	N/A	N/A	Exploratory behavior, no screen touches	N/A	N/A	N/A

Table 1 — Participants from 'Palmas' Group in Habituation Sessions for Touchscreen Cognitive Testing: The first column lists the names of individuals who interacted directly with our testing apparatus during at least one of six sessions. The second column contains the sex and age class of each participating individual. The remaining columns contain a description of the behavior of each individual across sessions. If an individual did not arrive at testing platforms on a given session, they are marked as **N/A**. **Exploratory behavior**: behavior in which individuals approached and investigated the apparatus, without directing special attention to the screen. **Exploratory touches**: deliberate touching and interaction with the screen, without indication of a complete association of screen touching with reward dispensation. **Full association formed**: individual directs touches fully or predominantly at screen and anticipates reward dispensing after touching screen. **Full association retained**: an individual who has previously formed an association maintains that behavior immediately upon returning for a new session.

Individual	Sex/Age class	Session 1	Session 2	Session 3	Session 4	Session 5	Session 6
PEDRO	Male, Alpha	N/A	N/A	Exploratory behavior, accidental screen touches	Accidental screen touches, steals food rewards from TSUNAMI	Exploratory touches on screen.	N/A
TROMPUDO	Male, Adult	Multiple exploratory touches to screen	Exploratory touches on screen	**Full association formed**	N/A	**Full association retained**	**Full association retained**
TEMPISQUE	Male, Subadult	Exploratory Behavior	N/A	**Full association formed**	**Full association retained**	**Full association retained**	**Full association retained**
TSUNAMI	Male, Subadult	Exploratory behavior	N/A	Exploratory touches, deliberate	**Full association formed**	N/A	**Full association retained**
TILARAN	Male, Subadult	Multiple exploratory touches to screen	N/A	Exploratory touches, deliberate	No touches on screen	Exploratory touches on screen	N/A
TACO	Male, Subadult	N/A	N/A	Exploratory behavior	Exploratory touches on screen	N/A	Purposeful touches, but dispenser ran out of rewards.
TOBIAS	Male, Juv.	Exploratory behavior	N/A	N/A	N/A	N/A	N/A
TIQUICIA	Male, Juv.	Exploratory behavior, rapidly displaced	N/A	Exploratory behavior, attempts touching screen but is displaced	N/A	N/A	N/A
TAMARINDO	Female, Adult	N/A	N/A	Arrived at platform and approached apparatus, but was displaced before she could interact.	N/A	N/A	N/A
TURRIALBA	Female, Juv.	Exploratory behavior, rapidly displaced	N/A	N/A	N/A	N/A	N/A

Table 2 — Participants from 'Tenori' Group in Habituation Sessions for Touchscreen Cognitive Testing: The first column lists the names of individuals who interacted directly with our testing apparatus during at least one of six sessions. The second column contains the sex and age class of each participating individual. The remaining columns contain a description of the behavior of each individual across sessions. If an individual did not arrive at testing platforms on a given session, they are marked as **N/A**. **Exploratory behavior**: behavior in which individuals approached and investigated the apparatus, without directing special attention to the screen. **Exploratory touches**: deliberate touching and interaction with the screen, without indication of a complete association of screen touching with reward dispensation. **Full association formed**: individual directs touches fully or predominantly at screen, and anticipates reward dispensing after touching screen. **Full association retained**: individual that has previously formed association maintains that behavior immediately upon returning for a new session.

Taken together, the rates of voluntary participation and rapid habituation of multiple

individuals across both groups in the short timeframe in which they encountered our

experimental apparatus (2 weeks per group) suggest that this is a highly viable method to study

cognition in the wild in our model system — and easily adaptable to other primate species and

field sites. Furthermore, participating individuals rapidly learned an association between

touching the screen and receiving a food reward. They were further highly motivated to

participate whenever they were near the testing apparatus, suggesting that this method may

indeed be used to bring true-and-tested lab paradigms to the field. The motivation of individuals

to continue participating voluntarily across sessions is promising and suggests that with more

prolonged exposure to the apparatus, we'll be able to assemble a dataset comparable to captive

cognition studies.

3.2. Ongoing development of CapuchinAI v2.0 — Individual facial recognition and

personalized cognitive testing

The deployment of the CapuchinAI v.1.0 touchscreen apparatus succeeded not only in

habituating multiple individuals to using the touchscreen to earn a food reward, but also

employed our simplified Multiple Capuchins v.1 facial recognition model to generate an

abundance of video clips of monkeys interacting with the apparatus (**Figure 4**). Our facial

recognition script worked as intended, initiating recording via the connected camera when a

detection event occurred and stopping after 10 seconds without any faces detected. This resulted

in a library of footage of all 16 participants across both tested groups.

Figure 4 — **Habituation to testing apparatus and video collection via facial recognition model**. **Left:** PAPI (alpha male in
Palmas group) purposefully touches the screen with his left hand while placing his right hand on the food dispensing area and
looking down at it, displaying an association between touch and reward dispensing. PIBE (subadult male) observes closely.
Right: still image of PAPI taken from video recorded by CapuchinAI v.1.0's HD webcam. Blue bounding box indicates that the
facial recognition model is actively detecting a capuchin face within the designated area. Extracted frames such as this will be
used to train the next iteration of our facial recognition model.

To reduce the effort involved in manually extracting frames from these videos, we will

use the same facial recognition model to scan each frame and automatically extract all frames

that contain a face through a third Python script. These frames are currently being labeled to train

the next version of our facial recognition system, Multiple Capuchins v.2.0. While the initial

model achieved high accuracy in detecting and labeling six monkeys, the new model will be able

to distinguish all 16 monkeys that participated in our pilot deployment. This updated facial

recognition model will allow us to achieve our goal of acquiring individual-specific cognitive

data over time across multiple domains of cognition using touchscreen testing methods validated

in captive settings (e.g. Colares Leal et al., 2020; Fagot & Cook, 2006; Picanço & Barros, 2015).

Our efforts so far have demonstrated that it is possible to **a**) develop a high-quality AI model for

individual primate facial recognition, **b**) implement this model for real-time detection in wild

settings, and **c**) use the model to regulate the administration of stimuli and dispensing of rewards

for voluntarily participating wild primates.

In the next version of our pipeline, we plan to implement a feature that uses the updated facial

recognition model to both provide individualized testing <u>and</u> record videos of approachi*ng*

individuals. When the model confidently recognizes a capuchin it was trained on, it assigns a

specific cognitive test. If the model's confidence is low—meaning the individual is unfamiliar—

it assigns the baseline habituation stimulus and starts recording video. These recordings will be

used to periodically update the model, helping it recognize new monkeys as they interact with

the testing setup.

4. COMPARISON AND CRITIQUE

4.1 CapuchinAI provides an unprecedented level of experimental control in the wild

There is a classic trade-off in studies of primate cognition between ecological validity and

experimental control. Studies in the wild capture behavior in the fitness-relevant contexts in

which cognition evolves, but it has historically been difficult to address the mechanisms

underlying observed patterns, something that laboratory experiments do well. The method we

describe here takes sizeable steps toward bringing the best of the lab to the field, increasing our

control over cognitive data collection in several ways.

One major difficulty in studying cognition in the wild is that experiments have typically been

limited to one trial per session (e.g., Lopresti-Goodman et al., 2022; Thornton and Samson,

2012), which restricts the number of individuals that can be tested at one time and increases the

likelihood that a single individual will monopolize access (Benítez et al., 2022). Our method

directly addresses this limitation. By using machine vision, the apparatus can rapidly shift tests

from one identified individual to another and allow multiple individuals to participate in a single

session. Because the system does not rely on an experimenter to switch tasks based on

participant identity, but instead automates recognition of the participant, assignment of the

appropriate experiment, and reward delivery, multiple apparatuses can be installed in close

proximity without any one individual monopolizing testing opportunities. This design allows

researchers to collect data from multiple group members simultaneously and enables multiple

trials per individual per session, greatly accelerating the rate at which robust cognitive datasets

can be assembled in the wild.

A second advantage is that the apparatus only dispenses rewards when two conditions are

met: the facial detection model must identify a study subject and the assigned touchscreen task

must be completed. If an animal from a non-target species approaches and interacts with the

apparatus, no reward is dispensed because the model does not detect a valid face. This feature

ensures compliance with research permits and minimizes food loss to non-study organisms. For

example, at our field site coatis (*Nasua narica*) occasionally approach the testing platforms, but

under this design they cannot obtain food rewards and quickly lose interest. Although we cannot

fully control which individuals choose to participate (see Limitations), we can actively exclude

species and individuals from whom we do not wish to collect data.

A third key advantage is that the method is adaptable to multiple species and field sites. If a

research group already has a large database of images or videos of study subjects, a site-specific

facial recognition model can be trained immediately. Even without such a database, the more

general model we trained using the Ultralytics YOLOv5 architecture can serve as a starting

point. Because this model was trained with a looser concept of a capuchin face, it generalizes to

other primate species and, in our tests, detected human, marmoset, and macaque faces. Used as

we describe here, this general model can be deployed to assemble a video database that can then

be used to train a species- and site-specific model, as we did for the second iteration of our facial

recognition model (see Section 3.2). The physical testing apparatus is similarly exportable. It is

relatively lightweight (about 35 lbs; 15.9 kg) and can be carried by a single person. All electronic

components were selected for low cost and ease of replacement, and the two components with

which subjects directly interact (the infrared touchscreen overlay and camera) were chosen for

durability and affordability. The internal design is modular, so failure of one component does not

require replacement of the entire system.

Taken together, these features position our method at the vanguard of efforts to understand

cognition in ecologically relevant contexts while retaining a high degree of experimental control.

They substantially reduce the gap between laboratory experimentation and field studies and

move us closer to a long-sought goal: studying primate cognition in the wild with the rigor and

precision typically reserved for the lab.

4.2 CapuchinAI: a versatile system for studying within- and between-individual variation

in cognition in the wild

527   Touchscreen methods have emerged in recent years as highly versatile and robust tools

for testing primate cognition (e.g., Martin et al., 2022). They allow researchers to collect

standardized data on a wide array of cognitive traits within the same experimental framework,

facilitating direct comparisons across tasks, individuals, and species. Bringing such methods to

the field makes it possible to collect systematic data across various cognitive domains, rather

than testing a single aspect of cognition in isolation, and greatly expands the range of

experiments that can be implemented within a single study population. Traditionally, each new

cognitive experiment has required habituation to a different apparatus. In contrast, the

programmable nature of touchscreen experiments means that subjects need only habituate to a

single smart testing station, which can then present a modular battery of lab-validated tasks

targeting domains such as learning, memory, inhibitory control, flexibility, and social decision

making.

Our goal is for CapuchinAI to serve as a flexible, long-term testing platform where tasks

can be added, removed, or reordered in software without altering the hardware, and contingency

rules can be used to scaffold individuals through tests of increasing difficulty at their own pace.

The facial recognition software allows each subject to follow a personalized progression through

the battery, automatically delivering the next task once predefined performance criteria are met.

Because the system can run continuously, it supports longitudinal cognitive testing in the wild

and lays the groundwork for comparative, population-level, and individual-level studies of

cognitive variation and its ecological and fitness correlates.

This method can make a significant advance in the ability to measure inter-individual

variation in cognition in the wild. Because cognition is context-dependent and developmentally

malleable, deploying lab-based psychometric tools in natural settings will, for the first time,

allow us to study cognitive variation in the fitness-relevant environments in which animal minds

evolved (Horn et al., 2022). This, in turn, will help us address several central questions in

primate cognition, including the heritability of cognitive traits (Hopkins et al., 2014), whether

variation reflects a general intelligence "g" factor (Beran and Hopkins, 2018; Matzel and Sauce,

2017) or a more modular cognitive architecture (Amici et al., 2012), and which naturally varying

environmental factors shape primate cognitive development. Because CapuchinAI is designed to

track performance over time at the individual level, it allows us to view inter-individual variation

not as a single snapshot, but as trajectories of cognitive change across days, months, and years.

4.3. Potential Limitations

The primary limitation of this approach is that it is easier to implement at some field sites

and with some species than others. Our method is most readily adapted where primates are

already habituated to specific areas used for cognitive testing. This pre-habituation, as with

capuchins at Taboga and their familiarity with testing platforms, increases the likelihood that

individuals will approach and interact with touchscreen boxes. The system also works best with

species that show relatively low neophobia and high levels of self-motivated exploration, which

again fits capuchins well. With an appropriate power supply, however, the apparatus can be left

in place for extended periods without direct researcher supervision. Installing multiple units

across the range of study groups or populations can promote passive habituation and allow

individuals to engage with the system at their own pace.

A second limitation concerns participation and sampling. Because participation is entirely

voluntary, we cannot guarantee a minimum number of trials per session or per individual, in

contrast to many laboratory paradigms that use fixed trial numbers. We can set an upper limit on

trials per individual, which helps prevent a small number of subjects from monopolizing

rewards, but this does not solve the problem of low or uneven participation. In our pilot

deployment, adult and subadult males were the most frequent users of the apparatus, although an

adult female and a juvenile female also approached and investigated it before being displaced.

Such patterns may introduce sampling biases. Running multiple stations simultaneously, in

different parts of the home range, may help increase access and broaden participation across

age–sex classes.

A final limitation relates to the use of food rewards. At Taboga, we provisioned

capuchins with a food item they already encounter during natural foraging, provided quantities

that should not alter foraging patterns (daily routes and time at specific locations have not

changed in our longitudinal GPS data), and ensured that animals never observed researchers

handling the rewards. Even with these precautions, some sites or species will not permit any

level of provisioning. In those contexts, adapting our method would require tasks that are

intrinsically rewarding or otherwise sufficiently engaging to motivate participation without food

incentives.

ACKNOWLEDGEMENTS: We thank our colleagues and collaborators for their insightful

discussions that helped shape the development of this project. We are especially grateful to the

members of the Social Cognition and Primate Behavior Lab at Emory University and the

Capuchinos de Taboga project for their feedback and intellectual contributions. We would

further like to thank the members of the Collective Cognition Lab at the University of Rochester,

specifically Professor Dora Biro and graduate students Oviya Mohan and Rithwik Cherian, for

their valuable suggestions and guidance. We also thank the editors and anonymous reviewers for

their thoughtful comments and suggestions.

ETHICS STATEMENT: This study was reviewed and approved by the relevant oversight

committees, including the Institutional Animal Care and Use Committee (IACUC) at Emory

University, and Costa Rica's Sistema Nacional de Areas de Conservación (SINAC). Research

was conducted according to protocols approved by IACUC, SINAC, Costa Rica's National

Technical University (UTN), granting agencies, and adhering to Costa Rican law. This research

adhered to the American Society of Primatologists' Principles for the Ethical Treatment of Non-

human Primates.

References

Amici, F., Barney, B., Johnson, V. E., Call, J., & Aureli, F. (2012). A Modular Mind? A Test

Using Individual Data from Seven Primate Species. *PLOS ONE*, *7*(12), e51918.

https://doi.org/10.1371/journal.pone.0051918

Amici, F., Caicoya, A. L., Majolo, B., & Widdig, A. (2020). Innovation in wild Barbary

macaques (Macaca sylvanus). Scientific Reports, 10(1), 4597.

Barrett, B. J., Monteza-Moreno, C. M., Dogandžić, T., Zwyns, N., Ibáñez, A., & Crofoot, M. C.

(2018). Habitual stone-tool-aided extractive foraging in white-faced capuchins, Cebus

capucinus. *Royal Society Open Science*, *5*(8), 181002. https://doi.org/10.1098/rsos.181002

Benítez, M. E., Painter, M. C., Guisneuf, N., & Bergman, T. J. (2022). Answering big questions

with small data: The use of field experiments in primate cognition. *Current Opinion in*

Behavioral Sciences, *46*, 101141. https://doi.org/10.1016/j.cobeha.2022.101141

Beran, M. J., & Hopkins, W. D. (2018). Self-Control in Chimpanzees Relates to General

Intelligence. *Current Biology*, *28*(4), 574-579.e3.

https://doi.org/10.1016/j.cub.2017.12.043

Brosnan, S. F., Freeman, C., & De Waal, F. B. M. (2006). Partner's behavior, not reward

distribution, determines success in an unequal cooperative task in capuchin monkeys.

American Journal of Primatology, *68*(7), 713–724. https://doi.org/10.1002/ajp.20261

Brosnan, S. F. (2011). What Do Capuchin Monkeys Tell Us about Cooperation? In D. R. Forsyth

& C. L. Hoyt (Eds.), *For the Greater Good of All: Perspectives on Individualism, Society,*

and Leadership (pp. 11–27). Palgrave Macmillan US.

https://doi.org/10.1057/9780230116269_2

Butler J.L., Kennerley S.W. Mymou: A low-cost, wireless touchscreen system for automated

training of nonhuman primates. Behav. Res. Methods. 2019;51:2559–2572. doi:

10.3758/s13428-018-1109-5

Byrne, R. W. (2000). Evolution of Primate Cognition. *Cognitive Science*, *24*(3), 543–570.

https://doi.org/10.1207/s15516709cog2403_8

Canteloup, C., Hoppitt, W., & van de Waal, E. (2020). Wild primates copy higher-ranked

individuals in a social transmission experiment. *Nature Communications*, *11*(1), 459.

https://doi.org/10.1038/s41467-019-14209-8

Cauchoix, M., Chow, P. K. Y., van Horik, J. O., Atance, C. M., Barbeau, E. J., Barragan-Jason,

G., Bize, P., Boussard, A., Buechel, S. D., Cabirol, A., Cauchard, L., Claidière, N.,

Dalesman, S., Devaud, J. M., Didic, M., Doligez, B., Fagot, J., Fichtel, C., Henke-von der

Malsburg, J., … Morand-Ferron, J. (2018). The repeatability of cognitive performance: A

meta-analysis. *Philosophical Transactions of the Royal Society B: Biological Sciences*,

373(1756), 20170281. https://doi.org/10.1098/rstb.2017.0281

Claidière, N., Whiten, A., Mareno, M. C., Messer, E. J. E., Brosnan, S. F., Hopper, L. M.,

Lambeth, S. P., Schapiro, S. J., & McGuigan, N. (2015). Selective and contagious prosocial

resource donation in capuchin monkeys, chimpanzees and humans. *Scientific Reports*, *5*(1),

7631. https://doi.org/10.1038/srep07631

Colares Leal, T. R., de Faria Brino, A. L., de Almeida Costa, L. A., de Faria Galvão, O., &

McIlvane, W. J. (2020). Acquisition and maintenance of delayed matching-to-sample in

tufted capuchin monkeys. *Journal of the Experimental Analysis of Behavior*, *113*(3),

549–564. https://doi.org/10.1002/jeab.599

Crouse, D., Jacobs, R. L., Richardson, Z., Klum, S., Jain, A., Baden, A. L., & Tecot, S. R.

(2017). LemurFaceID: A face recognition system to facilitate individual identification of

lemurs. *BMC Zoology*, *2*(1), 2. https://doi.org/10.1186/s40850-016-0011-9

Darwin, C. (1859). Origin of the Species. In *British Politics and the Environment in the Long*

Nineteenth Century. Routledge.

Dukas, R. (2004). Evolutionary Biology of Animal Cognition. *Annual Review of Ecology,*

Evolution, and Systematics, *35*(Volume 35, 2004), 347–374.

https://doi.org/10.1146/annurev.ecolsys.35.112202.130152

Dunbar, R. I. M., & Shultz, S. (2007). Understanding primate brain evolution. *Philosophical*

Transactions of the Royal Society B: Biological Sciences.

https://doi.org/10.1098/rstb.2006.2001

Dwyer, B., Nelson, J., Hansen, T., et al. (2025). Roboflow (Version 1.0) [Software]. Available

from https://roboflow.com. Computer vision.

Fagot, J., & Cook, R. G. (2006). Evidence for large long-term memory capacities in baboons and

pigeons and its implications for learning and the evolution of cognition. *Proceedings of*

the National Academy of Sciences, *103*(46), 17564–17567.

https://doi.org/10.1073/pnas.0605184103

Friard, O., & Gamba, M. (2016). BORIS: A free, versatile open-source event-logging software

for video/audio coding and live observations. *Methods in Ecology and Evolution*, *7*(11),

1325–1330. https://doi.org/10.1111/2041-210X.12584

Glazko, G. V., & Nei, M. (2003). Estimation of Divergence Times for Major Lineages of

Primate Species. *Molecular Biology and Evolution*, *20*(3), 424–434.

https://doi.org/10.1093/molbev/msg050

Grabowski, M., Kopperud, B. T., Tsuboi, M., & Hansen, T. F. (2023). Both Diet and Sociality

Affect Primate Brain-Size Evolution. *Systematic Biology*, *72*(2), 404–418.

https://doi.org/10.1093/sysbio/syac075

Guo, S., Xu, P., Miao, Q., Shao, G., Chapman, C. A., Chen, X., He, G., Fang, D., Zhang, H.,

Sun, Y., Shi, Z., & Li, B. (2020). Automatic Identification of Individual Primates with Deep

Learning Techniques. *iScience*, *23*(8), 101412. https://doi.org/10.1016/j.isci.2020.101412

679
Harrison, R. A., Mohr, T., & van de Waal, E. (2023). Lab cognition going wild: Implementing a

new portable touchscreen system in vervet monkeys. *Journal of Animal Ecology*, *92*(8),

1545–1559. https://doi.org/10.1111/1365-2656.13857

Hopkins, W. D., Russell, J. L., & Schaeffer, J. (2014). Chimpanzee Intelligence Is Heritable.

Current Biology, *24*(14), 1649–1652. https://doi.org/10.1016/j.cub.2014.05.076

Horn, L., Cimarelli, G., Boucherie, P. H., Šlipogor, V., & Bugnyar, T. (2022). Beyond the

dichotomy between field and lab—The importance of studying cognition in context.

Current Opinion in Behavioral Sciences, *46*, 101172.

https://doi.org/10.1016/j.cobeha.2022.101172

Huebner, F., Fichtel, C., & Kappeler, P. M. (2018). Linking cognition with fitness in a wild

primate: Fitness correlates of problem-solving performance and spatial learning ability.

Philosophical Transactions of the Royal Society B: Biological Sciences, *373*(1756),

20170295. https://doi.org/10.1098/rstb.2017.0295

LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. *Nature*, *521*(7553), 436–444.

https://doi.org/10.1038/nature14539

Leigh, S. r. (2004). Brain growth, life history, and cognition in primate and human evolution.

American Journal of Primatology, *62*(3), 139–164. https://doi.org/10.1002/ajp.20012

Lopresti-Goodman, S. M., & Villatoro-Sorto, B. (2023). The Benefits and Challenges of

Conducting Primate Research in Different Settings. *Animals*, *13*(1), 133.

https://doi.org/10.3390/ani13010133

Mathe, S. E., Kondaveeti, H. K., Vappangi, S., Vanambathina, S. D., & Kumaravelu, N. K.

(2024). A comprehensive review on applications of Raspberry Pi. *Computer Science*

Review, *52*, 100636. https://doi.org/10.1016/j.cosrev.2024.100636

Matzel, L. D., & Sauce, B. (2017). Individual differences: Case studies of rodent and primate

intelligence. *Journal of Experimental Psychology: Animal Learning and Cognition*,

43(4), 325–340. https://doi.org/10.1037/xan0000152

Martin, C. F., Muramatsu, A., & Matsuzawa, T. (2022). Apex and ApeTouch: Development of a

Portable Touchscreen System and Software for Primates at Zoos. *Animals*, *12*(13), 1660.

https://doi.org/10.3390/ani12131660

McGugan, W. (Ed.). (2007). Introducing Pygame. In *Beginning Game Development with Python*

and Pygame: From Novice to Professional (pp. 41–66). Apress.

https://doi.org/10.1007/978-1-4302-0325-4_3

Molesti, S., & Majolo, B. (2016). Cooperation in wild Barbary macaques: Factors affecting free

partner choice. *Animal Cognition*, *19*(1), 133–146. https://doi.org/10.1007/s10071-015-

0919-4

Norouzzadeh, M. S., Nguyen, A., Kosmala, M., Swanson, A., Palmer, M. S., Packer, C., &

Clune, J. (2018). Automatically identifying, counting, and describing wild animals in

camera-trap images with deep learning. *Proceedings of the National Academy of Sciences*,

115(25), E5716–E5725. https://doi.org/10.1073/pnas.1719367115

Parrish, A., Brosnan, S., & Beran, M. (2015). Capuchin Monkeys Alternate Play and Reward in a

Dual Computerized Task. *Animal Behavior and Cognition*, *2*(4), 334–347.

https://doi.org/10.12966/abc.11.03.2015

Perry, S. (1996). Intergroup encounters in wild white-faced capuchins (Cebus capucinus).

International Journal of Primatology, *17*(3), 309–330. https://doi.org/10.1007/BF02736624

Perry, S. (2020). Behavioural variation and learning across the lifespan in wild white-faced

capuchin monkeys. *Philosophical Transactions of the Royal Society B: Biological*

Sciences, *375*(1803), 20190494. https://doi.org/10.1098/rstb.2019.0494

Picanço, C. R. F., & Barros, R. S. (2015). Symmetry Evaluation by Comparing Acquisition of

Conditional Relations in Successive (Go/No-Go) Matching-to-Sample Training. *The*

Psychological Record, *65*(1), 131–139. https://doi.org/10.1007/s40732-014-0096-x

Richardson W.K., Washburn D.A., Hopkins W.D., Savage-Rumbaugh E.S., Rumbaugh D.M.
The NASA/LRC computerized test system. Behav. Res. Methods Instrum. Comput.
1990;22:127–131. doi: 10.3758/BF03203132

733
Rilling, J. K., & Insel, T. R. (1999). The primate neocortex in comparative perspective using

magnetic resonance imaging. *Journal of Human Evolution*, *37*(2), 191–223.

https://doi.org/10.1006/jhev.1999.0313

Roth, G., & Dicke, U. (2012). Chapter 20—Evolution of the brain and intelligence in primates.

In M. A. Hofman & D. Falk (Eds.), *Progress in Brain Research* (Vol. 195, pp. 413–430).

Elsevier. https://doi.org/10.1016/B978-0-444-53860-4.00020-9

Scarry, C. J. (2017). Male resource defence during intergroup aggression among tufted capuchin

monkeys. *Animal Behaviour*, *123*, 169–178. https://doi.org/10.1016/j.anbehav.2016.10.015

Schofield, D., Nagrani, A., Zisserman, A., Hayashi, M., Matsuzawa, T., Biro, D., & Carvalho, S.

(2019). Chimpanzee face recognition from videos in the wild using deep learning.

Science Advances, *5*(9), eaaw0736. https://doi.org/10.1126/sciadv.aaw0736

Schofield, D. P., Albery, G. F., Firth, J. A., Mielke, A., Hayashi, M., Matsuzawa, T., Biro, D., &

Carvalho, S. (2023). Automated face recognition using deep neural networks produces

robust primate social networks and sociality measures. *Methods in Ecology and*

Evolution, *14*(8), 1937–1951. https://doi.org/10.1111/2041-210X.14181

Simmons, S. M. V., & Brosnan, S. F. (2023). Humans' (Homo sapiens), capuchin monkeys'

(Sapajus [Cebus] apella), and rhesus macaques' (Macaca mulatta) size judgments shift

when stimuli change in frequency. *Journal of Comparative Psychology (Washington,*

D.C.: 1983). https://doi.org/10.1037/com0000365

Shettleworth, S. J. (2001). Animal cognition and animal behaviour. Animal Behaviour, 61(2),

277–286. https://doi.org/10.1006/anbe.2000.1606

Sosnowski, M., & Brosnan, S. (2025). Familiarity, Active Memory And Pressure During A

Delayed Matching-To-Sample Task In Tufted Capuchin Monkeys (Sapajus [Cebus]

Apella). *Animal Behavior and Cognition*, *12*(1), 32–44.

https://doi.org/10.26451/abc.12.01.02.2025

Tabak, M. A., Norouzzadeh, M. S., Wolfson, D. W., Sweeney, S. J., Vercauteren, K. C., Snow,

N. P., Halseth, J. M., Di Salvo, P. A., Lewis, J. S., White, M. D., Teton, B., Beasley, J. C.,

Schlichting, P. E., Boughton, R. K., Wight, B., Newkirk, E. S., Ivan, J. S., Odell, E. A.,

Brook, R. K., … Miller, R. S. (2019). Machine learning to classify animal species in camera

trap images: Applications in ecology. *Methods in Ecology and Evolution*, *10*(4), 585–590.

https://doi.org/10.1111/2041-210X.13120

Thornton, A., & Samson, J. (2012). Innovative problem solving in wild meerkats. *Animal*

Behaviour, *83*(6), 1459–1468. https://doi.org/10.1016/j.anbehav.2012.03.018

Tinsley Johnson, E., Benítez, M. E., Fuentes, A., McLean, C. R., Norford, A. B., Ordoñez, J. C.,

Beehner, J. C., & Bergman, T. J. (2020). High density of white-faced capuchins (*Cebus*

capucinus) and habitat quality in the Taboga Forest of Costa Rica. *American Journal of*

Primatology, *82*(2), e23096. https://doi.org/10.1002/ajp.23096

Varghese, R., & M., S. (2024). YOLOv8: A Novel Object Detection Algorithm with Enhanced

Performance and Robustness. *2024 International Conference on Advances in Data*

Engineering and Intelligent Computing Systems (ADICS), 1–6.

https://doi.org/10.1109/ADICS58448.2024.10553619

van de Waal, E., Renevey, N., Favre, C. M., & Bshary, R. (2010). Selective attention to

philopatric models causes directed social learning in wild vervet monkeys. Proceedings.

Biological Sciences, 277(1691), 2105–2111. https://doi.org/10.1098/rspb.2009.2260

Wang, M., & Deng, W. (2021). Deep face recognition: A survey. *Neurocomputing*, *429*, 215–

244. https://doi.org/10.1016/j.neucom.2020.10.081

Wang, C.-Y., Bochkovskiy, A., & Liao, H.-Y. M. (2023). YOLOv7: Trainable Bag-of-Freebies

Sets New State-of-the-Art for Real-Time Object Detectors. *2023 IEEE/CVF Conference on*

Computer Vision and Pattern Recognition (CVPR), 7464–7475.

https://doi.org/10.1109/CVPR52729.2023.00721

Witham, C. L. (2018). Automated face recognition of rhesus macaques. *Journal of Neuroscience*

Methods, *300*, 157–165. https://doi.org/10.1016/j.jneumeth.2017.07.020

Zhang, J.-J., Gao, Y., Zhang, B.-L., & Wu, D.-D. (2025). A deep learning lightweight model for

real-time captive macaque facial recognition based on an improved YOLOX model.

Zoological Research, *46*(2), 339–354. https://doi.org/10.24272/j.issn.2095-8137.2024.296

789
790