Title: Hierarchical and Context-Dependent Encoding of Actions in Human Posterior Parietal
and Motor Cortex

Authors: V. Bougou[1], J. Gamez[1], E. Rosario[3], C. Liu[3,4,5], K. Pejsa[1], A. Bari[4], R. A. Andersen[1,2]

Affiliations:

[1]*Division of Biology and Biological Engineering, California Institute of Technology, Pasadena, CA*
[2]*T&C Chen Brain-machine Interface Center, California Institute of Technology, Pasadena, CA*
[3]*Casa Colina Hospital and Center for Healthcare, Pomona, CA*
[4]*Department of Neurological Surgery, Keck School of Medicine of USC, Neurological Surgery, Los Angeles, CA*
[5]*Department of Neurological Surgery, University of California, Los Angeles, CA*

Abstract:

Action understanding requires internal models that link vision to motor goals. In monkeys,
mirror neurons demonstrate motor resonance during observation, but single-unit evidence in
humans is limited, leaving open whether such representations rely solely on motor resonance.
We recorded neural activity from motor cortex (MC) and superior parietal lobule (SPL) in two
tetraplegic participants implanted with Utah arrays while they intended or observed hand
actions. MC strongly encoded intention but showed only weak, feature-specific overlap during
observation, evident primarily at the population level. SPL, in contrast, supported shared
models across intended movement and observation formats at both single-unit and population
levels. In variants with incongruent instructed and observed actions, SPL encoded observed
actions only when behaviorally relevant, whereas MC remained intention-dominant. Our results
identify a context-dependent gating mechanism in SPL and suggest a hierarchical organization in
which MC maintains intention-specific codes while SPL flexibly links observed input with
internal goals to support action understanding.

Introduction:

The ability to interpret the actions of others, to identify what is being done, by whom, and in what context, is a fundamental feature of intelligent behavior. It relies on internal representations that can flexibly map visual input onto motor knowledge, enabling the brain to simulate, predict, and interpret observed movements. For decades, these processes have been framed through the lens of mirror mechanisms: the idea that shared neural codes support both action execution and observation[1–3]. Yet the scope, structure, and cortical distribution of these representations remain deeply debated[4]. Is action understanding underpinned by motor-constrained reactivations of one's own movements, or by more abstract, generalizable codes that transcend the observer's motor repertoire? And how are these representations organized across regions traditionally implicated in sensory-motor control versus those thought to support higher-order cognitive functions?

Mirror neurons, first identified in macaques, respond during both execution and observation, supporting the motor simulation theory that action perception relies on covert motor reactivation [1,2,5–8]. While influential, this framework has been refined by evidence that mirror responses are shaped by prior experience and task context (contextual flexibility), that individual units often encode only subsets of action features (partial tuning), and that visuomotor congruence emerges more robustly at the ensemble rather than single-cell level (population encoding). [9]. These findings point to more complex and heterogeneous mechanisms than strict motor mirroring can explain. Converging theoretical work suggests that cognitive flexibility emerges from internal models that are compositional, building complex structures from separable and recombinable elements, and generalizable capturing abstract structure that extends across contexts and tasks to support adaptive behavior.[10–12] Yet in humans, direct single-neuron evidence remains scarce, and the broader principles underlying action representations, particularly their flexibility and generalizability, are still not well defined.

These theoretical shifts, from rigid mirroring to flexible, predictive, and context-sensitive encoding, highlight the need to reassess how action representations are structured in the human brain. Action observation provides a unique lens into this flexibility. Unlike execution, it allows testing whether neural populations encode actions disentangled from the specific motor commands or output normally coupled to them This is particularly relevant in higher-order regions such as the parietal cortex, where mixed selectivity is prevalent [13–16]and encoding may reflect abstract and goal-directed representations rather than motor-specific plans[17–19]. Assessing such generalizability requires moving beyond single-neuron selectivity towards the structure of population codes. Recent advances in neural manifold analysis[20] and representational geometry [21] (the structure of neural population activity, often captured as trajectories) have shown that population activity can reveal compositional and generalizable

subspaces, but these approaches have rarely been applied to investigate action
representations[22]. To date, only a handful of studies have examined action observation
responses at the single-neuron level in humans[22–24], and none have systematically characterized
the geometry or cross-format alignment, i.e. generalization, of action representations in core
regions of the motor system.

To investigate how intended and observed actions are represented in the human brain, we
recorded single- and multi-unit activity together with local field potentials from motor and
posterior parietal cortices in two tetraplegic participants implanted with Utah arrays. Using a
factorial design that manipulated hand, action type, and movement direction, we compared
neural representations across intention and observation. Our analyses revealed a gradient of
representational overlap, with posterior parietal cortex encoding action identity in a format-
general manner across intention and observation, whereas motor cortex representations were
predominantly intention-specific, with observation responses reflecting only a latent projection
of the intention-related structure. To test whether this overlap was modulated by behavioral
relevance, we introduced a dissociation task that decoupled instructed and observed actions.
This manipulation demonstrated that parietal representations of observed actions emerged
only when those actions were behaviorally relevant, consistent with a gating mechanism driven
by task demands, whereas motor cortex consistently reflected only the instructed movement.
Together, these findings provide direct human electrophysiological evidence that action
representations extend beyond motor mirroring, supporting a hierarchical and context-
dependent coding framework in the frontoparietal system.

Results:

We recorded single- and multi-unit activity as well as local field potentials (LFPs) from two
tetraplegic participants (JJ, RD) implanted with Utah arrays targeting motor and posterior
parietal cortices. Participant JJ had 96-channel arrays in the hand knob area of the primary
motor cortex (MC) and the superior parietal lobule (SPL). Participant RD had 64-channel arrays
in two regions of the hand knob in motor cortex, one positioned more medially (MCM) and one
more laterally (MCL), as well as an array in the superior parietal lobule (SPL). An additional array
targeting the supramarginal gyrus (SMG) in RD was excluded from all analyses, as it did not yield
reliable task-related responses across sessions or experimental variations.

To investigate action encoding across intention and observation, we designed a task with a fully
crossed 2 (hand: left/right) × 3 (action: lift, slide, rotate) × 2 (direction: left/right) structure (Fig.
1A). Direction refers to an abstract left/right factor, defined per action type (see Methods).In
the intention condition, participants intended the cued action; in observation, they passively
viewed a video of the same action. This structure allowed independent assessment of effector,
action type, and direction encoding across formats.

We recorded 421 units in MC and 326 in SPL from JJ, and 441 (MCM), 479 (MCL), and 532 (SPL)
units from RD during the main task (Table S1). In RD, two further dissociation experiments
yielded an additional 885 (MCM), 794 (MCL), and 1020 (SPL) units (Tables S2–S3), which were
analyzed separately. Implant locations are shown in Figure 1B. Based on the quality factor
classification (see Methods), 81 units in RD-MCM, 109 in RD-MCL, and 92 in RD-SPL were well
isolated (quality 1–2), with the remainder classified as multiunit activity (quality 3–4). For JJ,
whose arrays had been implanted for an extended period of time, the majority of signals were
classified as multiunit activity, yielding only 5 well-isolated MC units and 4 well-isolated SPL
units. For the dissociation tasks, the numbers of well-isolated units were 134 in RD-MCM, 107 in
RD-MCL, and 254 in RD-SPL.

Eye-tracking confirmed stable fixation across all conditions. Figure S1 shows the two-
dimensional distributions of gaze positions (in degrees of visual angle) aggregated across all
trials. Across both participants and formats, gaze remained consistently centered, confirming
compliance with fixation instructions throughout the experiment.

Distinct tuning profiles in parietal and motor cortices across action formats

We first examined condition-specific responses at the single-unit level across regions. Figure 2A
shows example units from RD: one in SPL tuned to action "lift", and one in MCM tuned to right-
hand actions. Both showed consistent tuning across formats. The SPL unit exhibited peak
responses for lift at 2.1 s (159 spikes/s) during intention and at 2.0 s (82.5 spikes/s) during
observation. The MCM unit showed sustained right-hand selectivity, peaking at 2.0 s (83.2
spikes/s) during intention and 1.7 s (48.5 spikes/s) during observation. However, consistent
cross-format tuning was not ubiquitous; many neurons showed divergent selectivity across
formats.

To compare temporal dynamics, we computed response latencies per condition and unit,
defined as the center of the first of three consecutive bins (100 ms each) significantly above
baseline. Figure 2B shows latency distributions across regions and formats. During intention, SPL
responses preceded those in motor cortex (median latencies: JJ/SPL: 1.2 s; RD/SPL: 1.4 s;
MC/MCM/MCL: 1.9–2.1 s; ANOVA p < 0.001). With the effector cue at 0 s, the action and
direction cue at 0.5 s, and the go cue at 1.5 s, these latencies indicate that SPL activity emerged
~700–900 ms after the action cue and ~100–300 ms before the go cue, whereas MC responses
appeared ~400–600 ms after the go cue. During observation, SPL also preceded MC in JJ (1.1 vs.
1.5 s, p = 0.02), but no significant timing differences were found in RD. These results point to a
leading role of SPL during action intention, with less consistent dynamics during observation.

We quantified the number of units responsive to at least one condition in each format and brain
area. A unit was considered responsive if it showed three consecutive time bins significantly
above baseline (see Methods). Figure 2C shows the distribution of responsive units per
condition, separately for intention (top row, green) and observation (bottom row, blue). In
motor cortex, substantially more units responded during intention than observation: JJ/MC: 220
vs. 50; RD/MCM: 215 vs. 40; RD/MCL: 172 vs. 39. Notably, in JJ's MC, responses were strongest
for right-hand rotation, whereas MCM and MCL exhibited broader tuning, though with a right-
hand bias. In SPL, responses were widespread across both formats. During intention, 139 (JJ)
and 256 (RD) units were responsive; during observation, 88(JJ) and 137(RD). This exceeds the
number observed in any motor cortex array, indicating that SPL supports robust responsiveness
across formats, whereas motor cortex is primarily active during intention.

To assess tuning to specific task features, we performed a three-way ANOVA on binned firing
rates with action type, effector (hand), and direction as factors (Fig. 2D). In motor cortex during
intention, tuning patterns differed by participant. In JJ's MC, action tuning dominated (peak: 144
units at 2.75 s), while effector tuning was minimal (14 units). In RD, MCM showed strong
effector tuning (118 units at 2.25 s), with weaker action (28) and interaction tuning (e.g.,
action×hand: 18). MCL showed tuning for both hand (45) and action (33), with hand remaining
dominant. SPL exhibited a distinct profile. In both participants, action was the most commonly
tuned feature during intention (JJ: 27; RD: 58), followed by effector (JJ: 16; RD: 37). This
structure was largely preserved during observation (JJ: 16; RD: 21 action-tuned units), whereas
observation-related tuning in motor cortex was minimal (≤5 units for all features in RD; 5 action-
tuned units in JJ's MC). Across regions, effector tuning tended to emerge earlier than action,
particularly during intention suggesting a sequential encoding of task parameters. For example,
hand tuning peaked around 2.25 s in MCM and MCL, while action peaked at 2.75 s. SPL showed
a similar temporal shift. Interaction terms were rarely significant, suggesting that most units
were modulated by single task features. Overall, motor cortex was dominated by effector or
action tuning during intention, while SPL consistently encoded action type in both formats.

We next quantified format-specific responsiveness by counting units active for at least one
condition during intention only, observation only, or both (Fig. 2E, top row). In motor cortex,
most units were responsive exclusively during intention. In JJ's MC, 63 units were intention-only,
compared to 20 observation-only and 7 responsive in both formats. Similar distributions were
found in RD: MCM (48 intention-only, 34 observation-only, 18 both) and MCL (87, 25, and 16,
respectively). In contrast, SPL showed a higher proportion of units responsive across both
formats. In total, 76 units in JJ and 61 in RD responded in both formats, nearly matching or

exceeding the format-specific counts. This suggests that SPL encodes actions in a more format-
invariant manner than motor cortex.

To characterize tuning structure and generalization, we applied a linear model framework
adapted from Chivukula et al. 2025 [22]. For each unit, we fit a full factorial model using action,
hand, and direction (including all interactions), separately for intention and observation. Units
were assigned to the best-fitting model via stratified 5-fold cross-validation. Shared tuning
categories (consistent tuning to a given feature across both intention and observation formats)
included action, hand, direction, mixed (e.g., action ×hand), or invariant (consistent across all 12
conditions). Units were labeled idiosyncratic if they were tuned in both formats but with
unrelated profiles, single-format if tuned in only one, and unselective if no model exceeded $R^2 >$
0.01 or reached significance after FDR correction. Figure 2E (bottom) shows the distribution of
model classifications across regions. In RD, MCM and MCL were dominated by single-format
units (83 and 64), followed by shared hand (43 and 35), consistent with effector-dominant
tuning (Fig. 2D). JJ's MC showed a strikingly different pattern: despite few observation-
responsive units (Fig. 2E, top), the majority were best fit by a shared action model (112), with
only 34 classified as single-format. SPL in both participants exhibited consistent format-general
structure. Shared action was the most frequent model (JJ: 38; RD: 54), followed by shared hand
(21; 44), invariant (17; 20), and mixed models (13; 22). Single-format tuning was also present,
particularly in RD (42 units). These findings further support the view that SPL contains a
population of units that encode action features in a consistent and generalizable format across
observation and intention.

To ensure that collapsing leftward and rightward variants of each action did not inflate shared-
action fits, we repeated the model comparison using a 6-level action factor (action × direction;
Fig. S2). The overall distribution of model fits remained consistent. Across areas, the 3-action
model continued to dominate, particularly in PPC (JJ SPL: 52 action(3) vs 25 action(6) units; RD
SPL: 29 action(3) vs 12 action(6)). In motor cortex, a similar profile was observed (JJ MC: 96
action(3) vs 28 action(6); RD MCM: 8 action(3) vs 6 action(6), RD MCL: 9 action(3) vs 5
action(6)). Thus, redefining actions as direction-specific variants revealed only a minor subset of
additional tuned units, confirming that the dominance of action(3) tuning (particularly in PPC)
reflects genuine encoding of action identity rather than conflation of directional movements.

At the single unit level SPL exhibited robust, format-general tuning across participants. In both JJ
and RD, many units responded in both formats (76 and 61, respectively; Fig. 2C–E), with action
tuning aligned in time and shared action emerging as the most frequent model. In contrast,
motor cortex responses were predominantly intention specific. JJ's MC showed strong action
tuning, and RD's MCM and MCL were dominated by effector tuning, but observation-related

responses were sparse. Most MC units were classified as single-format, except in JJ, where
shared action tuning was prevalent despite limited observation responsiveness. This apparent
discrepancy reflects the difference between the baseline test, which detects only strong
increases in firing, and the model analysis, which can reveal shared tuning structure even when
observation responses are weak. Direction tuning was negligible across all regions. Overall, SPL
supported consistent, format-invariant encoding, while motor cortex tuning was more format-
dependent.

Cross-format representational similarity is robust in SPL but conditional or absent in MC:

Single-unit analyses revealed strong format independent tuning in SPL and single format,
intention-dominant responses in motor cortex. We then examined whether this
representational structure was preserved across formats at the population level. To test this, we
applied representational similarity analysis (RSA) to quantify condition-specific similarities in
population activity within and across formats (see Methods). We included only task-relevant
units, as defined by the linear model analysis (see Methods), with the following counts per
array: MC/JJ: 163, SPL/JJ: 101, MCM/RD: 117, MCL/RD: 88, and SPL/RD: 165.

Figure 3A shows cross-format RSA matrices for each array and task variable (action, hand,
direction). Corresponding within-format matrices are shown in Figure S3, and analysis using
different time windows and including all recorded units are presented in Figure S4. In JJ's MC,
cross-format similarity was specific to rotation (R^2 = 0.31); lift and slide were near zero. In RD's
MCM, correlations were strong for the right hand (0.71) and moderate for lift (0.53) and
rotation (0.52); left-hand and slide were weaker (≤0.24). RD's MCL showed no meaningful
correlations (R^2 < 0.12). These patterns reflect selective generalization in MC/JJ and MCM/RD,
aligned with their dominant intention-driven features (rotation and right-hand tuning; Fig. 2C–
D), despite minimal observation tuning at the unit level. In contrast, SPL showed robust,
distributed cross-format similarity across all task variables in both participants. Correlations
were high for all actions (JJ: 0.59–0.72; RD: 0.71–0.79), hands (JJ: 0.63–0.68; RD: 0.76–0.78),
and directions (JJ: 0.63–0.64; RD: 0.73–0.79), consistent with stable representational structure.

Figure 3B shows RSA diagonal values for the 12 task conditions in intention, observation, and
cross-format analyses. During intention, diagonal values consistently exceeded the off-diagonal
mean across all arrays, reflecting strong condition-specific encoding, most pronounced in SPL,
MCL, and MCM, and weaker in MC/JJ. Observation responses showed similar but reduced
structure across arrays. Cross-format RSA revealed selective structure in MC/JJ and MCM/RD. In
MC/JJ, rotation actions showed elevated diagonal values and in MCM/RD, the highest values

corresponded to right-hand actions, consistent with effector-specific generalization. MCL
showed no meaningful cross-format structure, with all diagonals near the baseline. In contrast,
SPL in both participants showed consistently elevated diagonal values across nearly all
conditions, reflecting robust and generalizable cross-format representations.

Lastly, to quantify structure, we compared the difference between mean diagonal and off-
diagonal RSA values against a null distribution generated via 1,000 label permutations (Fig. 3C).
In SPL, all formats showed significant structure in both participants (JJ: int = 0.35, obs = 0.21,
cross = 0.22; RD: int = 0.20, obs = 0.10, cross = 0.10; all p < 0.001). MC/JJ and MCM/RD also
showed significant structure in all formats (MC: 0.14, 0.08, 0.05; MCM: 0.47, 0.14, 0.15; all p <
0.05). MCL/RD reached significance only during intention (0.25, p < 0.001); observation and
cross-format effects were nonsignificant (p > 0.05).

Together, these results demonstrate that SPL consistently encodes task structure across formats
at the population level, while in motor cortex, representational similarity is either absent or
limited to specific, strongly encoded features, highlighting the importance of population-level
analyses in revealing structure that may not be apparent from single-unit responses alone.

SPL supports robust cross-format decoding, while motor cortex shows asymmetric or absent
generalization

We assessed how reliably task features could be extracted from population activity over time,
by performing time-resolved decoding analyses for action type, effector, and movement
direction, separately for intention (Figure 4A) and observation (Figure 4B) trials. Figure S5
displays decoding accuracy and confusion matrices for all 12 task conditions. During intention all
arrays showed robust decoding of action type and effector. Action decoding peaked above 90%
in SPL for both participants (JJ: 91.1%; RD: 95.8%) and ranged from ~74–83% in the motor
cortex arrays (JJ/MC: 73.6%; RD/MCM: 77.9%, MCL: 83.2%). Effector decoding was similarly
strong, peaking above 93% in all of RD's arrays (MCM: 93.7%, MCL: 93.8%, SPL: 93.0%), and
above 75% in JJ (MC: 76.4%, SPL: 86.9%). Direction decoding remained weak across regions.
Effector decoding consistently peaked earlier than action, supporting a sequential encoding
scheme. During observation, decoding was strongest in SPL (action: JJ: 77.7%, RD: 77.1%), with
moderate effector (JJ: 65.7%, RD: 67.4%) and direction decoding. Motor cortex decoding during
observation was weak, except for action in MC/JJ (72.2%). Thus, SPL reliably encoded action
type across formats. Across sessions (Figure S6), decoding performance remained stable: action
and hand decoding were consistently above chance for intention in all regions, with SPL
showing the highest action decoding during observation, while direction decoding remained
uniformly poor.

To assess generalization across formats, we performed cross-temporal decoding by training
classifiers on one format and testing on the other, across all time point pairs (Figs. 4C–D).
Analyses were run bidirectionally: Intention → Observation (Fig. 4C) and Observation →
Intention (Fig. 4D), for action and hand. Results for movement direction are shown in Figure S7.
Decoding accuracy matrices were statistically thresholded via permutation testing (see
Methods). In the Intention → Observation direction, SPL showed robust cross-decoding of
action in both participants (JJ: 77.1% at 2.7→2.6 s; RD: 79.9% at 2.6→2.8 s), with strong hand
decoding in JJ (78.5% at 1.1→2.1 s). A small number of additional significant effects were also
observed in MC of JJ and MCM of RD, with the strongest in MCM for hand (72.2% at 2.1→2.5 s).
No significant generalization was detected in MCL. In the Observation → Intention direction
(Fig. 4D), SPL exhibited robust generalization for both action (JJ: 77.0% at 2.5→2.5 s; RD: 92.4%
at 2.9→2.8 s) and hand (RD: 86.1% at 1.8→2.1 s; JJ: 71.5% at 1.2→1.2 s), with tightly aligned
timing across formats. Interestingly, motor cortex also showed significant decoding: MC/JJ
generalized action (62.5% at 1.5→2.1 s), and MCM/RD generalized both hand (88.2% at
2.5→1.9 s) and action (66.7% at 2.2→2.8 s). No effects were found in MCL. The unidirectional
decoding observed in MC and MCM is particularly notable given the weak or absent within-
format decoding during observation in these regions. This suggests that, even in the absence of
overt task selectivity, observation-related activity may retain structured components aligned
with intention representations. In contrast, the robust and bidirectional decoding in SPL
indicates the presence of a stable, format-invariant code, particularly for action type, consistent
with its generalized encoding across tasks and formats.

SPL and motor cortex exhibit distinct representational geometries across action formats

A central question in understanding action encoding is whether population activity occupies
similar geometric structure across cognitive states. To address this, we examined the
organization of neural trajectories during intention and observation. Trial-averaged responses
were projected into a shared PCA space based on condition means (Fig. 5A; Fig. S8), providing a
geometric perspective on population structure. These trajectories provide a striking and
intuitive geometric perspective on the population structure underlying action encoding. Table
S2 reports the variance explained by the first three principal components for intention,
observation, and the combined dataset, separately for each array and task variable. These
values confirm that the projections capture sufficient variance to support meaningful trajectory
analysis, with total explained variance exceeding 60% in all cases. They also highlight format-
specific differences: observation variance was consistently lower than intention in motor cortex,
while SPL showed comparable variance across formats. In MC of JJ, trajectories appeared similar

across formats only for the rotation action, consistent with its selective generalization in RSA (Fig. 3A) and decoding (Fig. 4D). In MCM of RD, responses were more similar for right-hand conditions, in line with effector-specific cross-format structure. MCL showed clearly segregated trajectories across formats for all conditions, matching the absence of generalization observed throughout prior analyses. In contrast, SPL exhibited qualitatively similar trajectories for all actions across formats, consistent with its robust and generalized encoding. To quantify cross-format similarity, we applied Procrustes analysis between observation and intention trajectories for each task variable and condition (Fig. 5B–C). This method estimates the best-fitting linear transformation (translation, rotation, scaling) to align observation trajectories onto their intention counterparts and returns a distance metric reflecting residual dissimilarity. SPL showed low alignment distances across all conditions (d < 0.1), indicating consistent geometric overlap. In MC of JJ, low distance was found only for rotation (d = 0.25), with poor alignment for lift (0.89) and slide (0.64). In MCM of RD, right-hand trajectories aligned more closely (d = 0.13) than left-hand ones (0.30). No condition in MCL yielded meaningful alignment. These results confirm that SPL supports a shared representational geometry across formats, while MC and MCM exhibit selective overlap, and MCL none. Although Procrustes alignment does not mean that observation and intention trajectories occupy the same neural space, the transformation removes differences in translation, rotation, and scale to reveal their intrinsic geometry. Successful alignment therefore indicates that observation and intention preserve a similar representational structure that can be linearly mapped across formats despite global shifts in activity or response gain.

To further assess population structure across formats, we applied Uniform Manifold Approximation and Projection (UMAP) to embed single-trial activity from both intention and observation into a shared low-dimensional space (Fig. 5D; Fig. S9). Trials were color-coded by condition, and ellipses were fit to the format-specific distributions to visualize condition clustering and cross-format overlap. Figure 5D presents three representative UMAP embeddings (MCM/RD (effector), MCL/RD (effector), and SPL/JJ (action type). Three distinct regimes emerged. In MCM of RD, responses for right-hand trials formed overlapping clusters across formats, whereas left-hand trials remained separated, mirroring the effector-specific generalization seen in RSA, decoding, and PCA. In MCL, intention and observation trials occupied distinct, non-overlapping regions, consistent with the complete absence of cross-format generalization. In contrast, SPL of JJ showed strong cross-format overlap for all action types, with well-separated but aligned clusters, particularly for rotation. These embeddings reinforce the dissociation across regions: SPL supports robust, format-general population codes; MCM exhibits conditional overlap; and MCL remains format-specific.

High-gamma LFP responses reveal format-consistent population encoding at the single channel level

To evaluate neural population structure beyond spiking activity, we analyzed high-gamma (60–120 Hz) LFP power as a complementary population-level metric (Fig. 6). Across all arrays and participants, all channels showed significant modulation for at least one condition in both intention and observation. Strikingly, all motor cortex arrays exhibited robust observation-related responses, in contrast to the sparse or absent observation tuning in the SUA/MUA data. Figure 6A illustrates these effects via time–frequency plots, showing consistent condition-specific activations across formats e.g., rotation tuning in JJ's MC, and right-hand selectivity in MCM and MCL of RD. Figure 6B quantifies the distribution of significantly modulated channels across conditions, highlighting that format-specific tuning was preserved: rotation tuning in JJ MC and effector tuning in MCM/MCL of RD appeared in both formats. SPL again exhibited widespread modulation across all conditions in both participants. Figure 6C shows the evolution of tuning over time. In motor cortex, tuning profiles were nearly identical between intention and observation: action-selectivity in JJ's MC and hand-selectivity in MCM and MCL of RD. SPL showed consistent tuning for action during observation in both participants; during intention, tuning was action-dominant in JJ and hand-dominant in RD. Decoding from LFPs was weaker than from SUA but followed similar trends (Fig. 6D, S10). During intention, both action and hand could be decoded above chance in all arrays (action: JJ/MC: 57.6%, SPL: 70.4%; RD/MCM: 47.8%, MCL: 47.4%, SPL: 60.8%; hand: JJ/MC: 63.3%, SPL: 70.7%; RD/MCM: 73.2%, MCL: 64.4%, SPL: 67.7%). During observation, only SPL supported above-chance decoding for action (JJ: 60.1%; RD: 48.9%). Cross-format decoding (Fig. S11) recapitulated key spiking results: SPL showed robust bidirectional generalization; MCM exhibited unidirectional hand generalization; and MC of JJ showed a weak action effect. These findings indicate that high-gamma activity captures structured population level encoding even when single-unit selectivity appears sparse. This pattern should not be interpreted as evidence for a distinct representational format in the LFPs. Rather, the discrepancy reflects differences in sampling: our spike recordings capture a limited subset of neurons, whereas high-gamma signals pool over a much broader local population. Consistent with this view, spike-based population analyses (RSA, cross-decoding, trajectory analyses) already uncovered latent representational geometry despite weak tuning at the single-unit level. High-gamma activity expressed this geometry more robustly, underscoring how population-level signals can expose consistent representational structure that is only partially evident in sparsely sampled units. In SPL, the convergence of SUA, LFP, and population metrics reinforces its role as a stable, format-general hub for action representation.

SPL Flexibly Represents Observed Actions Only When They Are Behaviorally Relevant

To determine whether neural representations of instructed and observed actions are encoded
in parallel or selectively modulated by task demands, we designed two dissociation tasks that
explicitly separated intention from observation (Fig. 7A). On every trial, participant RD was
presented with both an instruction cue (specifying which hand and action to perform) and a
concurrent video (showing a hand performing an action). The instruction and video could be
either congruent or incongruent, but task demands determined which source of information
was behaviorally relevant. In the no-probe variant, task blocks defined the relevant source:
during the intention block, RD executed the instructed action while the concurrent video was
present but not relevant to the task; during the observation block, RD passively viewed the
video while the instruction cue was present but not relevant. In the probe variant, RD again
executed the instructed action while a video played, but after movement completion was
required to report a feature of the video (action or hand) with a saccade, making both the
instruction and the video behaviorally relevant. This design enabled us to dissociate intention-
related and observation-related activity and to test how behavioral relevance affects neural
representations across regions. Session-level unit counts for both experiments are reported in
Tables S3, S4. In the no-probe intention block, all areas encoded the instructed action, with
strong hand tuning in MCM (163 units at 1.75 s) and MCL (90 at 1.25 s), and stronger action
tuning in SPL (60 units at 2.25 s) (Fig. 7B, green). However, none of the areas encoded the
concurrent video action while intention was underway. In the no-probe observation block,
where no movement was intended, tuning for the instructed (now irrelevant) action dropped to
baseline in all areas, while SPL selectively represented features of the video, with 23 units tuned
at 2.25, predominantly to action identity rather than hand or interaction terms (Fig. 7B, blue). In
the probe variant, tuning for the instructed action remained strong in motor cortex (MCM: 122
hand-tuned units at 2.25 s; MCL: 74 at 1.25 s) and SPL (96 action-tuned at 1.25 s) (Fig 7B,
gray).Crucially, SPL exhibited robust selectivity for the video features (29 units at 2.25 s), in
sharp contrast to the no-probe variant where the same visual input was present but elicited no
selectivity. Motor cortex, by comparison, again showed <5 tuned units for the video features
(Fig. 7b, gray).

Decoding results mirrored the tuning patterns (Fig. 8A). During the no-probe intention block,
instructed actions were decoded with high accuracy across all regions (peak accuracy: MCM:
99.4%, MCL: 97.5% SPL: 91.9%; Fig. 8A, green), but decoding of the concurrent video action
remained near chance (<37% in all areas). In the observation block, decoding of the instructed
(irrelevant) action dropped below 42% in all regions, while decoding of the video action rose
sharply in SPL (66.3% at 2.5 s) but remained weak in motor cortex (<45%) (Fig. 8A, blue). In the
probe variant, decoding of the instructed action remained robust across all regions (MCM:
97.9%, MCL: 94.2%, SPL: 97.5%). Notably, the video action could now also be decoded from SPL
with above-chance accuracy (52.9% at 2.3 s), whereas decoding from motor cortex remained at

chance levels (Fig. 8A, gray). This contrasts with the no-probe variant, where the same visual
input was present during intention but yielded no decodable information in any area, including
SPL.

To rule out the possibility that decoding results were influenced by visual–motor congruency,
we repeated all analyses in both the no-probe (intention and observation) and probe tasks using
only incongruent trials. Decoding performance was virtually identical to that obtained when
including all trials (Fig. S12A), indicating that population activity reflected genuine task-related
representations rather than shared visual overlap. We also tested whether any units explicitly
encoded the congruency between instructed and observed actions. Neither tuning nor
decoding analyses revealed significant selectivity for conflict type across arrays, and decoding
accuracy remained at chance in both task variants (Fig. S12B).

We next examined the temporal stability of the instructed and video action representations
within the probe task using cross-time decoding (Fig. 8B). For the instructed action, all regions
showed a strong and sustained diagonal, indicating stable decoding over time. The lack of broad
off-diagonal generalization suggests that these representations were maintained but gradually
reconfigured rather than held in a fixed subspace. SPL exhibited a slightly broader diagonal
confined to the Go epoch, indicating that representations of the executed action were more
temporally sustained during movement intention. In contrast, decoding of the video action was
temporally restricted. Above-chance decoding emerged only in SPL and only within a short time
window during the video presentation, indicating that SPL's visual representations were brief
and time-locked to sensory input, while motor cortex showed no reliable decoding.

To further characterize the structure of task representations, we trained classifiers to decode all
16 trial types from the dissociation task (2 actions × 2 hands × 4 conflict types; Fig. S13). In the
no-probe intention block (Fig. S13A), decoding in MCM, MCL, and SPL revealed distinct clusters
corresponding to the instructed action, consistent with selective encoding of executed
movements. In the observation block (Fig. S13B), decoding accuracy dropped across all areas,
and confusion matrices lacked systematic structure. In the probe task (Fig. S13C), motor cortex
again showed clustered decoding aligned with the instructed action. In contrast, SPL exhibited a
diagonal structure in the confusion matrix, indicating that it captured the full trial identity
across all 16 conditions (peak accuracy: 49.6%), including both instructed and video features.
This parallel representation emerged despite the fact that the task structure was nearly identical
to the intention block of the no-probe version, differing only by the presence of a post-trial
probe.

Together, these results reveal a gating mechanism in SPL. While motor cortex consistently
reflected the instructed movement, SPL encoded observed (video) actions only when they were
behaviorally relevant. This selective engagement occurred despite identical visual input across
task variants, indicating that SPL's visual selectivity was context-dependent rather than stimulus-
driven. The absence of congruency or conflict effects confirms that decoding reflected genuine
task-specific representations. In contrast, motor cortex maintained stable motor codes
throughout. Overall, SPL dynamically allocated its representational resources according to
behavioral relevance, supporting transient, task-dependent encoding of visual actions alongside
stable motor representations.

Discussion:

We conducted the first systematic comparison of intended and observed actions using single-
unit recordings in the human motor and posterior parietal cortex. In motor cortex, intended
actions were robustly encoded, but passive observation failed to elicit mirror-like responses at
the single-unit level. Still, population analyses revealed a weak but structured geometry during
observation, partially aligned with the execution format and centered on the most strongly
tuned features. In the superior parietal lobule, observed actions were reliably encoded, with
most selective units maintaining shared tuning for action type across formats. These
representations generalized across the population and were sensitive to behavioral relevance:
when observed actions were not task-relevant, their encoding was suppressed. Our findings
suggest that action observation engages distinct encoding schemes across cortical regions,
reflecting a flexible, context-dependent system rather than a fixed mirror mechanism.

In motor cortex, the absence of mirror-like tuning at the single-unit level during passive
observation contrasts with prior reports in nonhuman primates, where neurons in M1 and
premotor areas exhibit consistent observation-driven responses[25–27]. However, population-level
analyses revealed a more nuanced structure: neural activity projected into low-dimensional
space revealed partially aligned trajectories between execution and observation, successful
cross-decoding from observation to execution, and localized overlap in UMAP space, specifically
for intention-tuned features (Figures 3-5). These results suggest that while single units do not
overtly mirror observed actions, MC maintains a latent representational geometry during
observation that reflects core aspects of the execution structure.

Jiang et al. (2020) [28] reported that executed and observed movements in monkey M1 and PMd
occupy a shared subspace, with closely aligned population trajectories. In our recordings from
human motor cortex, population overlap was more limited, confined to specific subregions and
features strongly represented during intention. We also did not observe strong single-unit

responses during passive observation, in contrast to reports in monkeys[25], suggesting that human motor cortex may contribute less directly to action observation. Consistent with this, Rastogi et al. (2023)[29] found that activity in human motor cortex was primarily structured by volitional state, with observation responses substantially weaker than those during attempted movement. Differences between species may partly reflect that our participants could not reproduce observed actions with matching kinematics, which could reduce overlap, but across human data the absence of robust single-unit mirroring appears to be a general finding. Our results extend this view by showing that, even without overt motor output, observation engages a small but structured latent representation in motor cortex, aligned with features strongly encoded during intention.

Our population-level findings are further supported by high-gamma LFP signals, which revealed robust and condition-congruent responses in both areas during observation fulfilling the classical criteria for mirroring (Fig. 6) and closely paralleling human fMRI results, that consistently report motor cortical activation during passive action viewing [30].The convergence across methods points to a representational gradient: while single units in motor cortex showed minimal tuning during observation, the population exhibited a weak but structured geometry that became more apparent at broader spatial scales. LFP, and by extension fMRI, may reflect subthreshold or spatially distributed synaptic activity. This interpretation is supported by evidence that the BOLD contrast mechanism correlates most strongly with LFPs (more so than with multi-unit activity) and primarily reflects synaptic input and intracortical processing rather than spiking output [31]. Our results highlight a critical distinction: population-level metrics can reveal shared representational frameworks between formats even when overt mirror responses are absent at the single-neuron level.

In contrast to motor cortex, SPL exhibited robust encoding of observed actions, with a large proportion of selective units showing shared tuning to the same action across execution and observation (Fig 2E). The cross-format encoding was strongest for action type pointing to a higher-order representation of action identity. Such structure was also evident across the population. Neural trajectories were aligned across formats for matching actions; cross-decoding from execution to observation and vice versa was successful for action type; and UMAP projections revealed spatial overlap (Figures 4-6). These results suggest that SPL encodes a conceptual representation of action, generalizable across sensory format and resilient to contextual mismatch (e.g., when participants do not precisely reproduce the observed movement) not tied to specific motor output. Our findings converge with a growing body of work suggesting that PPC supports abstract action encoding. Aflalo et al. (2020)[24] demonstrated shared population codes in human PPC for action verbs and visual action stimuli. Lanzillotto et al. (2020)[32] showed that AIP neurons do not encode actions invariantly, but population activity allows reliable decoding across viewpoints and formats. Similarly, Chivukula et al. (2025)[22]

showed that somatosensory representations in PPC generalize across both experienced and
observed touch. Across these studies, as in ours, PPC appears to encode not the physical
parameters of an event, but the concept of the action itself. Our results extend this literature by
showing that such conceptual generalization is supported by both single-unit tuning and aligned
population geometry.

The dissociation paradigms allowed us to determine whether these abstract action
representations in SPL are fixed or dynamically modulated. In the no-probe variant, SPL
encoded only the instructed action, with no detectable representation of the concurrent
videostream (Fig 7C, 7E). This dissociation confirms that the motor responses observed in our
main task were not visually driven, ruling out the possibility that SPL activity merely reflects
responses to visual input. In the probe variant (identical in sensory input but requiring
participants to recall the video action on every trial) SPL encoded both the instructed and video
actions (Fig 7D, 7F), whereas MC encoded only the instructed action in both task variants. To
our knowledge, this is the first single-neuron evidence in humans of gating between motor and
visual encoding in SPL. We show that observed features are not represented by default; their
encoding emerges only when they are task-relevant. When motor and visual goals conflict,
internally generated actions suppress irrelevant sensory input. The dissociation between motor
output and visual input demonstrates that observed actions are not mirrored automatically but
are flexibly gated by task demands.

Such task-dependent gating aligns with prior findings in nonhuman primates and human fMRI
studies showing that sensory responses in PPC are modulated by cognitive context and
behavioral relevance [33] and extends them by demonstrating flexible population-level
reconfiguration at the level of individual neurons in human SPL. The role of SPL in this process is
consistent with its proposed function within the frontoparietal multiple-demand (MD) network,
a domain-general system implicated in cognitive control, goal-directed behavior, and adaptive
task management [34,35]. Rather than serving as a static relay of sensorimotor signals, PPC is
increasingly viewed as a dynamic integrator whose representational structure is shaped by task
goals. Models of attentional control further support this view, proposing that the dorsal
frontoparietal network (including the intraparietal sulcus and superior parietal regions) allocates
top-down attention and formulates predictions about incoming stimuli, while the ventral
attention network centered on the temporoparietal junction and ventral frontal cortex) detects
salient or unexpected events and redirects attention accordingly [36]. These dynamics are closely
related to the principle of mixed selectivity, whereby neurons encode combinations of task-
relevant features across domains, a mechanism proposed to enable flexible and high-capacity
representation in cognitive systems [13–15].

Our findings suggest that action understanding does not rely on automatic mirroring, but on a
hierarchical organization in which motor cortex encodes intention-dominant signals and
posterior parietal cortex flexibly integrates observed input with internal goals. This geometry-
based dissociation points to context-sensitive transformations rather than reflexive resonance
as the basis for linking perception to action. These conclusions are drawn from small cortical
regions in two individuals with tetraplegia, raising the broader question of whether intact motor
systems or other frontoparietal areas would reveal similar balances between intention and
observation. Addressing such questions will be essential for testing whether the gating and
geometric principles identified here reflect local properties or a general cortical strategy. In
either case, our results highlight a framework in which human action representations emerge as
flexible, context-dependent geometries embedded within the broader architecture of cognitive
control.

Methods:

Participants

Participants JJ and RD are right-handed males (ages 55 and 40) enrolled in a brain–machine
interface (BMI) clinical trial (clinicaltrials.gov identifier: NCT01958086), approved by the
institutional review boards of Caltech, Casa Colina Hospital, and UCLA. Participant JJ sustained a
C4–C5 level spinal cord injury that occurred approximately 10 years prior to enrollment. He
retains voluntary control of the eyes, head, and shoulders. Participant RD sustained a C3–C4
level spinal cord injury approximately 3 years prior to enrollment. He retains similar control of
the eyes, head, and shoulders, and shows weak residual movements of the wrists and thumbs.
Both participants were clinically stable at the time of participation. Presurgical functional MRI
confirmed task-related activation in regions near the planned implant sites.

Neural Recordings

Participant JJ was implanted in 2018 with two 96-channel Utah arrays targeting the left
precentral gyrus (denoted JJ-MC) and superior parietal lobule (SPL) (denoted JJ-SPL). Participant
RD was implanted in 2023 with four 64-channel Utah arrays targeting the left precentral gyrus
(denoted RD-MCM, RD-MCL), SPL (denoted RD-SPL), and supramarginal gyrus (SMG). The SMG
array in RD did not exhibit reliable task-related activity across sessions and was therefore
excluded from all analyses. All arrays were 4 × 4 mm with 400 μm interelectrode spacing
(Blackrock Microsystems). Neural signals were recorded using a 128-channel neural signal

processor (NeuroPort System, Blackrock Neurotech). Multiunit activity (MUA) was sampled at
30 kHz and high-pass filtered at 750 Hz. Action potentials were detected using a threshold of −
3.5 times the root mean square (RMS) of the high-pass filtered (250 Hz full bandwidth signal).
Local field potentials (LFPs) were recorded continuously at a sampling rate of 1 kHz.

Experimental setup: Experiments were conducted at Casa Colina Hospital and Centers for
Healthcare for Participant RD, and at home for Participant JJ. In all sessions, participants
remained seated in their motorized wheelchairs with their hands resting prone on a flat surface,
in a well-lit room. A 30-inch LCD monitor was positioned directly in front of them. Stimulus
presentation was controlled using the Psychophysics Toolbox[38] for MATLAB (MathWorks).

Action Intention and Observation Task

The experimental design consisted of a primary task performed under two cognitive conditions:
intention and observation. In both conditions, participants viewed identical visual stimuli—a
virtual hand performing actions—on a monitor positioned directly in front of them. Stimulus
timing and content were matched across conditions. Eye position was continuously monitored
using a Tobii eye tracker to confirm that participants attended to the stimuli, although no
fixation requirement was imposed.

In the intention block, participants were instructed to internally generate the cued action using
the specified hand while looking at the screen. Participant JJ remained physically still but
volitionally intended the instructed action. Participant RD, who retained partial motor function,
was instructed to overtly perform the cued action. Although his movements did not always
replicate the precise kinematics of the video stimuli due to physical limitations, we allowed
naturalistic execution and instructed him to maintain consistency in the type of response across
trials and sessions. In the observation block, participants passively viewed the same videos
while remaining still. They were instructed to observe the actions without intending any
movement.

Each trial began with a 0.5-second inter-trial interval (ITI), followed by a 0.5-second hand cue.
The hand cue consisted of a static image of a virtual left or right hand holding a small
parallelogram object between the thumb and index finger, indicating the instructed effector.
This was followed by a 1-second symbolic action cue, presented as an overlaid arrow indicating
both the action type and direction. Arrow shape specified the action: straight for sliding, curved
for lifting, and circular for rotating. The endpoint of the arrow indicated the direction of
movement (leftward or rightward). For sliding and lifting, this corresponded to a horizontal
displacement of the object to the left or right, while for rotation it corresponded to a clockwise
or counterclockwise turn. For consistency, we refer to this factor abstractly as left/right

direction throughout the manuscript. The disappearance of the symbol served as the go cue.
Immediately afterward, the static frame of the hand transitioned into a 1-second video showing
the hand performing the cued action in the indicated direction. The task followed a fully crossed
2 (hand) × 3 (action) × 2 (direction) design, resulting in 12 unique conditions. Each participant
completed 12 repetitions per condition, per block, in each session. Participant JJ completed five
sessions, yielding a total of 421 units in MC and 326 units in SPL, aggregated across sessions.
Participant RD completed six sessions, yielding 441 units in MCM, 479 units in MCL, and 532
units in SPL.

Dissociation Task Variants

To examine how task demands and cue congruency shape action representations, Participant
RD completed two additional experiments with an observation phase that is dissociated from
the instruction phase. These experiments were performed only with RD, who retained partial
motor function and was able to overtly execute the instructed actions. This was essential to
ensure correct task performance in the dissociation paradigm, where precise execution of the
cued action—despite incongruent visual input—was required. To reduce complexity, we fixed
the direction of movement to rightward and used only two action types: *slide* and *rotate*,
performed with either the left or right hand. This yielded a 2 (action) × 2 (hand) design. For
rotation, the rightward direction corresponded to a clockwise turn, while for sliding it
corresponded to a rightward displacement.

Each trial began with a 0.5-second inter-trial interval (ITI) displaying a fixation cross. This was
followed by:

• a 0.5-second hand instruction screen, indicating the instructed effector (left or right
hand),

• a 1-second symbolic cue, showing an overlaid arrow that specified the instructed action
type (slide or rotate),

• and a 1-second go phase, during which a video of a hand performing an action was
displayed.

The action in the video could be congruent or incongruent with the instructed action.
Specifically, the trial could present one of four cue–video pairings:

1. Fully congruent (same action and hand),

2. Action incongruent (same hand, different action),

3. Hand incongruent (same action, different hand), or

4. Action and hand incongruent (different action and hand).

The participant was instructed to perform the cued action with the specified hand concurrently
with the video playback, regardless of what was shown.

Dissociation–No-Probe Task

This version included two blocks: an intention block and an observation block. In the intention
block, the participant executed the instructed action while watching the video. In the
observation block, the participant passively viewed the same videos, with no movement or
intention. No response was required after the trial. This allowed us to dissociate encoding of
instructed versus observed actions.

Dissociation–Probe Task

This version was identical in structure but added a 1-second probe screen immediately after the
video. On each trial, the probe queried either the hand or the action shown in the video. Two
icons were presented (left vs. right hand, or slide vs. rotate), and the participant was required to
make a saccade to the correct icon to report what they had observed. This response was
recorded using the eye-tracking system. By forcing explicit recall of the observed action or
effector, while the participant simultaneously performed the instructed action, this task ensured
that both streams of information were behaviorally relevant.

Spatial Distribution of Gaze: To visualize spatial gaze patterns during the experiment, we
computed two-dimensional heatmaps of gaze position separately for the intention and
observation blocks, combining data across all runs and sessions. Gaze coordinates from all trials
were concatenated, and two-dimensional histograms were computed using a fixed grid
(100 × 100 bins) spanning the full range of observed horizontal and vertical gaze values. The
resulting gaze density distributions were smoothed using interpolation for visualization, yielding
continuous heatmaps that reflect the spatial concentration of gaze over the course of the
experiment.

Data Preprocessing:

Single Unit Activity (SUA) and Multiunit Activity (MUA): Each detected waveform consisted of
48 samples (1.6 ms total), including 10 samples before threshold crossing and 38 samples after.
Single-unit and multiunit activity were sorted using Gaussian mixture modeling applied to the
first three principal components of the waveform shapes[14]. In addition to spike assignments, the

sorting procedure provided a quality factor ranging from 1 to 4, determined by (1) the
percentage of interspike intervals shorter than 3 ms, (2) the signal-to-noise ratio of the mean
waveform, (3) the projection distance between clusters, (4) the modified coefficient of variation
of the interspike intervals (CV2), and (5) the isolation distance of each cluster. Units with a
quality factor of 1 or 2 were considered well-isolated, whereas those with a factor of 3 or 4
were classified as multiunit activity. [14] After spike sorting, net average responses were
computed in 100 ms bins by subtracting baseline activity (−500 to 0 ms before stimulus onset)
from the post-stimulus activity (0 to 3000 ms after stimulus onset) on a trial-by-trial basis.

Local Field Potential (LFP): Line noise was suppressed using a combined spectral and spatial
filtering approach that preserves underlying neural signals while attenuating non-neural
components[39]. The data were then high-pass filtered above 2 Hz using a zero-phase infinite
impulse response (IIR) filter. Trials in which the broadband signal amplitude exceeded two
standard deviations from the session mean were excluded from further analysis. High-gamma
(60–120 Hz) power was estimated using Morlet wavelet convolution with a 7-cycle resolution[40].
To minimize edge artifacts introduced by filtering and wavelet convolution, the first and last
100 ms of each trial were discarded. Power was normalized within each trial by dividing the
time–frequency power at each frequency by the mean power at that frequency during the
500 ms pre-stimulus baseline.

Quantification and Statistical Analysis:

Statistical Comparison to Baseline: To identify task-modulated activity, we compared post-
stimulus responses to baseline on a per-condition basis. For high-gamma analyses, this was
performed at the channel level, for spiking activity, at the unit level. Neural responses (spike
rates or high-gamma power) were binned into overlapping 200 ms windows with a 100 ms
step size, starting at stimulus onset. For each bin, a paired t-test compared the binned activity
to the mean activity during the 500 ms pre-stimulus baseline across trials. Statistical
significance was assessed using a Bonferroni-corrected threshold ($\alpha = 0.05$ / number of bins). A
channel or unit was classified as significantly responsive to a condition if it exhibited at least
three consecutive time bins with significant deviation from baseline. This analysis was
performed separately for each brain region, condition, and signal type.

Latency: For each condition and each significantly responsive unit, response latency was
defined as the center of the first time bin within the earliest sequence of three consecutive bins
showing significant modulation relative to baseline. This latency reflects the earliest consistent
deviation from baseline activity. To assess regional differences in response timing, we compared
latency distributions across brain areas using one-way ANOVAs, conducted separately for each
participant and for each task format (intention and observation). Each unit contributed a single

latency value per condition, and group-level comparisons tested for significant differences in
peak response timing between motor and parietal regions.

Tuning Analysis: To quantify selectivity for task variables, we performed a time-resolved three-
way ANOVA separately for spiking activity (multi- and single-unit) and high-gamma (HG) power.
For each unit or channel and for each 500-ms time bin, we computed the mean response
across time. A three-way ANOVA was then used to test for main effects of action type (rotate,
slide, lift), effector (left vs. right hand), and movement direction (leftward vs. rightward), as well
as their three-way interaction. For the dissociation tasks, in which movement direction was held
constant, a two-way ANOVA was performed with action and hand as factors. Trial labels were
parsed from condition names into categorical variables corresponding to each factor.
Significance was assessed using a Bonferroni-corrected threshold ($\alpha = 0.05$ / number of units or
channels). A unit or channel was classified as selectively tuned to a main effect (e.g., action
type) if the corresponding factor reached significance in the absence of a significant interaction.
Tuning to a combination of factors was labeled as an interaction effect. This analysis was
performed independently for each time bin and brain region, and the number of significantly
tuned units or channels was tracked across time for each tuning category.

Overlap of Task-Relevant Units Across Formats: To assess the distribution of task-related neural
responses across formats, we identified task-responsive units independently for the intention
and observation blocks. A unit was classified as task-responsive if it exhibited a significant
increase in activity relative to baseline for at least one task condition (see *Statistical Comparison*
to Baseline). This analysis was performed separately for each brain region and format. We then
quantified the degree of overlap between formats by computing, for each region, the number
of units responsive exclusively during intention, exclusively during observation, or during both.
These distributions were used to evaluate the extent to which task-related neural activity was
shared or format-specific across the two conditions.

Linear Model Analysis: We classified units based on their selectivity to task variables across
observation and intention conditions. We implemented a structured model comparison
framework similar to that described by Chivukula et al., 2025[22]. For each neuron, firing rates
were averaged over a fixed task window (1–2 s after trial onset) for each of the 12 observation
and 12 intention conditions. These 24 condition-averaged responses were then combined into a
single dataset for that unit, and a series of linear regression models was fit to predict neural
responses based on different combinations of experimental factors (hand used, action type,
movement direction) and format-specific terms (intention vs. observation).

(1) a null model including only a constant term (*Unselective*)

(2) a fully shared model including action, hand, and direction as predictors with the same
weights across formats (*Invariant*)

(3–5) models with shared tuning to a specific task variable: action, hand, or direction (*Action,*
Hand, or *Direction*)

(6) an additional model in which "action" was redefined as six distinct action × direction
combinations (*Action (6)*);

(7) a fully shared model with all main effects and interactions (*Mixed*)

(8) a format-specific model with separate parameters for intention and observation
(*Idiosyncratic*)

(9–10) models including task features only for intention or only for observation trials (*Single*
format)

Model performance was assessed using five-fold stratified cross-validation based on condition
labels, and each unit was assigned to the model with the highest cross-validated R^2 value. To
determine whether the observed R^2 exceeded chance, we implemented a permutation test in
which the neural responses were randomly shuffled across trials while keeping the design
matrix fixed. For each unit, we computed a null distribution of R^2 values (1,000 permutations)
and derived a one-tailed p-value based on the proportion of null R^2 values exceeding the true
R^2. P-values were corrected for multiple comparisons across units using the Benjamini–
Hochberg false discovery rate (FDR) procedure (q = 0.05). Units were considered selective if
they met all of the following criteria: (1) cross-validated $R^2 > 0.01$, (2) permutation-derived p-
value < 0.05 after FDR correction, and (3) the best-fitting model was not the null model. Units
that did not meet all three criteria were classified as unselective.

Population Analysis:

Representational Similarity Analysis: To evaluate the structure of neural representations across
intention and observation, we performed a cross-validated representational similarity analysis
(RSA), separately for each task variable: action type (3 levels), effector/hand (2 levels), and
movement direction (2 levels). Trial labels were regrouped accordingly, and only task-relevant
units in both formats, defined as those that were neither unselective nor best fit by single-
format models in the linear model-based tuning analysis (see *Linear Model Analysis*), were
included. All analyses were conducted independently per brain region. RSA was computed both
within format (intention–intention and observation–observation) and *across format* (intention–
observation), using the same framework across all comparisons. Neural responses were
extracted from a fixed 1–2 s post-stimulus window, and each trial was reshaped into a single
feature vector by concatenating the time and unit dimensions. For each of 500 random splits,

trials were divided into halves within each condition. Condition-averaged activity vectors were
computed independently for intention and observation trials, and Pearson correlations were
calculated between all pairs of vectors across formats, resulting in a condition-by-condition
cross-format RSA matrix per split. These matrices were averaged to obtain a final similarity
matrix. To test whether the observed structure reflected meaningful condition-specific
information, we compared the similarity between matched and unmatched conditions by
computing the mean diagonal and off-diagonal values of each RSA matrix. The difference
between these values (diagonal − off-diagonal) served as a measure of structure strength. To
generate null distributions, we repeated the same procedure after shuffling condition labels
independently within each format prior to trial splitting. Statistical significance was assessed by
comparing the observed difference to the empirical null distribution from shuffled data,
separately for the cross-format matrix and for each within-format matrix (intention and
observation). In addition, we computed the full RSA matrices and permutation-matched nulls
for each format and task variable. Mean diagonal values were extracted as a measure of within-
condition reliability and representational consistency.

To assess the robustness of the RSA results, we conducted control analyses using four
alternative time windows (0–1 s, 0.5–1 s, 1.5–2.5 s, and 2–3 s). For each window, we
recomputed RSA matrices for intention, observation, and cross-format comparisons, and then
quantified similarity to the main analysis (1–2 s window) by computing the Pearson correlation
between the lower triangles (excluding the diagonal) of each matrix and the corresponding 1–2
s RSA matrix. This analysis provided a direct measure of how stable the representational
structure was across different temporal windows.

We also repeated the RSA using all recorded units, rather than only task-relevant ones, and
computed matrix correlations between the RSA results from all units and those from relevant
units only for each comparison type (intention, observation, and cross-format).

Linear Discriminant Analysis (LDA) Within Format: We assessed whether neural population
activity encoded task-relevant information within each format, by training LDA classifiers using a
time-resolved, cross-validated decoding framework. The analysis was performed separately for
each brain area and each classification level. For the main task, classifiers were trained to
distinguish among: (1) the 12 fully crossed task conditions (hand × action × direction), and (2)
individual task variables: action type (3 levels), effector/hand (2 levels), and movement
direction (2 levels). Trials were relabeled accordingly, and each classification problem was
evaluated independently. For the dissociation tasks, decoding was performed in two
complementary ways. First, classifiers were trained to distinguish among all 16 trial types,
defined by the 2 (action) × 2 (hand) × 4 (conflict type) design. Second, to separately assess

encoding of the instructed and observed actions, trials were relabeled based on the 2 (action) ×
2 (hand) combinations corresponding to either the instructed cues or the observed video, and
decoding was performed independently for each. For all analyses, neural responses were
binned in 100 ms steps, and decoding was performed using non-overlapping 200 ms windows
by averaging adjacent bins. Ten-fold cross-validation was used. Within each fold, principal
component analysis (PCA) was applied to the training data across all time bins to reduce
dimensionality. The number of components was selected to capture 95% of the variance, with
an upper limit of 50 components. Both training and test data were projected into this reduced-
dimensional space. LDA classifiers were trained on the reduced training data and evaluated on
the held-out test set for each time window. Classification accuracy was computed per fold and
averaged across folds to yield time-resolved performance curves for each brain region and
classification level. For each region, the time window with the highest decoding accuracy was
identified, and confusion matrices were computed at that time point. Confusion matrices were
normalized by row and visualized as percent classification accuracy. To evaluate the consistency
of decoding performance across sessions, we additionally ran the same decoding analysis
separately within each session. This was done for each of the three individual task variables
(action, hand, direction), and the maximum decoding accuracy per session was extracted. This
allowed us to assess whether the results observed in the concatenated analysis were driven by
any session-specific peaks or drops in performance.

Cross – Time Decoding: To evaluate the temporal stability of neural representations, we
performed cross-time decoding within the probe variant of the dissociation task, separately for
each brain area and for classifiers trained on the instructed or video actions. The analysis
followed the same preprocessing and cross-validation procedures described above. For each
array, neural activity was binned in 100 ms steps, and non-overlapping 200 ms windows were
created by averaging adjacent bins. Within each fold of a ten-fold cross-validation, principal
component analysis (PCA) was computed on the training data across all time bins, and both
training and test data were projected into the same reduced-dimensional space using the
coefficients derived from the training set (95% cumulative variance threshold, maximum 50
components). LDA classifiers were then trained to discriminate either the instructed or the
video actions at each time window and tested on all other time windows, generating a two-
dimensional matrix of decoding accuracy (train × test time). This procedure was repeated for all
folds, and decoding accuracies were averaged across folds to yield cross-temporal generalization
matrices for each array. The diagonal of the matrix reflects standard within-time decoding,
while off-diagonal values quantify the degree to which representations generalize across time.
Sustained off-diagonal accuracy indicates temporally stable population codes, whereas narrow,
diagonal patterns correspond to dynamic, time-specific encoding.

LDA Within Format – LFP: To decode task variables from LFP, we extracted high-gamma (HG)
power following the methodology described in Bouchard et al. 2013[41]. Raw LFP signals were re-
referenced using common average referencing (CAR) and filtered using eight Gaussian-like
bandpass filters, with logarithmically spaced center frequencies between 73 and 144 Hz. The
bandwidth for each filter was scaled semi-logarithmically at 20% of the center frequency. The
analytic amplitude for each filtered signal was computed using the Hilbert transform, and the
resulting envelopes were downsampled to 100 Hz. Amplitude envelopes were then z-scored
per channel across all timepoints and trials, and outlier suppression was applied using a
hyperbolic tangent function. To reduce dimensionality across the eight frequency bands, we
performed singular value decomposition (SVD) on the concatenated envelope matrix (channels
× time × frequency) and retained the first singular vector as the unified HG estimate per
channel. We identified task-relevant channels by comparing HG power during a task window (1–
2 s post-stimulus) against a baseline window (0–0.5 s) using paired t-tests per channel and
included only those with significant differences ($p < 0.05$). LDA decoding was then performed
separately for each brain area and task variable (action type, effector/hand, movement
direction), as well as for the full 12-condition design. Decoding was performed in 500 ms non-
overlapping windows across the trial duration (–0.5 to 3 s), using 10-fold cross-validation.
Classification accuracy was computed per time bin, and peak decoding performance was
visualized alongside confusion matrices derived from the best-performing time window.

Cross – Format Decoding: We evaluated whether neural population representations generalized
across formats, by training LDA classifiers on trials from one format (intention or observation)
and testing them on the other. This analysis was performed separately for each brain region and
each task variable: action type (3 levels), effector/hand (2 levels), and movement direction (2
levels). Decoding was conducted in both directions: training on intention and testing on
observation, and vice versa. Neural activity was binned in 100 ms steps, and decoding was
performed per time bin. For each time bin in the training format, PCA was applied to the full
training dataset (all time bins and trials), and the top 50 components were retained. Training
and test data were projected into this common PCA space. An LDA classifier trained on each
individual training time bin was then evaluated on all test time bins, yielding a full train × test
time bin decoding accuracy matrix. This matrix captures temporal generalization and reveals
whether neural representations aligned across different time points between formats. To assess
statistical significance, we performed permutation testing by randomly shuffling test set labels
across 1000 iterations and recomputing decoding accuracy. For each train–test pair, a p-value
was computed as the proportion of permuted accuracies greater than or equal to the observed
accuracy. Significance thresholds were corrected for multiple comparisons using Bonferroni
adjustment.

Cross – Format Decoding LFP: To evaluate whether HG activity encoded similar task-related information across formats, we performed cross-format decoding using the same HG signal described in the within-format LFP decoding analysis (see *LDA Within Format – LFP*). For each brain area and task variable (action type, effector, direction), a linear discriminant analysis (LDA) classifier was trained on single-trial HG activity from one format (e.g., intention) and tested on data from the other (e.g., observation), and vice versa. HG power was averaged within non-overlapping 500 ms windows spanning −0.5 to 3 s, yielding one feature vector per trial per time bin. Decoding accuracy was computed for all train × test time bin combinations, resulting in a time-resolved decoding matrix for each direction. Statistical significance was assessed by generating null distributions through 1000 permutations of the test labels. Empirical p-values were computed for each timepoint pair and corrected for multiple comparisons using a Bonferroni threshold.

PCA Trajectory Analysis: To visualize the temporal evolution of neural population activity during each task, we performed PCA separately for each brain region and task variable (action type, effector/hand, or movement direction). Only units classified as task-relevant in both formats based on the linear model analysis (i.e., not unselective or single format) were included. Neural responses were extracted from a time window spanning −0.5 to 2.5 s relative to trial onset, using 100 ms binning. The PCA was applied jointly to intention and observation data. For each trial, neural activity was grouped by condition (e.g., action identity) and format (intention or observation). Trials were averaged within each condition and format, resulting in a set of condition-averaged response matrices of size time × units with the number of matrices equal to the number of task levels (e.g., 3 for action, 2 for hand) multiplied by 2 formats. These matrices were concatenated across time and condition, and the resulting (conditions × time) × units matrix was used as input to PCA. The top three principal components were retained, and each condition's time series was projected into this low-dimensional space. The resulting trajectories were plotted separately for intention and observation to compare their temporal geometry. In addition, we quantified the variance explained by the top three components in three ways: based on the PCA decomposition of the combined dataset, and separately for intention and observation by computing the variance captured within each format after projection into the shared PCA space.

Procrustes Analysis: To compare the geometry of neural trajectories between formats, we applied Procrustes analysis to the condition-averaged neural trajectories in PCA space. This analysis was performed separately for each brain region and task variable (action type, effector/hand, or movement direction). For each condition within a task variable (e.g., "lift" or "right hand"), we extracted one trajectory from the intention format and one from the

observation format, both represented in the space defined by the top three principal
components computed from the combined dataset. Procrustes alignment was then used to
align the 3D trajectories of the two formats. This transformation computes the optimal
translation, rotation, and isotropic scaling that minimizes the Frobenius norm between the two
trajectories. A Procrustes distance was computed for each condition, providing a measure of
geometric dissimilarity between formats. Lower values indicate greater similarity in the
temporal structure of neural activity between intention and observation for that condition. As a
control, we repeated the PCA and alignment procedure using all recorded units, and computed
Procrustes distances for all brain regions and task variables.

UMAP Visualization of Neural Representations: To visualize the structure of trial-level neural
activity in a low-dimensional space, we applied Uniform Manifold Approximation and Projection
(UMAP) separately for each brain region. Only task-relevant units (identified via linear model
analysis) were included. Neural responses were averaged over a 1–2 s window following
stimulus onset. Trials from the intention and observation formats were concatenated and
projected jointly. UMAP was performed using the cosine distance metric with 15 nearest
neighbors and a minimum distance of 0.1. The resulting two-dimensional embeddings were
used to visualize the structure of population activity across task conditions and formats. To
visualize the spatial distribution of each condition in the UMAP space, we computed a separate
2D ellipse for each condition and format combination. The center of each ellipse was defined as
the empirical centroid of the UMAP coordinates for that group (i.e., the mean across all trials).
The shape and orientation of the ellipse were derived from the empirical 2D covariance matrix
of the points. We used the eigenvectors and eigenvalues of this matrix to construct an ellipse
representing the major and minor axes of the group's spread. This approach provides an
interpretable summary of the distribution of trials in the reduced space, allowing visual
assessment of separation or alignment between formats.

References:

1. di Pellegrino, G., Fadiga, L., Fogassi, L., Gallese, V. & Rizzolatti, G.
Understanding motor events: a neurophysiological study. *Exp. Brain Res.* **91**,
176–180 (1992).

2. Rizzolatti, G., Fadiga, L., Gallese, V. & Fogassi, L. Premotor cortex and the
recognition of motor actions. *Cogn. Brain Res.* **3**, 131–141 (1996).

3. Gallese, V., Fadiga, L., Fogassi, L. & Rizzolatti, G. Action recognition in the
premotor cortex. *Brain* **119**, 593–609 (1996).

4. Hickok, G. *Eight Problems for the Mirror Neuron Theory of Action Understanding*
in Monkeys and Humans. http://mitprc.silverchair.com/jocn/article-

pdf/21/7/1229/1760190/jocn.2009.21189.pdf.

5.   Gallese, V., Fadiga, L., Fogassi, L. & Rizzolatti, G. Action recognition in the premotor cortex. *Brain* **119**, 593–609 (1996).

6.   Bonini, L. & Ferrari, P. F. Evolution of mirror systems: A simple mechanism for complex cognitive functions. *Ann. N. Y. Acad. Sci.* **1225**, 166–175 (2011).

7.   Rizzolatti, G. & Sinigaglia, C. The mirror mechanism: A basic principle of brain function. *Nat. Rev. Neurosci.* **17**, 757–765 (2016).

8.   Rizzolatti, G., Fadiga, L., Gallese, V. & Fogassi, L. Premotor cortex and the recognition of motor actions. *Cogn. Brain Res.* **3**, 131–141 (1996).

9.   Bonini, L., Rotunno, C., Arcuri, E. & Gallese, V. Mirror neurons 30 years later: implications and applications. *Trends Cogn. Sci.* **26**, 767–781 (2022).

10. Lake, B. M., Ullman, T. D., Tenenbaum, J. B. & Gershman, S. J. Building machines that learn and think like people. *Behav. Brain Sci.* **40**, (2017).

11. Schwettmann, S. E., Tenenbaum, J. B. & Kanwisher, N. Invariant representations of mass in the human brain. *Elife* **8**, (2019).

12. Aflalo, T. *et al.* Cognition through internal models: Mirror neurons as one manifestation of a broader mechanism. at https://doi.org/10.1101/2022.09.06.506071 (2022).

13. Fusi, S., Miller, E. K. & Rigotti, M. Why neurons mix: High dimensionality for higher cognition. *Current Opinion in Neurobiology* vol. 37 66–74 at https://doi.org/10.1016/j.conb.2016.01.010 (2016).

14. Zhang, C. Y. *et al.* Partially Mixed Selectivity in Human Posterior Parietal Association Cortex. *Neuron* **95**, 697-708.e4 (2017).

15. Zhang, C. Y. *et al.* Preservation of partially mixed selectivity in human posterior parietal cortex across changes in task context. *eNeuro* **7**, (2020).

16. Rigotti, M. *et al.* The importance of mixed selectivity in complex cognitive tasks. *Nature* **497**, 585–590 (2013).

17. Andersen, R. A. & Cui, H. Intention, Action Planning, and Decision Making in Parietal-Frontal Circuits. *Neuron* **63**, 568–583 (2009).

18. Snyder, L. H., Batista, A. P. & Andersen, R. A. Coding of intention in the posterior parietal cortex. *Nature* **386**, 167–170 (1997).

19. Andersen, R. A. & Buneo, C. A. Intentional maps in posterior parietal cortex. *Annual Review of Neuroscience* vol. 25 189–220 at https://doi.org/10.1146/annurev.neuro.25.112701.142922 (2002).

20. Gallego, J. A., Perich, M. G., Miller, L. E. & Solla, S. A. Neural Manifolds for the Control of Movement. *Neuron* **94**, 978–984 (2017).

21. Fu, Z. *et al.* The geometry of domain-general performance monitoring in the

human medial frontal cortex. *Science (80-.).* **376**, (2022).

22.   Chivukula, S. *et al.* Population encoding of observed and actual
somatosensations in the human posterior parietal cortex. *Proc. Natl. Acad. Sci. U.*
S. A. **122**, (2025).

23.   Mukamel, R., Ekstrom, A. D., Kaplan, J., Iacoboni, M. & Fried, I. Single-neuron
responses in humans during execution and observation of actions. *Curr. Biol.* **20**,
750–756 (2010).

24.   Aflalo, T. *et al.* A shared neural substrate for action verbs and observed actions in
human posterior parietal cortex. *Sci. Adv.* **6**, (2020).

25.   Dushanova, J. & Donoghue, J. Neurons in primary motor cortex engaged during
action observation. *Eur. J. Neurosci.* **31**, 386–398 (2010).

26.   Tkach, D., Reimer, J. & Hatsopoulos, N. G. Congruent activity during action and
action observation in motor cortex. *J. Neurosci.* **27**, 13241–13250 (2007).

27.   Vigneswaran, G., Philipp, R., Lemon, R. N. & Kraskov, A. M1 corticospinal mirror
neurons and their role in movement suppression during action observation. *Curr.*
Biol. **23**, 236–243 (2013).

28.   Jiang, X., Saggar, H., Ryu, S. I., Shenoy, K. V. & Kao, J. C. Structure in Neural
Activity during Observed and Executed Movements Is Shared at the Neural
Population Level, Not in Single Neurons. *Cell Rep.* **32**, 108148 (2020).

29.   Rastogi, A. *et al.* Neural Representation of Observed, Imagined, and Attempted
Grasping Force in Motor Cortex of Individuals with Chronic Tetraplegia. *Sci.*
Reports 2020 101 **10**, 1–16 (2020).

30.   Molenberghs, P., Cunnington, R. & Mattingley, J. B. Brain regions with mirror
properties: A meta-analysis of 125 human fMRI studies. *Neurosci. Biobehav. Rev.*
36, 341–349 (2012).

31.   Logothetis, N. K., Pauls, J., Augath, M., Trinath, T. & Oeltermann, A.
Neurophysiological investigation of the basis of the fMRI signal. (2001).

32.   Lanzilotto, M. *et al.* Stable readout of observed actions from format-dependent
activity of monkey's anterior intraparietal neurons. *Proc. Natl. Acad. Sci. U. S. A.*
117, 16596–16605 (2020).

33.   Freedman, D. J. & Ibos, G. An Integrative Framework for Sensory, Motor, and
Cognitive Functions of the Posterior Parietal Cortex. *Neuron* **97**, 1219–1234
(2018).

34.   Duncan, J. The Structure of Cognition: Attentional Episodes in Mind and Brain.
Neuron **80**, 35–50 (2013).

35.   Erez, Y. & Duncan, J. Discrimination of visual categories based on behavioral
relevance in widespread regions of frontoparietal cortex. *J. Neurosci.* **35**, 12383–
12393 (2015).

36. Corbetta, M. & Shulman, G. L. Control of goal-directed and stimulus-driven
attention in the brain. *Nat. Rev. Neurosci.* **3**, 201–215 (2002).

37. Woolgar, A., Hampshire, A., Thompson, R. & Duncan, J. Adaptive Coding of
Task-Relevant Information in Human Frontoparietal Cortex. *J. Neurosci.* **31**,
14592–14599 (2011).

38. Brainard, D. H. The Psychophysics Toolbox. *Spat. Vis.* **10**, 433–436 (1997).

39. de Cheveigné, A. ZapLine: A simple and effective method to remove power line
artifacts. *Neuroimage* **207**, (2020).

40. Kronland-Martinet, R., Morlet, J. & Grossmann, A. Analysis of Sound Patterns
through Wavelet transforms. *Int. J. Pattern Recognit. Artif. Intell.* **01**, 273–302
(1987).

41. Bouchard, K. E., Mesgarani, N., Johnson, K. & Chang, E. F. Functional
organization of human sensorimotor cortex for speech articulation. *Nature* **495**,
327–332 (2013).

1075

1076

1077

1078

1079

Data Availability

All data produced in the present study are available upon reasonable request to the authors

Acknowledgements

We would like to express our gratitude to participants N1 and N2 for making this research possible. This work was supported by National Eye Institute grant UG1EY032039, Tianqiao and Chrissy Chen Brain-Machine Interface Center at Caltech, Swartz Foundation, and Boswell Foundation. VB is supported by Fonds Wetenschappelijk Onderzoek (FWO) grant 1264926N.

Contributions

VB, and RAA conceived and designed the experiment. VB performed the recordings, data analysis and wrote the manuscript. JG and RAA supervised and guided the study. ERR, AAB, and CL provided clinical support. VB, JG, RAA, KP acquired funding. KP and RAA were responsible for project administration. All authors reviewed and edited the manuscript.

1095

Competing interests

1097   The authors declare no competing interests.

1098

A)

INTENTION BLOCK

OBSERVATION BLOCK

VIDEO + INTENDED ACTION

VIDEO ONLY

GO (1 s)

LEFT / RIGHT HAND

Action Instruction (1 s)

THREE ACTION TYPES

TWO DIRECTIONS

Hand Instruction (0.5 s)

ITI (0.5 s)

B)

JJ

CS

IPS

● MC
● SPL

MEDIAL

ANT ↔ POST

LATERAL

RD

CS

IPS

● MCL
● MCM
● SPL
● SMG

A)

B)