ModSeqR: An R package for efficient analysis of modified nucleotide data

Hailey E. Zimmerman[1,2], Jordan L Moore[1,3], Ryan H. Miller[1,2], Isaac Stirland[1], Andrew Jenkins[1,3], Erin Saito[1], Tim Jenkins[1,3,*], Jonathon T. Hill[1,3,*]
*These authors contributed equally to this work.

Affiliations
[1] Wasatch BioLabs, 2315 West 700 South, Suite R, Pleasant Grove, UT 84062 USA.
[2] Department of Biology, Brigham Young University, 701 E. University Pkwy, LSB 4102, Provo, UT 84602 USA.
[3] Department of Cell Biology & Physiology, Brigham Young University, 701 E. University Pkwy, LSB 4005, Provo, UT 84602 USA.

Email Addresses
Hailey Zimmerman: hailey@renewbt.com
Jordan Moore: jlmoore8@byu.edu
Ryan Miller: ryanhm@byu.edu
Isaac Stirland: isaac@wasatchbiolabs.com
Andrew Jenkins: jenk2319@byu.edu
Erin Saito: erin@renewbt.com
Tim Jenkins: tim_jenkins@byu.edu
Jonathon T. Hill: jhill@byu.edu

Corresponding Authors
Jonathon T. Hill
Department of Cell Biology and Physiology
Brigham Young University
701 E. University Pkwy, LSB 4005
Provo, UT 84602

Tim Jenkins
Department of Cell Biology and Physiology
Brigham Young University
701 E. University Pkwy, LSB 4005
Provo, UT 84602

Keywords
DNA methylation, differential methylation analyses, Illumina methylation microarray, Oxford Nanopore sequencing, 5-methylcytosine, 5-hydroxymethylcytosine, R

1 Abstract

DNA methylation regulates a wide range of biological processes, including gene

expression, disease progression, and cell identity. Long-read technologies now enable

more comprehensive and accurate methylome analyses than ever before, but they are

hindered by the computational resources needed to analyze the massive datasets. Here,

we present the CH3 file format, which aids data storage and transfer by reducing file

sizes by more than 95%, and the ModSeqR R package, which builds on the CH3 format

and a database backend to enable a broad range of epigenetic analyses. Together, these

tools enable high-throughput methylation analysis while minimizing computational

resource requirements.

11 Background

Although nearly every cell in an organism contains the same DNA sequence, DNA

function varies widely across cell types, over developmental time, and in response to

environmental stimuli. This regulatory diversity creates the rich mosaic of cellular

behaviors that makes multicellular life possible. One of the most important mechanisms

underlying this phenomenon is the chemical modification of DNA and RNA nucleotides[1].

These modifications encompass a wide range of chemical changes and are only beginning

to be systematically described and understood. Thus, accurate detection and analysis of

DNA modification patterns are essential for understanding development, disease

mechanisms, and responses to environmental changes[2].

The most well-characterized DNA modification is the addition of methyl groups to the

fifth carbon of cytosine residues, typically within cytosine-guanine dinucleotide (CpG)

contexts. DNA methylation plays vital roles in regulating cellular identity and function in

humans and other species. Aberrant methylation patterns can destabilize the genome and

disrupt normal gene expression, contributing to numerous diseases and serving as

important diagnostic biomarkers[3,4,5]. Traditional approaches to DNA methylation

profiling have relied heavily on microarray technologies such as the Illumina

MethylationEpic Bead Chip. These arrays, while cost-effective and high-throughput, are

inherently limited in genomic coverage and resolution[6]. Recent sequencing-based

methods, including bisulfite sequencing and enzymatic methyl-seq (EM-seq), have

extended our ability to interrogate methylation on a genomic scale. However, these

technologies introduce additional limitations, including biases introduced during cytosine

conversion and PCR amplification, as well as computational analysis challenges due to

the number of mismatches introduced by the conversion process. In contrast, native

methylation sequencing directly analyzes unamplified, unconverted DNA, avoiding these

limitations. Platforms such as Oxford Nanopore Technologies (ONT) and PacBio have

enabled native, PCR-free sequencing and subsequent genome-wide detection of DNA

modifications in real time and at high resolution[7,8]. These third-generation technologies

offer more comprehensive and unbiased epigenetic analyses than array-based platforms

and other traditional methods[9], thus providing significant technical advantages in most

use cases, especially when studying genomes from non-model organisms or exploring

genomic regions that are poorly represented by commercial arrays[10].

Despite its promise, native modified-base sequencing data remains challenging to work

with due to its large size and lack of streamlined analytical tools[11]. A single pass of the

human genome (1x) produces 3-5 gigabases (Gbases) of data. Thus, sequencing at deeper

coverages or with multiple samples can produce terabytes of information. Several tools

have been developed to address this issue by compressing raw sequencing data[12], but they

fall short in providing support for further analysis. Other software packages provide

differential methylation analysis capabilities, but were primarily developed for short-read

bisulfite sequencing data[13]. Consequently, their performance is suboptimal for analyzing

data from other paradigms, such as long-read sequencing or studying alternative DNA

modifications[14]. As a result, there remains an urgent need for efficient tools to analyze

downstream data from long-read, native DNA modification sequencing.

To address these gaps, we developed a two-part solution: a highly efficient modified-

nucleotide data storage format (CH3) that reduces nanopore data sizes by 90-95%, and

ModSeqR, a publicly available R package for fast, flexible downstream analysis.

ModSeqR supports differential methylation analysis at single-base, sliding windows, or

regional levels, includes built-in visualization and read-classification tools, and offers

customizable parameters for diverse experimental designs. Here we present the package's

workflow, features, and performance.

Results

CH3 - Efficient DNA Modification Data Storage

Methylation sequencing generates large volumes of raw data, typically in the form of binary alignment map (bam) files containing raw read sequences. When modified base calling is enabled, two tags are added to each record in the file: one for the modified base call positions and a second with probabilities for modification at the position. In order to analyze the data, these files undergo a series of pre-processing steps, as summarized in **Figure 1a**. This process includes alignment, merging, sorting, and indexing. Finally, base modification predictions—such as methylation events—can be extracted and stored in .tsv files using tools like the modkit package (https://github.com/nanoporetech/modkit). While convenient as a human-readable format, these plain-text call files are often unmanageably large, presenting challenges for downstream analysis, storage, and sharing.

Figure 1: Specification for the CH3 file format. A) The general workflow used to

generate a CH3 file. B) Sample CH3 file contents. C) Memory comparison between CH3

and modkit calls formats across 29 nanopore sequencing runs. Each bar represents the

total file size in gigabytes (GB) for a single sequencing run, with modkit calls files shown

in light blue and the corresponding CH3 files shown in red.

To address the limitations inherent in the standard methylation output format, we

developed the custom CH3 file format (named after the chemical formula for a methyl

group), a compact, efficient representation of base modification calls designed for

efficient compression and retrieval. This format contains all essential nucleotide

modification information, including the sample name, read ID, chromosome, 0-based

reference position, read length, query k-mer, call probability, call code, base quality, and

samtools flag value. The CH3 file specification is also extensible, allowing additional

columns can be added to meet unique needs. Internally, the CH3 format leverages the

Apache Parquet framework (https://parquet.apache.org/), enabling fast, column-based

access and easy integration with many popular programming languages, including R,

Python, C++, and Java. The Parquet format reduces file size by utilizing dictionary-based

encoding for string columns and incorporates the zstd compression algorithm

(https://github.com/facebook/zstd) to efficiently represent data within the file, allowing

for fast access. In addition to the inherent efficiencies of the Parquet format, the CH3 file

specification also relies on the samtools flag, which encodes alignment classification

(unaligned, primary, secondary, or supplementary) and strand (+ or -) into a single integer

instead of having multiple columns for this information (**Figure 1b**), further reducing its

size. Together, these factors reduce the size of methylation data stored in TSV files to just

5–10% of their original size, ensuring that large-scale epigenomic datasets can be stored,

transferred, and queried using minimal computational resources (**Figure 1c**).

ModSeqR - An R Package for Analyzing Modified DNA

Current R packages for analyzing modified DNA have two major limitations. First, many

are built around a bisulfite conversion paradigm. Thus, they do not support direct

detection of modifications and are generally limited to methylation calls. However, third-

generation sequencing platforms, such as the Nanopore platform, can directly detect a

large number of modifications. Second, the amount of data generated from sequencing is

extremely large. For example, there are approximately 30 million CpG dinucleotides in

the human genome. At a sequencing depth of 10x, 300 million calls per sample, the data

is orders of magnitude larger than the 900,000 data points generated by the Epic Array,

and large enough to utilize the entire vector memory limit on machines with modest

hardware specifications.

To address both of these issues, we have created the ModSeqR package (outlined in

Figure 2a). This package implements a DuckDB database backend, enabling users to

conduct large, complex analyses on a wide range of hardware[15]. The database is managed

internally to maintain ease of use and familiarity for users accustomed to using R's

conventional data structures and paradigms (e.g. piping). The package also provides

several built-in functions for working with the base call data to facilitate common

workflows, including QC, data summarization by position, read, window, and region, and

differential methylation analysis. An example pipeline with explanations for each

function is shown in **Figure 2b-c**. Below, we outline the key steps of an analysis

workflow and highlight the functionality and outputs of the package.

Figure 2: ModSeqR Core Design and Workflow. A) Schematic of possible ModSeqR

workflows, starting from the input of CH3 files and progressing through database

creation, summarization, analysis, and output. B) Example pipeline for a full differential

methylation pipeline using R's native pipe syntax. Pipeline begins with creating a

database, then summarizes data using sliding windows, and performs a differential

methylation analysis. Finally, significant windows are collapsed into merged regions, and

the results are exported to a user-defined path. C) The core functions used in the example

pipeline in Panel B, along with their required arguments and a brief description.

Database Creation and Filtering

The first step in any ModSeqR pipeline is to create a database with all samples to be

included in the analysis (**Figure 2**). The CH3 file format is designed to store the data

from a single sample, while the database combines multiple samples into a single data

structure, a calls table, for analysis (**Supplemental Figure 1**). The database is written to

the local directory as "filename.ch3.db" and is updated as tables are created within it,

allowing for the persistent storage of intermediate data structures and reducing the need

to rerun calculations between sessions or to maintain large amounts of data in memory

during multistep pipelines.

During this stage, the data can also be filtered for a variety of QC parameters, including

minimum read length, minimum call probability, and minimum base quality.

Additionally, users can choose to focus on specific types of modifications or

combinations of several modifications. For example, users importing data from CH3 files

containing methylation and hydroxymethylation can choose to use either modification,

combine both into a single call, or retain all modifications. This level of customization

empowers researchers to refine their workflows and explore epigenetic patterns in a way

that aligns with their biological questions and data characteristics.

Summarizing DNA methylation information over positions, pre-defined

regions, or tiling windows

The modification calls stored in the database can be summarized in several ways

(**Figure 2**). ModSeqR can summarize DNA methylation data across individual genomic

positions, predefined regions (such as promoters, CpG islands, or introns), or sliding

windows for further analysis. It also supports read-level summarization for mixture

analysis (described below). These summaries can then be used for downstream analyses

of these unique sites of interest. More detailed explanations of all functions within the

package can be found in the ModSeqR vignette.

Users can export any resulting summary tables directly into their R environment for

further exploration with the get_table() function. This includes data summarized by

position, window, region, read, or a differential analysis. Example summarization table

outputs using a synthetic dataset are shown in **Supplemental Figure 2**. Additionally,

users can save the data table as a CSV file for external use by using export_table().

Differential Methylation Analysis

A differential methylation analysis can be performed to identify statistically

significant differences in DNA methylation levels at individual bases or genomic

windows/regions between two different sample groups. This analysis is essential for

detecting epigenetic changes that may play a role in gene regulation, development, or

disease processes such as cancer and neurological disorders[16]. Differential methylation

testing is performed using ModSeqR's adaptive statistical framework (see Methods),

which selects an appropriate hypothesis test based on replicate structure

Calibration of differential methylation testing

To evaluate the statistical calibration of ModSeqR's differential methylation analysis, we

generated synthetic nanopore modification datasets with known ground truth. Simulated

datasets contained 1,000 CpG sites, of which 100 were assigned true methylation

differences of ≥ 0.5 between case and control groups, while the remaining sites

represented true nulls. Read coverage, per-read methylation probabilities, and replicate

structure were simulated to reflect empirical nanopore sequencing data.

Differential methylation testing was performed using ModSeqR's standard

workflow, with p-values adjusted for multiple testing across all loci using the Benjamini–

Hochberg procedure. At an adjusted p-value threshold of $q < 0.05$, ModSeqR identified

103 sites, of which 100 corresponded to true differentially methylated positions, yielding

an empirical false discovery rate of 2.9% (**Supplemental Figure 3b**). Consistent with

appropriate statistical calibration, p-values for true null sites were uniformly distributed

prior to multiple testing correction and exhibited a conservative shift toward 1.0

following a Benjamini–Hochberg adjustment (**Supplemental Figure 3A**). Across a broad

range of q-value thresholds, the empirical false discovery rate closely tracked or

remained slightly below the nominal level (**Supplemental Figure 3c**), demonstrating

effective control of false positives under realistic sequencing noise and replicate

structure. Together, these results indicate that ModSeqR's differential methylation

analysis is well calibrated under realistic conditions, and that adjusted p-value thresholds

provide reliable control of the false discovery rate.

Outputs

The output of a differential methylation analysis can be directly plotted as a heatmap or a

volcano plot, among others (**Figure 3a and b**). It can also be exported as a table to use

with standard plotting functions in R **(Figure 3c)**.

Figure 3: Example Output and Plots for Differential Expression Analysis. A)

Heatmap showing the top 150 differentially methylated regions between sperm and

blood. B) Example differential volcano plot generated with a custom ModSeqR function.

Each square represents a genomic window/position. The x-axis represents the

1 methylation-fraction difference between the sperm and blood samples, while the y-axis

2 indicates the statistical significance (adjusted p-value). Density correlates with darker

3 colors, and points near the center indicate regions with little or no difference C) An

4 example R output table generated from the calc_mod_diff() function.

QC metrics: descriptive statistics, sample correlation, and PCA

In addition to its core analysis pipelines, ModSeqR provides a suite of tools for whole

methylome characterization, including general quality control metrics, sample-level

comparisons, and dimensionality reduction. Users can visually assess key characteristics

of their methylation data using built-in plotting functions (**Figure 4**). Two primary

visualization options are available: read coverage per base, which provides insight into

sequencing depth and data reliability, and percent methylation per base, which reflects

the underlying biological signal. These metrics are stored in the package's core data

structures and are easily accessible for customized visualizations.

Figure 4: Descriptive Statistics and Quality Control Function Outputs. A) Percent

methylation per base graph: This histogram shows the distribution of CpG methylation

percentages across all bases for a sample. It provides an overview of the methylation

landscape, allowing users to quickly assess whether methylation values are skewed,

bimodal, or evenly distributed. B) Read coverage graph: This histogram displays the

distribution of CpG read coverage (on a log10 scale) per base. It helps evaluate the depth

and consistency of sequencing coverage, which is critical for assessing the reliability of

methylation calls. C) PCA plot: The principal component analysis (PCA) plot reduces

high-dimensional methylation data into two main components (PC1 and PC2) that

capture the largest variance. This visualization helps identify clustering of samples and

potential batch effects or outliers. D) Correlation plot: The sample correlation matrix

helps visualize the pairwise Pearson correlation coefficients between samples based on

methylation values. It quantifies the linear relationship between samples, helping assess

similarity and reproducibility across experimental conditions.

To compare methylation profiles across samples, ModSeqR includes correlation plots

based on the Pearson correlation coefficient, a measure of the linear relationship between

two continuous variables. Additionally, a principal component analysis (PCA) function is

provided to explore global patterns in methylation data and detect clustering among

samples. PCA reduces the dimensionality of high-throughput data by projecting it into a

smaller set of orthogonal components that capture the greatest variance, helping reveal

biological trends or batch effects across the dataset.

Performance

ModSeqR is designed to be computationally efficient and capable of analyzing large

datasets in practical runtimes and on common hardware configurations. We tested the

performance of several key analysis steps on various dataset sizes. The most

computationally intense step within the analysis is summarization. The database is

initially created with one row per methylation call. These calls are then summarized into

positions, reads, regions, or sliding windows across all samples, which requires large

amounts of database read and write calls. As shown in **Figure 5a**, the time required to

conduct summarization depends on both the type of summarization and the dataset size.

Importantly, however, the computation completes for all dataset sizes, even when they

are larger than the available memory. Differential analysis also reveals a similar smooth

increase over time without failure (**Figure 5b**). Finally, we compared run times between

an analysis server with 250 GB of RAM and 96 CPU cores and a personal computer with

16 GB of RAM and 8 cores (**Figure 5c**). While run times were significantly longer on the

personal computer, times were still reasonable, and all analyses were completed.

Figure 5: ModSeqR Performance on different hardware configurations. A)

Summarizing Data Analysis Time vs. Size for different data collection functions. This

includes summarizing methylation data by windows (100 bp step size), reads, genomic

positions, or regions. B) Differential Analysis Time vs. Size. This figure depicts a

differential analysis between three available options (regions, positions, and windows).

These functions were run on a personal computer with 16GB of RAM. C) Time vs. RAM

available for 4 functions on two different machines - one is a personal computer with

16GB of RAM available, while the other is a large server with 250GB of memory

available. The dataset consisted of 4 samples of 5x coverage.

We also compared ModSeqR to four other software packages used to analyze differential

methylation: diffONT, DSS, modkit, and PoreMeth2 (Table 1). We installed the latest

version of each package, which we used to identify DMRs between one sperm sample of

5x coverage and one blood sample of 5x coverage. Note that both these samples were

pulled from the dataset aforementioned. Each package was used to identify DMRs twice

with the following settings: 16 GB RAM / 4 CPUs and 256 GB RAM / 16 CPUs (Table

2). With 16 GB RAM / 4 CPUs allotted, each package maxed out memory at 16 GB, and

ModSeqR was by far the fastest analysis (9m 19s). With 256 GB RAM / 16 CPUs

allotted , diffONT was the most efficient in memory usage (18.76 GB), but ModSeqR

was again the fastest analysis (4m 8s).

	Sequencing Type	Language	Sample QC	Modification Types	Multi-Modification Analysis	Differential Analyses	Read Classification	Data Plots
ModSeqR	All	R	PCA on methylation fraction and coverage correlation	5mC, 5hmC, 4mC, and 6mA (Any SAM/CHEBI code)	Yes	DMP, DMW, DMR	Yes	Coverage statistics, methylation histogram, methylation scatterplot, methylation volcano plot, PCA
diffONT	ONT	Python	None	5mC or 5hmC	No	DMP, DMR	No	None
DSS	All	R	Minimum coverage parameters	5mC, 5hmC, 4mC, and 6mA (Any SAM/CHEBI code)	No	DMP, DMR	No	Methylation line graph
modkit	ONT	Rust	Methylation fraction parameters	5mC, 5hmC, 4mC, and 6mA (Any SAM/CHEBI code)	No	DMP, DMR	No	None
PoreMeth2	ONT	Python	Shannon's Entropy parameters	5mC or 5hmC	No	DMP, DMW, DMR	No	DMR Δβ / ΔS plot, DMR annotation plot

Table 1: Feature Comparison of Five Differential Methylation Tools

A summary of each package's key features, including sample QC methods, accepted

modification types, and statistical analyses.

	16 GB RAM / 4 CPUs		256 GB RAM / 16 CPUs	
	Time	Max Memory	Time	Max Memory
ModSeqR	9m 19s	16.00 GB	4m 8s	45.89 GB
diffONT	192m 22s	16.00 GB	200m 22s	18.76 GB
DSS	45m 26s	16.00 GB	37m 47s	255.99 GB
modkit	32m 34s	15.99 GB	10m 51s	82.08 GB
PoreMeth2	94m 40s	16.00 GB	27m 6s	130.69 GB

Table 2: Performance Comparison of Five Differential Methylation Tools

Each package was used to identify DMRs between the same two samples using two

different configurations: 16 GB RAM / 4 CPUs and 256 GB RAM / 16 CPUs. This table

summarizes the wall-clock time and max memory usage for each analysis.

Discussion

Analyses of DNA methylation and other nucleotide modifications have enormous

potential to provide novel biological insights into both natural processes and disease

mechanisms. While such analyses have been conducted for over a decade, the recent

development of direct, modified base calling on the NanoPore and PacBio platforms has

significantly increased the genomic coverage of these assays. For example, the current

Epic Array has approximately 900 thousand of the approximately 30 million CpG sites in

the genome (approximately 3%). However, sequencing regularly provides information on

over 28 million sites (93%) . This represents a significant leap forward, providing

valuable insights ~~that were previously missed by other~~ technologies.

Although the increased genomic coverage provided by third-generation sequencing is

very welcome, it also results in a significant increase in the size of the data files

produced, hindering analysis due to the requirement for large amounts of computational

resources and specialized bioinformatics expertise to manage the data effectively. Here,

we have presented two tools to address these issues: the CH3 file format and the

ModSeqR R package. These tools, used together, will enable more users to perform

modified nucleotide analysis and drive wider adoption across the field. Furthermore, our

comparison of ModSeqR to four other differential methylation tools demonstrates that it

significantly reduces the time and memory required, thereby enabling more users with

limited computing resources to analyze large datasets more efficiently.

One of the primary challenges with large datasets lies in the cost and complexity of

storing and transferring them—difficulties that will only intensify as data generation

continues to grow. Thus, we created a file format specification, CH3, that addresses these

problems by vastly decreasing the file size for modified base data. Analyses presented

here show that CH3 typically reduces file sizes by 95%. These reductions come from a

number of sources, including the removal of redundant and unnecessary data fields,

efficient compression algorithms, and careful selection of data types. File access and read

times are also improved by using column-based storage and internal indexing.

Importantly, the file specification is designed to be used with any modification code and

allows users to add additional columns as needed to address specific use cases and future-

proof the format. Thus, this file format will provide a strong foundation for future studies

on nucleotide modifications.

We also present in this paper the first R package designed specifically for use with native,

modified base calling. We have also incorporated a large number of functions to access

and interact with the data, measure QC, and conduct differential methylation analyses on

positions, sliding windows, annotated regions, or reads. As we look to the future, our

team plans to further enhance ModSeqR's analytical capabilities by integrating

sophisticated machine learning algorithms, such as k-Nearest Neighbors (KNN) and

regularized regression models, further advancing modified base analysis in various use

cases[17].

By dramatically reducing data storage requirements and offering an accessible, purpose-

built R package, our work lowers key technical barriers that have limited the broader

adoption of third-generation sequencing for epigenomic research. As the field continues

to evolve, we anticipate that these tools will not only accelerate discovery but also inspire

the development of new methodologies for understanding the biological roles of modified

nucleotides in health and disease.

Conclusions

The CH3 file format and the ModSeqR R package introduced in this study represent important advances for analyzing native DNA modifications using third-generation sequencing. By addressing key challenges in data size, accessibility, and analytical flexibility, these tools enable researchers to efficiently store, manage, and analyze high-throughput methylation data across a range of hardware configurations. The CH3 file format significantly reduces storage demands while preserving analytical utility, and ModSeqR provides a comprehensive and user-friendly R-based framework for differential methylation analysis, quality control, and visualization. Together, they remove critical technical barriers and empower broader use of native nucleotide modification data across biological research. As interest in epigenetic mechanisms continues to expand, these tools will serve as a foundational platform for scalable, accessible, and reproducible studies of DNA methylation and other base modifications in both health and disease contexts.

Methods

CH3 File Specification

To address the challenges of storing large-scale native base modification data, we developed the CH3 file format—a compressed, columnar format based on Apache Parquet. CH3 includes required fields such as read ID, chromosome, position, modification type, and probability, and supports additional optional metadata. File

reduction is achieved via dictionary encoding and Zstandard compression, both natively

implemented as part of the Parquet standard. The format also supports fast, column-based

access and is compatible with ModSeqR and common data science tools (e.g., DuckDB,

PyArrow). Full specification details, including field definitions and encoding rules, are

available at the public GitHub repository https://github.com/Wasatch-Biolabs-Bfx/CH3.

Additionally, a website has been developed for package explanation, a vignette, and

function definitions at https://wasatch-biolabs-bfx.github.io/ModSeqR/.

ModSeqR Implementation

ModSeqR is implemented in R and SQL and structured around modular functions that

facilitate scalable, memory-efficient analysis of native base modification data. At its core,

the package uses a DuckDB backend to support disk-based storage and efficient SQL-like

querying of CH3-formatted data. Key functions are organized into workflow stages,

including database creation (create_ch3_database()), read filtering (filter_ch3_reads()),

summarization (summarize_ch3_positions(), summarize_ch3_windows(),

summarize_ch3_regions()), and differential methylation analysis (calc_ch3_diff()).

Additional tools provide sample correlation (calc_ch3_samplecor()), read classification

(classify_ch3_reads()), quality control, and dimensionality reduction via PCA. Each

function is optimized to perform reliably on systems with limited RAM and supports both

single-sample and multi-sample analysis workflows. Extensive helper functions manage

database connections, cleanup, and internal metadata. ModSeqR supports piping syntax

and outputs tidy data frames, making it highly compatible with the broader tidyverse

ecosystem. Full source code and documentation are available at:

https://github.com/Wasatch-Biolabs-Bfx/ModSeqR.

Differential methylation analysis

ModSeqR provides multiple statistical frameworks for conducting differential

methylation analysis, including logistic regression, Fisher's exact test, a rapid

implementation of Fisher's exact test (r_fisher), and the Wilcoxon rank-sum test.

Differential methylation can be assessed at individual genomic positions, sliding

windows, or predefined genomic regions. For each locus, ModSeqR computes per-

sample methylation fractions, from which group-level methylation summaries are

derived. Effect sizes are reported as the difference in modification fraction between case

and control groups, along with associated p-values.

For hypothesis testing, ModSeqR employs an adaptive test selection strategy based on the

number of biological replicates in each group. When either the case or control group

contains five or fewer samples, differential methylation significance is assessed using

Fisher's exact test applied to aggregated modified and unmodified read counts, an

approach well suited for sparse data and low replicate numbers. When both case and

control groups contain more than five samples, ModSeqR instead applies the Wilcoxon

rank-sum test to compare distributions of per-sample methylation fractions between

groups. This non-parametric test does not assume normality and leverages increased

replicate numbers to provide improved robustness and sensitivity in analyses of larger

cohorts. By dynamically selecting the appropriate statistical test based on sample size,

ModSeqR ensures accurate and well-calibrated differential methylation inference across

diverse experimental designs.

Testing Data

We created a synthetic dataset to test the accuracy of our summarization functions and

differential analysis. We hope this will also enable a fast workflow through all steps of

the package. The positions are divided into deliberately chosen effect-size bands: eight

groups with absolute methylation-fraction shifts of ±0.90, ±0.50, ±0.25 and ±0.10 (60

loci per band), and two mid-fraction bands (0.25–0.50 and 0.50–0.75; 120 loci each). We

also included randomized noise for more realistic visuals. This dataset contains two CH3

files and is also publicly available for users to create a database and test the package

under the inst/extdata/ directory in the GitHub repository.

Generation of Biological Data From Biological Data

DNA from sperm and blood samples were used to generate biologically relevant test data.

1 µg of fragmented isolated DNA was sent to Wasatch Biolabs (Heber City, Utah) for

library preparation. Libraries were then sequenced at both Wasatch Biolabs and Brigham

Young University.

All sequencing was conducted using ONT PromethION flow cells (FLO-PRO114)

according to the manufacturer's instructions. Sequencing, basecalling, and

demultiplexing were performed using MinKNOW software with live high-accuracy

basecalling selected and with 5mC and 5hmC modifications in the CpG context turned

on. Reads with a Q score less than 10 were marked as "failed" and were removed from

subsequent analysis.

Performance Benchmarking

Performance testing was conducted on two markedly different hardware configurations to

assess scalability and resource utilization. The first environment was a MacBook Pro

equipped with an M3 processor and 16 GB of RAM, representing a typical end-user

system. The second environment was a high-performance server with 250 GB of

available memory and an AMD Threadripper processor with 96 cores, providing

substantially greater computational capacity.

To compare the performance of ModSeqR to other differential methylation tools, we

utilized an HPC cluster with Slurm job scheduling. Using Apptainer, we deployed the

latest version of each package in separate containers, along with their respectively

required dependencies. Each analysis was submitted with either 16 GB RAM / 4 CPUs or

256 GB RAM / 16 CPUs via Slurm resource allocations. Wall-clock time and max

memory usage were automatically recorded for each submission.

Declarations

Software Availability and Requirements:

Project name: ModSeqR

Project home page: https://github.com/Wasatch-Biolabs-Bfx/ModSeqR

Operating system(s): Platform independent (works on Windows, macOS, and Linux

wherever R is available).

Programming language: R

Other requirements: R package dependencies include: arrow, DBI, dplyr, dbplyr,

duckdb, duckplyr, ggplot2, progress, tidyr, utils, readr (Imports). Optional for

vignettes/docs: knitr, rmarkdown (Suggests).

License: Personal and Internal Research License (v1.1) Based on PolyForm

Noncommercial License 1.0.0, with an Additional Grant of Rights (Internal Research Use

Exception) provided for internal research use by commercial entities.

Any restrictions to use by non-academics: Internal evaluation and research only.

Funding

No funding

Ethics approval and consent to participate

All human-derived materials were collected in accordance with relevant

institutional guidelines and regulations and in compliance with the Declaration of

Helsinki. Sperm samples were obtained under a protocol reviewed by the Brigham

Young University Institutional Review Board (IRB) and determined to be exempt

from IRB oversight (Protocol #A2019-349). Menstrual blood samples were

collected under a protocol approved by the Brigham Young University IRB

(Protocol #IRB2022-245). Informed consent was obtained from all participants

where applicable.

Consent for publication

Not applicable

Availability of data and materials

The dataset analyzed during the current study is available in the ModSeqR repository

through the Wasatch-Biolabs-Bfx organization, at https://github.com/Wasatch-Biolabs-

Bfx/ModSeqR. Documentation and a package vignette is publicly available on our

package website at https://wasatch-biolabs-bfx.github.io/ModSeqR/. Sequencing data is

available in the NCBI SRA database under project number PRJNA1311512.

Competing interests

JH and TJ are cofounders of Wasatch Biolabs, which is currently applying for patents for

the CH3 file format and ModSeqR package.

Authors' contributions

HZ and JH wrote the code for the ModSeqR package, as well as writing this manuscript.

RM, JM, and AJ assisted in developing the package and writing this paper. IS assisted in

writing and figure generation. ES assisted in writing and editing the manuscript. TJ

helped oversee the project and provided guidance for methylation analysis standards.

References

1.   Bilyard MK, Becker S, Balasubramanian S. Natural, modified DNA bases. *Curr Opin Chem Biol.* 2020;57:1–7. doi:10.1016/j.cbpa.2020.01.014

2.   Smith ZD, Meissner A. DNA methylation: roles in mammalian development. *Nat Rev Genet*. 2013;14(3):204-220. doi:10.1038/nrg3354

3.   Locke WJ, Guanzon D, Ma C, et al. DNA Methylation Cancer Biomarkers: Translation to the Clinic. *Front Genet*. 2019;10:1150. doi:10.3389/fgene.2019.01150

4.   Ahsan M, Ek WE, Rask-Andersen M, et al. The relative contribution of DNA methylation and genetic variants on protein biomarkers for human diseases. Greally JM, ed. *PLOS Genet*. 2017;13(9):e1007005. doi:10.1371/journal.pgen.1007005

5.   Klughammer J, Romanovskaia D, Nemc A, et al. Comparative analysis of genome-scale, base-resolution DNA methylation profiles across 580 animal species. *Nat Commun*. 2023;14(1):232. doi:10.1038/s41467-022-34828-y

6.   Pidsley R, Zotenko E, Peters TJ, et al. Critical evaluation of the Illumina MethylationEPIC BeadChip microarray for whole-genome DNA methylation profiling. *Genome Biol*. 2016;17(1):208. doi:10.1186/s13059-016-1066-1

7.   Simpson JT, Workman RE, Zuzarte PC, David M, Dursi LJ, Timp W. Detecting DNA cytosine methylation using nanopore sequencing. *Nat Methods*. 2017;14(4):407-410. doi:10.1038/nmeth.4184

8. Flusberg BA, Webster DR, Lee JH, et al. Direct detection of DNA methylation during single-molecule, real-time sequencing. *Nat Methods*. 2010;7(6):461-465. doi:10.1038/nmeth.1459

9. Athanasopoulou K, Boti MA, Adamopoulos PG, Skourou PC, Scorilas A. Third-Generation Sequencing: The Spearhead towards the Radical Transformation of Modern Genomics. *Life*. 2021;12(1):30. doi:10.3390/life12010030

10. Logsdon GA, Vollger MR, Eichler EE. Long-read human genome sequencing and its applications. *Nat Rev Genet*. 2020;21(10):597-614. doi:10.1038/s41576-020-0236-x

11. Fu Y, Timp W, Sedlazeck FJ. Computational analysis of DNA methylation from long-read sequencing. *Nat Rev Genet*. Published online March 28, 2025. doi:10.1038/s41576-025-00822-5

12. Meng Q, Chandak S, Zhu Y, Weissman T. Reference-free lossless compression of nanopore sequencing reads using an approximate assembly approach. *Sci Rep*. 2023;13(1):2082. doi:10.1038/s41598-023-29267-8

13. Akalin A, Kormaksson M, Li S, et al. methylKit: a comprehensive R package for the analysis of genome-wide DNA methylation profiles. *Genome Biol*. 2012;13(10):R87. doi:10.1186/gb-2012-13-10-r87

14.   Meyer D, Barth E, Wiehle L, Marz M. diffONT: predicting methylation-specific PCR biomarkers based on nanopore sequencing data for clinical application. Published online February 20, 2025. doi:10.1101/2025.02.17.638597

15.   Raasveldt M, Mühleisen H. DuckDB: an Embeddable Analytical Database. In: *Proceedings of the 2019 International Conference on Management of Data*. ACM; 2019:1981-1984. doi:10.1145/3299869.3320212

16.   Li L, Chen R, Zhang H, et al. The epigenetic modification of DNA methylation in neurological diseases. *Front Immunol*. 2024;15:1401962. doi:10.3389/fimmu.2024.1401962

17.   Friedman J, Hastie T, Tibshirani R. Regularization Paths for Generalized Linear Models via Coordinate Descent. *J Stat Softw*. 2010;33(1):1-22.