Shared neural geometries for bilingual semantic representations

Xinyuan Yan[1], Aaditya Krishna[1], Katie Van Arsdel[1], Ivy Gautam[1], Brian Kim[1], Aadit Shrivastava[1], James Belanger[1], Ana G. Chavez[1], Assia Chericoni[1], Melissa Franch[1], Taha Ismail[1], Kalman A. Katlowitz[1], Elizabeth A. Mickiewicz[1], Danika Paulo[1], Hanlin Zhu[1], Alica M. Goldman[2], Vaishnav Krishnan[2], Atul Maheshwari[2], Eleonora Bartoli[1,3], Nicole R. Provenza[1,3,4], Seng Bum Michael Yoo[5], Benjamin Y. Hayden*[1,3], and Sameer A. Sheth*[1,3]

1. Neurosurgery, Baylor College of Medicine
2. Neurology, Baylor College of Medicine
3. Neuroengineering Initiative and Electrical and Computer Engineering, Rice University
4. Department of Bioengineering, Rice University
5. Department of Biomedical Engineering and Intelligent Precision Healthcare Convergence, Sungkyunkwan University

Correspondence: Benjamin.Hayden@bcm.edu
* These authors contributed equally

Funding statement
>   This research was supported by the McNair Foundation and by NIH R01 MH129439, U01 NS121472, UE5NS070694-15, the SNS Allan Friedman RUNN Research Grant, the NLM Training Program in Biomedical Informatics & Data Science for Predoctoral & Postdoctoral Fellows, T15LM007093-33, Gordon and Mary Cain Pediatric Neurology Research Foundation

Competing interests
>   S.A.S has consulting agreements with Boston Scientific, Zimmer Biomet, Koh Young, Abbott, and Neuropace. SAS is Co-founder of Motif Neurotech

Acknowledgements
>   We thank Joshua Adkinson, Justin Fine, Victoria Gates, Suzanne Kemmer, George Kokalas, and Steven Piantadosi for their assistance.

ABSTRACT

The human brain has the remarkable ability to understand and express similar concepts in multiple languages. To understand how it does so, we examined responses of hippocampal neurons during passive listening, directed speaking, and spontaneous conversation, in both English and Spanish, in a small group of balanced bilinguals. We find putative *translation neurons*, whose responses to equivalent words (e.g., "*tierra*" and "*earth*") are correlated. More broadly, however, neurons' semantic tunings differed substantially by language, suggesting language-specific neural implementations. Despite this, distances between words' neural responses are preserved between the two languages, creating a shared semantic geometry. That geometry was implemented by the same neurons but along distinct readout axes; this difference in readout may help prevent cross-language interference. Shared semantic geometry with distinct readout axes is also observed in mBERT, a multi-language LLM, suggesting this may be a general computational principle for multilingual representation. Together, these results suggest that hippocampus encodes a language-independent internal model for meaning.

INTRODUCTION

Humans have the remarkable capacity to understand and express the same thoughts in multiple languages without confusing them. For example, in Arnhem Land (Northern Australia), speakers commonly manage six or seven languages (Evans, 2011). Indeed, the ability to speak fluently in more than one language is quite common among humans (Bialystok, 2017). This flexibility raises the question of how we adeptly perform multiple distinct sound-meaning mappings. A growing body of evidence suggests that bilingual speakers use at least partially shared neural substrates for each of their languages. For example, in fMRI with listening or reading, bilingual brains show broadly overlapping language-network responses across languages (Abutalebi & Green, 2007; Brignoni-Pérez et al., 2022; Cao et al., 2013; de Varda et al., 2025; Klein et al., 1995; Hengshuang Liu & Cao, 2016; Hongyan Liu et al., 2010; Malik-Moraleda et al., 2022; Sulpizio et al., 2020; Tan et al., 2003). Even constructed languages (e.g., Klingon and Na'vi) reliably recruit the same brain areas as natural languages (Malik-Moraleda et al., 2025). However, these findings do not tell us *how* the brain matches corresponding concepts between languages while simultaneously maintaining a functional separation.

We hypothesized that the bilingual brain uses shared neural geometry for representing meaning (the "*shared semantic geometry*" hypothesis) in both languages. That is, the brain may have similar sets of coding distances between all pairs of words in high-dimensional neural space. Thus, if "*cat*" and "*dog*" elicit similar neural activation patterns and "*door*" is dissimilar, then "*gato*" and "*perro*" should evoke similar neural activation patterns, and "*puerta*" will be dissimilar. Indeed, this is the strategy used by multilingual LLMs, such as mBERT, and it allows

corresponding words to be directly mapped between languages (Artetxe & Schwenk, 2019; Pires et al., 2019).

A small body of neuroimaging work provides support for the idea that the brain may employ shared semantic geometry. In particular, a recent neuroimaging study shows that voxelwise encoding models trained to predict neural activity from language-model embeddings (e.g., mBERT) in one language can transfer across languages within the same bilingual participants (Chen et al., 2024). Several fMRI studies also show cross-linguistic generalization across different monolingual groups who listened to translations of the same story (de Varda et al., 2025; Dehghani et al., 2017; Zada et al., 2025), so that encoding models trained on neural responses from speakers of one language predict neural responses to the translated story in a different group speaking another language (de Varda et al., 2025; Dehghani et al., 2017; Zada et al., 2025). One study used electrocorticography (ECoG), which provides dense sampling of local field potentials (LFPs), with corresponding bilingual speech in one bilingual patient (Silva et al., 2024). This study found shared articulatory codes sufficient for cross-language decoding, although it did not investigate semantics. Moreover, none of these studies directly examined whether the *shared semantic geometry* (i.e., representational geometry of semantics) exists nor the computational principles underlying how meanings are organized in the bilingual brain.

If shared semantic geometry provides the scaffolding that links language to meaning, an important next question is how different languages access this common structure. Do they use identical or distinct neural readouts to reach the shared semantic geometry? The properties of representational geometry (Kriegeskorte & Kievit, 2013; Kriegeskorte & Wei, 2021) suggest that rotations of neural axes preserve pairwise relationships, leaving the overall geometric structure

invariant. As a result, the bilingual brain could access the same semantic geometry through language-specific readout axes. Prior research has mostly emphasized how control regions suppress one language to prevent interference (Calabria et al., 2018; Crinion et al., 2006) but has offered little insight from the perspective of single neuron encoding of semantics. In motor cortex, rotation of neural activity planes enables the same population to produce diverse reaching movements (Sabatini & Kaufman, 2024). Motivated by that work, we reasoned that an analogous process may occur in language, wherein rotated neural axes may themselves provide an intrinsic mechanism that keeps languages from interfering.

We are particularly interested in the hippocampus, which has a clear role in language, especially in encoding word meanings (Binder et al., 2009; Brown-Schmidt et al., 2001; Chavez et al., 2025; Dijksterhuis et al., 2024; Duff & Brown-Schmidt, 2012; Franch et al., 2025; Karkowski et al., 2025; Katlowitz et al., 2025; Piai et al., 2016; Van De Ven et al., 2020). That role in turn is likely part of a broader role in flexibly representing and linking concepts (Bakermans et al., 2025; Bakker et al., 2008; Bernardi et al., 2020; Courellis et al., 2024; Leutgeb et al., 2005; Rodrigo Quian Quiroga, 2012; Yassa & Stark, 2011). Our laboratory has demonstrated that single neurons in the hippocampus track meanings of words during both listening and monolingual speech production (Chavez et al., 2025; Franch et al., 2025; Katlowitz et al., 2025). Together, these findings suggest that hippocampal neurons form a high-dimensional *semantic geometry* in which the distances between neural activity patterns correspond to the relationships between word meanings.

We recorded single-unit activity from the hippocampus in a rare sample of four fully bilingual (English/Spanish) patients with treatment-resistant epilepsy. Using high-density

microelectrodes (N=3) and a Neuropixels probe (N=1), we recorded single units across three studies: (1) passive listening to matched stories in English and Spanish (~120 minutes each), (2) reading and speaking matched phrases in English and Spanish (using the task developed by Silva et al, 2024), and (3) unconstrained, naturalistic conversations with English and Spanish conversation partners, respectively. Overall, we find evidence of a *shared semantic geometry* that is common to both listening and speaking and that is preserved across the three tasks. We also find a small group of *translation neurons*, whose responses to co-translated words (such as "*friend*" and "*amigo*") are highly correlated in both domains. Notably, however, these neurons were rare. Likely much more important for translation was the observation of a shared geometry between languages. However, despite the shared semantic geometry, individual neurons' semantic tuning curves differed substantially between English and Spanish. Moreover, each language constructs its semantic geometry through distinct readout configurations of the same neurons. Parallel analyses of mBERT revealed the same organizational principle: shared semantic geometry across languages and rotated semantic readout axes. Together, these results clarify how bilingual brains represent shared meanings and suggest a readout-based approach to avoiding interference.

RESULTS

We recorded responses of single neurons in the hippocampus of four bilingual individuals undergoing neurosurgical procedures (**Figure 1A**). All patients acquired both English and Spanish in early childhood (ages 4-5), used both regularly, and were fully balanced bilinguals. Bilingualism was also confirmed informally through conversations in both English and Spanish with both caregivers fluent in each language and by family members. Patients 1-3 underwent stereo-electroencephalography (sEEG) for seizure detection in the epilepsy monitoring unit with an implant strategy that included microelectrodes (AdTech Behnke-Fried) in the hippocampus. Patient 4 underwent anterior temporal lobectomy for medically refractory epilepsy under general anesthesia. Following resection of the neocortex, we recorded from the exposed hippocampus using a Neuropixels probe prior to the hippocampal resection.

All patients performed a passive listening task with equivalent speech in English and Spanish (**Figure 1B**, 603 neurons; Stimulus set *K*: 4530 English words, 4375 Spanish words; Stimulus set *A*: 4855 English words, 4745 Spanish words, **Figure 1C**). Two patients (patients 2 and 3) also performed a speech production task in both languages (74 neurons total) in which they saw 99 matching phrases in English and Spanish (198 phrases total) on a computer screen and had to say those words out loud (same task and stimuli as Silva et al., 2024). In all cases, phrases in English and their translations in Spanish were used (**Figure 1D**). These two patients also performed a conversation task (Chavez et al., 2025) twice, once in each language (**Figure 1E**). Specifically, these two participants took part in conversations in English (durations: 51.37 and 45.5 minutes) and in Spanish (32.42 and 99.98 minutes). Word-level, time-aligned transcripts of the listening and speaking content were produced by combining automated

transcription with manual correction in Praat (Boersma, P. 2001) by trained lab members (**Figure 1F**, see **Methods**).

Figure1. Experimental design for single-neuron recordings during bilingual language processing in the human hippocampus.

(A) Schematic of recording setup showing bilateral human hippocampus with microelectrode. Green regions indicate recording locations. Inset shows Neuropixels probe configuration used in Patient 4 and microelectrodes cohort configuration used in Patients 1-3.

(B) Study 1: passive listening task. Stimulus set K (~60 minutes, from *"kurzgesagt"*) comprises three nature-themed narratives (K1 = "dark forest", K2 = "deep sea", K3 = "true limits"). Stimulus set A (~60 minutes) consisted of selected excerpts (~60 minutes total) from an audiobook (*"eat, pray, love"*) presented across three separate recording sessions (A1, A2, and A3, recorded on consecutive days; A1 = intro & book i, A2 = book ii, A3 = book iii & iv). Each stimulus set was presented in both English and Spanish versions. Single-neuron recordings yielded 172 neurons from Patient 4 under anesthesia (Neuropixels probe, stimulus KN), 105 neurons from Patients 1-3 (microelectrodes, stimulus K), and 103, 96, and 127 neurons for stimulus A1, A2, and A3, respectively (from Patients 2-3, microelectrodes).

(C) Two stimulus sets used for Spanish-English bilingual participants. Word count distributions for stimulus sets K and A showing comparable totals across languages (Set K: 4530 English words, 4375 Spanish words; Set A: 4855 English words, 4745 Spanish words). Overall language distribution pie chart showing 50.7% English and 49.3% Spanish content, show perfect language balance.

(D) Study 2: read aloud task. Two bilingual patients (Patients 2 and 3, microelectrodes recordings) viewed and spoke aloud 99 matched short phrases (3-4 words per phrase) in both English and Spanish (198 total phrases). Example shown: "let's have fun" (English) / "vamos a divertirnos" (Spanish). A total of 74 neurons were recorded across both patients.

(E) Study 3: naturalistic conversation task (lasting 32-99 minutes). Two bilingual patients (Patients 2 and 3, microelectrodes recordings) engaged in unconstrained conversations lasting 60-90 minutes per session with English and Spanish native speakers. Recordings yielded 56 neurons across both patients. During the conversation, Patient 2 listened to 4552 English words and 1645 Spanish words, and spoke 2771 English words and 1537 Spanish words. Patient 3 listened to 2880 English words and 1926 Spanish words and spoke 5901 English words and 8520 Spanish words.

(F) Precise audio-text alignment. Top panel: audio waveform of sample English/Spanish texts. Middle panel: corresponding spectrogram (0-6 kHz) with word boundaries; timestamps are accurate to within 100 ms relative to consensus manual annotations. Bottom panel: example single-neuron responses from three simultaneously recorded cells showing firing rates. Time axis shows milliseconds relative to first word onset for both English (right, blue) and Spanish (left, red) text.

Abbreviation: Pt. = Patient.

A small number of translation neurons

We first asked whether neurons show similar responses to co-translated words across language. We initially tried cross-language word-by-word alignment using two open-source software packages (GIZA++ and fast_align) but found their alignments to be insufficiently accurate. We therefore performed a manual English-Spanish alignment (example, **Figure 2A**). To align, we identified words with similar meanings and excluded from analysis words without corresponding meanings. For example, part of the English text in Stimulus set A reads "*When you're travelling in India…*" and is translated as "*Al viajar por India…*" In this context, "*When*" and "*Al*" have similar, but not identical, meanings, and were aligned (that is, treated as co-translated pairs). In contrast, "*you're*" does not have an equivalent word in the Spanish translation and therefore was excluded from the analysis. Meanwhile, "*travelling*" and "*viajar*" have corresponding meanings but different conjugations; given our focus here on semantics over grammar, they were included as co-translated words.

Example responses (**Figure 2B**) illustrate neurons that show comparable evoked responses to co-translated words across languages. The blue (English) and red (Spanish) peristimulus time histograms (PSTHs) rise and fall on similar time. For each neuron, we correlated its firing rates for all English words with the firing rates for the matched Spanish words. Example units (Patient 1, microelectrodes; Patient 4, Neuropixels) showed significant positive relationships across thousands of matched items, indicating that words that elicit above-average (e.g., "*friends*"/"*amigos*") or below-average (e.g., "*and*"/"*y*") firing rates in English tend to do so in Spanish as well (**Figure 2C**).

These neurons have similar response profiles to matched words across languages, suggesting they may play a special role in cross-language understanding by representing meaning regardless of language. To systematically identify putative *translation neurons*, we computed a Pearson correlation across all matched words for every neuron (e.g., for stimulus set K, n=3457 matched words for Patients 1-3; n=1252 matched words for Patient 4) and used a binomial test to determine whether the proportion of significant correlations exceeded chance levels (**Figure 2D**, **Methods**). A small number of neurons with zero firing rates across all words in either language was excluded (n=1 in dataset A3, listening task; n=1 in read aloud task).

A subset of neurons met the translation neuron criterion (**Figure 2E**). The largest fraction of these was in dataset A1 (Audiobook Introduciton and Chapter 1, 2 patients, microelectrodes; 20 out of 103 valid neurons, 19.4%, this proportion is significant by binomial test, p<0.001; chance level: 2.5%). Smaller fractions were observed in dataset K (podcast, 3 patients, 6 out of 105 valid neurons, 5.7%, p=0.04; note this proportion is significant because the false positive rate is 2.5%), dataset A2 (Audiobook, Chapter 2, 2 patients, 11 out of 96 valid neurons, 11.5%, p<0.001), dataset A3 (Audiobook, Chapters 3-4, 2 patients, 8 out of 126 valid neurons, 6.3%, p=0.01), and in Neuropixels recordings under anesthesia (podcast, 1 patient, dataset KN-Neuropixel, 9 out of 172 valid neurons, 5.2%, p=0.02). In contrast, we found essentially no evidence for "anti-translation" neurons (i.e., neurons with significant negative correlations between neural responses for matched words across languages). In the entire dataset for listening, we observed 13/105 such neurons in stimulus set K (12.4%, p<0.001) but not in other datasets (A1, A2, A3, KN-Neuropixel: all p>0.25). Likewise, the proportion of anti-translation neurons was insignificant in the speech production task; n=0/73 neurons; p=1. The lack of *a*

priori equally likely anti-translation neurons in all datasets supports the idea that translation neurons, while rare, are not simply a statistical artifact.

We found translation neurons for speaking as well as for listening. The example neuron shown in **Figure 2F** had correlated firing across 99 translation-matched phrases (r = 0.22, p = 0.02). At the group level, 5 neurons out of 73 valid neurons (6.8%, p=0.03) exhibited significant cross-language similarity during production. When analyzed at the word level during speech production, a much larger proportion of neurons (61 out of 73 valid neurons, p < 0.001) exhibited significant cross-language similarity. Here, the chance level corresponding to p=0.05 is 2.5%, because we used a two-tailed t-test to identify the neurons with positive correlation. Note that sessions of the listening task (Study1) were collected on different days, so we cannot tell if the same translation neurons contribute to speaking and listening. In Study 3 (naturalistic conversation), word-matched firing-rate analysis was not possible due to differing conversational content and word counts between languages (**Figure 1E**). Even shared function words like "*and*"/"*y*" will necessarily have different contextual meanings, preventing the one-to-one alignment across languages required for this analysis.

At the patient level, combing all available data (i.e., the data from Study 1 and Study 2), all four patients displayed above-chance proportions of translation neurons (Patient 1: 3/31, 9.6%, p =0.04, Patient 2: 18/237, 7.6%, p < 0.001, Patient 3: 26/235, 10.25%, p < 0.001, Patient 4 (Neuropixels), 9/172 valid neurons, 5.2%, p=0.02). Collectively, these results demonstrate that small subsets of hippocampal neurons generalize semantic content across languages.

Figure 2. Cross-language single-neuron firing-rate similarity across matched items in passive listening and speech production.

(A) Word-to-word alignment mapping between English (left) and Spanish (right) translations. Purple lines connect semantically equivalent words across languages. Numbers indicate word order in each language. Only matched items enter the scatter/correlation analyses below.

(B) Peristimulus time histograms (PSTHs) from example neurons. For each panel, top: average response (firing rate, Hz) to 50 matched words in English (blue traces) and Spanish (red traces), bottom: Raster plots below each trace show word-wise spikes.

(C) Pearson correlation analysis of firing rates for matched word pairs. Top: Pt. 1 neuron #3 (microelectrodes) showing strong correlation between English and Spanish firing rates for 3457 matched words (r = 0.07, p < 0.001). Bottom: Pt. 4 neuron #37 (Neuropixels) displaying similar language-invariant responses across 1252 matched words (r = 0.08, p < 0.01). Each dot is one matched word pair, x-axis is the unit's firing rate in English, y-axis represents the unit's firing rate in Spanish. For visualization, several items are annotated (e.g., *friends/amigos*, *life/vida*). Shaded regions represent +/- SEM.

(D) For each neuron, we computed the Pearson correlation between firing rates across translation-matched English-Spanish word pairs and assessed significance with a one-tailed permutation test (positive direction; 1000 shuffles of Spanish indices). We then counted neurons with r>0 and two-tailed permutation p<0.05 and tested whether this fraction exceeds chance using a right-tailed binomial test with (p_0 = 0.025).

(E) A set of "translation neurons" across all stimulus conditions. Pie charts show the proportion of neurons exhibiting significant cross-language similarity for each stimulus set (purple), with grey portions indicating the expected 2.5% false positive rate under the null hypothesis of no cross-language positive relationships. Stimulus set K: 6 out of 105 valid neurons, 5.7%, p=0.04. Stimulus set A1: 20/103 neurons (19.4%). Stimulus set A2: 11/96 neurons (11.5%). Stimulus set A3: 8/126 neurons (6.3%). Stimulus set KN: 9/172 neurons (5.2%, p=0.02, Neuropixels under anesthesia). One excluded neuron (in A3) shown with zero firing rates (preventing correlation analysis) in either language.

(F) A set of "translation neurons" during speech production (Study2, read aloud task). Example neuron from Pt. 2 shows correlated firing patterns when patient was speaking matched English-Spanish phrase pairs (n = 99 phrases, r = 0.22, p = 0.03). Example phrases shown with English words in blue and Spanish translations in red. The pie chart indicates that 5/73 neurons (6.8%) showed significant cross-language similarity at the phrase level, while 61/73 neurons (83.6%) demonstrated stronger cross-language similarity at the word level during speech production. One neuron with zero firing rates in either language was excluded. Shaded regions represent +/- SEM.

(***p<0.001, **p<0.01, *p<0.05).

Abbreviation: Pt. = Patient.

English-Spanish tuning profiles rarely align at the single-neuron level

Individual neurons respond systematically to word meanings with *semantic tuning functions* (Chavez et al., 2025; Franch et al., 2025; Jamali et al., 2024). This raises the question of whether neurons have matching tuning functions across languages. To answer this question, we first extracted contextual word embeddings using multilingual BERT (mBERT, **Figure 3A**, **Methods**), a transformer model trained on 104 languages that learns cross-linguistic representations through masked language modeling (Devlin et al., 2019).

For stimulus set A, we combined excerpts from the audiobook presented across three recording sessions (A1, A2, A3). Sentences were tokenized using mBERT preserving their original narrative sequence (**Methods**). For every matched translation pair (e.g., *"dog"/ "perro"*), we calculated the correlation between English and Spanish word embeddings (768-dimensional vectors from mBERT itself, not neural data) at each mBERT layer and computed the average correlation across words (**Methods**). Layer 11 (out of 13) yielded the highest cross-language similarity (**Figure 3B**). This result is consistent with reports that deeper layers carry semantic information and yield stronger cross-lingual alignment (Mousi et al., 2024). We therefore used layer 11 embeddings for Study 1 and Study 3, as these involved words presented within sentences and narrative passages where contextual information influences word meaning. For Study 2 (read aloud task), where single words or short phrases were presented in isolation (i.e., without any surrounding sentence or discourse context), we used static Word2Vec (Mikolov et al., 2013) embeddings (300 dimensions for each word **Figure 3C**, **Methods**).

Semantically selective neurons could operate in two ways in a bilingual brain: language-invariant tuning, where the neuron uses similar semantic weights for both languages (high

correlation between English and Spanish tuning vectors). Alternatively, tuning could be language-specific, meaning the neuron uses different semantic weights for each language (low correlation between English and Spanish tuning vectors). To test these possibilities, we first projected both languages' embeddings (768 dimensions from mBERT; 300 dimensions from Word2Vec) into a common space by concatenating English and Spanish embeddings and applying joint PCA, retaining 100 principal components (**Figure 3D**). This approach ensured both languages were projected onto identical semantic axes.

To validate this shared PCA space, we conducted two control analyses. First, for each shared component, we computed the fractional contribution of each language to the total variance explained by that component, which yielded nearly balanced contributions (English = 0.518; Spanish = 0.482). Second, we confirmed that each principal component derived from the joint PCA showed a strong correlation between English and Spanish scores (average correlation = 0.632, all PCs, $p < 0.001$), indicating that both languages aligned along the same semantic axes. Together, these results suggest that the shared PCA captured common axes for both languages.

For every neuron, we then fit ridge regressions mapping these shared semantic features to firing rates separately for English and Spanish. To avoid overfitting, we selected a single ridge penalty (λ) per neuron via 5-fold cross-validation that minimized the average normalized error across both languages (see **Methods**). A neuron's cross-language tuning similarity was defined as the Pearson correlation between its English and Spanish tuning profiles (i.e., the tuning vectors across the shared PCA components from ridge regression). Significance was assessed by 1000-fold permutation test (**Figure 3E**).

Significant correlations between English and Spanish tuning curves were rare, indicating that neurons do not generally have matching overall tuning in the two languages. Example neurons (**Figure 3F, G**) illustrate minimal cross-language tuning alignment, with correlations that are either non-significant (for positive correlation) or negative. Across all stimulus sets, only KN-Neuropixel and A2 had a significant proportion of neurons with positive cross-language tuning alignment, and these proportions were low (KN-Neuropixel: 10/172 neurons, 5.8%, $p=0.01$; A2: 7/96 neurons, 7.3%, $p=0.01$; all other stimulus sets: $p > 0.12$). Thus, the great majority of hippocampal neurons employ language-specific semantic tuning.

We next asked whether the divergence in tuning curves between English and Spanish was greater than expected by chance. For each study (Study1, listening; Study2: read aloud; Study 3: conversation) separately, we split the English and Spanish words into two halves (independently, 1000 random splits), refit ridge weights on each half, and computed within-language split-half tuning curve correlations per neuron. The mean value cross-language tuning correlation fell at the extreme left of the within-language tuning curve correlation distribution (near the 0.3 percentile). Cross-language tuning profile correlations were significantly lower than the within-language tuning profile correlation (Wilcoxon signed-rank test for all stimuli sets. All z-value < -2.20, all $p <0.02$; **Figure 3H-J**). This finding indicates that observed cross-language tuning is not only nonsignificant but also well below what would be expected by chance given the noise properties of our data. In short, semantically tuned neurons have significantly different tuning for semantics in English and Spanish.

We further examined the differences in the across-language tuning correlations from translation neurons and non-translation neurons. We hypothesized that translation neurons would

exhibit stronger cross-language tuning profile correlations than others. The results supported our hypothesis. The translation neurons (n=115) showed significantly higher cross-language tuning similarity (mean = 0.02, SD = 0.12) compared to non-translation neurons (n=560, mean = -0.01, SD = 0.15). Due to significant variance in heterogeneity between groups (Levene's test: p = 0.007), we employed Welch's t-test, which revealed a statistically significant difference (t(192.7) = 2.16, p = 0.03, Cohen's d = 0.19), indicating a small but meaningful difference between the two populations. The translation neurons exhibited positive cross-language correlation on average, suggesting preserved semantic tuning across languages, while non-translation neurons showed slightly negative correlation, likely reflecting a downward bias introduced by the selection criterion (i.e., regression-to-the-mean).

Figure 3. Semantic embeddings and tuning curves similarity at a single neuron level.

(A) Multilingual BERT (mBERT) architecture and contextual embedding extraction pipeline. We extracted 768-dimensional contextual embeddings from all 13 transformer layers (plus embedding layer 0) of mBERT (bert-base-multilingual-cased) for complete English and Spanish transcripts.

(B) Cross-language correlation (purple curves; two stimulus sets: K = *Kurzgesagt* podcasts; A = audiobook) rises with depth and peaks at layer 11, which we therefore used in all analyses in passive listening (Study1) and conversation (Study3). All layers' cross-language similarity is higher than the cross-language similarity based on baseline embeddings using untrained versions of the same models with identical architectures but randomized weights (i.e., the black dot line in the bottom).

(C) Token embeddings for context-independent items (Study 2, read aloud task). In the speech production task, phrases are presented without sentential context, so we represent matched items with 300-dimension word2vec embeddings.

(D) Fitting tuning curves in a shared semantic coordinate system.
English and Spanish words' embeddings from each dataset are concatenated and projected onto a joint PCA, yielding a 100-PC shared basis.

(E) For each neuron and each language separately, we fit ridge regression from the 100 PCs of all words to firing rates of all words, selecting λ by 5-fold cross-validation. The resulting beta is the neuron's semantic tuning curve for that language (for each neuron, there are 100 β (i.e., 100 tuning vectors) for English, and 100 β for Spanish). Across-language tuning curve similarity of each neuron was defined by the Pearson correlation between English and Spanish tuning curves.

(F) Different tuning preferences across languages in the example neurons. Bars show β weights across the 100 shared PCs for two representative neurons (left panel from example "translation" neuron, right panel from example "non-translation" neuron). Neuron-wise English-Spanish tuning curve correlations are not significant.

(G) Cartoon illustration to explain different tuning preferences across languages but may result in similar firing rates. Left: English and Spanish use different readout directions in the semantic PC1-PC2 plane; Right: projections of the *same words* onto those directions are nevertheless similar, yielding similar firing rates. This visualizes "output-similar does not mean recipe-identical": firing rates similarity across languages can arise from different weights of semantic components.

(H, I, J) Mean value of across-language tuning curves similarity (purple vertical ticks) of all neurons compared with within-language tuning curves similarity in (H) passive listening (Study1), (I) speech production (Study2), and (J) naturalistic conversation (Study3). Histograms show the distribution of within-language tuning curve similarity. Across all tasks, the across-language tuning curve similarities are far below the within-language similarity, demonstrating that tuning curves were not well aligned at the single-neuron level.

Population geometry preserves cross-language semantic structure

The results so far suggest that what carries meaning is the pattern across many neurons for each word. Pairwise distances and angles can define a stable representational geometry even if individual neurons' tuning functions re-mix or rotate (Kriegeskorte & Kievit, 2013; Kriegeskorte & Wei, 2021). We next sought to quantify the semantic geometry, or relative layout of words, so that we can test whether the *semantic geometry* living in hippocampal neuronal population activity is shared across English and Spanish. We utilized representational dissimilarity matrices (RDMs), which capture the pairwise distances between word representations and are invariant to axis swaps, rotations, and linear remixing (Diedrichsen & Kriegeskorte, 2017; Kriegeskorte et al., 2006; Kriegeskorte & Wei, 2021). These transformations (e.g., rotation) can change single-neuron tuning functions without altering the population geometry, making RDMs ideal for testing whether English and Spanish maintain the same semantic geometry despite neurons having unrelated tuning functions.

For both languages, we constructed RDMs from populational hippocampal neural activity by concatenating word-evoked firing-rate vectors across neurons and computing pairwise cosine distances (hereafter referred to as "*neural semantic maps*") among words. In parallel, we computed mBERT RDMs from mBERT Layer 11 embeddings of the same words ("*LLM semantic maps,*" **Figure 4A-F** and **Methods**). We aimed to answer two questions: first, how similar is the *neural semantic map* to the *LLM semantic map* (brain-model alignment), which would establish how well artificial neural networks capture biological semantic representations; second, how similar is the *neural semantic map* across English and Spanish within the brain (cross-language neural RDM correlation), which would reveal fundamental computational principles for meaning or semantic construction.

We used Spearman tests to analyze representational similarity, following best practices (Nili et al., 2014), because Spearman rank correlation makes fewer assumptions about the relationship between neural and model RDMs. Brain-model alignment was significant within both languages. This extends previous findings from an independent dataset showing significant alignment in English alone (Franch et al., 2025). Specifically, across datasets in Study 1 (microelectrodes cohorts, K, A1, A2, A3 and Neuropixel cohort KN), the *neural semantic map* significantly correlated with the *LLM semantic map* (Spearman's rho = 0.132-0.263, all p < 0.001, permutation test; **Figure 4G**). This alignment demonstrates that word pairs that are distant in the *LLM semantic map* (e.g., "*human*" and "*galaxy*") are also distant in the *neural semantic map*, while close word pairs (e.g., "*cat*" and "*dog*") in the *LLM semantic map* would be close in the *neural semantic map*. These alignments are robust in both English and Spanish. Study 3 (conversation) showed similar brain-model alignment, despite using different sets of words: correlations were significant during listening (Spanish: Pt. 2, r = 0.179, Pt. 3, r = 0.128; English: Pt. 2, r = 0.148, Pt. 3, r = 0.093) and speaking (Spanish: Pt. 2, r = 0.197, Pt. 3, r = 0.136; English: Pt. 2, r = 0.153, Pt. 3, r = 0.089), all p < 0.001 (**Figure 4H**). Together, these results confirm that the hippocampus and mBERT share semantic geometry both for English and Spanish.

Figure 4. Neuronal population semantic geometry preserved across English and Spanish.

(A) Construction of LLM semantic map. Word embeddings from mBERT (layer 11, 768 dimensions per word, shown as triangular markers) are used to compute pairwise cosine distance matrices for each language. These matrices capture semantic relationships between all word pairs, quantifying how semantic geometry is organized within each language. Matrix dimensionality: $n \times (n - 1)/2$, where n = number of words.

(B) Multidimensional scaling (MDS) visualization of LLM semantic map for words from the example sentence. In Spanish: "competitivas y expansionistas culturas expanden deprisa y más", in English: "competitive and expansionary cultures expand faster and further". Gray lines represent distances between word pairs. Semantic geometry constructed from mBERT embeddings shows that words with close semantic distances in English maintain similar relationships in Spanish (e.g., "competitive", "expansionary", "cultures" cluster together, as do "competitivas", "expansionistas", "culturas"). Example sentence is from the podcast stimulus *K*.

(C) Construction of neural semantic map. Pairwise neural distance matrices are computed from population firing rate vectors (neurons shown as circles) using cosine distance. The resulting matrices capture how the neural population differentiates between words: the more dissimilar two words are, the larger their distance in neural space. Matrix dimensionality: $n \times (n - 1)/2$, where n = number of words.

(D) Multidimensional scaling (MDS) visualization of neural semantic map for words from the example sentence. Neural population geometry shows that neurons organize words using similar patterns in English and Spanish. For instance, the relationships between "expanden", "culturas", and "deprisa" mirror those between "spread", "cultures", and "further" in English.

(E) Schematic illustrating the relationship between LLM semantic map and neural semantic map analyzed in panels G-H. If "cat-dog" are close in semantic space, they also tend to be close in neural space, appearing near the diagonal line in the rightmost panel. This correspondence suggests that the neural population geometry in the hippocampus preserves the semantic structure captured by the LLM-mBERT.

(F) Distance matrix correlation computation. Semantic distance matrices (green, from word embeddings) and neural distance matrices (purple, from population responses) are vectorized and correlated using Spearman correlation. High correlations indicate that the semantic geometry in neuronal space preserves the semantic geometry in LLM-mBERT. Vector length: $n \times (n - 1)/2$, where n = number of words.

(G) Brain-model alignment in passive listening (Study 1). Scatter plots show correlations between words distances in LLM-mBERT space (x-axis) and neural space (y-axis) for datasets K, A1, A2, A3, and KN-Neuropixel. All datasets show significant positive correlations (r = 0.114-0.237, all p < 0.001), demonstrating that if "*dog*" and "*cat*" have a close distance in LLM-mBERT space, they also have a close distance in neural space, while "*galaxy*" and "*human*", if distant in semantic space, are also distant in neural space. This result exists in both English and Spanish contexts. Each point reflects how similarly two words are represented in both LLM-mBERT and neural semantic geometries. A positive correlation indicates that word pairs close in LLM-mBERT space tend to evoke similar neural responses in neural space (red: Spanish word pairs, blue: English word pairs).

(H) Brain-model alignment in naturalistic conversation (Study 3). Word distances in neural space aligned to the words distances in LLM-mBERT during listening (Spanish: Pt. 2 r = 0.179, Pt. 3 r = 0.128; English: Pt. 2 r = 0.148, Pt. 3 r = 0.093) and speaking (Spanish: Pt. 2 r = 0.197, Pt. 3 r = 0.136; English: Pt. 2 r = 0.153, Pt. 3 r = 0.089), all p < 0.001.

(***p<0.001, **p<0.01, *p<0.05).

RDM=representational dissimilarity matrix (by cosine distance)

LLM=large language model.

Crucially, the *neural semantic map* was preserved across languages (example see **Figure 5A-B**). We directly compared the neural RDMs of the two languages by correlating pairwise neural distances between words in English with the corresponding pairwise neural distances between their Spanish translations across all matched word pairs. We found significant positive correlations for all passive listening datasets (rho = 0.255-0.477, all p < 0.001), with strongest alignment in dataset K (rho = 0.477; **Figure 5C&D** & **Method**). The dense clustering along the diagonal in 2D histograms illustrates that word pairs maintaining specific distances in English neural space reflect similar distances in Spanish neural space. Cross-language alignment remained reliable in Study 2 (rho = 0.247, p < 0.001; **Figure 5E&F**). Permutation controls show that shuffled Spanish word labels produced null distributions centered near zero, with observed correlations falling far outside these distributions for both passive listening and speech production (all z-value>3.0, all p <0.001; **Figure 5D, F**). This confirms that cross-language semantic geometry alignment reflects semantic content rather than statistical artifact.

We also compared cross-language RDMs derived from mBERT embeddings. Given the strong brain-model alignment observed within each language (Figure 4G&H), it is unsurprising that mBERT exhibited similarly high correlations between English and Spanish RDMs (rho = 0.651 for K; rho = 0.620 for KN; rho = 0.504 for A1; rho = 0.467 for A2; rho = 0.529 for A3; all p < 0.001). These results indicate that both hippocampal activity and mBERT representations preserve comparable cross-linguistic geometric structures.

Local geometric structure enables cross-language prediction

Previous studies have used learned encoding weights between word embeddings and neural responses to predict neural activity in another language (Chen et al., 2024; de Varda et al.,

2025; Zada et al., 2025). However, none have tested whether such prediction is possible at the single-word level. This question is crucial, because when learning a new language, we can often infer the meaning of an unfamiliar word from its context, even without explicit translation knowledge. For example, in English we know that "*dog*" and "*wolf*" are close in meaning, while both are far from "*fork*". When encountering the Spanish sentence "*El tenedor está en la mesa, pero el lobo y el perro están afuera*" ("*The fork is on the table, but the wolf and the dog are outside*"), even without knowing "*perro*", we can infer from its clustering with "*lobo*" ("*wolf*") and distance from "*tenedor*" (fork) that "*perro*" likely refers to another animal, a constraint that significantly narrows the semantic possibilities. This ability to infer semantic category membership from local geometric relationships, by leveraging learned structure to constrain unknown variables, reflects a form of zero-shot learning (Pourpanah et al., 2023; Socher et al., 2013) and highlights the cognitive flexibility supported by the brain's representational geometry (Behrens et al., 2018; Ehrlich & Murray, 2022).

To test whether preserved semantic structure could support single-word's neural response vector prediction, we used local Procrustes alignment to predict Spanish word's neural responses based on English semantic geometry (**Figure 5G**, **Methods**). For each target word, we identified its five nearest semantic neighbors in English neural space, learned a rotation matrix from these neighbors' cross-language response pairs, and applied this transformation to predict the target's Spanish response. To establish statistical significance, we tested 3000-word predictions (randomly sampled) and compared them against 1000 permutations. Each permutation broke semantic correspondence by randomly shuffling English-Spanish word pairings, randomly selecting prediction targets, and using random rather than semantic neighbors for transformation

learning, while preserving the statistical properties of neural responses. Predictions using correct English-Spanish correspondences achieved remarkably high accuracy (all mean cosine similarity between real word vector and predicted word vector < 17.6 degree for K, A1, A2, A3, KN-Neuropixel, and 12.5 degree for read-aloud task), exceeding the permuted null distribution (mean±SD=89.87 ± 0.12 degree; all p < 0.001; **Figure 5H**), indicating that local semantic neighborhoods in English neural space contain sufficient geometric information to predict Spanish responses (within the translation-equivalent semantic structure) with near-perfect angular alignment. This demonstrates that cross-language semantic preservation (**Figure 5C-F**) reflects not merely correlated distance patterns but a shared geometric structure precise enough to enable accurate neural decoding across languages.

Note that Study 2 (read aloud task) was excluded from brain-mBERT model alignment analysis (**Figure 4**) because the short, context-independent phrases lacked the semantic structure captured by contextual embeddings. Study 3 was not included in cross-language neural comparisons (**Figure 5**) because conversational content differed between languages, precluding word-by-word matching.

Translation neurons are not essential for cross-language neural semantic geometry

We next confirmed that the previously identified translation neurons are not responsible for the cross-language embedding match. To test this, we repeated the analyses above excluding the translation neurons (that is, the ones that showed similar English-Spanish firing profiles, identified in **Figure 2**, n=105/665). We found that even after excluding these neurons, we still observed brain-model alignment within languages (all p <0.001) and cross-language neural

semantic map correlations (all p <0.001). Thus, the shared pattern is not solely due to these

neurons.

Figure 5. Cross-language alignment of neural population geometry reveals shared semantic geometry.

(A) Schematic illustrating cross-language neural distance preservation. Left: Example words ("gato"/"perro") in Spanish neural space. Middle: Same words ("cat"/"dog") in English neural space. Right: Cross-language distance correlation plot where each point represents a word pair. If word pairs maintain similar relative distances across languages, points fall near the diagonal, indicating preserved geometric relationships (e.g., if "cat" and "dog" are close in English neural space, "gato" and "perro" are also close in Spanish neural space).

(B) Zoomed views highlighting semantic clusters within each language from the example sentence in Figure 4. Words with close semantic relationships cluster together in both languages: "competitive", "expansionary", and "cultures" form a tight cluster in English, mirrored by "competitivas", "expansionistas", and "culturas" in Spanish, demonstrating the preserved semantic geometry across languages.

(C) Shared neural semantic geometry between English and Spanish. The two-dimensional histograms show the joint distribution of pairwise neural distances measured in English (x-axis) and in Spanish (y-axis) for corresponding word pairs. Color intensity represents $\log_{10}$(count + 1) of word pairs falling within each bin (60×60 bins, color scale 0-5; **Methods**). Purple gradient from white (sparse) to dark purple (dense) indicates concentration of data points. Diagonal dashed line represents perfect cross-language correspondence. Passive listening datasets (K, A1, A2, A3, KN-Neuropixel) show significant positive Spearman correlations (rho = 0.255-0.477, all p < 0.001).

(D) Permutation test validation for passive listening. Histogram shows null distribution of cross-language neural distance correlations generated by randomly shuffling word-pair assignments (1000 permutations, gray bars). Observed correlations for matched translation pairs (purple vertical line) fall far outside the null distribution for all datasets (K, A1, A2, A3, KN-Neuropixel), confirming that cross-language geometric alignment is specific to semantic content rather than statistical artifact.

(E) Speech production (read aloud task) shows significant alignment (rho = 0.247, p < 0.001). Dense clustering along diagonal indicates that word pairs maintaining specific distances in English neural space preserve similar distances in Spanish neural space.

(F) Permutation test for speech production (read aloud task). Similar analysis showing that the observed cross-language correlation (purple vertical line, rho = 0.247) significantly exceeds the null distribution from random word-pair assignments (gray histogram), validating semantic specificity of neural geometric alignment during speech.

(G) Schematic of local Procrustes prediction method. The aim is to predict the target word (e.g., "perro" in light red) in Spanish given known structure from matched English words. For the translation-equivalent target word in English (e.g., "dog"), we identified its 5 nearest semantic neighbors in English neural space (left, for visualization, only 3 words shown), learned a rotation matrix Q from the cross-language response pairs of these neighbors (middle), and applied Q to predict the target word's Spanish neural response (right). The predicted Spanish response (light red) is compared with the true Spanish response vector (dark red) via cosine similarity.

(H) Prediction accuracy quantified as angular error (θ) between predicted and true Spanish response vectors. Across all datasets, predictions using correct English-Spanish correspondences achieved high accuracy (mean angular error: 12.5degree-17.6degree, red arrows, for visualization, only results from dataset *K* shown), exceeding shuffled null distributions (mean±SD=89.87 ± 0.12degree; all p < 0.001).
(***p<0.001, **p<0.01, *p<0.05).
RDM=representational dissimilarity matrix (by cosine distance)

Shared semantic geometry emerges from language-specific semantic axes within a common

neural ensemble

We next asked whether both languages rely on the same neural semantic axes to implement their shared geometry. Identical or highly similar pairwise distances can, in principle, be maintained even if the underlying coordinate axes are altered, leaving the geometry unchanged (Kriegeskorte & Wei, 2021), **Figure 6A**). Accordingly, a shared semantic geometry across languages could arise in two ways: either by relying on the same semantic axes (left panel, hypothesis *H1*) or by altering the underlying semantic axes (right panel, hypothesis *H2*). If *H2* holds, two mechanisms could explain how different neural semantic axes emerge across languages: *H2.1*, English and Spanish may engage distinct subsets of neurons to construct their respective semantic spaces; or *H2.2*, they may recruit the same neuronal population but implement different rotations or re-weightings of the neuronal axes to form language-specific semantic axes. Our results support the latter account (*H2* and *H2.2*), showing that a shared semantic geometry is realized through language-specific semantic axes within a common neural ensemble.

We applied eigendecomposition to the representational similarity matrices (RSMs, 1-RDM, **Figure 6B**) to extract the principal axes (eigenvectors) and quantified cross-language subspace alignment using variance-capture alignment indices (**Figure 6C**, Elsayed et al., 2016; **Methods**). We term the eigenvectors of the semantic similarity matrix as *semantic axes*, representing the principal directions of meaning in population space. From a systems-neuroscience perspective, these axes can be interpreted as *semantic readout axes*, because they specify linearly decodable directions that downstream circuits could access.

Despite the similar semantic geometry, the manifold constructed from semantic axes for English and Spanish were less aligned than the within-language subspaces both for mBERT (K,

A1, A2, A3, KN, all $p<0.001$) and hippocampus (K, A1, A2, A3, all $p<0.001$; KN-Neuropixel, $p>0.05$, **Figure 6C**). The reduction in alignment from within-language to cross-language conditions was comparable between the hippocampus and mBERT (hippocampus=0.11 ± 0.06 vs. mBERT=0.17 ± 0.10, $p = 0.31$, Wilcoxon signed-rank test; **Figure 6D**). For both systems, the across-language alignments are significantly higher than randomly shuffled distribution (unmatched words) across all stimulus sets (all $p<0.001$), indicating that English and Spanish implement similar semantic geometry through differently oriented, partially independent semantic axes rather than random similarity.

There are two possible mechanisms that could give rise to different neural semantic axes across languages, one is that the English and Spanish may engage different subsets of neurons to construct their semantic axes, or they may recruit the same subset of neurons (through rotation to distinguish the semantic axes between languages). To find which neural architecture is correct, we examined the neural coordination structure through eigendecomposition of neuron×neuron covariance matrices, which quantify how neurons co-vary across words within each language (**Methods**). This analysis revealed nearly identical neural subspaces across languages (**Figure 6E**). The top-k eigenvectors capturing >95% variance showed strong alignment (K: 0.99; A1: 0.98; A2: 0.97; A3: 0.97; KN-Neuropixel: 0.84, all $p<0.001$, permutation test by shuffling the neuron order). Each neuron's participation strength (the sum of squared loadings across the top eigenvectors, reflecting how heavily it contributes to these coordination modes), was highly correlated between languages (K: r=0.97; A1: r=0.92; A2: r=0.96; A3: r=0.94; KN-Neuropixel: r=0.73; all $p<0.001$).

Together, these results suggest that both languages rely on the same neural ensemble but differ in how those neurons are linearly combined to constructed semantic readout axes, resulting in distinct neural semantic subspace orientations that nevertheless preserve a shared semantic geometry.

Finally, we summarize our findings in **Figure 6F** across Marr's three levels of analysis (Marr, 1982). Both the brain and mBERT achieve shared representational geometries (same computational goal) through similar algorithms (language-specific semantic readout axes) implemented within overlapping neuronal populations (same physical substrate).

Figure 6. English and Spanish recruit the same group of neurons but different semantic readout axes to support a shared semantic geometry.
(A) Conceptual illustration showing that the shared semantic geometry across-language can be

preserved in two ways: either by relying on the same semantic axes (left panel, hypothesis *H1*), or by altering the underlying semantic axes (right panel, red and green axes rotated 56° in X-Y plane, blue axes tilted 30°, supporting hypothesis *H2*). If *H2* is correct, then there are two possible mechanisms that could give rise to different neural semantic axes across languages: *H2.1*, English and Spanish may engage different subsets of neurons to construct their semantic spaces, or *H2.2*, they may recruit the same subset of neurons but use rotations or reweighting of the neuronal axes to form language-specific semantic axes.

(B) Conceptual illustration of possible subspace alignments between languages. Fully aligned (1.0, support H1), partially aligned (0.5, support H2), and orthogonal (alignment = 0, support H2).

(C) Eigendecomposition of the centered RSM (representational similarity matrix, 1-RDM) yields the principal semantic axes (eigenvectors) for each language. Then we build the subspaces based on the top eigenvectors (which captured 95% of variance) and test the across-language alignment (**Methods**). The principal semantic axes for English and Spanish were less aligned compared to within-language subspaces both for mBERT (K, A1, A2, A3, KN-Neuropixel, all $p<0.001$) and hippocampus (K, A1, A2, A3, all $p<0.001$; KN-Neuropixel, $p>0.05$).

(D) The reduction in alignment from within-language to cross-language was comparable between the hippocampus and mBERT.

(E) Per-neuron participation strength in the top subspace (explaining > 95 % variance) was highly correlated between languages (all $r>0.72$, all $p<0.001$) both for hippocampus and mBERT, showing that both English and Spanish rely on nearly the same group of neurons to form their semantic readout axes, even though their semantic subspaces differ in directions. If we treated the embedding dimension of mBERT as a neuron, the per-artificial neuron participation strength in the top subspace (explaining > 95 % variance) was highly correlated between languages (all $r>0.950$, all $p<0.001$), showing that both two systems utilized the same "hardware" to construct language-specific semantic readout axes to achieve the shared meaning.

(F) Summary of all findings based on Marr's three-level analysis (Marr, 1982). Both brain and mBERT achieve shared representational geometries (same goal) through similar algorithms (language-specific semantic readout axes) and using the same neuronal populations (same implementation).

(*** $p < 0.001$).

DISCUSSION

We examined responses of hippocampal neurons in four bilingual English-Spanish speakers with implanted microelectrodes. We find evidence for a shared cross-linguistic neural embedding space for both listening and speaking for the two languages. That is, words with similar meanings in English and Spanish evoke similar neural patterns of responses across the two languages, leading to shared semantic geometry. This result supports earlier proposals that different languages involve reactivation of the same regions (Chen et al., 2024; Hengshuang Liu & Cao, 2016; Sulpizio et al., 2020; Zada et al., 2025) and shows that it extends to the level of single neurons. This result is consistent with hypotheses about the role of hippocampus in abstract conceptual representation (Quian Quiroga, 2023; Quian Quiroga, 2012). However, representations were not amodal. Instead, each neuron had distinct semantic tuning for the two languages, and the shared semantic geometry was from different semantic readout axes of two languages. Thus, cross-language shared representation of concepts appears to be a complex emergent phenomenon that takes place not primarily through specialized neurons or even a translation axis, but rather on the manifold, through shared geometry (Ebitz & Hayden, 2021; Perich et al., 2025; Vyas et al., 2020). Together, these results suggest a specific solution to the problem of translation, one that gives a central role to shared coactivation patterns in driving the ability to move between languages.

While important neuroimaging studies (Chen et al., 2024; Correia et al., 2014; de Varda et al., 2025; Van de Putte et al., 2017; Zada et al., 2025) demonstrate that the brain encodes semantic features in similar way across languages, our single-unit findings take a further step. We quantify the population neural embeddings for each individual word and reveal how every

word occupies a specific position within a continuous, context-dependent, high-dimensional semantic space. The across-language prediction based on local geometric features revealed that the preserved semantic geometry in hippocampal population codes is sufficient to infer the embedding vectors of a hidden word, indicating that shared conceptual geometry is sufficient for translation, and that direct word-to-word mapping is not necessary. Also, we show that neuronal responses share key computational properties with multilingual language model mBERT. Both systems represent words as high-dimensional vectors with linearly decodable structure, exhibit cross-lingual geometric alignment in which translation equivalents occupy similar relative positions (Devlin et al., 2019; Pires et al., 2019; Wu et al., 2022).

Translation neurons. We identify a new class of what we call "*translation neurons*," whose responses to co-translated words are correlated. Such neurons would have similar responses to, for example, "*maybe*" and "*quizás.*" Consistent with this, these neurons have stronger tuning functions for English and Spanish. These neurons may play an important role in translation or abstract cross-linguistic reasoning. However, even when we remove these neurons from our analysis, the semantic geometry is still robustly maintained, suggesting that these neurons do not play a necessary role in translation. Moreover, while their tuning functions are more aligned than chance, they are not perfectly aligned, indicating that they are not simply amodal conceptual representations. Consistent with this, like the others in our sample, they have response preferences that span multiple semantic categories, meaning that they are unlikely to correspond to concept cells (Quian Quiroga et al., 2005; Quian Quiroga, 2012). Speculatively, one possibility is that they play a special role in context-free translation (that is, when we are

asked the equivalent of a single word). Another possibility is that they are simply the extreme end of a larger distribution of neurons.

How the representation geometry could support shared meaning but language-specific readout. Bilingual individuals can not only translate an abstract thought into words but do so in the appropriate language. Moreover, they can converse in a single language, with no danger of inadvertently flipping back and forth between languages. That may seem effortless, but it actually requires a specialized representational scheme that allows for simultaneous, readout-dependent semantic coding. The observation that single-neuron tuning functions differ across languages indicates that individual neurons shift their semantic preferences, meaning the same neuron may weight different semantic features in English and Spanish. At the population level, these tuning shifts could give rise to rotated, near-orthogonal readout axes (alignment ≈ 0.05), which correspond to different projections of a shared semantic geometry. The relationship between tuning differences and readout rotations is correlational rather than causal; they are like the two sides of the one computational coin at different level (single vs. populational). This organization may reduce confusability between languages by decorrelating their output directions, achieving a balance between generalization and differentiation (Barak et al., 2013; Bernardi et al., 2020; Johnston et al., 2024; Libby & Buschman, 2021; Tang et al., 2020; Tian et al., 2024; Xie et al., 2022). We hypothesize that language context (provided by surrounding words, interlocutor cues) could gate which readout axes' "rotation" is active, like task-switching mechanisms in the prefrontal cortex (Rigotti et al., 2013). This rotation effectively minimizes interference while enabling computation efficiency. Rather than requiring separate neural populations for each language (which would be metabolically expensive), the brain reuses the

same neurons with different mixing weights, which aligns with broader principles of neural reuse (Anderson, 2010).

Finally, and more speculatively, words with identical translations do not have identical semantic meanings. Roman Jakobson uses the famous example of the English word "*cheese*," which is generally translated into Russian as "сыр" (*syr*), but the Russian term specifically excludes cottage cheese (Jakobson, 1959). Another well-known example comes from the distinction between the inclusive and exclusive "*we*" in many world languages, although not English. Such examples show that even translation-equivalent words occupy slightly different semantic neighborhoods, which may naturally bias neural representations toward distinct tuning directions. In this way, small divergences in meaning could help shape partially rotated readout axes across languages, maintaining shared semantic geometry while minimizing representational overlap and interference.

Limitations. One limitation of our study is the low number of patients that we recorded. The main reason for this is the rarity of obtaining fully balanced bilingual patients who acquired both languages early in life with access to single units in hippocampus. However, our core finding of shared semantic geometry was replicated across all listening datasets, extended to speech production (i.e., read-aloud task), and was significant in all four patients individually. Second, we did not test additional languages beyond English and Spanish. This limitation reflects a practical limitation of intracranial recordings, as it is exceedingly rare to identify trilingual patients with high-quality single-unit data. Third, our data cannot address how the shared semantic geometry is formed. Future studies that track participants as they learn a new language could reveal how semantic geometry emerges and becomes aligned across languages.

Place-cell and grid-cell like codes, and extending the cognitive maps for meanings. Our

findings in hippocampus resonate with research on cognitive maps in spatial and non-spatial

domains (Behrens et al., 2018; Constantinescu et al., 2016; Courellis et al., 2024; Hafting et al.,

2005; Muller et al., 1996), extending the framework to semantic representations across

languages. Individual neurons exhibit language-specific tuning profiles. At the population level,

the neural readout axes are modulated by different languages, reflecting context-dependent

remapping similar to place cells that change their firing fields when sensory environment

changes (Bostock et al., 1991; Leutgeb et al., 2005). By contrast, the preserved semantic

geometry across languages resembles grid cells' stable, environment-invariant coordinate system

(Constantinescu et al., 2016; Courellis et al., 2024; Doeller et al., 2010; Hafting et al., 2005;

Muller et al., 1996). However, language's representation is high-dimensional and distributed, far

beyond the 2D world representation. Therefore, the internal model for complex stimuli like

concepts and semantics, may not be captured by individual neurons alone. More generally, this

framework aligns with evidence that hippocampal circuits encode diverse non-spatial variables,

from sound frequency (Aronov et al., 2017) to abstract knowledge (Constantinescu et al., 2016)

and social relationships (Schafer & Schiller, 2018; Tavares et al., 2015), supporting the view that

the hippocampus provide a domain-general geometric code for navigating "conceptual space"

(Behrens et al., 2018; Bellmund et al., 2018; Gardenfors, 2014; Nieh et al., 2021). In this

framework, bilingual comprehension and production may reflect flexible readouts from a

common underlying semantic geometry. If language acts as a symbolic system for

communicating information, then semantic geometry reflects how that meaning is internally

organized within the brain's high-dimensional neural space. Like a building with many

entrances, different languages open alternative pathways that may lead to the same semantic meanings. This geometric isomorphism implies that the hippocampus provides a cognitive map for meaning, supporting abstract navigation across linguistic boundaries.

METHODS

Ethics approval

The experiment's procedures were conducted by the standards set by the Declaration of Helsinki and approved by the Institutional Review Board for Baylor College of Medicine, Houston, TX (H-50885 and H-18112). Participants provided written informed consent after the experimental procedure had been fully explained and were reminded of their right to withdraw at any time during the study.

Patient recruitment

Four fully balanced Spanish-English bilingual epilepsy patients (daily use of both languages since age 4) participate in the study and were aware that participation was voluntary and would not affect their clinical course. Patients' age ranged from 26-54 years old (mean ± s.e.m = 38.50 ± 7.08 years), with four female patients. None of the patients reported explicit memory of intraoperative events after the case when discussed in the post-operative care unit or while recovering in the hospital the next day.

Experimental stimuli in study 1 (Figure 1B&1C)

Neural activity was recorded using either Neuropixels probe (P04) or microelectrodes enabling single neuron isolation (P01-P03). During passive listening tasks (Study1), participants were presented with naturalistic audio stimuli in both Spanish and English. To assess the robustness of our findings across different content domains, we employed two distinct stimulus sets (Set A (audiobook: "*eat, pray, love*") and Set K (*kurzgesagt*)) that varied in their linguistic properties and semantic content. The stimuli consisted of four distinct recordings: three educational podcast episodes from *Kurzgesagt* (K: K1-"dark forest"; K2-"true limits"; K3-"deep sea") and one complete audiobook (A: audiobook "*Eat, Pray, Love*" by Elizabeth Gilbert). The stimulus presentation varied by participant based on recording availability: P04 (with Neuropixels probe) listened to K1 only (we termed this dataset *KN-Neuropixel*), P01 listened to K1-K3, while P02 and P03 listened to both stimulus sets (K1-K3 and A). Due to clinical care requirements, the audiobook stimulus (A) was recorded across three non-consecutive days for P02 and P03 (Day 1: A1 (books 0-1); Day 2: A2 (book 2); Day 3: A3 (books 3-4)), whereas all podcast stimuli (K1-K3) were collected in single sessions.

Experimental stimuli in study 2

We adapted the bilingual speech neuroprosthesis paradigm from Silva et al. (2024) to investigate cross-linguistic neural encoding during active speech production (in our study, we called it as "read aloud task"). The experimental design employed a carefully curated vocabulary of bilingual short phrases presented in an isolated-target task paradigm, where participants attempted to produce individual words in either English or Spanish upon visual cue presentation. The core vocabulary comprised 99 matched English and Spanish short phrases (3-4 words; see Supplementary Table 7 of Silva et al., 2024). During this task, participants viewed a single target word displayed on a screen, then the participants attempted to produce the word overtly. The task design incorporated several key features to optimize neural signal quality. First, phrases were presented in randomized order across both languages to prevent anticipatory effects and ensure

that neural responses reflected language-specific processing rather than sequential patterns. Second, the visual presentation format remained consistent across all trials, with text displayed in the same font, size, and screen position to minimize visual processing confounds.

Neuropixels data acquisition setup and intraoperative recordings in the hippocampus

Neuropixels 1.0-S probes (IMEC) with 384 recording channels (total recording contacts = 960, usable recording contacts = 384) were used for recordings (dimensions: 70μm width, 100μm thickness, 10mm length). The Neuropixels probe, consisting of both the recording shank and the headstage, were individually sterilized with ethylene oxide (Bioseal, CA, (Coughlin et al., 2023)). Our intraoperative data acquisition system included a custom-built rig including a PXI chassis affixed with an IMEC/Neuropixels PXIe Acquisition module (PXIe-1071) and National Instruments DAQ (PXI466 6133) for acquiring neuronal signals and any other task-relevant analog/digital signals respectively. Our recording rig was certified by the Biomedical Engineering at Baylor St. Luke's Medical Center, where the intraoperative recording experiments were conducted. A high-performance computer (10-core processor) was used for neural data acquisition using open-source software such as SpikeGLX 3.0 and OpenEphys version 0.6x for data acquisition (AP band (spiking data)), band-pass filtered from 0.3kHz to 10kHz was acquired at 30kHz sampling rate; LFP band, band-pass filtered from 0.5Hz to 500Hz, was acquired at 2500Hz sampling rate). We used a "short-map" probe channel configuration for recording, selecting the 384 contacts located along the bottom 1/3 of the recording shank.

Audio was played via a separate computer using pre-generated wav files and captured at 30kHz or 1000kHz on the NIDAQ via a coaxial cable splitter that sent the same signal to speakers adjacent to the patient. MATLAB (MathWorks, Inc.; Natick, MA) in conjunction with a LabJack (LabJack U6; Lakewood, CO) was used to generate a continuous TTL pulse whose width was modulated by the current timestamp and recorded on both the neural and audio datafiles. Online synchronization of the AP and LFP files was performed by the OpenEphys recording software. Offline synchronization of the neural and audio data was performed by calculating a scale and offset factor via a linear regression between the time stamps of the reconstructed TTL pulses and confirmed with visual inspection of the aligned traces.

Acute intraoperative recordings were conducted in brain tissue designated for resection based on purely clinical considerations. The probe was positioned using a ROSA ONE Brain (Zimmer Biomet) robotic arm and lowered into the brain 5-6mm from the ependymal surface using an AlphaOmega microdrive. The penetration was monitored via online visualization of the neuronal data and through direct visualization with the operating microscope (Kinevo 900). Reference and ground signals on the Neuropixels probe were acquired separately by connecting to a sterile microneedle placed in the scalp (separate needles inserted at distinct scalp locations for ground and reference respectively).

Motion analysis. The motion-corrected location estimates were obtained at a 250Hz sampling frequency using the DREDge algorithm. This signal was down sampled to 10Hz. The power spectrum of the calculated motion was then estimated using Welch's overlapped segment averaging estimator for frequencies between 0.1 and 3Hz. The amount of motion was defined as the root mean square error of the location trace of the probes center relative to its average location.

Thresholding method. Spike detection was performed using an adaptive thresholding algorithm designed to achieve a target firing rate of approximately 20 Hz per channel. A threshold was set dynamically for each channel based on signal characteristics and noise level. For each channel noise level was estimated using the mean absolute deviation (MAD), calculated as MAD = median (|x|)/0.6745, where x is the band-passed filtered signal. Channels with MAD values below 1x10-6 were classified as dead channels and excluded. An iterative binary search algorithm was used to determine the optimal threshold multiplier for each channel. Different values were tested within a range. Negative-going threshold crossings were considered a neuronal spike. If the iterative firing rate was too high, the threshold was made more negative and vice versa for a low firing rate. A refractory period of 1ms was also used to eliminate some level of noise.

Microelectrodes recording in the hippocampus

The hippocampus was not a seizure focus area in any of the patients included in the study. Single neuron data were recorded from stereo-EEG (sEEG) probes, specifically Ad-Tech Medical probes in a Behnke-Fried configuration. Each patient had an average of three probes terminating in the left and right hippocampus. Electrode locations were verified by co-registered pre-operative MRI and post-operative CT scans. Each probe includes eight microwires, each with eight contacts, designed explicitly for recording single-neuron activity. Single neuron data were recorded using a 512-channel *Blackrock Microsystems Neuroport* system sampled at 30 kHz. To identify single neuron action potentials, the raw traces were spike sorted using the *Wave_clus* sorting algorithm (Chaure et al., 2018) and then manually evaluated and modified to improve sorting. Noise was removed, and each signal was classified as multi or single unit using several criteria: consistent spike waveforms, waveform shape (slope, amplitude, trough-to-peak), and an exponentially decaying ISI histogram with no ISI shorter than the refractory period (1 ms). The analyses here used all single and multiunit activity.

Firing rate responses to words

In Study 1 (listening) and Study 3 (conversation-listening), firing rates were computed from spikes occurring 200 ms after word onset to 200 ms after word offset, accounting for transmission delays to hippocampus (Charest et al., 2009; Chavez et al., 2025). In Study 2 (read aloud task) and Study 3 (conversation-speaking), the analysis window was shifted 200 ms earlier (from 200 ms before word onset to 200 ms before word offset) to capture neural activity during speech preparation (Chavez et al., 2025). Spike counts were divided by window duration and multiplied by 1000 to yield spikes per second.

Audio transcription

After experiments, the audio.wav file was automatically transcribed using Assembly AI, a state-of-the-art AI model trained to transcribe speech. Speaker diarization was achieved with Assembly AI's internal speaker diarization model. The transcribed words, corresponding timestamps, and speaker labels output from these models were converted to a TextGrid and then loaded into Praat, a well-established software for speech analysis (https://www.fon.hum.uva.nl/praat/) . The original .*wav* file was also loaded into Praat. Trained lab members manually

inspected the spectrograms, timestamps, and speaker labels, correcting each word to ensure that onset and offset times were precise and assigned to the correct speaker (this process took about 4-5 hours per minute of speech). The TextGrid output of corrected words and timestamps from Praat was converted to an Excel file and loaded into Python (version 3.11) for further analysis.

Electrode visualization for Figure 1A

Electrode visualization was performed using MNE-Python (version 0.24.0) with FreeSurfer's fsaverage template brain. The visualization pipeline created an ultra-transparent glass brain (3% opacity) with highlighted hippocampal structures to clearly display electrode positions within deep brain regions. For each patient, DICOM images of the preoperative T1 anatomical MRI and the postoperative Stealth CT scans were acquired and converted to NIfTI format (Li et al., 2016). The CT was aligned to MRI space using FSL (M. Jenkinson & Smith, 2001; Mark Jenkinson et al., 2002). The resulting co-registered CT was loaded into BioImage Suite (version 3.5β1; (Joshi et al., 2011)), and the electrode contacts were manually localized. Electrodes' coordinates were converted to the patient's native space using iELVis MATLAB functions (Groppe et al., 2017) and plotted on the Freesurfer (version 7.4.1) reconstructed brain surface (Dale et al., 1999). Microelectrode coordinates are taken from the first (deepest) macro contact on the Ad-Tech Behnke Fried depth electrodes. RAVE (Magnotti et al., 2020) was used to transform each patient's brain and electrode coordinates into MNI152 average space. The coordinates were plotted together on a glass brain with the hippocampus segmentation.

Methods for translation neurons identification (Figure 2)

For each dataset group, we computed Pearson correlations between English and Spanish firing-rate responses across all matched words for each neuron. Neurons with zero variance in either language were excluded from inference and carried as NaN. For every remaining neuron, we assessed significance with a permutation test. Specifically, we generated a null distribution by randomly shuffling the Spanish word indices 1000 times and recomputing the correlation for each shuffle. The per-neuron p-value was the proportion of null correlations whose absolute value was greater than or equal to the absolute observed correlation. Neurons with $p < 0.05$ were classified as significant and then split by sign into significant positive (cross-language similar) and significant negative (cross-language anticorrelated). We set the random seed at the start of the analysis to ensure reproducibility.

At the population level, we summarized each group with two complementary tests. First, to ask whether the number of significant positive (and, separately, significant negative) neurons exceeded what would be expected from the per-neuron test's false-positive rate, we used right-tailed binomial tests with chance probability $p_0 = 0.025$. This value corresponds to the expected false-positive rate from the two-tailed per-neuron permutation test ($\alpha = 0.05$), in which only one tail represents positive correlations. The proportion of significant neurons in each dataset was visualized using pie charts (Figure 2), which displayed the percentage of neurons with significant positive cross-language correlations (purple), the expected proportion by chance (grey), and the remaining non-significant neurons (white).

Contextual embedding extraction from multilingual BERT (Figure 3)

We extracted contextual word embeddings from multilingual BERT (mBERT) for complete English and Spanish versions of the transcripts for both stimulus sets, processing each language's full stimulus independently before identifying matched word pairs for cross-linguistic analysis. The embedding extraction process was designed to maintain the contextual nature of transformer representations while ensuring that each word received naturalistic linguistic context from its own language stream. For each sentence in the transcripts (282 sentences in *set K*, 296 sentences in *set A*), we tokenized the text using mBERT's tokenizer (bert-base-multilingual-cased) without adding special tokens initially, creating a flat sequential representation of all tokens across the entire stimuli. This approach allowed us to maintain accurate tracking of token positions and their relationships to original words in the transcript.

To preserve contextual information is crucial for mBERT's contextualized representations, we implemented a sliding window strategy that provided each sentence with up to 509 tokens of preceding context (Zada et al., 2025). For each sentence, we calculated the available context window by subtracting the sentence length from the maximum allowable tokens (512 tokens minus 3 special tokens: [CLS], [SEP], [SEP]). The input sequence was then constructed following the format [CLS] + context_tokens + [SEP] + sentence_tokens + [SEP], where context tokens were drawn from immediately preceding text up to the calculated limit. This ensured that each word received rich contextual information from surrounding discourse while staying within mBERT's architectural constraints.

The model processed each constructed input sequence to generate hidden state representations across all 13 layers (layers 0-12), with each layer capturing increasingly abstract linguistic features. We extracted embeddings specifically for the sentence tokens, excluding the context tokens and special tokens, by indexing into the appropriate positions of the output tensors. For words that were split into multiple subword tokens by the tokenizer, we averaged the embeddings across all constituent tokens to obtain a single word-level representation, ensuring that our analysis operated at the word level despite the subword tokenization scheme. This averaging preserved the dimensional structure (768 dimensions) while consolidating information from word pieces that collectively represent single lexical units.

The extraction process was performed identically for both English and Spanish transcripts, yielding parallel sets of contextualized embeddings where each word in the English version had a corresponding translation-equivalent word in the Spanish version. For each of the three podcast episodes and both languages, this resulted in a three-dimensional tensor of shape (n_layers × n_words × 768), where n_layers = 13 and n_words varied by stimuli set length. These layer-wise embeddings captured the hierarchical processing of linguistic information, from surface-level features in early layers to more abstract semantic representations in deeper layers, enabling our subsequent analysis of cross-linguistic alignment patterns. The identical processing pipeline for both languages ensured that any observed differences in representation patterns could be attributed to linguistic rather than methodological factors.

Computing similarity between English-Spanish word embeddings in all layers
To investigate how multilingual language models represent semantic equivalences across languages, we analyzed the similarity between English and Spanish word embeddings extracted from parallel translated content. We obtained contextual embeddings for matched word pairs

across three podcast episodes in both English and Spanish versions, extracting representations from multiple transformer-based models: multilingual BERT (mBERT) (Devlin et al., 2019; Pires et al., 2019) with 13 layers (layers 0-12). For each word pair, embeddings were extracted from every layer of these models to capture the hierarchical development of cross-linguistic representations.

For each stimulus set (Set A (audiobook: "*eat, pray, love*") and Set K (*kurzgesagt*)), we computed Pearson correlations between the embedding vectors of each English-Spanish word pair (e.g., *"human-humano"*), yielding a correlation coefficient for every matched word across all layers. This approach quantified how similarly the models represent semantically equivalent words in different languages at various stages of processing depth.

To control for spurious similarities that might arise from random initialization or architectural properties rather than learned linguistic knowledge, we established a baseline using untrained versions of the same models with identical architectures but randomized weights. These baseline models underwent the same embedding extraction and correlation computation procedures as their trained counterparts, maintaining near-zero correlations across all layers as expected from random representations.

We aggregated correlations across all word pairs by computing means and standard errors for each layer, with error propagation applied when calculating the relative similarities to account for uncertainty in both trained and baseline measurements properly. The resulting layer-wise profiles revealed how cross-linguistic semantic alignment emerges and evolves through the depth of each model, with both stimulus sets showing progressive increases in correlation through the middle layers before reaching maximum alignment at Layer 11 (Figure 3B).

Non-contextual (static) embeddings (Figure 3)

We also extracted static word embeddings using the pre-trained fastText Word2Vec model in MATLAB (R2024b), specifically the wiki-news-300d-1M vectors (Bojanowski et al., 2017; Grave et al., 2018). This model provides fixed 300-dimensional vectors for over one million words and phrases, trained on Wikipedia and news text to capture broad semantic relationships. Unlike contextual embeddings, which vary depending on sentence position or surrounding words, these static embeddings assign the same representation to each word regardless of context. For our dataset, we mapped every word in the transcripts to its corresponding fastText vector. Words without valid embeddings (e.g., uncommon surnames or rare tokens do not present in the model's vocabulary) were excluded from further analyses.

Single neuron's tuning vector analyses (Figure 3)

For each dataset (K, A1, A2, A3, KN-Neuropixel, read aloud task, conversation-listening, conversation-speaking), we concatenated single-unit firing-rate matrices across all words to form word × neuron matrices separately for English and Spanish. We extracted mBERT token embeddings for the matched words in each language (Layer 11, see above), then concatenated English and Spanish embeddings and ran a single PCA on the combined matrix to obtain ashared embedding basis. The resulting PCA scores were split back into English and Spanish, yielding a common set of semantic predictors with identical axes across languages (100 components).

Then, for every neuron, we fit two ridge regressions that map shared PCA embeddings to firing rates, one in English and one in Spanish. The ridge penalty was selected per neuron by cross-validation, using a grid of penalties and 5-fold CV jointly across languages (the chosen penalty minimized the average normalized prediction error over English and Spanish folds). With the selected penalty, we refit the English and Spanish ridge models and extracted, for each neuron, we got a *tuning vector*, that is, the vector of regression coefficients on the shared PCA semantic features. Each tuning vector (length = number of PCA components) specifies how strongly that neuron weights each semantic dimension to predict its firing rate.

We quantified neuron-wise similarity by correlating, for each neuron, its English tuning vector with its Spanish tuning vector (over PCA dimensions). To test whether English-Spanish similarity exceeded chance, we generated a null distribution by randomly permuting the Spanish word indices (1000 permutations, this procedure is same as we did in Figure 2), refitting the Spanish ridge model for every neuron with the same cross-validated penalty, and recomputing neuron-wise correlations. Per-metric p-values were computed as the proportion of null correlations whose absolute value was greater than or equal to the observed value (two-sided $\alpha = 0.05$ test). Same as the method we used for Figure 2 (identify the translation neurons), we used right-tailed binomial tests with chance probability $p_0 = 0.025$ (corresponding to one tail of the per-neuron two-sided $\alpha = 0.05$ test).

To evaluate whether the observed cross-language tuning similarity could be explained by within-language variability, we quantified the split-half reliability of tuning vectors for each neuron within English and within Spanish. For every iteration, word indices were randomly split into two equal halves, and independent ridge models were fit on each half using the neuron's cross-validated penalty. The two resulting tuning vectors were correlated to obtain a within-language reliability value per neuron. This procedure was repeated 1000 times, generating a distribution of split-half correlations for each neuron and, when pooled across all neurons and both languages, a global distribution of within-language reliability. The vertical red line in Figure 3 (last panel) marks the mean cross-language tuning similarity across all neurons, shown relative to this within-language reliability distribution. We ran a paired Wilcoxon signed-rank test across neurons, testing whether per-neuron mean within-language reliability exceeded cross-language similarity.

Constructing embedding dissimilarity matrix and neural dissimilarity matrix (Figure 4)
For both neural and semantic spaces, we computed *Representational Dissimilarity Matrices* (RDMs; (Diedrichsen & Kriegeskorte, 2017; Kriegeskorte & Kievit, 2013; Nili et al., 2014)) using cosine distance as the dissimilarity metric. The cosine distance between two vectors **x** and **y** is defined as:

$$d_{\text{cosine}}(\mathbf{x}, \mathbf{y}) = 1 - \frac{\mathbf{x} \cdot \mathbf{y}}{\|\mathbf{x}\|\|\mathbf{y}\|}$$

For a dataset with *n* words, this yields a condensed distance vector of length n*(n-1)/2 containing all unique pairwise distances. The neural RDM for language l was computed as:

$$\mathbf{D}^{(l)}_{\text{neural}} = \{d_{\text{cosine}}(\mathbf{n}_i^{(l)}, \mathbf{n}_j^{(l)}) : 1 \leq i < j \leq n\}$$

Where $\mathbf{n}_i^{(l)}$ represents the neural population vector for word i in language l. Similarly, the semantic RDM was computed as:

$$\mathbf{D}_{\text{semantic}}^{(l)} = \{d_{\text{cosine}}(\mathbf{s}_i^{(l)}, \mathbf{s}_j^{(l)}) : 1 \leq i < j \leq n\}$$

Where $\mathbf{s}_i^{(l)}$ represents the mBERT embedding vector for word i in language l.

Neural-semantic correspondence quantification

The correspondence between neural and semantic representational geometries was quantified by computing Spearman correlation between the vectorized RDMs (i.e., $\mathbf{D}_{\text{semantic}}^{(l)}$ and $\mathbf{D}_{\text{neural}}^{(l)}$). This correlation coefficient quantifies the degree to which neural dissimilarity patterns mirror semantic dissimilarity patterns. A high positive correlation indicates that words with similar meanings (small semantic distance) tend to evoke similar neural responses (small neural distance), supporting the hypothesis of semantic encoding in the neural population.

Cross-language semantic map similarity analysis (Figure5)

We performed a cross-language similarity analysis comparing neural response patterns for matched English-Spanish word pairs to investigate the correspondence between neural representations of semantic content across languages. This analysis quantifies whether words that elicit similar neural responses in one language also elicit similar responses in another, providing evidence for shared or distinct neural geometry for semantic representation across languages. Neural similarity between word representations was quantified using cosine distance, which measures the angular separation between neural population vectors independent of their magnitude. For each language, we computed pairwise cosine distances between all word pairs, this yielded similarity matrices $S^{(E)}$ and $S^{(S)}$ for English and Spanish, respectively, with values ranging from 0 (identical patterns) to 1 (maximally dissimilar patterns).

To assess the preservation of similarity structure across languages, we extracted the upper triangular portions of both similarity matrices (excluding the diagonal), yielding vectors of unique pairwise similarities. Then we use the Spearman correlation (Nili et al., 2014) to quantify the cross-language correspondence. A high positive correlation indicates that word pairs with similar neural representations in English tend to have similar representations in Spanish, suggesting a shared neural geometry for organizing semantic content across languages.

To evaluate whether the observed cross-language correlation exceeded chance, we generated a null distribution by randomly shuffling the Spanish word labels 1000 times and recomputing the correlation after each shuffle. This procedure destroys the correspondence between matched English-Spanish word pairs while preserving each language's internal structure. The resulting distribution of shuffled correlations represents the range of values expected if there were no true relationship across languages. The *p*-value was then calculated as the proportion of shuffled correlations whose absolute value was equal to or greater than the observed correlation (two-sided test, α = 0.05)

Multidimensional Scaling (MDS) network visualization

In Figure 4B and Figure 4D, we employed classical Multidimensional Scaling (MDS) (Mead, 1992) combined with network visualization techniques to visualize the geometric organization of neural representations for matched word pairs across languages. This approach reveals the topological structure of semantic representations in neural space by projecting high-dimensional neural patterns onto interpretable low-dimensional manifolds while preserving pairwise dissimilarities. The resulting 2D coordinates were visualized as network graphs where nodes represent words and weighted edges encode distance between words.

Two-dimensional histogram visualization in Figure 5C and Figure 5E
We constructed a two-dimensional histogram with 60 × 60 bins spanning the range [0, 1] for both dimensions to visualize the joint distribution of similarity values across languages. The bin counts were log-transformed using:
$$N_{\text{display}} = \log_{10}(N + 1)$$
Where *N* represents the raw count in each bin, this transformation enhances visibility of the full density range while preventing singularities from empty bins.

Local geometric cross-language prediction (Figure 5G-H)
To test whether preserved semantic geometry could support single-word neural decoding across languages, we implemented a local Procrustes alignment approach. All neural firing rate vectors were first mean-centered across words (subtracting each neuron's average firing rate) and L2-normalized to unit length, which removes neuron-specific baseline firing rates and focuses analysis on semantic modulation patterns. For each target word with English response vector $\mathbf{e}_{\text{target}}$, we identified its $k = 5$ nearest semantic neighbors in English neural space using cosine distance, then extracted these neighbors' responses in both languages to form matrices $\mathbf{X}_E$ (English, $n_{\text{neurons}} \times k$) and $\mathbf{X}_S$ (Spanish, $n_{\text{neurons}} \times k$). After centering both matrices by subtracting column means ($\boldsymbol{\mu}_E$ and $\boldsymbol{\mu}_S$), we computed the cross-covariance matrix $\mathbf{M} = (\mathbf{X}_S - \boldsymbol{\mu}_S)(\mathbf{X}_E - \boldsymbol{\mu}_E)^T$ and performed singular value decomposition $\mathbf{M} = \mathbf{U}\boldsymbol{\Sigma}\mathbf{V}^T$.

The optimal orthogonal rotation matrix was obtained as $\mathbf{Q} = \mathbf{U}\mathbf{V}^T$, and the predicted Spanish response was computed as $\hat{\mathbf{y}} = \boldsymbol{\mu}_S + \mathbf{Q}(\mathbf{e}_{\text{target}} - \boldsymbol{\mu}_E)$, then L2-normalized to unit length. Prediction accuracy was quantified as angular error $\theta = \arccos(\hat{\mathbf{y}} \cdot \mathbf{y}_{\text{true}})$ in degrees. We tested 3,000 word-level predictions per dataset by randomly sampling unique words and, for each one, predicting its Spanish response from its own nearest neighbors selected from the full English vocabulary. Statistical significance was assessed against 1000 null permutations where we randomly shuffled English-Spanish word pairings using derangement (ensuring no correct translations), randomly selected Spanish prediction targets from left words, and used randomly selected Spanish words as neighbors for learning $\mathbf{Q}$, thereby destroying semantic correspondence while preserving neural response distributions. p-values represented the proportion of null means exceeding the real mean (two-tailed).

Cross-language subspace alignment analysis

To examine how English and Spanish neural population representations relate to each other in geometric structure, we performed a cross-language subspace alignment analysis based on representational dissimilarity matrix (RDM, by cosine distance) and eigendecomposition. To enable eigendecomposition, we first converted cosine distances to a similarity matrix via 1 minus the RDM (where the subtraction is elementwise) to get the RSM (representation similarity matrix). We then applied double-centering (kernel centering) to remove the mean structure and obtain a centered Gram matrix (Borg & Groenen, 2005; Hofmann et al., 2008) directly in MATLAB (Statistics and Machine Learning Toolbox).

We then performed the eigendecomposition. Eigenvalues were sorted in descending order, and the corresponding eigenvectors were arranged accordingly. The eigenvectors define the principal semantic axes (or we called the "semantic readout axes" in *Result* sections) in the high-dimensional word space along which the neural population responses vary most strongly across words. That is, they are the directions that maximize variance in the centered word-word similarity structure.

To quantify representational dimensionality, we used the cumulative variance threshold, defined as the smallest number of components capturing at least 95% of the total variance. The top-k eigenvectors from each language formed orthonormal bases $\mathbf{U}_E$ and $\mathbf{U}_S$ representing the English and Spanish *semantic subspaces*, respectively. To quantify their geometric relationship, we adopted the alignment index from Elsayed et al. (2016)(Elsayed et al., 2016). We computed the variance-capture alignment index, which measures how much variance in one dataset's representational structure is captured by another dataset's subspace, normalized by the variance that the dataset could optimally capture on its own. The directional alignment is defined as:

$$\text{Alignment}(A \leftarrow B) = \frac{\text{Tr}(\mathbf{U}_B^T \mathbf{G}_A \mathbf{U}_B)}{\sum_{i=1}^{k} \lambda_A^{(i)}}$$

where $\mathbf{G}_A$ denotes the centered cosine Gram matrix for language A, which is mathematically equivalent to the second-moment (covariance-like) structure of neural activity in the cosine similarity space. $Tr(.)$ is the matrix trace. Conceptually, $\mathbf{G}_A$ plays the same role as a covariance matrix, it captures how population responses co-vary across stimuli, which is computed from cosine similarities. $\mathbf{U}_B$ is the matrix of source language B's top-k eigenvectors, and denominator is the sum of language A's top-k eigenvalues. This metric ranges from 0 (no overlap) to 1 (perfect alignment), measuring what fraction of A's top-k variance can be explained by projecting onto B's top-k subspace. We computed bidirectional alignments $\text{Alignment}(\text{Eng} \leftarrow \text{Spa})$ and $\text{Alignment}(\text{Spa} \leftarrow \text{Eng})$, and reported their mean as a symmetric measure of overall subspace overlap between English and Spanish.

$$\text{Alignment}_{\text{sym}} = \frac{1}{2}\left[\text{Alignment}(\text{Eng} \leftarrow \text{Spa}) + \text{Alignment}(\text{Spa} \leftarrow \text{Eng})\right]$$

Permutation test. To test whether cross-language alignment exceeded chance, we performed 1000 permutation. In each permutation, the word order of the Spanish Gram matrix was randomly shuffled, disrupting the one-to-one correspondence between matched English-Spanish word pairs while preserving each language's internal structure. For each shuffled instance, we recomputed the symmetric alignment index, producing a null distribution of alignment scores expected by chance. The empirical alignment was compared to this null

distribution, and a permutation *p*-value was then calculated as the proportion of shuffled alignment whose absolute value was equal to or greater than the observed alignment (two-sided test, α = 0.05)

Compare to within-language subspace alignment. To assess the reliability of the across-language alignment, we computed within-language subspace alignment as a control. Because different subsets of words can produce distinct cosine-distance structures, splitting the words would alter the geometry of the representational dissimilarity matrix and thus would not reflect the reproducibility of the underlying subspace. Instead, we randomly divided the neurons into two equal halves (50% each) and repeated the procedure 1000 times. For each half, we recomputed the centered cosine Gram matrix, performed eigendecomposition, and re-estimated subspace alignment using the same alignment index calculation. To statistically evaluate whether the across-language alignment was significantly lower than within-language alignment, we compared the observed cross-language alignment value against the distribution of within-language alignments pooled across English and Spanish halves. We computed a *z*-score as the deviation of the observed value from the within-language mean, normalized by the within-language standard deviation. Significance thresholds followed standard criteria: $|z| > 1.64$ ($p < 0.10$), $|z| > 1.96$ ($p < 0.05$), and $|z| > 2.58$ ($p < 0.01$).

Neuron-space coordination structure analysis (Figure 6E)

To determine whether English and Spanish engage the same neural ensemble with similar coordination patterns, we analyzed the covariance structure across neurons for each language. This analysis addresses whether cross-language semantic similarity arises from different neural subsets forming language-specific representations, or the same neurons reorganizing through different linear readouts.

Constructing neuron by neuron covariance matrix. For each language, we computed how pairs of neurons covary in their firing rates across all words. We first centered each neuron's responses by subtracting its mean firing rate across words, then computed the covariance between all neuron pairs. This neuron-by-neuron covariance matrix quantifies patterns of coordinated neural activity: neurons with high positive covariance tend to increase their firing rates together across words, while neurons with negative covariance show opposite response patterns. We then performed eigendecomposition of each neuron covariance matrix to identify the dominant modes of coordinated neural activity. Each eigenvector represents a pattern of how neurons covary together, that is, neurons with high loadings on the same eigenvector tend to increase or decrease their firing rates together across words. The eigenvalues reflect the variance explained by each coordination mode, sorted from largest to smallest. We retained eigenvectors capturing greater than 95% of total variance. The number of eigenvectors required to reach this threshold was determined separately for each language. For cross-language comparisons, we used the minimum number of eigenvectors needed across both languages to ensure comparable dimensionality. We also quantified effective dimensionality using the participation ratio, which measures how many coordination modes contribute meaningfully to neural activity patterns. Then we quantified whether English and Spanish recruit the same patterns of neural coordination using the same alignment index for semantic subspaces alignment analyses.

Per-neuron participation strength. Also, to quantify each neuron's contribution to the main coordination subspace, we computed participation strength as the sum of squared loadings across all retained eigenvectors. This metric reflects how strongly each neuron participates in the dominant coordination patterns. We computed the Pearson correlation between English and Spanish participation strengths to test whether the same neurons serve as the similar role of coordination in both languages.

Statistical validation via neuron-identity permutation. To test whether cross-language neural coordination alignment exceeds chance expectations, we performed 1000 permutations by randomly shuffling neuron identities between languages. This permutation test addresses the null hypothesis that neuron correspondences between English and Spanish are arbitrary. For each permutation, we randomly reordered the neurons in the Spanish data, breaking the neuron-to-neuron correspondence between languages while preserving each language's word-evoked activity patterns. Then we recomputed the Spanish neuron covariance matrix from the permuted data, performed eigendecomposition and extracted the top coordination modes. Finally, we computed the alignment index and participation strength correlation under permutation. The permutation *p*-value was then calculated as the proportion of shuffled alignment whose absolute value was equal to or greater than the observed alignment (two-sided test, $\alpha = 0.05$). If the observed values significantly exceeding the permutation distribution indicate that English and Spanish specifically recruit the same neurons with matched coordination patterns.

REFERENCES

Abutalebi, J., & Green, D. (2007). Bilingual language production: The neurocognition of language representation and control. *Journal of Neurolinguistics*, *20*(3), 242–275.

Anderson, M. L. (2010). Neural reuse: a fundamental organizational principle of the brain. *The Behavioral and Brain Sciences*, *33*(4), 245–266; discussion 266-313.

Aronov, D., Nevers, R., & Tank, D. W. (2017). Mapping of a non-spatial dimension by the hippocampal–entorhinal circuit. *Nature*, *543*(7647), 719–722.

Artetxe, M., & Schwenk, H. (2019). Massively multilingual sentence embeddings for zero-shot cross-lingual transfer and beyond. *Transactions of the Association for Computational Linguistics*, *7*, 597–610.

Bakermans, J. J. W., Warren, J., Whittington, J. C. R., & Behrens, T. E. J. (2025). Constructing future behavior in the hippocampal formation through composition and replay. *Nature Neuroscience*, *28*(5), 1061–1072.

Bakker, A., Kirwan, C. B., Miller, M., & Stark, C. E. L. (2008). Pattern separation in the human hippocampal CA3 and dentate gyrus. *Science (New York, N.Y.)*, *319*(5870), 1640–1642.

Barak, O., Rigotti, M., & Fusi, S. (2013). The sparseness of mixed selectivity neurons controls the generalization-discrimination trade-off. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *33*(9), 3844–3856.

Behrens, T. E. J., Muller, T. H., Whittington, J. C. R., Mark, S., Baram, A. B., Stachenfeld, K. L., & Kurth-Nelson, Z. (2018). What is a cognitive map? Organizing knowledge for flexible behavior. *Neuron*, *100*(2), 490–509.

Bellmund, J. L. S., Gärdenfors, P., Moser, E. I., & Doeller, C. F. (2018). Navigating cognition: Spatial codes for human thinking. *Science (New York, N.Y.)*, *362*(6415), eaat6766.

Bernardi, S., Benna, M. K., Rigotti, M., Munuera, J., Fusi, S., & Salzman, C. D. (2020). The geometry of abstraction in the hippocampus and prefrontal cortex. *Cell*, *183*(4), 954-967.e21.

Bialystok, E. (2017). The bilingual adaptation: How minds accommodate experience. *Psychological Bulletin*, *143*(3), 233–262.

Binder, J. R., Desai, R. H., Graves, W. W., & Conant, L. L. (2009). Where is the semantic

system? A critical review and meta-analysis of 120 functional neuroimaging studies. *Cerebral Cortex (New York, N.Y.: 1991)*, *19*(12), 2767–2796.

Blanchard, T. C., Piantadosi, S. T., & Hayden, B. Y. (2018). Robust mixture modeling reveals category-free selectivity in reward region neuronal ensembles. Journal of neurophysiology, 119(4), 1305-1318.

Blanchard, T. C., Wolfe, L. S., Vlaev, I., Winston, J. S., & Hayden, B. Y. (2014). Biases in preferences for sequences of outcomes in monkeys. Cognition, 130(3), 289-299.

Boersma, P. (2001). Praat, a system for doing phonetics by computer. Glot International, 5, 341-345. - References - Scientific Research Publishing. (n.d.). Retrieved October 31, 2025, from https://www.scirp.org/reference/referencespapers?referenceid=913785

Bojanowski, P., Grave, E., Joulin, A., & Mikolov, T. (2017). Enriching word vectors with subword information. *Transactions of the Association for Computational Linguistics*, *5*, 135–146.

Borg, I., & Groenen, P. (2005). Modern multidimensional scaling: Theory and applications, 2nd ed. *Springer Series in Statistics.*, *2*, 614.

Bostock, E., Muller, R. U., & Kubie, J. L. (1991). Experience-dependent modifications of hippocampal place cell firing. *Hippocampus*, *1*(2), 193–205.

Brignoni-Pérez, E., Jamal, N. I., & Eden, G. F. (2022). Functional neuroanatomy of English word reading in early bilingual and monolingual adults. *Human Brain Mapping*, *43*(14), 4310–4325.

Brown-Schmidt, S., Trueswell, J. C., & Tanenhaus, M. K. (2001). The role of the hippocampus in discourse comprehension: Memory for referents across sentences. *Psychological Science*, *12*(6), 493–498.

Calabria, M., Costa, A., Green, D. W., & Abutalebi, J. (2018). Neural basis of bilingual language control: Bilingual language control. *Annals of the New York Academy of Sciences*, *1426*(1), 221–235.

Cao, F., Tao, R., Liu, L., Perfetti, C. A., & Booth, J. R. (2013). High proficiency in a second language is characterized by greater involvement of the first language network: evidence from Chinese learners of English. *Journal of Cognitive Neuroscience*, *25*(10), 1649–

1663.

Charest, I., Pernet, C. R., Rousselet, G. A., Quiñones, I., Latinus, M., Fillion-Bilodeau, S., Chartrand, J.-P., & Belin, P. (2009). Electrophysiological evidence for an early processing of human voices. *BMC Neuroscience, 10*(1), 127.

Chaure, F. J., Rey, H. G., & Quian Quiroga, R. (2018). A novel and fully automatic spike-sorting implementation with variable number of features. *Journal of Neurophysiology, 120*(4), 1859–1871.

Chavez, A. G., Franch, M., Mickiewicz, E. A., Baltazar, W., Belanger, J. L., Devara, D., Etta, M., Hamre, T., Ismail, T., Joiner, B., Kim, Y., Kona, A., Mansourian, K., Nangia, A., Pluenneke, M., Soubra, S., Venkateswaran, T., Venkudusamy, K., Chericoni, A., … Hayden, B. Y. (2025). Mirror manifolds: partially overlapping neural subspaces for speaking and listening. In *bioRxivorg* (p. 2025.09. 20.677504). https://doi.org/10.1101/2025.09.20.677504

Chen, C., Gong, X., Tseng, C., Klein, D., Gallant, J., & Deniz, F. (2024). Bilingual language processing relies on shared semantic representations that are modulated by each language. In *bioRxiv*. https://doi.org/10.1101/2024.06.24.600505

Constantinescu, A. O., O'Reilly, J. X., & Behrens, T. E. J. (2016). Organizing conceptual knowledge in humans with a gridlike code. *Science (New York, N.Y.), 352*(6292), 1464–1468.

Correia, J., Formisano, E., Valente, G., Hausfeld, L., Jansma, B., & Bonte, M. (2014). Brain-based translation: fMRI decoding of spoken words in bilinguals reveals language-independent semantic representations in anterior temporal lobe. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience, 34*(1), 332–338.

Coughlin, B., Muñoz, W., Kfir, Y., Young, M. J., Meszéna, D., Jamali, M., Caprara, I., Hardstone, R., Khanna, A., Mustroph, M. L., Trautmann, E. M., Windolf, C., Varol, E., Soper, D. J., Stavisky, S. D., Welkenhuysen, M., Dutta, B., Shenoy, K. V., Hochberg, L. R., … Paulk, A. C. (2023). Modified Neuropixels probes for recording human neurophysiology in the operating room. *Nature Protocols, 18*(10), 2927–2953.

Courellis, H. S., Minxha, J., Cardenas, A. R., Kimmel, D. L., Reed, C. M., Valiante, T. A.,

Salzman, C. D., Mamelak, A. N., Fusi, S., & Rutishauser, U. (2024). Abstract representations emerge in human hippocampal neurons during inference. *Nature*, *632*(8026), 841–849.

Crinion, J., Turner, R., Grogan, A., Hanakawa, T., Noppeney, U., Devlin, J. T., Aso, T., Urayama, S., Fukuyama, H., Stockton, K., Usui, K., Green, D. W., & Price, C. J. (2006). Language control in the bilingual brain. *Science (New York, N.Y.)*, *312*(5779), 1537–1540.

Dale, A. M., Fischl, B., & Sereno, M. I. (1999). Cortical surface-based analysis. I. Segmentation and surface reconstruction. *NeuroImage*, *9*(2), 179–194.

de Varda, A. G., Malik-Moraleda, S., Tuckute, G., & Fedorenko, E. (2025). Multilingual computational models reveal shared brain responses to 21 languages. In *bioRxiv* (p. 2025.02.01.636044). https://doi.org/10.1101/2025.02.01.636044

Dehghani, M., Boghrati, R., Man, K., Hoover, J., Gimbel, S. I., Vaswani, A., Zevin, J. D., Immordino-Yang, M. H., Gordon, A. S., Damasio, A., & Kaplan, J. T. (2017). Decoding the neural representation of story meanings across languages. *Human Brain Mapping*, *38*(12), 6096–6106.

Devlin, J., Chang, M.-W., Lee, K., & Toutanova, K. (2019). BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In J. Burstein, C. Doran, & T. Solorio (Eds.), *Proceedings of the 2019 Conference of the North* (pp. 4171–4186). Association for Computational Linguistics.

Diedrichsen, J., & Kriegeskorte, N. (2017). Representational models: A common framework for understanding encoding, pattern-component, and representational-similarity analysis. *PLoS Computational Biology*, *13*(4), e1005508.

Dijksterhuis, M., Tibon, R., & Hagoort, P. (2024). Hippocampal contributions to language processing: Integrating memory and meaning. *Nature Communications*, *15*.

Doeller, C. F., Barry, C., & Burgess, N. (2010). Evidence for grid cells in a human memory network. *Nature*, *463*(7281), 657–661.

Duff, M. C., & Brown-Schmidt, S. (2012). The hippocampus and the flexible use and processing of language. *Frontiers in Human Neuroscience*, *6*, 69.

Ebitz, R. B., & Hayden, B. Y. (2021). The population doctrine in cognitive neuroscience. *Neuron*,

109(19), 3055–3068.

Ebitz, R. B., Sleezer, B. J., Jedema, H. P., Bradberry, C. W., & Hayden, B. Y. (2019). Tonic
    exploration governs both flexibility and lapses. PLoS computational biology, 15(11),
    e1007475.

Ehrlich, D. B., & Murray, J. D. (2022). Geometry of neural computation unifies working
    memory and planning. *Proceedings of the National Academy of Sciences of the United
    States of America*, *119*(37), e2115610119.

Eisenreich, B. R., Hayden, B. Y., & Zimmermann, J. (2019). Macaques are risk-averse in a freely
    moving foraging task. Scientific reports, 9(1), 15091.

Elsayed, G. F., Lara, A. H., Kaufman, M. T., Churchland, M. M., & Cunningham, J. P. (2016).
    Reorganization between preparatory and movement population responses in motor
    cortex. *Nature Communications*, *7*(1), 13239.

Evans, N. (2011). *Dying words* [EPUB]. Wiley-Blackwell.

Franch, M., Mickiewicz, E. A., Belanger, J. L., Chericoni, A., Chavez, A. G., Katlowitz, K. A.,
    Mathura, R., Paulo, D., Bartoli, E., Kemmer, S., Piantadosi, S. T., Provenza, N. R.,
    Watrous, A. J., Sheth, S. A., & Hayden, B. Y. (2025). A vectorial code for semantics in
    human hippocampus. In *bioRxivorg*. https://doi.org/10.1101/2025.02.21.639601

Gardenfors, P. (2014). *The geometry of meaning*. MIT Press.

Grave, E., Bojanowski, P., Gupta, P., Joulin, A., & Mikolov, T. (2018). Learning word vectors for
    157 languages. In *arXiv [cs.CL]*. arXiv. http://arxiv.org/abs/1802.06893

Groppe, D. M., Bickel, S., Dykstra, A. R., Wang, X., Mégevand, P., Mercier, M. R., Lado, F. A.,
    Mehta, A. D., & Honey, C. J. (2017). iELVis: An open source MATLAB toolbox for
    localizing and visualizing human intracranial electrode data. *Journal of Neuroscience
    Methods*, *281*, 40–48.

Hafting, T., Fyhn, M., Molden, S., Moser, M.-B., & Moser, E. I. (2005). Microstructure of a
    spatial map in the entorhinal cortex. *Nature*, *436*(7052), 801–806.

Hayden, B. Y., & Walton, M. E. (2014). Neuroscience of foraging. Frontiers in neuroscience, 8,
    81.

Hofmann, T., Schölkopf, B., & Smola, A. J. (2008). Kernel methods in machine learning. *Annals*

of Statistics, *36*(3), 1171–1220.

Jakobson, R. (1959). On Linguistic Aspects of Translation. In *On Translation* (pp. 232–239). Harvard University Press.

Jamali, M., Grannan, B., Cai, J., Khanna, A. R., Muñoz, W., Caprara, I., Paulk, A. C., Cash, S. S., Fedorenko, E., & Williams, Z. M. (2024). Semantic encoding during language comprehension at single-cell resolution. *Nature*, *631*(8021), 610–616.

Jenkinson, M., & Smith, S. M. (2001). A global optimisation method for robust affine registration of brain images. *Medical Image Analysis*, *5*(2), 143–156.

Jenkinson, Mark, Bannister, P., Brady, M., & Smith, S. (2002). Improved optimization for the robust and accurate linear registration and motion correction of brain images. *NeuroImage*, *17*(2), 825–841.

Johnston, W. J., Fine, J. M., Yoo, S. B. M., Ebitz, R. B., & Hayden, B. Y. (2024). Semi-orthogonal subspaces for value mediate a binding and generalization trade-off. *Nature Neuroscience*, *27*(11), 2218–2230.

Joshi, A., Scheinost, D., Okuda, H., Belhachemi, D., Murphy, I., Staib, L. H., & Papademetris, X. (2011). Unified framework for development, deployment and robust testing of neuroimaging algorithms. *Neuroinformatics*, *9*(1), 69–84.

Karkowski, K., Kehl, M. S., Qin, Y., Darcher, A., Karkowski, P., Borger, V., Surges, R., Hebart, M. N., Reber, T. P., Dehaene, S., Lakretz, Y., & Mormann, F. (2025). Semantic Tuning of Single Neurons in the Human Medial Temporal Lobe. In *Neuroscience* (biorxiv;2025.10.21.682935v1). bioRxiv. https://www.biorxiv.org/content/ 10.1101/2025.10.21.682935v1.full.pdf

Katlowitz, K. A., Belanger, J. L., Ismail, T., Chavez, A. G., Chericoni, A., Franch, M., ... & Hayden, B. Y. (2025). Attention is all you need (in the brain): semantic contextualization in human hippocampus. bioRxiv, 2025-06.

Katlowitz, K. A., Shah, S., Franch, M. C., Adkinson, J., Belanger, J. L., Mathura, R. K., Meszéna, D., Mickiewicz, E. A., McGinley, M., Muñoz, W., Banks, G. P., Cash, S. S., Hsu, C.-W., Paulk, A. C., Provenza, N. R., Watrous, A., Williams, Z., Heilbronner, S. R., Kim, R., … Sheth, S. A. (2025). Learning and language in the unconscious human

hippocampus. In *bioRxivorg*. https://doi.org/10.1101/2025.04.09.648012

Klein, D., Milner, B., Zatorre, R. J., Meyer, E., & Evans, A. C. (1995). The neural substrates underlying word generation: a bilingual functional-imaging study. *Proceedings of the National Academy of Sciences of the United States of America*, *92*(7), 2899–2903.

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional brain mapping. *Proceedings of the National Academy of Sciences of the United States of America*, *103*(10), 3863–3868.

Kriegeskorte, N., & Kievit, R. A. (2013). Representational geometry: integrating cognition, computation, and the brain. *Trends in Cognitive Sciences*, *17*(8), 401–412.

Kriegeskorte, N., & Wei, X.-X. (2021). Neural tuning and representational geometry. *Nature Reviews. Neuroscience*, *22*(11), 703–718.

Leutgeb, S., Leutgeb, J. K., Barnes, C. A., Moser, E. I., McNaughton, B. L., & Moser, M.-B. (2005). Independent codes for spatial and episodic memory in hippocampal neuronal ensembles. *Science (New York, N.Y.)*, *309*(5734), 619–623.

Li, X., Morgan, P. S., Ashburner, J., Smith, J., & Rorden, C. (2016). The first step for neuroimaging data analysis: DICOM to NIfTI conversion. *Journal of Neuroscience Methods*, *264*, 47–56.

Libby, A., & Buschman, T. J. (2021). Rotational dynamics reduce interference between sensory and memory representations. *Nature Neuroscience*, *24*(5), 715–726.

Liu, Hengshuang, & Cao, F. (2016). L1 and L2 processing in the bilingual brain: A meta-analysis of neuroimaging studies. *Brain and Language*, *159*, 60–73.

Liu, Hongyan, Hu, Z., Guo, T., & Peng, D. (2010). Speaking words in two languages with one brain: neural overlap and dissociation. *Brain Research*, *1316*, 75–82.

Magnotti, J. F., Wang, Z., & Beauchamp, M. S. (2020). RAVE: Comprehensive open-source software for reproducible analysis and visualization of intracranial EEG data. *NeuroImage*, *223*(117341), 117341.

Maisson, D. J. N., Cervera, R. L., Voloh, B., Conover, I., Zambre, M., Zimmermann, J., & Hayden, B. Y. (2023). Widespread coding of navigational variables in prefrontal cortex. Current Biology, 33(16), 3478-3488.

Maisson, D. J. N., Cash-Padgett, T. V., Wang, M. Z., Hayden, B. Y., Heilbronner, S. R., &
Zimmermann, J. (2021). Choice-relevant information transformation along a ventrodorsal
axis in the medial prefrontal cortex. Nature communications, 12(1), 4830.

Malik-Moraleda, S., Ayyash, D., Gallée, J., Affourtit, J., Hoffmann, M., Mineroff, Z., Jouravlev,
O., & Fedorenko, E. (2022). An investigation across 45 languages and 12 language
families reveals a universal language network. *Nature Neuroscience*, *25*(8), 1014–1019.

Malik-Moraleda, S., Taliaferro, M., Shannon, S., Jhingan, N., Swords, S., Peterson, D. J.,
Frommer, P., Okrand, M., Peterson, J., Cardwell, R., Freeman, C., & Fedorenko, E.
(2025). Constructed languages are processed by the same brain mechanisms as natural
languages. *Proceedings of the National Academy of Sciences of the United States of
America*, *122*(12), e2313473122.

Marr, D. (1982). *Vision Marr*. W.H. Freeman.

Mead, A. (1992). Review of the development of multidimensional scaling methods. *The
Statistician: Journal of the Institute of Statisticians*, *41*(1), 27.

Mikolov, T., Chen, K., Corrado, G., & Dean, J. (2013). Efficient estimation of word
representations in vector space. In *arXiv [cs.CL]*. arXiv. http://arxiv.org/abs/1301.3781

Mousi, B., Durrani, N., Dalvi, F., Hawasly, M., & Abdelali, A. (2024). Exploring alignment in
shared cross-lingual spaces. In L.-W. Ku, A. Martins, & V. Srikumar (Eds.), *Proceedings
of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1:
Long Papers)* (pp. 6326–6348). Association for Computational Linguistics.

Muller, R. U., Stead, M., & Pach, J. (1996). The hippocampus as a cognitive graph. *The Journal
of General Physiology*, *107*(6), 663–694.

Nieh, E. H., Schottdorf, M., Freeman, N. W., Low, R. J., Lewallen, S., Koay, S. A., Pinto, L.,
Gauthier, J. L., Brody, C. D., & Tank, D. W. (2021). Geometry of abstract learned
knowledge in the hippocampus. *Nature*, *595*(7865), 80–84.

Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., & Kriegeskorte, N. (2014). A
toolbox for representational similarity analysis. *PLoS Computational Biology*, *10*(4),
e1003553.

Pearson, J. M., Hayden, B. Y., & Platt, M. L. (2010). Explicit information reduces discounting

behavior in monkeys. Frontiers in psychology, 1, 237.

Perich, M. G., Narain, D., & Gallego, J. A. (2025). A neural manifold view of the brain. *Nature Neuroscience*, *28*(8), 1582–1597.

Piai, V., Anderson, K. L., Lin, J. J., Dewar, C., Parvizi, J., Dronkers, N. F., & Knight, R. T. (2016). Direct brain recordings reveal hippocampal rhythm underpinnings of language processing. *Proceedings of the National Academy of Sciences of the United States of America*, *113*(40), 11366–11371.

Pires, T., Schlinger, E., & Garrette, D. (2019). How multilingual is Multilingual BERT? In *arXiv [cs.CL]*. arXiv. http://arxiv.org/abs/1906.01502

Pourpanah, F., Abdar, M., Luo, Y., Zhou, X., Wang, R., Lim, C. P., Wang, X.-Z., & Wu, Q. M. J. (2023). A review of generalized zero-shot learning methods. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, *45*(4), 4051–4070.

Quian Quiroga, R. (2023). An integrative view of human hippocampal function: Differences with other species and capacity considerations. *Hippocampus*, *33*(5), 616–634.

Quiroga, R. Quian, Reddy, L., Kreiman, G., Koch, C., & Fried, I. (2005). Invariant visual representation by single neurons in the human brain. *Nature*, *435*(7045), 1102–1107.

Quiroga, Rodrigo Quian. (2012). Concept cells: the building blocks of declarative memory functions. *Nature Reviews. Neuroscience*, *13*(8), 587–597.

Rigotti, M., Barak, O., Warden, M. R., Wang, X.-J., Daw, N. D., Miller, E. K., & Fusi, S. (2013). The importance of mixed selectivity in complex cognitive tasks. *Nature*, *497*(7451), 585–590.

Sabatini, D. A., & Kaufman, M. T. (2024). Reach-dependent reorientation of rotational dynamics in motor cortex. *Nature Communications*, *15*(1), 7007.

Schafer, M., & Schiller, D. (2018). Navigating social space. *Neuron*, *100*(2), 476–489.

Silva, A. B., Liu, J. R., Metzger, S. L., Bhaya-Grossman, I., Dougherty, M. E., Seaton, M. P., Littlejohn, K. T., Tu-Chan, A., Ganguly, K., Moses, D. A., & Chang, E. F. (2024). A bilingual speech neuroprosthesis driven by cortical articulatory representations shared between languages. *Nature Biomedical Engineering*, *8*(8), 977–991.

Socher, R., Ganjoo, M., Manning, C. D., & Ng, A. (2013). Zero-shot learning through cross-

modal transfer. *Neural Information Processing Systems*, *26*, 935–943.

Sulpizio, S., Del Maschio, N., Fedeli, D., & Abutalebi, J. (2020). Bilingual language processing: A meta-analysis of functional neuroimaging studies. *Neuroscience and Biobehavioral Reviews*, *108*, 834–853.

Tan, L. H., Spinks, J. A., Feng, C.-M., Siok, W. T., Perfetti, C. A., Xiong, J., Fox, P. T., & Gao, J.-H. (2003). Neural systems of second language reading are shaped by native language. *Human Brain Mapping*, *18*(3), 158–166.

Tang, C., Herikstad, R., Parthasarathy, A., Libedinsky, C., & Yen, S.-C. (2020). Minimally dependent activity subspaces for working memory and motor preparation in the lateral prefrontal cortex. *ELife*, *9*(e58154). https://doi.org/10.7554/eLife.58154

Tavares, R. M., Mendelsohn, A., Grossman, Y., Williams, C. H., Shapiro, M., Trope, Y., & Schiller, D. (2015). A map for social navigation in the human brain. *Neuron*, *87*(1), 231–243.

Tian, Z., Chen, J., Zhang, C., Min, B., Xu, B., & Wang, L. (2024). Mental programming of spatial sequences in working memory in the macaque frontal cortex. *Science (New York, N.Y.)*, *385*(6716), eadp6091.

Van de Putte, E., De Baene, W., Brass, M., & Duyck, W. (2017). Neural overlap of L1 and L2 semantic representations in speech: A decoding approach. *NeuroImage*, *162*, 106–116.

Van De Ven, V., Esposito, F., & Christoffels, I. K. (2020). Neural network dynamics of verbal working memory in bilinguals: The role of the hippocampus. *Cerebral Cortex*, *30*(5), 3124–3136.

Voloh, B., Maisson, D. J. N., Cervera, R. L., Conover, I., Zambre, M., Hayden, B., & Zimmermann, J. (2023). Hierarchical action encoding in prefrontal cortex of freely moving macaques. Cell reports, 42(9).

Vyas, S., Golub, M. D., Sussillo, D., & Shenoy, K. V. (2020). Computation through neural population dynamics. *Annual Review of Neuroscience*, *43*(1), 249–275.

Wang, M. Z., & Hayden, B. Y. (2021). Latent learning, cognitive maps, and curiosity. Current Opinion in Behavioral Sciences, 38, 1-7.

Wang, M. Z., Hayden, B. Y., & Heilbronner, S. R. (2022). A structural and functional subdivision

in central orbitofrontal cortex. Nature communications, 13(1), 3623.

Wu, S., Van Durme, B., & Dredze, M. (2022). Zero-shot Cross-lingual Transfer is Under-specified Optimization. In *arXiv [cs.CL]*. arXiv. http://arxiv.org/abs/2207.05666

Xie, Y., Hu, P., Li, J., Chen, J., Song, W., Wang, X.-J., Yang, T., Dehaene, S., Tang, S., Min, B., & Wang, L. (2022). Geometry of sequence working memory in macaque prefrontal cortex. *Science (New York, N.Y.)*, *375*(6581), 632–639.

Yacoub, E., Grier, M. D., Auerbach, E. J., Lagore, R. L., Harel, N., Adriany, G., ... & Zimmermann, J. (2020). Ultra-high field (10.5 T) resting state fMRI in the macaque. Neuroimage, 223, 117349.

Yassa, M. A., & Stark, C. E. L. (2011). Pattern separation in the hippocampus. *Trends in Neurosciences*, *34*(10), 515–525.

Yoo, S. B. M., Tu, J. C., & Hayden, B. Y. (2021). Multicentric tracking of multiple agents by anterior cingulate cortex during pursuit and evasion. Nature communications, 12(1), 1985.

Zada, Z., Nastase, S. A., Li, J., & Hasson, U. (2025). Brains and language models converge on a shared conceptual space across different languages. In *ArXiv*. arXiv. https://www.ncbi.nlm.nih.gov/pubmed/41019213