SNaQ.jl: Improved Scalability for Phylogenetic Network Inference

Nathan Kolbow[1,2,‡], Sungsik Kong[1,3,‡], Tyler Chafin[4,5], Joshua Justison[1], Cécile Ané,[2], and Claudia Solís-Lemus[1,6,*]

[1] *Wisconsin Institute for Discovery, University of Wisconsin–Madison, N Orchard St, 53706, WI, USA*
[2] *Department of Statistics, University of Wisconsin–Madison, University Ave, 53706, WI, USA*
[3] *Division of Fundamental Mathematical Science, RIKEN Center for Interdisciplinary Theoretical and Mathematical Sciences (iTHEMS), Wako, 351-0198, Saitama, Japan*
[4] *University of Arkansas, W. Dickson St., 72704, Arkansas, USA*
[5] *Tree of Life Programme, Wellcome Sanger Institute, Wellcome Trust Genome Campus, CB10 1RQ, Cambridge, United Kingdom*
[6] *Department of Plant Pathology, University of Wisconsin–Madison, Lincoln Dr, 53706, WI, USA*
[‡]Joint first authorship
[*]Correspondence: solislemus@wisc.edu

Abstract

Phylogenetic networks represent complex biological scenarios that are overlooked in trees, such as hybridization and horizontal gene transfer. Although numerous methods have been developed for phylogenetic network inference, their scalability is severely limited by the computational demands of likelihood optimization and the vastness of network space. Composite (or pseudo-) likelihood approaches like `SNaQ` have improved computational tractability for network inference, but they remain inadequate for datasets of sizes routinely handled by tree inference methods. Here, we introduce `SNaQ.jl`, a new standalone Julia package with the composite likelihood inference originally implemented within `PhyloNetworks.jl` as well as new scalability features that enhance computational efficiency through (1) parallelization of quartet likelihood calculations during composite likelihood computation, (2) weighted random selection of quartets, and (3) probabilistic decision-making during network search. Through a simulation study and empirical data analysis, we show that this new version of `SNaQ.jl` (version 1.1) improves average runtimes by up to 400% with no change in accuracy.

1 Introduction

Phylogenetic networks depict complex biological scenarios that phylogenetic trees overlook, such as hybrid speciation, introgression, and horizontal gene transfer [Huson and Bryant, 2006, Kong et al., 2025]. Existing network inference methods that utilize full likelihood [Yu et al., 2014, Wen et al., 2016, 2018, Zhang et al., 2018] are not scalable enough for datasets with more than a dozen taxa, due to the high complexity and computational burden of full likelihood equations. To improve scalability, network inference methods that utilize a composite likelihood framework (sometimes referred to as pseudo-likelihood) were introduced. These methods simplify calculations by decomposing the full network into a set of smaller units (typically 4-taxon trees or networks referred to as quartets or quarnets) before computing likelihood calculations on each of these subunits. Then, the overall composite likelihood of the network is obtained as the product of the likelihoods of all quarnets. This approach has been useful in trees (e.g., `MP-EST` [Liu et al., 2010]) and networks (e.g., `SNaQ` [Solís-Lemus and Ané, 2016], `PhyNEST` [Kong et al., 2022b], `PhyloNet` [Yu and

Nakhleh, 2015, Zhu and Nakhleh, 2018]) and is much faster than full likelihood methods without compromising method accuracy [Hejase and Liu, 2016]. Despite its computational advantages, composite likelihood estimation remains limited to inference with approximately 50 taxa, which is far below the scale of datasets typically encountered in tree analyses [e.g., One Thousand Plant Transcriptomes Initiative, 2019].

Here, we introduce (1) `SNaQ.jl` version 1.0 (v1.0), a new Julia package implementing the composite likelihood inference method proposed in Solís-Lemus and Ané [2016] which was originally part of `PhyloNetworks.jl` [Solís-Lemus et al., 2017], and (2) `SNaQ.jl` version 1.1 (v1.1), a new version with improved computational efficiency via (i) parallelization of the quartet likelihood calculation during composite likelihood calculation, (ii) weighted random selection of quartets, and (iii) probabilistic decision-making during network search. In the following, we briefly introduce the core components of `SNaQ.jl` followed by the key improvements made in v1.1. Then, we present the results of a simulation study that compares the performance of `SNaQ.jl` with and without these computational improvements (i.e., v1.0 versus v1.1) before applying `SNaQ.jl` v1.1 on an empirical dataset. Our results clearly demonstrate that `SNaQ.jl` v1.1 significantly improves the computational efficiency of network analyses with no change in method accuracy.

2 Methods

2.1 A new Julia package: `SNaQ.jl`

Originally developed as part of the Julia package `PhyloNetworks.jl` [Solís-Lemus et al., 2017], the composite likelihood method `SNaQ` [Species Networks applying Quartets; Solís-Lemus and Ané, 2016] improved scalability of network inference by decomposing the full likelihood into quartet and quarnet likelihoods. In brief, for each set of 4 taxa, (a, b, c, d) for instance, there are three possible unrooted quartets that can be observed in a gene tree: $q_1 = ab|cd$, $q_2 = ac|bd$, $q_3 = ad|bc$. `SNaQ` uses as input the estimated frequency of each of these quartets denoted as quartet *concordance factors* (CF) $X = (X_{q_1}, X_{q_2}, X_{q_3})$ [Baum, 2007] in a set of gene trees across g loci. These frequencies can be estimated from one tree per locus, or from one tree distribution per locus to account for gene tree estimation error.

Next, `SNaQ` traverses the space of level-1 networks (see Kong et al. [2022a] for a formal definition) in search of the network that best fits the data. In order to quantify how well a given network N fits the data, `SNaQ` computes the expected concordance factors for each quarnet q_i according to the multispecies network coalescent model [Yu et al., 2012, Degnan, 2018]. We denote expected concordance factors for a given network N as $(CF_{q_1}, CF_{q_2}, CF_{q_3})$. Then, a composite likelihood function is calculated with these data as follows:

$$L = \prod_{s \in S} (CF_{q_1})^{X_{q_1}} (CF_{q_2})^{X_{q_2}} (CF_{q_3})^{X_{q_3}} \tag{1}$$

where S is the collection of all possible sets of 4 taxa.

Finally, `SNaQ` applies a hill-climbing algorithm to search for the network topology that maximizes the composite likelihood L. The algorithm explores the network space using five topological moves: (i) nearest-neighbor interchange (NNI), (ii) addition of a reticulation, (iii) changing the direction of a reticulation edge, and moving either (iv) the target or (v) the origin of an existing reticulation edge. Note that reticulation removal is not considered as a network move because the algorithm uses strict hill-climbing and removal of a reticulation will always result in a lower (or equal) L. However, if a reticulation edge is estimated to have inheritance probability 0, then it is removed.

The network space search begins with an initial network topology N_0 and its corresponding composite likelihood L_0. To explore potential improvements, the algorithm generates a new network topology by randomly choosing one of the aforementioned five topological moves. This generates a new network N_1 with composite likelihood L_1. If $L_1 > L_0$, the new topology is considered an improvement and becomes the focus of subsequent evaluations (i.e., assigning N_1 as N_0). Otherwise, N_1 is discarded and different topological moves are attempted instead. This iterative process continues until no further improvements are found after a predefined number of attempts. Additionally, to mitigate the risk of converging on local optima, `SNaQ` conducts multiple independent runs, by default 10, with varied starting topologies. This methodology is now implemented in the standalone Julia package `SNaQ.jl` and is no longer part of `PhyloNetworks.jl`.

2.2 Improvements to `SNaQ.jl` (version 1.1)

2.2.1 Computational parallelizations

`SNaQ.jl` v1.0 parallelizes independent runs across processors, but does not have any parallelization within individual runs. `SNaQ.jl` v1.1 reduces this bottleneck by parallelizing composite likelihood computations and all quartet related operations within individual runs across multiple threads.

2.2.2 Quartet sampling

In `SNaQ.jl` v1.0, every available 4-taxon subset is used when computing the composite likelihood function. This scales quartically with the number of taxa n because the total number of 4-taxon sets on n taxa is $k = \binom{n}{4} = O(n^4)$. In `SNaQ.jl` v1.1, we introduce the argument `propQuartets`. This argument takes a decimal value in $(0, 1]$ specifying the proportion of 4-taxon subsets that are utilized when computing a network's composite likelihood. Note that `propQuartets=1` (which remains as the default) corresponds to the approach utilized in version 1.0. So, if there are k 4-taxon subsets in the CF input table, a subset of $\lceil k \times \texttt{propQuartets} \rceil$ are chosen uniformly at random at the beginning of each composite likelihood calculation. This subsampling approach has already been successfully used in phylogenetic inference [Chifman and Kubatko, 2014, 2015], but could be further improved with weighted subsampling [Zhang and Mirarab, 2022] which is not yet implemented in `SNaQ.jl`. Once the network topology search is completed, one final round of optimization is performed with all k CFs to attain the final network's full log composite likelihood score. This ensures that networks inferred with different subsets of CFs have log likelihood scores that are comparable to one another.

2.2.3 Topological moves using quartet weighting

In `SNaQ.jl` v1.0, all topological moves involve the random selection of a reticulation edge that acts as the focus of the topological modification or "move". For example, in "move origin", we select one reticulation node at random and one reticulation edge connected to this reticulation node. Then, the parent or "origin" of this reticulation edge is moved to a randomly chosen neighbor edge. This process is often wasteful as it does not take into account whether the current placement of the origin was a good fit for the observed CFs.

In `SNaQ.jl` v1.1, we introduce the novel argument `probQR`, which takes a value in $[0, 1]$ and defines the probability of utilizing weighted random selection instead of simple random selection when choosing the reticulation edge at which the next topological move is performed. Note that `probQR=0` (which remains as the default) corresponds to the approach utilized in v1.0. When weighted random sampling is used, each quartet q_i extracted from the current network is given a

weight $W = \sum_{i=1}^{3} |X_{q_i} - CF_{q_i}|$ based on the absolute difference between the observed (X_{q_i}) and the expected (CF_{q_i}) CF. On 4-taxon sets with high weights, the current network CF fit the data poorly. A 4-taxon set is sampled at random using these weights, and one of the edges spanned by the associated quarnet is sampled uniformly at random to be the focus on the move in order to sample poorly-fitting edges more frequently.

2.3 Evaluation using simulated and empirical data

2.3.1 Simulations

To evaluate the performance of `SNaQ.jl` (version 1.1), we generated a set of species networks with $n \in \{10, 20\}$ taxa and $h \in \{1, 3\}$ reticulations. To do so, we first generated a species tree under a Yule process using the R package `phytools` [Revell, 2012] for each n, then we added h reticulations onto the topologies at arbitrary positions. We ensured that each network was level-1 using the R package `SiPhyNetworks` [Justison et al., 2023]. To simulate low, medium, and high levels of incomplete lineage sorting, we set the average branch length in each network to 2.0, 1.0, and 0.5 respectively, excluding minor hybrid edges which had length 0.

Using the Julia package `PhyloCoalSimulations.jl` [Fogg et al., 2023], we generated a set of $g \in \{300, 1000, 3000\}$ gene trees for each species network. For each gene tree, we generated a multiple sequence alignment with 1,000 base pairs using `seq-gen` [Rambaut and Grass, 1997], setting the branch length scale parameter to 0.03 and base frequency of nucleotides as $A = T = 0.3$ and $C = G = 0.2$ under the HKY85 model [Hasegawa et al., 1985]. These sequence alignments were then used to estimate gene trees with `IQ-TREE` (version 1.6.12) [Nguyen et al., 2015] under its automatic model selection option under Bayesian information criterion.

Observed CFs were calculated from the estimated gene trees and used as input for `SNaQ.jl` version 1.0 and version 1.1. Starting topologies were randomly selected from among the estimated gene trees and the true h was specified for each simulation. Default optimization parameters were used for both versions of `SNaQ.jl`, but we additionally specified `probQuartets` $\in \{1.0, 0.9, 0.7, 0.5\}$ and `proqQR` $\in \{0, 0.5, 1.0\}$ for version 1.1. We computed the hardwired cluster dissimilarity (HWCD) metric between the estimated and true networks using the Julia package `PhyloNetworks.jl` [Solís-Lemus et al., 2017] and recorded the runtime for each network analysis. The analyses were executed with 4, 8, and 16 processors and 2 threads per processor to assess efficiency in different computational settings. This process was repeated 100 times when $n = 10$ and 20 times when $n = 20$ for each set of parameters and network topologies with new gene trees and multiple sequence alignments being simulated each time. Each replicate analysis was conducted with 10 independent runs.

2.3.2 Empirical data

We repeated the analysis of 24 swordtails and platyfishes (*Xiphophorus*: Poeciliidae) from Solís-Lemus and Ané [2016] with data consisting of 1,183 gene trees from Cui et al. [2013]. Networks were inferred with $h = 0$ to 5 reticulations where each network with $h > 0$ used the previous best scoring network as its starting point. When $h = 0$, a random estimated gene tree was used as the inference starting point. After obtaining these networks, a single best-fitting network was selected by applying the slope heuristic method implemented in CAPUSHE [Baudry et al., 2012] to the networks' composite likelihood scores. Inference was performed with 10 processors, 2 threads per processor, and default arguments to illustrate that previous empirical results can be attained much faster as a consequence of the new parallelizations introduced in `SNaQ.jl` v1.1.

3 Results and discussion

3.1 Simulations

Figure 1 shows the performance of `SNaQ.jl` v1.1 in terms of accuracy measured using HWCD over various combinations of `propQuartets`, `probQR`, number of estimated gene trees g, and number of processors. We show the results for the network with ten taxa and three reticulations as an example, but see Supplementary Material Figures S1, S2, and S3 for other networks. As expected, both versions exhibit the same accuracy when their parameters are identical (i.e., `prop Quartets`=1 and `probQR`=0). Moreover, we found that neither `propQuartets` nor `probQR` had a statistically significant impact on topological accuracy. We suspect that accuracy will diminish if `propQuartets` is lowered past 0.5, but further experimentation is necessary to ascertain when this would happen.

Next, we highlight improvements in the efficiency of version 1.1 relative to version 1.0 (Figure 2 for 20 taxa and 3 hybridization events; Figures S8, S9 and S10 for other networks). First, `SNaQ.jl` v 1.1 utilizes computational resources more efficiently than v1.0. For instance, runtimes for v1.0 changed very little as the number of processors increased, but runtimes for v1.1 fell drastically. We observe this behavior when method parameters are the same between both versions of `SNaQ.jl` (`propQuartets=1` and `probQR=0`), so this improvement is the effect of the parallelization of the composite likelihood calculations and quartet operations.

Figure 1: Accuracy in hardwired cluster distance (HWCD; y-axis) between true and estimated networks with 10 taxa and 3 reticulations with various settings involving `probQR` (columns) and number of input gene trees (rows) using different numbers of processors (x-axis) and 2 threads per processor. Results for `SNaQ.jl` v1.0 are outlined in red while version 1.1 results are outlined in black. Each violin plot covers 100 replicates.

Figure 2: Binary log-transformed runtimes (measured in seconds; y-axis) for the network with 20 taxa and 3 reticulations. As in Figure 1, we used various settings involving `probQR` and dataset size using different computing power. `SNaQ.jl` v1.0 results are outlined in red while version 1.1 results are outlined in black. Each violin plot covers 20 replicates and each simulation utilized 2 threads per processor.

While we expected higher `probQR` values to reduce the time spent searching for networks or to improve inference accuracy, there was no noticable improvement in either metric when `probQR` was changed. We suspect that higher values of `probQR` could be reducing the overall stochasticity of the search algorithm resulting in higher chances of being stuck in local optima. On the other hand, alternative weighting methods or different network topologies could yield different results but are outside of the scope of this study. Such adaptations would be interesting to examine in future work.

Lastly, the effect of `propQuartets` on the performance of `SNaQ.jl` v1.1 was clear in our simulations. Decreasing `propQuartets` led to significant improvements in runtime performance without a significant drop in accuracy (p-value$< 10^{-12}$). The most significant average speed improvement observed in these simulations was an average improvement of 811% on the network with $n = 20, h = 1$ with 16 processors, $g = 1000$, `probQR=1`, and `propQuartets=0.5`. Additionally, across all simulations with 16 processors, v1.1 is 499%, 576%, and 757% more efficient than v1.0 with `propQuartets=1.0`, 0.9, and 0.7 respectively. When `propQuartets<1`, a simple random sampling approach is taken, but a more informative sampling approach, such as weighted sampling, may lead to more robust results and enable even smaller values of `propQuartets` to be utilized while retaining overall method accuracy. In general, we suggest reducing `propQuartets` to as low as 0.5 when needed for computational feasibility, but otherwise recommend using the highest feasible value.

3.2 Empirical data

`SNaQ.jl` requires the number of hybridizations in the inferred network to be specified prior to inference. To pick the best-fitting network to the observed data, networks were inferred with $h = 0$ to 5 reticulations after which a single best-fitting network was selected by applying the model selection method implemented in the CAPUSHE R package [Baudry et al., 2012] to the networks' composite likelihood scores. `SNaQ.jl` v1.1 took 54 hours in aggregate to compute all 6 network topologies (each of which has different h), which is 14.4 fewer days than v1.0 took originally, equating to a 641% runtime improvement. The longest runs for v1.0 and v1.1 were 208.8 hours and 16.5 hours, respectively, equating to a 1165% improvement in worst-case runtimes.

Next, we examine topological differences in the networks inferred by v1.0 and v1.1 (see Figures S11-S16 in the Supplementary Material). Networks with $h = 0$ were identical when inferred with both versions and were also identical to the total evidence tree in Cui et al. [2013]. Networks

Runtimes (hours)						
Reticulation (h)	0	1	2	3	4	5
Version 1.0	17.3	29.3	37.8	58.2	208.8	48.8
Version 1.1	8.0	16.5	15.8	3.2	4.4	6.1
Difference	9.3	12.9	22.0	55.1	204.3	42.7
% Difference	115	78	139	1742	4613	703

Table 1: Runtimes (measured in hours) and improvements from `SNaQ.jl` v1.0 to v1.1 on empirical data with 24 taxa and networks inferred with h reticulations using 10 CPU cores and 2 threads per core. The difference in efficiency measured in hours and percent of improvement is also provided.

with $h = 1$ contained the same hybridization event and differed only in a small change in the placement of *X. milleri*. Both networks with $h = 2$ identified the hybridization that appeared in the $h = 1$ networks, and also identified the same target for their second hybridization (*X. helleri*) but slightly different origins (*X .clemenciae* versus its ancestor). Similarly, networks with $h = 3$ and $h = 4$ contained two identical hybridizations but differed in the placement of their remaining hybridizations. The difference in log likelihood scores between v1.0 and v1.1 for $h = 2, 3, 4$ were each small ($\leq 3\%$), but version 1.1 always inferred the better network. Finally, networks with $h = 5$ had the same inferred topologies. Inferred inheritance probabilities (γ) were roughly similar between the two versions, regardless of differences in the placements of hybridizations.

Despite the similarity of these networks to those in Solís-Lemus and Ané [2016], the network inferred by `SNaQ.jl` v1.1 with $h = 1$ had a drastically better log likelihood score than its counterpart inferred by `SNaQ.jl` v1.0. As a result, the best-fitting network determined by slope heuristics would be the network inferred with $h = 1$. This is in contrast to Solís-Lemus and Ané [2016], where the network inferred with $h = 2$ was chosen as the best-fitting model.

4   Conclusion

`SNaQ.jl` v1.1 implements parallel computing techniques to significantly improve its computational efficiency when run on a machine with multiple processing cores and threads. In our simulation study, we observed upwards of 499% faster average runtimes with v1.1 than with v1.0 when identical arguments were utilized with 16 processors. Further, upwards of 757% faster average runtimes were achieved when the new optimization parameter `propQuartets` was reduced to 0.5. These runtime improvements come without any significant change in method accuracy. This efficiency was further substantiated by re-analyzing an empirical *Xiphophorus* fish dataset with 24 taxa where runtimes improved by a similar magnitude and major findings in the original analysis were confirmed.

In addition, `SNaQ.jl` v1.1 implements two new parameters to the `snaq!` function: `propQuartets` and `probQR`. Our analyses show that reducing `propQuartets` as low as 0.5 significantly improves method runtime with no significant difference in method accuracy. These results may be partially dependent on the specific network topologies analysed here, though, so further investigation is warranted to verify the robustness of this parameter to various topological features. Additionally, future work could build on these results by identifying values of `propQuartets` for which `SNaQ.jl`'s accuracy beings to deteriorate, or by improving upon the current implementation by utilizing more sophisticated sampling strategies. On the other hand, `probQR` appeared to have no effect on method accuracy or runtime, so further investigation is needed to assess the effects of this parameter.

5 Code and data availability

SNaQ.jl is a new Julia package that is open source and publicly available on `https://github.com/JuliaPhylo/SNaQ.jl`. Scripts for simulation and empirical data analyses can be found at this Zenodo repository. Original data used and generated in these simulations can be found at this Dryad repository.

6 Competing interests

No competing interest is declared.

7 Author contributions statement

CSL and TC conceived the idea for the scalability implementations. TC implemented the improvements into SNaQ.jl version 1.1. NK and SK designed the simulations and prepared the manuscript. NK conducted the empirical and simulated analyses. JJ, NK, CA, and CSL refactored the original codebase, split it into two modular packages (PhyloNetworks.jl and SNaQ.jl), implemented unit tests, and wrote documentation.

8 Acknowledgments

This work was supported by the National Science Foundation (DEB-2144367 to CSL and DBI-2010774 to TC).

References

J.-P. Baudry, C. Maugis, and B. Michel. Slope heuristics: Overview and implementation. *Statistics and Computing*, 22(2):455–470, Mar. 2012. ISSN 1573-1375. doi: 10.1007/s11222-011-9236-1.

D. A. Baum. Concordance trees, concordance factors, and the exploration of reticulate genealogy. *TAXON*, 56(2):417–426, May 2007. ISSN 00400262. doi: 10.1002/tax.562013.

J. Chifman and L. Kubatko. Quartet inference from SNP data under the coalescent model. *Bioinformatics*, 30(23):3317–3324, Dec. 2014. ISSN 1460-2059, 1367-4803. doi: 10.1093/bioinformatics/btu530.

J. Chifman and L. Kubatko. Identifiability of the unrooted species tree topology under the coalescent model with time-reversible substitution processes, site-specific rate variation, and invariable sites. *Journal of Theoretical Biology*, 374:35–47, June 2015. ISSN 00225193. doi: 10.1016/j.jtbi.2015.03.006.

R. Cui, M. Schumer, K. Kruesi, R. Walter, P. Andolfatto, and G. G. Rosenthal. Phylogenomics reveals extensive reticulate evolution in *Xiphophorus* fishes: Phylogenomics of *Xiphophorus* fishes. *Evolution*, 67(8):2166–2179, Aug. 2013. ISSN 00143820. doi: 10.1111/evo.12099.

J. H. Degnan. Modeling hybridization under the network multispecies coalescent. *Systematic Biology*, 67(5):786–799, Sept. 2018. ISSN 1063-5157, 1076-836X. doi: 10.1093/sysbio/syy040.

J. Fogg, E. S. Allman, and C. Ané. PhyloCoalSimulations: A Simulator for Network Multispecies Coalescent Models, Including a New Extension for the Inheritance of Gene Flow. *Systematic Biology*, 72(5):1171–1179, Nov. 2023. ISSN 1063-5157, 1076-836X. doi: 10.1093/sysbio/syad030.

M. Hasegawa, H. Kishino, and T.-a. Yano. Dating of the human-ape splitting by a molecular clock of mitochondrial dna. *Journal of Molecular Evolution*, 22(2):160–174, Oct. 1985. ISSN 1432-1432. doi: 10.1007/BF02101694.

H. A. Hejase and K. J. Liu. A scalability study of phylogenetic network inference methods using empirical datasets and simulations involving a single reticulation. *BMC Bioinformatics*, 17(1): 422, Dec. 2016. ISSN 1471-2105. doi: 10.1186/s12859-016-1277-1.

D. H. Huson and D. Bryant. Application of phylogenetic networks in evolutionary studies. *Molecular Biology and Evolution*, 23(2):254–267, Feb. 2006. ISSN 1537-1719, 0737-4038. doi: 10.1093/molbev/msj030.

J. A. Justison, C. Solis-Lemus, and T. A. Heath. SiPhyNetwork : An R package for simulating phylogenetic networks. *Methods in Ecology and Evolution*, 14(7):1687–1698, July 2023. ISSN 2041-210X, 2041-210X. doi: 10.1111/2041-210X.14116.

S. Kong, J. C. Pons, L. Kubatko, and K. Wicke. Classes of Explicit Phylogenetic Networks and their Biological and Mathematical Significance. *arXiv:2109.10251 [math, q-bio]*, Jan. 2022a.

S. Kong, D. L. Swofford, and L. S. Kubatko. Inference of Phylogenetic Networks from Sequence Data using Composite Likelihood. Preprint, Evolutionary Biology, Nov. 2022b.

S. Kong, C. Solís-Lemus, and G. P. Tiley. Phylogenetic networks empower biodiversity research. *Proceedings of the National Academy of Sciences*, 122(31):e2410934122, 2025. doi: 10.1073/pnas. 2410934122. URL https://www.pnas.org/doi/abs/10.1073/pnas.2410934122.

L. Liu, L. Yu, and S. V. Edwards. A maximum pseudo-likelihood approach for estimating species trees under the coalescent model. *BMC Evolutionary Biology*, 10(1):302, 2010. ISSN 1471-2148. doi: 10.1186/1471-2148-10-302.

L.-T. Nguyen, H. A. Schmidt, A. von Haeseler, and B. Q. Minh. IQ-TREE: A fast and effective stochastic algorithm for estimating maximum-likelihood phylogenies. *Molecular Biology and Evolution*, 32(1):268–274, Jan. 2015. ISSN 1537-1719, 0737-4038. doi: 10.1093/molbev/msu300.

One Thousand Plant Transcriptomes Initiative. One thousand plant transcriptomes and the phylogenomics of green plants. *Nature*, 574(7780):679–685, 2019.

A. Rambaut and N. C. Grass. Seq-Gen: An application for the Monte Carlo simulation of DNA sequence evolution along phylogenetic trees. *Bioinformatics*, 13(3):235–238, 1997. ISSN 1367-4803, 1460-2059. doi: 10.1093/bioinformatics/13.3.235.

L. J. Revell. Phytools: An R package for phylogenetic comparative biology (and other things). *Methods in Ecology and Evolution*, 3(2):217–223, Apr. 2012. ISSN 2041-210X, 2041-210X. doi: 10.1111/j.2041-210X.2011.00169.x.

C. Solís-Lemus and C. Ané. Inferring phylogenetic networks with maximum pseudolikelihood under incomplete lineage sorting. *PLOS Genetics*, 12(3):e1005896, Mar. 2016. ISSN 1553-7404. doi: 10.1371/journal.pgen.1005896.

C. Solís-Lemus, P. Bastide, and C. Ané. PhyloNetworks: A package for phylogenetic networks. *Molecular Biology and Evolution*, 34(12):3292–3298, Dec. 2017. ISSN 0737-4038, 1537-1719. doi: 10.1093/molbev/msx235.

D. Wen, Y. Yu, and L. Nakhleh. Bayesian inference of reticulate phylogenies under the multispecies network coalescent. *PLOS Genetics*, 12(5):e1006006, May 2016. ISSN 1553-7404. doi: 10.1371/journal.pgen.1006006.

D. Wen, Y. Yu, J. Zhu, and L. Nakhleh. Inferring phylogenetic networks using phylonet. *Systematic Biology*, 67(4):735–740, July 2018. ISSN 1063-5157, 1076-836X. doi: 10.1093/sysbio/syy015.

Y. Yu and L. Nakhleh. A maximum pseudo-likelihood approach for phylogenetic networks. *BMC Genomics*, 16(S10):S10, Dec. 2015. ISSN 1471-2164. doi: 10.1186/1471-2164-16-S10-S10.

Y. Yu, J. H. Degnan, and L. Nakhleh. The probability of a gene tree topology within a phylogenetic network with applications to hybridization detection. *PLoS Genetics*, 8(4):e1002660, Apr. 2012. ISSN 1553-7404. doi: 10.1371/journal.pgen.1002660.

Y. Yu, J. Dong, K. J. Liu, and L. Nakhleh. Maximum likelihood inference of reticulate evolutionary histories. *Proceedings of the National Academy of Sciences*, 111(46):16448–16453, Nov. 2014. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas.1407950111.

C. Zhang and S. Mirarab. Weighting by Gene Tree Uncertainty Improves Accuracy of Quartet-based Species Trees. *Molecular Biology and Evolution*, 39(12):msac215, Dec. 2022. ISSN 0737-4038, 1537-1719. doi: 10.1093/molbev/msac215.

C. Zhang, H. A. Ogilvie, A. J. Drummond, and T. Stadler. Bayesian inference of species networks from multilocus sequence data. *Molecular Biology and Evolution*, 35(2):504–517, Feb. 2018. ISSN 0737-4038, 1537-1719. doi: 10.1093/molbev/msx307.

J. Zhu and L. Nakhleh. Inference of species phylogenies from bi-allelic markers using pseudo-likelihood. *Bioinformatics*, 34(13):i376–i385, July 2018. ISSN 1367-4803, 1460-2059. doi: 10.1093/bioinformatics/bty295.

Appendix

A1 Additional Simulation Results

Below we display accuracy and runtime results for every replicate performed on each network topology in our simulation study.

A1.1 Accuracy results

Figure 3: Accuracy results in hardwired cluster distance (HWCD) for the topology with 10 taxa and 1 reticulation across a wide array of simulation parameters. Violin plots outlined in red represent results for `SNaQ.jl` version 1.0, whereas all others represent results for version 1.1.

N20R1

Figure 4: Accuracy results in hardwired cluster distance (HWCD) for the topology with 20 taxa and 1 reticulation across a wide array of simulation parameters. Violin plots outlined in red represent results for `SNaQ.jl` version 1.0, whereas all others represent results for version 1.1.

N20R3

Figure 5: Accuracy results in hardwired cluster distance (HWCD) for the topology with 20 taxa and 3 reticulations across a wide array of simulation parameters. Violin plots outlined in red represent results for `SNaQ.jl` version 1.0, whereas all others represent results for version 1.1.

Figure 6: Accuracy results in hardwired cluster distance (HWCD) for the topology with 10 taxa and 1 reticulation relative to the number of input gene trees across a wide array of simulation parameters. Margins represent 95% empirical confidence intervals for observed accuracies, while point estimates are the mean HWCDs for each parameter combination. Simulations utilizing `SNaQ.jl` version 1.0 are shown in red, whereas those utilizing `SNaQ.jl` version 1.1 are shown in blue.

Figure 7: Accuracy results in hardwired cluster distance (HWCD) for the topology with 10 taxa and 3 reticulations relative to the number of input gene trees across a wide array of simulation parameters. Margins represent 95% empirical confidence intervals for observed accuracies, while point estimates are the mean HWCDs for each parameter combination. Simulations utilizing `SNaQ.jl` version 1.0 are shown in red, whereas those utilizing `SNaQ.jl` version 1.1 are shown in blue.

Figure 8: Accuracy results in hardwired cluster distance (HWCD) for the topology with 20 taxa and 1 reticulation relative to the number of input gene trees across a wide array of simulation parameters. Margins represent 95% empirical confidence intervals for observed accuracies, while point estimates are the mean HWCDs for each parameter combination. Simulations utilizing `SNaQ.jl` version 1.0 are shown in red, whereas those utilizing `SNaQ.jl` version 1.1 are shown in blue.

Figure 9: Accuracy results in hardwired cluster distance (HWCD) for the topology with 20 taxa and 3 reticulations relative to the number of input gene trees across a wide array of simulation parameters. Margins represent 95% empirical confidence intervals for observed accuracies, while point estimates are the mean HWCDs for each parameter combination. Simulations utilizing `SNaQ.jl` version 1.0 are shown in red, whereas those utilizing `SNaQ.jl` version 1.1 are shown in blue.

A1.2   Runtime results

Figure 10: Log2 runtime results in seconds for the topology with 10 taxa and 1 reticulation across a wide array of simulation parameters. Violin plots outlined in red represent results for `SNaQ.jl` version 1.0, whereas all others represent results for version 1.1.

A2   Additional Empirical Results

A2.1   Inferred networks

Below are all networks topologies inferred for species *Xiphophorus*: Poeciliidae with $h \in \{0, 1, 2, 3, 4, 5\}$ inferred by `SNaQ.jl` versions 1.0 and 1.1 with *X. mayae* arbitrarily chosen as outgroup in all figures.

Figure 11: Log2 runtime results in seconds for the topology with 10 taxa and 3 reticulations across a wide array of simulation parameters. Violin plots outlined in red represent results for `SNaQ.jl` version 1.0, whereas all others represent results for version 1.1.

Figure 12: Log2 runtime results in seconds for the topology with 20 taxa and 1 reticulation across a wide array of simulation parameters. Violin plots outlined in red represent results for `SNaQ.jl` version 1.0, whereas all others represent results for version 1.1.

Figure 13: Highest negative log likelihood empirical network inferred by `SNaQ.jl` version 1.1 (left; negative log composite likelihood ≈ 12306) and version 1.0 (right; negative log composite likelihood ≈ 12306) with 0 hybridizations.

Figure 14: Highest negative log likelihood empirical network inferred by `SNaQ.jl` version 1.1 (left; negative log composite likelihood ≈ 8087) and version 1.0 (right; negative log composite likelihood ≈ 10051) with 1 hybridization. Hybrid inheritance proportions are labelled in cyan font.

Figure 15: Highest negative log likelihood empirical network inferred by `SNaQ.jl` version 1.1 (left; negative log composite likelihood ≈ 8010) and version 1.0 (right; negative log composite likelihood ≈ 8015) with 2 hybridizations. Hybrid inheritance proportions are labelled in cyan font.

Figure 16: Highest negative log likelihood empirical network inferred by `SNaQ.jl` version 1.1 (left; negative log composite likelihood ≈ 7045) and version 1.0 (right; negative log composite likelihood ≈ 7268) with 3 hybridizations. Hybrid inheritance proportions are labelled in cyan font.

Figure 17: Highest negative log likelihood empirical network inferred by `SNaQ.jl` version 1.1 (left; negative log composite likelihood ≈ 6911) and version 1.0 (right; negative log composite likelihood ≈ 7053) with 4 hybridizations. Hybrid inheritance proportions are labelled in cyan font.

Figure 18: Highest negative log likelihood empirical network inferred by `SNaQ.jl` version 1.1 (left; negative log composite likelihood ≈ 6911) and version 1.0 (right; negative log composite likelihood ≈ 6943) with 5 hybridizations. Hybrid inheritance proportions are labelled in cyan font.

A2.2 Model selection curves

Figure 19: Best inferred log composite likelihoods, slope heuristic penalized scores, and selected model for each empirical network with $h \in \{0, 1, 2, 3, 4, 5\}$ inferred by `SNaQ.jl` version 1.1 (left) and version 1.0 (right).